

Package ‘CEDARS’

October 12, 2022

Type Package

Title Simple and Efficient Pipeline for Electronic Health Record Annotation

Description Streamlined annotation pipeline for collection and aggregation of time-to-event data in retrospective clinical studies. 'CEDARS' aims to systematize and accelerate the review of electronic health record (EHR) corpora. It accomplishes those goals by deploying natural language processing as a tool to assist detection and characterization of clinical events by human abstractors. The online user manual presents the necessary steps to install 'CEDARS', process EHR corpora and obtain clinical event dates: <<https://cedars.io>>.

Version 1.90

Imports fastmatch, jsonlite, mongolite, parallel, readr, shiny, udpipe, utils

License GPL-3

URL <https://cedars.io> (main) <https://github.com/simon-hans/CEDARS> (devel)

BugReports <https://github.com/simon-hans/CEDARS/issues>

Depends R (>= 3.5.0)

RoxygenNote 7.1.1

Language en-US

Encoding UTF-8

LazyData true

NeedsCompilation no

Author Simon Mantha [aut, cre] (<<https://orcid.org/0000-0003-4277-5261>>)

Maintainer Simon Mantha <smantha@cedars.io>

Repository CRAN

Date/Publication 2021-02-07 10:40:08 UTC

R topics documented:

add_end_user	2
automatic_NLP_processor	3
create_project	5
delete_end_user	7
download_events	8
end_users	9
find_project_name	9
get_model	10
get_wrapper	11
initialize_annotations	12
initialize_notes	13
initialize_patients	13
initialize_users	14
mongo_uri_standard	15
mrconso_upload	16
mrrel_upload	17
negex	18
negex_upload	18
post_wrapper	19
pre_search	20
save_credentials	21
save_query	22
save_tags	23
simulated_patients	24
start_local	24
terminate_project	25
unlock_user	26
upload_events	27
upload_notes	28
Index	29

add_end_user	<i>Add a CEDARS End User</i>
--------------	------------------------------

Description

Adds an end user. Password must be at least 8 characters in length.

Usage

```
add_end_user(
  uri_fun,
  user,
  password,
  host,
```

```
    port,  
    database,  
    end_user,  
    end_user_password  
)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
end_user	CEDARS end user name.
end_user_password	CEDARS end user password.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:  
add_end_user(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',  
             host = 'server1234', port = NA, database = 'TEST_PROJECT', end_user = 'Mike',  
             end_user_password = 'user_pw_5678')  
  
## End(Not run)
```

automatic_NLP_processor

Process NLP Annotations on the Current Patient Cohort

Description

Accepts a list of patient ID's or alternatively can perform NLP annotations on all available patients in the database.

Usage

```
automatic_NLP_processor(
  patient_vect = NA,
  text_format = "latin1",
  nlp_engine = "udpipe",
  uri_fun = mongo_uri_standard,
  user,
  password,
  host,
  port,
  database,
  max_n_grams_length = 7,
  negex_depth = 6,
  select_cores = NA,
  URL = NA
)
```

Arguments

patient_vect	Vector of patient ID's. Default is NA, in which case all available patient records will undergo NLP annotation.
text_format	Text format for NLP engine.
nlp_engine	Which NLP engine should be used? UDPipe is the only one supported for now.
uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
max_n_grams_length	Maximum length of tokens for matching with UMLS concept unique identifiers (CUI's). Shorter values will result in faster processing. If 0 is chosen, UMLS CUI tags will not be provided.
negex_depth	Maximum distance between negation item and token to negate. Shorter distances will result in decreased sensitivity but increased specificity for negation.
select_cores	How many CPU cores should be used for parallel processing? Max allowed is total number of cores minus one. If 1 is entered, parallel processing will not be used.
URL	UDPipe model URL.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:
automatic_NLP_processor(patient_vect = NA, text_format = 'latin1', nlp_engine = 'udpipe',
  URL = 'models/english-ewt-ud-2.4-190531.udpipe', uri_fun = mongo_uri_standard, user = 'John',
  password = 'db_password_1234', host = 'server1234', port = NA, database = 'TEST_PROJECT',
  max_n_grams_length = 7, negex_depth = 6, select_cores = 1)

## End(Not run)
```

create_project	<i>Create a New CEDARS Project</i>
----------------	------------------------------------

Description

Creates a new MongoDB database and collections needed for a CEDARS annotation project. The MongoDB account used must have sufficient privileges.

Usage

```
create_project(
  uri_fun,
  user,
  password,
  host,
  port,
  database,
  project_name,
  investigator_name
)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
project_name	Research or QA project name.
investigator_name	Investigator name.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```

# The code below creates an instance of CEDARS project on a public test MongoDB cluster, populated
# with fictitious EHR corpora.

# MongoDB credentials
db_user_name <- "testUser"
db_user_pw <- "testPW"
db_host <- "cedars.yvjp6.mongodb.net"
db_port <- NA

# Using standard MongoDB URL format
uri_fun <- mongo_uri_standard

# Name for MongoDB database which will contain the CEDARS project
# In this case we generate a random name
mongo_database <- find_project_name()

# We create the database and all required collections on a test cluster
create_project(uri_fun, db_user_name, db_user_pw, db_host, db_port, mongo_database,
"CEDARS Example Project", "Dr Smith")

# Adding one CEDARS end user
add_end_user(uri_fun, db_user_name, db_user_pw, db_host, db_port, mongo_database, "John",
"strongpassword")

## Not run:

# Negex is included with CEDARS and required for assessment of negation
negex_upload(uri_fun, db_user_name, db_user_pw, db_host, db_port, mongo_database)

## End(Not run)

# Uploading the small simulated collection of EHR corpora
upload_notes(uri_fun, db_user_name, db_user_pw, db_host, db_port, mongo_database,
simulated_patients)

# This is a simple query which will report all sentences with a word starting in
# "bleed" or "hem", or an exact match for "bled"
search_query <- "bleed* OR hem* OR bled"
use_negation <- TRUE
hide_duplicates <- TRUE
skip_after_event <- TRUE
save_query(uri_fun, db_user_name, db_user_pw, db_host, db_port, mongo_database, search_query,
use_negation, hide_duplicates, skip_after_event)

## Not run:

# Running the NLP annotations on EHR corpora
# We are only using one core, for large datasets parallel processing is faster
automatic_NLP_processor(NA, "latin1", "udpiper", uri_fun, db_user_name, db_user_pw,
db_host, db_port, mongo_database, max_n_grams_length = 0, negex_depth = 6, select_cores = 1)

```

```

# Pre-searching based on query
# This is optional but will speed-up the interface
pre_search(patient_vect = NA, uri_fun, db_user_name, db_user_pw, db_host, db_port, mongo_database)

# Start the CEDARS GUI locally
# Your user name is "John", password is "strongpassword"
# Once you have entered those credentials, click on button "ENTER NEW DATE" and CEDARS will
# seek the first record to annotate
# Try out the interface, adjudicating sentences, entering event dates, comments, moving
# between sentences and searching for records
# Once you have entered some data, close the GUI
start_local(db_user_name, db_user_pw, db_host, db_port, mongo_database)

# Obtaining events and info associated with data entry
# The annotations entered in the GUI are now available in this dataframe
event_output <- download_events(uri_fun, db_user_name, db_user_pw, db_host, db_port, mongo_database)

## End(Not run)

# Remove project from MongoDB
terminate_project(uri_fun, db_user_name, db_user_pw, db_host, db_port, mongo_database, fast=TRUE)

```

delete_end_user

Delete a CEDARS End User

Description

Deletes one end user and associated password.

Usage

```
delete_end_user(uri_fun, user, password, host, port, database, end_user)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
end_user	CEDARS end user name.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:
delete_end_user(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port = NA, database = 'TEST_PROJECT', end_user = 'Mike')

## End(Not run)
```

download_events	<i>Download Event Data</i>
-----------------	----------------------------

Description

Downloads patient event data. Typically done after all records have been annotated and the project is complete.

Usage

```
download_events(uri_fun, user, password, host, port, database)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

Object of class data.frame containing patient ID for all cohort members, date of recorded event if any, abstractor comments, sentences reviewed along with statistics about review process.

Examples

```
## Not run:
download_events(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port = NA)

## End(Not run)
```

end_users	<i>Download End User List</i>
-----------	-------------------------------

Description

Downloads list of CEDARS end users along with their passwords.

Usage

```
end_users(uri_fun, user, password, host, port, database)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

An object of class `data.frame`, listing all project users along with their associated password. This information is not available if using Active Directory feature because in this case the value pairs would be stored outside of the CEDARS project database.

Examples

```
## Not run:
end_users(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port = NA, database = 'TEST_PROJECT')

## End(Not run)
```

find_project_name	<i>Generate unique test project name (i.e. DB name) on MongoDB CEDARS testing cluster</i>
-------------------	---

Description

Parses existing DB names and randomly generates a unique test project name on MongoDB CEDARS testing cluster. This is used for convenience purposes when the R user does not have an existing MongoDB connection. The corresponding database and collections are PUBLIC so no patient information or any other privileged/confidential data should be used! This is for testing on simulated records only.

Usage

```
find_project_name()
```

Details

No parameter; the operation is performed on a preset server with no user input.

Value

An object of class character, the randomly generated name of a test CEDARS project.

Examples

```
## Not run:  
find_project_name()  
  
## End(Not run)
```

get_model

Get a NLP Model

Description

Downloads a NLP model, presently only UDPipe models supported.

Usage

```
get_model(model_name = "english-ewt", platform = "udpipe")
```

Arguments

model_name	Name of models to download.
platform	Name of NLP platform, currently only UDPipe is supported.

Value

Saves model in inst/models.

get_wrapper	<i>Wrap the get_data() Function</i>
-------------	-------------------------------------

Description

Obtain one sentence and related info from MongoDB. Uses DB credentials pre-loaded in the main environment. For use with Shiny or REST GET (latter yet to be implemented).

Usage

```
get_wrapper(  
  database,  
  end_user,  
  end_user_password,  
  html = TRUE,  
  position,  
  patient_id = NA,  
  ldap = FALSE  
)
```

Arguments

database	MongoDB database.
end_user	CEDARS end user name..
end_user_password	CEDARS end user password.
html	Should output keywords/concepts be highlighted with HTML markup? Default is TRUE.
position	Sentence position within the sequence of selected sentences for a given patient.
patient_id	Used if a specific patient record is requested, instead of a search for next record to annotate.
ldap	Is LDAP authentication being used? If so, password will not be checked and access will be granted automatically.

Value

A list with patient-specific information and a dataframe with selected sentences along with sentence-specific data.

Examples

```
## Not run:  
get_wrapper(database = 'TEST_PROJECT', end_user = 'John', end_user_password = 'db_password_1234',  
  html = TRUE, position = NA)  
  
## End(Not run)
```

initialize_annotations

Initialize Annotations Deletes all NLP annotations and patient-specific information, including clinical event dates. New, empty 'ANNOTATIONS' and 'PATIENTS' collections are created. Dictionaries and original patient notes are preserved.

Description

Initialize Annotations Deletes all NLP annotations and patient-specific information, including clinical event dates. New, empty 'ANNOTATIONS' and 'PATIENTS' collections are created. Dictionaries and original patient notes are preserved.

Usage

```
initialize_annotations(uri_fun, user, password, host, port, database)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:  
initialize_annotations(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',  
host = 'server1234', port = NA, database = 'TEST_PROJECT')  
  
## End(Not run)
```

initialize_notes	<i>Initialize EHR Notes</i>
------------------	-----------------------------

Description

Deletes all patient notes from the database.

Usage

```
initialize_notes(uri_fun, user, password, host, port, database)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:  
initialize_notes(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',  
host = 'server1234', port = NA, database = 'TEST_PROJECT')  
  
## End(Not run)
```

initialize_patients	<i>Initialize Patient List</i>
---------------------	--------------------------------

Description

All patient-specific information is deleted, including clinical event dates. Original notes and NLP annotations are preserved.

Usage

```
initialize_patients(uri_fun, user, password, host, port, database)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:
initialize_patients(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port = NA, database = 'TEST_PROJECT')

## End(Not run)
```

initialize_users	<i>Initialize End User List</i>
------------------	---------------------------------

Description

Deletes all CEDARS end user credentials information.

Usage

```
initialize_users(uri_fun, user, password, host, port, database)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:
initialize_users(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port = NA, database = 'TEST_PROJECT')

## End(Not run)
```

mongo_uri_standard *Prepare MongoDB URI string, most commonly used format*

Description

Formats the MongoDB URI string for use by package mongolite. In this case the 'standard' URI format is used.

Usage

```
mongo_uri_standard(user, password, host, port = NA)
```

Arguments

user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.

Value

URI string.

Examples

```
## Not run:
mongo_uri_standard(user = 'John', password = 'db_password_1234', host = 'server1234', port = NA)

## End(Not run)
```

mrconso_upload	<i>Upload UMLS Dictionary</i>
----------------	-------------------------------

Description

Prepares and uploads UMLS MRCONSO.RRF file. This file is not included in the CEDARS package and can be obtained on the NIH web site at <https://www.nlm.nih.gov/research/umls/index.html>.

Usage

```
mrconso_upload(  
  path,  
  language = "ENG",  
  subsets,  
  max_grams = 7,  
  uri_fun,  
  user,  
  password,  
  host,  
  port,  
  database  
)
```

Arguments

path	Path to file MRCONSO.RRF.
language	Language of biomedical lexicon, default is English (ENG).
subsets	Character vector of lexicon subsets to retain. UMLS is quite large so most applications can use only a few lexicon subsets.
max_grams	Maximum length of token in grams. Tokens above the threshold length will not be retained. Empirically, a value of 7 suffices for most applications.
uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

Progress report of dictionary processing and upload.

Examples

```
## Not run:
mrconso_upload(path = 'dictionaries/MRCONSO.RRF', language = 'ENG', subsets = c('SNOMEDCT_US',
'MTHICD9', 'ICD9CM', 'ICD10', 'ICD10CM', 'DSM-5', 'MSH', 'RXNORM', 'NCI'), max_grams = 7,
user = 'John', password = 'db_password_1234', host = 'server1234', port = NA,
database = 'TEST_PROJECT')

## End(Not run)
```

mrrel_upload

Upload UMLS Relationships

Description

Prepares and uploads UMLS MRREL.RRF file. This file is not included in the CEDARS package and can be obtained on the NIH web site at <https://www.nlm.nih.gov/research/umls/index.html>. It is very large and not currently used by CEDARS.

Usage

```
mrrel_upload(path, uri_fun, user, password, host, port, database)
```

Arguments

path	Path to file MRREL.RRF.
uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

Progress report of UMLS processing and upload.

Examples

```
## Not run:
mrrel_upload(path = 'dictionaries/MRREL.RRF', uri_fun = mongo_uri_standard, user = 'John',
password = 'db_password_1234', host = 'server1234', port = NA, database = 'TEST_PROJECT')

## End(Not run)
```

negex

Negex data Apache License 2.0

Description

Negex data Apache License 2.0

Usage

```
data(negex)
```

Format

An object of class 'data.frame'.

Source

[Google Code Archive](#)

References

Chapman et al. (2013) Stud Health Technol Inform 192:677-681 ([PubMed](#))

Examples

```
data(negex)
```

negex_upload

Upload NegEx

Description

Prepares and uploads NegEx negation lexicon. It is not absolutely required for CEDARS to function but in practice will improve search accuracy for most applications.

Usage

```
negex_upload(  
  uri_fun,  
  user,  
  password,  
  host,  
  port,  
  database,  
  selected_model_path = NA  
)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
selected_model_path	Path to NLP model file.

Value

Confirmation of upload.

Examples

```
## Not run:
negex_upload(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
             host = 'server1234', port = NA, database = 'TEST_PROJECT', NA)

## End(Not run)
```

post_wrapper	<i>Wrap the post_data() Function</i>
--------------	--------------------------------------

Description

Posts results of human reviewer annotation to MongoDB. Uses DB credentials pre-loaded in the main environment. For use with Shiny or REST POST (latter yet to be implemented).

Usage

```
post_wrapper(
  database,
  end_user,
  end_user_password,
  position,
  event_date,
  pt_comments,
  ldap = FALSE
)
```

Arguments

database	MongoDB database.
end_user	CEDARS end user name.
end_user_password	CEDARS end user password.
position	Sentence position within the sequence of selected sentences for a given patient.
event_date	Date of clinical event as determined by human reviewer.
pt_comments	Patient-specific comments from the reviewer.
ldap	Is LDAP authentication being used? If so, password will not be checked and access will be granted automatically.

Value

No return value, called to post data.

Examples

```
## Not run:
post_wrapper(database = 'TEST_PROJECT', end_user = 'John', end_user_password = 'db_password_1234',
position = NA, event_date = NA, pt_comments = 'This is a comment')

## End(Not run)
```

pre_search

Execute Search on a Set of Records

Description

Batches a keyword/CUI search for a cohort of patients. Useful to speed up the process by end users, since search results will be pre-populated. Locks each record before proceeding with search on existing NLP annotations. Patient records with no matching sentences or a known event date at or before the earliest matching sentence will be marked as reviewed. The latter assumes the query orders to skip sentences after events.

Usage

```
pre_search(patient_vect = NA, uri_fun, user, password, host, port, database)
```

Arguments

patient_vect	Vector of patient ID's. Default is NA, in which case all unlocked records will be searched.
uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.

password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.

Value

No return value, called to execute a query in the database.

Examples

```
## Not run:
pre_search(patient_vect = NA, uri_fun = mongo_uri_standard, user = 'John',
password = 'db_password_1234', host = 'server1234', database = 'TEST_PROJECT')

## End(Not run)
```

save_credentials	<i>Save MongoDB Credentials</i>
------------------	---------------------------------

Description

Saves MongoDB credentials as 'db_credentials.Rdata' and Shiny app file as 'app.R'. Those two files should be copied to the Shiny Server app directory. Needed only if using Shiny Server; credentials are entered in the command line for local app use.

Usage

```
save_credentials(
  user,
  password,
  host,
  port,
  database,
  LDAP,
  destination_path = getwd()
)
```

Arguments

user	MongoDB user name.
password	MongoDB user password.
host	MongoDB server host.
port	MongoDB port.
database	MongoDB database name.

LDAP is LDAP being used? In this case, CEDARS will not prompt for user ID/password and a check will NOT be made on the users table. Access will be granted, relying on LDAP authentication. Annotations will be stamped with LDAP user name.

destination_path Folder where the files should be saved. Default is working directory.

Value

No return value, saves DB administrator credentials in local folder.

Examples

```
## Not run:
save_credentials(user = 'John', password = 'db_password_1234', host = 'server1234',
database = 'myDB', LDAP = FALSE, destination_path = getwd())

## End(Not run)
```

save_query	<i>Save Search Query</i>
------------	--------------------------

Description

Saves the search query. The query consists of keywords/UMLS concept unique identifiers (CUI's), boolean elements and other operators ('AND', 'OR', '!', '(', or ')').

Usage

```
save_query(
  uri_fun,
  user,
  password,
  host,
  port,
  database,
  search_query,
  use_negation,
  hide_duplicates,
  skip_after_event
)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.

password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
search_query	Medical corpus query containg keywords/CUI's, boolean elements and other operators ('AND', 'OR', '!', '(', or ')').
use_negation	Should negated items be ignored in the keyword/concept search?
hide_duplicates	Should duplicated sentences be removed for search results?
skip_after_event	Should sentences occurring after recorded clinical event be skipped?

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:
save_query(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port = NA, database = 'TEST_PROJECT', search_query = 'thrombosis AND venous',
use_negation = TRUE, hide_duplicates = TRUE, skip_after_event = TRUE)

## End(Not run)
```

save_tags	<i>Save Document Tags</i>
-----------	---------------------------

Description

Save name of EHR document metadata tags. Individual notes or parts of notes can be labelled with up to 10 tags, typically the patient's name at the time, the type of note, the note section, the author, etc. Tags are not mandatory.

Usage

```
save_tags(uri_fun, user, password, host, port, database, tag_vect)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
tag_vect	Character vector of 10 tag names.

Value

MongoDB operation results.

Examples

```
## Not run:
save_tags(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port = NA, database = 'TEST_PROJECT',
tag_vect = c('note_type', 'note_section', 'author', 'patient_name', NA, NA, NA, NA, NA, NA))

## End(Not run)
```

simulated_patients	<i>Simulated patient data GPL-3 license</i>
--------------------	---

Description

Simulated patient data GPL-3 license

Usage

```
data(simulated_patients)
```

Format

An object of class 'data.frame'.

Examples

```
data(simulated_patients)
```

start_local	<i>Start CEDARS Locally</i>
-------------	-----------------------------

Description

Starts CEDARS locally from RStudio. This is a functional approach and is easier to implement than a full-fledged Shiny Server. Multiple users can access the same CEDARS project on the MongoDB server using separate local R sessions, however in that case MongoDB credentials would have to be shared to all. The best option for multi-user implementations is to use Shiny Server.

Usage

```
start_local(user, password, host, port, database)
```


Arguments

user	DB user name.
password	DB password.
host	Host server.
port	MongoDB port.
database	MongoDB database name.

Value

Launches the CEDARS Shiny app locally (on the desktop computer).

Examples

```
## Not run:
start_local(user = 'John', password = 'db_password_1234', host = 'server1234', port = NA,
database = 'myDB')

## End(Not run)
```

terminate_project	<i>Terminate CEDARS Project</i>
-------------------	---------------------------------

Description

Everything is removed, including dictionaries. MongoDB account used must have sufficient privileges.

Usage

```
terminate_project(uri_fun, user, password, host, port, database, fast = FALSE)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
fast	If TRUE, delete everything without asking security questions.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:
terminate_project(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port = NA, database = 'TEST_PROJECT')

## End(Not run)
```

unlock_user	<i>Unlock User-Specific Records Removes any pending lock(s) for a specific user. Normally there should not be more than one record locked per user at any given time, but if there were more than one, i.e. DB corruption, all locks would be lifted at once.</i>
-------------	---

Description

Unlock User-Specific Records Removes any pending lock(s) for a specific user. Normally there should not be more than one record locked per user at any given time, but if there were more than one, i.e. DB corruption, all locks would be lifted at once.

Usage

```
unlock_user(uri_fun, user, password, host, port, database, end_user)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
end_user	CEDARS end user.

Value

No return value, unlocks alls records for a specific user in the database.

Examples

```
## Not run:
unlock_user(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
host = 'server1234', port= NA, database = 'TEST_PROJECT', end_user = 'Mike')

## End(Not run)
```

upload_events	<i>Upload Event Data</i>
---------------	--------------------------

Description

Uploads event dates for patients already in the patient list. Useful when some events have already been documented before running CEDARS, for example as a second-line method to catch events missed with a different approach. Only event dates for existing records are altered, missing patient records are not added!

Usage

```
upload_events(
  uri_fun,
  user,
  password,
  host,
  port,
  database,
  patient_ids,
  event_dates
)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
patient_ids	Vector of patient ID's.
event_dates	Vector of clinical event dates.

Value

Objects of class character, reporting on completed event uploads.

Examples

```
## Not run:
upload_events(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
  host = 'server1234', port = NA, database = 'TEST_PROJECT', patient_ids = ids, event_dates = events)

## End(Not run)
```

 upload_notes

Upload Notes to Database

Description

Allows user to populate notes in database from dataframe; could be easily inserted into wrapper batch function to serially download from other DB etc. Notes dataframe must contain: 'patient_id', 'text_id' (a unique identifier for each text segment), along with 'text', 'text_date', 'doc_id' (designates unique EHR document) and ideally 'text_sequence' which indicates order of text section within document. 'doc_section_name' along 'text_tag_1' to 'text_tag_10' are optional. 'text_date' must be in format '%Y-%m-%d'!

Usage

```
upload_notes(uri_fun, user, password, host, port, database, notes)
```

Arguments

uri_fun	Uniform resource identifier (URI) string generating function for MongoDB credentials.
user	MongoDB user name.
password	MongoDB user password.
host	MongoDB host server.
port	MongoDB port.
database	MongoDB database name.
notes	Dataframe of EHR documents with metadata. The documents can consist of full notes or note subsections.

Value

Confirmation that requested operation was completed, or error message if attempt failed.

Examples

```
## Not run:
upload_notes(uri_fun = mongo_uri_standard, user = 'John', password = 'db_password_1234',
  host = 'server1234', port = NA, database = 'TEST_PROJECT', notes = simulated_patients)

## End(Not run)
```

Index

* datasets

- negex, [18](#)
- simulated_patients, [24](#)

[add_end_user](#), [2](#)
[automatic_NLP_processor](#), [3](#)
[create_project](#), [5](#)
[delete_end_user](#), [7](#)
[download_events](#), [8](#)
[end_users](#), [9](#)
[find_project_name](#), [9](#)
[get_model](#), [10](#)
[get_wrapper](#), [11](#)
[initialize_annotations](#), [12](#)
[initialize_notes](#), [13](#)
[initialize_patients](#), [13](#)
[initialize_users](#), [14](#)
[mongo_uri_standard](#), [15](#)
[mrconso_upload](#), [16](#)
[mrrel_upload](#), [17](#)
[negex](#), [18](#)
[negex_upload](#), [18](#)
[post_wrapper](#), [19](#)
[pre_search](#), [20](#)
[save_credentials](#), [21](#)
[save_query](#), [22](#)
[save_tags](#), [23](#)
[simulated_patients](#), [24](#)
[start_local](#), [24](#)
[terminate_project](#), [25](#)
[unlock_user](#), [26](#)
[upload_events](#), [27](#)
[upload_notes](#), [28](#)