

Package ‘CausCor’

October 12, 2022

Title Calculate Correlations and Estimate Causality

Version 0.1.2

Description This tool performs pairwise correlation analysis and estimate causality.

Particularly, it is useful for detecting the metabolites that would be altered by the gut bacteria.

URL <https://github.com/sugym/CausCor>

License MIT + file LICENSE

Language en-US

Encoding UTF-8

RoxygenNote 7.1.2

Imports cowplot, dplyr, ggplot2, grDevices, magrittr, stats, WriteXLS

Suggests testthat (>= 3.0.0)

Config/testthat.edition 3

NeedsCompilation no

Author Tomomi Sugiyama [aut, cre]

Maintainer Tomomi Sugiyama <sugiyama.t.am@m.titech.ac.jp>

Repository CRAN

Date/Publication 2022-05-24 06:10:02 UTC

R topics documented:

filter_40	2
filter_n	2
plot_16	3
save_text	3

Index

4

filter_40*Make list of A-B pair causal correlations - 40% Filtering version***Description**

Make list of A-B pair causal correlations - 40% Filtering version

Usage

```
filter_40(
  a_mat,
  b_mat,
  a_category,
  b_category,
  min_cor,
  min_r2,
  min_sample = ceiling((ncol(a_mat) - 1) * 0.4),
  max_sample = ncol(a_mat) - 1 - min_sample
)
```

Arguments

a_mat	Matrix of measurements of A for each sample.
b_mat	Matrix of measurements of B for each sample.
a_category	Category name of A.
b_category	Category name of B.
min_cor	Minimum spearman correlation coefficient.
min_r2	Minimum R2.
min_sample	Minimum number of samples. The default is 40% of the total samples.
max_sample	Maximum number of samples. The default is 60% of the total samples.

filter_n*Make list of A-B pair causal correlations - Normal Filtering version***Description**

Make list of A-B pair causal correlations - Normal Filtering version

Usage

```
filter_n(a_mat, b_mat, a_category, b_category, min_cor, min_sample, min_r2)
```

Arguments

a_mat	Matrix of measurements of A for each sample.
b_mat	Matrix of measurements of B for each sample.
a_category	Category name of A.
b_category	Category name of B.
min_cor	Minimum spearman correlation coefficient.
min_sample	Minimum number of samples.
min_r2	Minimum R2.

plot_16 *Save scatter plots*

Description

Save scatter plots

Usage

```
plot_16(a_mat, b_mat, list, out_info)
```

Arguments

a_mat	Matrix of measurements of A for each sample.
b_mat	Matrix of measurements of B for each sample.
list	List of results.
out_info	Output directory.

save_text *Save list as text file*

Description

Save list as text file

Usage

```
save_text(list, out_info, file_type)
```

Arguments

list	List of results.
out_info	Output directory.
file_type	Choose from "excel", "csv", "tsv".

Index

filter_40, [2](#)

filter_n, [2](#)

plot_16, [3](#)

save_text, [3](#)