

Package ‘MainExistingDatasets’

October 12, 2022

Title Main Existing Human Datasets

Version 1.0.1

Description Shiny for Open Science to visualize, share, and inventory the main existing human datasets for researchers.

License GPL-3

Depends R (>= 2.10)

Imports config, dplyr, DT, glue, golem, grDevices, htmltools, htmlwidgets, magrittr, openxlsx, pkgload, processx, rlang, sf, shiny, spData, tidyr, tmap, tmaptools, utils

Suggests covr, knitr, rmarkdown, testthat

VignetteBuilder knitr

Encoding UTF-8

Language en-US

LazyData false

RoxygenNote 7.1.2

NeedsCompilation no

Author Etienne Camenen [aut, cre],
Baptiste Couvy-Duchesne [aut]

Maintainer Etienne Camenen <etienne.camenen@gmail.com>

Repository CRAN

Date/Publication 2022-06-27 14:10:02 UTC

R topics documented:

human_datasets	2
run_app	2

Index	4
--------------	----------

human_datasets	<i>Human datasets</i>
----------------	-----------------------

Description

A table of human datasets from various sources (e.g., genetics, imagery, omics) and accessible in open-access.

Usage

```
data(human_datasets)
```

run_app	<i>Run the Shiny Application</i>
---------	----------------------------------

Description

Runs a Shiny application. This function normally does not return; interrupt R to stop the application (usually by pressing Ctrl+C or Esc).

Usage

```
run_app(
  onStart = NULL,
  options = list(),
  enableBookmarking = NULL,
  uiPattern = "/",
  ...
)
```

Arguments

- | | |
|-------------------|---|
| onStart | A function that will be called before the app is actually run. This is only needed for shinyAppObj, since in the shinyAppDir case, a global .R file can be used for this purpose. |
| options | Named options that should be passed to the runApp call (these can be any of the following: "port", "launch.browser", "host", "quiet", "display.mode" and "test.mode"). You can also specify width and height parameters which provide a hint to the embedding environment about the ideal height/width for the app. |
| enableBookmarking | Can be one of "url", "server", or "disable". The default value, NULL, will respect the setting from any previous calls to enableBookmarking() . See enableBookmarking() for more information on bookmarking your app. |

<code>uiPattern</code>	A regular expression that will be applied to each GET request to determine whether the <code>ui</code> should be used to handle the request. Note that the entire request path must match the regular expression in order for the match to be considered successful.
<code>...</code>	arguments to pass to <code>golem_opts</code> . See <code>?golem::get_golem_options</code> for more details.

Details

For more information about this function, please take a look at https://CRAN.R-project.org/package=golem/vignettes/c_deploy.html.

Value

An object that represents the app.

Examples

```
## Not run:  
# Start app in the current working directory  
run_app()  
  
# Start app in a subdirectory called myapp  
run_app("myapp")  
  
## End(Not run)
```

Index

* **datasets**

human_datasets, [2](#)

enableBookmarking(), [2](#)

human_datasets, [2](#)

run_app, [2](#)