

# Package ‘OpenRepGrid.ic’

October 25, 2022

**License** MIT + file LICENSE

**Title** Interpretive Clustering for Repertory Grids

**Type** Package

**LazyLoad** yes

**Description** Shiny UI to identify cliques of related constructs in repertory grid data.  
See Burr, King, & Heckmann (2020) <[doi:10.1080/14780887.2020.1794088](https://doi.org/10.1080/14780887.2020.1794088)> for a description of the interpretive clustering (IC) method.

**Version** 0.6.1

**Date** 2022-10-25

**Imports** graphics, grDevices, utils, shiny, shinyjs, shinyBS, shinythemes, shinyWidgets, shinydashboard, shinydashboardPlus (>= 2.0.0), shinycssloaders, shinyFeedback, rintrojs, formattable, openxlsx, DT, magrittr, dplyr, stringr, reshape2, scales, splines, igraph, tidyr, withr, RColorBrewer, tidyverse

**Suggests** knitr, rmarkdown, covr, testthat

**Encoding** UTF-8

**URL** <https://github.com/markheckmann/OpenRepGrid.ic>

**BugReports** <https://github.com/markheckmann/OpenRepGrid.ic/issues>

**RoxygenNote** 7.2.1

**NeedsCompilation** no

**Author** Mark Heckmann [aut, cre, cph] (<<https://orcid.org/0000-0002-0736-7417>>),  
Viv Burr [aut],  
Nigel King [aut]

**Maintainer** Mark Heckmann <[heckmann.mark@gmail.com](mailto:heckmann.mark@gmail.com)>

**Repository** CRAN

**Date/Publication** 2022-10-25 18:57:49 UTC

## R topics documented:

calculate_similarity . . . . .	2
check_excel_input . . . . .	2
check_excel_input_test . . . . .	3
create_excel_output . . . . .	3
ic . . . . .	4
network_graph_images . . . . .	4
OpenRepGrid.ic . . . . .	5

<b>Index</b>	<b>8</b>
--------------	----------

---

calculate\_similarity *Calculate similarity matrix*

---

### Description

Calculate similarity matrix

### Usage

```
calculate_similarity(x, min_matches = 6, align_poles = TRUE)
```

### Arguments

x	Grid data.
min_matches	Minimal number of matches to considers constructs as related.
align_poles	Align positive poles on the right and negative poles on the left.

---

check\_excel\_input *Check if Excel input file contains valid data*

---

### Description

Check if Excel input file contains valid data

### Usage

```
check_excel_input(x)
```

### Arguments

x	Data from Excel input file.
---	-----------------------------

---

`check_excel_input_test`*Check if Excel input file contains valid data*

---

**Description**

Check if Excel input file contains valid data

**Usage**

```
check_excel_input_test(x)
```

**Arguments**

x                    Data from Excel input file.

---

`create_excel_output`    *Create output Excel file*

---

**Description**

Loads the supplied workbook and adds calculations

**Usage**

```
create_excel_output(file, data = list())
```

**Arguments**

file                Path to workbook.  
data                Named list of data objects to add to Excel file. The following contents are expected: TODO

**Value**

Path to saved file.

ic *Launch app in browser*

---

### Description

Launch app in browser

### Usage

```
ic(display.mode = "auto", launch.browser = TRUE)
```

### Arguments

display.mode auto by default, can also be showcase. See [runApp](#).

launch.browser Boolean, set TRUE (default) to open the app in the browser. See [runApp](#).

### Examples

```
if (interactive()) {  
  ic()  
}
```

---

network\_graph\_images *Build network graph plots*

---

### Description

Detects maximal cliques and saves images of network graphs into tempfile. Tempfile paths and info on cliques are returned.

### Usage

```
network_graph_images(  
  x,  
  min_clique_size = 3,  
  show_edges = TRUE,  
  min_matches = 6,  
  label_wrap_width = 15,  
  label_max_length = -1,  
  indicate_direction = show_edges,  
  colorize_direction = TRUE,  
  colorize_cliques = TRUE,  
  colorize_poles = TRUE,  
  align_poles = TRUE,  
  alpha = 0.1,
```

```

    valence_prefix = FALSE,
    border_default = "#987824",
    fill_default = "#00000008",
    image_border_color = grey(0.6),
    seed = 0
)

```

### Arguments

x	A dataframe with a grid.
min_clique_size	Minimal size of cliques to be considered.
show_edges	Whether to show edges in plot.
min_matches	Minimal number of matching scores between constructs to be marked as related.
label_wrap_width	Width of wrapped element label text.
label_max_length	Trim element label at max length characters.
indicate_direction, colorize_direction	Indicate direction of relatedness by edge label +/- and edge color (red, green). Only applied if show_edges = TRUE.
colorize_cliques	Draw cliques in different colors? (default TRUE).
colorize_poles	Colorize positive/negative/neutral poles as red, green, and gray respectively (default TRUE).
align_poles	Align preferred poles on the same side.
alpha	Alpha color value for cliques fillings (default .1).
valence_prefix	Add (+/-) pole prefix to indicate preference. Empty means no preference.
border_default, fill_default	Default border and fill color of polygon encircling clique constructs. Used when colorize_cliques is FALSE. Use NA for no color.
image_border_color	Color of border around generated graph images. If NULL or NA no border is drawn.
seed	Seed number passed to set . seed. Will determine the orientation of the graph.

## Description

The **OpenRepGrid.ic** package implements *Interpretive Clustering (IC)* as outlined in Burr, King, and Heckmann (2020). The authors describe a variant of construct clustering which uses a procedure from graph theory called **maximal cliques enumeration**. Given a similarity measure, in our case the number of matching scores between two constructs, a network graph of relatedness between constructs is construed. A clique is a group of constructs which are all mutually related, given some cut-off criterion for relatedness (e.g. 6 matching scores in a grid with 7 elements). While the paper also describes an offline approach to identify the construct cliques, this software automates the process. Under the hood, the package uses the *igraph* package for clique identification.

The package also contains a shiny based UI you can start via the function `ic()`. Visit <http://ic.openrepgrid.org> for an online version. An introduction to the software is also available on [YouTube](#). Below you find an example of how to process a repgrid in an Excel file using code only.

## References

Burr, V. King, N. & Heckmann, M. (2020) The qualitative analysis of repertory grid data: Interpretive Clustering, *Qualitative Research in Psychology*, doi:10.1080/14780887.2020.1794088

## Examples

```
# The shiny package is just a small UI wrapper around the
# the workhorse core functions. Here is how to call them.

library(tidyverse)
library(openxlsx)
library(igraph)
library(OpenRepGrid.ic)

file <- system.file("extdata", "sylvia.xlsx", package = "OpenRepGrid.ic")
file_out <- str_replace(file, ".xlsx$", " CLIQUES.xlsx") %>% basename

x <- read.xlsx(file)          # read grid
tests <- check_excel_input(x) # check if input format is correct
l <- network_graph_images(x, min_clique_size = 3,
                          show_edges = TRUE,
                          min_matches = 6) # produce images
file_tmp <- create_excel_output(file, l) # create Excel file
# file.show(file_tmp) # not run during tests

# open images saved as temp files (as shown in output Excel file)
file.show(l$img_all_constructs)
file.show(l$img_all_constructs_full_labels)
file.show(l$img_all_constructs_separate_poles)

file.show(l$img_cliques_only)
file.show(l$img_cliques_only_full_labels)
file.show(l$img_cliques_only_separate_poles)

# calculation results used in network_graph_images
# some of them are also contained in Excel file
s <- calculate_similarity(x)
```

s

# Index

- \* **OpenRepGrid.ic**

  - OpenRepGrid.ic, [5](#)

- \* **package**

  - OpenRepGrid.ic, [5](#)

calculate\_similarity, [2](#)

check\_excel\_input, [2](#)

check\_excel\_input\_test, [3](#)

create\_excel\_output, [3](#)

ic, [4](#)

network\_graph\_images, [4](#)

OpenRepGrid.ic, [5](#)

runApp, [4](#)