

Package ‘SUNGEO’

October 12, 2022

Type Package

Title Sub-National Geospatial Data Archive: Geoprocessing Toolkit

Version 0.2.292

Date 2022-08-18

Author Jason Byers, Marty Davidson, Yuri M. Zhukov

Maintainer Yuri M. Zhukov <zhukov@umich.edu>

Description Tools for integrating spatially-misaligned GIS datasets. Part of the Sub-National Geospatial Data Archive System.

URL <<https://github.com/zhukovyuri/SUNGEO>>

License GPL-2

Encoding UTF-8

LazyData TRUE

Depends R (>= 2.10)

Imports

sf,data.table,dplyr,RCurl,jsonlite,raster,stats,methods,purrr,measurements,RANN,cartogram,fasterize,packcircles,rmapsha

RoxygenNote 7.1.1

NeedsCompilation no

Repository CRAN

Date/Publication 2022-08-18 14:20:02 UTC

R topics documented:

clea_deu2009	2
clea_deu2009_df	3
clea_deu2009_pt	4
df2sf	5
fix_geom	6
geocode_osm	7
geocode_osm_batch	8
gpw4_deu2010	10

hex_05_deu	11
highways_deu1992	11
hot_spot	12
line2poly	14
nesting	16
point2poly_krige	18
point2poly_simp	21
point2poly_tess	23
poly2poly_ap	26
sf2raster	29
SUNGEO	31
utm_select	32

Index 33

clea_deu2009	<i>Constituency level results for lower chamber legislative elections, Germany 2009.</i>
--------------	--

Description

A simple feature collection containing the spatial geometries of electoral constituency borders, and data on turnout levels, votes shares and other attributes of lower chamber legislative elections.

Usage

clea_deu2009

Format

Simple feature collection with 16 features and 10 fields. geometry type: MULTIPOLYGON. dimension: XY. bbox: xmin: 5.867281 ymin: 47.27096 xmax: 15.04388 ymax: 55.05902. epsg (SRID): 4326. proj4string: +proj=longlat +datum=WGS84 +no_defs.

est Constituency number. Numeric.

est_n Constituency name. Character.

ctr Country number. Numeric.

ctr_n Country name. Character.

yrmo Year and month of election (YYYYMM). Character.

to1 Turnout in first round. Numeric.

vv1 Number of valid votes in first round. Numeric.

pvs1_margin Popular vote share margin in first round. Numeric.

incumb_pty_n Incumbent party name.

win1_pty_n Party name of popular vote share winner in first round. Character.

Source

Constituency-Level Elections Archive (CLEA) <https://electiondataarchive.org/>

clea_deu2009_df	<i>Constituency level results for lower chamber legislative elections, Germany 2009.</i>
-----------------	--

Description

A data.frame object containing the geographic centroids of electoral constituencies, and data on turnout levels, votes shares and other attributes of lower chamber legislative elections.

Usage

```
clea_deu2009_df
```

Format

data.frame with 16 observations and 12 variables.

cst Constituency number. Numeric.

cst_n Constituency name. Character.

ctr Country number. Numeric.

ctr_n Country name. Character.

yrmo Year and month of election (YYYYMM). Character.

to1 Turnout in first round. Numeric.

vv1 Number of valid votes in first round. Numeric.

pvs1_margin Popular vote share margin in first round. Numeric.

incumb_pty_n Incumbent party name.

win1_pty_n Party name of popular vote share winner in first round. Character.

longitude Longitude of constituency centroid. Numeric.

latitude Latitude of constituency centroid. Numeric.

Source

Constituency-Level Elections Archive (CLEA) <https://electiondataarchive.org/>

clea_deu2009_pt	<i>Constituency level results for lower chamber legislative elections, Germany 2009.</i>
-----------------	--

Description

A simple feature collection containing the geographic centroids of electoral constituencies, and data on turnout levels, votes shares and other attributes of lower chamber legislative elections.

Usage

clea_deu2009_pt

Format

Simple feature collection with 16 features and 10 fields. geometry type: POINT. dimension: XY. bbox: xmin: 6.953882 ymin: 48.54535 xmax: 13.40315 ymax: 54.18635. epsg (SRID): 4326. proj4string: +proj=longlat +datum=WGS84 +no_defs.

cst Constituency number. Numeric.

cst_n Constituency name. Character.

ctr Country number. Numeric.

ctr_n Country name. Character.

yrmo Year and month of election (YYYYMM). Character.

to1 Turnout in first round. Numeric.

vv1 Number of valid votes in first round. Numeric.

pvs1_margin Popular vote share margin in first round. Numeric.

incumb_pty_n Incumbent party name.

win1_pty_n Party name of popular vote share winner in first round. Character.

Source

Constituency-Level Elections Archive (CLEA) <https://electiondataarchive.org/>

df2sf

*Convert data.frame object into simple features object***Description**

Function takes in x-, y-coordinates, and a data.frame of variables (optional) and returns an SFC object

Usage

```
df2sf(
  x_coord,
  y_coord,
  input_data = NULL,
  file = NULL,
  n_max = Inf,
  start = 0,
  projection_input = "EPSG:4326",
  zero.policy = FALSE,
  show_removed = FALSE
)
```

Arguments

x_coord	Numeric vector with longitude or easting projected coordinates. When input_data or file is supplied, can be either column name or numeric vector of the same length as nrow(input_data).
y_coord	Numeric vector with latitude or northing projected coordinates. Must be equal to the vector length of x_coord. When input_data or file is supplied, can be either column name or numeric vector of the same length as nrow(input_data).
input_data	Optional data frame object, containing x_coord and y_coord. nrow(input_data) must be equal to the vector length of x_coord. NOTE: Rows corresponding to non-usable coordinates are removed from the final output.
file	Optional path to csv file. Overrides input_data.
n_max	Maximum number of rows to read in file. Default is Inf.
start	Number of rows to skip in file. Default is 0 (start on first row).
projection_input	Projection string associated with x_coord and y_coord. Default is '+proj=longlat'.
zero.policy	If TRUE, removes rows where corresponding coordinates equals (0,0). Default is FALSE.
show_removed	If TRUE, returns a vector of indices corresponding to non-usable coordinates. Default is FALSE.

Value

If show_removed==FALSE, returns an sf object, with rows corresponding to non-usable coordinates removed. If show_removed==TRUE, returns a list, with an sf object (Spatial_Coordinates), and a vector of indices corresponding to non-usable coordinates removed (Removed_Rows).

Examples

```
# Coordinates supplied as vectors
## Not run:
data(clea_deu2009_df)
out_1 <- df2sf(x_coord=clea_deu2009_df$longitude,y_coord = clea_deu2009_df$latitude)
class(out_1)
plot(out_1$geometry)

## End(Not run)
# Coordinates supplied as column names
## Not run:
out_2 <- df2sf(x_coord="longitude",y_coord ="latitude", input_data = clea_deu2009_df)
plot(out_2["geometry"])

## End(Not run)
# Load from external file
## Not run:
tmp <- tempfile()
write.csv(clea_deu2009_df,file=tmp)
out_3 <- df2sf(x_coord="longitude",y_coord ="latitude", file=tmp)
plot(out_3["geometry"])

## End(Not run)
```

fix_geom

Fix polygon geometries

Description

Function to check validity and fix broken geometries in simple features polygon objects

Usage

```
fix_geom(x, n_it = 10)
```

Arguments

x	Polygon layer to be checked and fixed. sf object.
n_it	Number of iterations. Default is 10. Numeric..

Value

Returns a sf polygon object, with self-intersections and other geometry problems fixed.

Examples

```
# Assignment of a single variable (sums)
## Not run:
data(clea_deu2009)
out_1 <- fix_geom(clea_deu2009)

## End(Not run)
```

geocode_osm

Geocode addresses with OpenStreetMap

Description

Function to find geographic coordinates of addresses and place names, using OpenStreetMap's Nominatum API.

Usage

```
geocode_osm(
  query,
  match_num = 1,
  return_all = FALSE,
  details = FALSE,
  user_agent = NULL
)
```

Arguments

query	Address or place name to be geocoded. Character string.
match_num	If query matches multiple locations, which match to return? Default is 1 (highest-ranking match, by relevance). Numeric.
return_all	Should all matches be returned? Overrides match_num if TRUE. Default is FALSE. Logical.
details	Should detailed results be returned? Default is FALSE. Logical.
user_agent	Valid User-Agent identifying the application for OSM-Nominatum. If none supplied, function will attempt to auto-detect. Character string.

Details

Note that Nominatum Usage Policy stipulates an absolute maximum of 1 request per second (<https://operations.osmfoundation.org/policies/nominatum/>). For batch geocoding of multiple addresses, please use [geocode_osm_batch](#).

Value

A data.frame object. If details=FALSE, contains fields

- "query". User-supplied address query(ies). Character string.
- "osm_id". OpenStreetMap ID. Character string.
- "address". OpenStreetMap address. Character string.
- "longitude". Horizontal coordinate. Numeric.
- "latitude". Vertical coordinate. Numeric.

If details=TRUE, contains additional fields

- "osm_type". OpenStreetMap ID. Character string.
- "importance". Relevance of Nominatum match to query, from 0 (worst) to 1 (best). Numeric.
- "bbox_ymin". Minimum vertical coordinate of bounding box. Numeric.
- "bbox_ymax". Maximum vertical coordinate of bounding box. Numeric.
- "bbox_xmin". Minimum horizontal coordinate of bounding box. Numeric.
- "bbox_xmax". Maximum horizontal coordinate of bounding box. Numeric.

Examples

```
# Geocode an address (top match only)
## Not run:
geocode_osm("Michigan Stadium")

## End(Not run)
# Return detailed results for top match
## Not run:
geocode_osm("Michigan Stadium", details=TRUE)

## End(Not run)
# Return detailed results for all matches
## Not run:
geocode_osm("Michigan Stadium", details=TRUE, return_all = TRUE)

## End(Not run)
```

geocode_osm_batch

Batch geocode addresses with OpenStreetMap

Description

Function to find geographic coordinates of multiple addresses and place names, using OpenStreetMap's Nominatum API.

Usage

```

geocode_osm_batch(
  query,
  delay = 1,
  return_all = FALSE,
  match_num = 1,
  details = FALSE,
  user_agent = NULL,
  verbose = FALSE
)

```

Arguments

query	Addresses or place names to be geocoded. Character string.
delay	Delay between requests. Default is 1 second. Numeric.
return_all	Should all matches be returned? Overrides match_num if TRUE. Default is FALSE. Logical.
match_num	If query matches multiple locations, which match to return? Default is 1 (highest-ranking match, by relevance). Numeric.
details	Should detailed results be returned? Default is FALSE. Logical.
user_agent	Valid User-Agent identifying the application for OSM-Nominatum. If none supplied, function will attempt to auto-detect. Character string.
verbose	Print status messages and progress? Default is FALSE. Logical.

Details

Wrapper function for [geocode_osm](#). Because Nominatum Usage Policy stipulates an absolute maximum of 1 request per second, this function facilitates batch geocoding by adding a small delay between queries (<https://operations.osmfoundation.org/policies/nominatum/>).

Value

A data.frame object. If details=FALSE, contains fields

- "query". User-supplied address query(ies). Character string.
- "osm_id". OpenStreetMap ID. Character string.
- "address". OpenStreetMap address. Character string.
- "longitude". Horizontal coordinate. Numeric.
- "latitude". Vertical coordinate. Numeric.

If details=TRUE, contains additional fields

- "osm_type". OpenStreetMap ID. Character string.
- "importance". Relevance of Nominatum match to query, from 0 (worst) to 1 (best). Numeric.
- "bbox_ymin". Minimum vertical coordinate of bounding box. Numeric.
- "bbox_ymax". Maximum vertical coordinate of bounding box. Numeric.
- "bbox_xmin". Minimum horizontal coordinate of bounding box. Numeric.
- "bbox_xmax". Maximum horizontal coordinate of bounding box. Numeric.

Examples

```
# Geocode multiple addresses (top matches only)
## Not run:
geocode_osm_batch(c("Ann Arbor", "East Lansing", "Columbus"))

## End(Not run)
# With progress reports
## Not run:
geocode_osm_batch(c("Ann Arbor", "East Lansing", "Columbus"), verbose = TRUE)

## End(Not run)
# Return detailed results for all matches
## Not run:
geocode_osm_batch(c("Ann Arbor", "East Lansing", "Columbus"),
                  details = TRUE, return_all = TRUE)

## End(Not run)
```

gpw4_deu2010

Population count raster for Germany, 2010.

Description

2.5 arc-minute resolution raster of estimates of human population (number of persons per pixel), consistent with national censuses and population registers, for the year 2010.

Usage

```
gpw4_deu2010
```

Format

class : RasterLayer. dimensions : 186, 220, 40920 (nrow, ncol, ncell). resolution : 0.04166667, 0.04166667 (x, y). extent : 5.875, 15.04167, 47.29167, 55.04167 (xmin, xmax, ymin, ymax). coord. ref. : +proj=longlat +datum=WGS84 +no_defs +ellps=WGS84 +towgs84=0,0,0. data source : in memory. names : gpw_v4_population_count_rev11_2010_2pt5_min. values : 0, 92915.66 (min, max).

Source

Gridded Population of the World (GPW) v4: Population Count, v4.11 <doi:10.7927/H4JW8BX5>.

hex_05_deu	<i>Hexagonal grid for Germany.</i>
------------	------------------------------------

Description

Regular hexagonal grid of 0.5 degree diameter cells, covering territory of Germany (2020 borders).

Usage

hex_05_deu

Format

Simple feature collection with 257 features and 3 fields. geometry type: POLYGON. dimension: XY. bbox: xmin: 5.375001 ymin: 46.76568 xmax: 15.375 ymax: 55.13726. epsg (SRID): 4326. proj4string: +proj=longlat +datum=WGS84 +no_defs.

HEX_ID Unique cell identifier. Character.

HEX_X Longitude of cell centroid. Numeric.

HEX_Y Latitude of cell centroid. Numeric.

Source

SUNGEO

highways_deu1992	<i>Roads polylines for Germany, 1992</i>
------------------	--

Description

Roads thematic layer from Digital Chart of the World. Subset: divided multi-lane highways.

Usage

highways_deu1992

Format

Simple feature collection with 1741 features and 5 fields. geometry type: MULTILINESTRING. dimension: XY. bbox: xmin: 5.750933 ymin: 47.58799 xmax: 14.75109 ymax: 54.80712 epsg (SRID): 4326. proj4string: +proj=longlat +datum=WGS84 +no_defs.

MED_DESCRI Is the road a divided multi-lane highway with a median? Character string.

RTT_DESCRI Primary or secondary route? Character string.

F_CODE_DES Feature code description (road or trail). Character string.

ISO ISO 3166-1 alpha-3 country code. Character string.

ISOCOUNTRY Country name. Character string.

Source

Defense Mapping Agency (DMA), 1992. Digital Chart of the World. Defense Mapping Agency, Fairfax, Virginia. (Four CD-ROMs). Available through DIVA-GIS: <http://www.diva-gis.org/gData> (accessed August 12, 2021).

hot_spot	<i>Automatically calculate Local G hot spot intensity</i>
----------	---

Description

Function automatically calculates the Local G hot spot intensity measure for spatial points, spatial polygons, and single raster layers. Uses RANN for efficient nearest neighbor calculation (spatial points and single raster layers only); users can specify the number of neighbors (k). Users can specify the neighborhood style (see `spdep::nb2listw`) with default being standardized weight matrix (W).

Usage

```
hot_spot(
  insert,
  variable = NULL,
  style = "W",
  k = 9,
  remove_missing = TRUE,
  NA_Value = 0,
  include_Moran = FALSE
)
```

Arguments

insert	Spatial point, spatial polygon, or single raster layer object. Acceptable formats include <code>sf</code> , <code>SpatialPolygonsDataFrame</code> , <code>SpatialPointsDataFrame</code> , and <code>RasterLayer</code> .
variable	Column name or numeric vector containing the variable from which the local G statistic will be calculated. Must possess a natural scale that orders small and large observations (i.e. number, percentage, ratio and not model residuals).
style	Style can take values 'W', 'B', 'C', 'U', 'mimax', 'S' (see <code>nb2listw</code>). Character string.
k	Number of neighbors. Default is 9. Numeric.
remove_missing	Whether to calculate statistic without missing values. If FALSE, substitute value must be supplied to <code>NA_Value</code> .
NA_Value	Substitute for missing values. Default value is 0. Numeric.
include_Moran	Calculate local Moran's I statistics. Default is FALSE. Logical.

Value

If input is sf, SpatialPolygonsDataFrame or SpatialPointsDataFrame object, returns sf object with same geometries and columns as input, appended with additional column containing Local G estimates (LocalG). If input is RasterLayer object, returns RasterBrick object containing original values (Original) and Local G estimates (LocalG).

Examples

```
# Calculate Local G for sf point layer

## Not run:
data(clea_deu2009_pt)
out_1 <- hot_spot(insert=clea_deu2009_pt, variable = clea_deu2009_pt$to1)
class(out_1)
plot(out_1["LocalG"])

## End(Not run)

# Calculate Local G for sf polygon layer (variable as numeric vector)

## Not run:
data(clea_deu2009)
out_2 <- hot_spot(insert=clea_deu2009, variable = clea_deu2009$to1)
summary(out_2$LocalG)
plot(out_2["LocalG"])

## End(Not run)

# Calculate Local G for sf polygon layer (variable as column name)

## Not run:
out_3 <- hot_spot(insert=clea_deu2009, variable = "to1")
summary(out_3$LocalG)
plot(out_3["LocalG"])

## End(Not run)

# Calculate Local G for sf polygon SpatialPolygonsDataFrame (variable as column name)

## Not run:
out_4 <- hot_spot(insert=as(clea_deu2009,"Spatial"), variable = "to1")
summary(out_4$LocalG)
plot(out_4["LocalG"])

## End(Not run)

# Calculate Local G for RasterLayer
## Not run:
data(gp4_deu2010)
out_5 <- hot_spot(insert=gp4_deu2010)
class(out_5)
raster::plot(out_5)
```

```
## End(Not run)
```

```
line2poly
```

```
Line-in-polygon analysis
```

Description

Function for basic geometry calculations on polyline features, within an overlapping destination polygon layer.

Usage

```
line2poly(
  linez,
  polyz,
  poly_id,
  measurez = c("length", "density", "distance"),
  outvar_name = "line",
  unitz = "km",
  reproject = TRUE,
  na_val = NA,
  verbose = TRUE
)
```

Arguments

linez	Source polyline layer. sf object.
polyz	Destination polygon layer. Must have identical CRS to linez. sf object.
poly_id	Name of unique ID column for destination polygon layer. Character string.
measurez	Desired measurements. Could be any of "length" (sum of line lengths by polygon), "density" (sum of line lengths divided by area of polygon) and/or "distance" (distance from each polygon to nearest line feature). Default is to report all three. Character string or vector of character strings.
outvar_name	Name (root) to be given to output variable. Default is "line". Character string.
unitz	Units of measurement (linear). Default is "km". Character string.
reproject	Temporarily reproject layers to planar projection for geometric operations? Default is TRUE. Logical.
na_val	Value to be assigned to missing values (line lengths and densities only). Default is NA. Logical or list.
verbose	Print status messages and progress? Default is TRUE. Logical.

Value

An sf polygon object, with summary statistics of linez features aggregated to the geometries of polyz.

If measurez = "lengths", contains fields with suffixes

- "_length". Sum of line lengths within each polygon, in km or other units supplied in unitz.

If measurez = "density", contains fields with suffixes

- "_length". Sum of line lengths within each polygon, in km or other units supplied in unitz.
- "_area". Area of each polygon, in km² or the square of linear units supplied in unitz.
- "_density". Sum of line lengths divided by area of each polygon, in km/km² or other units supplied in unitz.

If measurez = "distance", contains fields with suffixes

- "_distance". Distance from each polygon to nearest line feature, in km or other units supplied in unitz.

If measurez = c("length", "density", "distance") (default), contains all of the above.

Examples

```
# Road lengths, densities and distance from polygon to nearest highway
## Not run:
data(hex_05_deu)
data(highways_deu1992)
out_1 <- line2poly(linez = highways_deu1992,
                  polyz = hex_05_deu,
                  poly_id = "HEX_ID")
plot(out_1["line_length"])
plot(out_1["line_density"])
plot(out_1["line_distance"])

## End(Not run)

# Replace missing road lengths and densities with 0's, rename variables
## Not run:
out_2 <- line2poly(linez = highways_deu1992,
                  polyz = hex_05_deu,
                  poly_id = "HEX_ID",
                  outvar_name = "road",
                  na_val = 0)
plot(out_2["road_length"])
plot(out_2["road_density"])
plot(out_2["road_distance"])

## End(Not run)
```

 nesting

Relative scale and nesting coefficients

Description

Function to calculate relative scale and nesting metrics for changes of support from a source polygon layer to an overlapping (but spatially misaligned) destination polygon layer.

Usage

```
nesting(
  poly_from = NULL,
  poly_to = NULL,
  metrix = "all",
  tol_ = 0.001,
  by_unit = FALSE
)
```

Arguments

<code>poly_from</code>	Source polygon layer. <code>sf</code> object (polygon or multipolygon).
<code>poly_to</code>	Destination polygon layer. Must have identical CRS to <code>poly_from</code> . <code>sf</code> object (polygon or multipolygon).
<code>metrix</code>	Requested scaling and nesting metrics. See "details". Default is "all". Character string or vector of character strings.
<code>tol_</code>	Minimum area of polygon intersection, in square meters. Default is 0.001. Numeric.
<code>by_unit</code>	Include a by-unit decomposition of requested nesting metrics (if available)? Default is FALSE. Logical.

Details

Currently supported metrics (`metrix`) include:

- Relative scale ("rs"). Measures whether a change-of-support (CoS) task is one of aggregation or disaggregation, by calculating the share of source units that are smaller than destination units. Its range is from 0 to 1, where values of 1 indicate pure aggregation (all source units are smaller than destination units) and values of 0 indicate no aggregation (all source units are at least as large as destination units). Values between 0 and 1 indicate a hybrid (i.e. some source units are smaller, others are larger than target units).
- Relative nesting ("rn"). Measures how closely source and destination boundaries align, by calculating the share of source units that cannot be split across multiple destination units. Its range is from 0 to 1, where values of 0 indicate no nesting (every source unit can be split across multiple destination units) and values of 1 indicate full nesting (no source unit can be split across multiple destination units).

- Relative scale, symmetric ("rs_sym"). Alternative measure of "rs", which ranges from -1 to 1. It calculates a difference between two proportions: the share of source units that is smaller than destination units (i.e. "rs" from standpoint of source units), and the share that is larger (i.e. "rs" from standpoint of destination units). Values of -1 indicate pure disaggregation (all source units are larger than destination units), 1 indicates pure aggregation (all source units are smaller than destination units). Values of 0 indicate that all source units are the same size as target units.
- Relative nesting, symmetric ("rn_sym"). Alternative measure of "rn", which ranges from -1 to 1. It calculates a difference between two components: the nesting of source units within destination units (i.e. "rn" from standpoint of source units), and the nesting of destination units within source units (i.e. "rn" from standpoint of destination units). Values of 1 indicate that source units are perfectly nested within destination units; -1 indicates that destination units are perfectly nested within source units.
- Relative scale, alternative ("rs_alt"). Alternative measure of "rs", rescaled as a proportion of destination unit area. This measure can take any value on the real line, with positive values indicating aggregation and negative values indicating disaggregation.
- Relative nesting, alternative ("rn_alt"). Alternative measure of "rn", which places more weight on areas of maximum overlap. The main difference between this measure and "rn" is its use of the maximum intersection area for each source polygon instead of averaging over the quadratic term. Two sets of polygons are considered nested if one set is completely contained within another, with as few splits as possible. If none or only a sliver of a source polygon area falls outside a single destination polygon, those polygons are "more nested" than a case where half of a source polygon falls in destination polygon A and half falls into another polygon B.
- Relative scale, conditional ("rs_nn"). Alternative measure of "rs", calculated for the subset of source units that are not fully nested within destination units.
- Relative nesting, conditional ("rn_nn"). Alternative measure of "rn", calculated for the subset of source units that are not fully nested within destination units.
- Proportion intact ("p_intact"). A nesting metric that requires no area calculations at all. This measure ranges from 0 to 1, where 1 indicates full nesting (i.e. every source unit is intact/no splits), and 0 indicates no nesting (i.e. no source unit is intact/all are split).
- Proportion fully nested ("full_nest"). A stricter version of "p_intact". This measure ranges from 0 to 1, where 1 indicates full nesting (i.e. every source unit is intact/no splits AND falls completely inside the destination layer), and 0 indicates no nesting (i.e. no source unit is both intact and falls inside destination layer).
- Relative overlap ("ro"). Assesses extent of spatial overlap between source and destination polygons. This measure is scaled between -1 and 1. Values of 0 indicate perfect overlap (there is no part of source units that fall outside of destination units, and vice versa). Values between 0 and 1 indicate a "source underlap" (some parts of source polygons fall outside of destination polygons; more precisely, a larger part of source polygon area falls outside destination polygons than the other way around). Values between -1 and 0 indicate a "destination underlap" (some parts of destination polygons fall outside of source polygons; a larger part of destination polygon area falls outside source polygons than the other way around). Values of -1 and 1 indicate no overlap (all source units fall outside destination units, and vice versa). This is a theoretical limit only; the function returns an error if there is no overlap.
- Gibbs-Martin index of diversification ("gmi"). Inverse of "rn", where values of 1 indicate that every source unit is evenly split across multiple destination units, and 0 indicates that no source unit is split across any destination units.

It is possible to pass multiple arguments to `metrix` (e.g. `metrix=c("rn","rs")`). The default (`metrix="all"`) returns all of the above metrics.

The function automatically reprojects source and destination geometries to Lambert Equal Area prior to calculation, with map units in meters.

Values of `tol_` can be adjusted to increase or decrease the sensitivity of these metrics to small border misalignments. The default value discards polygon intersections smaller than 0.001 square meters in area.

Value

Named list, with numeric values for each requested metric in `metrix`. If `by_unit==TRUE`, last element of list is a `data.table`, with nesting metrics disaggregated by source unit, where the first column is a row index for the source polygon layer.

Examples

```
# Calculate all scale and nesting metrics for two sets of polygons
## Not run:
data(clea_deu2009)
data(hex_05_deu)
nest_1 <- nesting(
  poly_from = clea_deu2009,
  poly_to = hex_05_deu
)
nest_1

## End(Not run)

# Calculate just Relative Nesting, in the opposite direction
## Not run:
nest_2 <- nesting(
  poly_from = hex_05_deu,
  poly_to = clea_deu2009,
  metrix = "rn"
)
nest_2

## End(Not run)
```

point2poly_krige

Point-to-polygon interpolation, ordinary and universal Kriging method

Description

Function for interpolating values from a source points layer to an overlapping destination polygon layer, using ordinary and universal kriging with automatic variogram fitting

Usage

```

point2poly_krige(
  pointz,
  polyz,
  rasterz = NULL,
  yvarz = NULL,
  xvarz = NULL,
  pycno_yvarz = NULL,
  funz = base::mean,
  use_grid = TRUE,
  nz_grid = 100,
  blockz = 0,
  pointz_x_coord = NULL,
  pointz_y_coord = NULL,
  polyz_x_coord = NULL,
  polyz_y_coord = NULL,
  messagez = ""
)

```

Arguments

pointz	Source points layer. sf, sp, or data frame object.
polyz	Destination polygon layer. Must have identical CRS to pointz. sf, sp, or data frame object.
rasterz	Source raster layer (or list of raster), with covariate(s) used for universal kriging. Must have identical CRS to polyz. RasterLayer object or list of RasterLayer objects.
yvarz	Names of numeric variable(s) to be interpolated from source points layer to destination polygons. Character string or vector of character strings.
xvarz	Names of numeric variable(s) for universal Kriging, in which yvarz is linearly dependent. Character string or vector of character strings.
pycno_yvarz	Names of spatially extensive numeric variables for which the pycnophylactic (mass-preserving) property should be preserved. Must be a subset of yvarz. Character string or vector of character strings.
funz	Aggregation function to be applied to values in rasterz and to interpolated values. Must take as an input a vector x. Default is mean. Function.
use_grid	Use regular grid as destination layer for interpolation, before aggregating to polygons? Default is TRUE.
nz_grid	Number of grid cells in x and y direction (columns, rows). Integer of length 1 or 2. Default is 100. Ignored if use_grid=FALSE.
blockz	Size of blocks used for Block Kriging, in meters. Integer of length 1 or 2. Default is 0.
pointz_x_coord	Name of numeric variable corresponding to a measure of longitude (Easting) in a data frame object for pointz. Character string.

pointz_y_coord	Name of numeric variable corresponding to a measure of Latitude (Northing) in a data frame object for pointz. Character string.
polyz_x_coord	Name of numeric variable corresponding to a measure of longitude (Easting) in a data frame object for polyz. Character string.
polyz_y_coord	Name of numeric variable corresponding to a measure of Latitude (Northing) in a data frame object for polyz. Character string.
messagez	Optional message to be printed during Kriging estimation. Character string.

Details

This function performs Ordinary and Universal Kriging, automatically selecting a variogram model with the smallest residual sum of squares from the sample variogram. See [autofitVariogram](#).

Unlike other available point-to-polygon interpolation techniques, this function currently only accepts numeric variables in varz and does not support interpolation of character strings.

Value

sp polygon object, with variables from pointz interpolated to the geometries of polyz.

Examples

```
# Ordinary Kriging with one variable
## Not run:
data(clea_deu2009)
data(clea_deu2009_pt)
out_1 <- point2poly_krige(pointz = clea_deu2009_pt,
                          polyz = clea_deu2009,
                          yvarz = "to1")

par(mfrow=c(1,2))
plot(clea_deu2009["to1"], key.pos = NULL, reset = FALSE)
plot(out_1["to1.pred"], key.pos = NULL, reset = FALSE)

## End(Not run)

# Ordinary Kriging with multiple variables
## Not run:
out_2 <- point2poly_krige(pointz = clea_deu2009_pt,
                          polyz = clea_deu2009,
                          yvarz = c("to1", "pvs1_margin"))

par(mfrow=c(1,2))
plot(clea_deu2009["pvs1_margin"], key.pos = NULL, reset = FALSE)
plot(out_2["pvs1_margin.pred"], key.pos = NULL, reset = FALSE)

## End(Not run)

# Universal Kriging with one variable from a raster
## Not run:
data(gp4_deu2010)
data(clea_deu2009)
data(clea_deu2009_pt)
```

```

out_3 <- point2poly_krige(pointz = clea_deu2009_pt,
                          polyz = clea_deu2009,
                          yvarz = "to1",
                          rasterz = gpw4_deu2010)

par(mfrow=c(1,2))
plot(clea_deu2009["to1"], key.pos = NULL, reset = FALSE)
plot(out_3["to1.pred"], key.pos = NULL, reset = FALSE)

## End(Not run)

# Block Kriging with block size of 100 km
## Not run:
data(clea_deu2009)
data(clea_deu2009_pt)
out_4 <- point2poly_krige(pointz = clea_deu2009_pt,
                          polyz = clea_deu2009,
                          yvarz = "to1",
                          blockz = 100000)

par(mfrow=c(1,2))
plot(clea_deu2009["to1"], key.pos = NULL, reset = FALSE)
plot(out_4["to1.pred"], key.pos = NULL, reset = FALSE)

## End(Not run)

```

point2poly_simp

Point-to-polygon interpolation, simple overlay method

Description

Function for assigning values from a source point layer to a destination polygon layer, using simple point-in-polygon overlays

Usage

```

point2poly_simp(
  pointz,
  polyz,
  varz,
  char_varz = NULL,
  funz = list(function(x) {      sum(x, na.rm = TRUE) }),
  na_val = NA,
  drop_na_cols = FALSE
)

```

Arguments

pointz Source points layer. sf object.

polyz Destination polygon layer. Must have identical CRS to pointz. sf object.

<code>varz</code>	Names of variable(s) to be assigned from source polygon layer to destination polygons. Character string or vector of character strings.
<code>char_varz</code>	Names of character string variable(s) in <code>varz</code> . Character string or vector of character strings.
<code>funz</code>	Aggregation function to be applied to variables specified in <code>varz</code> . Must take as an input a vector <code>x</code> . Function or list of functions.
<code>na_val</code>	Value to be assigned to missing values. Default is NA. Logical or list.
<code>drop_na_cols</code>	Drop columns with completely missing values. Default is FALSE. Logical.

Details

Assignment procedures are the same for numeric and character string variables. All variables supplied in `varz` are passed directly to the function specified in `funz`. If different sets of variables are to be aggregated with different functions, both `varz` and `funz` should be specified as lists (see examples below).

Value

Returns a `sf` polygon object, with variables from `pointz` assigned to the geometries of `polyz`.

Examples

```
# Assignment of a single variable (sums)
## Not run:
data(hex_05_deu)
data(clea_deu2009_pt)
out_1 <- point2poly_simp(pointz=clea_deu2009_pt,
                        polyz=hex_05_deu,
                        varz="vv1")

plot(out_1["vv1"])

## End(Not run)

# Replace NA's with 0's
## Not run:
out_2 <- point2poly_simp(pointz = clea_deu2009_pt,
                        polyz = hex_05_deu,
                        varz = "vv1",
                        na_val = 0)

plot(out_2["vv1"])

## End(Not run)

# Multiple variables, with different assignment functions
## Not run:
out_3 <- point2poly_simp(pointz = clea_deu2009_pt,
                        polyz = hex_05_deu,
                        varz = list(
                          c("to1", "pvs1_margin"),
                          c("vv1"),
```

```

      c("incumb_pty_n", "win1_pty_n")),
  funz = list(
    function(x){mean(x, na.rm=TRUE)},
    function(x){sum(x, na.rm=TRUE)},
    function(x){paste0(unique(na.omit(x)), collapse=" | ") }),
  na_val = list(NA_real_, 0, NA_character_)

## End(Not run)

```

point2poly_tess

Point-to-polygon interpolation, tessellation method

Description

Function for interpolating values from a source point layer to a destination polygon layer, using Voronoi tessellation and area/population weights.

Usage

```

point2poly_tess(
  pointz,
  polyz,
  poly_id,
  char_methodz = "aw",
  methodz = "aw",
  pop_raster = NULL,
  varz = NULL,
  pycno_varz = NULL,
  char_varz = NULL,
  char_assign = "biggest_overlap",
  funz = function(x, w) { stats::weighted.mean(x, w, na.rm = TRUE) },
  return_tess = FALSE,
  seed = 1
)

```

Arguments

pointz	Source points layer. sf object.
polyz	Destination polygon layer. Must have identical CRS to pointz. sf object.
poly_id	Name of unique ID column for destination polygon layer. Character string.
char_methodz	Interpolation method(s) for character strings. Could be either of "aw" (areal weighting, default) or "pw" (population weighting). See "details". Character string.
methodz	Interpolation method(s) for numeric covariates. Could be either of "aw" (areal weighting, default) and/or "pw" (population weighting). See "details". Character string or vector of character strings.

pop_raster	Population raster to be used for population weighting, Must be supplied if methodz="pw". Must have identical CRS to poly_from. raster object.
varz	Names of numeric variable(s) to be interpolated from source polygon layer to destination polygons. Character string or list of character strings.
pycno_varz	Names of spatially extensive numeric variables for which the pycnophylactic (mass-preserving) property should be preserved. Character string or vector of character strings.
char_varz	Names of character string variables to be interpolated from source polygon layer to destination polygons. Character string or vector of character strings.
char_assign	Assignment rule to be used for variables specified in char_varz. Could be either "biggest_overlap" (default) or "all_overlap". See "details". Character string or vector of character strings.
funz	Aggregation function to be applied to variables specified in varz. Must take as an input a numeric vector x and vector of weights w. Function or list of functions.
return_tess	Return Voronoi polygons, in addition to destination polygon layer? Default is FALSE. Logical.
seed	Seed for generation of random numbers. Default is 1. Numeric.

Details

This function interpolates point data to polygons with a two-step process. In the first step (tessellation), each point is assigned a Voronoi cell, drawn such that (a) the distance from its borders to the focal point is less than or equal to the distance to any other point, and (b) no gaps between cells remain. The second step (interpolation) performs a polygon-in-polygon interpolation, using the Voronoi cells as source polygons.

Currently supported integration methods in the second step (methodz) include:

- Areal weighting ("aw"). Values from poly_from weighted in proportion to relative area of spatial overlap between source features and geometries of poly_to.
- Population weighting ("pw"). Values from poly_from weighted in proportion to relative population sizes in areas of spatial overlap between source features and geometries of poly_to. This routine uses a third layer (supplied in pop_raster) to calculate the weights.

When a list of variables are supplied and one methods argument specified, then the chosen method will be applied to all variables.

When a list of of variables are supplied and multiple methods arguments specified, then weighting methods will be applied in a pairwise order. For example, specifying `varz = list(c("to1", "pvs1_margin"), c("vv1"))` and `methodz = c('aw', 'pw')` will apply areal weighting to the the first set of variables (to1 and pvs1_margin) and population weighing to the second set (vv1).

Interpolation procedures are handled somewhat differently for numeric and character string variables. For numeric variables supplied in varz, "aw" and/or "pw" weights are passed to the function specified in funz. If different sets of numeric variables are to be aggregated with different functions, both varz and funz should be specified as lists (see examples below).

For character string (and any other) variables supplied in char_varz, "aw" and/or "pw" weights are passed to the assignment rule(s) specified in char_assign. Note that the char_varz argument may include numerical variables, but varz cannot include character string variables.

Currently supported assignment rules for character strings (char_assign) include:

- "biggest_overlap". For each variable in char_varz, the features in poly_to are assigned a single value from overlapping poly_from features, corresponding to the intersection with largest area and/or population weight.
- "all_overlap". For each variable in char_varz, the features in poly_to are assigned all values from overlapping poly_from features, ranked by area and/or population weights (largest-to-smallest) of intersections.

It is possible to pass multiple arguments to char_assign (e.g. char_assign=c("biggest_overlap", "all_overlap")), in which case the function will calculate both, and append the resulting columns to the output.

Value

If return_tess=FALSE, returns a sf polygon object, with variables from pointz interpolated to the geometries of polyz.

If return_tess=TRUE, returns a list, containing

- "result". The destination polygon layer. sf object.
- "tess". The (intermediate) Voronoi tessellation polygon layer. sf object.

Examples

```
# Interpolation of a single variable, with area weights
## Not run:
data(hex_05_deu)
data(clea_deu2009_pt)
out_1 <- point2poly_tess(pointz = clea_deu2009_pt,
                        polyz = hex_05_deu,
                        poly_id = "HEX_ID",
                        varz = "to1")

plot(out_1["to1_aw"])

## End(Not run)

# Extract and inspect tessellation polygons
## Not run:
out_2 <- point2poly_tess(pointz = clea_deu2009_pt,
                        polyz = hex_05_deu,
                        poly_id = "HEX_ID",
                        varz = "to1",
                        return_tess = TRUE)

plot(out_2$tess["to1"])
plot(out_2$result["to1_aw"])

## End(Not run)

# Interpolation of multiple variables, with area and population weights
## Not run:
data(gpw4_deu2010)
out_3 <- point2poly_tess(pointz = clea_deu2009_pt,
                        polyz = hex_05_deu,
                        poly_id = "HEX_ID",
```

```

methodz = c("aw", "pw"),
varz = list(
  c("to1", "pvs1_margin"),
  c("vv1")
),
pycno_varz = "vv1",
funz = list(
  function(x,w){stats::weighted.mean(x,w)},
  function(x,w){sum(x*w)}
),
char_varz = c("incumb_pty_n", "win1_pty_n"),
pop_raster = gpw4_deu2010)

plot(out_3["pvs1_margin_pw"])

## End(Not run)

```

poly2poly_ap

Area and population weighted polygon-to-polygon interpolation

Description

Function for interpolating values from a source polygon layer to an overlapping (but spatially mis-aligned) destination polygon layer, using area and/or population weights.

Usage

```

poly2poly_ap(
  poly_from,
  poly_to,
  poly_to_id,
  geo_vor = NULL,
  methodz = "aw",
  char_methodz = "aw",
  pop_raster = NULL,
  varz = NULL,
  pycno_varz = NULL,
  char_varz = NULL,
  char_assign = "biggest_overlap",
  funz = function(x, w) { stats::weighted.mean(x, w, na.rm = TRUE) },
  seed = 1
)

```

Arguments

poly_from	Source polygon layer. sf object.
poly_to	Destination polygon layer. Must have identical CRS to poly_from. sf object.
poly_to_id	Name of unique ID column for destination polygon layer. Character string.
geo_vor	Voronoi polygons object (used internally by point2poly_tess). sf object.

methodz	Area interpolation method(s). Could be either of "aw" (areal weighting, default) and/or "pw" (population weighting). See "details". Character string or vector of character strings.
char_methodz	Interpolation method(s) for character strings. Could be either of "aw" (areal weighting, default) or "pw" (population weighting). See "details". Character string.
pop_raster	Population raster to be used for population weighting, Must be supplied if methodz="pw". Must have identical CRS to poly_from. raster object.
varz	Names of numeric variable(s) to be interpolated from source polygon layer to destination polygons. Character string or vector of character strings.
pycno_varz	Names of spatially extensive numeric variables for which the pycnophylactic (mass-preserving) property should be preserved. Character string or vector of character strings.
char_varz	Names of character string variables to be interpolated from source polygon layer to destination polygons. Character string or vector of character strings.
char_assign	Assignment rule to be used for variables specified in char_varz. Could be either "biggest_overlap" (default) or "all_overlap". See "details". Character string or vector of character strings.
funz	Aggregation function to be applied to variables specified in varz. Must take as an input a numeric vector x and vector of weights w. Function or list of functions.
seed	Seed for generation of random numbers. Default is 1. Numeric.

Details

Currently supported integration methods (methodz) include:

- Areal weighting ("aw"). Values from poly_from weighted in proportion to relative area of spatial overlap between source features and geometries of poly_to.
- Population weighting ("pw"). Values from poly_from weighted in proportion to relative population sizes in areas of spatial overlap between source features and geometries of poly_to. This routine uses a third layer (supplied in pop_raster) to calculate the weights.

It is possible to pass multiple arguments to methodz (e.g. methodz=c("aw", "pw")), in which case the function will calculate both sets of weights, and append the resulting columns to the output.

Interpolation procedures are handled somewhat differently for numeric and character string variables. For numeric variables supplied in varz, "aw" and/or "pw" weights are passed to the function specified in funz. If different sets of numeric variables are to be aggregated with different functions, both varz and funz should be specified as lists (see examples below).

For character string (and any other) variables supplied in char_varz, "aw" and/or "pw" weights are passed to the assignment rule(s) specified in char_assign. Note that the char_varz argument may include numerical variables, but varz cannot include character string variables.

Currently supported assignment rules for character strings (char_assign) include:

- "biggest_overlap". For each variable in char_varz, the features in poly_to are assigned a single value from overlapping poly_from features, corresponding to the intersection with largest area and/or population weight.

- "all_overlap". For each variable in char_varz, the features in poly_to are assigned all values from overlapping poly_from features, ranked by area and/or population weights (largest-to-smallest) of intersections.

It is possible to pass multiple arguments to char_assign (e.g. char_assign=c("biggest_overlap", "all_overlap")), in which case the function will calculate both, and append the resulting columns to the output.

Value

sf polygon object, with variables from poly_from interpolated to the geometries of poly_to.

Examples

```
# Interpolation of a single variable, with area weights
## Not run:
data(clea_deu2009)
data(hex_05_deu)
out_1 <- poly2poly_ap(poly_from = clea_deu2009,
                      poly_to = hex_05_deu,
                      poly_to_id = "HEX_ID",
                      varz = "to1"
                      )

## End(Not run)

# Interpolation of multiple variables, with area weights
## Not run:
out_2 <- poly2poly_ap(
  poly_from = clea_deu2009,
  poly_to = hex_05_deu,
  poly_to_id = "HEX_ID",
  varz = list(
    c("to1", "pvs1_margin"),
    c("vv1") ),
  pycno_varz = "vv1",
  funz = list(
    function(x,w){stats::weighted.mean(x,w)},
    function(x,w){sum(x*w)} ),
  char_varz = c("incumb_pty_n", "win1_pty_n")
)

## End(Not run)

# Interpolation of a single variable, with population weights
## Not run:
data(gpw4_deu2010)
out_3 <- poly2poly_ap(poly_from = clea_deu2009,
                      poly_to = hex_05_deu,
                      poly_to_id = "HEX_ID",
                      varz = "to1",
                      methodz = "pw",
                      pop_raster = gpw4_deu2010)
```

```
## End(Not run)

# Interpolation of a single variable, with area and population weights
## Not run:
out_4 <- poly2poly_ap(poly_from = clea_deu2009,
                      poly_to = hex_05_deu,
                      poly_to_id = "HEX_ID",
                      varz = "to1",
                      methodz = c("aw", "pw"),
                      pop_raster = gpw4_deu2010)

## End(Not run)
```

sf2raster

Convert simple features object into regularly spaced raster

Description

This function takes in an sf spatial object (polygon or point) and returns a regularly spaced RasterLayer. Reverse translation option allows users to create an sf polygon object from the regularly spaced RasterLayer. This function can also convert the sf object into a cartogram with a user-specified variable name.

Usage

```
sf2raster(
  polyz_from = NULL,
  pointz_from = NULL,
  input_variable = NULL,
  reverse = FALSE,
  poly_to = NULL,
  return_output = NULL,
  return_field = NULL,
  aggregate_function = list(function(x) mean(x, na.rm = TRUE)),
  reverse_function = list(function(x) mean(x, na.rm = TRUE)),
  grid_res = c(1000, 1000),
  cartogram = FALSE,
  carto_var = NULL,
  message_out = TRUE,
  return_list = FALSE
)
```

Arguments

`polyz_from` Source polygon layer. sf object.

`pointz_from` Source point layer. sf object.

`input_variable` Name of input variable from source layer. Character string.

<code>reverse</code>	Reverse translation from raster layer to <code>sf</code> polygon object (polygon features only). Default is <code>FALSE</code> .
<code>poly_to</code>	Destination polygon layer for reverse conversion. Must be specified if <code>reverse=TRUE</code> . <code>sf</code> object.
<code>return_output</code>	Return output for reverse conversion. Must be specified if <code>reverse=TRUE</code> .
<code>return_field</code>	Return field for reverse conversion. Must be specified if <code>reverse=TRUE</code> .
<code>aggregate_function</code>	Aggregation function to be applied to variables specified in <code>input_variable</code> . Must take as an input a numeric vector <code>x</code> . Function or list of functions. Default is <code>mean</code> .
<code>reverse_function</code>	Aggregation function for reverse conversion. Must be specified if <code>reverse=TRUE</code> . Function or list of functions. Default is <code>mean</code> .
<code>grid_res</code>	Resolution of raster grid, in meters. Numerical vector of length 2 (number of rows, number of columns). Default is <code>c(1000, 1000)</code> .
<code>cartogram</code>	Cartogram transformation. Logical. Default is <code>FALSE</code> .
<code>carto_var</code>	Input variable for cartogram transformation. Must be specified if <code>cartogram=TRUE</code> . Character string.
<code>message_out</code>	Print informational messages. Logical. Default is <code>TRUE</code> .
<code>return_list</code>	Return full set of results, including input polygons, centroids and field raster. Default is <code>FALSE</code> . Logical.

Value

If `return_list=FALSE` (default) and `reverse=FALSE` (default), returns `RasterLayer` object, with cell values corresponding to `input_variable`.

If `return_list=TRUE` and input layer is polygon, returns a list containing

- `"return_output"`. Output raster, with values corresponding to `input_variable`. `RasterLayer` object.
- `"return_centroid"`. Raster of centroids, with values corresponding to `input_variable`. `RasterLayer` object.
- `"poly_to"`. Source polygons, with columns corresponding to `input_variable` and auto-generated numerical ID Field. `sf` object.
- `"return_field"`. Output raster, with values corresponding to auto-generated numerical ID Field. `RasterLayer` object.

If `return_list=TRUE` and input layer is points, returns a list containing

- `"return_output"`. Output raster, with values corresponding to `input_variable`. `RasterLayer` object.
- `"return_point"`. Source points, with column corresponding to `input_variable`.

If `reverse=TRUE`, returns an `sf` polygon layer, with columns corresponding to `input_variable` and auto-generated numerical ID Field.

Examples

```

# Rasterization of polygon layer.
## Not run:
data(clea_deu2009)
out_1 <- sf2raster(polyz_from = utm_select(clea_deu2009),
                  input_variable = "to1")
raster::plot(out_1)

## End(Not run)
# Rasterization of point layer
## Not run:
data(clea_deu2009_pt)
out_2 <- sf2raster(pointz_from = utm_select(clea_deu2009_pt),
                  input_variable = "to1",
                  grid_res = c(25000,25000))
raster::plot(out_2)

## End(Not run)
# Cartogram (vote turnout scaled by number of valid votes)
## Not run:
out_3 <- sf2raster(polyz_from = utm_select(clea_deu2009),
                  input_variable = "to1",
                  cartogram = TRUE,
                  carto_var = "vv1")
raster::plot(out_3)

## End(Not run)
# Polygonization of cartogram raster
## Not run:
out_4a <- sf2raster(polyz_from = utm_select(clea_deu2009),
                  input_variable = "to1",
                  cartogram = TRUE,
                  carto_var = "vv1",
                  return_list = TRUE)
out_4 <- sf2raster(reverse = TRUE,
                  poly_to = out_4a$poly_to,
                  return_output = out_4a$return_output,
                  return_field = out_4a$return_field)
raster::plot(out_4)

## End(Not run)

```

Description

Sub-National Geospatial Data Archive System: Geoprocessing Toolkit

Details

See the README on [GitHub](#)

utm_select	<i>Automatically convert geographic (degree) to planar coordinates (meters)</i>
------------	---

Description

Function to automatically convert simple feature, spatial and raster objects with geographic coordinates (longitude, latitude / WGS 1984, EPSG:4326) to planar UTM coordinates. If the study region spans multiple UTM zones, defaults to Albers Equal Area.

Usage

```
utm_select(x, max_zones = 5, return_list = FALSE)
```

Arguments

x	Layer to be reprojected. sf, sp or RasterLayer object.
max_zones	Maximum number of UTM zones for single layer. Default is 5. Numeric.
return_list	Return list object instead of reprojected layer (see Details). Default is FALSE. Logical.

Details

Optimal map projection for the object x is defined by matching its horizontal extent with that of the 60 UTM zones. If object spans multiple UTM zones, uses either the median zone (if number of zones is equal to or less than max_zones) or Albers Equal Area projection with median longitude as projection center (if number of zones is greater than max_zones).

Value

Re-projected layer. sf or RasterLayer object, depending on input.

If return_list=TRUE, returns a list object containing

- "x_out". The re-projected layer. sf or RasterLayer object, depending on input.
- "proj4_best". proj4string of the projection. Character string.

Examples

```
# Find a planar projection for an unprojected (WSG 1984) hexagonal grid of Germany
## Not run:
data(hex_05_deu)
hex_tr <- utm_select(hex_05_deu)

## End(Not run)
```


Index

* datasets

- clea_deu2009, [2](#)
- clea_deu2009_df, [3](#)
- clea_deu2009_pt, [4](#)
- gpw4_deu2010, [10](#)
- hex_05_deu, [11](#)
- highways_deu1992, [11](#)

autofitVariogram, [20](#)

- clea_deu2009, [2](#)
- clea_deu2009_df, [3](#)
- clea_deu2009_pt, [4](#)

df2sf, [5](#)

fix_geom, [6](#)

- geocode_osm, [7](#), [9](#)
- geocode_osm_batch, [7](#), [8](#)
- gpw4_deu2010, [10](#)

- hex_05_deu, [11](#)
- highways_deu1992, [11](#)
- hot_spot, [12](#)

line2poly, [14](#)

nb2listw, [12](#)

nesting, [16](#)

- point2poly_krige, [18](#)
- point2poly_simp, [21](#)
- point2poly_tess, [23](#)
- poly2poly_ap, [26](#)

sf2raster, [29](#)

SUNGEO, [31](#)

utm_select, [32](#)