

# Package ‘TCGAretriever’

October 12, 2022

**Type** Package

**Title** Retrieve Genomic and Clinical Data from TCGA

**Version** 1.5

**Date** 2019-12-17

**Author** Damiano Fantini

**Maintainer** Damiano Fantini <damiano.fantini@gmail.com>

**Description** The Cancer Genome Atlas (TCGA) is a program aimed at improving our understanding of Cancer Biology. Several TCGA Datasets are available online. 'TCGAretriever' helps accessing and downloading TCGA data hosted on 'cBioPortal' via its Web Interface (see <<http://www.cbioportal.org/>> for more information). 'TCGAretriever' is easy to use (get all the TCGA data you need with a few lines of code), enforces reliable data download (via 'httr'), and is suitable for downloading large volumes of data.

**URL** [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

**Depends** R(>= 3.1)

**Imports** httr

**Suggests** graphics, utils, knitr, rmarkdown

**VignetteBuilder** knitr

**Encoding** UTF-8

**License** GPL-2

**RoxygenNote** 6.1.1

**NeedsCompilation** no

**Repository** CRAN

**Date/Publication** 2019-12-17 21:20:02 UTC

## R topics documented:

basic_tcga_query . . . . .	2
expand_cases . . . . .	3
fetch_all_tcgadata . . . . .	3
get_cancer_studies . . . . .	4

get_cancer_types . . . . .	5
get_case_lists . . . . .	6
get_clinical_data . . . . .	7
get_ext_mutation . . . . .	8
get_genetic_profiles . . . . .	9
get_profile_data . . . . .	9
get_protein_data . . . . .	10
get_protein_info . . . . .	11
make_groups . . . . .	12

<b>Index</b>	<b>14</b>
--------------	-----------

---

basic_tcga_query	<i>TCGA Core Query Engine</i>
------------------	-------------------------------

---

## Description

Core Function that queries the URL provided as argument (typically a cbioportal.org URL). The function halts until the content has been completely downloaded and returns a data frame.

## Usage

```
basic_tcga_query(my_url)
```

## Arguments

my\_url                    string. Typically, a URL pointing to the cBioPortal API.

## Details

This is a core function invoked by other functions in the package.

## Author(s)

Damiano Fantini, <damiano.fantini@gmail.com>

## References

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

---

expand_cases	<i>Explode TCGA Case Identifiers from a TCGA Study</i>
--------------	--

---

**Description**

Each TCGA Study includes one or more "case lists". These are lists of sample/patient identifiers. All case lists of a study of interest are retrieved and the individual case identifiers are expanded and returned

**Usage**

```
expand_cases(csid = NULL)
```

**Arguments**

csid                    string corresponding to a TCGA Cancer Study identifier

**Value**

list containing as many elements as TCGA case lists available for a given TCGA Study. Each element is a list containing two elements:

- a string corresponding to the Id of the case list as defined by TCGA
- character vector including all case IDs corresponding to the case list

**Examples**

```
expand_cases("blca_tcga")
```

---

fetch_all_tcgadata	<i>Recursively Fetch All Data Included in a TCGA Study Subset</i>
--------------------	---

---

**Description**

Recursively query TCGA to retrieve large volumes of data corresponding to a high number of genes (up to the entire genome). Data are returned as a data frame that can be easily manipulated for further analyses.

**Usage**

```
fetch_all_tcgadata(case_id = NULL, gprofile_id = NULL, glist = NULL,  
                  mutations = FALSE)
```

**Arguments**

case_id	string corresponding to the identifier of the TCGA Case List of interest
gprofile_id	string corresponding to the identifier of the TCGA Profile of interest
glist	character vector including one or more gene identifiers (ENTREZID or the OFFICIAL SYMBOL can be used)
mutations	logical. If TRUE, extended mutation data are fetched instead of the standard TCGA data

**Value**

A data.frame is returned, including the desired TCGA data. Typically, rows are genes and columns are cases. If "extended mutation" data are retrieved (mutations = TRUE), rows correspond to individual mutations while columns are populated with mutation features

**Author(s)**

Damiano Fantini, <damiano.fantini@gmail.com>

**References**

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

**Examples**

```
# Mutations occurring on TP53 and PTEN genes in the bladder cancer study
# Returns 1 data frame: rows = genes; columns = cases
fetch_all_tcgadata("blca_tcga_all", "blca_tcga_mutations", c("PTEN", "TP53"), mutation = FALSE)
# Extended mutations occurring on TP53 and PTEN genes in the bladder cancer study
# Returns 1 data frame: rows = mutations; columns = extended information
fetch_all_tcgadata("blca_tcga_all", "blca_tcga_mutations", c("PTEN", "TP53"), mutation = TRUE)
```

---

get\_cancer\_studies      *Retrieve a List of Cancer Studies Available at TCGA*

---

**Description**

Retrieve information about the different TCGA studies that are available at cBioPortal. Information include a cancer\_study\_id, a name of the study and a description for each study.

**Usage**

```
get_cancer_studies()
```

**Value**

Data Frame including one study per row and three columns.

**Author(s)**

Damiano Fantini, <damiano.fantini@gmail.com>

**References**

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

**Examples**

```
all_studies <- get_cancer_studies()
message(paste("There are", nrow(all_studies), "studies currently available..."))
if(ncol(all_studies) >= 2) {
  head(all_studies[,1:2])
}
```

---

get\_cancer\_types

*Retrieve a List of Cancer Types as Defined by the TCGA Guidelines*

---

**Description**

Retrieve information about the different types of cancer that may be included in TCGA Studies. Information include Identifier and Cancer Name.

**Usage**

```
get_cancer_types()
```

**Value**

A data.frame with one row per cancer type and two columns

**Author(s)**

Damiano Fantini, <damiano.fantini@gmail.com>

**References**

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

## Examples

```
all_canc <- get_cancer_types()
message(paste("There are", nrow(all_canc), "types on cancer defined at TCGA..."))
head(all_canc)
```

---

get_case_lists	<i>Retrieve All Case List Available for a Specific TCGA Study</i>
----------------	---

---

## Description

TCGA keeps track of which samples were analyzed by which technique within a given Study. Sample identifiers are organized in lists of cases (samples/patients) and are associated with a case\_list identifier. The function retrieves information about the case lists available for a given TCGA Study.

## Usage

```
get_case_lists(csid = NULL)
```

## Arguments

csid                   String corresponding to the Identifier of the TCGA Study of Interest

## Value

Data Frame including one row per case\_list and five columns

## Author(s)

Damiano Fantini, <damiano.fantini@gmail.com>

## References

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

## Examples

```
all_case_lists <- get_case_lists("blca_tcga")
if(ncol(all_case_lists) >= 3) {
  all_case_lists[,1:3]
}
```

---

get\_clinical\_data      *Retrieve Clinical Information from a TCGA Study*

---

### Description

Retrieve Information about the Patients included in a TCGA Study of Interest. Each patient is associated with a case\_id. Each case\_id is accompanied by a set of clinical information that may include sex, age, therapeutic regimen, Tumor Staging, vital status and others. NA are allowed.

### Usage

```
get_clinical_data(case_id = NULL)
```

### Arguments

case\_id            string corresponding to the case\_list identifier of a specific list of cases of interest

### Value

data.frame including one row per patient/case/sample

### Author(s)

Damiano Fantini, <damiano.fantini@gmail.com>

### References

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

### Examples

```
clinic_data <- get_clinical_data("blca_tcga_all")
if (nrow(clinic_data) >= 6 & ncol(clinic_data) >= 5) {
  clinic_data[1:6,1:5]
  hist(as.numeric(clinic_data$AGE),
       col = "darkorange",
       xlab = "Age",
       main = "Bladder Cancer, age of diagnosis")
}
```

---

get_ext_mutation	<i>Retrieve Extended Information About DNA Mutations from TCGA</i>
------------------	--

---

### Description

Query TCGA for Data about DNA Sequence Variations (Mutations) identified by exome sequencing projects. The function will retrieve an extensive set of information for each mutation that was identified in the set of cases of interest. The function can only handle a limited number of query genes. For larger queries, use the `fetch_all_tcgadata()` function.

### Usage

```
get_ext_mutation(case_id = NULL, gprofile_id = NULL, glist = NULL)
```

### Arguments

<code>case_id</code>	string corresponding to the Identifier of the case_list of interest
<code>gprofile_id</code>	string corresponding to the Identifier of the Genetic Profile of Interest
<code>glist</code>	character vector including Gene Identifiers (ENTREZID or OFFICIAL_SYMBOL)

### Value

data Frame including one row per mutation

### Author(s)

Damiano Fantini, <damiano.fantini@gmail.com>

### References

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

### Examples

```
tp53_mutats <- get_ext_mutation("blca_tcga_all", "blca_tcga_mutations", "TP53")
if(ncol(tp53_mutats) >= 6 & nrow(tp53_mutats) >= 10){
  tp53_mutats[1:10,1:6]
}
```



---

get\_genetic\_profiles    *Retrieve Genetic Profiles for a TCGA Study of Interest*

---

### Description

Retrieve Information about all genetic profiles associated with a TCGA Study of interest. Each TCGA Study includes one or more kind of molecular analyses whose results are referred to as genetic profiles.

### Usage

```
get_genetic_profiles(csid = NULL)
```

### Arguments

csid                    string corresponding to the cancer study id of interest

### Value

data.frame including one row per genetic profile and six columns

### Author(s)

Damiano Fantini, <damiano.fantini@gmail.com>

### References

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

### Examples

```
get_genetic_profiles("blca_tcga")
```

---

get\_profile\_data            *Retrieve TCGA Data corresponding to a Specific Genetic Profile of Interest*

---

### Description

Retrieve Data corresponding to a Genetic Profile of interest from a given TCGA Study. This function is the workhorse of the TCGAretriever package and can be used to fetch data concerning several genes at once. For larger queries, the use of the fetch\_all\_tcgadata() function is mandatory

**Usage**

```
get_profile_data(case_id = NULL, gprofile_id = NULL, glist = NULL)
```

**Arguments**

case_id	String corresponding to the Identifier of a list of cases
gprofile_id	String corresponding to the Identifier of a genetic Profile of interest
glist	Character vector including one or more gene identifiers (ENTREZID or OFFICIAL_SYMOL)

**Value**

data.frame with one row per gene and one column per case/sample

**Author(s)**

Damiano Fantini, <damiano.fantini@gmail.com>

**References**

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

**Examples**

```
get_profile_data("blca_tcga_all", "blca_tcga_mutations", c("TP53", "E2F1"))
```

---

get_protein_data	<i>Retrieve Protein Expression Data from a TCGA Study</i>
------------------	---

---

**Description**

TCGA includes Information about Protein Expression measured by reverse-phase protein arrays. Antibody Information can be exported together with Expression Data. All expression data will be retrieved for all available protein targets.

**Usage**

```
get_protein_data(case_id = NULL, array_info = TRUE)
```

**Arguments**

case_id	String corresponding to the Identifier of the Case List of Interest
array_info	Logical. If TRUE, Antibody Information will also be exported

**Value**

Data Frame with one gene (protein target) per row

**Author(s)**

Damiano Fantini, <damiano.fantini@gmail.com>

**References**

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

**Examples**

```
# Protein Expression Only
blca_protein <- get_protein_data("blca_tcga_sequenced", FALSE)
if (nrow(blca_protein) > 10 & ncol(blca_protein) > 8) {
  blca_protein[1:8,1:8]
} else {
  message("Server may be down, please try again later...")
}
#
# Example including Antibody Information
blca_protein <- get_protein_data("blca_tcga_sequenced", TRUE)
if (nrow(blca_protein) > 10 & ncol(blca_protein) > 8) {
  blca_protein[1:8,1:8]
} else {
  message("Server may be down, please try again later...")
}
```

---

get\_protein\_info

*Retrieve Information on Antibodies Used for Protein Levels Determination*

---

**Description**

Retrieve information on antibodies used by reverse-phase protein arrays (RPPA) to measure protein/phosphoprotein levels.

**Usage**

```
get_protein_info(csid = NULL, array_type = "protein_level",
  glist = NULL)
```

**Arguments**

csid	String corresponding to the Cancer Study Identifier
array_type	String, c("protein_level", "phosphorylation"). Retrieve information about antibodies used for detecting total protein levels or phosphorylated levels of the protein product of the gene of interest
glist	Character vector including one or more gene identifiers (ENTREZID or OFFICIAL_SYMBOL)

**Value**

data frame having one antibody per row and four columns

**Author(s)**

Damiano Fantini, <damiano.fantini@gmail.com>

**References**

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

**Examples**

```
info1 <- get_protein_info("blca_tcga", glist = c("TP53", "PTEN", "E2F1", "AKT1"))
if (nrow(info1) > 0) {
  message("Total protein levels information")
  info1
} else {
  message("Server may be down, please try again later...")
}
#
info2 <- get_protein_info("blca_tcga", "phosphorylation", c("TP53", "PTEN", "E2F1", "AKT1"))
if (nrow(info2) > 0) {
  message("Phospho-protein levels information")
  info2
} else {
  message("Server may be down, please try again later...")
}
```

---

make\_groups

*Split Numeric Vectors in Groups*

---

**Description**

Assign each element of a numeric vector to a group. Grouping is based on ranks: numeric values are sorted and then split in 2 or more groups. Values may be sorted in an increasing or decreasing fashion. The vector is returned in the original order. Labels may be assigned to each group.

**Usage**

```
make_groups(num_vector, groups, group_labels = NULL, desc = FALSE)
```

**Arguments**

num_vector	numeric vector. It includes the values to be assigned to the different groups
groups	integer. The number of groups that will be generated
group_labels	character vector. Labels for each group. Note that the length of group_labels has to be equal to the number of groups
desc	logical. If TRUE, the sorting is applied in a decreasing fashion

**Value**

data.frame including the vector provided as argument in the original order ("value") and the grouping vector ("rank"). If labels are provided as an argument, group labels are also included in the data.frame ("labels").

**Author(s)**

Damiano Fantini, <damiano.fantini@gmail.com>

**References**

- <http://www.biotechworld.it/bioinf/2016/07/11/tcga-data-via-tcgaretriever/>
- [https://www.data-pulse.com/dev\\_site/TCGAretriever/](https://www.data-pulse.com/dev_site/TCGAretriever/)

**Examples**

```
exprs_geneX <- c(19.1,18.4,22.4,15.5,20.2,17.4,9.4,12.4,31.2,33.2,18.4,22.1)
groups_num <- 3
groups_labels <- c("high", "med", "low")
make_groups(exprs_geneX, groups_num, groups_labels, desc = TRUE)
```

# Index

## \* **intenal**

- basic\_tcga\_query, [2](#)
- basic\_tcga\_query, [2](#)
- expand\_cases, [3](#)
- fetch\_all\_tcgadata, [3](#)
- get\_cancer\_studies, [4](#)
- get\_cancer\_types, [5](#)
- get\_case\_lists, [6](#)
- get\_clinical\_data, [7](#)
- get\_ext\_mutation, [8](#)
- get\_genetic\_profiles, [9](#)
- get\_profile\_data, [9](#)
- get\_protein\_data, [10](#)
- get\_protein\_info, [11](#)
- make\_groups, [12](#)