

Package ‘apexcharter’

January 8, 2023

Version 0.4.0

Title Create Interactive Chart with the JavaScript 'ApexCharts'
Library

Description Provides an 'htmlwidgets' interface to 'apexcharts.js'.
'Apexcharts' is a modern JavaScript charting library to build interactive charts and visualizations with simple API.
'Apexcharts' examples and documentation are available here: [<https://apexcharts.com/>](https://apexcharts.com/).

License MIT + file LICENSE

Encoding UTF-8

LazyData true

ByteCompile true

Depends R (>= 2.10)

Imports htmltools, htmlwidgets (>= 1.5.3), magrittr, rlang, ggplot2,
jsonlite, shiny (>= 1.1.0)

Suggests testthat, knitr, scales, rmarkdown, covr

RoxygenNote 7.2.1

URL <https://github.com/dreamRs/apexcharter>,
<https://dreamrs.github.io/apexcharter/>

BugReports <https://github.com/dreamRs/apexcharter/issues>

VignetteBuilder knitr

NeedsCompilation no

Author Victor Perrier [aut, cre],
Fanny Meyer [aut],
Juned Chhipa [cph] (apexcharts.js library),
Mike Bostock [cph] (d3.format library)

Maintainer Victor Perrier <victor.perrier@dreamrs.fr>

Repository CRAN

Date/Publication 2023-01-08 18:40:02 UTC

R topics documented:

apexcharter-package	3
add-line	3
add-shade	5
add-vh-lines	7
add_event	9
add_event_marker	10
add_point	11
apex	13
apex-facets	15
apexchart	19
apexcharter-exports	20
apexcharter-shiny	21
apexcharter-shiny-facets	22
apexcharter-shiny-grid	24
apexchartProxy	25
apex_grid	25
ax-series	27
ax_annotations	28
ax_chart	30
ax_colors	34
ax_colors_manual	35
ax_dataLabels	36
ax_fill	38
ax_grid	39
ax_labels	41
ax_labs	42
ax_legend	43
ax_markers	45
ax_nodata	46
ax_plotOptions	47
ax_proxy_options	48
ax_proxy_series	50
ax_responsive	51
ax_states	52
ax_stroke	53
ax_subtitle	55
ax_theme	56
ax_title	57
ax_tooltip	58
ax_xaxis	60
ax_yaxis	63
ax_yaxis2	65
bar_opts	66
bubble_opts	67
candles	68
climate_paris	69

config_update	70
consumption	70
events_opts	71
format_date	73
format_num	74
heatmap_opts	75
label	77
parse_df	78
pie_opts	79
radialBar_opts	80
run_demo_input	81
run_demo_sparkbox	82
run_demo_sync	82
set_input_click	83
set_input_export	84
set_input_selection	85
set_input_zoom	87
set_tooltip_fixed	88
spark_box	89
unhcr_ts	90

Index	92
--------------	-----------

apexcharter-package	<i>An htmlwidget interface to the ApexCharts javascript chart library</i>
---------------------	---

Description

This package allow you to use ApexCharts.js (<https://apexcharts.com/>), to create interactive and modern SVG charts.

Author(s)

Victor Perrier (@dreamRs_fr)

add-line	<i>Add a line to a chart</i>
----------	------------------------------

Description

Add a line to an existing chart (bar, scatter and line types supported). On scatter charts you can also add a smooth line.

Usage

```
add_line(
  ax,
  mapping,
  data = NULL,
  type = c("line", "spline"),
  serie_name = NULL
)
```

```
add_smooth_line(
  ax,
  formula = y ~ x,
  model = c("lm", "loess"),
  n = 100,
  ...,
  type = c("line", "spline"),
  serie_name = NULL
)
```

Arguments

<code>ax</code>	An apexchart() htmlwidget object.
<code>mapping</code>	Default list of aesthetic mappings to use for chart.
<code>data</code>	A data.frame to use to add a line, if NULL (default), the data.frame provided in <code>apex()</code> will be used.
<code>type</code>	Type of line.
<code>serie_name</code>	Name for the serie displayed in tooltip and legend.
<code>formula</code>	Formula passed to the method, default to <code>y ~ x</code> from main aesthetics.
<code>model</code>	Model to use between lm or loess .
<code>n</code>	Number of points used for predictions.
<code>...</code>	Arguments passed to model.

Value

An [apexchart\(\)](#) htmlwidget object.

Examples

```
library(apexcharter)

# Bar ----

data("climate_paris")

# Add a line on a column's chart
apex(climate_paris, aes(month, precipitation), type = "column") %>%
```

```
    add_line(aes(month, temperature))

# Add secondary axis
apex(climate_paris, aes(month, precipitation), type = "column") %>%
  add_line(aes(month, temperature)) %>%
  ax_yaxis(
    title = list(text = "Precipitation (in mm)")
  ) %>%
  ax_yaxis2(
    opposite = TRUE,
    decimalsInFloat = 0,
    title = list(text = "Temperature (in degree celsius)")
  ) %>%
  ax_dataLabels(
    enabled = TRUE, enabledOnSeries = list(1)
  )

# Scatter ----

# add smooth line on scatter plot
apex(cars, aes(speed, dist), type = "scatter") %>%
  add_line(aes(x, y), data = lowess(cars), serie_name = "lowess")

# or directly
apex(cars, aes(speed, dist), type = "scatter") %>%
  add_smooth_line()

apex(cars, aes(speed, dist), type = "scatter") %>%
  add_smooth_line(model = "loess", span = 1)

apex(cars, aes(speed, dist), type = "scatter") %>%
  add_smooth_line(model = "loess", degree = 1)

apex(cars, aes(speed, dist), type = "scatter") %>%
  add_smooth_line(formula = y ~ poly(x, 2))

apex(cars, aes(speed, dist), type = "scatter") %>%
  add_smooth_line(model = "lm", serie_name = "lm") %>%
  add_smooth_line(model = "loess", serie_name = "loess")
```

Description

`add_shade()` allow to add a shaded area on specified range, `add_shade_weekend()` add a shadow on every week-end.

Usage

```
add_shade(ax, from, to, color = "#848484", opacity = 0.2, label = NULL, ...)
```

```
add_shade_weekend(ax, color = "#848484", opacity = 0.2, label = NULL, ...)
```

Arguments

<code>ax</code>	An <code>apexchart()</code> <code>htmlwidget</code> object.
<code>from</code>	Vector of position to start shadow.
<code>to</code>	Vector of position to end shadow.
<code>color</code>	Color of the shadow.
<code>opacity</code>	Opacity of the shadow.
<code>label</code>	Add a label to the shade, use a character or see <code>label</code> for more controls.
<code>...</code>	Additional arguments, see https://apexcharts.com/docs/options/annotations/ for possible options.

Value

An `apexchart()` `htmlwidget` object.

Note

`add_shade_weekend` only works if variable used for x-axis is of class `Date` or `POSIXt`.

Examples

```
library(apexcharter)
data("consumption")

# specify from and to date
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_shade(from = "2020-01-06", to = "2020-01-20")

# you can add several shadows
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_shade(from = "2020-01-06", to = "2020-01-20") %>%
  add_shade(from = "2020-02-04", to = "2020-02-10")

# or use a vector
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_shade(
    from = c("2020-01-06", "2020-02-04"),
    to = c("2020-01-20", "2020-02-10")
  )
```

```
)

# Add a label
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_shade(
    from = "2020-01-06", to = "2020-01-20",
    label = "interesting period"
  )

# add label with more options
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_shade(
    from = "2020-01-06", to = "2020-01-20",
    color = "firebrick",
    label = label(
      text = "something happened",
      background = "firebrick",
      color = "white",
      fontWeight = "bold",
      padding = c(3, 5, 3, 5)
    )
  )

# automatically add shadow on week-ends
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_shade_weekend()
```

add-vh-lines	<i>Add horizontal or vertical line</i>
--------------	--

Description

Add horizontal or vertical line

Usage

```
add_hline(ax, value, color = "#000", dash = 0, label = NULL, ...)
```

```
add_vline(ax, value, color = "#000", dash = 0, label = NULL, ...)
```

Arguments

ax	An apexchart() htmlwidget object.
value	Vector of position for the line(s).

color	Color(s) of the line(s).
dash	Creates dashes in borders of SVG path. A higher number creates more space between dashes in the border. Use 0 for plain line.
label	Add a label to the shade, use a character or see label for more controls.
...	Additional arguments, see https://apexcharts.com/docs/options/annotations/ for possible options.

Value

An `apexchart()` htmlwidget object.

Examples

```
library(apexcharter)

# On a column chart
unhcr_ts %>%
  subset(year == 2017 & population_type == "Asylum-seekers") %>%
  apex(
    aes(continent_origin, n),
    "column"
  ) %>%
  add_hline(value = 5e5)

# On a scatter chart
apex(
  data = cars,
  aes(speed, dist),
  "scatter"
) %>%
  add_hline(value = mean(cars$dist)) %>%
  add_vline(value = mean(cars$speed))

# With labels
apex(
  data = cars,
  aes(speed, dist),
  "scatter"
) %>%
  add_hline(
    value = mean(cars$dist),
    label = "Mean of dist"
  ) %>%
  add_vline(
    value = mean(cars$speed),
    label = label(
      text = "Mean of speed",
      borderColor = "red"
    )
  )
)
```

add_event	<i>Add an event to a chart</i>
-----------	--------------------------------

Description

Add a vertical line to mark a special event on a chart.

Usage

```
add_event(ax, when, color = "#E41A1C", dash = 4, label = NULL, ...)
```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
when	Vector of position to place the event.
color	Color of the line.
dash	Creates dashes in borders of SVG path. A higher number creates more space between dashes in the border. Use 0 for plain line.
label	Add a label to the shade, use a character or see <code>label</code> for more controls.
...	Additional arguments, see https://apexcharts.com/docs/options/annotations/ for possible options.

Value

An `apexchart()` htmlwidget object.

See Also

`add_event_marker` to add a point.

Examples

```
library(apexcharter)
data("consumption")

# specify from and to date
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_event(when = "2020-01-11")

# several events
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_event(when = c("2020-01-11", "2020-01-29"))

# Add labels on events
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_event(
    when = c("2020-01-11", "2020-01-29"),
```

```

    label = label(text = c("Am", "Ar"))
  )

# can be combined with shade
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_shade(from = "2020-01-06", to = "2020-01-20")%>%
  add_event(when = c("2020-01-11", "2020-01-29"))

```

add_event_marker *Add an event marker to a chart*

Description

Add a point with a label based on a datetime.

Usage

```

add_event_marker(
  ax,
  when,
  y,
  size = 5,
  color = "#000",
  fill = "#FFF",
  width = 2,
  shape = "circle",
  radius = 2,
  label = NULL,
  ...
)

```

Arguments

ax	An apexchart() htmlwidget object.
when	Vector of position to place the event.
y	Coordinate(s) on the y-axis.
size	Size of the marker.
color	Stroke Color of the marker point.
fill	Fill Color of the marker point.
width	Stroke Size of the marker point.
shape	Shape of the marker: "circle" or "square".
radius	Radius of the marker (applies to square shape).
label	Add a label to the shade, use a character or see label for more controls.
...	Additional arguments, see https://apexcharts.com/docs/options/annotations/ for possible options.

Value

An `apexchart()` `htmlwidget` object.

See Also

`add_event` to add a vertical line.

Examples

```
library(apexcharter)
data("consumption")

# add a marker
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_event_marker(when = "2020-01-22", y = 1805)

# with a label
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_event_marker(when = "2020-01-22", y = 1805, label = "Consumption peak")

# add several markers
apex(consumption, aes(date, value, group = type), "spline") %>%
  add_event_marker(
    when = c("2020-01-02", "2020-01-06", "2020-01-13",
            "2020-01-22", "2020-01-28", "2020-02-06",
            "2020-02-13", "2020-02-19", "2020-02-27"),
    y = c(1545, 1659, 1614,
          1805, 1637, 1636,
          1597, 1547, 1631),
    size = 10,
    color = "firebrick"
  )
```

`add_point`*Add an annotation point*

Description

Add an annotation point

Usage

```
add_point(
  ax,
  x,
  y,
  size = 5,
  color = "#000",
  fill = "#FFF",
```

```

width = 2,
shape = "circle",
radius = 2,
label = NULL,
...
)

```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
x	Coordinate(s) on the x-axis.
y	Coordinate(s) on the y-axis.
size	Size of the marker.
color	Stroke Color of the marker point.
fill	Fill Color of the marker point.
width	Stroke Size of the marker point.
shape	Shape of the marker: "circle" or "square".
radius	Radius of the marker (applies to square shape).
label	Add a label to the shade, use a character or see <code>label</code> for more controls.
...	Additional arguments, see https://apexcharts.com/docs/options/annotations/ for possible options.

Value

An `apexchart()` htmlwidget object.

See Also

`add_event_marker` to add a point when x-axis is a datetime.

Examples

```

library(apexcharter)

# On scatter chart
apex(
  data = iris,
  aes(Sepal.Length, Sepal.Width),
  "scatter"
) %>%
  add_point(
    x = mean(iris$Sepal.Length),
    y = mean(iris$Sepal.Width)
  )

# Some options
apex(

```

```
data = iris,
aes(Sepal.Length, Sepal.Width),
"scatter"
) %>%
add_point(
  x = mean(iris$Sepal.Length),
  y = mean(iris$Sepal.Width),
  fill = "firebrick",
  color = "firebrick",
  size = 8,
  label = label(text = "Mean", offsetY = 0)
)

# Several points
clusters <- kmeans(iris[, 1:2], 3)
apex(
  data = iris,
  aes(Sepal.Length, Sepal.Width),
  "scatter"
) %>%
add_point(
  x = clusters$centers[, 1],
  y = clusters$centers[, 2]
)
```

Description

Initialize a chart with three main parameters : data, mapping and type of chart.

Usage

```
apex(
  data,
  mapping,
  type = "column",
  ...,
  auto_update = TRUE,
  synchronize = NULL,
  serie_name = NULL,
  width = NULL,
  height = NULL,
  elementId = NULL
)
```

Arguments

<code>data</code>	Default dataset to use for chart. If not already a <code>data.frame</code> , it will be coerced to with <code>as.data.frame</code> .
<code>mapping</code>	Default list of aesthetic mappings to use for chart
<code>type</code>	Specify the chart type. Available options: "column", "bar", "line", "step", "spline", "area", "area-step", "area-spline", "pie", "donut", "radialBar", "radar", "scatter", "heatmap", "treemap", "timeline".
<code>...</code>	Other arguments passed on to methods. Not currently used.
<code>auto_update</code>	In Shiny application, update existing chart rather than generating new one. Can be TRUE/FALSE or use <code>config_update()</code> for more control.
<code>synchronize</code>	Give a common id to charts to synchronize them (tooltip and zoom).
<code>serie_name</code>	Name for the serie displayed in tooltip, only used for single serie.
<code>width, height</code>	A numeric input in pixels.
<code>elementId</code>	Use an explicit element ID for the widget.

Value

An `apexchart()` `htmlwidget` object.

Examples

```
library(ggplot2)
library(apexcharter)

# make a barchart with a frequency table
data("mpg", package = "ggplot2")
apex(mpg, aes(manufacturer), type = "bar")

# timeseries
data("economics", package = "ggplot2")
apex(
  data = economics,
  mapping = aes(x = date, y = uempmed),
  type = "line"
)

# you can add option to apex result :
apex(
  data = economics,
  mapping = aes(x = date, y = uempmed),
  type = "line"
) %>%
  ax_stroke(width = 1)

# with group variable
data("economics_long", package = "ggplot2")
```

```

apex(
  data = economics_long,
  mapping = aes(x = date, y = value01, group = variable),
  type = "line"
)

```

apex-facets

Facets for ApexCharts

Description

Create matrix of charts by row and column faceting variable (`ax_facet_grid`), or by specified number of row and column for faceting variable(s) (`ax_facet_wrap`).

Usage

```

ax_facet_wrap(
  ax,
  facets,
  nrow = NULL,
  ncol = NULL,
  scales = c("fixed", "free", "free_y", "free_x"),
  labeller = label_value,
  chart_height = "300px",
  grid_width = "100%"
)

```

```

ax_facet_grid(
  ax,
  rows = NULL,
  cols = NULL,
  scales = c("fixed", "free", "free_y", "free_x"),
  labeller = label_value,
  chart_height = "300px",
  grid_width = "100%"
)

```

Arguments

<code>ax</code>	An apexchart() htmlwidget object.
<code>facets</code>	Variable(s) to use for faceting, wrapped in <code>vars(...)</code> .
<code>nrow</code> , <code>ncol</code>	Number of row and column in output matrix.
<code>scales</code>	Should scales be fixed ("fixed", the default), free ("free"), or free in one dimension ("free_x", "free_y")?
<code>labeller</code>	A function with one argument containing for each facet the value of the faceting variable.

<code>chart_height</code>	Individual chart height, ignored if an height is defined in <code>apex()</code> or <code>apexcharter()</code> .
<code>grid_width</code>	Total width for the grid, regardless of the number of column.
<code>rows, cols</code>	A set of variables or expressions quoted by <code>vars()</code> and defining faceting groups on the rows or columns dimension.

Value

An `apexchart()` `htmlwidget` object with an additional class `"apex_facet"`.

Warning

To properly render in Shiny applications, use `apexfacetOutput()` (in UI) and `renderApexfacet()` (in Server).

Examples

```
### Wrap -----

if (interactive()) {
  library(apexcharter)

  # Scatter ----

  data("mpg", package = "ggplot2")

  # Create facets
  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_facet_wrap(vars(drv))

  # Change number of columns
  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_facet_wrap(vars(drv), ncol = 2)

  # Free axis
  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_facet_wrap(vars(drv), ncol = 2, scales = "free")

  # labels
  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_facet_wrap(
      vars(drv), ncol = 2,
      labeller = function(x) {
        switch(
          x,
          "f" = "front-wheel drive",
          "r" = "rear wheel drive",
          "4" = "4wd"
        )
      }
    )

  # Title and subtitle are treated as global
```



```

apex(mpg, aes(displ, cty), type = "scatter") %>%
  ax_labs(
    title = "Facet wrap example",
    subtitle = "mpg data from ggplot2"
  ) %>%
  ax_facet_wrap(vars(drv), ncol = 2)

# Multiple variables
apex(mpg, aes(displ, cty), type = "scatter") %>%
  ax_facet_wrap(vars(year, drv))

apex(mpg, aes(displ, cty), type = "scatter") %>%
  ax_facet_wrap(vars(year, drv), ncol = 2, nrow = 3)

apex(mpg, aes(displ, cty), type = "scatter") %>%
  ax_chart(toolbar = list(show = FALSE)) %>%
  ax_facet_wrap(
    vars(year, drv),
    labeller = function(x) {
      paste(x, collapse = " / ")
    }
  )

# Lines ----

data("unhcr_ts")
refugees <- unhcr_ts %>%
  subset(population_type == "Refugees (incl. refugee-like situations)") %>%
  transform(date = as.Date(paste0(year, "-01-01")))

apex(refugees, aes(date, n), type = "line") %>%
  ax_yaxis(tickAmount = 5) %>%
  ax_facet_wrap(vars(continent_origin))

# Free y-axis and synchronize
apex(refugees, aes(date, n), type = "line", synchronize = "my-id") %>%
  ax_yaxis(tickAmount = 5) %>%
  ax_xaxis(tooltip = list(enabled = FALSE)) %>%
  ax_tooltip(x = list(format = "yyyy")) %>%
  ax_facet_wrap(vars(continent_origin), scales = "free_y")

# Bars ----

data("unhcr_ts")
refugees <- unhcr_ts %>%

```

```

subset(year == 2017)

apex(refugees, aes(continent_origin, n), type = "column") %>%
  ax_yaxis(
    labels = list(
      formatter = format_num("~s")
    ),
    tickAmount = 5
  ) %>%
  ax_facet_wrap(vars(population_type), ncol = 2)
}

### Grid -----
if (interactive()) {
  library(apexcharter)

  # Scatter ----

  data("mpg", package = "ggplot2")

  # Only rows
  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_facet_grid(rows = vars(drv), chart_height = "200px")

  # Only cols
  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_facet_grid(cols = vars(year))

  # Rows and Cols
  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_facet_grid(rows = vars(drv), cols = vars(year))

  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_chart(toolbar = list(show = FALSE)) %>%
    ax_facet_grid(vars(drv), vars(cyl))

  # Labels
  apex(mpg, aes(displ, cty), type = "scatter") %>%
    ax_facet_grid(
      vars(drv),
      labeller = function(x) {
        switch(
          x,
          "f" = "front-wheel drive",
          "r" = "rear wheel drive",
          "4" = "4wd"
        )
      }
    )
}

```

```

# Title and subtitle are treated as global
apex(mpg, aes(displ, cty), type = "scatter") %>%
  ax_labs(
    title = "Facet grid example",
    subtitle = "mpg data from ggplot2"
  ) %>%
  ax_facet_grid(rows = vars(drv), cols = vars(year))
}

```

apexchart

Create an ApexCharts widget

Description

Create an ApexCharts widget

Usage

```

apexchart(
  ax_opts = list(),
  auto_update = TRUE,
  width = NULL,
  height = NULL,
  elementId = NULL
)

```

Arguments

<code>ax_opts</code>	A list in JSON format with chart parameters.
<code>auto_update</code>	In Shiny application, update existing chart rather than generating new one. Can be TRUE/FALSE or use <code>config_update()</code> for more control.
<code>width, height</code>	A numeric input in pixels.
<code>elementId</code>	Use an explicit element ID for the widget.

Value

An `apexchart()` `htmlwidget` object.

See Also

For quickly create a chart, see `apex()`.

Examples

```
library(apexcharter)

# Use raw API by passing a list of
# parameters to the function

apexchart(ax_opts = list(
  chart = list(
    type = "bar"
  ),
  series = list(list(
    name = "Example",
    data = sample(1:100, 5)
  )),
  xaxis = list(
    categories = LETTERS[1:5]
  )
))

# Or use apexchart() to initialize the chart
# before passing parameters

apexchart() %>%
  ax_chart(type = "bar") %>%
  ax_series(
    list(
      name = "Example",
      data = sample(1:100, 5)
    )
  ) %>%
  ax_xaxis(
    categories = LETTERS[1:5]
  )
```

apexcharter-exports *apexcharter exported operators and S3 methods*

Description

The following functions are imported and then re-exported from the apexcharter package to avoid listing the magrittr as Depends of apexcharter

Description

Output and render functions for using apexcharter within Shiny applications and interactive Rmd documents.

Usage

```
apexchartOutput(outputId, width = "100%", height = "400px")
renderApexchart(expr, env = parent.frame(), quoted = FALSE)
sparkBoxOutput(outputId, width = "100%", height = "160px")
renderSparkBox(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	Output variable to read from.
width, height	Must be a valid CSS unit (like 100%, 400px, auto) or a number, which will be coerced to a string and have px appended.
expr	An expression that generates a calendar
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

Value

Output element that can be included in UI. Render function to create output in server.

Note

To render a chart with facets (using [ax_facet_wrap\(\)](#) or [ax_facet_grid\(\)](#)) in Shiny, see [apexfacetOutput\(\)](#) (in UI) and [renderApexfacet\(\)](#) (in Server).

Examples

```
if (interactive()) {
  library(shiny)
  library(apexcharter)

  ui <- fluidPage(
    fluidRow(
      column(
        width = 8, offset = 2,
```

```

      tags$h2("Apexchart in Shiny"),
      actionButton("redraw", "Redraw chart"),
      apexchartOutput("chart")
    )
  )
)

server <- function(input, output, session) {

  output$chart <- renderApexchart({
    input$redraw
    apexchart() %>%
      ax_chart(type = "bar") %>%
      ax_series(
        list(
          name = "Example",
          data = sample(1:100, 5)
        )
      ) %>%
      ax_xaxis(
        categories = LETTERS[1:5]
      )
  })

}

shinyApp(ui, server)
}

```

apexcharter-shiny-facets

Shiny bindings for faceting with apexcharter

Description

Output and render functions for using apexcharter faceting within Shiny applications and interactive Rmd documents.

Usage

```
apexfacetOutput(outputId)
```

```
renderApexfacet(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
expr	An expression that generates a apexcharter facet with ax_facet_wrap() or ax_facet_grid() .

env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

Value

An Apexcharts output that can be included in the application UI.

See Also

[ax_facet_wrap\(\)](#), [ax_facet_grid\(\)](#)

Examples

```
library(shiny)
library(apexcharter)

data("unhcr_ts")
refugees <- unhcr_ts %>%
  subset(
    population_type == "Refugees (incl. refugee-like situations)"
  ) %>%
  transform(date = as.Date(paste0(year, "-01-01")))

ui <- fluidPage(
  tags$h2("Apexcharts Facets Example"),
  apexfacetOutput("myfacet")
)

server <- function(input, output, session) {
  output$myfacet <- renderApexfacet({
    apex(refugees, aes(date, n), type = "column") %>%
      ax_yaxis(tickAmount = 5) %>%
      ax_facet_wrap(
        vars(continent_origin),
        scales = "free"
      )
  })
}

if (interactive())
  shinyApp(ui, server)
```

apexcharter-shiny-grid

Shiny bindings for grid with apexcharter

Description

Output and render functions for using apexcharter grid within Shiny applications and interactive Rmd documents.

Usage

```
apexgridOutput(outputId)
```

```
renderApexgrid(expr, env = parent.frame(), quoted = FALSE)
```

Arguments

outputId	output variable to read from
expr	An expression that generates a apexcharter grid.
env	The environment in which to evaluate expr.
quoted	Is expr a quoted expression (with quote())? This is useful if you want to save an expression in a variable.

Value

An Apexcharts output that can be included in the application UI.

Examples

```
library(shiny)
library(apexcharter)

ui <- fluidPage(

  tags$h2("Apexcharts Grid Example"),

  apexgridOutput("myfacet")

)

server <- function(input, output, session) {

  output$myfacet <- renderApexgrid({
    a1 <- apex(mpg, aes(manufacturer), type = "bar")
    a2 <- apex(mpg, aes(trans), type = "column")
    a3 <- apex(mpg, aes(drv), type = "pie")
  })
}
```



```

    apex_grid(
      a1, a2, a3,
      grid_area = c("1 / 1 / 3 / 2", "1 / 2 / 2 / 4", "2 / 2 / 3 / 4"),
      ncol = 3,
      nrow = 2,
      height = "600px"
    )
  })
}

if (interactive())
  shinyApp(ui, server)

```

apexchartProxy	<i>Proxy for apexchart</i>
----------------	----------------------------

Description

Allow to update a chart in Shiny application.

Usage

```
apexchartProxy(shinyId, session = shiny::getDefaultReactiveDomain())
```

Arguments

shinyId	single-element character vector indicating the output ID of the chart to modify (if invoked from a Shiny module, the namespace will be added automatically)
session	the Shiny session object to which the chart belongs; usually the default value will suffice

apex_grid	<i>Create a grid of ApexCharts</i>
-----------	------------------------------------

Description

Create a grid of ApexCharts

Usage

```
apex_grid(
  ...,
  nrow = NULL,
  ncol = NULL,
  row_gap = "10px",
  col_gap = "0px",
  grid_area = NULL,
  height = NULL,
  width = NULL,
  .list = NULL
)
```

Arguments

...	Several apexcharts htmlwidget objects.
nrow, ncol	Number of rows and columns.
row_gap, col_gap	Gap between rows and columns.
grid_area	Custom grid area to make elements take more than a single cell in grid, see https://cssgrid-generator.netlify.app/ for examples.
height, width	Height and width of the main grid.
.list	A list of apexcharts htmlwidget objects.

Value

Custom apex_grid object.

Note

You have to provide either height for the grid or individual chart height to make it work.

Examples

```
if (interactive()) {
  library(apexcharter)
  data("mpg", package = "ggplot2")

  # Two chart side-by-side
  a1 <- apex(mpg, aes(manufacturer), type = "bar")

  a2 <- apex(mpg, aes(trans), type = "column")

  apex_grid(a1, a2, height = "400px")

  # More complex layout:
  a3 <- apex(mpg, aes(drv), type = "pie")
}
```

```
apex_grid(  
  a1, a2, a3,  
  grid_area = c("1 / 1 / 3 / 2", "1 / 2 / 2 / 4", "2 / 2 / 3 / 4"),  
  ncol = 3, nrow = 2,  
  height = "600px"  
)  
}
```

ax-series

Add data to a chart

Description

Add data to a chart

Usage

```
ax_series(ax, ...)
```

```
ax_series2(ax, 1)
```

Arguments

ax	An apexchart() htmlwidget object.
...	Lists containing data to plot, typically list with two items: name and data.
1	A list.

Value

An [apexchart\(\)](#) htmlwidget object.

Examples

```
# One serie  
apexchart() %>%  
  ax_series(list(  
    name = "rnorm",  
    data = rnorm(10)  
  ))  
  
# Two series  
apexchart() %>%  
  ax_series(  
    list(  
      name = "rnorm 1",  
      data = rnorm(10)  
    ),  
    list(  
      name = "rnorm 2",  
      data = rnorm(10)  
    )  
  )
```

```
        name = "rnorm 2",
        data = rnorm(10)
    )
)
```

ax_annotations

Annotations properties

Description

Annotations properties

Usage

```
ax_annotations(  
  ax,  
  position = NULL,  
  yaxis = NULL,  
  xaxis = NULL,  
  points = NULL,  
  ...  
)
```

Arguments

ax	An apexchart() htmlwidget object.
position	Whether to put the annotations behind the charts or in front of it. Available Options: "front" or "back".
yaxis	List of lists.
xaxis	List of lists.
points	List of lists.
...	Additional parameters.

Value

An [apexchart\(\)](#) htmlwidget object.

Note

See <https://apexcharts.com/docs/options/annotations/>.

Examples

```
data("economics", package = "ggplot2")

# Horizontal line
apex(
  data = tail(economics, 200),
  mapping = aes(x = date, y = uempmed),
  type = "line"
) %>%
  ax_annotations(
    yaxis = list(list(
      y = 11.897,
      borderColor = "firebrick",
      opacity = 1,
      label = list(
        text = "Mean uempmed",
        position = "left",
        textAnchor = "start"
      )
    ))
  )

# Vertical line
apex(
  data = tail(economics, 200),
  mapping = aes(x = date, y = uempmed),
  type = "line"
) %>%
  ax_annotations(
    xaxis = list(list(
      x = htmlwidgets::JS("new Date('1 Mar 2007').getTime()"),
      strokeDashArray = 0,
      borderColor = "#775DD0",
      label = list(
        text = "A label",
        borderColor = "#775DD0",
        style = list(
          color = "#fff",
          background = "#775DD0"
        )
      )
    ))
  )

# Vertical range
apex(
  data = tail(economics, 200),
  mapping = aes(x = date, y = uempmed),
  type = "line"
) %>%
```

```

ax_annotations(
  xaxis = list(list(
    x = htmlwidgets::JS("new Date('1 Jan 2009').getTime()"),
    x2 = htmlwidgets::JS("new Date('1 Feb 2010').getTime()"),
    fillColor = "#B3F7CA",
    opacity = 0.4,
    label = list(
      text = "A label",
      borderColor = "#B3F7CA",
      style = list(
        color = "#fff",
        background = "#B3F7CA"
      )
    )
  )
)

# Point annotation
apex(
  data = tail(economics, 200),
  mapping = aes(x = date, y = uempmed),
  type = "line"
) %>%
  ax_annotations(
    points = list(list(
      x = htmlwidgets::JS("new Date('1 Jun 2010').getTime()"),
      y = 25.2,
      marker = list(
        size = 8,
        fillColor = "#fff",
        strokeColor = "red",
        radius = 2
      ),
      label = list(
        text = "Highest",
        offsetY = 0,
        borderColor = "#FF4560",
        style = list(
          color = "#fff",
          background = "#FF4560"
        )
      )
    )
  )
)

```

ax_chart

Chart parameters

Description

Chart parameters

Usage

```

ax_chart(
  ax,
  type = NULL,
  stacked = NULL,
  stackType = NULL,
  defaultLocale = NULL,
  locales = NULL,
  animations = NULL,
  background = NULL,
  foreColor = NULL,
  dropShadow = NULL,
  events = NULL,
  offsetX = NULL,
  offsetY = NULL,
  selection = NULL,
  sparkline = NULL,
  toolbar = NULL,
  zoom = NULL,
  width = NULL,
  height = NULL,
  ...
)

```

Arguments

ax	An apexchart() htmlwidget object.
type	Specify the chart type. Available Options: "bar", "column", "line", "pie", "donut", "radialBar", "scatter", "bubble", "heatmap".
stacked	Logical. Enables stacked option for axis charts.
stackType	When stacked, should the stacking be percentage based or normal stacking. Available options: "normal" or "100%".
defaultLocale	Locale to use : "ca", "cs", "de", "el", "en", "es", "fi", "fr", "he", "hi", "hr", "hy", "id", "it", "ko", "lt", "nb", "nl", "pl", "pt-br", "pt", "ru", "se", "sk", "sl", "th", "tr", "ua".
locales	Array of custom locales parameters.
animations	A list of parameters.
background	Background color for the chart area. If you want to set background with css, use <code>.apexcharts-canvas</code> to set it.
foreColor	Sets the text color for the chart. Defaults to #373d3f.
dropShadow	A list of parameters. See https://apexcharts.com/docs/options/chart/dropshadow/ .
events	See events_opts .
offsetX	Sets the left offset for chart.
offsetY	Sets the top offset for chart.

selection	A list of parameters.
sparkline	List. Sparkline hides all the elements of the charts other than the primary paths. Helps to visualize data in small areas. .
toolbar	A list of parameters. See https://apexcharts.com/docs/options/chart/toolbar/ .
zoom	A list of parameters. See https://apexcharts.com/docs/options/chart/zoom/ .
width	Width of the chart.
height	Height of the chart.
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Examples

```
library(apexcharter)
data("diamonds", package = "ggplot2")

## Stack bar type
# default is dodge
apex(
  data = diamonds,
  mapping = aes(x = cut, fill = color)
)

# stack
apex(
  data = diamonds,
  mapping = aes(x = cut, fill = color)
) %>%
  ax_chart(stacked = TRUE)

# stack filled
apex(
  data = diamonds,
  mapping = aes(x = cut, fill = color)
) %>%
  ax_chart(stacked = TRUE, stackType = "100%")

# Toolbar -----

# Hide the toolbar
apex(
  data = diamonds,
  mapping = aes(x = cut, fill = color)
```



```
) %>%
  ax_chart(toolbar = list(show = FALSE))

# Hide download buttons
data("economics", package = "ggplot2")
apex(
  data = economics,
  mapping = aes(x = date, y = pce),
  type = "line"
) %>%
  ax_chart(
    toolbar = list(tools= list(download = FALSE))
  )

# Zoom -----

# Disable
apex(
  data = economics,
  mapping = aes(x = date, y = pce),
  type = "line"
) %>%
  ax_chart(
    zoom = list(enabled = FALSE)
  )

# Auto-scale Y axis
apex(
  data = economics,
  mapping = aes(x = date, y = pce),
  type = "line"
) %>%
  ax_chart(
    zoom = list(autoScaleYaxis = TRUE)
  )

# Localization -----

# Use included localization config
dat <- data.frame(
  x = Sys.Date() + 1:20,
  y = sample.int(20, 20)
)

# French
apex(dat, aes(x, y), "line") %>%
  ax_chart(defaultLocale = "fr")

# Italian
```

```
apex(dat, aes(x, y), "line") %>%
  ax_chart(defaultLocale = "it")

# Custom config
apex(dat, aes(x, y), "line") %>%
  ax_chart(locales = list(
    list(
      name = "en", # override 'en' locale
      options = list(
        toolbar = list(
          exportToSVG = "GET SVG",
          exportToPNG = "GET PNG"
        )
      )
    )
  ))
```

ax_colors

Colors

Description

Colors

Usage

```
ax_colors(ax, ...)
```

Arguments

ax	An apexchart() htmlwidget object.
...	Colors for the chart's series. When all colors are used, it starts from the beginning.

Value

An [apexchart\(\)](#) htmlwidget object.

Note

See <https://apexcharts.com/docs/options/colors/>

Examples

```
data("diamonds", package = "ggplot2")

# Change default color(s)
apex(
  data = diamonds,
  mapping = aes(x = cut)
) %>%
  ax_colors("#F7D358")

library(scales)
apex(
  data = diamonds,
  mapping = aes(x = cut, fill = color)
) %>%
  ax_colors(brewer_pal(palette = "Set2")(7))
```

ax_colors_manual *Set specific color's series*

Description

Set specific color's series

Usage

```
ax_colors_manual(ax, values)
```

Arguments

ax An `apexchart()` htmlwidget object.
values Named list, names represent data series, values colors to use.

Value

An `apexchart()` htmlwidget object.

Examples

```
## scatter

apex(
  data = mtcars,
  type = "scatter",
  mapping = aes(x = wt, y = mpg, fill = cyl)
) %>%
  ax_colors_manual(list(
    "4" = "steelblue",
```

```

    "6" = "firebrick",
    "8" = "forestgreen"
  ))

# If missing level, colors are recycled
apex(
  data = mtcars,
  type = "scatter",
  mapping = aes(x = wt, y = mpg, fill = cyl)
) %>%
  ax_colors_manual(list(
    "4" = "steelblue",
    "8" = "forestgreen"
  ))

# Ignore levels not present in data
apex(
  data = mtcars,
  type = "scatter",
  mapping = aes(x = wt, y = mpg, fill = cyl)
) %>%
  ax_colors_manual(list(
    "4" = "steelblue",
    "6" = "firebrick",
    "8" = "forestgreen",
    "99" = "yellow"
  ))

## Bar

tab <- table(sample(letters[1:5], 100, TRUE), sample(LETTERS[1:5], 100, TRUE))
dat <- as.data.frame(tab)

apex(
  data = dat,
  type = "column",
  mapping = aes(x = Var1, y = Freq, group = Var2)
) %>%
  ax_colors_manual(list(
    A = "steelblue",
    C = "firebrick",
    D = "forestgreen",
    B = "peachpuff",
    E = "chartreuse"
  ))

```

Description

Labels on data

Usage

```
ax_dataLabels(  
  ax,  
  enabled = NULL,  
  textAnchor = NULL,  
  offsetX = NULL,  
  offsetY = NULL,  
  style = NULL,  
  dropShadow = NULL,  
  formatter = NULL,  
  ...  
)
```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
enabled	To determine whether to show dataLabels or not.
textAnchor	The alignment of text relative to dataLabel's drawing position. Accepted values "start", "middle" or "end".
offsetX	Sets the left offset for dataLabels.
offsetY	Sets the top offset for dataLabels.
style	A list of parameters.
dropShadow	A list of parameters.
formatter	The formatter function takes in a single value and allows you to format the value before displaying
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/datalabels/>

Examples

```
data("diamonds", package = "ggplot2")  
  
# Add data labels  
apex(  
  data = diamonds,  
  mapping = aes(x = cut)
```

```
) %>%
  ax_dataLabels(enabled = TRUE)
```

 ax_fill

Fill property

Description

Fill property

Usage

```
ax_fill(
  ax,
  type = NULL,
  colors = NULL,
  opacity = NULL,
  gradient = NULL,
  image = NULL,
  pattern = NULL,
  ...
)
```

Arguments

ax	An apexchart() htmlwidget object.
type	Whether to fill the paths with solid colors or gradient. Available options: "solid", "gradient", "pattern" or "image".
colors	Colors to fill the svg paths..
opacity	Opacity of the fill attribute.
gradient	A list of parameters.
image	A list of parameters.
pattern	A list of parameters.
...	Additional parameters.

Value

An [apexchart\(\)](#) htmlwidget object.

Note

See <https://apexcharts.com/docs/options/fill/>

Examples

```
data("diamonds", package = "ggplot2")

# Use a pattern to fill bars
apex(
  data = diamonds,
  mapping = aes(x = color, fill = cut)
) %>%
  ax_fill(
    type = "pattern",
    opacity = 1,
    pattern = list(
      style = c("circles", "slantedLines", "verticalLines", "horizontalLines", "squares")
    )
  )

data("economics", package = "ggplot2")

# Customise gradient
apex(
  data = economics,
  mapping = aes(x = date, y = psavert),
  type = "area"
) %>%
  ax_fill(gradient = list(
    enabled = TRUE,
    shadeIntensity = 1,
    inverseColors = FALSE,
    opacityFrom = 0,
    opacityTo = 1,
    stops = c(0, 2000)
  ))
```

ax_grid

Add grids on chart

Description

Add grids on chart

Usage

```
ax_grid(
  ax,
  show = NULL,
  borderColor = NULL,
  strokeDashArray = NULL,
  position = NULL,
```

```

    xaxis = NULL,
    yaxis = NULL,
    row = NULL,
    column = NULL,
    padding = NULL,
    ...
  )

```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
show	Logical. To show or hide grid area (including xaxis / yaxis)
borderColor	Colors of grid borders / lines.
strokeDashArray	Creates dashes in borders of svg path. Higher number creates more space between dashes in the border.
position	Whether to place grid behind chart paths of in front. Available options for position: "front" or "back"
xaxis	A list of parameters.
yaxis	A list of parameters.
row	A list of parameters.
column	A list of parameters.
padding	A list of parameters.
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/grid/>

Examples

```

data("mpg", package = "ggplot2")

# Hide Y-axis and gridlines
apex(
  data = mpg,
  mapping = aes(x = manufacturer)
) %>%
  ax_grid(show = FALSE)

# just grid lines
apex(
  data = mpg,

```



```

    mapping = aes(x = manufacturer)
  ) %>%
    ax_grid(yaxis = list(lines = list(show = FALSE)))

# both x & y
data("economics", package = "ggplot2")
apex(
  data = economics,
  mapping = aes(x = date, y = psavert),
  type = "line"
) %>%
  ax_grid(
    yaxis = list(lines = list(show = TRUE)),
    xaxis = list(lines = list(show = TRUE))
  )

```

ax_labels	<i>Alternative axis labels</i>
-----------	--------------------------------

Description

Alternative axis labels

Usage

```

ax_labels(ax, ...)

ax_labels2(ax, labels)

```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
...	Vector. In Axis Charts (line / column), labels can be set instead of setting <code>xaxis categories</code> option. While, in pie/donut charts, each label corresponds to value in series array.
labels	A vector to use as labels.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/labels/>

Examples

```

apexchart() %>%
  ax_chart(type = "pie") %>%
  ax_series(23, 45, 56) %>%
  ax_labels("A", "B", "C")

# same as
apexchart() %>%
  ax_chart(type = "pie") %>%
  ax_series2(c(23, 45, 56)) %>%
  ax_labels2(c("A", "B", "C"))

```

 ax_labs

Modify axis, legend, and chart labels

Description

Modify axis, legend, and chart labels

Usage

```
ax_labs(ax, title = NULL, subtitle = NULL, x = NULL, y = NULL)
```

Arguments

ax	An <code>apexchart()</code> <code>htmlwidget</code> object.
title	Text for the title.
subtitle	Text for the subtitle.
x	Text for the x-axis label.
y	Text for the y-axis label.

Value

An `apexchart()` `htmlwidget` object.

Examples

```

meteo_paris <- data.frame(
  month = month.name,
  tmax = c(7, 8, 12, 15, 19, 23, 25, 25, 21, 16, 11, 8),
  tmin = c(3, 3, 5, 7, 11, 14, 16, 16, 13, 10, 6, 3)
)

apex(meteo_paris, type = "column", aes(x = month, y = tmin)) %>%
  ax_labs(
    title = "Average minimal temperature in Paris",
    subtitle = "Data from NOAA",
    x = "Month",

```

```

    y = "Temperature (\u00b0C)"
  )

```

 ax_legend

Legend properties

Description

Legend properties

Usage

```

ax_legend(
  ax,
  show = NULL,
  position = NULL,
  showForSingleSeries = NULL,
  showForNullSeries = NULL,
  showForZeroSeries = NULL,
  horizontalAlign = NULL,
  fontSize = NULL,
  textAnchor = NULL,
  offsetY = NULL,
  offsetX = NULL,
  formatter = NULL,
  labels = NULL,
  markers = NULL,
  itemMargin = NULL,
  containerMargin = NULL,
  onItemClick = NULL,
  onItemHover = NULL,
  floating = NULL,
  ...
)

```

Arguments

ax	An apexchart() htmlwidget object.
show	Logical. Whether to show or hide the legend container.
position	Available position options for legend: "top", "right", "bottom", "left".
showForSingleSeries	Show legend even if there is just 1 series.
showForNullSeries	Allows you to hide a particular legend if it's series contains all null values.
showForZeroSeries	Allows you to hide a particular legend if it's series contains all 0 values.

horizontalAlign	Available options for horizontal alignment: "right", "center", "left".
fontSize	Sets the fontSize of legend text elements
textAnchor	The alignment of text relative to legend's drawing position
offsetY	Sets the top offset for legend container.
offsetX	Sets the left offset for legend container.
formatter	JS function. A custom formatter function to append additional text to the legend series names.
labels	List with two items "foreColor" (Custom text color for legend labels) and "useSeriesColors" (Logical, whether to use primary colors or not)
markers	List.
itemMargin	List with two items "horizontal" (Horizontal margin for individual legend item) and "vertical" (Vertical margin for individual legend item).
containerMargin	List with two items "top" (Top margin for the whole legend container) and "left" (Left margin for the whole legend container).
onItemClick	List with item "toggleDataSeries", logical, when clicked on legend item, it will toggle the visibility of the series in chart.
onItemHover	List with item "highlightDataSeries", logical, when hovered on legend item, it will highlight the paths of the hovered series in chart.
floating	Logical. The floating option will take out the legend from the chart area and make it float above the chart.
...	Additional parameters.

Value

An `apexchart()` `htmlwidget` object.

Note

See <https://apexcharts.com/docs/options/legend/>

Examples

```
data("mpg", package = "ggplot2")

# Legend position
apex(
  data = mpg,
  mapping = aes(x = manufacturer, fill = year)
) %>%
  ax_legend(position = "right")

# hide legend
apex(
  data = mpg,
```

```

    mapping = aes(x = manufacturer, fill = year)
  ) %>%
  ax_legend(show = FALSE)

```

 ax_markers

Markers properties

Description

Markers properties

Usage

```

ax_markers(
  ax,
  size = NULL,
  colors = NULL,
  strokeColor = NULL,
  strokeWidth = NULL,
  strokeOpacity = NULL,
  fillOpacity = NULL,
  shape = NULL,
  radius = NULL,
  offsetX = NULL,
  offsetY = NULL,
  hover = NULL,
  ...
)

```

Arguments

ax	An apexchart() htmlwidget object.
size	Numeric. Size of the marker point.
colors	Sets the fill color(s) of the marker point.
strokeColor	Stroke Color of the marker.
strokeWidth	Stroke Size of the marker.
strokeOpacity	Opacity of the border around marker.
fillOpacity	Opacity of the marker fill color.
shape	Shape of the marker. Available Options for shape: "square" or "circle".
radius	Numeric. Radius of the marker (applies to square shape)
offsetX	Numeric. Sets the left offset of the marker.
offsetY	Numeric. Sets the top offset of the marker.
hover	List with item size (Size of the marker when it is active).
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/markers/>

Examples

```
data("economics", package = "ggplot2")

# show points
apex(
  data = tail(economics, 20),
  type = "line",
  mapping = aes(x = date, y = uempmed)
) %>%
  ax_markers(size = 6)
```

ax_nodata

Configuration for charts with no data

Description

Configuration for charts with no data

Usage

```
ax_nodata(
  ax,
  text = "No data",
  align = "center",
  verticalAlign = "middle",
  color = NULL,
  fontSize = NULL,
  fontFamily = NULL,
  offsetX = NULL,
  offsetY = NULL
)
```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
text	The text to display when no-data is available.
align	Horizontal alignment: "left", "center" or "right".
verticalAlign	Vertical alignment: "top", "middle" or "bottom".
color	ForeColor of the text.

fontSize	FontSize of the text.
fontFamily	FontFamily of the text.
offsetX, offsetY	Text offset.

Value

An `apexchart()` htmlwidget object.

Examples

```
empty <- data.frame(
  var1 = character(0),
  var2 = numeric(0)
)
apex(empty, aes(var1, var2), "column") %>%
  ax_nodata(
    text = "Sorry no data to visualize",
    fontSize = "30px"
  )
```

ax_plotOptions	<i>Specific options for chart</i>
----------------	-----------------------------------

Description

Specific options for chart

Usage

```
ax_plotOptions(
  ax,
  bar = NULL,
  heatmap = NULL,
  radialBar = NULL,
  pie = NULL,
  bubble = NULL,
  ...
)
```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
bar	See <code>bar_opts</code> .
heatmap	See <code>heatmap_opts</code> .
radialBar	See <code>radialBar_opts</code> .
pie	See <code>pie_opts</code> .
bubble	See <code>bubble_opts</code> .
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Examples

```
data("diamonds", package = "ggplot2")

# Stack bar type
apex(
  data = diamonds,
  mapping = aes(x = cut)
) %>%
  ax_plotOptions(
    bar = bar_opts(endingShape = "rounded", columnWidth = "10%")
  )

# Pie
apex(
  data = diamonds,
  mapping = aes(x = cut),
  type = "pie"
) %>%
  ax_plotOptions(
    pie = pie_opts(customScale = 0.5)
  )

# Radial
apexchart() %>%
  ax_chart(type = "radialBar") %>%
  ax_plotOptions(
    radialBar = radialBar_opts(
      hollow = list(size = "70%")
    )
  ) %>%
  ax_series(70) %>%
  ax_labels("Indicator")
```

ax_proxy_options

Proxy for updating options

Description

Allows you to update the configuration object.

Usage

```
ax_proxy_options(proxy, options)
```


Arguments

proxy A apexchartProxy htmlwidget object.
options New options to set.

Examples

```
if (interactive()) {
  library(shiny)

  ui <- fluidPage(
    fluidRow(
      column(
        width = 8, offset = 2,
        tags$h2("Update options"),
        apexchartOutput(outputId = "chart"),
        checkboxInput(
          inputId = "show_label_xaxis",
          label = "Show x-axis labels"
        ),
        textInput(
          inputId = "yaxis_title",
          label = "Y-axis title"
        )
      )
    )
  )
  server <- function(input, output, session) {

    output$chart <- renderApexchart({
      apexchart() %>%
        ax_chart(type = "bar") %>%
        ax_series(list(
          name = "Example",
          data = c(23, 43, 76, 31)
        )) %>%
        ax_xaxis(
          categories = c("Label A", "Label B",
            "Label C", "Label D")
        )
    })

    observe({
      apexchartProxy("chart") %>%
        ax_proxy_options(list(
          xaxis = list(
            labels = list(show = input$show_label_xaxis)
          ),
          yaxis = list(
            title = list(text = input$yaxis_title)
          )
        ))
    })
  }
}
```

```
    })  
  }  
  shinyApp(ui, server)  
}
```

ax_proxy_series *Proxy for updating series.*

Description

Allows you to update the series array overriding the existing one.

Usage

```
ax_proxy_series(proxy, newSeries, animate = TRUE)
```

Arguments

proxy	A apexchartProxy htmlwidget object.
newSeries	The series array to override the existing one.
animate	Should the chart animate on re-rendering.

Examples

```
if (interactive()) {  
  library(shiny)  
  
  ui <- fluidPage(  
    fluidRow(  
      column(  
        width = 8, offset = 2,  
        tags$h2("Real time chart"),  
        apexchartOutput(outputId = "chart")  
      )  
    )  
  )  
  
  server <- function(input, output, session) {  
  
    rv <- reactiveValues()  
    rv$df <- data.frame(  
      date = Sys.Date() + 1:20,  
      values = sample(10:90, 20, TRUE)  
    )  
  }  
}
```

```

observe({
  invalidateLater(1000, session)
  df <- isolate(rv$df)
  # Append new line of data
  df <- rbind(
    df, data.frame(
      date = df$date[length(df$date)] + 1,
      values = sample(10:90, 1, TRUE)
    )
  )
  rv$df <- df
})

output$chart <- renderApexchart({
  # Generate chart once
  apex(isolate(rv$df), aes(date, values), "spline") %>%
    ax_xaxis(
      range = 10 * 24 * 60 * 60 * 1000
      # Fixed range for x-axis : 10 days
      # days*hours*minutes*seconds*milliseconds
    )
})

observe({
  # Update chart to add new data
  apexchartProxy("chart") %>%
    ax_proxy_series(
      parse_df(rv$df),
      T
    )
})

}

shinyApp(ui, server)
}

```

ax_responsive

Responsive options

Description

Responsive options

Usage

```
ax_responsive(ax, ...)
```

Arguments

ax An `apexchart()` htmlwidget object.
 ... Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/responsive/>

Examples

```
data("mpg", package = "ggplot2")

# Open in browser and resize window
apex(
  data = mpg,
  mapping = aes(x = manufacturer, fill = year),
  type = "bar"
) %>%
  ax_legend(position = "right") %>%
  ax_responsive(
    list(
      breakpoint = 1000,
      options = list(
        plotOptions = list(
          bar = list(
            horizontal = FALSE
          )
        ),
        legend = list(
          position = "bottom"
        )
      )
    )
  )
)
```

 ax_states

Charts' states

Description

Charts' states

Usage

```
ax_states(ax, normal = NULL, hover = NULL, active = NULL, ...)
```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
normal	A list of parameters.
hover	A list of parameters.
active	A list of parameters.
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/states/>

Examples

```
data("mpg", package = "ggplot2")

# Inverse effect on hover
apex(
  data = mpg,
  mapping = aes(x = manufacturer),
  type = "bar"
) %>%
  ax_states(
    hover = list(
      filter = list(
        type = "darken"
      )
    )
  )
)
```

ax_stroke

Stroke properties

Description

Stroke properties

Usage

```
ax_stroke(
  ax,
  show = NULL,
  curve = NULL,
  lineCap = NULL,
```

```

width = NULL,
colors = NULL,
dashArray = NULL,
...
)

```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
show	Logical. To show or hide path-stroke / line
curve	In line / area charts, whether to draw smooth lines or straight lines. Available Options: "smooth" (connects the points in a curve fashion. Also known as spline) and "straight" (connect the points in straight lines.).
lineCap	For setting the starting and ending points of stroke. Available Options: "butt" (ends the stroke with a 90-degree angle), "square" (similar to butt except that it extends the stroke beyond the length of the path) and "round" (ends the path-stroke with a radius that smooths out the start and end points)
width	Sets the width of border for svg path.
colors	Colors to fill the border for paths.
dashArray	Creates dashes in borders of svg path. Higher number creates more space between dashes in the border.
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/stroke/>

Examples

```

data("economics", package = "ggplot2")
apex(
  data = economics,
  mapping = aes(x = date, y = uempmed),
  type = "line"
) %>%
  ax_stroke(
    width = 1,
    dashArray = 4
  )

data("economics_long", package = "ggplot2")
apex(
  data = economics_long,
  mapping = aes(x = date, y = value01, group = variable),
  type = "line"
)

```

```

) %>%
  ax_stroke(
    width = c(1, 2, 3, 4, 5),
    dashArray = c(1, 2, 3, 4, 5)
  )

```

 ax_subtitle

Chart's subtitle

Description

Chart's subtitle

Usage

```

ax_subtitle(
  ax,
  text = NULL,
  align = NULL,
  margin = NULL,
  offsetX = NULL,
  offsetY = NULL,
  floating = NULL,
  style = NULL,
  ...
)

```

Arguments

ax	An apexchart() htmlwidget object.
text	Text to display as a subtitle of chart.
align	Alignment of subtitle relative to chart area. Possible Options: "left", "center" and "right".
margin	Numeric. Vertical spacing around the subtitle text.
offsetX	Numeric. Sets the left offset for subtitle text.
offsetY	Numeric. Sets the top offset for subtitle text
floating	Logical. The floating option will take out the subtitle text from the chart area and make it float on top of the chart.
style	List with two items: <code>fontSize</code> (Font Size of the subtitle text) and <code>color</code> (Fore color of the subtitle text).
...	Additional parameters.

Value

An [apexchart\(\)](#) htmlwidget object.

Note

See <https://apexcharts.com/docs/options/subtitle/>

Examples

```
data("economics", package = "ggplot2")
apex(
  data = economics,
  mapping = aes(x = date, y = uempmed),
  type = "line"
) %>%
  ax_title(
    text = "Median duration of unemployment"
  ) %>%
  ax_subtitle(
    text = "in weeks"
  )
```

 ax_theme

Theme for charts

Description

Theme for charts

Usage

```
ax_theme(ax, mode = c("light", "dark"), palette = NULL, monochrome = NULL, ...)
```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
mode	use light or dark theme.
palette	Character. Available palettes: "palette1" to "palette10".
monochrome	A list of parameters.
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/theme/>

Examples

```
data("mpg", package = "ggplot2")
data("diamonds", package = "ggplot2")

# Dark mode
apex(
  data = mpg,
  mapping = aes(x = manufacturer)
) %>%
  ax_theme(mode = "dark")

# Use predefined palette (1 to 10)
apex(
  data = diamonds,
  mapping = aes(x = color, fill = cut)
) %>%
  ax_theme(palette = "palette2")

# monochrome palette
apex(
  data = diamonds,
  mapping = aes(x = color, fill = cut)
) %>%
  ax_theme(monochrome = list(enabled = TRUE, color = "#0B6121"))
```

ax_title

Chart's title

Description

Chart's title

Usage

```
ax_title(
  ax,
  text = NULL,
  align = NULL,
  margin = NULL,
  offsetX = NULL,
  offsetY = NULL,
  floating = NULL,
  style = NULL,
  ...
)
```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
text	Text to display as a title of chart.
align	Alignment of subtitle relative to chart area. Possible Options: "left", "center" and "right".
margin	Numeric. Vertical spacing around the title text.
offsetX	Numeric. Sets the left offset for subtitle text.
offsetY	Numeric. Sets the top offset for subtitle text
floating	Logical. The floating option will take out the subtitle text from the chart area and make it float on top of the chart.
style	List with two items: <code>fontSize</code> (Font Size of the title text) and <code>color</code> (Fore color of the title text).
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/title/>

Examples

```
data("economics", package = "ggplot2")
apex(
  data = economics,
  mapping = aes(x = date, y = uempmed),
  type = "line"
) %>%
  ax_title(
    text = "Median duration of unemployment, in weeks"
  )
```

ax_tooltip

Tooltip options

Description

Tooltip options

Usage

```

ax_tooltip(
  ax,
  enabled = NULL,
  shared = NULL,
  followCursor = NULL,
  intersect = NULL,
  inverseOrder = NULL,
  custom = NULL,
  fillSeriesColor = NULL,
  onDatasetHover = NULL,
  theme = NULL,
  x = NULL,
  y = NULL,
  z = NULL,
  marker = NULL,
  items = NULL,
  fixed = NULL,
  ...
)

```

Arguments

ax	An apexchart() htmlwidget object.
enabled	Logical. Show tooltip when user hovers over chart area.
shared	Logical. When having multiple series, show a shared tooltip.
followCursor	Logical. Follow user's cursor position instead of putting tooltip on actual data points.
intersect	Logical. Show tooltip only when user hovers exactly over datapoint.
inverseOrder	Logical. In multiple series, when having shared tooltip, inverse the order of series (for better comparison in stacked charts).
custom	JS function. Draw a custom html tooltip instead of the default one based on the values provided in the function arguments.
fillSeriesColor	Logical. When enabled, fill the tooltip background with the corresponding series color.
onDatasetHover	A list of parameters.
theme	A list of parameters.
x	A list of parameters.
y	A list of parameters.
z	A list of parameters.
marker	A list of parameters.
items	A list of parameters.
fixed	A list of parameters.
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/tooltip/>

Examples

```
data("mpg", package = "ggplot2")

# Hide tooltip
apex(
  data = mpg,
  mapping = aes(x = manufacturer, fill = year)
) %>%
  ax_tooltip(enabled = FALSE)

# Share between series
apex(
  data = mpg,
  mapping = aes(x = manufacturer, fill = year)
) %>%
  ax_tooltip(shared = TRUE)

# Fixed tooltip
data("economics", package = "ggplot2")
apex(
  data = economics,
  mapping = aes(x = date, y = psavert),
  type = "line"
) %>%
  ax_tooltip(
    fixed = list(enabled = TRUE, position = "topLeft")
  )
```

ax_xaxis

X-axis options

Description

X-axis options

Usage

```
ax_xaxis(
  ax,
  type = NULL,
  categories = NULL,
```

```

    labels = NULL,
    axisBorder = NULL,
    axisTicks = NULL,
    tickAmount = NULL,
    min = NULL,
    max = NULL,
    range = NULL,
    floating = NULL,
    position = NULL,
    title = NULL,
    crosshairs = NULL,
    tooltip = NULL,
    ...
)

```

Arguments

ax	An apexchart() htmlwidget object.
type	Character. Available Options : "categories" and "datetime".
categories	Categories are labels which are displayed on the x-axis.
labels	A list of parameters.
axisBorder	A list of parameters.
axisTicks	A list of parameters.
tickAmount	Number of Tick Intervals to show.
min	Lowest number to be set for the x-axis. The graph drawing beyond this number will be clipped off.
max	Highest number to be set for the x-axis. The graph drawing beyond this number will be clipped off.
range	Range takes the max value of x-axis, subtracts the provided range value and gets the min value based on that. So, technically it helps to keep the same range when min and max values gets updated dynamically.
floating	Logical. Floating takes x-axis is taken out of normal flow and places x-axis on svg element directly, similar to an absolutely positioned element. Set the offsetX and offsetY then to adjust the position manually
position	Setting this option allows you to change the x-axis position. Available options: "top" and "bottom".
title	A list of parameters.
crosshairs	A list of parameters.
tooltip	A list of parameters.
...	Additional parameters.

Value

An [apexchart\(\)](#) htmlwidget object.

Note

See <https://apexcharts.com/docs/options/xaxis/>

Examples

```
data("mpg", package = "ggplot2")

# X axis title
apex(
  data = mpg,
  mapping = aes(x = manufacturer)
) %>%
  ax_xaxis(title = list(text = "Car's manufacturer"))

# force labels to rotate and increase height
apex(
  data = mpg,
  mapping = aes(x = manufacturer)
) %>%
  ax_xaxis(labels = list(rotateAlways = TRUE, maxHeight = 180))

# force to not rotate
apex(
  data = mpg,
  mapping = aes(x = manufacturer)
) %>%
  ax_xaxis(labels = list(rotate = 0, trim = FALSE))

data("economics", package = "ggplot2")

# Custom crosshair
apex(
  data = tail(economics, 50),
  mapping = aes(x = date, y = psavert),
  type = "line"
) %>%
  ax_xaxis(
    crosshairs = list(
      opacity = 1,
      width = 2,
      fill = list(color = "red"),
      stroke = list(width = 0)
    )
  )

# Date format (zoom to see changes)
apex(
  data = tail(economics, 150),
  mapping = aes(x = date, y = psavert),
  type = "line"
```

```

) %>%
  ax_xaxis(
    labels = list(
      dateTimeFormatter = list(
        year = "yyyy-MM",
        month = "yyyy-MM-dd",
        day = "yyyy-MM-dd HH:mm"
      )
    )
  )
)

```

ax_yaxis

Y-axis options

Description

Y-axis options

Usage

```

ax_yaxis(
  ax,
  opposite = NULL,
  tickAmount = NULL,
  max = NULL,
  min = NULL,
  floating = NULL,
  labels = NULL,
  axisBorder = NULL,
  axisTicks = NULL,
  title = NULL,
  tooltip = NULL,
  crosshairs = NULL,
  ...
)

```

Arguments

ax	An apexchart() htmlwidget object.
opposite	Logical. When enabled, will draw the yaxis on the right side of the chart.
tickAmount	Number of Tick Intervals to show.
max	Lowest number to be set for the y-axis. The graph drawing beyond this number will be clipped off.
min	Highest number to be set for the y-axis. The graph drawing beyond this number will be clipped off.

floating	Logical. Floating takes y-axis is taken out of normal flow and places y-axis on svg element directly, similar to an absolutely positioned element. Set the offsetX and offsetY then to adjust the position manually
labels	A list of parameters.
axisBorder	A list of parameters.
axisTicks	A list of parameters.
title	A list of parameters.
tooltip	A list of parameters.
crosshairs	A list of parameters.
...	Additional parameters.

Value

An `apexchart()` htmlwidget object.

Note

See <https://apexcharts.com/docs/options/yaxis/>

Examples

```
data("economics_long", package = "ggplot2")
apex(
  data = economics_long,
  mapping = aes(x = date, y = value01, group = variable),
  type = "line"
) %>%
  ax_yaxis(
    decimalsInFloat = 2, title = list(text = "Rescaled to [0,1]")
  )

# Format tick labels
temperature <- data.frame(
  month = head(month.name),
  tp = c(4, -2, 2, 7, 11, 14)
)
apex(temperature, aes(month, tp), "line") %>%
  ax_yaxis(
    labels = list(
      formatter = htmlwidgets::JS("function(value) {return value + '\u00b0C';}")
    )
  )
)
```

`ax_yaxis2`*Secondary Y-axis options*

Description

Secondary Y-axis options

Usage`ax_yaxis2(ax, ...)`**Arguments**

`ax` An `apexchart()` htmlwidget object.
`...` See arguments from `ax_yaxis`.

ValueAn `apexchart()` htmlwidget object.**Examples**

```
library(apexcharter)
data("economics_long", package = "ggplot2")

eco <- economics_long %>%
  subset(variable %in% c("pce", "pop")) %>%
  transform(value = round(value))

# add second y-axis
apex(eco, aes(x = date, y = value, color = variable), type = "line") %>%
  ax_yaxis(title = list(text = "Pce")) %>%
  ax_yaxis2(opposite = TRUE, title = list(text = "Pop"))

# Customize axis a bit more
apex(eco, aes(x = date, y = value, color = variable), type = "line") %>%
  ax_yaxis(
    title = list(text = "Pce"),
    axisBorder = list(
      show = TRUE,
      color = "#008FFB"
    ),
    labels = list(
      style = list(
        colors = "#008FFB"
      )
    ),
    tooltip = list(
      enabled = TRUE
    )
  )
```

```

    )
) %>%
ax_yaxis2(
  opposite = TRUE,
  min = 160000,
  forceNiceScale = TRUE,
  title = list(text = "Pop"),
  axisBorder = list(
    show = TRUE,
    color = "#00E396"
  ),
  labels = list(
    style = list(
      colors = "#00E396"
    )
  ),
  tooltip = list(
    enabled = TRUE
  )
)
)

```

bar_opts

Bar options

Description

Use these options in [ax_plotOptions](#).

Usage

```

bar_opts(
  horizontal = NULL,
  endingShape = NULL,
  columnWidth = NULL,
  barHeight = NULL,
  distributed = NULL,
  colors = NULL,
  dataLabels = NULL,
  ...
)

```

Arguments

horizontal	Logical. This option will turn a column chart into a horizontal bar chart.
endingShape	Available Options: "flat" or "rounded".
columnWidth	In column charts, columnWidth is the percentage of the available width in the grid-rect.

barHeight	In horizontal bar charts, barHeight is the percentage of the available height in the grid-rect.
distributed	Logical. Turn this option to make the bars discrete. Each value indicates one bar per series.
colors	A list of parameters.
dataLabels	List with fields position (available options: "top", "center" or "bottom")
...	Additional parameters.

Value

A list of options that can be used in `ax_plotOptions`.

Note

See <https://apexcharts.com/docs/options/plotoptions/bar/>.

Examples

```
data("mpg", package = "ggplot2")

apex(mpg, aes(manufacturer)) %>%
  ax_plotOptions(
    bar = bar_opts(
      endingShape = "rounded",
      columnWidth = 100,
      distributed = TRUE
    )
  )
```

 bubble_opts

Bubble options

Description

Use these options in `ax_plotOptions`.

Usage

```
bubble_opts(minBubbleRadius, maxBubbleRadius, ...)
```

Arguments

<code>minBubbleRadius</code>	Minimum radius size of a bubble. If a bubble value is too small to be displayed, this size will be used.
<code>maxBubbleRadius</code>	Maximum radius size of a bubble. If a bubble value is too large to cover the chart, this size will be used.
<code>...</code>	Additional parameters.

Value

A list of options that can be used in `ax_plotOptions`.

Note

See <https://apexcharts.com/docs/options/plotoptions/bubble/>.

Examples

```
apex(
  data = mtcars,
  type = "scatter",
  mapping = aes(x = wt, y = mpg, z = qsec)
) %>%
  ax_plotOptions(
    bubble = bubble_opts(
      minBubbleRadius = 1,
      maxBubbleRadius = 20
    )
  )
```

candles

Candlestick demo data

Description

Candlestick demo data

Usage

candles

Format

A data frame with 60 observations and the following 5 variables:

datetime Timestamp.

open Open value.

high Highest value.

low Lowest value.

close Close value.

Source

Apexcharts (<https://apexcharts.com/javascript-chart-demos/candlestick-charts/basic/>)

climate_paris

Paris Climate

Description

Average temperature and precipitation in Paris for the period 1971-2000.

Usage

climate_paris

Format

A data frame with 12 observations and the following 3 variables:

month Month

temperature Temperature (in degree celsius).

precipitation Precipitation (in mm).

Source

Wikipedia (https://fr.wikipedia.org/wiki/Climat_de_Paris)

config_update *Configuration for auto update*

Description

Configuration for auto update

Usage

```
config_update(  
  series_animate = TRUE,  
  update_options = FALSE,  
  options_animate = TRUE,  
  options_redrawPaths = TRUE,  
  update_synced_charts = FALSE  
)
```

Arguments

`series_animate` Should the chart animate on re-rendering.

`update_options` Update or not global options for chart.

`options_animate` Should the chart animate on re-rendering.

`options_redrawPaths`
When the chart is re-rendered, should it draw from the existing paths or completely redraw the chart paths from the beginning. By default, the chart is re-rendered from the existing paths.

`update_synced_charts`
All the charts in a group should also update when one chart in a group is updated.

consumption *Electricity consumption and forecasting*

Description

Electricity consumption per day in France for january and february of year 2020.

Usage

```
consumption
```

Format

A data frame with 120 observations and the following 3 variables:

date date.

type Type of data : realized or forecast.

value Value in giga-watt per hour.

Source

Rte (Electricity Transmission Network in France) (<https://data.rte-france.com/>)

events_opts	<i>Events options</i>
-------------	-----------------------

Description

Events options

Usage

```
events_opts(
  click = NULL,
  beforeMount = NULL,
  mounted = NULL,
  updated = NULL,
  legendClick = NULL,
  selection = NULL,
  dataPointSelection = NULL,
  dataPointMouseEnter = NULL,
  dataPointMouseLeave = NULL,
  beforeZoom = NULL,
  zoomed = NULL,
  scrolled = NULL,
  ...
)
```

Arguments

click	Fires when user clicks on any area of the chart.
beforeMount	Fires before the chart has been drawn on screen.
mounted	Fires after the chart has been drawn on screen.
updated	Fires when the chart has been dynamically updated.
legendClick	Fires when user clicks on legend.
selection	Fires when user selects rect using the selection tool.

dataPointSelection	Fires when user clicks on a datapoint (bar/column/marker/bubble/donut-slice).
dataPointMouseEnter	Fires when user's mouse enter on a datapoint (bar/column/marker/bubble/donut-slice).
dataPointMouseLeave	MouseLeave event for a datapoint (bar/column/marker/bubble/donut-slice).
beforeZoom	This function, if defined, runs just before zooming in/out of the chart allowing you to set a custom range for zooming in/out.
zoomed	Fires when user zooms in/out the chart using either the selection zooming tool or zoom in/out buttons.
scrolled	Fires when user scrolls using the pan tool.
...	Additional parameters.

Value

A list of options that can be used in [ax_chart](#).

Note

All arguments should be JavaScript function defined with `htmlwidgets::JS`.

See <https://apexcharts.com/docs/options/chart/events/>.

Examples

```
if (interactive()) {
  library(shiny)

  ui <- fluidPage(
    fluidRow(
      column(
        width = 8, offset = 2,
        tags$h2("Apexchart in Shiny"),
        apexchartOutput("chart"),
        verbatimTextOutput(outputId = "res_click")
      )
    )
  )

  server <- function(input, output, session) {

    output$chart <- renderApexchart({
      apexchart() %>%
      ax_chart(
        type = "bar",
        events = events_opts(
          dataPointSelection = JS(
            "function(event, chartContext, config) {
              Shiny.setInputValue('click', config.selectedDataPoints)
            }"
          )
        )
      )
    })
  }
}
```



```
        }"
      )
    )
  ) %>%
  ax_series(
    list(
      name = "Example",
      data = sample(1:100, 5)
    )
  ) %>%
  ax_xaxis(
    categories = LETTERS[1:5]
  )
})

output$res_click <- renderPrint({
  input$click
})
}

shinyApp(ui, server)
}
```

format_date

Format date in JS

Description

Format date in JS

Usage

```
format_date(x)
```

Arguments

x Date to use in JavaScript

Value

a JavaScript string

format_num	<i>Format numbers (with D3)</i>
------------	---------------------------------

Description

Format numbers (with D3)

Usage

```
format_num(format, prefix = "", suffix = "", locale = "en-US")
```

Arguments

format	Format for numbers, currency, percentage, e.g. ".0%" for rounded percentage. See online documentation : https://github.com/d3/d3-format .
prefix	Character string to append before formatted value.
suffix	Character string to append after formatted value.
locale	Localization to use, for example "fr-FR" for french, see possible values here: https://github.com/d3/d3-format/tree/master/locale .

Value

a JS function

Examples

```
# Use SI prefix
dat <- data.frame(
  labels = c("apex", "charts"),
  values = c(1e4, 2e4)
)

apex(dat, aes(labels, values), "column") %>%
  ax_yaxis(labels = list(
    formatter = format_num("~s")
  ))

apex(dat, aes(labels, values * 100), "column") %>%
  ax_yaxis(labels = list(
    formatter = format_num("~s")
  ))

# Percentage
dat <- data.frame(
  labels = c("apex", "charts"),
  values = c(0.45, 0.55)
)
```

```
apex(dat, aes(labels, values), "column") %>%
  ax_yaxis(labels = list(
    formatter = format_num(".0%")
  ))

# Currency
dat <- data.frame(
  labels = c("apex", "charts"),
  values = c(570, 1170)
)

apex(dat, aes(labels, values), "column") %>%
  ax_yaxis(labels = list(
    formatter = format_num("$,.2f")
  ))

# Change locale
apex(dat, aes(labels, values), "column") %>%
  ax_yaxis(labels = list(
    formatter = format_num("$,.2f", locale = "fr-FR")
  ))

# Customize tooltip value
# Use SI prefix
dat <- data.frame(
  labels = c("apex", "charts"),
  values = c(1e4, 2e4)
)

apex(dat, aes(labels, values), "column") %>%
  ax_tooltip(y = list(
    formatter = format_num(",", suffix = " GW/h")
  ))
```

heatmap_opts

Heatmap options

Description

Use these options in [ax_plotOptions](#).

Usage

```
heatmap_opts(
  radius = NULL,
```

```

    enableShades = NULL,
    shadeIntensity = NULL,
    colorScale = NULL,
    ...
  )

```

Arguments

radius	Numeric. Radius of the rectangle inside heatmap.
enableShades	Logical. Enable different shades of color depending on the value
shadeIntensity	Numeric [0, 1]. The intensity of the shades generated for each value.
colorScale	List.
...	Additional parameters.

Value

A list of options that can be used in `ax_plotOptions`.

Note

See <https://apexcharts.com/docs/options/plotoptions/heatmap/>.

Examples

```

df <- expand.grid(
  month = month.name,
  person = c("Obi-Wan", "Luke", "Anakin", "Leia")
)
df$value <- sample(0:1, nrow(df), TRUE)

apex(
  data = df,
  mapping = aes(x = month, y = person, fill = value),
  type = "heatmap"
) %>%
  ax_plotOptions(
    heatmap = heatmap_opts(
      enableShades = FALSE,
      colorScale = list(
        ranges = list(
          list(from = 0, to = 0.5, color = "#FF0000"),
          list(from = 0.5, to = 1, color = "#088A08")
        )
      )
    )
  )

```

label	<i>Label for annotations</i>
-------	------------------------------

Description

Label for annotations

Usage

```
label(
    text = NULL,
    borderColor = NULL,
    borderWidth = NULL,
    textAnchor = NULL,
    position = NULL,
    offsetX = NULL,
    offsetY = NULL,
    background = NULL,
    color = NULL,
    fontSize = NULL,
    fontWeight = NULL,
    fontFamily = NULL,
    cssClass = NULL,
    padding = c(2, 5, 2, 5)
)
```

Arguments

text	Text for the annotation label.
borderColor	Border color for the label.
borderWidth	Border width for the label.
textAnchor	The alignment of text relative to label's drawing position.
position	Available options: left or right.
offsetX	Sets the left offset for annotation label.
offsetY	Sets the top offset for annotation label.
background	Background Color for the annotation label.
color	ForeColor for the annotation label.
fontSize	FontSize for the annotation label.
fontWeight	Font-weight for the annotation label.
fontFamily	Font-family for the annotation label.
cssClass	A custom Css Class to give to the annotation label elements.
padding	Padding for the label: top, right, bottom, left.

Value

A list that can be used in [add_shade](#), [add_point](#), [add_event](#), [add_event_marker](#).

parse_df	<i>Convert a data.frame to a list</i>
----------	---------------------------------------

Description

Convert data to a format suitable for ApexCharts.js

Usage

```
parse_df(data, add_names = FALSE)
```

Arguments

data	A data.frame or an object coercible to data.frame.
add_names	Use names of columns in output. Can be logical to reuse data names or a character vector of new names.

Value

A list that can be used to specify data in [ax_series](#) for example.

Examples

```
# All iris dataset
parse_df(iris)

# Keep variables names
parse_df(iris[, 1:2], add_names = TRUE)

# Use custom names
parse_df(iris[, 1:2], add_names = c("x", "y"))
```

pie_opts	<i>Pie options</i>
----------	--------------------

Description

Use these options in [ax_plotOptions](#).

Usage

```
pie_opts(  
    size = NULL,  
    donut = NULL,  
    customScale = NULL,  
    offsetX = NULL,  
    offsetY = NULL,  
    dataLabels = NULL,  
    ...  
)
```

Arguments

size	Numeric. Custom size of the pie which will override the default size calculations.
donut	List with two fields size (Donut / ring size in percentage relative to the total pie area.) and background (The background color of the pie).
customScale	Numeric. Transform the scale of whole pie/donut overriding the default calculations.
offsetX	Numeric. Sets the left offset of the whole pie area.
offsetY	Numeric. Sets the top offset of the whole pie area.
dataLabels	List with field offset (Numeric, Offset by which labels will move outside / inside of the donut area)
...	Additional parameters.

Value

A list of options that can be used in [ax_plotOptions](#).

Note

See <https://apexcharts.com/docs/options/plotoptions/pie/>.

Examples

```
data("mpg", package = "ggplot2")

apex(mpg, aes(cyl), type = "donut") %>%
  ax_plotOptions(
    pie = pie_opts(
      donut = list(size = "90%", background = "#BABABA")
    )
  )
```

radialBar_opts

Radial bar options

Description

Use these options in [ax_plotOptions](#).

Usage

```
radialBar_opts(
  size = NULL,
  inverseOrder = NULL,
  startAngle = NULL,
  endAngle = NULL,
  offsetX = NULL,
  offsetY = NULL,
  hollow = NULL,
  track = NULL,
  dataLabels = NULL,
  ...
)
```

Arguments

size	Numeric. Manual size of the radialBars instead of calculating automatically from default height / width.
inverseOrder	Logical. Whether to make the first value of series innermost or outermost.
startAngle	Numeric. Angle from which the radialBars should start.
endAngle	Numeric. Angle to which the radialBars should end. The sum of the startAngle and endAngle should not exceed 360.
offsetX	Numeric. Sets the left offset for radialBars.
offsetY	Numeric. Sets the top offset for radialBars.
hollow	List.
track	List.
dataLabels	List.
...	Additional parameters.

Value

A list of options that can be used in `ax_plotOptions`.

Note

See <https://apexcharts.com/docs/options/plotoptions/radialbar/>.

Examples

```
apexchart() %>%
  ax_chart(type = "radialBar") %>%
  ax_plotOptions(
    radialBar = radialBar_opts(
      startAngle = -135,
      endAngle = 135,
      dataLabels = list(
        name = list(
          fontSize = "16px",
          # color = undefined,
          offsetY = 120
        ),
        value = list(
          offsetY = 76,
          fontSize = "22px",
          # color = undefined,
          formatter = htmlwidgets::JS("function (val) {return val + '%';}")
        )
      )
    )
  ) %>%
  ax_stroke(dashArray = 4) %>%
  ax_series(70) %>%
  ax_labels("Indicator")
```

run_demo_input

Run Shiny input events examples

Description

Run Shiny input events examples

Usage

```
run_demo_input(example = c("click", "zoom", "selection"))
```

Arguments

example Name of the example.

Examples

```
if (interactive()) {  
  run_demo_input("click")  
  run_demo_input("zoom")  
  run_demo_input("selection")  
}
```

run_demo_sparkbox *Run Shiny spark boxes example*

Description

Run Shiny spark boxes example

Usage

```
run_demo_sparkbox()
```

Examples

```
if (interactive()) {  
  run_demo_sparkbox()  
}
```

run_demo_sync *Run Shiny synchronization example*

Description

Run Shiny synchronization example

Usage

```
run_demo_sync()
```

Examples

```
if (interactive()) {  
  run_demo_sync()  
}
```

set_input_click	<i>Retrieve click information in Shiny</i>
-----------------	--

Description

According to type of chart, different values are retrieved:

- **bar and column:** retrieve category (x-axis).
- **pie and donut:** retrieve label.
- **time-series:** retrieve x-axis value, you have to display markers with size > 0 and set tooltip's options intersect = TRUE and shared = FALSE.
- **scatter:** retrieve XY coordinates.

Usage

```
set_input_click(  
  ax,  
  inputId,  
  multiple = FALSE,  
  effect_type = c("darken", "lighten", "none"),  
  effect_value = 0.35,  
  session = shiny::getDefaultReactiveDomain()  
)
```

Arguments

ax	An apexchart() htmlwidget object.
inputId	The id that will be used server-side for retrieving click.
multiple	Allow multiple selection: TRUE or FALSE (default).
effect_type	Type of effect for selected element, default is to use lightly darken color.
effect_value	A larger value intensifies the select effect, accept value between 0 and 1.
session	The Shiny session.

Value

An [apexchart\(\)](#) htmlwidget object.

Note

If x-axis is of type datetime, value retrieved is of class POSIXct.

Examples

```
library(apexcharter)

# Not in Shiny but you can still click on bars
data.frame(
  month = month.abb,
  value = sample(1:100, 12)
) %>%
  apex(aes(month, value)) %>%
  set_input_click("month_click", multiple = TRUE)

# Interactive examples:
if (interactive()) {

  run_demo_input("click")

}
```

set_input_export	<i>Retrieve chart's base64 dataURI.</i>
------------------	---

Description

Retrieve chart's base64 dataURI.

Usage

```
set_input_export(ax, inputId, session = shiny::getDefaultReactiveDomain())
```

Arguments

ax	An apexchart() htmlwidget object.
inputId	The id that will be used server-side for retrieving data.
session	The Shiny session.

Value

An [apexchart\(\)](#) htmlwidget object.

Examples

```
library(shiny)
library(apexcharter)

ui <- fluidPage(
  fluidRow(
```

```

    column(
      width = 8, offset = 2,
      tags$h2("Export PNG"),
      actionButton("redraw", "Redraw chart"),
      apexchartOutput("chart"),
      verbatimTextOutput("result"),
      uiOutput(outputId = "image")
    )
  )
)

server <- function(input, output, session) {

  output$chart <- renderApexchart({
    input$redraw
    apexchart() %>%
      ax_chart(type = "bar") %>%
      ax_series(
        list(
          name = "Example",
          data = sample(1:100, 5)
        )
      ) %>%
      ax_xaxis(
        categories = LETTERS[1:5]
      ) %>%
      set_input_export("export")
  })

  output$result <- renderPrint({
    input$export
  })

  output$image <- renderUI({
    tags$img(src = input$export)
  })

}

if (interactive())
  shinyApp(ui, server)

```

set_input_selection *Retrieve selection information in Shiny*

Description

Retrieve selection information in Shiny

Usage

```

set_input_selection(
  ax,
  inputId,
  type = c("x", "xy", "y"),
  fill_color = "#24292e",
  fill_opacity = 0.1,
  stroke_width = 1,
  stroke_dasharray = 3,
  stroke_color = "#24292e",
  stroke_opacity = 0.4,
  xmin = NULL,
  xmax = NULL,
  ymin = NULL,
  ymax = NULL,
  session = shiny::getDefaultReactiveDomain()
)

```

Arguments

ax	An apexchart() htmlwidget object.
inputId	The id that will be used server-side for retrieving selection.
type	Allow selection either on x-axis, y-axis or on both axis.
fill_color	Background color of the selection rect which is drawn when user drags on the chart.
fill_opacity	Opacity of background color of the selection rectangle.
stroke_width	Border thickness of the selection rectangle.
stroke_dasharray	Creates dashes in borders of selection rectangle. Higher number creates more space between dashes in the border.
stroke_color	Colors of selection border.
stroke_opacity	Opacity of selection border.
xmin, xmax	Start value of x-axis. Both min and max must be provided.
ymin, ymax	Start value of y-axis. Both min and max must be provided.
session	The Shiny session.

Value

An [apexchart\(\)](#) htmlwidget object.

Examples

```

library(apexcharter)
data("economics", package = "ggplot2")

```

```
# Not in Shiny so no events
# but you can still select an area on chart
apex(economics, aes(date, psavert), type = "line") %>%
  set_input_selection("selection")

# Default selection at start
apex(economics, aes(date, psavert), type = "line") %>%
  set_input_selection(
    inputId = "selection",
    xmin = format_date("1980-01-01"),
    xmax = format_date("1985-01-01")
  )
```

set_input_zoom

Retrieve zoom information in Shiny

Description

Retrieve zoom information in Shiny

Usage

```
set_input_zoom(ax, inputId, session = shiny::getDefaultReactiveDomain())
```

Arguments

ax	An <code>apexchart()</code> htmlwidget object.
inputId	The id that will be used server-side for retrieving zoom.
session	The Shiny session.

Value

An `apexchart()` htmlwidget object.

Note

If x-axis is of type `datetime`, value retrieved is of class `POSIXct`.

Examples

```
if (interactive()) {
  run_demo_input("zoom")
}
```

set_tooltip_fixed	<i>Fixed tooltip</i>
-------------------	----------------------

Description

Fixed tooltip

Usage

```
set_tooltip_fixed(  
  ax,  
  position = c("topLeft", "topRight", "bottomLeft", "bottomRight"),  
  offsetX = NULL,  
  offsetY = NULL  
)
```

Arguments

ax	An apexchart() htmlwidget object.
position	Predefined position: "topLeft", "topRight", "bottomLeft" or "bottomRight".
offsetX	Sets the left offset for the tooltip container in fixed position.
offsetY	Sets the top offset for the tooltip container in fixed position.

Value

An [apexchart\(\)](#) htmlwidget object.

Examples

```
library(apexcharter)  
data("economics", package = "ggplot2")  
  
apex(  
  data = tail(economics, 350),  
  mapping = aes(x = date, y = uempmed),  
  type = "line"  
) %>%  
  set_tooltip_fixed()
```

spark_box	<i>Create a box with a sparkline</i>
-----------	--------------------------------------

Description

Create a box with a sparkline

Usage

```
spark_box(
  data,
  title = NULL,
  subtitle = NULL,
  color = "#2E93fA",
  background = "#FFF",
  type = c("area", "line", "spline", "column"),
  synchronize = NULL,
  title_style = NULL,
  subtitle_style = NULL,
  width = NULL,
  height = NULL,
  elementId = NULL
)
```

Arguments

data	A data.frame-like object with at least two columns, first is mapped to x-axis, second to y-axis.
title	Title to display in the box.
subtitle	Subtitle to display in the box.
color	Color of the chart.
background	Background color of the box.
type	Type of chart, currently type supported are : "area" (default), "line", "spline", "column".
synchronize	Give a common id to charts to synchronize them (tooltip and zoom).
title_style, subtitle_style	A list of named attributes to style the title / subtitle, possible values are fontSize, fontWeight, fontFamily, color.
width, height	A numeric input in pixels.
elementId	Use an explicit element ID for the widget.

Value

An apexcharts htmlwidget object.

Note

In Shiny use `sparkBoxOutput / renderSparkBox` to render boxes, see example. Boxes have CSS class `"apexcharter-spark-box"` if you need more styling.

Examples

```
library(apexcharter)

spark_data <- data.frame(
  date = Sys.Date() + 1:20,
  var1 = round(rnorm(20, 50, 10)),
  var2 = round(rnorm(20, 50, 10)),
  var3 = round(rnorm(20, 50, 10))
)

spark_box(
  data = spark_data,
  title = mean(spark_data$var1),
  subtitle = "Variable 1"
)

# In Shiny
if (interactive()) {
  run_sparkbox_demo()
}
```

unhcr_ts

UNHCR data by continent of origin

Description

The dataset contains data about UNHCR's populations of concern summarised by continent of origin.

Usage

```
unhcr_ts
```

Format

A data frame with 913 observations and the following 4 variables:

`year` Year concerned.

`population_type` Populations of concern : Refugees, Asylum-seekers, Internally displaced persons (IDPs), Returned refugees, Returned IDPs, Stateless persons, Others of concern.

`continent_origin` Continent of residence of population.

`n` Number of people concerned.

Source

UNHCR (The UN Refugee Agency) (<https://www.unhcr.org/>)

Index

- * **datasets**
 - candles, [68](#)
 - climate_paris, [69](#)
 - consumption, [70](#)
 - unhcr_ts, [90](#)
- %>% (apexcharter-exports), [20](#)

- add-line, [3](#)
- add-shade, [5](#)
- add-vh-lines, [7](#)
- add_event, [9](#), [11](#), [78](#)
- add_event_marker, [9](#), [10](#), [12](#), [78](#)
- add_hline (add-vh-lines), [7](#)
- add_line (add-line), [3](#)
- add_point, [11](#), [78](#)
- add_shade, [78](#)
- add_shade (add-shade), [5](#)
- add_shade_weekend (add-shade), [5](#)
- add_smooth_line (add-line), [3](#)
- add_vline (add-vh-lines), [7](#)
- aes (apexcharter-exports), [20](#)
- apex, [13](#)
- apex(), [19](#)
- apex-facets, [15](#)
- apex_grid, [25](#)
- apexchart, [19](#)
- apexchart(), [4](#), [6–12](#), [14–16](#), [19](#), [27](#), [28](#), [31](#), [32](#), [34](#), [35](#), [37](#), [38](#), [40–48](#), [52–56](#), [58–61](#), [63–65](#), [83](#), [84](#), [86–88](#)
- apexcharter-exports, [20](#)
- apexcharter-package, [3](#)
- apexcharter-shiny, [21](#)
- apexcharter-shiny-facets, [22](#)
- apexcharter-shiny-grid, [24](#)
- apexchartOutput (apexcharter-shiny), [21](#)
- apexchartProxy, [25](#)
- apexfacetOutput
 - (apexcharter-shiny-facets), [22](#)
- apexfacetOutput(), [16](#), [21](#)

- apexgridOutput
 - (apexcharter-shiny-grid), [24](#)
- ax-series, [27](#)
- ax_annotations, [28](#)
- ax_chart, [30](#), [72](#)
- ax_colors, [34](#)
- ax_colors_manual, [35](#)
- ax_dataLabels, [36](#)
- ax_facet_grid (apex-facets), [15](#)
- ax_facet_grid(), [21–23](#)
- ax_facet_wrap (apex-facets), [15](#)
- ax_facet_wrap(), [21–23](#)
- ax_fill, [38](#)
- ax_grid, [39](#)
- ax_labels, [41](#)
- ax_labels2 (ax_labels), [41](#)
- ax_labs, [42](#)
- ax_legend, [43](#)
- ax_markers, [45](#)
- ax_nodata, [46](#)
- ax_plotOptions, [47](#), [66–68](#), [75](#), [76](#), [79–81](#)
- ax_proxy_options, [48](#)
- ax_proxy_series, [50](#)
- ax_responsive, [51](#)
- ax_series, [78](#)
- ax_series (ax-series), [27](#)
- ax_series2 (ax-series), [27](#)
- ax_states, [52](#)
- ax_stroke, [53](#)
- ax_subtitle, [55](#)
- ax_theme, [56](#)
- ax_title, [57](#)
- ax_tooltip, [58](#)
- ax_xaxis, [60](#)
- ax_yaxis, [63](#), [65](#)
- ax_yaxis2, [65](#)

- bar_opts, [47](#), [66](#)
- bubble_opts, [47](#), [67](#)

candles, 68
climate_paris, 69
config_update, 70
config_update(), 14, 19
consumption, 70

events_opts, 31, 71

format_date, 73
format_num, 74

heatmap_opts, 47, 75

JS (apexcharter-exports), 20

label, 6, 8–10, 12, 77
label_value (apexcharter-exports), 20
lm, 4
loess, 4

parse_df, 78
pie_opts, 47, 79

radialBar_opts, 47, 80
renderApexchart (apexcharter-shiny), 21
renderApexfacet
 (apexcharter-shiny-facets), 22
renderApexfacet(), 16, 21
renderApexgrid
 (apexcharter-shiny-grid), 24
renderSparkBox (apexcharter-shiny), 21
run_demo_input, 81
run_demo_sparkbox, 82
run_demo_sync, 82

set_input_click, 83
set_input_export, 84
set_input_selection, 85
set_input_zoom, 87
set_tooltip_fixed, 88
spark_box, 89
sparkBoxOutput (apexcharter-shiny), 21

unhcr_ts, 90

vars (apexcharter-exports), 20