

Package ‘ecb’

December 15, 2022

Type Package

Title Programmatic Access to the European Central Bank's Statistical Data Warehouse

Version 0.4.1

Date 2022-12-15

Description Provides an interface to the 'European Central Bank's Statistical Data Warehouse' API <<https://sdw.ecb.europa.eu/>>, allowing for programmatic retrieval of a vast quantity of statistical data.

License CC0

URL <https://sdw.ecb.europa.eu/>

Suggests knitr, rmarkdown, dplyr, lubridate, ggplot2, testthat, zoo

Imports curl, rsdmx, xml2, httr

VignetteBuilder knitr

RoxygenNote 7.1.1

NeedsCompilation no

Author Eric Persson [aut, cre]

Maintainer Eric Persson <expersso5@gmail.com>

Repository CRAN

Date/Publication 2022-12-15 11:20:03 UTC

R topics documented:

convert_dates	2
get_data	2
get_dataflows	4
get_description	4
get_dimensions	5

Index	6
--------------	----------

convert_dates	<i>Format date variable retrieved from the SDW into a proper date variable</i>
---------------	--

Description

Format date variable retrieved from the SDW into a proper date variable

Usage

```
convert_dates(x)
```

Arguments

x	A vector of dates
---	-------------------

Value

A date-formatted vector

Examples

```
hicip <- get_data("ICP.M.U2.N.000000.4.ANR")
hicip$obstime <- convert_dates(hicip$obstime)
str(hicip)
```

get_data	<i>Retrieve data from the ECB Statistical Data Warehouse API</i>
----------	--

Description

Retrieve data from the ECB Statistical Data Warehouse API

Usage

```
get_data(key, filter = NULL, ...)
```

Arguments

key	A character string identifying the series to be retrieved
filter	A named list with additional filters (see details)
...	Arguments passed to GET (e.g. timeout(10) to add maximum request time)

Details

The filter option of `get_data()` takes a named list of key-value pairs. If left blank, it returns all data for the current version.

Available filter parameters:

- startPeriod & endPeriod
 - YYYY for annual data (e.g.: 2013)
 - YYYY-S[1-2] for semi-annual data (e.g.: 2013-S1)
 - YYYY-Q[1-4] for quarterly data (e.g.: 2013-Q1)
 - YYYY-MM for monthly data (e.g.: 2013-01)
 - YYYY-W[01-53] for weekly data (e.g.: 2013-W01)
 - YYYY-MM-DD for daily data (e.g.: 2013-01-01)
- updatedAfter
 - A timestamp to retrieve the latest version of changed values in the database since a certain point in time
 - Example: `filter = list(updatedAfter = 2009-05-15T14:15:00+01:00)`
- firstNObservations & lastNObservations
 - Example: `filter = list(firstNObservations = 12)` retrieves the first 12 observations of all specified series
- detail
 - Possible options: `full/dataonly/serieskeyonly/nodata`
 - `dataonly` is the default
 - Use `serieskeyonly` or `nodata` to list series that match a certain query, without returning the actual data
 - An alternative to using `serieskeys/nodata` is the convenience function `get_dimensions()`, which returns a list of dataframes with dimensions and explanations (see extended example below).
 - `full` returns both the series values and all metadata. This entails retrieving much more data than with the `'dataonly'` option.
- includeHistory (not currently implemented)
 - `false` (default) returns only version currently in production
 - `true` returns version currently in production, as well as all previous versions

See the [SDW API](#) for more details.

Value

A data frame

Examples

```
# Get monthly data on annualized euro area headline HICP
hicip <- get_data("ICP.M.U2.N.000000.4.ANR")
head(hicip)
```

get_dataflows	<i>Retrieve data frame of all datasets in the ECB Statistical Data Warehouse</i>
---------------	--

Description

Retrieve data frame of all datasets in the ECB Statistical Data Warehouse

Usage

```
get_dataflows(...)
```

Arguments

... Arguments passed to GET (e.g. timeout(10) to add maximum request time)

Value

A dataframe

Examples

```
df <- get_dataflows()
head(df)
```

get_description	<i>Get full, human-readable description of a series</i>
-----------------	---

Description

Get full, human-readable description of a series

Usage

```
get_description(key)
```

Arguments

key A character string identifying the series to be retrieved

Value

A character vector

Examples

```
get_description("ICP.M.DE.N.000000+XEF000.4.ANR")
```

get_dimensions	<i>Retrieve dimensions of series in the ECB's SDW</i>
----------------	---

Description

Retrieve dimensions of series in the ECB's SDW

Usage

```
get_dimensions(key, ...)
```

Arguments

key	A character string identifying the series to be retrieved
...	Arguments passed to GET (e.g. timeout(10) to add maximum request time)

Value

A list of data frames, one for each series retrieved

Examples

```
hisp_dims <- get_dimensions("ICP.M.U2.N.000000.4.ANR")  
hisp_dims[[1]]
```

Index

`convert_dates`, [2](#)

`get_data`, [2](#)

`get_dataflows`, [4](#)

`get_description`, [4](#)

`get_dimensions`, [5](#)