

Package ‘func2vis’

October 13, 2022

Type Package

Title Clean and Visualize Over Expression Results from
'ConsensusPathDB'

Version 1.0-2

Date 2022-07-22

Author Raghvendra Mall [aut, cre]

Maintainer Raghvendra Mall <raghvendra5688@gmail.com>

Repository CRAN

Description

Provides functions to have visualization and clean-up of enriched gene ontologies (GO) terms, protein complexes and pathways (obtained from multiple databases) using 'ConsensusPathDB' from gene set over-expression analysis. Performs clustering of pathway based on similarity of over-expressed gene sets and visualizations similar to Ingenuity Pathway Analysis (IPA) when up and down regulated genes are known. The methods are described in a paper currently submitted by Orecchioni et al, 2020 in Nanoscale.

License GPL (>= 3)

LazyLoad true

Depends ggplot2, igraph, devtools, ggrepel, grDevices, R (>= 3.6)

NeedsCompilation yes

Date/Publication 2022-08-29 11:00:02 UTC

RoxygenNote 7.1.1

R topics documented:

clean_go_terms	2
clean_pathways	3
clean_pc	4
enriched_goterms	5
enriched_pathways	5
enriched_pc	6
plot_go_terms	6

plot_pathways	7
plot_pathways_stacked_barplot	8
t.tests.treatment.sign	9

Index	10
--------------	-----------

clean_go_terms	<i>Clean Gene Ontologies (GO) Terms</i>
----------------	---

Description

Clean set of enriched goterms obtained from 'ConsensusPathDB' for gene set overexpression analysis. We also append two columns indicating the number of up-regulated and number of down-regulated genes based on fold change information available in data frame case_vs_ctrl.

Usage

```
clean_go_terms(df_case_vs_ctrl, df_goterms)
```

Arguments

df_case_vs_ctrl	Data frame which has at least 2 columns: <gene,fc>. Here gene represents the set of genes which are differentially expressed between case and control. Here fc represents the fold-change value for each gene.
df_goterms	The tab-separated data frame with the goterms information obtained after performing gene set overexpression analysis using 'ConsensusPathDB'.

Value

Returns clean enriched GO terms data frame.

Note

rmall@hbku.edu.qa

Author(s)

Raghvendra Mall

See Also

See Also as [clean_pc](#), [plot_go_terms](#)

Examples

```
data("t.tests.treatment.sign")
data("enriched_goterms")
revised_goterms <- clean_go_terms(df_case_vs_ctrl=t.tests.treatment.sign,
                                df_goterms = enriched_goterms)
print(head(revised_goterms))
```

clean_pathways	<i>Clean Enriched Pathways</i>
----------------	--------------------------------

Description

Clean set of enriched pathways obtained from 'ConsensusPathDB' for gene set overexpression analysis. We also append two columns indicating the number of up-regulated and number of down-regulated genes based on fold change information available in data frame case_vs_ctrl. We cluster pathways based on similarity of gene set using igraph's walktrap clustering algorithm. Within each cluster, pathways are ordered by most to least significant pathway in terms of p-values.

Usage

```
clean_pathways(df_case_vs_ctrl, df_pathway)
```

Arguments

df_case_vs_ctrl	Data frame which has at least 2 columns: <gene,fc>. Here gene represents the set of genes which are differentially expressed between case and control. Here fc represents the fold-change value for each gene.
df_pathway	The tab-separated data frame with the pathways information obtained after performing gene set overexpression analysis using 'ConsensusPathDB'.

Value

Returns clean enriched pathways data frame. The data frame has an additional column clusters highlighting the cluster to which each enriched pathway belongs.

Note

rmall@hbku.edu.qa

Author(s)

Raghvendra Mall

See Also

[clean_go_terms](#), [clean_pc](#)

Examples

```
data("t.tests.treatment.sign")
data("enriched_pathways")
revised_pathway <- clean_pathways(df_case_vs_ctrl=t.tests.treatment.sign,
                                df_pathway = enriched_pathways)
print(head(revised_pathway))
```

clean_pc

Clean Enriched Protein Complexes

Description

Clean set of enriched protein complexes obtained from 'ConsensusPathDB' for gene set overexpression analysis. We also append two columns indicating the number of up-regulated and number of down-regulated genes based on fold change information available in data frame case_vs_ctrl.

Usage

```
clean_pc(df_case_vs_ctrl,df_pc)
```

Arguments

df_case_vs_ctrl

Data frame which has at least 2 columns: <gene,fc>. Here gene represents the set of genes which are differentially expressed between case and control. Here fc represents the fold-change value for each gene.

df_pc

The tab-separated data frame with the protein complexes information obtained after performing gene set overexpression analysis using 'ConsensusPathDB'.

Value

Returns clean enriched protein complexes data frame.

Note

rmall@hbku.edu.qa

Author(s)

Raghvendra Mall

See Also

See Also as [clean_go_terms](#), [plot_go_terms](#)

Examples

```
data("t.tests.treatment.sign")
data("enriched_pc")
revised_pc <- clean_pc(df_case_vs_ctrl=t.tests.treatment.sign,
                      df_pc = enriched_pc)
print(head(revised_pc))
```

enriched_goterms *Sample Enriched Gene Ontologies (GO) Terms*

Description

This dataset highlights enriched gene ontologies (GO) terms identified by using ConsensusPathDB while performing overexpression analysis for a sample set of genes.

Usage

```
data("enriched_goterms")
```

References

Kamburov, A., Stelzl, U., Lehrach, H. and Herwig, R., 2013. The ConsensusPathDB interaction database: 2013 update. Nucleic acids research, 41(D1), pp.D793-D800.

Examples

```
data(enriched_goterms)
## maybe str(enriched_goterms) ;
```

enriched_pathways *Sample Enriched Pathways*

Description

This dataset highlights enriched pathways identified by using 'ConsensusPathDB' while performing overexpression analysis for a sample set of genes.

Usage

```
data("enriched_pathways")
```

References

Kamburov, A., Stelzl, U., Lehrach, H. and Herwig, R., 2013. The ConsensusPathDB interaction database: 2013 update. Nucleic acids research, 41(D1), pp.D793-D800.

Examples

```
data(enriched_pathways)
## maybe str(enriched_pathways) ;
```

enriched_pc	<i>Sample Enriched Protein Complexes</i>
-------------	--

Description

This dataset highlights protein complexes identified by using 'ConsensusPathDB' while performing overexpression analysis for a sample set of genes.

Usage

```
data("enriched_pc")
```

References

Kamburov, A., Stelzl, U., Lehrach, H. and Herwig, R., 2013. The ConsensusPathDB interaction database: 2013 update. Nucleic acids research, 41(D1), pp.D793-D800.

Examples

```
data(enriched_pc)
## maybe str(enriched_pc) ;
```

plot_go_terms	<i>Bubble Plot for GO Terms</i>
---------------	---------------------------------

Description

Make a bubble plot for significantly enriched Gene Ontologies (GO) Terms obtained after performing gene set overexpression analysis using 'ConsensusPathDB'.

Usage

```
plot_go_terms(df_goterms, total_no_background_genes, negative_log_10_p_value_cutoff)
```

Arguments

df_goterms	The tab-separated data frame with the GO terms information obtained after performing gene set overexpression analysis using 'ConsensusPathDB'.
total_no_background_genes	Total no of genes in the background set.
negative_log_10_p_value_cutoff	The threshold on $-\log_{10}(\text{pvalue})$ to be used to identify the GO terms to be highlighted in the plot.

Details

Plots the significantly enriched molecular function (m), cellular components (c) and biological processes (b) obtained via ConsensusPathDB.

Value

Returns a bubble plot of type ggplot.

Note

rmall@hbku.edu.qa

Author(s)

Raghvendra Mall

Examples

```
data("enriched_goterms")
g <- plot_go_terms(df_goterms = enriched_goterms, negative_log_10_p_value_cutoff=17)
g
```

plot_pathways

Plot clean enriched pathways as a bubble plot

Description

Make a bubble plot of clean enriched pathways obtained from 'ConsensusPathDB' by performing gene set overexpression analysis. Colours represent the clusters to which each pathway belongs. You need to run the function [clean_pathways](#) to obtain the input data frame.

Usage

```
plot_pathways(final_df_pathway, total_no_background_genes, fontsize)
```

Arguments

`final_df_pathway` Clean and clustered pathways obtained using [clean_pathways](#).

`total_no_background_genes` Total no of genes in the background set.

`fontsize` Font size of the pathways to be displayed on y-axis.

Value

Returns a bubble plot of type ggplot. Colours represent the clusters to which each pathway belongs.

Note

rmall@hbku.edu.qa

Author(s)

Raghvendra Mall

See Also

See Also as [clean_pathways](#), [plot_pathways_stacked_barplot](#), [plot_go_terms](#)

Examples

```
data("t.tests.treatment.sign")
data("enriched_pathways")
revised_pathway <- clean_pathways(df_case_vs_ctrl=t.tests.treatment.sign,
                                df_pathway = enriched_pathways)
p <- plot_pathways(revised_pathway)
p
```

plot_pathways_stacked_barplot

Stacked Barplot of Cleaned Pathways

Description

Make a stacked barplot like the one available in Ingenuity Pathway Analysis highlighting percentage of up, down and non-differentially expressed genes in the set of clean enriched pathways obtained from 'ConsensusPathDB' by performing gene set overexpression analysis. You need to run the function [clean_pathways](#) to obtain the input data frame

Usage

```
plot_pathways_stacked_barplot(final_df_pathway)
```

Arguments

final_df_pathway
Clean and clustered pathways obtained using [clean_pathways](#).

Value

Returns a stacked barplot of type ggplot.

Note

rmall@hbku.edu.qa

Author(s)

Raghvendra Mall

See Also

[clean_pathways](#), [plot_go_terms](#)

Examples

```
data("t.tests.treatment.sign")
data("enriched_pathways")
revised_pathway <- clean_pathways(df_case_vs_ctrl=t.tests.treatment.sign,
                                df_pathway = enriched_pathways)
p <- plot_pathways_stacked_barplot(revised_pathway)
p
```

t.tests.treatment.sign

List of differentially expressed genes

Description

Consist of list of differentially expressed genes (DEG) with fold-change information i.e. up and down regulated genes between case and control.

Usage

```
data("t.tests.treatment.sign")
```

Format

A data frame with 1820 observations on the following 8 variables.

- gene a character vector
- p.value a numeric vector
- p.value.fdr a numeric vector
- fc a numeric vector
- mean.A a numeric vector
- mean.B a numeric vector
- sd.A a numeric vector
- sd.B a numeric vector

Examples

```
data(t.tests.treatment.sign)
## maybe str(t.tests.treatment.sign) ;
```

Index

* datasets

- enriched_goterms, 5
- enriched_pathways, 5
- enriched_pc, 6
- t.tests.treatment.sign, 9

- clean_go_terms, 2, 3, 4
- clean_pathways, 3, 7-9
- clean_pc, 2, 3, 4

- enriched_goterms, 5
- enriched_pathways, 5
- enriched_pc, 6

- plot_go_terms, 2, 4, 6, 8, 9
- plot_pathways, 7
- plot_pathways_stacked_barplot, 8, 8

- t.tests.treatment.sign, 9