

Package ‘gp’

January 12, 2023

Type Package

Title Maximum Likelihood Estimation of the Generalized Poisson Distribution

Version 1.0

Date 2023-01-11

Author Michail Tsagris [aut, cre]

Maintainer Michail Tsagris <mtsagris@uoc.gr>

Depends R (>= 4.0)

Imports Rfast, RNGforGPD, stats

Description Functions to estimate the parameters of the generalized Poisson distribution with or without covariates using maximum likelihood. The references include Nikolouloupolos A.K. & Karlis D. (2008). ``On modeling count data: a comparison of some well-known discrete distributions''. Journal of Statistical Computation and Simulation, 78(3): 437--457, <[doi:10.1080/10629360601010760](https://doi.org/10.1080/10629360601010760)> and Consul P.C. & Famoye F. (1992). ``Generalized Poisson regression model''. Communications in Statistics - Theory and Methods, 21(1): 89--109, <[doi:10.1080/03610929208830766](https://doi.org/10.1080/03610929208830766)>.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2023-01-12 18:20:05 UTC

R topics documented:

gp-package	2
gp.mle	2
gp.reg	3
rgp	5

Index

7

gp-package*Maximum Likelihood Estimation of the Generalized Poisson Distribution.*

Description

Maximum likelihood estimation of the generalized Poisson distribution. Regression modelling is also supported.

Details

Package:	nlgmcr	Type:	Package
Version:	1.0		
Date:	2023-01-11		
License:	GPL-2		

Maintainers

Michail Tsagris <mtsagris@uoc.gr>.

Author(s)

Michail Tsagris <mtsagris@uoc.gr>.

References

Nikoloulopoulos A.K. & Karlis D. (2008). On modeling count data: a comparison of some well-known discrete distributions. *Journal of Statistical Computation and Simulation*, 78(3): 437–457.
 Consul P.C. & Famoye F. (1992). Generalized poisson regression model. *Communications in Statistics - Theory and Methods*, 21(1): 89–109.

gp.mle*Maximum likelihood estimation of the generalized Poisson distribution*

Description

Maximum likelihood estimation of the generalized Poisson distribution.

Usage

```
gp.mle(y)
```

Arguments

y	A vector with non negative integer values.
---	--

Details

The probability density function of the generalized Poisson distribution is the following (Nikoloulopoulos & Karlis, 2008):

$$P(Y = y|\theta, \lambda) = \theta(\theta + \lambda y)^{y-1} \frac{e^{-\theta-\lambda y}}{y!}, \quad y = 0, 1, \dots \quad \theta > 0, \quad 0 \leq \lambda \leq 1.$$

To ensure that θ is positive we use the "log" link and for λ to lie within 0 and 1 we use the "logit" link within the [optim](#) function.

Value

A vector with three numbers, the θ and λ parameters and the value of the log-likelihood.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Nikoloulopoulos A.K. & Karlis D. (2008). On modeling count data: a comparison of some well-known discrete distributions. *Journal of Statistical Computation and Simulation*, 78(3): 437–457.

See Also

[gp.reg](#), [rgp](#)

Examples

```
y <- rgp(1000, 10, 0.5, method = "Inversion")
gp.mle(y)
```

gp.reg

Generalized Poisson regression

Description

Generalized Poisson regression.

Usage

```
gp.reg(y, x, tol = 1e-7)
gp.reg2(y, x, tol = 1e-7)
```

Arguments

<i>y</i>	The response variable, a vector with non negative integer values.
<i>x</i>	A data.frame or a matrix with the independent variables.
<i>tol</i>	The tolerance value to terminate the optimization.

Details

The loglikelihood of the generalised Poisson distribution when covariates are present is the following (Consul & Famoye, 1992):

$$\ell(\beta, \phi) = \sum_{i=1}^n \log(\mu_i) + \sum_{i=1}^n (y_i - 1) \log [\mu_i + (\phi - 1)y_i] - \log \phi \sum_{i=1}^n y_i - \frac{1}{\phi} \sum_{i=1}^n [\mu_i + (\phi - 1)y_i] - \sum_{i=1}^n \log(y_i),$$

where $\mu_i = e^{\sum_{j=0}^k X_{ij}\beta_j}$, n denotes the sample size, k is the number of β coefficients, and $\phi > 0$.

Breslow (1984) suggested the (moment) estimation of a dispersion parameter by equating the chi-square statistic to its degrees of freedom. For the generalised Poisson regression model, this leads to $\sum_{i=1}^n \frac{(y_i - \mu_i)^2}{\mu_i \phi^2} = n - k$ and we solve this for ϕ .

According to Consul and Famoye (1992) we begin by fitting a Poisson regression model and obtain initial values for β_s and ϕ . If $\hat{\phi} \approx 1$, it implies that the Poisson regression model is appropriate and no further estimation needs to be done. However, if $\hat{\phi} \neq 1$, this is used to obtain new values of the estimated β_s by maximizing the log-likelihood. This process is iterated until we obtain a stable solution.

The function as seen below returns the log-likelihood of the initial Poisson regression as well. This is useful if one wants to test, via the log-likelihood ratio test as 1 degree of freedom, if the generalized Poisson regression is to be preferred over the Poisson regression.

gp.reg() estimates the *beta* coefficients using Newton-Raphson, whereas *gp.reg2()* uses the *optim* function. For some reason these two do not always agree. One might yield higher log-likelihood than the other and this is why I offer both ways.

Value

A list including:

<i>pois.loglik</i>	The initial Poisson regression log-likelihood.
<i>gp.loglik</i>	The generalized Poisson regression log-likelihood.
<i>be</i>	The estimated <i>beta</i> coefficients.
<i>phi</i>	The estimated ϕ parameter.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

- Consul P.C. & Famoye F. (1992). Generalized poisson regression model. Communications in Statistics - Theory and Methods, 21(1): 89–109.
- Breslow N. E. (1984). Extra-Poisson variation in log-linear models. Journal of the Royal Statistical Society: Series C (Applied Statistics), 33(1): 38–44.

See Also

[gp.mle](#)

Examples

```
n <- 500
x <- matrix (rnorm(n * 2), nrow = n, ncol = 2)
be <- c(1, 1)
mi <- x[, 1] * be[1] + x[, 2] * be[2] + 1
mi <- exp(mi)
y <- numeric(n)
for (i in 1:n) y[i] <- rgp(2, mi[i], 0.5, method = "Inversion")[1]
gp.reg(y, x)
gp.reg2(y, x)
```

rgp

Random values simulation from the generalized Poisson distribution

Description

Random values simulation from the generalized Poisson distribution.

Usage

```
rgp(n, theta, lambda, method)
```

Arguments

n	The number of random values to generate.
theta	The value of the θ parameter.
lambda	The value of the λ parameter.
method	The simulation method to use. The available options are: "Inversion", "Branching", "Normal-Approximation", "Build-Up" and "Chop-Down".

Details

The values θ and λ affect the method of simulation to use. See Li et al. (2020) for more information.

Value

A vector with values from the generalized Poisson distribution.

Author(s)

Michail Tsagris.

R implementation and documentation: Michail Tsagris <mtsagris@uoc.gr>.

References

Li H., Demirtas H. & Chen R. (2020). RNGforGPD: An R Package for Generation of Univariate and Multivariate Generalized Poisson Data. *R JOURNAL*, 12(2): 173–188.

Demirtas H. (2017). On accurate and precise generation of generalized Poisson variates. *Communications in Statistics - Simulation and Computation*, 46(1): 489–499.

See Also

[gp.mle](#)

Examples

```
y <- rgp(1000, 10, 0.5, method = "Inversion")
gp.mle(y)
```

Index

gp-package, 2
gp.mle, 2, 5, 6
gp.reg, 3, 3
gp.reg2 (gp.reg), 3
optim, 3, 4
rgp, 3, 5