Package 'gravity'

October 13, 2022

```
Type Package
Title Estimation Methods for Gravity Models
Version 1.0
Description A wrapper of different standard estimation methods for gravity models.
     This package provides estimation methods for log-log models and multiplicative models.
URL https://pacha.dev/gravity/
BugReports https://github.com/pachadotdev/gravity/issues/
Imports Imtest, sandwich, glm2, MASS, stats, censReg, survival,
     multiwayvcov, tibble, magrittr, dplyr, tidyr, purrr, rlang,
     Rdpack, utils
RdMacros Rdpack
Depends R(>= 3.4.0)
License Apache License (>= 2)
Encoding UTF-8
LazyData true
RoxygenNote 7.1.2
Suggests knitr, rmarkdown, testthat, broom
VignetteBuilder knitr
NeedsCompilation no
Author Anna-Lena Woelwer [aut, cph],
     Jan Pablo Burgard [aut, cph],
     Joshua Kunst [aut, cph],
     Mauricio Vargas [aut, cre, cph]
      (<https://orcid.org/0000-0003-1017-7574>),
     Romain Francois [ctb] (adapted parts of the code to use dplyr 0.8.0),
     Lionel Henry [ctb] (simplified parts of the code),
     Sarah Johnson [ctb] (improved the double demeaning function),
     Hrisyana Doytchinova [rev] (sent us different suggestions and bug
      reports)
Maintainer Mauricio Vargas <mv.sepulveda@mail.utoronto.ca>
```

2 bvu

Repository CRAN

Date/Publication 2022-01-05 09:50:02 UTC

R topics documented:

```
bvu
et tobit .......
gravity_zeros
42
Index
     49
 Bonus vetus OLS (BVU)
bvu
```

Description

byu estimates gravity models via Bonus vetus OLS with simple averages.

Usage

```
bvu(
   dependent_variable,
   distance,
   additional_regressors = NULL,
   income_origin,
   income_destination,
   code_origin,
   code_destination,
   robust = FALSE,
   data,
   ...
)
```

bvu 3

Arguments

dependent_variable

(Type: character) name of the dependent variable. This dependent variable is divided by the product of unilateral incomes such (i.e. income_origin and income_destination) and logged afterwards.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDP should be inserted via the arguments income_origin and income_destination. As country specific effects are subdued due to demeaning, no further unilateral variables apart from incomes can be added.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

 $income_origin \quad (Type: \ character) \ origin \ income \ variable \ (e.g. \ GDP) \ in \ the \ dataset.$

income_destination

(Type: character) destination income variable (e.g. GDP) in the dataset.

code_origin (Type: character) country of origin variable (e.g. ISO-3 country codes). The

variables are grouped using this parameter.

code_destination

(Type: character) country of destination variable (e.g. country ISO-3 codes).

The variables are grouped using this parameter.

robust (Type: logical) whether robust fitting should be used. By default this is set to

FALSE.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

Bonus vetus OLS is an estimation method for gravity models developed by Baier and Bergstrand (2009); Baier and Bergstrand (2010) using simple averages to center a Taylor-series.

The bvu function considers Multilateral Resistance terms and allows to conduct comparative statics. Country specific effects are subdued due to demeaning. Hence, unilateral variables apart from incomes cannot be included in the estimation.

bvu is designed to be consistent with the Stata code provided at Gravity Equations: Workhorse, Toolkit, and Cookbook when choosing robust estimation.

As, to our knowledge at the moment, there is no explicit literature covering the estimation of a gravity equation by byu using panel data, we do not recommend to apply this method in this case.

Value

The function returns the summary of the estimated gravity model as an 1m-object.

4 bvu

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

lm, coeftest, vcovHC

byw 5

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")
# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")</pre>
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
fit <- bvu(
  dependent_variable = "flow",
  distance = "distw",
  additional_regressors = c("rta", "contig", "comcur"),
  income_origin = "gdp_o",
  income_destination = "gdp_d",
  code_origin = "iso_o",
  code_destination = "iso_d",
  robust = FALSE,
  data = grav_small
)
```

bvw

Bonus vetus OLS (BVW)

Description

byw estimates gravity models via Bonus vetus OLS with income-weights.

Usage

```
bvw(
  dependent_variable,
  distance,
  additional_regressors = NULL,
  income_origin,
  income_destination,
  code_origin,
  code_destination,
  robust = FALSE,
  data,
  ...
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. This dependent variable is divided by the product of unilateral incomes such (i.e. income_origin and income_destination) and logged afterwards.

6 bvw

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDP should be inserted via the arguments income_origin and income_destination. As country specific effects are subdued due to demeaning, no further unilateral variables apart from incomes can be added.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

income_origin (Type: character) origin income variable (e.g. GDP) in the dataset. income destination

(Type: character) destination income variable (e.g. GDP) in the dataset.

code_origin (Type: character) country of origin variable (e.g. ISO-3 country codes). The

variables are grouped using this parameter.

code_destination

(Type: character) country of destination variable (e.g. country ISO-3 codes).

The variables are grouped using this parameter.

robust (Type: logical) whether robust fitting should be used. By default this is set to

FALSE.

data (Type: data.frame) the dataset to be used.

. . . Additional arguments to be passed to the function.

Details

Bonus vetus OLS is an estimation method for gravity models developed by Baier and Bergstrand (2009); Baier and Bergstrand (2010) using income-weights to center a Taylor series.

The bww function considers Multilateral Resistance terms and allows to conduct comparative statics. Country specific effects are subdued due to demeaning. Hence, unilateral variables apart from inc_o and inc_d cannot be included in the estimation.

byw is designed to be consistent with the Stata code provided at Gravity Equations: Workhorse, Toolkit, and Cookbook when choosing robust estimation.

As, to our knowledge at the moment, there is no explicit literature covering the estimation of a gravity equation by byw using panel data, we do not recommend to apply this method in this case.

Value

The function returns the summary of the estimated gravity model as an 1m-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

bvw 7

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

lm, coeftest, vcovHC

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")

# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
```

8 ddm

```
fit <- bvw(
  dependent_variable = "flow",
  distance = "distw",
  additional_regressors = c("rta", "comcur", "contig"),
  income_origin = "gdp_o",
  income_destination = "gdp_d",
  code_origin = "iso_o",
  code_destination = "iso_d",
  robust = FALSE,
  data = grav_small
)</pre>
```

ddm

Double Demeaning (DDM)

Description

ddm estimates gravity models via double demeaning the left hand side and right hand side of the gravity equation.

Usage

```
ddm(
  dependent_variable,
  distance,
  additional_regressors = NULL,
  code_origin,
  code_destination,
  robust = FALSE,
  data,
  ...
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. This dependent variable is divided by the product of unilateral incomes such (i.e. income_origin and income_destination) and logged afterwards.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDP should be inserted via the arguments income_origin and income_destination. As country specific effects are subdued due to demeaning, no further unilateral variables apart from incomes can be added.

ddm 9

Write this argument as c(contiguity, common currency, ...). By default

this is set to NULL.

code_origin (Type: character) country of origin variable (e.g. ISO-3 country codes). The

variables are grouped using this parameter.

code_destination

(Type: character) country of destination variable (e.g. country ISO-3 codes).

The variables are grouped using this parameter.

robust (Type: logical) whether robust fitting should be used. By default this is set to

FALSE.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

ddm is an estimation method for gravity models presented in Head and Mayer (2014).

Country specific effects are subdued due double demeaning. Hence, unilateral income proxies such as GDP cannot be considered as exogenous variables.

Unilateral effect drop out due to double demeaning and therefore cannot be estimated.

ddm is designed to be consistent with the Stata code provided at Gravity Equations: Workhorse, Toolkit, and Cookbook when choosing robust estimation.

As, to our knowledge at the moment, there is no explicit literature covering the estimation of a gravity equation by ddm using panel data, we do not recommend to apply this method in this case.

Value

The function returns the summary of the estimated gravity model as an 1m-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

10 ddm

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

lm, coeftest, vcovHC

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")
# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")</pre>
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
fit <- ddm(
  dependent_variable = "flow",
  distance = "distw",
  additional_regressors = c("rta", "comcur", "contig"),
  code_origin = "iso_o",
  code_destination = "iso_d",
  robust = FALSE,
  data = grav_small
)
```

discard_unusable 11

discard_unusable	Discard non-positive and/or non-finite observations in datasets

Description

discard_unusable drops observations that cannot be used with models that convert columns to log scale, and therefore requiere non-negative and finite observations.

Consider that some of the functions within this package will drop observations when required and it is not required to be run before fitting a model.

Usage

```
discard_unusable(data, columns)
```

Arguments

data (Type: data.frame) the dataset to be used.

columns The columns to be cleaned (e.g. c("flow", "distw")) in the case of ddm when

used with the example dataset gravity_zeros)

Value

The function returns the summary of the estimated gravity model as an 1m-object.

See Also

```
lm, coeftest, vcovHC
```

Examples

```
discard_unusable(gravity_zeros, "flow")
discard_unusable(gravity_zeros, c("flow", "distw"))
```

ek_tobit

Eaton and Kortum (2001) Tobit model (EK Tobit)

Description

ek_tobit estimates gravity models in their additive form by conducting a censored regression.

12 ek_tobit

Usage

```
ek_tobit(
  dependent_variable,
  distance,
  additional_regressors = NULL,
  code_destination,
  robust = FALSE,
  data,
  ...
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. This variable is logged and then used as the dependent variable in the estimation. As the log of zero is not defined, all flows equal to zero are replaced by a left open interval with the logged minimum trade flow of the respective importing country as right border.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDP should be inserted via the arguments income_origin and income_destination.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

code_destination

(Type: character) country of destination variable (e.g. country ISO-3 codes).

The variables are grouped using this parameter.

robust (Type: logical) whether robust fitting should be used. By default this is set to

FALSE.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

ek_tobit represents the Eaton and Kortum (2001) Tobit model where each country is assigned specific censoring bounds.

When taking the log of the gravity equation flows equal to zero constitute a problem as their log is not defined. Therefore, in ek_tobit all values of the dependent variable are redefined as intervals.

The positive observations have both interval bounds equal to their original value.

For zero flows the interval is left open. The right border of the interval is set to the log of the minimum positive trade flow of the respective importing country.

The defined data object of class Surv is then inserted in survreg for the parameter estimation.

ek_tobit 13

ek_tobit is designed to be consistent with the Stata code provided at Gravity Equations: Workhorse, Toolkit, and Cookbook when choosing robust estimation.

For other Tobit functions, see tobit for a simple Tobit model where number 1 is added to all observations and et_tobit for the Eaton and Tamura (1995) threshold Tobit model where instead of simply adding number 1 to the data the threshold is estimated.

The function is designed for cross-sectional data, but can be extended to panel data using the survreg function.

Value

The function returns the summary of the estimated gravity model as a survreg-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

14 et_tobit

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

Surv, survreg, tobit

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")
# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")</pre>
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
grav_small <- grav_small %>%
  mutate(
    flow = ifelse(flow < 5, 0, flow), # cutoff for testing purposes</pre>
    lgdp_o = log(gdp_o),
    lgdp_d = log(gdp_d)
  )
fit <- ek_tobit(</pre>
  dependent_variable = "flow",
  distance = "distw",
  additional_regressors = c("distw", "rta", "lgdp_o", "lgdp_d"),
  code_destination = "iso_d",
  robust = FALSE,
  data = grav_small
)
```

et_tobit

Eaton and Tamura (1995) threshold Tobit model (ET Tobit)

Description

et_tobit estimates gravity models in their additive form by conducting a left-censored regression.

Usage

```
et_tobit(dependent_variable, distance, additional_regressors = NULL, data, ...)
```

et_tobit 15

Arguments

dependent_variable

(Type: character) name of the dependent variable. Following Carson and Sun (2007), the smallest positive flow value is used as an estimate of the threshold, this value is added to the dependent_variable, the result is logged and taken as the dependent variable in the Tobit estimation with lower bound equal to the log of the smallest possible flow value.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDP should be inserted via the arguments income_origin and income_destination.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

et_tobit represents the Eaton and Tamura (1995) Tobit model which is often used when several gravity models are compared, instead of adding number 1 to the dependent variable as done in tobit, the constant added to the data is estimated and interpreted as a threshold.

When taking the log of the gravity equation flows equal to zero constitute a problem as their log is not defined. Therefore, a constant is added to the flows.

Compared to the usual ET-Tobit approaches, in this package, the estimation of the threshold is done before the other parameters are estimated.

We follow Carson and Sun (2007), who show that taking the minimum positive flow value as an estimate of the threshold is super-consistent and that using this threshold estimate ensures that the parameter MLE are asymptotically normal with the asymptotic variance identical to the variance achieved when the threshold is known. Hence, first the threshold is estimated as the minimum positive flow. This threshold is added to the flow variable, it is logged afterwards and taken as the dependent variable.

The Tobit estimation is then conducted using the censReg function and setting the lower bound equal to the log of the minimum positive flow value which was added to all observations.

A Tobit regression represents a combination of a binary and a linear regression. This procedure has to be taken into consideration when interpreting the estimated coefficients.

The marginal effects of an explanatory variable on the expected value of the dependent variable equals the product of both the probability of the latent variable exceeding the threshold and the marginal effect of the explanatory variable of the expected value of the latent variable.

For a more elaborate Tobit function, see ek_tobit for the Eaton and Kortum (2001) Tobit model where each zero trade volume is assigned a country specific interval with the upper bound equal to the minimum positive trade level of the respective importing country.

16 et_tobit

The function is designed for cross-sectional data, but can be extended to panel data using the censReg function.

A robust estimations is not implemented to the present as the censReg function is not compatible with the vcovHC function.

Value

The function returns the summary of the estimated gravity model as a censReg-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

fixed_effects 17

See Also

```
censReg, et_tobit
```

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")
# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")</pre>
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
grav_small <- grav_small %>%
  mutate(
    flow = ifelse(flow < 5, 0, flow), # cutoff for testing purposes
    lgdp_o = log(gdp_o),
    lgdp_d = log(gdp_d)
  )
fit <- et_tobit(</pre>
  dependent_variable = "flow",
  distance = "distw",
  additional_regressors = c("rta", "lgdp_o", "lgdp_d"),
  data = grav_small
)
```

fixed_effects

Fixed Effects

Description

fixed_effects estimates gravity models via OLS and fixed effects for the countries of origin and destination.

Usage

```
fixed_effects(
  dependent_variable,
  distance,
  additional_regressors = NULL,
  code_origin,
  code_destination,
  robust = FALSE,
  data,
  ...
)
```

18 fixed_effects

Arguments

dependent_variable

(Type: character) name of the dependent variable. This variable is logged and then used as the dependent variable in the estimation.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDPs can be added but those variables have to be logged first.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

code_origin

(Type: character) country of origin variable (e.g. ISO-3 country codes). The variables are grouped using this parameter.

code_destination

(Type: character) country of destination variable (e.g. country ISO-3 codes).

The variables are grouped using this parameter.

robust (Type: logical) whether robust fitting should be used. By default this is set to

FALSE.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

To account for MR terms, Feenstra (2002) and Feenstra (2015) propose to use importer and exporter fixed effects. Due to the use of these effects, all unilateral influences such as GDPs can no longer be estimated.

A disadvantage of the use of fixed_effects is that, when applied to panel data, the number of country-year or country-pair fixed effects can be too high for estimation. In addition, no comparative statistics are possible with fixed_effects as the Multilateral Resistance terms are not estimated explicitly. Nevertheless, Head and Mayer (2014) highlight the importance of the use of fixed effects.

By including country specific fixed effects, all monadic effects are captured, including Multilateral Resistance terms. Therefore, no other unilateral variables such as GDP can be included as independent variables in the estimation.

fixed_effects estimation can be used for both, cross-sectional as well as panel data.

Nonetheless, the function is designed to be consistent with the Stata code for cross-sectional data provided at the website Gravity Equations: Workhorse, Toolkit, and Cookbook when choosing robust estimation.

The function fixed_effects was therefore tested for cross-sectional data. Its up to the user to ensure that the functions can be applied to panel data.

Also, note that by including bilateral fixed effects such as country-pair effects, the coefficients of time-invariant observables such as distance can no longer be estimated.

Depending on the specific model, the code of the respective function might have to be changed in order to exclude the distance variable from the estimation.

fixed_effects 19

At the very least, the user should take special care with respect to the meaning of the estimated coefficients and variances as well as the decision about which effects to include in the estimation.

When using panel data, the parameter and variance estimation of the models may have to be changed accordingly.

For a comprehensive overview of gravity models for panel data see Egger and Pfaffermayr (2003), Gómez-Herrera (2013) and Head et al. (2010) as well as the references therein.

Value

The function returns the summary of the estimated gravity model as an 1m-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

20 gpml

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

```
lm, coeftest, vcovHC
```

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")
# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")</pre>
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
fit <- fixed_effects(</pre>
  dependent_variable = "flow",
  distance = "distw",
  additional_regressors = c("rta", "comcur", "contig"),
  code_origin = "iso_o",
  code_destination = "iso_d",
  robust = FALSE,
  data = grav_small
)
```

gpml

Gamma Pseudo Maximum Likelihood (GPML)

Description

gpml estimates gravity models in their multiplicative form via Gamma Pseudo Maximum Likelihood.

Usage

```
gpml(
  dependent_variable,
  distance,
  additional_regressors,
  robust = FALSE,
  data,
  ...
)
```

gpml 21

Arguments

dependent_variable

(Type: character) name of the dependent variable. This variable is logged and then used as the dependent variable in the estimation.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDPs can be added but those variables have to be logged first. Interaction terms can be added.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

robust (Type: logical) whether robust fitting should be used. By default this is set to

FALSE.

data (Type: data.frame) the dataset to be used.

. . . Additional arguments to be passed to the function.

Details

gpml is an estimation method for gravity models belonging to generalized linear models. It is described in Silva and Tenreyro (2006) and the model is estimated via glm2 using the gamma distribution and a log-link.

For similar functions, utilizing the multiplicative form via the log-link, but different distributions, see ppml, nls, and nbpml.

gpml estimation can be used for both, cross-sectional as well as panel data, but its up to the user to ensure that the functions can be applied to panel data.

Depending on the panel dataset and the variables - specifically the type of fixed effects - included in the model, it may easily occur that the model is not computable.

Also, note that by including bilateral fixed effects such as country-pair effects, the coefficients of time-invariant observables such as distance can no longer be estimated.

Depending on the specific model, the code of the respective function might have to be changed in order to exclude the distance variable from the estimation.

At the very least, the user should take special care with respect to the meaning of the estimated coefficients and variances as well as the decision about which effects to include in the estimation.

When using panel data, the parameter and variance estimation of the models may have to be changed accordingly.

For a comprehensive overview of gravity models for panel data see Egger and Pfaffermayr (2003), Gómez-Herrera (2013) and Head et al. (2010).

Value

The function returns the summary of the estimated gravity model similar to a glm-object.

22 gpml

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

glm2, coeftest, vcovHC

gravity_no_zeros 23

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")
# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")</pre>
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
grav_small <- grav_small %>%
  mutate(
    lgdp_o = log(gdp_o),
    lgdp_d = log(gdp_d)
  )
fit <- gpml(
  dependent_variable = "flow",
  distance = "distw",
  additional_regressors = c("rta", "iso_o", "iso_d"),
  data = grav_small
)
```

gravity_no_zeros

Gravity dataset without zero trade flows

Description

An edited version of the full gravity dataset: The "square" gravity dataset for all possible pairs of Countries worldwide, 1948-2006, which is used in the article: Head, K., T. Mayer and J. Ries, 2010, "The erosion of colonial linkages after independence". Journal of International Economics, 81(1):1-14 (lead article). Dataset gravity_no_zeros corresponds to the dataset without zero trade flows, gravity_zeros, on the other hand, includes zero trade flows.

Usage

```
data("gravity_no_zeros")
```

Format

A data frame with 17088 observations on the following 10 variables.

```
iso_o ISO-Code of country of originiso_d ISO-Code of country of destinationdistw weighted distancegdp_o GDP of country of origin in million dollarsgdp_d GDP of country of destination in million dollars
```

24 gravity_zeros

```
rta regional trade agreement dummy
flow trade flow in million dollars
contig contiguity dummy
comlang_off common official language dummy
comcur common currency dummy
```

Source

```
https://sites.google.com/site/hiegravity/data-sources
```

References

Head, K. and Mayer, T. (2014). Chapter 3 - gravity equations: Workhorse, toolkit, and cookbook. In Gita Gopinath, E. H. and Rogoff, K., editors, Handbook of International Economics, volume 4 of Handbook of International Economics, pages 131-195. Elsevier. (Gravity Equations: Workhorse, Toolkit, and Cookbook)

Head, K., T. Mayer and J. Ries, 2010, "The erosion od colonial linkages after independence". Journal of International Economics, 81(1):1-14 (lead article).

Examples

```
data(gravity_no_zeros)
str(gravity_no_zeros)
```

gravity_zeros

Gravity dataset without zero trade flows

Description

An edited version of the full gravity dataset: The "square" gravity dataset for all possible pairs of Countries worldwide, 1948-2006, which is used in the article: Head, K., T. Mayer and J. Ries, 2010, "The erosion of colonial linkages after independence". Journal of International Economics, 81(1):1-14 (lead article). Dataset gravity_no_zeros corresponds to the dataset without zero trade flows, gravity_zeros, on the other hand, includes zero trade flows.

Usage

```
data("gravity_zeros")
```

Format

A data frame with 22588 observations on the following 10 variables.

```
iso_o ISO-Code of country of origin
iso_d ISO-Code of country of destination
distw weighted distance
```

hm_summary 25

```
gdp_o GDP of country of origin in million dollars
gdp_d GDP of country of destination in million dollars
rta regional trade agreement dummy
flow trade flow in million dollars
contig contiguity dummy
comlang_off common official language dummy
comcur common currency dummy
```

Source

```
https://sites.google.com/site/hiegravity/data-sources
```

References

Head, K. and Mayer, T. (2014). Chapter 3 - gravity equations: Workhorse, toolkit, and cookbook. In Gita Gopinath, E. H. and Rogoff, K., editors, Handbook of International Economics, volume 4 of Handbook of International Economics, pages 131-195. Elsevier. (Gravity Equations: Workhorse, Toolkit, and Cookbook)

Head, K., T. Mayer and J. Ries, 2010, "The erosion od colonial linkages after independence". Journal of International Economics, 81(1):1-14 (lead article).

Examples

```
data(gravity_zeros)
str(gravity_zeros)
```

hm_summary

Head and Mayer consistent summary statistics

Description

Summary of estimates function that, if is used with default options, provides estimation results are consistent with the Stata methods used in Head and Mayer (2014). This function is adapted from the work of Isidore Beautrelet.

Usage

```
hm_summary(model, robust = FALSE, ...)
```

26 log_distance

Arguments

robust

model (Type: lm) Regression object obtained by using the estimation methods from

this package or a generic method such as 1m or g1m. Some particular classes

(gpml, nbpml, negbin and nls) don't return R squared and F statistic.

(Type: logical) Determines whether a robust variance-covariance matrix should

be used. By default is set to FALSE.

If set TRUE the estimation results are consistent with the Stata code provided at the website Gravity Equations: Workhorse, Toolkit, and Cookbook when choos-

ing robust estimation.

... additional arguments to be passed to tobit.

Value

Summary 1m object.

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")
# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")</pre>
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
# Using OLS for testing
fit <- ols(
 dependent_variable = "flow",
 distance = "distw",
 additional_regressors = c("rta", "contig", "comcur"),
 income_origin = "gdp_o",
 income_destination = "gdp_d",
 code_origin = "iso_o",
 code_destination = "iso_d",
 uie = FALSE,
 robust = FALSE,
 data = grav_small
)
fit2 <- hm_summary(fit, robust = FALSE)</pre>
```

log_distance

Apply logarithm to distance column

Description

log_distance creates a new dist_log column in log scale by taking the original distance column in the data

nbpml 27

Usage

```
log_distance(data, distance)
```

Arguments

data (Type: data.frame) the dataset to be used.

distance The distance column

Value

The function returns the summary of the estimated gravity model as an 1m-object.

See Also

```
lm, coeftest, vcovHC
```

Examples

```
log_distance(gravity_zeros, "distw")
```

nbpml

Negative Binomial Pseudo Maximum Likelihood (NBPML)

Description

nbpml estimates gravity models in their multiplicative form via Negative Binomial Pseudo Maximum Likelihood.

Usage

```
nbpml(
  dependent_variable,
  distance,
  additional_regressors,
  robust = FALSE,
  data,
  ...
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. This variable is logged and then used as the dependent variable in the estimation.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

28 nbpml

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDPs can be added but those variables have to be logged first. Interaction terms can be added.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

robust (Type: logical) whether robust fitting should be used. By default this is set to

FALSE.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

nbpml is an estimation method for gravity models belonging to generalized linear models. It is estimated via glm.nb using the negative binomial distribution and a log-link.

For similar functions, utilizing the multiplicative form via the log-link, but different distributions, see nbpml, gpml, and nls.

gpml estimation can be used for both, cross-sectional as well as panel data, but its up to the user to ensure that the functions can be applied to panel data.

Depending on the panel dataset and the variables - specifically the type of fixed effects - included in the model, it may easily occur that the model is not computable.

Also, note that by including bilateral fixed effects such as country-pair effects, the coefficients of time-invariant observables such as distance can no longer be estimated.

Depending on the specific model, the code of the respective function may has to be changed in order to exclude the distance variable from the estimation.

At the very least, the user should take special care with respect to the meaning of the estimated coefficients and variances as well as the decision about which effects to include in the estimation. When using panel data, the parameter and variance estimation of the models may have to be changed accordingly.

For a comprehensive overview of gravity models for panel data see Egger and Pfaffermayr (2003), Gómez-Herrera (2013) and Head et al. (2010).

Value

The function returns the summary of the estimated gravity model similar to a glm-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

nbpml 29

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

```
glm.nb, coeftest, vcovHC
```

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")

# Choose 3 countries for testing
countries_chosen <- c("AUS", "GBR", "CAN")
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)

fit <- nbpml(
    dependent_variable = "flow",</pre>
```

30 nls

```
distance = "distw",
  additional_regressors = c("rta", "iso_o", "iso_d"),
  data = grav_small
)
```

nls

Non-linear Least Squares (NLS)

Description

nls estimates gravity models in their multiplicative form via Nonlinear Least Squares.

Usage

```
nls(dependent_variable, distance, additional_regressors = NULL, data, ...)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. This variable is logged and then used as the dependent variable in the estimation.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDPs can be added but those variables have to be logged first. Interaction terms can be added.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

data

(Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

nls is an estimation method for gravity models belonging to generalized linear models. It is estimated via glm using the gaussian distribution and a log-link.

As the method may not lead to convergence when poor starting values are used, the linear predictions, fitted values, and estimated coefficients resulting from a ppml estimation are used for the arguments etastart, mustart, and start.

For similar functions, utilizing the multiplicative form via the log-link, but different distributions, see ppml, gpml, and nbpml.

nls estimation can be used for both, cross-sectional as well as panel data, but its up to the user to ensure that the functions can be applied to panel data.

nls 31

Depending on the panel dataset and the variables - specifically the type of fixed effects - included in the model, it may easily occur that the model is not computable.

Also, note that by including bilateral fixed effects such as country-pair effects, the coefficients of time-invariant observables such as distance can no longer be estimated.

Depending on the specific model, the code of the respective function may has to be changed in order to exclude the distance variable from the estimation.

At the very least, the user should take special care with respect to the meaning of the estimated coefficients and variances as well as the decision about which effects to include in the estimation. When using panel data, the parameter and variance estimation of the models may have to be changed accordingly.

For a comprehensive overview of gravity models for panel data see Egger and Pfaffermayr (2003), Gómez-Herrera (2013) and Head et al. (2010) as well as the references therein.

Value

The function returns the summary of the estimated gravity model similar to a glm-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

```
glm, coeftest, vcovHC
```

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")
# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")</pre>
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)</pre>
grav_small <- grav_small %>%
 mutate(
   lgdp_o = log(gdp_o),
    lgdp_d = log(gdp_d)
fit <- nls(
 dependent_variable = "flow",
 distance = "distw",
 additional_regressors = c("rta", "lgdp_o", "lgdp_d"),
 data = grav_small
)
```

Ordinary Least Squares (OLS)

Description

ols estimates gravity models in their traditional form via Ordinary Least Squares (ols). It does not consider Multilateral Resistance terms.

ols

Usage

```
ols(
   dependent_variable,
   distance,
   additional_regressors = NULL,
   income_origin,
   income_destination,
   code_origin,
   code_destination,
   uie = FALSE,
   robust = FALSE,
   data,
   ...
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable.

If uie = TRUE the dependent variable is divided by the product of unilateral incomes (e.g. income_origin and income_destination) and logged afterwards. If uie=FALSE the dependent variable is logged directly. The transformed variable is then used as the dependent variable and the logged income variables are used as independent variables in the estimation.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDPs can be added but those variables have to be logged first. Interaction terms can be added.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

income_origin (Type: character) origin income variable (e.g. GDP) in the dataset.

income_destination

(Type: character) destination income variable (e.g. GDP) in the dataset.

code_origin (Type: character) country of origin variable (e.g. ISO-3 country codes). The variables are grouped using this parameter.

code_destination

(Type: character) country of destination variable (e.g. country ISO-3 codes). The variables are grouped using this parameter.

uie

(Type: logical) Dtermines whether the parameters are to be estimated assuming unitary income elasticities. The default value is set to FALSE.

robust

(Type: logical) whether robust fitting should be used. By default this is set to FALSE.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

ols estimates gravity models in their traditional, additive, form via Ordinary Least Squares using the 1m function. Multilateral Resistance terms are not considered by this function.

As the coefficients for the country's incomes were often found to be close to unitary and unitary income elasticities are in line with some theoretical foundations on international trade, it is sometimes assumed that the income elasticities are equal to unity.

In order to allow for the estimation with and without the assumption of unitary income elasticities, the option uie is built into ols with the default set to FALSE.

ols estimation can be used for both, cross-sectional and panel data. Nonetheless, the function is designed to be consistent with the Stata code for cross-sectional data provided at the website Gravity Equations: Workhorse, Toolkit, and Cookbook when choosing robust estimation.

The function ols was therefore tested for cross-sectional data. For the use with panel data no tests were performed. Therefore, it is up to the user to ensure that the functions can be applied to panel data.

Depending on the panel dataset and the variables - specifically the type of fixed effects - included in the model, it may easily occur that the model is not computable. Also, note that by including bilateral fixed effects such as country-pair effects, the coefficients of time-invariant observables such as distance can no longer be estimated.

Depending on the specific model, the code of the respective function may has to be changed in order to exclude the distance variable from the estimation.

At the very least, the user should take special care with respect to the meaning of the estimated coefficients and variances as well as the decision about which effects to include in the estimation. When using panel data, the parameter and variance estimation of the models may have to be changed accordingly.

For a comprehensive overview of gravity models for panel data see Egger and Pfaffermayr (2003), Gómez-Herrera (2013) and Head et al. (2010) as well as the references therein.

Value

The function returns the summary of the estimated gravity model as an 1m-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

lm, coeftest, vcovHC

Examples

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")

# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)

fit <- ols(
   dependent_variable = "flow",
   distance = "distw",
   additional_regressors = c("rta", "contig", "comcur"),
   income_origin = "gdp_o",</pre>
```

36 ppml

```
income_destination = "gdp_d",
code_origin = "iso_o",
code_destination = "iso_d",
uie = FALSE,
robust = FALSE,
data = grav_small
)
```

ppml

Poisson Pseudo Maximum Likelihood (PPML)

Description

ppml estimates gravity models in their multiplicative form via Poisson Pseudo Maximum Likelihood.

Usage

```
ppml(
  dependent_variable,
  distance,
  additional_regressors,
  robust = FALSE,
  data,
  ...
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. This variable is used as the dependent variable in the estimation.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDPs can be added but those variables have to be logged first. Interaction terms can be added.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

robust

(Type: logical) whether robust fitting should be used. By default this is set to FALSE.

data

(Type: data.frame) the dataset to be used.

. . .

Additional arguments to be passed to the function.

ppml 37

Details

ppml is an estimation method for gravity models belonging to generalized linear models. It is estimated via glm using the quasipoisson distribution and a log-link. ppml is presented in Silva and Tenreyro (2006).

For similar functions, utilizing the multiplicative form via the log-link, but different distributions, see gpml, nls, and nbpml.

ppml estimation can be used for both, cross-sectional as well as panel data. The function is designed to be consistent with the results from the Stata function ppml written by Silva and Tenreyro (2006).

The function ols was therefore tested for cross-sectional data. For the use with panel data no tests were performed. Therefore, it is up to the user to ensure that the functions can be applied to panel data.

Depending on the panel dataset and the variables - specifically the type of fixed effects - included in the model, it may easily occur that the model is not computable. Also, note that by including bilateral fixed effects such as country-pair effects, the coefficients of time-invariant observables such as distance can no longer be estimated.

Depending on the specific model, the code of the respective function may has to be changed in order to exclude the distance variable from the estimation.

At the very least, the user should take special care with respect to the meaning of the estimated coefficients and variances as well as the decision about which effects to include in the estimation. When using panel data, the parameter and variance estimation of the models may have to be changed accordingly.

For a comprehensive overview of gravity models for panel data see Egger and Pfaffermayr (2003), Gómez-Herrera (2013) and Head et al. (2010) as well as the references therein.

Value

The function returns the summary of the estimated gravity model as an glm-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

38 ppml

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762.

See Also

```
glm, coeftest, vcovHC
```

and the references therein.

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")

# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)

fit <- ppml(
    dependent_variable = "flow",
    distance = "distw",
    additional_regressors = c("rta", "iso_o", "iso_d"),
    data = grav_small
)</pre>
```

sils 39

sils

Structural Iterated Least Squares (SILS)

Description

sils estimates gravity models via Structural Iterated Least Squares and an explicit inclusion of the Multilateral Resistance terms.

Usage

```
sils(
  dependent_variable,
  distance,
  additional_regressors = NULL,
  income_origin,
  income_destination,
  code_origin,
  code_destination,
  maxloop = 100,
  decimal_places = 4,
  robust = FALSE,
  verbose = FALSE,
  data,
  ...
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. This dependent variable is divided by the product of unilateral incomes such (i.e. income_origin and income_destination) and logged afterwards.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDP should be inserted via the arguments income_origin and income_destination. As country specific effects are subdued due to demeaning, no further unilateral variables apart from incomes can be added.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

income_origin (Type: character) origin income variable (e.g. GDP) in the dataset. income_destination

(Type: character) destination income variable (e.g. GDP) in the dataset.

40 sils

code_origin (Type: character) country of origin variable (e.g. ISO-3 country codes). The

variables are grouped using this parameter.

code_destination

(Type: character) country of destination variable (e.g. country ISO-3 codes).

The variables are grouped using this parameter.

maxloop (Type: numeric) maximum number of outer loop iterations. The default is set to

100. There will be a warning if the iterations did not converge.

decimal_places (Type: numeric) number of decimal places that should not change after a new

iteration for the estimation to stop. The default is set to 4.

robust (Type: logical) whether robust fitting should be used. By default this is set to

FALSE.

verbose (Type: logical) determines whether the estimated coefficients of each iteration

should be printed in the console. The default is set to FALSE.

data (Type: data.frame) the dataset to be used.

. . . Additional arguments to be passed to the function.

Details

sils is an estimation method for gravity models developed by Head and Mayer (2014).

The function sils utilizes the relationship between the Multilateral Resistance terms and the transaction costs. The parameters are estimated by an iterative procedure. The function executes loops until the parameters stop changing significantly.

sils is designed to be consistent with the Stata code provided at Gravity Equations: Workhorse, Toolkit, and Cookbook when choosing robust estimation.

As, to our knowledge at the moment, there is no explicit literature covering the estimation of a gravity equation by sils using panel data, and we do not recommend to apply this method in this case.

Value

The function returns the summary of the estimated gravity model as an lm-object. It furthermore returns the resulting coefficients for each iteration.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

sils 41

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

lm, coeftest, vcovHC

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")

# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)

fit <- sils(
    dependent_variable = "flow",
    distance = "distw",
    additional_regressors = "rta",
    income_origin = "gdp_o",
    income_destination = "gdp_d",
    code_origin = "iso_o",
    code_destination = "iso_d",</pre>
```

42 tetrads

```
maxloop = 50,
dec_places = 3,
robust = FALSE,
verbose = FALSE,
data = grav_small
)
```

tetrads

Tetrads

Description

tetrads estimates gravity models by taking the ratio of the ratio of flows.

Usage

```
tetrads(
  dependent_variable,
  distance,
  additional_regressors,
  code_origin,
  code_destination,
  filter_origin = NULL,
  filter_destination = NULL,
  multiway = FALSE,
  data,
  ...
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. This variable is logged and then used as the dependent variable in the estimation.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDP should be inserted via the arguments income_origin and income_destination.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

code_origin

(Type: character) country of origin variable (e.g. ISO-3 country codes). The variables are grouped using this parameter.

code_destination

(Type: character) country of destination variable (e.g. country ISO-3 codes). The variables are grouped using this parameter.

tetrads 43

filter_origin (Type: character) Reference exporting country.

filter_destination

(Type: character) Reference importing country.

multiway (Type: logical) in case multiway = TRUE, the cluster.vcov function is used for

estimation following Cameron et al. (2011) multi-way clustering of variance-

covariance matrices. The default value is set to TRUE.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

tetrads is an estimation method for gravity models developed by Head et al. (2010).

The function tetrads utilizes the multiplicative form of the gravity equation. After choosing a reference exporter A and importer B one can eliminate importer and exporter fixed effects by taking the ratio of ratios.

Only those exporters trading with the reference importer and importers trading with the reference exporter will remain for the estimation. Therefore, reference countries should preferably be countries which trade with every other country in the dataset.

After restricting the data in this way, tetrads estimates the gravity equation in its additive form by OLS.

By taking the ratio of ratios, all monadic effects diminish, hence no unilateral variables such as GDP can be included as independent variables.

tetrads estimation can be used for both, cross-sectional as well as panel data. Nonetheless, the function is designed to be consistent with the Stata code for cross-sectional data provided on the website Gravity Equations: Workhorse, Toolkit, and Cookbook when choosing robust estimation.

The function tetrads was therefore tested for cross-sectional data.

If tetrads is used for panel data, the user may have to drop distance as an independent variable as time-invariant effects drop.

For applying tetrads to panel data see Head et al. (2010).

Value

The function returns the summary of the estimated gravity model as an 1m-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

44 tetrads

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

lm, coeftest,

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")

# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)

fit <- tetrads(
   dependent_variable = "flow",
   distance = "distw",
   additional_regressors = "rta",
   code_origin = "iso_o",</pre>
```

```
code_destination = "iso_d",
  filter_origin = countries_chosen[1],
 filter_destination = countries_chosen[2],
 data = grav_small
)
```

tobit

Left-censored Tobit model with known threshold

Description

tobit estimates gravity models in their additive form by conducting a left-censored regression, which, after adding the constant 1 to the dependent variable, utilizes log(1) = 0 as the censoring value.

Usage

```
tobit(
  dependent_variable,
  distance,
  additional_regressors = NULL,
  added_constant = 1,
  data,
)
```

Arguments

dependent_variable

(Type: character) name of the dependent variable. The number 1 is added and the transformed variable is logged and taken as the dependent variable in the tobit estimation with lower bound equal to 0 as log(1) = 0 represents the smallest flows in the transformed variable.

distance

(Type: character) name of the distance variable that should be taken as the key independent variable in the estimation. The distance is logged automatically when the function is executed.

additional_regressors

(Type: character) names of the additional regressors to include in the model (e.g. a dummy variable to indicate contiguity). Unilateral metric variables such as GDP should be inserted via the arguments income_origin and income_destination.

Write this argument as c(contiguity, common currency, ...). By default this is set to NULL.

added_constant (Type: numeric) the constant to be added to the dependent variable. The default value is 1. The minimum of log(y + added_constant) is taken as the left boundary in the Tobit model.

> In the often used case of added_constant = 1, the dependent variable is leftcensored at value 0 as log(1) = 0.

data (Type: data.frame) the dataset to be used.

... Additional arguments to be passed to the function.

Details

tobit represents the left-censored tobit Tobin (1958) approach utilizing a known censoring threshold which is often used when several gravity models are compared.

When taking the log of the gravity equation flows equal to zero constitute a problem as their log is not defined.

Therefore, in the execution of the function the number 1 is added to all flows and the log(flows+1) is taken as the dependent variable.

The tobit estimation is conducted using the censReg function and setting the lower bound equal to θ as $\log(1)=\theta$ represents the smallest flows in the transformed variable.

A tobit regression represents a combination of a binary and a linear regression.

This procedure has to be taken into consideration when interpreting the estimated coefficients.

The marginal effects of an explanatory variable on the expected value of the dependent variable equals the product of both the probability of the latent variable exceeding the threshold and the marginal effect of the explanatory variable of the expected value of the latent variable.

The function is designed for cross-sectional data, but can be easily extended to panel data using the censReg function.

A robust estimations is not implemented to the present as the censReg function is not compatible with the vcovHC function.

For a more elaborate Tobit function, see ek_tobit for the Eaton and Kortum (2001) Tobit model where each zero trade volume is assigned a country specific interval with the upper bound equal to the minimum positive trade level of the respective importing country.

Value

The function returns the summary of the estimated gravity model as a censReg-object.

References

For more information on gravity models, theoretical foundations and estimation methods in general see

Anderson JE (1979). "A Theoretical Foundation for the Gravity Equation." *The American Economic Review*, **69**(1), 106–116. ISSN 00028282.

Anderson JE, van Wincoop E (2001). "Gravity with Gravitas: A Solution to the Border Puzzle." Working Paper 8079, National Bureau of Economic Research. doi: 10.3386/w8079.

Anderson JE (2010). "The Gravity Model." Working Paper 16576, National Bureau of Economic Research. doi: 10.3386/w16576.

Baier SL, Bergstrand JH (2009). "Bonus vetus OLS: A simple method for approximating international trade-cost effects using the gravity equation." *Journal of International Economics*, **77**(1), 77 - 85. ISSN 0022-1996, doi: 10.1016/j.jinteco.2008.10.004.

Baier SL, Bergstrand JH (2010). "The Gravity Model in International Trade: Advances and Applications." In van Bergeijk PAG, Brakman S (eds.), chapter 4. Cambridge University Press. doi: 10.1017/CBO9780511762109.

Feenstra RC (2002). "Border effects and the gravity equation: consistent methods for estimation." *Scottish Journal of Political Economy*, **49**(5), 491–506.

Head K, Mayer T, Ries J (2010). "The erosion of colonial trade linkages after independence." *Journal of International Economics*, **81**(1), 1 - 14. ISSN 0022-1996, doi: 10.1016/j.jinteco.2010.01.002.

Head K, Mayer T (2014). "Chapter 3 - Gravity Equations: Workhorse, Toolkit, and Cookbook." In Gopinath G, Helpman E, Rogoff K (eds.), *Handbook of International Economics*, volume 4 of *Handbook of International Economics*, 131 - 195. Elsevier. doi: 10.1016/B9780444543141.00003-3.

Silva JMCS, Tenreyro S (2006). "The Log of Gravity." *The Review of Economics and Statistics*, **88**(4), 641-658. doi: 10.1162/rest.88.4.641.

and the citations therein.

See Gravity Equations: Workhorse, Toolkit, and Cookbook for gravity datasets and Stata code for estimating gravity models.

For estimating gravity equations using panel data see

Egger P, Pfaffermayr M (2003). "The proper panel econometric specification of the gravity equation: A three-way model with bilateral interaction effects." *Empirical Economics*, **28**(3), 571–580. ISSN 1435-8921, doi: 10.1007/s001810200146.

Gómez-Herrera E (2013). "Comparing alternative methods to estimate gravity models of bilateral trade." *Empirical Economics*, **44**(3), 1087–1111. ISSN 1435-8921, doi: 10.1007/s0018101205762. and the references therein.

See Also

censReg

```
# Example for CRAN checks:
# Executable in < 5 sec
library(dplyr)
data("gravity_no_zeros")

# Choose 5 countries for testing
countries_chosen <- c("AUS", "CHN", "GBR", "BRA", "CAN")
grav_small <- filter(gravity_no_zeros, iso_o %in% countries_chosen)

grav_small <- grav_small %>%
    mutate(
    lgdp_o = log(gdp_o),
    lgdp_d = log(gdp_d)
)

fit <- tobit(
    dependent_variable = "flow",</pre>
```

```
distance = "distw",
  additional_regressors = c("rta", "lgdp_o", "lgdp_d"),
  added_constant = 1,
  data = grav_small
)
```

Index

```
* datasets
                                                     survreg, 12–14
    gravity_no_zeros, 23
                                                     tetrads, 42
    gravity_zeros, 24
                                                     tobit, 13–15, 45
bvu, 2
                                                     vcovHC, 4, 7, 10, 11, 16, 20, 22, 27, 29, 32, 35,
bvw, 5
                                                               38, 41, 46
censReg, 15-17, 46, 47
cluster.vcov, 43
coeftest, 4, 7, 10, 11, 20, 22, 27, 29, 32, 35,
         38, 41, 44
ddm, 8
discard_unusable, 11
ek_tobit, 11, 15, 46
et_tobit, 13, 14, 17
fixed_effects, 17
glm, 21, 28, 30–32, 37, 38
glm.nb, 28, 29
glm2, 21, 22
gpm1, 20, 28, 30, 37
gravity_no_zeros, 23
gravity_zeros, 24
hm_summary, 25
lm, 3, 4, 6, 7, 9–11, 19, 20, 27, 34, 35, 40, 41,
         43, 44
log\_distance, 26
nbpml, 21, 27, 28, 30, 37
nls, 21, 28, 30, 37
ols, 32
ppm1, 21, 30, 36
sils, 39
Surv, 12, 14
```