

# Package ‘gtsummary’

January 12, 2023

**Title** Presentation-Ready Data Summary and Analytic Result  
Tables

**Version** 1.7.0

**Description** Creates presentation-ready tables summarizing data sets, regression models, and more. The code to create the tables is concise and highly customizable. Data frames can be summarized with any function, e.g. `mean()`, `median()`, even user-written functions. Regression models are summarized and include the reference rows for categorical variables. Common regression models, such as logistic regression and Cox proportional hazards regression, are automatically identified and the tables are pre-filled with appropriate column headers.

**License** MIT + file LICENSE

**URL** <https://github.com/ddsjoberg/gtsummary>,  
<https://www.danielsjoberg.com/gtsummary/>

**BugReports** <https://github.com/ddsjoberg/gtsummary/issues>

**Depends** R (>= 3.4)

**Imports** broom (>= 1.0.1),  
broom.helpers (>= 1.11.0),  
cli (>= 3.1.1),  
dplyr (>= 1.0.7),  
forcats (>= 0.5.1),  
glue (>= 1.6.0),  
gt (>= 0.8.0),  
knitr (>= 1.37),  
lifecycle (>= 1.0.1),  
purrr (>= 0.3.4),  
rlang (>= 1.0.3),  
stringr (>= 1.4.0),  
tibble (>= 3.1.6),  
tidyr (>= 1.1.4),  
vctrs (>= 0.5.1)

**Suggests** aod (>= 1.3.1),  
broom.mixed (>= 0.2.9),  
car (>= 3.0-11),  
cmprsk,  
covr,

effectsize ( $\geq$  0.6.0),  
 emmeans ( $\geq$  1.7.3),  
 flextable ( $\geq$  0.8.1),  
 geepack,  
 ggstats ( $\geq$  0.2.1),  
 Hmisc,  
 huxtable ( $\geq$  5.4.0),  
 insight ( $\geq$  0.15.0),  
 kableExtra ( $\geq$  1.3.4),  
 lme4,  
 mgcv,  
 mice ( $\geq$  3.10.0),  
 nnet,  
 officer,  
 openxlsx,  
 parameters ( $\geq$  0.19.0),  
 parsnip ( $\geq$  0.1.7),  
 rmarkdown,  
 sandwich ( $\geq$  3.0.1),  
 scales,  
 smd ( $\geq$  0.6.6),  
 spelling ( $\geq$  2.2),  
 survey,  
 survival ( $\geq$  3.2-11),  
 testthat ( $\geq$  3.0.4),  
 tidycmprsk ( $\geq$  0.1.2),  
 workflows ( $\geq$  0.2.4)

**VignetteBuilder** knitr  
**RdMacros** lifecycle  
**Encoding** UTF-8  
**Language** en-US  
**LazyData** true  
**Roxygen** list(markdown = TRUE)  
**RoxygenNote** 7.2.3  
**Config/testthat/edition** 3  
**Config/testthat/parallel** true  
**Config/Needs/website** lubridate

## R topics documented:

add_ci . . . . .	4
add_difference . . . . .	6
add_glance . . . . .	8
add_global_p . . . . .	11
add_n.tbl_summary . . . . .	12
add_n.tbl_survfit . . . . .	14
add_nevent.tbl_survfit . . . . .	15
add_nevent_regression . . . . .	16
add_n_regression . . . . .	17

add_overall	18
add_p.tbl_continuous	20
add_p.tbl_cross	21
add_p.tbl_summary	22
add_p.tbl_survfit	24
add_p.tbl_svysummary	26
add_q	28
add_significance_stars	29
add_stat	31
add_stat_label	34
add_vif	35
as_flex_table	36
as_gt	38
as_hux_table	39
as_kable	40
as_kable_extra	41
as_tibble.gtsummary	43
bold_italicize_labels_levels	44
bold_p	46
combine_terms	47
continuous_summary	48
custom_tidiers	49
inline_text.gtsummary	52
inline_text.tbl_cross	52
inline_text.tbl_regression	53
inline_text.tbl_summary	55
inline_text.tbl_survfit	56
inline_text.tbl_uvregression	58
modify	60
modify_column_alignment	63
modify_column_hide	63
modify_column_indent	64
modify_column_merge	65
modify_fmt_fun	67
modify_table_body	68
modify_table_styling	69
plot	71
proportion_summary	72
ratio_summary	74
remove_row_type	75
select_helpers	76
separate_p_footnotes	77
set_gtsummary_theme	78
sort_filter_p	80
style_number	81
style_percent	82
style_pvalue	83
style_ratio	84
style_sigfig	85
tbl_butcher	86
tbl_continuous	87
tbl_cross	88

tbl_custom_summary . . . . .	90
tbl_merge . . . . .	94
tbl_regression . . . . .	96
tbl_split . . . . .	98
tbl_stack . . . . .	99
tbl_strata . . . . .	101
tbl_summary . . . . .	104
tbl_survfit . . . . .	108
tbl_svsummary . . . . .	110
tbl_uvregression . . . . .	114
theme_gtsummary . . . . .	117
trial . . . . .	119

<b>Index</b>	<b>121</b>
--------------	------------

---

add_ci	<i>Add CI Column</i>
--------	----------------------

---

## Description

Add a new column with the confidence intervals for proportions, means, etc.

## Usage

```
add_ci(x, ...)
```

```
## S3 method for class 'tbl_summary'
```

```
add_ci(
  x,
  method = NULL,
  include = everything(),
  statistic = NULL,
  conf.level = 0.95,
  style_fun = NULL,
  pattern = NULL,
  df = NULL,
  ...
)
```

```
## S3 method for class 'tbl_svsummary'
```

```
add_ci(
  x,
  method = NULL,
  include = everything(),
  statistic = NULL,
  conf.level = 0.95,
  style_fun = NULL,
  pattern = NULL,
  df = NULL,
  ...
)
```

**Arguments**

x	A <code>tbl_summary</code> or a <code>tbl_svysummary</code> object
...	Not used
method	Confidence interval method. Default is <code>list(all_categorical() ~ "wilson", all_continuous() ~ "t.test")</code> for <code>tbl_summary</code> objects and <code>list(all_categorical() ~ "svyprop", all_continuous() ~ "svymean")</code> for <code>tbl_svysummary</code> objects. See details below.
include	variables to include in the summary table. Default is <code>everything()</code>
statistic	Formula indicating how the confidence interval will be displayed. Default is <code>list(all_categorical() ~ "{conf.low}%, {conf.high}%", all_continuous() ~ "{conf.low}, {conf.high}")</code>
conf.level	Confidence level. Default is 0.95
style_fun	Function to style upper and lower bound of confidence interval. Default is <code>list(all_categorical() ~ purrr::partial(style_sigfig, scale = 100), all_continuous() ~ style_sigfig)</code> .
pattern	string indicating the pattern to use to merge the CI with the statistics cell. The default is <code>NULL</code> , where no columns are merged. The two columns that will be merged are the statistics column, represented by <code>"{stat}"</code> and the CI column represented by <code>"{ci}"</code> , e.g. <code>pattern = "{stat} ({ci})"</code> will merge the two columns with the CI in parentheses.
df	For <code>tbl_svysummary()</code> , the number of degrees of freedom used to estimate confidence intervals. By default, will use <code>survey::degf()</code> .

**Value**

gtsummary table

**method argument****for `tbl_summary` tables**

Must be one of `c("wilson", "wilson.no.correct", "exact", "asymptotic")` for categorical variables, and `c("t.test", "wilcox.test")` for continuous variables.

Methods `c("wilson", "wilson.no.correct")` are calculated with `prop.test(correct = c(TRUE, FALSE))`. The default method, "wilson", includes the Yates continuity correction. Methods `c("exact", "asymptotic")` are calculated with `Hmisc::binconf(method=)`.

Confidence intervals for means are calculated using `t.test()` and `wilcox.test()` for pseudo-medians.

**for `tbl_svysummary` tables**

Must be one of `c("svyprop", "svyprop.logit", "svyprop.likelihood", "svyprop.asin", "svyprop.beta", "svyprop.mean", "svyprop.xlogit")` for categorical variables, and `c("svymean", "svymedian", "svymedian.mean", "svymedian.beta", "svymedian.xlogit", "svymedian.asin", "svymedian.score")` for continuous variables.

Confidence intervals for proportions are computed with `survey::svyciprop()`. See the help file of this function for details on the different methods available to compute CIs. The default method "svyprop" is equivalent to "svyprop.logit", corresponding to a call to `survey::svyciprop()` with `method = "logit"`.

Confidence intervals for means (method "svymean") are computed using `confint(svymean())`.

Confidence intervals for medians are computed with `survey::svyquantile()`. See the help file of this function for details on the different methods available to compute CIs. The default method "svymedian" is equivalent to "svymedian.mean", corresponding to a call to `survey::svyquantile()` with `method = "mean"`.

## Example Output

## See Also

Review [list, formula, and selector syntax](#) used throughout `gtsummary`

## Examples

```
# Example 1 -----
add_ci_ex1 <-
  trial %>%
  select(marker, response, trt) %>%
  tbl_summary(
    missing = "no",
    statistic = all_continuous() ~ "{mean} ({sd})"
  ) %>%
  add_ci()

# Example 2 -----
add_ci_ex2 <-
  trial %>%
  select(response, grade) %>%
  tbl_summary(
    statistic = all_categorical() ~ "{p}%",
    missing = "no"
  ) %>%
  add_ci(pattern = "{stat} ({ci})") %>%
  modify_footnote(everything() ~ NA)

# Example 3 -----
data(api, package = "survey")
add_ci_ex3 <-
  survey::svydesign(id = ~dnum, weights = ~pw, data = apiclus1, fpc = ~fpc) %>%
  tbl_svysummary(
    include = c(api00, hsg, stype),
    statistic = hsg ~ "{mean} ({sd})"
  ) %>%
  add_ci(
    method = api00 ~ "svymedian"
  )
```

**Description**

Add the difference between two groups (typically mean difference), along with the difference confidence interval and p-value.

**Usage**

```
add_difference(
  x,
  test = NULL,
  group = NULL,
  adj.vars = NULL,
  test.args = NULL,
  conf.level = 0.95,
  include = everything(),
  pvalue_fun = NULL,
  estimate_fun = NULL
)
```

**Arguments**

x	"tbl_summary" or "tbl_svysummary" object
test	List of formulas specifying statistical tests to perform for each variable, e.g. <code>list(all_continuous() ~ "t.test")</code> . Common tests include "t.test" or "ancova" for continuous data, and "prop.test" for dichotomous variables. See <a href="#">tests</a> for details and more tests.
group	Column name (unquoted or quoted) of an ID or grouping variable. The column can be used to calculate p-values with correlated data. Default is NULL. See <a href="#">tests</a> for methods that utilize the <code>group=</code> argument.
adj.vars	Variables to include in mean difference adjustment (e.g. in ANCOVA models)
test.args	List of formulas containing additional arguments to pass to tests that accept arguments. For example, add an argument for all t-tests, use <code>test.args = all_tests("t.test") ~ list(var.equal = TRUE)</code>
conf.level	Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
include	Variables to include in output. Input may be a vector of quoted variable names, unquoted variable names, or <code>tidyselect</code> select helper functions. Default is <code>everything()</code> .
pvalue_fun	Function to round and format p-values. Default is <a href="#">style_pvalue</a> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
estimate_fun	List of formulas specifying the formatting functions to round and format differences. Default is <code>list(all_continuous() ~ style_sigfig, all_categorical() ~ function(x) paste0(style_sigfig(x * 100), "%"))</code> Function to round and format difference. Default is <a href="#">style_sigfig()</a>

**Example Output**

**See Also**

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

**Examples**

```
# Example 1 -----
add_difference_ex1 <-
  trial %>%
  select(trt, age, marker, response, death) %>%
  tbl_summary(
    by = trt,
    statistic =
      list(
        all_continuous() ~ "{mean} ({sd})",
        all_dichotomous() ~ "{p}%"
      ),
    missing = "no"
  ) %>%
  add_n() %>%
  add_difference()

# Example 2 -----
# ANCOVA adjusted for grade and stage
add_difference_ex2 <-
  trial %>%
  select(trt, age, marker, grade, stage) %>%
  tbl_summary(
    by = trt,
    statistic = list(all_continuous() ~ "{mean} ({sd})",
    missing = "no",
    include = c(age, marker, trt)
  ) %>%
  add_n() %>%
  add_difference(adj.vars = c(grade, stage))
```

---

 add\_glance

*Add Model Statistics*


---

**Description**

Add model statistics returned from broom: :glance(). Statistics can either be appended to the table (add\_glance\_table()), or added as a table source note (add\_glance\_source\_note()).

**Usage**

```
add_glance_table(
  x,
  include = everything(),
  label = NULL,
  fmt_fun = NULL,
  glance_fun = NULL
)
```



```

add_glance_source_note(
  x,
  include = everything(),
  label = NULL,
  fmt_fun = NULL,
  glance_fun = NULL,
  text_interpret = c("md", "html"),
  sep1 = " = ",
  sep2 = "; "
)

```

### Arguments

x	'tbl_regression' object
include	list of statistics to include in output. Must be column names of the tibble returned by <code>broom::glance()</code> . The include argument can also be used to specify the order the statistics appear in the table.
label	List of formulas specifying statistic labels, e.g. <code>list(r.squared ~ "R2", p.value ~ "P")</code>
fmt_fun	List of formulas where the LHS is a statistic and the RHS is a function to format/round the statistics. The default is to round the number of observations and degrees of freedom to the nearest integer, p-values are styled with <code>style_pvalue()</code> and the remaining statistics are styled with <code>style_sigfig(x, digits = 3)</code>
glance_fun	function that returns model statistics. Default is <code>broom::glance()</code> for most model objects, and <code>broom::glance(mice::pool())</code> for MICE 'mira' models. Custom functions must return a single row tibble.
text_interpret	String indicates whether source note text will be interpreted with <code>gt::md()</code> or <code>gt::html()</code> . Must be "md" (default) or "html".
sep1	Separator between statistic name and statistic. Default is " = ", e.g. "R2 = 0.456"
sep2	Separator between statistics. Default is "; "

### Value

gtsummary table

### Default Labels

The following statistics have set default labels when printed. When there is no default, the column name from `broom::glance()` is printed.

Statistic Name	Default Label
r.squared	R <sup>2</sup>
adj.r.squared	Adjusted R <sup>2</sup>
p.value	p-value
logLik	Log-likelihood
statistic	Statistic
df.residual	Residual df
null.deviance	Null deviance

df.null	Null df
nevent	N events
concordance	c-index
std.error.concordance	c-index SE
nobs	No. Obs.
deviance	Deviance
sigma	Sigma

### Tips

When combining `add_glance_table()` with `tbl_merge()`, the ordering of the model terms and the glance statistics may become jumbled. To re-order the rows with glance statistics on bottom, use the script below:

```
tbl_merge(list(tbl1, tbl2)) %>%
  modify_table_body(~.x %>% arrange(row_type == "glance_statistic"))
```

### Example Output

### See Also

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

### Examples

```
mod <- lm(age ~ marker + grade, trial) %>% tbl_regression()

# Example 1 -----
add_glance_ex1 <-
  mod %>%
  add_glance_table(
    label = list(sigma ~ "\u03C3"),
    include = c(r.squared, AIC, sigma)
  )

# Example 2 -----
add_glance_ex2 <-
  mod %>%
  add_glance_source_note(
    label = list(sigma ~ "\u03C3"),
    include = c(r.squared, AIC, sigma)
  )
```

---

add_global_p	<i>Add the global p-values</i>
--------------	--------------------------------

---

### Description

This function uses `car::Anova()` to calculate global p-values for model covariates. Output from `tbl_regression` and `tbl_uvregression` objects supported.

### Usage

```
add_global_p(x, ...)

## S3 method for class 'tbl_regression'
add_global_p(
  x,
  include = everything(),
  type = NULL,
  keep = FALSE,
  anova_fun = NULL,
  quiet = NULL,
  ...
)

## S3 method for class 'tbl_uvregression'
add_global_p(
  x,
  type = NULL,
  include = everything(),
  keep = FALSE,
  anova_fun = NULL,
  quiet = NULL,
  ...
)
```

### Arguments

x	Object with class 'tbl_regression' or 'tbl_uvregression'
...	Additional arguments to be passed to <code>car::Anova</code> , <code>aod::wald.test()</code> or <code>anova_fun</code> (if specified)
include	Variables to calculate global p-value for. Input may be a vector of quoted or unquoted variable names. Default is <code>everything()</code>
type	Type argument passed to <code>car::Anova(type=)</code> . Default is "III"
keep	Logical argument indicating whether to also retain the individual p-values in the table output for each level of the categorical variable. Default is FALSE.
anova_fun	Function that will be used in place of <code>car::Anova()</code> when specified to calculate the global p-values. <ul style="list-style-type: none"> <li>• function must return a tibble matching the output of <code>car::Anova()</code> %&gt;% <code>broom::tidy()</code> including a columns called "term" and "p.values"</li> </ul>

- function must accept arguments `anova_fun(x, ...)`, where `x` is a model object
  - arguments passed in `...` will be passed to `anova_fun(...)`
  - the `add_global_p(type=)` argument is *ignored* in `anova_fun=`
  - a common function used here is `tidy_wald_test()`, a wrapper for `aod::wald.test()`
- `quiet` Logical indicating whether to print messages in console. Default is FALSE

### Example Output

### Author(s)

Daniel D. Sjoberg

### See Also

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

Other `tbl_uvregression` tools: [add\\_q\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_uvregression\(\)](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_uvregression\(\)](#)

Other `tbl_regression` tools: [add\\_q\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [combine\\_terms\(\)](#), [inline\\_text.tbl\\_regression\(\)](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_regression\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

### Examples

```
# Example 1 -----
tbl_lm_global_ex1 <-
  lm(marker ~ age + grade, trial) %>%
  tbl_regression() %>%
  add_global_p()

# Example 2 -----
tbl_uv_global_ex2 <-
  trial[c("response", "trt", "age", "grade")] %>%
  tbl_uvregression(
    method = glm,
    y = response,
    method.args = list(family = binomial),
    exponentiate = TRUE
  ) %>%
  add_global_p()
```

---

add\_n.tbl\_summary      *Add column with N*

---

### Description

For each variable in a `tbl_summary` table, the `add_n` function adds a column with the total number of non-missing (or missing) observations

**Usage**

```
## S3 method for class 'tbl_summary'
add_n(
  x,
  statistic = "{n}",
  col_label = "**N**",
  footnote = FALSE,
  last = FALSE,
  ...
)

## S3 method for class 'tbl_svysummary'
add_n(
  x,
  statistic = "{n}",
  col_label = "**N**",
  footnote = FALSE,
  last = FALSE,
  ...
)
```

**Arguments**

x	Object with class <code>tbl_summary</code> from the <a href="#">tbl_summary</a> function or with class <code>tbl_svysummary</code> from the <a href="#">tbl_svysummary</a> function
statistic	String indicating the statistic to report. Default is the number of non-missing observation for each variable, <code>statistic = "{n}"</code> . Other statistics available to report include: <ul style="list-style-type: none"> <li>"{N_obs}" total number of observations,</li> <li>"{N_nonmiss}" number of non-missing observations,</li> <li>"{N_miss}" number of missing observations,</li> <li>"{p_nonmiss}" percent non-missing data,</li> <li>"{p_miss}" percent missing data</li> </ul> <p>survey summaries also have the following unweighted statistics available: <code>"N_obs_unweighted"</code>, <code>"N_miss_unweighted"</code>, <code>"N_nonmiss_unweighted"</code>, <code>"p_miss_unweighted"</code>, <code>"p_nonmiss_unweighted"</code></p> <p>The argument uses <a href="#">glue::glue</a> syntax and multiple statistics may be reported, e.g. <code>statistic = "{N_nonmiss} / {N_obs} ({p_nonmiss}%)"</code></p>
col_label	String indicating the column label. Default is <code>"**N**"</code>
footnote	Logical argument indicating whether to print a footnote clarifying the statistics presented. Default is <code>FALSE</code>
last	Logical indicator to include N column last in table. Default is <code>FALSE</code> , which will display N column first.
...	Not used

**Value**

A `tbl_summary` or `tbl_svysummary` object

## Example Output

### Author(s)

Daniel D. Sjoberg

### See Also

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

Other `tbl_summary` tools: [add\\_overall\(\)](#), [add\\_p.tbl\\_summary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_summary\(\)](#), [inline\\_text.tbl\\_survfit\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_custom\\_summary\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_summary\(\)](#)

Other `tbl_svysummary` tools: [add\\_overall\(\)](#), [add\\_p.tbl\\_svysummary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_svysummary\(\)](#)

### Examples

```
# Example 1 -----
tbl_n_ex <-
  trial[c("trt", "age", "grade", "response")] %>%
  tbl_summary(by = trt) %>%
  add_n()
```

---

add_n.tbl_survfit	<i>Add column with number of observations</i>
-------------------	---

---

### Description

**[Maturing]** For each `survfit()` object summarized with `tbl_survfit()` this function will add the total number of observations in a new column.

### Usage

```
## S3 method for class 'tbl_survfit'
add_n(x, ...)
```

### Arguments

<code>x</code>	object of class "tbl_survfit"
<code>...</code>	Not used

### Example Output

**See Also**

Review [list, formula, and selector syntax](#) used throughout gtsummary

Other tbl\_survfit tools: [add\\_nevent.tbl\\_survfit\(\)](#), [add\\_p.tbl\\_survfit\(\)](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_survfit\(\)](#)

**Examples**

```
library(survival)
fit1 <- survfit(Surv(ttdeath, death) ~ 1, trial)
fit2 <- survfit(Surv(ttdeath, death) ~ trt, trial)

# Example 1 -----
add_n.tbl_survfit_ex1 <-
  list(fit1, fit2) %>%
  tbl_survfit(times = c(12, 24)) %>%
  add_n()
```

---

```
add_nevent.tbl_survfit
```

*Add column with number of observed events*

---

**Description**

**[Maturing]** For each survfit() object summarized with tbl\_survfit() this function will add the total number of events observed in a new column.

**Usage**

```
## S3 method for class 'tbl_survfit'
add_nevent(x, ...)
```

**Arguments**

x	object of class 'tbl_survfit'
...	Not used

**Example Output****See Also**

Other tbl\_survfit tools: [add\\_n.tbl\\_survfit\(\)](#), [add\\_p.tbl\\_survfit\(\)](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_survfit\(\)](#)

**Examples**

```

library(survival)
fit1 <- survfit(Surv(ttdeath, death) ~ 1, trial)
fit2 <- survfit(Surv(ttdeath, death) ~ trt, trial)

# Example 1 -----
add_nevent.tbl_survfit_ex1 <-
  list(fit1, fit2) %>%
  tbl_survfit(times = c(12, 24)) %>%
  add_n() %>%
  add_nevent()

```

---

add\_nevent\_regression *Add event N to regression table*

---

**Description**

Add event N to regression table

**Usage**

```

## S3 method for class 'tbl_regression'
add_nevent(x, location = NULL, ...)

## S3 method for class 'tbl_uvregression'
add_nevent(x, location = NULL, ...)

```

**Arguments**

x	a <code>tbl_regression</code> or <code>tbl_uvregression</code> table
location	location to place Ns. When "label" total Ns are placed on each variable's label row. When "level" level counts are placed on the variable level for categorical variables, and total N on the variable's label row for continuous.
...	Not used

**Example Output****Examples**

```

# Example 1 -----
add_nevent.tbl_regression_ex1 <-
  trial %>%
  select(response, trt, grade) %>%
  tbl_uvregression(
    y = response,
    method = glm,
    method.args = list(family = binomial),

```



```

) %>%
  add_nevent()
# Example 2 -----
add_nevent.tbl_regression_ex2 <-
  glm(response ~ age + grade, trial, family = binomial) %>%
  tbl_regression(exponentiate = TRUE) %>%
  add_nevent(location = "level")

```

---

add_n_regression	<i>Add N to regression table</i>
------------------	----------------------------------

---

## Description

Add N to regression table

## Usage

```

## S3 method for class 'tbl_regression'
add_n(x, location = NULL, ...)

## S3 method for class 'tbl_uvregression'
add_n(x, location = NULL, ...)

```

## Arguments

x	a <code>tbl_regression</code> or <code>tbl_uvregression</code> table
location	location to place Ns. When "label" total Ns are placed on each variable's label row. When "level" level counts are placed on the variable level for categorical variables, and total N on the variable's label row for continuous.
...	Not used

## Example Output

## Examples

```

# Example 1 -----
add_n.tbl_regression_ex1 <-
  trial %>%
  select(response, age, grade) %>%
  tbl_uvregression(
    y = response,
    method = glm,
    method.args = list(family = binomial),
    hide_n = TRUE
  ) %>%
  add_n(location = "label")

# Example 2 -----
add_n.tbl_regression_ex2 <-
  glm(response ~ age + grade, trial, family = binomial) %>%

```

```
tbl_regression(exponentiate = TRUE) %>%
  add_n(location = "level")
```

---

add_overall	<i>Add column with overall summary statistics</i>
-------------	---

---

## Description

Adds a column with overall summary statistics to tables created by `tbl_summary`, `tbl_svsummary`, `tbl_continuous` or `tbl_custom_summary`.

## Usage

```
add_overall(x, ...)

## S3 method for class 'tbl_summary'
add_overall(
  x,
  last = FALSE,
  col_label = NULL,
  statistic = NULL,
  digits = NULL,
  ...
)

## S3 method for class 'tbl_svsummary'
add_overall(
  x,
  last = FALSE,
  col_label = NULL,
  statistic = NULL,
  digits = NULL,
  ...
)

## S3 method for class 'tbl_continuous'
add_overall(
  x,
  last = FALSE,
  col_label = NULL,
  statistic = NULL,
  digits = NULL,
  ...
)

## S3 method for class 'tbl_custom_summary'
add_overall(
  x,
  last = FALSE,
  col_label = NULL,
```

```

    statistic = NULL,
    digits = NULL,
    ...
  )

```

### Arguments

x	Object with class <code>tbl_summary</code> from the <a href="#">tbl_summary</a> function, object with class <code>tbl_svysummary</code> from the <a href="#">tbl_svysummary</a> function, object with class <code>tbl_continuous</code> from the <a href="#">tbl_continuous</a> function or object with class <code>tbl_custom_summary</code> from the <a href="#">tbl_custom_summary</a> function.
...	Not used
last	Logical indicator to display overall column last in table. Default is <code>FALSE</code> , which will display overall column first.
col_label	String indicating the column label. Default is <code>"**Overall**"</code> , <code>N = {N}</code>
statistic	Override the statistic argument in initial <code>tbl_*</code> function. call. Default is <code>NULL</code> .
digits	Override the digits argument in initial <code>tbl_*</code> function call. Default is <code>NULL</code> .

### Value

A `tbl_*` of same class as `x`

### Example Output

### Author(s)

Daniel D. Sjoberg

### See Also

Other `tbl_summary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_p.tbl\\_summary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_summary\(\)](#), [inline\\_text.tbl\\_survfit\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_custom\\_summary\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_summary\(\)](#)

Other `tbl_svysummary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_p.tbl\\_svysummary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_svysummary\(\)](#)

Other `tbl_continuous` tools: [add\\_p.tbl\\_continuous\(\)](#), [tbl\\_continuous\(\)](#)

Other `tbl_custom_summary` tools: [continuous\\_summary\(\)](#), [proportion\\_summary\(\)](#), [ratio\\_summary\(\)](#), [tbl\\_custom\\_summary\(\)](#)

### Examples

```

# Example 1 -----
tbl_overall_ex1 <-
  trial %>%
  tbl_summary(include = c(age, grade), by = trt) %>%
  add_overall()

# Example 2 -----

```

```
tbl_overall_ex2 <-
  trial %>%
  tbl_summary(
    include = grade,
    by = trt,
    percent = "row",
    statistic = ~"{p}%",
    digits = ~1
  ) %>%
  add_overall(
    last = TRUE,
    statistic = ~"{p}% (n={n})",
    digits = ~ c(1, 0)
  )

# Example 3 -----
tbl_overall_ex3 <-
  trial %>%
  tbl_continuous(
    variable = age,
    by = trt,
    include = grade
  ) %>%
  add_overall(last = TRUE)
```

---

add\_p.tbl\_continuous *P-values for tbl\_continuous*

---

## Description

P-values for `tbl_continuous`

## Usage

```
## S3 method for class 'tbl_continuous'
add_p(
  x,
  test = NULL,
  pvalue_fun = NULL,
  include = everything(),
  test.args = NULL,
  group = NULL,
  ...
)
```

## Arguments

`x` Object with class `tbl_summary` from the [tbl\\_summary](#) function

`test` List of formulas specifying statistical tests to perform for each variable. Default is two-way ANOVA when `by=` is not `NULL`, and has the same defaults as `add_p.tbl_continuous()` when `by = NULL`. See [tests](#) for details, more tests, and instruction for implementing a custom test.

pvalue_fun	Function to round and format p-values. Default is <a href="#">style_pvalue</a> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
include	Variables to include in output. Input may be a vector of quoted variable names, unquoted variable names, or tidyselect select helper functions. Default is <code>everything()</code> .
test.args	List of formulas containing additional arguments to pass to tests that accept arguments. For example, add an argument for all t-tests, use <code>test.args = all_tests("t.test") ~ list(var.equal = TRUE)</code>
group	Column name (unquoted or quoted) of an ID or grouping variable. The column can be used to calculate p-values with correlated data. Default is NULL. See <a href="#">tests</a> for methods that utilize the <code>group=</code> argument.
...	Not used

**See Also**

Other `tbl_continuous` tools: [add\\_overall\(\)](#), [tbl\\_continuous\(\)](#)

**Examples**

```
add_p_continuous_ex1 <-
tbl_continuous(
  data = trial,
  variable = age,
  by = trt,
  include = grade
) %>%
add_p()
```

---

add_p.tbl_cross	<i>Adds p-value to crosstab table</i>
-----------------	---------------------------------------

---

**Description**

Calculate and add a p-value comparing the two variables in the cross table. Missing values are included in p-value calculations.

**Usage**

```
## S3 method for class 'tbl_cross'
add_p(
  x,
  test = NULL,
  pvalue_fun = NULL,
  source_note = NULL,
  test.args = NULL,
  ...
)
```

**Arguments**

x	Object with class <code>tbl_cross</code> from the <code>tbl_cross</code> function
test	A string specifying statistical test to perform. Default is "chisq.test" when expected cell counts $\geq 5$ and "fisher.test" when expected cell counts $< 5$ .
pvalue_fun	Function to round and format p-value. Default is <code>style_pvalue</code> , except when <code>source_note = TRUE</code> when the default is <code>style_pvalue(x, prepend_p = TRUE)</code>
source_note	Logical value indicating whether to show p-value in the {gt} table source notes rather than a column.
test.args	Named list containing additional arguments to pass to the test (if it accepts additional arguments). For example, add an argument for a chi-squared test with <code>test.args = list(correct = TRUE)</code>
...	Not used

**Example Output****Author(s)**

Karissa Whiting

**See Also**

Other `tbl_cross` tools: `inline_text.tbl_cross()`, `tbl_cross()`

**Examples**

```
# Example 1 -----
add_p_cross_ex1 <-
  trial %>%
  tbl_cross(row = stage, col = trt) %>%
  add_p()

# Example 2 -----
add_p_cross_ex2 <-
  trial %>%
  tbl_cross(row = stage, col = trt) %>%
  add_p(source_note = TRUE)
```

---

add\_p.tbl\_summary      *Adds p-values to summary tables*

---

**Description**

Adds p-values to tables created by `tbl_summary` by comparing values across groups.

**Usage**

```
## S3 method for class 'tbl_summary'
add_p(
  x,
  test = NULL,
  pvalue_fun = NULL,
  group = NULL,
  include = everything(),
  test.args = NULL,
  ...
)
```

**Arguments**

x	Object with class <code>tbl_summary</code> from the <a href="#">tbl_summary</a> function
test	List of formulas specifying statistical tests to perform for each variable, e.g. <code>list(all_continuous() ~ "t.test", all_categorical() ~ "fisher.test")</code> . Common tests include <code>"t.test"</code> , <code>"aov"</code> , <code>"wilcox.test"</code> , <code>"kruskal.test"</code> , <code>"chisq.test"</code> , <code>"fisher.test"</code> , and <code>"lme4"</code> (for clustered data). See <a href="#">tests</a> for details, more tests, and instruction for implementing a custom test. Tests default to <code>"kruskal.test"</code> for continuous variables ( <code>"wilcox.test"</code> when <code>"by"</code> variable has two levels), <code>"chisq.test.no.correct"</code> for categorical variables with all expected cell counts $\geq 5$ , and <code>"fisher.test"</code> for categorical variables with any expected cell count $< 5$ .
pvalue_fun	Function to round and format p-values. Default is <a href="#">style_pvalue</a> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
group	Column name (unquoted or quoted) of an ID or grouping variable. The column can be used to calculate p-values with correlated data. Default is <code>NULL</code> . See <a href="#">tests</a> for methods that utilize the <code>group=</code> argument.
include	Variables to include in output. Input may be a vector of quoted variable names, unquoted variable names, or <code>tidyselect</code> select helper functions. Default is <code>everything()</code> .
test.args	List of formulas containing additional arguments to pass to tests that accept arguments. For example, add an argument for all t-tests, use <code>test.args = all_tests("t.test") ~ list(var.equal = TRUE)</code>
...	Not used

**Value**

A `tbl_summary` object

**Example Output****Author(s)**

Daniel D. Sjoberg, Emily C. Zabor

**See Also**

See `tbl_summary` [vignette](#) for detailed examples

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

Other `tbl_summary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_q()`, `add_stat_label()`, `bold_italicize_labels_levels`, `inline_text.tbl_summary()`, `inline_text.tbl_survfit()`, `modify`, `separate_p_footnotes()`, `tbl_custom_summary()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_summary()`

**Examples**

```
# Example 1 -----
add_p_ex1 <-
  trial[c("age", "grade", "trt")] %>%
  tbl_summary(by = trt) %>%
  add_p()

# Example 2 -----
add_p_ex2 <-
  trial %>%
  select(trt, age, marker) %>%
  tbl_summary(by = trt, missing = "no") %>%
  add_p(
    # perform t-test for all variables
    test = everything() ~ "t.test",
    # assume equal variance in the t-test
    test.args = all_tests("t.test") ~ list(var.equal = TRUE)
  )
```

---

`add_p.tbl_survfit`      *Adds p-value to survfit table*

---

**Description**

**[Maturing]** Calculate and add a p-value

**Usage**

```
## S3 method for class 'tbl_survfit'
add_p(
  x,
  test = "logrank",
  test.args = NULL,
  pvalue_fun = style_pvalue,
  include = everything(),
  quiet = NULL,
  ...
)
```



**Arguments**

x	Object of class "tbl_survfit"
test	string indicating test to use. Must be one of "logrank", "tarone", "survdiff", "petopeto_gehanwilcoxon", "coxph_lrt", "coxph_wald", "coxph_score". See details below
test.args	List of formulas containing additional arguments to pass to tests that accept arguments. For example, add an argument for all t-tests, use test.args = all_tests("t.test") ~ list(var.equal = TRUE)
pvalue_fun	Function to round and format p-values. Default is <a href="#">style_pvalue</a> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. pvalue_fun = function(x) style_pvalue(x, digits = 2) or equivalently, purrr::partial(style_pvalue, digits = 2)).
include	Variables to include in output. Input may be a vector of quoted variable names, unquoted variable names, or tidycselect select helper functions. Default is everything().
quiet	Logical indicating whether to print messages in console. Default is FALSE
...	Not used

**test argument**

The most common way to specify test= is by using a single string indicating the test name. However, if you need to specify different tests within the same table, the input is flexible using the list notation common throughout the gtsummary package. For example, the following code would call the log-rank test, and a second test of the *G-rho* family.

```
... %>%
  add_p(test = list(trt ~ "logrank", grade ~ "survdiff"),
        test.args = grade ~ list(rho = 0.5))
```

**Example Output****See Also**

Other `tbl_survfit` tools: [add\\_n.tbl\\_survfit\(\)](#), [add\\_nevent.tbl\\_survfit\(\)](#), [modify.tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_survfit\(\)](#)

**Examples**

```
library(survival)

gts_survfit <-
  list(
    survfit(Surv(ttdeath, death) ~ grade, trial),
    survfit(Surv(ttdeath, death) ~ trt, trial)
  ) %>%
  tbl_survfit(times = c(12, 24))

# Example 1 -----
add_p.tbl_survfit_ex1 <-
```

```

gts_survfit %>%
  add_p()

# Example 2 -----
# Pass `rho=` argument to `survdif()`
add_p.tbl_survfit_ex2 <-
  gts_survfit %>%
  add_p(test = "survdif", test.args = list(rho = 0.5))

```

---

add\_p.tbl\_svsummary *Adds p-values to svsummary tables*

---

## Description

Adds p-values to tables created by `tbl_svsummary` by comparing values across groups.

## Usage

```

## S3 method for class 'tbl_svsummary'
add_p(
  x,
  test = NULL,
  pvalue_fun = NULL,
  include = everything(),
  test.args = NULL,
  ...
)

```

## Arguments

<code>x</code>	Object with class <code>tbl_svsummary</code> from the <code>tbl_svsummary</code> function
<code>test</code>	List of formulas specifying statistical tests to perform, e.g. <code>list(all_continuous() ~ "svy.t.test", all_categorical() ~ "svy.wald.test")</code> . Options include <ul style="list-style-type: none"> <li>"svy.t.test" for a t-test adapted to complex survey samples (cf. <code>survey::svyttest</code>),</li> <li>"svy.wilcox.test" for a Wilcoxon rank-sum test for complex survey samples (cf. <code>survey::svyranktest</code>),</li> <li>"svy.kruskal.test" for a Kruskal-Wallis rank-sum test for complex survey samples (cf. <code>survey::svyranktest</code>),</li> <li>"svy.vanderwaerden.test" for a van der Waerden's normal-scores test for complex survey samples (cf. <code>survey::svyranktest</code>),</li> <li>"svy.median.test" for a Mood's test for the median for complex survey samples (cf. <code>survey::svyranktest</code>),</li> <li>"svy.chisq.test" for a Chi-squared test with Rao &amp; Scott's second-order correction (cf. <code>survey::svychisq</code>),</li> <li>"svy.adj.chisq.test" for a Chi-squared test adjusted by a design effect estimate (cf. <code>survey::svychisq</code>),</li> <li>"svy.wald.test" for a Wald test of independence for complex survey samples (cf. <code>survey::svychisq</code>),</li> </ul>

- "svy.adj.wald.test" for an adjusted Wald test of independence for complex survey samples (cf. `survey::svychisq`),
- "svy.lincom.test" for a test of independence using the exact asymptotic distribution for complex survey samples (cf. `survey::svychisq`),
- "svy.saddlepoint.test" for a test of independence using a saddlepoint approximation for complex survey samples (cf. `survey::svychisq`),

Tests default to "svy.wilcox.test" for continuous variables and "svy.chisq.test" for categorical variables.

pvalue_fun	Function to round and format p-values. Default is <code>style_pvalue</code> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
include	Variables to include in output. Input may be a vector of quoted variable names, unquoted variable names, or <code>tidyselect</code> select helper functions. Default is <code>everything()</code> .
test.args	List of formulas containing additional arguments to pass to tests that accept arguments. For example, add an argument for all t-tests, use <code>test.args = all_tests("t.test") ~ list(var.equal = TRUE)</code>
...	Not used

### Value

A `tbl_svysummary` object

### Example Output

### Author(s)

Joseph Larmarange

### See Also

Other `tbl_svysummary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_q()`, `add_stat_label()`, `modify`, `separate_p_footnotes()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_svysummary()`

### Examples

```
# Example 1 -----
# A simple weighted dataset
add_p_svysummary_ex1 <-
  survey::svydesign(~1, data = as.data.frame(Titanic), weights = ~Freq) %>%
  tbl_svysummary(by = Survived, include = c(Sex, Age)) %>%
  add_p()

# A dataset with a complex design
data(api, package = "survey")
d_clust <- survey::svydesign(id = ~dnum, weights = ~pw, data = apiclus1, fpc = ~fpc)

# Example 2 -----
```

```

add_p_svysummary_ex2 <-
  tbl_svysummary(d_clust, by = both, include = c(api00, api99, both)) %>%
  add_p()

# Example 3 -----
# change tests to svy t-test and Wald test
add_p_svysummary_ex3 <-
  tbl_svysummary(d_clust, by = both, include = c(cname, api00, api99, both)) %>%
  add_p(
    test = list(
      all_continuous() ~ "svy.t.test",
      all_categorical() ~ "svy.wald.test"
    )
  )

```

---

add\_q

*Add a column of q-values to account for multiple comparisons*


---

### Description

Adjustments to p-values are performed with [stats::p.adjust](#).

### Usage

```
add_q(x, method = "fdr", pvalue_fun = NULL, quiet = NULL)
```

### Arguments

x	a gtsummary object
method	String indicating method to be used for p-value adjustment. Methods from <a href="#">stats::p.adjust</a> are accepted. Default is method = "fdr".
pvalue_fun	Function to round and format p-values. Default is <a href="#">style_pvalue</a> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
quiet	Logical indicating whether to print messages in console. Default is FALSE

### Example Output

### Author(s)

Esther Drill, Daniel D. Sjoberg

**See Also**

Other `tbl_summary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_summary()`, `add_stat_label()`, `bold_italicize_labels_levels`, `inline_text.tbl_summary()`, `inline_text.tbl_survfit()`, `modify`, `separate_p_footnotes()`, `tbl_custom_summary()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_summary()`

Other `tbl_svysummary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_svysummary()`, `add_stat_label()`, `modify`, `separate_p_footnotes()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_svysummary()`

Other `tbl_regression` tools: `add_global_p()`, `bold_italicize_labels_levels`, `combine_terms()`, `inline_text.tbl_regression()`, `modify`, `tbl_merge()`, `tbl_regression()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`

Other `tbl_uvregression` tools: `add_global_p()`, `bold_italicize_labels_levels`, `inline_text.tbl_uvregression()`, `modify`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_uvregression()`

**Examples**

```
# Example 1 -----
add_q_ex1 <-
  trial[c("trt", "age", "grade", "response")] %>%
  tbl_summary(by = trt) %>%
  add_p() %>%
  add_q()

# Example 2 -----
add_q_ex2 <-
  trial[c("trt", "age", "grade", "response")] %>%
  tbl_uvregression(
    y = response,
    method = glm,
    method.args = list(family = binomial),
    exponentiate = TRUE
  ) %>%
  add_global_p() %>%
  add_q()
```

---

add\_significance\_stars

*Add significance stars*

---

**Description**

**[Experimental]** Add significance stars to estimates with small p-values

**Usage**

```
add_significance_stars(
  x,
  pattern = NULL,
```

```

thresholds = c(0.001, 0.01, 0.05),
hide_ci = TRUE,
hide_p = inherits(x, c("tbl_regression", "tbl_uvregression")),
hide_se = FALSE
)

```

### Arguments

x	a 'gtsummary' object with a 'p.value' column
pattern	glue-syntax string indicating what to display in formatted column. Default is "{estimate}{stars}" for regression summaries and "{p.value}{stars}" otherwise. A footnote is placed on the first column listed in the pattern. Other common patterns are "{estimate}{stars} ({conf.low}, {conf.high})" and "{estimate} ({conf.low} to {conf.high}){stars}"
thresholds	thresholds for significance stars. Default is c(0.001, 0.01, 0.05)
hide_ci	logical whether to hide confidence interval. Default is TRUE
hide_p	logical whether to hide p-value. Default is TRUE for regression summaries, and FALSE otherwise.
hide_se	logical whether to hide standard error. Default is FALSE

### Future Updates

There are planned updates to the implementation of this function with respect to the `pattern=` argument. Currently, this function replaces the numeric estimate column, with a formatted character column following `pattern=`. Once `gt::cols_merge()` gains the `rows=` argument the implementation will be updated to use it, which will keep numeric columns numeric. For the *vast majority* of users, *the planned change will be go unnoticed*.

### Example Output

### Examples

```

tbl <-
  lm(time ~ ph.ecog + sex, survival::lung) %>%
  tbl_regression(label = list(ph.ecog = "ECOG Score", sex = "Sex"))

# Example 1 -----
add_significance_stars_ex1 <-
  tbl %>%
  add_significance_stars(hide_ci = FALSE, hide_p = FALSE)

# Example 2 -----
add_significance_stars_ex2 <-
  tbl %>%
  add_significance_stars(
    pattern = "{estimate} ({conf.low}, {conf.high}){stars}",
    hide_ci = TRUE, hide_se = TRUE
  ) %>%
  modify_header(estimate ~ "**Beta (95% CI)**") %>%
  modify_footnote(estimate ~ "CI = Confidence Interval", abbreviation = TRUE)

```

```

# Example 3 -----
# Use ' \n' to put a line break between beta and SE
add_significance_stars_ex3 <-
  tbl %>%
  add_significance_stars(
    hide_se = TRUE,
    pattern = "{estimate}{stars} \n({std.error})"
  ) %>%
  modify_header(estimate ~ "**Beta \n(SE)**") %>%
  modify_footnote(estimate ~ "SE = Standard Error", abbreviation = TRUE) %>%
  as_gt() %>%
  gt::fmt_markdown(columns = everything()) %>%
  gt::tab_style(
    style = "vertical-align:top",
    locations = gt::cells_body(columns = label)
  )

# Example 4 -----
add_significance_stars_ex4 <-
  lm(marker ~ stage + grade, data = trial) %>%
  tbl_regression() %>%
  add_global_p() %>%
  add_significance_stars(
    hide_p = FALSE,
    pattern = "{p.value}{stars}"
  ) %>%
  as_gt() %>%
  gt::tab_style(
    style = "vertical-align:top",
    locations = gt::cells_body(columns = label)
  )

```

---

add\_stat

*Add a custom statistic column*


---

## Description

**[Maturing]** The function allows a user to add a new column (or columns) of statistics to an existing `tbl_summary`, `tbl_svsummary`, or `tbl_continuous` object.

## Usage

```
add_stat(x, fns, location = NULL, ...)
```

## Arguments

<code>x</code>	<code>tbl_summary</code> , <code>tbl_svsummary</code> , or <code>tbl_continuous</code> object
<code>fns</code>	list of formulas indicating the functions that create the statistic. See details below.

location	list of formulas indicating the location the new statistics are placed. The RHS of the formula must be one of c("label", "level", "missing"). When "label", a single statistic is placed on the variable label row. When "level" the statistics are placed on the variable level rows. The length of the vector of statistics returned from the fns function must match the dimension of levels. Default is to place the new statistics on the label row.
...	DEPRECATED

## Details

The returns from custom functions passed in `fns=` are required to follow a specified format. Each of these function will execute on a single variable.

1. Each function must return a tibble or a vector. If a vector is returned, it will be converted to a tibble with one column and number of rows equal to the length of the vector.
2. When `location = "label"`, the returned statistic from the custom function must be a tibble with one row. When `location = "level"` the tibble must have the same number of rows as there are levels in the variable (excluding the row for unknown values).
3. Each function may take the following arguments: `foo(data, variable, by, tbl, ...)`
  - `data=` is the input data frame passed to `tbl_summary()`
  - `variable=` is a string indicating the variable to perform the calculation on. This is the variable in the label column of the table.
  - `by=` is a string indicating the by variable from `tbl_summary=`, if present
  - `tbl=` the original `tbl_summary()/tbl_svsummary()` object is also available to utilize

The user-defined does not need to utilize each of these inputs. It's encouraged the user-defined function accept `...` as each of the arguments *will* be passed to the function, even if not all inputs are utilized by the user's function, e.g. `foo(data, variable, by, ...)`

- Use `modify_header()` to update the column headers
- Use `modify_fmt_fun()` to update the functions that format the statistics
- Use `modify_footnote()` to add a explanatory footnote

If you return a tibble with column names `p.value` or `q.value`, default p-value formatting will be applied, and you may take advantage of subsequent p-value formatting functions, such as `bold_p()` or `add_q()`.

To access the continuous variable in a `tbl_continuous()` table, use `tbl$inputs$variable`.

## Example Output

## See Also

Review [list, formula, and selector syntax](#) used throughout `gtsummary`

## Examples

```
library(dplyr, warn.conflicts = FALSE)
library(stringr)
# Example 1 -----
# fn returns t-test pvalue
my_ttest <- function(data, variable, by, ...) {
```



```

    t.test(data[[variable]] ~ as.factor(data[[by]]))$p.value
  }

add_stat_ex1 <-
  trial %>%
  select(trt, age, marker) %>%
  tbl_summary(by = trt, missing = "no") %>%
  add_stat(fns = everything() ~ my_ttest) %>%
  modify_header(
    list(
      add_stat_1 ~ "***p-value**",
      all_stat_cols() ~ "**{level}**"
    )
  )

# Example 2 -----
# fn returns t-test test statistic and pvalue
my_ttest2 <- function(data, variable, by, ...) {
  t.test(data[[variable]] ~ as.factor(data[[by]])) %>%
  broom::tidy() %>%
  mutate(
    stat = str_glue("t={style_sigfig(statistic)}, {style_pvalue(p.value, prepend_p = TRUE)}")
  ) %>%
  pull(stat)
}

add_stat_ex2 <-
  trial %>%
  select(trt, age, marker) %>%
  tbl_summary(by = trt, missing = "no") %>%
  add_stat(fns = everything() ~ my_ttest2) %>%
  modify_header(add_stat_1 ~ "***Treatment Comparison**")

# Example 3 -----
# return test statistic and p-value is separate columns
my_ttest3 <- function(data, variable, by, ...) {
  t.test(data[[variable]] ~ as.factor(data[[by]])) %>%
  broom::tidy() %>%
  select(statistic, p.value)
}

add_stat_ex3 <-
  trial %>%
  select(trt, age, marker) %>%
  tbl_summary(by = trt, missing = "no") %>%
  add_stat(fns = everything() ~ my_ttest3) %>%
  modify_header(
    list(
      statistic ~ "***t-statistic**",
      p.value ~ "***p-value**"
    )
  ) %>%
  modify_fmt_fun(
    list(
      statistic ~ style_sigfig,
      p.value ~ style_pvalue
    )
  )

```

)

---

add_stat_label	<i>Add statistic labels</i>
----------------	-----------------------------

---

**Description**

Adds labels describing the summary statistics presented for each variable in the [tbl\\_summary](#) / [tbl\\_svsummary](#) table.

**Usage**

```
add_stat_label(x, location = NULL, label = NULL)
```

**Arguments**

x	Object with class <code>tbl_summary</code> from the <a href="#">tbl_summary</a> function or with class <code>tbl_svsummary</code> from the <a href="#">tbl_svsummary</a> function
location	location where statistic label will be included. "row" (the default) to add the statistic label to the variable label row, and "column" adds a column with the statistic label.
label	a list of formulas or a single formula updating the statistic label, e.g. <code>label = all_categorical() ~ "No. (%)"</code>

**Value**

A `tbl_summary` or `tbl_svsummary` object

**Tips**

When using `add_stat_label(location='row')` with subsequent `tbl_merge()`, it's important to have somewhat of an understanding of the underlying structure of the `gtsummary` table. `add_stat_label(location='row')` works by adding a new column called "stat\_label" to `x$table_body`. The "label" and "stat\_label" columns are merged when the `gtsummary` table is printed. The `tbl_merge()` function merges on the "label" column (among others), which is typically the first column you see in a `gtsummary` table. Therefore, when you want to merge a table that has run `add_stat_label(location='row')` you need to match the "label" column values before the "stat\_column" is merged with it.

For example, the following two tables merge properly

```
tbl1 <- trial %>% select(age, grade) %>% tbl_summary() %>% add_stat_label()
tbl2 <- lm(marker ~ age + grade, trial) %>% tbl_regression()

tbl_merge(list(tbl1, tbl2))
```

**Example Output****Author(s)**

Daniel D. Sjoberg

**See Also**

Review [list, formula, and selector syntax](#) used throughout gtsummary

Other `tbl_summary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_summary()`, `add_q()`, `bold_italicize_labels_levels`, `inline_text.tbl_summary()`, `inline_text.tbl_survfit()`, `modify`, `separate_p_footnotes()`, `tbl_custom_summary()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_summary()`

Other `tbl_svysummary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_svysummary()`, `add_q()`, `modify`, `separate_p_footnotes()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_svysummary()`

**Examples**

```
tbl <- trial %>%
  dplyr::select(trt, age, grade, response) %>%
  tbl_summary(by = trt)

# Example 1 -----
# Add statistic presented to the variable label row
add_stat_label_ex1 <-
  tbl %>%
  add_stat_label(
    # update default statistic label for continuous variables
    label = all_continuous() ~ "med. (iqr)"
  )

# Example 2 -----
add_stat_label_ex2 <-
  tbl %>%
  add_stat_label(
    # add a new column with statistic labels
    location = "column"
  )

# Example 3 -----
add_stat_label_ex3 <-
  trial %>%
  select(age, grade, trt) %>%
  tbl_summary(
    by = trt,
    type = all_continuous() ~ "continuous2",
    statistic = all_continuous() ~ c("{mean} ({sd})", "{min} - {max}"),
  ) %>%
  add_stat_label(label = age ~ c("Mean (SD)", "Min - Max"))
```

**Description**

**[Maturing]** Add the variance inflation factor (VIF) or generalized VIF (GVIF) to the regression table. Function uses `car::vif()` to calculate the VIF.

**Usage**

```
add_vif(x, statistic = NULL, estimate_fun = NULL)
```

**Arguments**

`x` 'tbl\_regression' object

`statistic` "VIF" (variance inflation factors, for models with no categorical terms) or one of/combination of "GVIF" (generalized variance inflation factors), "aGVIF" 'adjusted GVIF, i.e.  $GVIF^{[1/(2*df)]}$  and/or "df" (degrees of freedom). See `car::vif()` for details.

`estimate_fun` Default is `style_sigfig()`.

**Example Output****See Also**

Review [list, formula, and selector syntax](#) used throughout gtsummary

**Examples**

```
# Example 1 -----
add_vif_ex1 <-
  lm(age ~ grade + marker, trial) %>%
  tbl_regression() %>%
  add_vif()

# Example 2 -----
add_vif_ex2 <-
  lm(age ~ grade + marker, trial) %>%
  tbl_regression() %>%
  add_vif(c("aGVIF", "df"))
```

---

as\_flex\_table

*Convert gtsummary object to a flextable object*

---

**Description**

Function converts a gtsummary object to a flextable object. A user can use this function if they wish to add customized formatting available via the flextable functions. The flextable output is particularly useful when combined with R markdown with Word output, since the gt package does not support Word.

**Usage**

```
as_flex_table(x, include = everything(), return_calls = FALSE, ...)
```

## Arguments

x	Object created by a function from the gtsummary package (e.g. <a href="#">tbl_summary</a> or <a href="#">tbl_regression</a> )
include	Commands to include in output. Input may be a vector of quoted or unquoted names. tidyselct and gtsummary select helper functions are also accepted. Default is everything().
return_calls	Logical. Default is FALSE. If TRUE, the calls are returned as a list of expressions.
...	Not used

## Details

The `as_flex_table()` function supports bold and italic markdown syntax in column headers and spanning headers ('\*\*' and '\_' only). Text wrapped in double stars ('\*\*bold\*\*') will be made bold, and text between single underscores ('\_italic\_') will be made italic. No other markdown syntax is supported and the double-star and underscore cannot be combined. To further style your table, you may convert the table to flextable with `as_flex_table()`, then utilize any of the flextable functions.

## Value

A flextable object

## Example Output

## Author(s)

Daniel D. Sjoberg

## See Also

Other gtsummary output types: [as\\_gt\(\)](#), [as\\_hux\\_table\(\)](#), [as\\_kable\\_extra\(\)](#), [as\\_kable\(\)](#), [as\\_tibble.gtsummary\(\)](#)

## Examples

```
as_flex_table_ex1 <-  
  trial %>%  
  select(trt, age, grade) %>%  
  tbl_summary(by = trt) %>%  
  add_p() %>%  
  as_flex_table()
```

as\_gt

*Convert gtsummary object to a gt object***Description**

Function converts a gtsummary object to a "gt\_tbl" object, that is, a table created with `gt::gt()`. Function is used in the background when the results are printed or knit. A user can use this function if they wish to add customized formatting available via the [gt package](#).

Review the [tbl\\_summary vignette](#) or [tbl\\_regression vignette](#) for detailed examples in the 'Advanced Customization' section.

**Usage**

```
as_gt(x, include = everything(), return_calls = FALSE, ...)
```

**Arguments**

x	Object created by a function from the gtsummary package (e.g. <a href="#">tbl_summary</a> or <a href="#">tbl_regression</a> )
include	Commands to include in output. Input may be a vector of quoted or unquoted names. <code>tidyselect</code> and <code>gtsummary</code> select helper functions are also accepted. Default is <code>everything()</code> .
return_calls	Logical. Default is FALSE. If TRUE, the calls are returned as a list of expressions.
...	Arguments passed on to <a href="#">gt::gt</a>

**Value**

A `gt_tbl` object

**Example Output****Author(s)**

Daniel D. Sjoberg

**See Also**

Other gtsummary output types: [as\\_flex\\_table\(\)](#), [as\\_hux\\_table\(\)](#), [as\\_kable\\_extra\(\)](#), [as\\_kable\(\)](#), [as\\_tibble.gtsummary\(\)](#)

**Examples**

```
# Example 1 -----
as_gt_ex1 <-
  trial[c("trt", "age", "response", "grade")] %>%
  tbl_summary(by = trt) %>%
  as_gt()
```

---

as_hux_table	<i>Convert gtsummary object to a huxtable object</i>
--------------	--

---

### Description

Function converts a gtsummary object to a huxtable object. A user can use this function if they wish to add customized formatting available via the huxtable functions. The huxtable package supports output to PDF via LaTeX, as well as HTML and Word.

### Usage

```
as_hux_table(
  x,
  include = everything(),
  return_calls = FALSE,
  strip_md_bold = FALSE
)
```

```
as_hux_xlsx(x, file, include = everything(), bold_header_rows = TRUE)
```

### Arguments

x	Object created by a function from the gtsummary package (e.g. <a href="#">tbl_summary</a> or <a href="#">tbl_regression</a> )
include	Commands to include in output. Input may be a vector of quoted or unquoted names. tidyselect and gtsummary select helper functions are also accepted. Default is everything().
return_calls	Logical. Default is FALSE. If TRUE, the calls are returned as a list of expressions.
strip_md_bold	DEPRECATED
file	File path for the output.
bold_header_rows	logical indicating whether to bold header rows. Default is TRUE

### Value

A huxtable object

### Excel Output

Use the `as_hux_xlsx()` function to save a copy of the table in an excel file. The file is saved using `huxtable::quick_xlsx()`.

### Author(s)

David Hugh-Jones, Daniel D. Sjoberg

### See Also

Other gtsummary output types: [as\\_flex\\_table\(\)](#), [as\\_gt\(\)](#), [as\\_kable\\_extra\(\)](#), [as\\_kable\(\)](#), [as\\_tibble.gtsummary\(\)](#)

## Examples

```
trial %>%
  dplyr::select(trt, age, grade) %>%
  tbl_summary(by = trt) %>%
  add_p() %>%
  as_hux_table()
```

---

as\_kable

*Convert gtsummary object to a kable object*

---

## Description

Output from `knitr::kable` is less full featured compared to summary tables produced with `gt`. For example, kable summary tables do not include indentation, footnotes, or spanning header rows.

## Usage

```
as_kable(x, ..., include = everything(), return_calls = FALSE)
```

## Arguments

<code>x</code>	Object created by a function from the gtsummary package (e.g. <code>tbl_summary</code> or <code>tbl_regression</code> )
<code>...</code>	Additional arguments passed to <code>knitr::kable</code>
<code>include</code>	Commands to include in output. Input may be a vector of quoted or unquoted names. <code>tidyselect</code> and <code>gtsummary</code> select helper functions are also accepted. Default is <code>everything()</code> .
<code>return_calls</code>	Logical. Default is <code>FALSE</code> . If <code>TRUE</code> , the calls are returned as a list of expressions.

## Details

Tip: To better distinguish variable labels and level labels when indenting is not supported, try `bold_labels()` or `italicize_levels()`.

## Value

A `knitr_kable` object

## Author(s)

Daniel D. Sjöberg

## See Also

Other gtsummary output types: `as_flex_table()`, `as_gt()`, `as_hux_table()`, `as_kable_extra()`, `as_tibble.gtsummary()`



**Examples**

```
trial %>%
  tbl_summary(by = trt) %>%
  bold_labels() %>%
  as_kable()
```

as\_kable\_extra

*Convert gtsummary object to a kableExtra object***Description**

Function converts a gtsummary object to a knitr::kable + kableExtra object. This allows the customized formatting available via knitr::kable() and kableExtra; as\_kable\_extra() supports arguments in knitr::kable(). as\_kable\_extra() output via gtsummary supports bold and italic cells for table bodies. Users are encouraged to leverage as\_kable\_extra() for enhanced pdf printing; for html output options there is better support via as\_gt().

**Usage**

```
as_kable_extra(
  x,
  escape = FALSE,
  format = NULL,
  ...,
  include = everything(),
  addtl_fmt = TRUE,
  return_calls = FALSE
)
```

**Arguments**

x	Object created by a function from the gtsummary package (e.g. <a href="#">tbl_summary</a> or <a href="#">tbl_regression</a> )
format, escape, ...	arguments passed to knitr::kable(). Default is escape = FALSE, and the format is auto-detected.
include	Commands to include in output. Input may be a vector of quoted or unquoted names. tidyselect and gtsummary select helper functions are also accepted. Default is everything().
addtl_fmt	logical indicating whether to include additional formatting. Default is TRUE. This is primarily used to escape special characters, convert markdown to LaTeX, and remove line breaks from the footnote.
return_calls	Logical. Default is FALSE. If TRUE, the calls are returned as a list of expressions.

**Value**

A kableExtra table

## PDF/LaTeX

This section shows options intended for use with `output: pdf_document` in `yml` of `.Rmd`.

When the default values of `as_kable_extra(escape = FALSE, addtl_fmt = TRUE)` are utilized, the following formatting occurs.

- Markdown bold, italic, and underline syntax in the headers, spanning headers, caption, and footnote will be converted to escaped LaTeX code
- Special characters in the table body, headers, spanning headers, caption, and footnote will be escaped with `.escape_latex()` or `.escape_latex2()`
- The `"\n"` symbol will be recognized as a line break in the table headers, spanning headers, caption, and the table body
- The `"\n"` symbol is removed from the footnotes

To suppress *these* additional formats, set `as_kable_extra(addtl_fmt = FALSE)`

Additional styling is available with `kableExtra::kable_styling()` as shown in Example 2, which implements row striping and repeated column headers in the presence of page breaks.

## HTML

This section discusses options intended for use with `output: html_document` in `yml` of `.Rmd`.

When the default values of `as_kable_extra(escape = FALSE, addtl_fmt = TRUE)` are utilized, the following formatting occurs.

- The default markdown syntax in the headers and spanning headers is removed
- Special characters in the table body, headers, spanning headers, caption, and footnote will be escaped with `.escape_html()`
- The `"\n"` symbol is removed from the footnotes

To suppress the additional formatting, set `as_kable_extra(addtl_fmt = FALSE)`

## Example Output

### Author(s)

Daniel D. Sjoberg

### See Also

Other `gtsummary` output types: [as\\_flex\\_table\(\)](#), [as\\_gt\(\)](#), [as\\_hux\\_table\(\)](#), [as\\_kable\(\)](#), [as\\_tibble.gtsummary\(\)](#)

## Examples

```
# basic gtsummary tbl to build upon
as_kable_extra_base <-
  trial %>%
  select(trt, age, stage) %>%
  tbl_summary(by = trt) %>%
  bold_labels()

# Example 1 (PDF via LaTeX) -----
```

```
# add linebreak in table header with '\n'
as_kable_extra_ex1_pdf <-
  as_kable_extra_base %>%
  modify_header(all_stat_cols() ~ "**{level}**\n*N = {n}*") %>%
  as_kable_extra()

# Example 2 (PDF via LaTeX) -----
# additional styling in `knitr::kable()` and with
# call to `kableExtra::kable_styling()`
as_kable_extra_ex2_pdf <-
  as_kable_extra_base %>%
  as_kable_extra(
    booktabs = TRUE,
    longtable = TRUE,
    linesep = ""
  ) %>%
  kableExtra::kable_styling(
    position = "left",
    latex_options = c("striped", "repeat_header"),
    stripe_color = "gray!15"
  )
```

---

as\_tibble.gtsummary    *Convert gtsummary object to a tibble*

---

## Description

Function converts a gtsummary object to a tibble.

## Usage

```
## S3 method for class 'gtsummary'
as_tibble(
  x,
  include = everything(),
  col_labels = TRUE,
  return_calls = FALSE,
  fmt_missing = FALSE,
  ...
)
```

## Arguments

x	Object created by a function from the gtsummary package (e.g. <a href="#">tbl_summary</a> or <a href="#">tbl_regression</a> )
include	Commands to include in output. Input may be a vector of quoted or unquoted names. tidyselect and gtsummary select helper functions are also accepted. Default is everything().
col_labels	Logical argument adding column labels to output tibble. Default is TRUE.
return_calls	Logical. Default is FALSE. If TRUE, the calls are returned as a list of expressions.

fmt\_missing Logical argument adding the missing value formats.  
 ... Not used

**Value**

a [tibble](#)

**Author(s)**

Daniel D. Sjoberg

**See Also**

Other gtsummary output types: [as\\_flex\\_table\(\)](#), [as\\_gt\(\)](#), [as\\_hux\\_table\(\)](#), [as\\_kable\\_extra\(\)](#), [as\\_kable\(\)](#)

**Examples**

```
tbl <-
  trial %>%
  select(trt, age, grade, response) %>%
  tbl_summary(by = trt)

as_tibble(tbl)

# without column labels
as_tibble(tbl, col_labels = FALSE)
```

---

`bold_italicize_labels_levels`

*Bold or Italicize labels or levels in gtsummary tables*

---

**Description**

Bold or Italicize labels or levels in gtsummary tables

**Usage**

```
bold_labels(x)

italicize_labels(x)

bold_levels(x)

italicize_levels(x)

## S3 method for class 'gtsummary'
bold_labels(x)

## S3 method for class 'gtsummary'
bold_levels(x)
```

```
## S3 method for class 'gtsummary'
italicize_labels(x)

## S3 method for class 'gtsummary'
italicize_levels(x)

## S3 method for class 'tbl_cross'
bold_labels(x)

## S3 method for class 'tbl_cross'
bold_levels(x)

## S3 method for class 'tbl_cross'
italicize_labels(x)

## S3 method for class 'tbl_cross'
italicize_levels(x)
```

### Arguments

x                    Object created using gtsummary functions

### Value

Functions return the same class of gtsummary object supplied

### Example Output

### Author(s)

Daniel D. Sjoberg

### See Also

Other `tbl_summary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_summary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [inline\\_text.tbl\\_summary\(\)](#), [inline\\_text.tbl\\_survfit\(\)](#), [modify](#), [separate\\_p\\_footnotes](#), [tbl\\_custom\\_summary\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_summary\(\)](#)

Other `tbl_regression` tools: [add\\_global\\_p\(\)](#), [add\\_q\(\)](#), [combine\\_terms\(\)](#), [inline\\_text.tbl\\_regression\(\)](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_regression\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

Other `tbl_uvregression` tools: [add\\_global\\_p\(\)](#), [add\\_q\(\)](#), [inline\\_text.tbl\\_uvregression\(\)](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_uvregression\(\)](#)

### Examples

```
# Example 1 -----
tbl_bold_ital_ex1 <-
  trial[c("trt", "age", "grade")] %>%
  tbl_summary() %>%
  bold_labels() %>%
  bold_levels() %>%
  italicize_labels() %>%
```

```
italicize_levels()
```

---

bold_p	<i>Bold significant p-values or q-values</i>
--------	--

---

### Description

Bold values below a chosen threshold (e.g. <0.05) in a gtsummary tables.

### Usage

```
bold_p(x, t = 0.05, q = FALSE)
```

### Arguments

x	Object created using gtsummary functions
t	Threshold below which values will be bold. Default is 0.05.
q	Logical argument. When TRUE will bold the q-value column rather than the p-values. Default is FALSE.

### Example Output

### Author(s)

Daniel D. Sjoberg, Esther Drill

### Examples

```
# Example 1 -----
bold_p_ex1 <-
  trial[c("age", "grade", "response", "trt")] %>%
  tbl_summary(by = trt) %>%
  add_p() %>%
  bold_p(t = 0.65)

# Example 2 -----
bold_p_ex2 <-
  glm(response ~ trt + grade, trial, family = binomial(link = "logit")) %>%
  tbl_regression(exponentiate = TRUE) %>%
  bold_p(t = 0.65)
```

---

combine_terms	<i>Combine terms in a regression model</i>
---------------	--

---

### Description

The function combines terms from a regression model, and replaces the terms with a single row in the output table. The p-value is calculated using `stats::anova()`.

### Usage

```
combine_terms(x, formula_update, label = NULL, quiet = NULL, ...)
```

### Arguments

x	a <code>tbl_regression</code> object
formula_update	formula update passed to the <code>stats::update</code> . This updated formula is used to construct a reduced model, and is subsequently passed to <code>stats::anova()</code> to calculate the p-value for the group of removed terms. See the <code>stats::update</code> help file for proper syntax. function's <code>formula.=</code> argument
label	Option string argument labeling the combined rows
quiet	Logical indicating whether to print messages in console. Default is FALSE
...	Additional arguments passed to <code>stats::anova</code>

### Value

`tbl_regression` object

### Example Output

### Author(s)

Daniel D. Sjoberg

### See Also

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

Other `tbl_regression` tools: [add\\_global\\_p\(\)](#), [add\\_q\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_regression](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_regression\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

### Examples

```
# Example 1 -----
# Logistic Regression Example, LRT p-value
combine_terms_ex1 <-
  glm(
    response ~ marker + I(marker^2) + grade,
    trial[c("response", "marker", "grade")] %>% na.omit(), # keep complete cases only!
    family = binomial
```

```
) %>%
tbl_regression(label = grade ~ "Grade", exponentiate = TRUE) %>%
# collapse non-linear terms to a single row in output using anova
combine_terms(
  formula_update = . ~ . - marker - I(marker^2),
  label = "Marker (non-linear terms)",
  test = "LRT"
)
```

---

continuous_summary	<i>Summarize a continuous variable</i>
--------------------	--

---

## Description

**[Experimental]** This helper, to be used with `tbl_custom_summary()`, creates a function summarizing a continuous variable.

## Usage

```
continuous_summary(variable)
```

## Arguments

variable	String indicating the name of the variable to be summarized. This variable should be continuous.
----------	--

## Details

When using `continuous_summary`, you can specify in the `statistic=` argument of `tbl_custom_summary()` the same continuous statistics than in `tbl_summary()`. See the *statistic argument* section of the help file of `tbl_summary()`.

## Example Output

## Author(s)

Joseph Larmarange

## See Also

Other `tbl_custom_summary` tools: `add_overall()`, `proportion_summary()`, `ratio_summary()`, `tbl_custom_summary()`



**Examples**

```
# Example 1 -----
continuous_summary_ex1 <-
  trial %>%
  tbl_custom_summary(
    include = c("stage", "grade"),
    by = "trt",
    stat_fns = ~ continuous_summary("age"),
    statistic = ~"{median} [{p25}]{p75}]",
    overall_row = TRUE,
    overall_row_label = "All stages & grades"
  ) %>%
  modify_footnote(
    update = all_stat_cols() ~ "Median age (IQR)"
  )
```

---

 custom\_tidiers

*Collection of custom tidiers*


---

**Description**

**[Maturing]** Collection of tidiers that can be utilized in gtsummary. See details below.

**Usage**

```
tidy_standardize(
  x,
  exponentiate = FALSE,
  conf.level = 0.95,
  conf.int = TRUE,
  ...,
  quiet = FALSE
)

tidy_bootstrap(
  x,
  exponentiate = FALSE,
  conf.level = 0.95,
  conf.int = TRUE,
  ...,
  quiet = FALSE
)

tidy_robust(
  x,
  exponentiate = FALSE,
  conf.level = 0.95,
  conf.int = TRUE,
  vcov = NULL,
  vcov_args = NULL,
  ...,
```

```

  quiet = FALSE
)

pool_and_tidy_mice(x, pool.args = NULL, ..., quiet = FALSE)

tidy_gam(x, conf.int = FALSE, exponentiate = FALSE, conf.level = 0.95, ...)

tidy_wald_test(x, tidy_fun = NULL, ...)

```

### Arguments

x	a regression model object
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. This is typical for logistic and multinomial regressions, but a bad idea if there is no log or logit link. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if <code>conf.int = TRUE</code> . Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
...	arguments passed to method; <ul style="list-style-type: none"> <li>• <code>pool_and_tidy_mice(): mice::tidy(x, ...)</code></li> <li>• <code>tidy_standardize(): parameters::standardize_parameters(x, ...)</code></li> <li>• <code>tidy_bootstrap(): parameters::bootstrap_parameters(x, ...)</code></li> <li>• <code>tidy_robust(): parameters::model_parameters(x, ...)</code></li> </ul>
quiet	Logical indicating whether to print messages in console. Default is FALSE
vcov, vcov_args	arguments passed to <code>parameters::model_parameters()</code> . At least one of these arguments <b>must</b> be specified.
pool.args	named list of arguments passed to <code>mice::pool()</code> in <code>pool_and_tidy_mice()</code> . Default is NULL
tidy_fun	Option to specify a particular tidier function for the model. Default is to use <code>broom::tidy()</code> , but if an error occurs then tidying of the model is attempted with <code>parameters::model_parameters()</code> , if installed.

### Regression Model Tidiers

These tidiers are passed to `tbl_regression()` and `tbl_uvregression()` to obtain modified results.

- `tidy_standardize()` tidier to report standardized coefficients. The `parameters` package includes a wonderful function to estimate standardized coefficients. The tidier uses the output from `parameters::standardize_parameters()`, and merely takes the result and puts it in `broom::tidy()` format.
- `tidy_bootstrap()` tidier to report bootstrapped coefficients. The `parameters` package includes a wonderful function to estimate bootstrapped coefficients. The tidier uses the output from `parameters::bootstrap_parameters(test = "p")`, and merely takes the result and puts it in `broom::tidy()` format.

- `tidy_robust()` tidier to report robust standard errors, confidence intervals, and p-values. The `parameters` package includes a wonderful function to calculate robust standard errors, confidence intervals, and p-values. The tidier uses the output from `parameters::model_parameters()`, and merely takes the result and puts it in `broom::tidy()` format. To use this function with `tbl_regression()`, pass a function with the arguments for `tidy_robust()` populated. This is easily done using `purrr::partial()` e.g. `tbl_regression(tidy_fun = partial(tidy_robust, vcov = "CL"))`
- `pool_and_tidy_mice()` tidier to report models resulting from multiply imputed data using the `mice` package. Pass the `mice` model object *before* the model results have been pooled. See example.

### Other Tidiers

- `tidy_wald_test()` tidier to report Wald p-values, wrapping the `aod::wald.test()` function. Use this tidier with `add_global_p(anova_fun = tidy_wald_test)`

### Example Output

### Examples

```
# Example 1 -----
mod <- lm(age ~ marker + grade, trial)

tbl_stnd <- tbl_regression(mod, tidy_fun = tidy_standardize)
tbl <- tbl_regression(mod)

tidy_standardize_ex1 <-
  tbl_merge(
    list(tbl_stnd, tbl),
    tab_spanner = c("**Standardized Model**", "**Original Model**")
  )

# Example 2 -----
# use "posthoc" method for coef calculation
tidy_standardize_ex2 <-
  tbl_regression(mod, tidy_fun = purrr::partial(tidy_standardize, method = "posthoc"))

# Example 3 -----
# Multiple Imputation using the mice package
set.seed(1123)
pool_and_tidy_mice_ex3 <-
  suppressWarnings(mice::mice(trial, m = 2)) %>%
  with(lm(age ~ marker + grade)) %>%
  tbl_regression()
```

---

inline\_text.gtsummary *Report statistics from summary tables inline*

---

### Description

Report statistics from summary tables inline

### Usage

```
## S3 method for class 'gtsummary'
inline_text(x, variable, level = NULL, column = NULL, pattern = NULL, ...)
```

### Arguments

x	gtsummary object
variable	Variable name of statistic to present
level	Level of the variable to display for categorical variables. Default is NULL
column	Column name to return from x\$table_body.
pattern	String indicating the statistics to return. Uses <a href="#">glue::glue</a> formatting. Default is NULL
...	Not used

### column + pattern

Some gtsummary tables report multiple statistics in a single cell, e.g. "{mean} ({sd})" in tbl\_summary() or tbl\_svsummary(). We often need to report just the mean or the SD, and that can be accomplished by using both the column= and pattern= arguments. When both of these arguments are specified, the column argument selects the column to report statistics from, and the pattern argument specifies which statistics to report, e.g. inline\_text(x, column = "stat\_1", pattern = "{mean}") reports just the mean from a tbl\_summary().

---

inline\_text.tbl\_cross *Report statistics from cross table inline*

---

### Description

**[Maturing]** Extracts and returns statistics from a tbl\_cross object for inline reporting in an R markdown document. Detailed examples in the [inline\\_text vignette](#)

### Usage

```
## S3 method for class 'tbl_cross'
inline_text(x, col_level = NULL, row_level = NULL, pvalue_fun = NULL, ...)
```

**Arguments**

x	a tbl_cross object
col_level	Level of the column variable to display. Default is NULL. Can also specify "p.value" for the p-value and "stat_0" for Total column.
row_level	Level of the row variable to display. Can also specify the 'Unknown' row. Default is NULL.
pvalue_fun	Function to round and format p-values. Default is <code>style_pvalue</code> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
...	Not used

**Value**

A string reporting results from a gtsummary table

**See Also**

Other tbl\_cross tools: [add\\_p.tbl\\_cross\(\)](#), [tbl\\_cross\(\)](#)

**Examples**

```
tbl_cross <-
  tbl_cross(trial, row = trt, col = response) %>%
  add_p()

inline_text(tbl_cross, row_level = "Drug A", col_level = "1")
inline_text(tbl_cross, row_level = "Total", col_level = "1")
inline_text(tbl_cross, col_level = "p.value")
```

---

```
inline_text.tbl_regression
```

*Report statistics from regression summary tables inline*

---

**Description**

Takes an object with class `tbl_regression`, and the location of the statistic to report and returns statistics for reporting inline in an R markdown document. Detailed examples in the [inline\\_text vignette](#)

**Usage**

```
## S3 method for class 'tbl_regression'
inline_text(
  x,
  variable,
  level = NULL,
  pattern = "{estimate} ({conf.level*100}% CI {conf.low}, {conf.high}; {p.value})",
```

```

estimate_fun = NULL,
pvalue_fun = NULL,
...
)

```

### Arguments

x	Object created from <a href="#">tbl_regression</a>
variable	Variable name of statistics to present
level	Level of the variable to display for categorical variables. Default is NULL, returning the top row in the table for the variable.
pattern	String indicating the statistics to return. Uses <a href="#">glue::glue</a> formatting. Default is "{estimate} ({conf.level}% CI {conf.low}, {conf.high}); {p.value}". All columns from x\$table_body are available to print as well as the confidence level (conf.level). See below for details.
estimate_fun	function to style model coefficient estimates. Columns 'estimate', 'conf.low', and 'conf.high' are formatted. Default is x\$inputs\$estimate_fun
pvalue_fun	function to style p-values and/or q-values. Default is function(x) style_pvalue(x, prepend_p = TRUE)
...	Not used

### Value

A string reporting results from a gtsummary table

### pattern argument

The following items (and more) are available to print. Use `print(x$table_body)` to print the table the estimates are extracted from.

- {estimate} coefficient estimate formatted with 'estimate\_fun'
- {conf.low} lower limit of confidence interval formatted with 'estimate\_fun'
- {conf.high} upper limit of confidence interval formatted with 'estimate\_fun'
- {p.value} p-value formatted with 'pvalue\_fun'
- {N} number of observations in model
- {label} variable/variable level label

### Author(s)

Daniel D. Sjoberg

### See Also

Other `tbl_regression` tools: [add\\_global\\_p\(\)](#), [add\\_q\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [combine\\_terms\(\)](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_regression\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

**Examples**

```

inline_text_ex1 <-
  glm(response ~ age + grade, trial, family = binomial(link = "logit")) %>%
  tbl_regression(exponentiate = TRUE)

inline_text(inline_text_ex1, variable = age)
inline_text(inline_text_ex1, variable = grade, level = "III")

```

---

```
inline_text.tbl_summary
```

*Report statistics from summary tables inline*

---

**Description**

Extracts and returns statistics from a `tbl_summary` object for inline reporting in an R markdown document. Detailed examples in the [inline\\_text vignette](#)

**Usage**

```

## S3 method for class 'tbl_summary'
inline_text(
  x,
  variable,
  column = NULL,
  level = NULL,
  pattern = NULL,
  pvalue_fun = NULL,
  ...
)

## S3 method for class 'tbl_svysummary'
inline_text(
  x,
  variable,
  column = NULL,
  level = NULL,
  pattern = NULL,
  pvalue_fun = NULL,
  ...
)

```

**Arguments**

<code>x</code>	Object created from <a href="#">tbl_summary</a>
<code>variable</code>	Variable name of statistic to present
<code>column</code>	Column name to return from <code>x\$table_body</code> . Can also pass the level of a by variable.
<code>level</code>	Level of the variable to display for categorical variables. Can also specify the 'Unknown' row. Default is <code>NULL</code>

pattern	String indicating the statistics to return. Uses <code>glue::glue</code> formatting. Default is pattern shown in <code>tbl_summary()</code> output
pvalue_fun	Function to round and format p-values. Default is <code>style_pvalue</code> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
...	Not used

**Value**

A string reporting results from a `gtsummary` table

**Author(s)**

Daniel D. Sjöberg

**See Also**

Other `tbl_summary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_summary()`, `add_q()`, `add_stat_label()`, `bold_italicize_labels_levels`, `inline_text.tbl_survfit()`, `modify`, `separate_p_footnotes()`, `tbl_custom_summary()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_summary()`

**Examples**

```
t1 <- trial[c("trt", "grade")] %>%
  tbl_summary(by = trt) %>%
  add_p()

inline_text(t1, variable = grade, level = "I", column = "Drug A", pattern = "{n}/{N} ({p})%")
inline_text(t1, variable = grade, column = "p.value")
```

---

```
inline_text.tbl_survfit
```

*Report statistics from survfit tables inline*

---

**Description**

**[Maturing]** Extracts and returns statistics from a `tbl_survfit` object for inline reporting in an R markdown document. Detailed examples in the [inline\\_text vignette](#)

**Usage**

```
## S3 method for class 'tbl_survfit'
inline_text(
  x,
  variable = NULL,
  level = NULL,
  pattern = NULL,
  time = NULL,
  prob = NULL,
```



```

    column = NULL,
    estimate_fun = x$inputs$estimate_fun,
    pvalue_fun = NULL,
    ...
  )

```

### Arguments

x	Object created from <a href="#">tbl_survfit</a>
variable	Variable name of statistic to present.
level	Level of the variable to display for categorical variables. Can also specify the 'Unknown' row. Default is NULL
pattern	String indicating the statistics to return.
time	time for which to return survival probabilities.
prob	probability with values in (0,1)
column	column to print from x\$table_body. Columns may be selected with time= or prob= as well.
estimate_fun	Function to round and format estimate and confidence limits. Default is the same function used in <a href="#">tbl_survfit()</a>
pvalue_fun	Function to round and format p-values. Default is <a href="#">style_pvalue</a> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
...	Not used

### Value

A string reporting results from a gtsummary table

### Author(s)

Daniel D. Sjoberg

### See Also

Other `tbl_summary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_summary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_summary\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_custom\\_summary\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_summary\(\)](#)

### Examples

```

library(survival)
# fit survfit
fit1 <- survfit(Surv(ttdeath, death) ~ trt, trial)
fit2 <- survfit(Surv(ttdeath, death) ~ 1, trial)

# summarize survfit objects
tbl1 <-
  tbl_survfit(
    fit1,

```

```

    times = c(12, 24),
    label = ~"Treatment",
    label_header = "**{time} Month**"
  ) %>%
  add_p()

tbl2 <-
  tbl_survfit(
    fit2,
    probs = 0.5,
    label_header = "**Median Survival**"
  )

# report results inline
inline_text(tbl1, time = 24, level = "Drug B")
inline_text(tbl1, column = p.value)
inline_text(tbl2, prob = 0.5)

```

---

```
inline_text.tbl_uvregression
```

*Report statistics from regression summary tables inline*

---

## Description

Extracts and returns statistics from a table created by the `tbl_uvregression` function for inline reporting in an R markdown document. Detailed examples in the [inline\\_text vignette](#)

## Usage

```

## S3 method for class 'tbl_uvregression'
inline_text(
  x,
  variable,
  level = NULL,
  pattern = "{estimate} ({{conf.level*100}}% CI {conf.low}, {conf.high}; {p.value})",
  estimate_fun = NULL,
  pvalue_fun = NULL,
  ...
)

```

## Arguments

<code>x</code>	Object created from <a href="#">tbl_uvregression</a>
<code>variable</code>	Variable name of statistics to present
<code>level</code>	Level of the variable to display for categorical variables. Default is <code>NULL</code> , returning the top row in the table for the variable.
<code>pattern</code>	String indicating the statistics to return. Uses <a href="#">glue::glue</a> formatting. Default is <code>"{estimate} ({{conf.level}}% CI {conf.low}, {conf.high}; {p.value})"</code> . All columns from <code>x\$table_body</code> are available to print as well as the confidence level ( <code>conf.level</code> ). See below for details.

estimate_fun	function to style model coefficient estimates. Columns 'estimate', 'conf.low', and 'conf.high' are formatted. Default is x\$inputs\$estimate_fun
pvalue_fun	function to style p-values and/or q-values. Default is function(x) style_pvalue(x, prepend_p = TRUE)
...	Not used

**Value**

A string reporting results from a gtsummary table

**pattern argument**

The following items (and more) are available to print. Use `print(x$table_body)` to print the table the estimates are extracted from.

- {estimate} coefficient estimate formatted with 'estimate\_fun'
- {conf.low} lower limit of confidence interval formatted with 'estimate\_fun'
- {conf.high} upper limit of confidence interval formatted with 'estimate\_fun'
- {p.value} p-value formatted with 'pvalue\_fun'
- {N} number of observations in model
- {label} variable/variable level label

**Author(s)**

Daniel D. Sjöberg

**See Also**

Other `tbl_uvregression` tools: [add\\_global\\_p\(\)](#), [add\\_q\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_uvregression\(\)](#)

**Examples**

```
inline_text_ex1 <-
  trial[c("response", "age", "grade")] %>%
  tbl_uvregression(
    method = glm,
    method.args = list(family = binomial),
    y = response,
    exponentiate = TRUE
  )

inline_text(inline_text_ex1, variable = age)
inline_text(inline_text_ex1, variable = grade, level = "III")
```

---

modify	<i>Modify column headers, footnotes, spanning headers, and table captions</i>
--------	---

---

### Description

These functions assist with updating or adding column headers (`modify_header()`), footnotes (`modify_footnote()`), spanning headers (`modify_spanning_header()`), and table captions (`modify_caption()`). Use `show_header_names()` to learn the column names.

### Usage

```
modify_header(
  x,
  update = NULL,
  ...,
  text_interpret = c("md", "html"),
  quiet = NULL,
  stat_by = NULL
)
```

```
modify_footnote(
  x,
  update = NULL,
  ...,
  abbreviation = FALSE,
  text_interpret = c("md", "html"),
  quiet = NULL
)
```

```
modify_spanning_header(
  x,
  update = NULL,
  ...,
  text_interpret = c("md", "html"),
  quiet = NULL
)
```

```
modify_caption(x, caption, text_interpret = c("md", "html"))
```

```
show_header_names(x = NULL, include_example = TRUE, quiet = NULL)
```

### Arguments

- |             |  |
|-------------|--|
| x           | a gtsummary object   |
| update, ... | use these arguments to assign updates to headers, spanning headers, and footnotes. See examples below. <ul style="list-style-type: none"> <li>• update expects a list of assignments, with the variable name or selector on the LHS of the formula, and the updated string on the RHS. Also accepts a named list.</li> </ul> |

- ... pass individual updates outside of a list, e.g. `modify_header(p.value = "**P**", all_stat_cols() ~ "**{level}**")`
- Use the `show_header_names()` to see the column names that can be modified.
- `text_interpret` String indicates whether text will be interpreted with `gt::md()` or `gt::html()`. Must be "md" (default) or "html".
- `quiet` Logical indicating whether to print messages in console. Default is FALSE
- `stat_by` DEPRECATED, use `update = all_stat_cols() ~ "<label>"` instead.
- `abbreviation` Logical indicating if an abbreviation is being updated.
- `caption` a string of the table caption/title
- `include_example` logical whether to include print of `modify_header()` example

**Value**

Updated gtsummary object

**tbl\_summary(), tbl\_svsummary(), and tbl\_cross()**

When assigning column headers, footnotes, spanning headers, and captions for these gtsummary tables, you may use {N} to insert the number of observations. `tbl_svsummary` objects additionally have {N\_unweighted} available.

When there is a stratifying `by=` argument present, the following fields are additionally available to stratifying columns: {level}, {n}, and {p} ({n\_unweighted} and {p\_unweighted} for `tbl_svsummary` objects)

Syntax follows `glue::glue()`, e.g. `all_stat_cols() ~ "**{level}**", N = {n}"`.

**tbl\_regression()**

When assigning column headers for `tbl_regression` tables, you may use {N} to insert the number of observations, and {N\_event} for the number of events (when applicable).

**captions**

Captions are assigned based on output type.

- `gt::gt(caption=)`
- `flextable::set_caption(caption=)`
- `huxtable::set_caption(value=)`
- `knitr::kable(caption=)`

**Example Output****Author(s)**

Daniel D. Sjoberg

**See Also**

Other `tbl_summary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_summary()`, `add_q()`, `add_stat_label()`, `bold_italicize_labels_levels`, `inline_text.tbl_summary()`, `inline_text.tbl_survfit()`, `separate_p_footnotes()`, `tbl_custom_summary()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_summary()`

Other `tbl_svysummary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_svysummary()`, `add_q()`, `add_stat_label()`, `separate_p_footnotes()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_svysummary()`

Other `tbl_regression` tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `combine_terms()`, `inline_text.tbl_regression()`, `tbl_merge()`, `tbl_regression()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`

Other `tbl_uvregression` tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `inline_text.tbl_uvregression()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_uvregression()`

Other `tbl_survfit` tools: `add_n.tbl_survfit()`, `add_nevent.tbl_survfit()`, `add_p.tbl_survfit()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`, `tbl_survfit()`

**Examples**

```
# create summary table
tbl <- trial[c("age", "grade", "trt")] %>%
  tbl_summary(by = trt, missing = "no") %>%
  add_p()

# print the column names that can be modified
show_header_names(tbl)

# Example 1 -----
# updating column headers, footnote, and table caption
modify_ex1 <- tbl %>%
  modify_header(label = "**Variable**", p.value = "**P**") %>%
  modify_footnote(all_stat_cols() ~ "median (IQR) for Age; n (%) for Grade") %>%
  modify_caption("**Patient Characteristics** (N = {N})")

# Example 2 -----
# updating headers, remove all footnotes, add spanning header
modify_ex2 <- tbl %>%
  modify_header(all_stat_cols() ~ "**{level}**", N = {n} ({style_percent(p)}%)") %>%
  # use `modify_footnote(everything() ~ NA, abbreviation = TRUE)` to delete abbrev. footnotes
  modify_footnote(update = everything() ~ NA) %>%
  modify_spanning_header(all_stat_cols() ~ "**Treatment Received**")

# Example 3 -----
# updating an abbreviation in table footnote
modify_ex3 <-
  glm(response ~ age + grade, trial, family = binomial) %>%
  tbl_regression(exponentiate = TRUE) %>%
  modify_footnote(ci = "CI = Credible Interval", abbreviation = TRUE)
```

---

 modify\_column\_alignment

*Modify Column Alignment*


---

### Description

**[Maturing]** Update column alignment/justification in a gtsummary table.

### Usage

```
modify_column_alignment(x, columns, align = c("left", "right", "center"))
```

### Arguments

x	gtsummary object
columns	vector or selector of columns in x\$table_body
align	string indicating alignment of column, must be one of c("left", "right", "center")

### See Also

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

Other Advanced modifiers: [modify\\_column\\_hide\(\)](#), [modify\\_column\\_indent\(\)](#), [modify\\_column\\_merge\(\)](#), [modify\\_fmt\\_fun\(\)](#), [modify\\_table\\_body\(\)](#), [modify\\_table\\_styling\(\)](#)

### Examples

```
# Example 1 -----
tbl <-
  lm(age ~ marker + grade, trial) %>%
  tbl_regression() %>%
  modify_column_alignment(columns = everything(), align = "left")
```

---

 modify\_column\_hide

*Modify Hidden Columns*


---

### Description

**[Maturing]** Use these functions to hide or unhide columns in a gtsummary table.

### Usage

```
modify_column_hide(x, columns)
```

```
modify_column_unhide(x, columns)
```

**Arguments**

x	gtsummary object
columns	vector or selector of columns in x\$table_body

**Example Output****See Also**

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

Other Advanced modifiers: [modify\\_column\\_alignment\(\)](#), [modify\\_column\\_indent\(\)](#), [modify\\_column\\_merge\(\)](#), [modify\\_fmt\\_fun\(\)](#), [modify\\_table\\_body\(\)](#), [modify\\_table\\_styling\(\)](#)

**Examples**

```
# Example 1 -----
# hide 95% CI, and replace with standard error
modify_column_hide_ex1 <-
  lm(age ~ marker + grade, trial) %>%
  tbl_regression() %>%
  modify_column_hide(columns = ci) %>%
  modify_column_unhide(columns = std.error)
```

---

modify\_column\_indent    *Add/Remove Indentation*

---

**Description**

Add/Remove Indentation

**Usage**

```
modify_column_indent(
  x,
  columns,
  rows = NULL,
  double_indent = FALSE,
  undo = FALSE
)
```

**Arguments**

x	a gtsummary table
columns	columns to add indentation to
rows	predicate expression to select rows to indent. Default is NULL, indicating all rows
double_indent	logical indicating whether to double indent the cells. Default is FALSE for a single indentation
undo	logical indicating whether an indentation should be removed/undone. Default is FALSE



**Value**

a gtsummary table

**See Also**

Other Advanced modifiers: [modify\\_column\\_alignment\(\)](#), [modify\\_column\\_hide\(\)](#), [modify\\_column\\_merge\(\)](#), [modify\\_fmt\\_fun\(\)](#), [modify\\_table\\_body\(\)](#), [modify\\_table\\_styling\(\)](#)

**Examples**

```
# remove indentation from `tbl_summary()`
modify_column_indent_ex1 <-
  trial %>%
  select(grade) %>%
  tbl_summary() %>%
  modify_column_indent(columns = label, undo = TRUE)
```

---

modify\_column\_merge     *Modify Column Merging*

---

**Description**

**[Experimental]** Merge two or more columns in a gtsummary table. Use `show_header_names()` to print underlying column names.

**Usage**

```
modify_column_merge(x, pattern, rows = NULL)
```

**Arguments**

x	gtsummary object
pattern	glue syntax string indicating how to merge columns in <code>x\$table_body</code> . For example, to construct a confidence interval use <code>"{conf.low}, {conf.high}"</code> .
rows	predicate expression to select rows in <code>x\$table_body</code> . Can be used to style footnote, formatting functions, missing symbols, and text formatting. Default is NULL. See details below.

**Value**

gtsummary table

**Details**

1. Calling this function merely records the instructions to merge columns. The actual merging occurs when the gtsummary table is printed or converted with a function like `as_gt()`.
2. Because the column merging is delayed, it is recommended to perform major modifications to the table, such as those with `tbl_merge()` and `tbl_stack()`, before assigning merging instructions. Otherwise, unexpected formatting may occur in the final table.

3. If this functionality is used in conjunction with `tbl_stack()` (which includes `tbl_uvregression()`), there is potential issue with printing. When columns are stack AND when the column-merging is defined with a quosure, you may run into issues due to the loss of the environment when 2 or more quosures are combined. If the expression version of the quosure is the same as the quosure (i.e. no evaluated objects), there should be no issues. Regardless, this argument is used internally with care, and **it is *not* recommended for users**.

### Future Updates

There are planned updates to the implementation of this function with respect to the `pattern=` argument. Currently, this function replaces a numeric column with a formatted character column following `pattern=`. Once `gt::cols_merge()` gains the `rows=` argument the implementation will be updated to use it, which will keep numeric columns numeric. For the *vast majority* of users, *the planned change will be go unnoticed*.

If this functionality is used in conjunction with `tbl_stack()` (which includes `tbl_uvregression()`), there is potential issue with printing. When columns are stack AND when the column-merging is defined with a quosure, you may run into issues due to the loss of the environment when 2 or more quosures are combined. If the expression version of the quosure is the same as the quosure (i.e. no evaluated objects), there should be no issues. Regardless, this argument is used internally with care, and it is *not* recommended for users.

### Example Output

### See Also

Other Advanced modifiers: [modify\\_column\\_alignment\(\)](#), [modify\\_column\\_hide\(\)](#), [modify\\_column\\_indent\(\)](#), [modify\\_fmt\\_fun\(\)](#), [modify\\_table\\_body\(\)](#), [modify\\_table\\_styling\(\)](#)

### Examples

```
# Example 1 -----
modify_column_merge_ex1 <-
  trial %>%
  select(age, marker, trt) %>%
  tbl_summary(by = trt, missing = "no") %>%
  add_p(all_continuous() ~ "t.test",
    pvalue_fun = ~ style_pvalue(., prepend_p = TRUE)
  ) %>%
  modify_fmt_fun(statistic ~ style_sigfig) %>%
  modify_column_merge(pattern = "t = {statistic}; {p.value}") %>%
  modify_header(statistic ~ "***t-test**")

# Example 2 -----
modify_column_merge_ex2 <-
  lm(marker ~ age + grade, trial) %>%
  tbl_regression() %>%
  modify_column_merge(
    pattern = "{estimate} ({ci})",
    rows = !is.na(estimate)
  )
```

---

modify_fmt_fun	<i>Modify Formatting Functions</i>
----------------	------------------------------------

---

## Description

**[Maturing]** Use this function to update the way numeric columns and rows of `.$table_body` are formatted

## Usage

```
modify_fmt_fun(x, update, rows = NULL)
```

## Arguments

x	gtsummary object
update	list of formulas or a single formula specifying the updated formatting function. The LHS specifies the column(s) to be updated, and the RHS is the updated formatting function.
rows	predicate expression to select rows in <code>x\$table_body</code> . Default is NULL. See details below.

## Example Output

### rows argument

The rows argument accepts a predicate expression that is used to specify rows to apply formatting. The expression must evaluate to a logical when evaluated in `x$table_body`. For example, to apply formatting to the age rows pass `rows = variable == "age"`. A vector of row numbers is NOT acceptable.

A couple of things to note when using the rows= argument.

1. You can use saved objects to create the predicate argument, e.g. `rows = variable == letters[1]`.
2. The saved object cannot share a name with a column in `x$table_body`. The reason for this is that in `tbl_merge()` the columns are renamed, and the renaming process cannot disambiguate the variable column from an external object named variable in the following expression `rows = .data$variable = .env$variable`.

## See Also

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

Other Advanced modifiers: [modify\\_column\\_alignment\(\)](#), [modify\\_column\\_hide\(\)](#), [modify\\_column\\_indent\(\)](#), [modify\\_column\\_merge\(\)](#), [modify\\_table\\_body\(\)](#), [modify\\_table\\_styling\(\)](#)

**Examples**

```
# Example 1 -----
# show 'grade' p-values to 3 decimal places
modify_fmt_fun_ex1 <-
  lm(age ~ marker + grade, trial) %>%
  tbl_regression() %>%
  modify_fmt_fun(
    update = p.value ~ function(x) style_pvalue(x, digits = 3),
    rows = variable == "grade"
  )
```

---

modify_table_body	<i>Modify Table Body</i>
-------------------	--------------------------

---

**Description**

**[Maturing]** Function is for advanced manipulation of gtsummary tables. It allow users to modify the `.$table_body` data frame included in each gtsummary object.

If a new column is added to the table, default printing instructions will then be added to `.$table_styling`. By default, columns are hidden. To show a column, add a column header with `modify_header()`.

**Usage**

```
modify_table_body(x, fun, ...)
```

**Arguments**

x	gtsummary object
fun	A function or formula. If a <i>function</i> , it is used as is. If a <i>formula</i> , e.g. <code>fun = ~ .x %&gt;% arrange(variable)</code> , it is converted to a function. The argument passed to <code>fun=</code> is <code>x\$table_body</code> .
...	Additional arguments passed on to the mapped function

**Example Output****See Also**

`modify_table_styling()`

See [gtsummary internals vignette](#)

Other Advanced modifiers: [modify\\_column\\_alignment\(\)](#), [modify\\_column\\_hide\(\)](#), [modify\\_column\\_indent\(\)](#), [modify\\_column\\_merge\(\)](#), [modify\\_fmt\\_fun\(\)](#), [modify\\_table\\_styling\(\)](#)

**Examples**

```
# Example 1 -----
# Add number of cases and controls to regression table
modify_table_body_ex1 <-
  trial %>%
  select(response, age, marker) %>%
  tbl_uvregression(
    y = response,
    method = glm,
    method.args = list(family = binomial),
    exponentiate = TRUE,
    hide_n = TRUE
  ) %>%
  # adding number of non-events to table
  modify_table_body(
    ~ .x %>%
      dplyr::mutate(N_nonevent = N_obs - N_event) %>%
      dplyr::relocate(c(N_event, N_nonevent), .before = estimate)
  ) %>%
  # assigning header labels
  modify_header(N_nonevent = "**Control N**", N_event = "**Case N**") %>%
  modify_fmt_fun(c(N_event, N_nonevent) ~ style_number)
```

---

modify\_table\_styling *Modify Table Styling*

---

**Description**

This is a function meant for advanced users to gain more control over the characteristics of the resulting gtsummary table by directly modifying `.$table_styling`

**Usage**

```
modify_table_styling(
  x,
  columns,
  rows = NULL,
  label = NULL,
  spanning_header = NULL,
  hide = NULL,
  footnote = NULL,
  footnote_abbrev = NULL,
  align = NULL,
  missing_symbol = NULL,
  fmt_fun = NULL,
  text_format = NULL,
  undo_text_format = FALSE,
  text_interpret = c("md", "html"),
  cols_merge_pattern = NULL
)
```

**Arguments**

x	gtsummary object
columns	vector or selector of columns in x\$table_body
rows	predicate expression to select rows in x\$table_body. Can be used to style footnote, formatting functions, missing symbols, and text formatting. Default is NULL. See details below.
label	string of column label(s)
spanning_header	string with text for spanning header
hide	logical indicating whether to hide column from output
footnote	string with text for footnote
footnote_abbrev	string with abbreviation definition, e.g. "CI = Confidence Interval"
align	string indicating alignment of column, must be one of c("left", "right", "center")
missing_symbol	string indicating how missing values are formatted.
fmt_fun	function that formats the statistics in the columns/rows in columns= and rows=
text_format	string indicated which type of text formatting to apply to the rows and columns. Must be one of c("bold", "italic", "indent", "indent2"). Do not assign both "indent" and "indent2" to the same cell.
undo_text_format	rarely used. Logical that undoes the indent, bold, and italic styling when TRUE
text_interpret	string, must be one of "md" or "html"
cols_merge_pattern	<b>[Experimental]</b> glue-syntax string indicating how to merge columns in x\$table_body. For example, to construct a confidence interval use "{conf.low}, {conf.high}". The first column listed in the pattern string must match the single column name passed in columns=.

**Details**

Review the [gtsummary definition](#) vignette for information on .table\_styling objects.

**rows argument**

The rows argument accepts a predicate expression that is used to specify rows to apply formatting. The expression must evaluate to a logical when evaluated in x\$table\_body. For example, to apply formatting to the age rows pass rows = variable == "age". A vector of row numbers is NOT acceptable.

A couple of things to note when using the rows= argument.

1. You can use saved objects to create the predicate argument, e.g. rows = variable == letters[1].
2. The saved object cannot share a name with a column in x\$table\_body. The reason for this is that in tbl\_merge() the columns are renamed, and the renaming process cannot disambiguate the variable column from an external object named variable in the following expression rows = .data\$variable = .env\$variable.

**cols\_merge\_pattern argument**

There are planned updates to the implementation of column merging. Currently, this function replaces the numeric column with a formatted character column following `cols_merge_pattern=`. Once `gt::cols_merge()` gains the `rows=` argument the implementation will be updated to use it, which will keep numeric columns numeric. For the *vast majority* of users, *the planned change will be go unnoticed*.

If this functionality is used in conjunction with `tbl_stack()` (which includes `tbl_uvregression()`), there is potential issue with printing. When columns are stack AND when the column-merging is defined with a quosure, you may run into issues due to the loss of the environment when 2 or more quosures are combined. If the expression version of the quosure is the same as the quosure (i.e. no evaluated objects), there should be no issues. Regardless, this argument is used internally with care, and it is *not* recommended for users.

**See Also**

`modify_table_body()`

See [gtsummary internals vignette](#)

Review [list, formula, and selector syntax](#) used throughout `gtsummary`

Other Advanced modifiers: [modify\\_column\\_alignment\(\)](#), [modify\\_column\\_hide\(\)](#), [modify\\_column\\_indent\(\)](#), [modify\\_column\\_merge\(\)](#), [modify\\_fmt\\_fun\(\)](#), [modify\\_table\\_body\(\)](#)

---

 plot

*Plot Regression Coefficients*


---

**Description**

The `plot()` function extracts `x$table_body` and passes the it to `ggstats::ggcoef_plot()` along with a formatting options.

**Usage**

```
## S3 method for class 'tbl_regression'
plot(x, remove_header_rows = TRUE, remove_reference_rows = FALSE, ...)
```

```
## S3 method for class 'tbl_uvregression'
plot(x, remove_header_rows = TRUE, remove_reference_rows = FALSE, ...)
```

**Arguments**

`x` `'tbl_regression'` or `'tbl_uvregression'` object

`remove_header_rows` logical indicating whether to remove header rows for categorical variables. Default is TRUE

`remove_reference_rows` logical indicating whether to remove reference rows for categorical variables. Default is FALSE.

`...` arguments passed to `ggstats::ggcoef_plot(...)`

**Details****[Experimental]****Value**

a ggplot

**Examples**

```
glm(response ~ marker + grade, trial, family = binomial) %>%
  tbl_regression(
    add_estimate_to_reference_rows = TRUE,
    exponentiate = TRUE
  ) %>%
  plot()
```

---

proportion\_summary      *Summarize a proportion*

---

**Description**

**[Experimental]** This helper, to be used with `tbl_custom_summary()`, creates a function computing a proportion and its confidence interval.

**Usage**

```
proportion_summary(
  variable,
  value,
  weights = NULL,
  na.rm = TRUE,
  conf.level = 0.95,
  method = c("wilson", "wilson.no.correct", "exact", "asymptotic")
)
```

**Arguments**

variable	String indicating the name of the variable from which the proportion will be computed.
value	Value (or list of values) of variable to be taken into account in the numerator.
weights	Optional string indicating the name of a weighting variable. If NULL, all observations will be assumed to have a weight equal to 1.
na.rm	Should missing values be removed before computing the proportion? (default is TRUE)
conf.level	Confidence level for the returned confidence interval. Must be strictly greater than 0 and less than 1. Default to 0.95, which corresponds to a 95 percent confidence interval.
method	Confidence interval method. Must be one of <code>c("wilson", "wilson.no.correct", "exact", "asymptotic")</code> . See details below.



**Details**

Computed statistics:

- {n} numerator, (weighted) number of observations equal to values
- {N} denominator, (weighted) number of observations
- {prop} proportion, i.e. n/N
- {conf.low} lower confidence interval
- {conf.high} upper confidence interval

Methods `c("wilson", "wilson.no.correct")` are calculated with `stats::prop.test()` (with `correct = c(TRUE, FALSE)`). The default method, "wilson", includes the Yates continuity correction. Methods `c("exact", "asymptotic")` are calculated with `Hmisc::binconf()` and the corresponding method.

**Example Output****Author(s)**

Joseph Larmarange

**See Also**

Other `tbl_custom_summary` tools: [add\\_overall\(\)](#), [continuous\\_summary\(\)](#), [ratio\\_summary\(\)](#), [tbl\\_custom\\_summary\(\)](#)

**Examples**

```
# Example 1 -----
proportion_summary_ex1 <-
  Titanic %>%
  as.data.frame() %>%
  tbl_custom_summary(
    include = c("Age", "Class"),
    by = "Sex",
    stat_fns = ~ proportion_summary("Survived", "Yes", weights = "Freq"),
    statistic = ~"{prop}% ({n}/{N}) [{conf.low}-{conf.high}]",
    digits = ~ list(
      function(x) {
        style_percent(x, digits = 1)
      },
      0, 0, style_percent, style_percent
    ),
    overall_row = TRUE,
    overall_row_last = TRUE
  ) %>%
  bold_labels() %>%
  modify_footnote(
    update = all_stat_cols() ~ "Proportion (%) of survivors (n/N) [95% CI]"
  )
```

---

ratio_summary	<i>Summarize the ratio of two variables</i>
---------------	---

---

### Description

**[Experimental]** This helper, to be used with `tbl_custom_summary()`, creates a function computing the ratio of two continuous variables and its confidence interval.

### Usage

```
ratio_summary(numerator, denominator, na.rm = TRUE, conf.level = 0.95)
```

### Arguments

numerator	String indicating the name of the variable to be summed for computing the numerator.
denominator	String indicating the name of the variable to be summed for computing the denominator.
na.rm	Should missing values be removed before summing the numerator and the denominator? (default is TRUE)
conf.level	Confidence level for the returned confidence interval. Must be strictly greater than 0 and less than 1. Default to 0.95, which corresponds to a 95 percent confidence interval.

### Details

Computed statistics:

- `{num}` sum of the variable defined by numerator
- `{denom}` sum of the variable defined by denominator
- `{ratio}` ratio of num by denom
- `{conf.low}` lower confidence interval
- `{conf.high}` upper confidence interval

Confidence interval is computed with `stats::poisson.test()`, if and only if num is an integer.

### Example Output

### Author(s)

Joseph Larmarange

### See Also

Other `tbl_custom_summary` tools: `add_overall()`, `continuous_summary()`, `proportion_summary()`, `tbl_custom_summary()`

**Examples**

```
# Example 1 -----
ratio_summary_ex1 <-
  trial %>%
  tbl_custom_summary(
    include = c("stage", "grade"),
    by = "trt",
    stat_fns = ~ ratio_summary("response", "ttdeath"),
    statistic = ~"{ratio} [{conf.low}; {conf.high}] ({num}/{denom})",
    digits = ~ c(3, 2, 2, 0, 0),
    overall_row = TRUE,
    overall_row_label = "All stages & grades"
  ) %>%
  bold_labels() %>%
  modify_footnote(
    update = all_stat_cols() ~ "Ratio [95% CI] (n/N)"
  )
```

---

remove_row_type	<i>Remove rows by type</i>
-----------------	----------------------------

---

**Description**

Removes either the header, reference, or missing rows from a gtsummary table.

**Usage**

```
remove_row_type(
  x,
  variables = everything(),
  type = c("header", "reference", "missing", "level", "all"),
  level_value = NULL
)
```

**Arguments**

x	gtsummary object
variables	variables to to remove rows from. Default is everything()
type	type of row to remove. Must be one of
level_value	When type='level' you can specify the <i>character</i> value of the level to remove. When NULL all levels are removed. c("header", "reference", "missing")

**Example Output****See Also**

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

**Examples**

```
# Example 1 -----
library(dplyr, warn.conflicts = FALSE, quietly = TRUE)
remove_row_type_ex1 <-
  trial %>%
  select(trt, age) %>%
  mutate(
    age60 = case_when(age < 60 ~ "<60", age >= 60 ~ "60+")
  ) %>%
  tbl_summary(by = trt, missing = "no") %>%
  remove_row_type(age60, type = "header")
```

---

 select\_helpers

*Select helper functions*


---

**Description**

Set of functions to supplement the tidymodels set of functions for selecting columns of data frames (and other items as well).

- `all_continuous()` selects continuous variables
- `all_continuous2()` selects only type "continuous2"
- `all_categorical()` selects categorical (including "dichotomous") variables
- `all_dichotomous()` selects only type "dichotomous"
- `all_tests()` selects variables by the name of the test performed
- `all_stat_cols()` selects columns from `tbl_summary/tbl_svsummary` object with summary statistics (i.e. "stat\_0", "stat\_1", "stat\_2", etc.)
- `all_interaction()` selects interaction terms from a regression model
- `all_intercepts()` selects intercept terms from a regression model
- `all_contrasts()` selects variables in regression model based on their type of contrast

**Usage**

```
all_continuous(continuous2 = TRUE)
```

```
all_continuous2()
```

```
all_categorical(dichotomous = TRUE)
```

```
all_dichotomous()
```

```
all_tests(tests = NULL)
```

```
all_stat_cols(stat_0 = TRUE)
```

```
all_interaction()
```

```
all_intercepts()
```

```
all_contrasts(contrasts_type = NULL)
```

**Arguments**

continuous2	Logical indicating whether to include continuous2 variables. Default is TRUE
dichotomous	Logical indicating whether to include dichotomous variables. Default is TRUE
tests	string indicating the test type of the variables to select, e.g. select all variables being compared with "t.test"
stat_0	When FALSE, will not select the "stat_0" column. Default is TRUE
contrasts_type	type of contrast to select. When NULL, all variables with a contrast will be selected. Default is NULL. Select among contrast types c("treatment", "sum", "poly", "helmert", "other")

**Value**

A character vector of column names selected

**Example Output****See Also**

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

**Examples**

```
select_ex1 <-
  trial %>%
  select(age, response, grade) %>%
  tbl_summary(
    statistic = all_continuous() ~ "{mean} ({sd})",
    type = all_dichotomous() ~ "categorical"
  )
```

---

separate\_p\_footnotes *Create footnotes for individual p-values*

---

**Description**

**[Experimental]** The usual presentation of footnotes for p-values on a gtsummary table is to have a single footnote that lists all statistical tests that were used to compute p-values on a given table. The separate\_p\_footnotes() function separates aggregated p-value footnotes to individual footnotes that denote the specific test used for each of the p-values.

**Usage**

```
separate_p_footnotes(x)
```

**Arguments**

x object with class "tbl\_summary" or "tbl\_svsummary"

## Example Output

## See Also

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

Other `tbl_summary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_summary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_summary\(\)](#), [inline\\_text.tbl\\_survfit\(\)](#), [modify](#), [tbl\\_custom\\_summary\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_summary\(\)](#)

Other `tbl_svysummary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_svysummary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_svysummary\(\)](#)

## Examples

```
# Example 1 -----
separate_p_footnotes_ex1 <-
  trial %>%
  select(trt, age, grade) %>%
  tbl_summary(by = trt) %>%
  add_p() %>%
  separate_p_footnotes()
```

---

set\_gtsummary\_theme    *Set a gtsummary theme*

---

## Description

**[Maturing]** Functions to **set**, **reset**, **get**, and evaluate **with** gtsummary themes.

- `set_gtsummary_theme()` set a theme
- `reset_gtsummary_theme()` reset themes
- `get_gtsummary_theme()` get a named list with all active theme elements
- `with_gtsummary_theme()` evaluate an expression with a theme temporarily set
- `check_gtsummary_theme()` checks if passed theme is valid

## Usage

```
set_gtsummary_theme(x, quiet = NULL)
```

```
reset_gtsummary_theme()
```

```
get_gtsummary_theme()
```

```
with_gtsummary_theme(
  x,
  expr,
  env = rlang::caller_env(),
  msg_ignored_elements = NULL
)
```

```
check_gtsummary_theme(x)
```

**Arguments**

x	A named list defining a gtsummary theme.
quiet	Logical indicating whether to print messages in console. Default is FALSE
expr	Expression to be evaluated with the theme specified in x= loaded
env	The environment in which to evaluate expr=
msg_ignored_elements	Default is NULL with no message printed. Pass a string that will be printed with <code>cli::cli_alert_info()</code> . The "{elements}" object contains vector of theme elements that will be overwritten and ignored.

**Details**

The default formatting and styling throughout the gtsummary package are taken from the published reporting guidelines of the top four urology journals: European Urology, The Journal of Urology, Urology and the British Journal of Urology International. Use this function to change the default reporting style to match another journal, or your own personal style.

**Example Output****See Also**

[Themes vignette](#)

Available [gtsummary themes](#)

**Examples**

```
# Setting JAMA theme for gtsummary
set_gtsummary_theme(theme_gtsummary_journal("jama"))
# Themes can be combined by including more than one
set_gtsummary_theme(theme_gtsummary_compact())

set_gtsummary_theme_ex1 <-
  trial %>%
  dplyr::select(age, grade, trt) %>%
  tbl_summary(by = trt) %>%
  add_stat_label() %>%
  as_gt()

# reset gtsummary theme
reset_gtsummary_theme()
```

---

sort_filter_p	<i>Sort and filter variables in table by p-values</i>
---------------	---

---

### Description

Sort and filter variables in table by p-values

### Usage

```
sort_p(x, q = FALSE)
```

```
filter_p(x, q = FALSE, t = 0.05)
```

### Arguments

x	An object created using gtsummary functions
q	Logical argument. When TRUE will the q-value column is used
t	p-values/q-values less than or equal to this threshold will be retained. Default is 0.05

### Example Output

### Author(s)

Karissa Whiting, Daniel D. Sjoberg

### Examples

```
# Example 1 -----
sort_filter_p_ex1 <-
  trial %>%
  select(age, grade, response, trt) %>%
  tbl_summary(by = trt) %>%
  add_p() %>%
  filter_p(t = 0.8) %>%
  sort_p()

# Example 2 -----
sort_p_ex2 <-
  glm(response ~ trt + grade, trial, family = binomial(link = "logit")) %>%
  tbl_regression(exponentiate = TRUE) %>%
  sort_p()
```



---

style_number	<i>Style numbers</i>
--------------	----------------------

---

**Description**

Style numbers

**Usage**

```
style_number(
  x,
  digits = 0,
  big.mark = NULL,
  decimal.mark = NULL,
  scale = 1,
  ...
)
```

**Arguments**

x	Numeric vector
digits	Integer or vector of integers specifying the number of decimals to round x=. When vector is passed, each integer is mapped 1:1 to the numeric values in x
big.mark	Character used between every 3 digits to separate hundreds/thousands/millions/etc. Default is ", ", except when decimal.mark = " " when the default is a space.
decimal.mark	The character to be used to indicate the numeric decimal point. Default is "." or <code>getOption("OutDec")</code>
scale	A scaling factor: x will be multiplied by scale before formatting.
...	Other arguments passed on to <code>base::format()</code>

**Value**

formatted character vector

**See Also**

Other style tools: [style\\_percent\(\)](#), [style\\_pvalue\(\)](#), [style\\_ratio\(\)](#), [style\\_sigfig\(\)](#)

**Examples**

```
c(0.111, 12.3) %>% style_number(digits = 1)
c(0.111, 12.3) %>% style_number(digits = c(1, 0))
```

---

style_percent	<i>Style percentages</i>
---------------	--------------------------

---

**Description**

Style percentages

**Usage**

```
style_percent(
  x,
  symbol = FALSE,
  digits = 0,
  big.mark = NULL,
  decimal.mark = NULL,
  ...
)
```

**Arguments**

x	numeric vector of percentages
symbol	Logical indicator to include percent symbol in output. Default is FALSE.
digits	number of digits to round large percentages (i.e. greater than 10%). Smaller percentages are rounded to digits + 1 places. Default is 0
big.mark	Character used between every 3 digits to separate hundreds/thousands/millions/etc. Default is ", ", except when decimal.mark = " " when the default is a space.
decimal.mark	The character to be used to indicate the numeric decimal point. Default is "." orgetOption("OutDec")
...	Other arguments passed on to base::format()

**Value**

A character vector of styled percentages

**Author(s)**

Daniel D. Sjoberg

**See Also**

See Table Gallery [vignette](#) for example

Other style tools: [style\\_number\(\)](#), [style\\_pvalue\(\)](#), [style\\_ratio\(\)](#), [style\\_sigfig\(\)](#)

**Examples**

```
percent_vals <- c(-1, 0, 0.0001, 0.005, 0.01, 0.10, 0.45356, 0.99, 1.45)
style_percent(percent_vals)
style_percent(percent_vals, symbol = TRUE, digits = 1)
```

---

style_pvalue	<i>Style p-values</i>
--------------	-----------------------

---

**Description**

Style p-values

**Usage**

```
style_pvalue(
  x,
  digits = 1,
  prepend_p = FALSE,
  big.mark = NULL,
  decimal.mark = NULL,
  ...
)
```

**Arguments**

x	Numeric vector of p-values.
digits	Number of digits large p-values are rounded. Must be 1, 2, or 3. Default is 1.
prepend_p	Logical. Should 'p=' be prepended to formatted p-value. Default is FALSE
big.mark	Character used between every 3 digits to separate hundreds/thousands/millions/etc. Default is ", ", except when decimal.mark = " " when the default is a space.
decimal.mark	The character to be used to indicate the numeric decimal point. Default is "." or <code>getOption("OutDec")</code>
...	Other arguments passed on to <code>base::format()</code>

**Value**

A character vector of styled p-values

**Author(s)**

Daniel D. Sjoberg

**See Also**

See `tbl_summary` [vignette](#) for examples

Other style tools: [style\\_number\(\)](#), [style\\_percent\(\)](#), [style\\_ratio\(\)](#), [style\\_sigfig\(\)](#)

**Examples**

```
pvals <- c(
  1.5, 1, 0.999, 0.5, 0.25, 0.2, 0.197, 0.12, 0.10, 0.0999, 0.06,
  0.03, 0.002, 0.001, 0.00099, 0.0002, 0.00002, -1
)
style_pvalue(pvals)
style_pvalue(pvals, digits = 2, prepend_p = TRUE)
```

---

 style\_ratio

*Style significant figure-like rounding for ratios*


---

### Description

When reporting ratios, such as relative risk or an odds ratio, we'll often want the rounding to be similar on each side of the number 1. For example, if we report an odds ratio of 0.95 with a confidence interval of 0.70 to 1.24, we would want to round to two decimal places for all values. In other words, 2 significant figures for numbers less than 1 and 3 significant figures 1 and larger. `style_ratio()` performs significant figure-like rounding in this manner.

### Usage

```
style_ratio(x, digits = 2, big.mark = NULL, decimal.mark = NULL, ...)
```

### Arguments

<code>x</code>	Numeric vector
<code>digits</code>	Integer specifying the number of significant digits to display for numbers below 1. Numbers larger than 1 will be <code>digits + 1</code> . Default is <code>digits = 2</code> .
<code>big.mark</code>	Character used between every 3 digits to separate hundreds/thousands/millions/etc. Default is <code>" , "</code> , except when <code>decimal.mark = " , "</code> when the default is a space.
<code>decimal.mark</code>	The character to be used to indicate the numeric decimal point. Default is <code>" . "</code> or <code>getOption("OutDec")</code>
<code>...</code>	Other arguments passed on to <code>base::format()</code>

### Value

A character vector of styled ratios

### Author(s)

Daniel D. Sjoberg

### See Also

Other style tools: [style\\_number\(\)](#), [style\\_percent\(\)](#), [style\\_pvalue\(\)](#), [style\\_sigfig\(\)](#)

### Examples

```
c(
  0.123, 0.9, 1.1234, 12.345, 101.234, -0.123,
  -0.9, -1.1234, -12.345, -101.234
) %>%
  style_ratio()
```

---

 style\_sigfig

*Style significant figure-like rounding*


---

### Description

Converts a numeric argument into a string that has been rounded to a significant figure-like number. Scientific notation output is avoided, however, and additional significant figures may be displayed for large numbers. For example, if the number of significant digits requested is 2, 123 will be displayed (rather than 120 or  $1.2 \times 10^2$ ).

### Usage

```
style_sigfig(
  x,
  digits = 2,
  scale = 1,
  big.mark = NULL,
  decimal.mark = NULL,
  ...
)
```

### Arguments

x	Numeric vector
digits	Integer specifying the minimum number of significant digits to display
scale	A scaling factor: x will be multiplied by scale before formatting.
big.mark	Character used between every 3 digits to separate hundreds/thousands/millions/etc. Default is ", ", except when decimal.mark = " " when the default is a space.
decimal.mark	The character to be used to indicate the numeric decimal point. Default is "." or <code>getOption("OutDec")</code>
...	Other arguments passed on to <code>base::format()</code>

### Value

A character vector of styled numbers

### Details

- Scientific notation output is avoided.
- If 2 significant figures are requested, the number is rounded to no more than 2 decimal places. For example, a number will be rounded to 2 decimals places when  $\text{abs}(x) < 1$ , 1 decimal place when  $\text{abs}(x) \geq 1$  &  $\text{abs}(x) < 10$ , and to the nearest integer when  $\text{abs}(x) \geq 10$ .
- Additional significant figures may be displayed for large numbers. For example, if the number of significant digits requested is 2, 123 will be displayed (rather than 120 or  $1.2 \times 10^2$ ).

### Author(s)

Daniel D. Sjoberg

**See Also**

Other style tools: [style\\_number\(\)](#), [style\\_percent\(\)](#), [style\\_pvalue\(\)](#), [style\\_ratio\(\)](#)

**Examples**

```
c(0.123, 0.9, 1.1234, 12.345, -0.123, -0.9, -1.1234, -132.345, NA, -0.001) %>%
  style_sigfig()
```

---

tbl\_butcher

*Reduce size of gtsummary objects*


---

**Description**

Some gtsummary objects can become large and the size becomes cumbersome when working with the object. The function removes all elements from a gtsummary object, except those required to print the table. This may result in gtsummary functions that add information or modify the table, such as `add_global_p()`, will no longer execute after the excess elements have been removed (aka butchered). Of note, the majority of `inline_text()` calls will continue to execute properly.

**Usage**

```
tbl_butcher(x, include = NULL)
```

**Arguments**

x	a gtsummary object
include	names of additional elements to retain in the gtsummary object. <code>c("table_body", "table_styling")</code> will always be retained. Default is NULL

**Value**

a gtsummary object

**Examples**

```
tbl_large <-
  trial %>%
  tbl_uvregression(
    y = age,
    method = lm
  )

tbl_butchered <-
  tbl_large %>%
  tbl_butcher()

# size comparison
object.size(tbl_large) %>% format(units = "Mb")
object.size(tbl_butchered) %>% format(units = "Mb")
```

---

tbl\_continuous                      *Summarize a continuous variable*


---

**Description**

**[Experimental]** Summarize a continuous variable by one or more categorical variables

**Usage**

```
tbl_continuous(
  data,
  variable,
  include = everything(),
  digits = NULL,
  by = NULL,
  statistic = NULL,
  label = NULL
)
```

**Arguments**

data	A data frame
variable	Variable name of the continuous column to be summarized
include	variables to include in the summary table. Default is everything()
digits	List of formulas specifying the number of decimal places to round continuous summary statistics. If not specified, an appropriate number of decimals to round statistics will be guessed based on the the variable's distribution.
by	A column name (quoted or unquoted) in data. Summary statistics will be calculated separately for each level of the by variable (e.g. by = trt). If NULL, summary statistics are calculated using all observations. To stratify a table by two or more variables, use tbl_strata()
statistic	List of formulas specifying types of summary statistics to display for each variable. The default is everything() ~ {median} ({p25}, {p75})
label	List of formulas specifying variables labels, e.g. list(age ~ "Age", stage ~ "Path T Stage"). If a variable's label is not specified here, the label attribute (attr(data\$age, "label")) is used. If attribute label is NULL, the variable name will be used.

**Value**

a gtsummary table

**Example Output****See Also**

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

Other tbl\_continuous tools: [add\\_overall\(\)](#), [add\\_p.tbl\\_continuous\(\)](#)

**Examples**

```
# Example 1 -----
tbl_continuous_ex1 <-
  tbl_continuous(
    data = trial,
    variable = age,
    by = trt,
    include = grade
  )

# Example 2 -----
tbl_continuous_ex2 <-
  tbl_continuous(
    data = trial,
    variable = age,
    include = c(trt, grade)
  )
```

tbl\_cross

*Create a cross table of summary statistics***Description**

The function creates a cross table of two categorical variables.

**Usage**

```
tbl_cross(
  data,
  row = NULL,
  col = NULL,
  label = NULL,
  statistic = NULL,
  digits = NULL,
  percent = c("none", "column", "row", "cell"),
  margin = c("column", "row"),
  missing = c("ifany", "always", "no"),
  missing_text = "Unknown",
  margin_text = "Total"
)
```

**Arguments**

data	A data frame
row	A column name in data= to be used for the rows of cross table.
col	A column name in data= to be used for the columns of cross table.
label	List of formulas specifying variables labels, e.g. list(age ~ "Age", stage ~ "Path T Stage"). If a variable's label is not specified here, the label attribute (attr(data\$age, "label")) is used. If attribute label is NULL, the variable name will be used.



statistic	A string with the statistic name in curly brackets to be replaced with the numeric statistic (see <code>glue::glue</code> ). The default is <code>{n}</code> . If percent argument is "column", "row", or "cell", default is <code>{n} ({p}%)</code> .
digits	Specifies the number of decimal places to round the summary statistics. By default integers are shown to the zero decimal places, and percentages are formatted with <code>style_percent()</code> . If you would like to modify either of these, pass a vector of integers indicating the number of decimal places to round the statistics. For example, if the statistic being calculated is <code>{n} ({p}%)</code> and you want the percent rounded to 2 decimal places use <code>digits = c(0, 2)</code> . User may also pass a styling function: <code>digits = style_sigfig</code>
percent	Indicates the type of percentage to return. Must be one of "none", "column", "row", or "cell". Default is "cell" when <code>{N}</code> or <code>{p}</code> is used in statistic.
margin	Indicates which margins to add to the table. Default is <code>c("row", "column")</code> . Use <code>margin = NULL</code> to suppress both row and column margins.
missing	Indicates whether to include counts of NA values in the table. Allowed values are "no" (never display NA values), "ifany" (only display if any NA values), and "always" (includes NA count row for all variables). Default is "ifany".
missing_text	String to display for count of missing observations. Default is "Unknown".
margin_text	Text to display for margin totals. Default is "Total"

**Value**

A `tbl_cross` object

**Example Output****Author(s)**

Karissa Whiting, Daniel D. Sjoberg

**See Also**

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

Other `tbl_cross` tools: [add\\_p.tbl\\_cross\(\)](#), [inline\\_text.tbl\\_cross\(\)](#)

**Examples**

```
# Example 1 -----
tbl_cross_ex1 <-
  trial %>%
  tbl_cross(row = trt, col = response) %>%
  bold_labels()

# Example 2 -----
tbl_cross_ex2 <-
  trial %>%
  tbl_cross(row = stage, col = trt, percent = "cell") %>%
  add_p() %>%
  bold_labels()
```

---

tbl\_custom\_summary      *Create a table of summary statistics using a custom summary function*


---

### Description

**[Experimental]** The `tbl_custom_summary()` function calculates descriptive statistics for continuous, categorical, and dichotomous variables. This function is similar to `tbl_summary()` but allows you to provide a custom function in charge of computing the statistics (see Details).

### Usage

```
tbl_custom_summary(
  data,
  by = NULL,
  label = NULL,
  stat_fns,
  statistic,
  digits = NULL,
  type = NULL,
  value = NULL,
  missing = NULL,
  missing_text = NULL,
  include = everything(),
  overall_row = FALSE,
  overall_row_last = FALSE,
  overall_row_label = NULL
)
```

### Arguments

<code>data</code>	A data frame
<code>by</code>	A column name (quoted or unquoted) in <code>data</code> . Summary statistics will be calculated separately for each level of the <code>by</code> variable (e.g. <code>by = trt</code> ). If <code>NULL</code> , summary statistics are calculated using all observations. To stratify a table by two or more variables, use <code>tbl_strata()</code>
<code>label</code>	List of formulas specifying variables labels, e.g. <code>list(age ~ "Age", stage ~ "Path T Stage")</code> . If a variable's label is not specified here, the label attribute ( <code>attr(data\$age, "label")</code> ) is used. If attribute <code>label</code> is <code>NULL</code> , the variable name will be used.
<code>stat_fns</code>	Formula or list of formulas specifying the function to be used to compute the statistics (see below for details and examples). You can also use dedicated helpers such as <code>continuous_summary()</code> , <code>ratio_summary()</code> or <code>proportion_summary()</code> .
<code>statistic</code>	List of formulas specifying the <code>glue::glue()</code> pattern to display the statistics for each variable. The statistics should be returned by the functions specified in <code>stat_fns</code> (see below for details and examples).
<code>digits</code>	List of formulas specifying the number of decimal places to round summary statistics. If not specified, <code>tbl_summary</code> guesses an appropriate number of decimals to round statistics. When multiple statistics are displayed for a single variable, supply a vector rather than an integer. For example, if the statistic being calculated is <code>"{mean} ({sd})"</code> and you want the mean rounded to 1 decimal

	place, and the SD to 2 use <code>digits = list(age ~ c(1, 2))</code> . User may also pass a styling function: <code>digits = age ~ style_sigfig</code>
<code>type</code>	List of formulas specifying variable types. Accepted values are <code>c("continuous", "continuous2", "categorical", "dichotomous")</code> , e.g. <code>type = list(age ~ "continuous", female ~ "dichotomous")</code> . If type not specified for a variable, the function will default to an appropriate summary type. See below for details.
<code>value</code>	List of formulas specifying the value to display for dichotomous variables. <code>gt-summary</code> selectors, e.g. <code>all_dichotomous()</code> , cannot be used with this argument. See below for details.
<code>missing</code>	Indicates whether to include counts of NA values in the table. Allowed values are "no" (never display NA values), "ifany" (only display if any NA values), and "always" (includes NA count row for all variables). Default is "ifany".
<code>missing_text</code>	String to display for count of missing observations. Default is "Unknown".
<code>include</code>	variables to include in the summary table. Default is <code>everything()</code>
<code>overall_row</code>	Logical indicator to display an overall row. Default is FALSE. Use <code>add_overall()</code> to add an overall column.
<code>overall_row_last</code>	Logical indicator to display overall row last in table. Default is FALSE, which will display overall row first.
<code>overall_row_label</code>	String indicating the overall row label. Default is "Overall".

## Value

A `tbl_custom_summary` and `tbl_summary` object

## Similarities with `tbl_summary()`

Please refer to the help file of `tbl_summary()` regarding the use of select helpers, and arguments `include`, `by`, `type`, `value`, `digits`, `missing` and `missing_text`.

## `stat_fns` argument

The `stat_fns` argument specify the custom function(s) to be used for computing the summary statistics. For example, `stat_fns = everything() ~ foo`.

Each function may take the following arguments: `foo(data, full_data, variable, by, type, ...)`

- `data=` is the input data frame passed to `tbl_custom_summary()`, subset according to the level of `by` or `variable` if any, excluding NA values of the current variable
- `full_data=` is the full input data frame passed to `tbl_custom_summary()`
- `variable=` is a string indicating the variable to perform the calculation on
- `by=` is a string indicating the by variable from `tbl_custom_summary=`, if present
- `type=` is a string indicating the type of variable (continuous, categorical, ...)
- `stat_display=` a string indicating the statistic to display (for the statistic argument, for that variable)

The user-defined does not need to utilize each of these inputs. It's encouraged the user-defined function accept `...` as each of the arguments *will* be passed to the function, even if not all inputs are utilized by the user's function, e.g. `foo(data, ...)` (see examples).

The user-defined function should return a one row `dplyr::tibble()` with one column per summary statistics (see examples).

**statistic argument**

The statistic argument specifies the statistics presented in the table. The input is a list of formulas that specify the statistics to report. For example, `statistic = list(age ~ "{mean} ({sd})")`. A statistic name that appears between curly brackets will be replaced with the numeric statistic (see [glue::glue\(\)](#)). All the statistics indicated in the statistic argument should be returned by the functions defined in the `stat_fns` argument.

When the summary type is "continuous2", pass a vector of statistics. Each element of the vector will result in a separate row in the summary table.

For both categorical and continuous variables, statistics on the number of missing and non-missing observations and their proportions are also available to display.

- `{N_obs}` total number of observations
- `{N_miss}` number of missing observations
- `{N_nonmiss}` number of non-missing observations
- `{p_miss}` percentage of observations missing
- `{p_nonmiss}` percentage of observations not missing

Note that for categorical variables, `{N_obs}`, `{N_miss}` and `{N_nonmiss}` refer to the total number, number missing and number non missing observations in the denominator, not at each level of the categorical variable.

It is recommended to use [modify\\_footnote\(\)](#) to properly describe the displayed statistics (see examples).

**Caution**

The returned table is compatible with all `gtsummary` features applicable to a `tbl_summary` object, like [add\\_overall\(\)](#), [modify\\_footnote\(\)](#) or [bold\\_labels\(\)](#).

However, some of them could be inappropriate in such case. In particular, [add\\_p\(\)](#) do not take into account the type of displayed statistics and always return the p-value of a comparison test of the current variable according to the by groups, which may be incorrect if the displayed statistics refer to a third variable.

**Example Output****Author(s)**

Joseph Larmarange

**See Also**

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

Other `tbl_summary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_summary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_summary\(\)](#), [inline\\_text.tbl\\_survfit\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_summary\(\)](#)

Other `tbl_custom_summary` tools: [add\\_overall\(\)](#), [continuous\\_summary\(\)](#), [proportion\\_summary\(\)](#), [ratio\\_summary\(\)](#)

**Examples**

```

# Example 1 -----
my_stats <- function(data, ...) {
  marker_sum <- sum(data$marker, na.rm = TRUE)
  mean_age <- mean(data$age, na.rm = TRUE)
  dplyr::tibble(
    marker_sum = marker_sum,
    mean_age = mean_age
  )
}

my_stats(trial)

tbl_custom_summary_ex1 <-
  trial %>%
  tbl_custom_summary(
    include = c("stage", "grade"),
    by = "trt",
    stat_fns = everything() ~ my_stats,
    statistic = everything() ~ "A: {mean_age} - S: {marker_sum}",
    digits = everything() ~ c(1, 0),
    overall_row = TRUE,
    overall_row_label = "All stages & grades"
  ) %>%
  add_overall(last = TRUE) %>%
  modify_footnote(
    update = all_stat_cols() ~ "A: mean age - S: sum of marker"
  ) %>%
  bold_labels()

# Example 2 -----
# Use `data[[variable]]` to access the current variable
mean_ci <- function(data, variable, ...) {
  test <- t.test(data[[variable]])
  dplyr::tibble(
    mean = test$estimate,
    conf.low = test$conf.int[1],
    conf.high = test$conf.int[2]
  )
}

tbl_custom_summary_ex2 <-
  trial %>%
  tbl_custom_summary(
    include = c("marker", "ttdeath"),
    by = "trt",
    stat_fns = ~mean_ci,
    statistic = ~"{mean} [{conf.low}; {conf.high}]"
  ) %>%
  add_overall(last = TRUE) %>%
  modify_footnote(
    update = all_stat_cols() ~ "mean [95% CI]"
  )

# Example 3 -----
# Use `full_data` to access the full datasets

```

```

# Returned statistic can also be a character
diff_to_great_mean <- function(data, full_data, ...) {
  mean <- mean(data$marker, na.rm = TRUE)
  great_mean <- mean(full_data$marker, na.rm = TRUE)
  diff <- mean - great_mean
  dplyr::tibble(
    mean = mean,
    great_mean = great_mean,
    diff = diff,
    level = ifelse(diff > 0, "high", "low")
  )
}

tbl_custom_summary_ex3 <-
  trial %>%
  tbl_custom_summary(
    include = c("grade", "stage"),
    by = "trt",
    stat_fns = ~diff_to_great_mean,
    statistic = ~"{mean} ({level}, diff: {diff})",
    overall_row = TRUE
  ) %>%
  bold_labels()

```

---

tbl\_merge

---

*Merge two or more gtsummary objects*


---

## Description

Merges two or more `tbl_regression`, `tbl_uvregression`, `tbl_stack`, `tbl_summary`, or `tbl_svysummary` objects and adds appropriate spanning headers.

## Usage

```
tbl_merge(tbls, tab_spanner = NULL)
```

## Arguments

<code>tbls</code>	List of <code>gtsummary</code> objects to merge
<code>tab_spanner</code>	Character vector specifying the spanning headers. Must be the same length as <code>tbls</code> . The strings are interpreted with <code>gt::md</code> . Must be same length as <code>tbls</code> argument. Default is <code>NULL</code> , and places a default spanning header. If <code>FALSE</code> , no header will be placed.

## Value

A `tbl_merge` object

## Example Output

**Author(s)**

Daniel D. Sjoberg

**See Also**[tbl\\_stack](#)

Other `tbl_regression` tools: [add\\_global\\_p\(\)](#), [add\\_q\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [combine\\_terms\(\)](#), [inline\\_text.tbl\\_regression\(\)](#), [modify](#), [tbl\\_regression\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

Other `tbl_uvregression` tools: [add\\_global\\_p\(\)](#), [add\\_q\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_uvregression\(\)](#), [modify](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_uvregression\(\)](#)

Other `tbl_summary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_summary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_summary\(\)](#), [inline\\_text.tbl\\_survfit\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_custom\\_summary\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_summary\(\)](#)

Other `tbl_survfit` tools: [add\\_n.tbl\\_survfit\(\)](#), [add\\_nevent.tbl\\_survfit\(\)](#), [add\\_p.tbl\\_survfit\(\)](#), [modify](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_survfit\(\)](#)

Other `tbl_svysummary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_svysummary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#), [tbl\\_svysummary\(\)](#)

**Examples**

```
# Example 1 -----
# Side-by-side Regression Models
library(survival)
t1 <-
  glm(response ~ trt + grade + age, trial, family = binomial) %>%
  tbl_regression(exponentiate = TRUE)
t2 <-
  coxph(Surv(ttdeath, death) ~ trt + grade + age, trial) %>%
  tbl_regression(exponentiate = TRUE)
tbl_merge_ex1 <-
  tbl_merge(
    tbls = list(t1, t2),
    tab_spanner = c("**Tumor Response**", "**Time to Death**")
  )

# Example 2 -----
# Descriptive statistics alongside univariate regression, with no spanning header
t3 <-
  trial[c("age", "grade", "response")] %>%
  tbl_summary(missing = "no") %>%
  add_n() %>%
  modify_header(stat_0 ~ "**Summary Statistics**")
t4 <-
  tbl_uvregression(
    trial[c("ttdeath", "death", "age", "grade", "response")],
    method = coxph,
    y = Surv(ttdeath, death),
    exponentiate = TRUE,
    hide_n = TRUE
  )
```

```
tbl_merge_ex2 <-
  tbl_merge(tbls = list(t3, t4)) %>%
  modify_spanning_header(everything() ~ NA_character_)
```

---

tbl_regression	<i>Display regression model results in table</i>
----------------	--

---

## Description

This function takes a regression model object and returns a formatted table that is publication-ready. The function is highly customizable allowing the user to obtain a bespoke summary table of the regression model results. Review the [tbl\\_regression vignette](#) for detailed examples.

## Usage

```
tbl_regression(x, ...)

## Default S3 method:
tbl_regression(
  x,
  label = NULL,
  exponentiate = FALSE,
  include = everything(),
  show_single_row = NULL,
  conf.level = NULL,
  intercept = FALSE,
  estimate_fun = NULL,
  pvalue_fun = NULL,
  tidy_fun = NULL,
  add_estimate_to_reference_rows = FALSE,
  conf.int = NULL,
  ...
)
```

## Arguments

x	Regression model object
...	<b>[Experimental]</b> Additional arguments passed to <code>broom.helpers::tidy_plus_plus()</code> . See <code>?tidy_plus_plus_dots</code> for details.
label	List of formulas specifying variables labels, e.g. <code>list(age ~ "Age", stage ~ "Path T Stage")</code>
exponentiate	Logical indicating whether to exponentiate the coefficient estimates. Default is FALSE.
include	Variables to include in output. Input may be a vector of quoted variable names, unquoted variable names, or <code>tidyselect</code> select helper functions. Default is <code>everything()</code> .
show_single_row	By default categorical variables are printed on multiple rows. If a variable is dichotomous (e.g. Yes/No) and you wish to print the regression coefficient on a single row, include the variable name(s) here—quoted and unquoted variable name accepted.



<code>conf.level</code>	Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
<code>intercept</code>	Logical argument indicating whether to include the intercept in the output. Default is FALSE
<code>estimate_fun</code>	Function to round and format coefficient estimates. Default is <code>style_sigfig</code> when the coefficients are not transformed, and <code>style_ratio</code> when the coefficients have been exponentiated.
<code>pvalue_fun</code>	Function to round and format p-values. Default is <code>style_pvalue</code> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
<code>tidy_fun</code>	Option to specify a particular tidier function for the model. Default is to use <code>broom::tidy()</code> , but if an error occurs then tidying of the model is attempted with <code>parameters::model_parameters()</code> , if installed.
<code>add_estimate_to_reference_rows</code>	add a reference value. Default is FALSE
<code>conf.int</code>	Logical indicating whether or not to include a confidence interval in the output. Defaults to TRUE.

### Value

A `tbl_regression` object

### Methods

The default method for `tbl_regression()` model summary uses `broom::tidy(x)` to perform the initial tidying of the model object. There are, however, a few models that use [modifications](#).

- "parsnip/workflows": If the model was prepared using `parsnip/workflows`, the original model fit is extracted and the original `x=` argument is replaced with the model fit. This will typically go unnoticed; however, if you've provided a custom tidier in `tidy_fun=` the tidier will be applied to the model fit object and not the `parsnip/workflows` object.
- "survreg": The scale parameter is removed, `broom::tidy(x) %>% dplyr::filter(term != "Log(scale)")`
- "multinom": This multinomial outcome is complex, with one line per covariate per outcome (less the reference group)
- "gam": Uses the internal tidier `tidy_gam()` to print both parametric and smooth terms.
- "tidycrr": Uses the tidier `tidycmprsk::tidy()` to print the model terms.
- "lmerMod", "glmerMod", "glmmTMB", "glmmadmb", "stanreg", "brmsfit": These mixed effects models use `broom.mixed::tidy(x, effects = "fixed")`. Specify `tidy_fun = broom.mixed::tidy` to print the random components.

### Example Output

### Author(s)

Daniel D. Sjoberg

**See Also**

See `tbl_regression` [vignette](#) for detailed examples

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

Other `tbl_regression` tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `combine_terms()`, `inline_text.tbl_regression()`, `modify`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_strata()`

**Examples**

```
# Example 1 -----
library(survival)
tbl_regression_ex1 <-
  coxph(Surv(ttdeath, death) ~ age + marker, trial) %>%
  tbl_regression(exponentiate = TRUE)

# Example 2 -----
tbl_regression_ex2 <-
  glm(response ~ age + grade, trial, family = binomial(link = "logit")) %>%
  tbl_regression(exponentiate = TRUE)

# Example 3 -----
suppressMessages(library(lme4))
tbl_regression_ex3 <-
  glmer(am ~ hp + (1 | gear), mtcars, family = binomial) %>%
  tbl_regression(exponentiate = TRUE)
```

---

tbl\_split

*Split gtsummary table*


---

**Description**

**[Experimental]** The `tbl_split` function splits a single `gtsummary` table into multiple tables. Updates to the print method are expected.

**Usage**

```
tbl_split(x, ...)

## S3 method for class 'gtsummary'
tbl_split(x, variables, ...)

## S3 method for class 'tbl_split'
print(x, ...)
```

**Arguments**

<code>x</code>	gtsummary table
<code>...</code>	not used
<code>variables</code>	variables at which to split the <code>gtsummary</code> table rows (tables will be separated after each of these variables)

**Value**

tbl\_split object

**See Also**

Other tbl\_regression tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `combine_terms()`, `inline_text.tbl_regression()`, `modify`, `tbl_merge()`, `tbl_regression()`, `tbl_stack()`, `tbl_strata()`

Other tbl\_uvregression tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `inline_text.tbl_uvregression`, `modify`, `tbl_merge()`, `tbl_stack()`, `tbl_strata()`, `tbl_uvregression()`

Other tbl\_summary tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_summary()`, `add_q()`, `add_stat_label()`, `bold_italicize_labels_levels`, `inline_text.tbl_summary()`, `inline_text.tbl_survfit()`, `modify`, `separate_p_footnotes()`, `tbl_custom_summary()`, `tbl_merge()`, `tbl_stack()`, `tbl_strata()`, `tbl_summary()`

Other tbl\_survfit tools: `add_n.tbl_survfit()`, `add_nevent.tbl_survfit()`, `add_p.tbl_survfit()`, `modify`, `tbl_merge()`, `tbl_stack()`, `tbl_strata()`, `tbl_survfit()`

Other tbl\_svsummary tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_svsummary()`, `add_q()`, `add_stat_label()`, `modify`, `separate_p_footnotes()`, `tbl_merge()`, `tbl_stack()`, `tbl_strata()`, `tbl_svsummary()`

**Examples**

```
tbl <-
  tbl_summary(trial) %>%
  tbl_split(variables = c(marker, grade))
```

---

tbl\_stack

*Stacks two or more gtsummary objects*


---

**Description**

Assists in patching together more complex tables. `tbl_stack()` appends two or more `tbl_regression`, `tbl_summary`, `tbl_svsummary`, or `tbl_merge` objects. Column attributes, including number formatting and column footnotes, are retained from the first passed `gtsummary` object.

**Usage**

```
tbl_stack(tbls, group_header = NULL, quiet = NULL)
```

**Arguments**

<code>tbls</code>	List of <code>gtsummary</code> objects
<code>group_header</code>	Character vector with table headers where length matches the length of <code>tbls</code>
<code>quiet</code>	Logical indicating whether to print messages in console. Default is FALSE

**Value**

A `tbl_stack` object

## Example Output

### Author(s)

Daniel D. Sjoberg

### See Also

#### [tbl\\_merge](#)

Other `tbl_summary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_summary()`, `add_q()`, `add_stat_label()`, `bold_italicize_labels_levels`, `inline_text.tbl_summary()`, `inline_text.tbl_survfit()`, `modify`, `separate_p_footnotes()`, `tbl_custom_summary()`, `tbl_merge()`, `tbl_split()`, `tbl_strata()`, `tbl_summary()`

Other `tbl_svysummary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_svysummary()`, `add_q()`, `add_stat_label()`, `modify`, `separate_p_footnotes()`, `tbl_merge()`, `tbl_split()`, `tbl_strata()`, `tbl_svysummary()`

Other `tbl_regression` tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `combine_terms()`, `inline_text.tbl_regression()`, `modify`, `tbl_merge()`, `tbl_regression()`, `tbl_split()`, `tbl_strata()`

Other `tbl_uvregression` tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `inline_text.tbl_uvregression()`, `modify`, `tbl_merge()`, `tbl_split()`, `tbl_strata()`, `tbl_uvregression()`

Other `tbl_survfit` tools: `add_n.tbl_survfit()`, `add_nevent.tbl_survfit()`, `add_p.tbl_survfit()`, `modify`, `tbl_merge()`, `tbl_split()`, `tbl_strata()`, `tbl_survfit()`

### Examples

```
# Example 1 -----
# stacking two tbl_regression objects
t1 <-
  glm(response ~ trt, trial, family = binomial) %>%
  tbl_regression(
    exponentiate = TRUE,
    label = list(trt ~ "Treatment (unadjusted)")
  )

t2 <-
  glm(response ~ trt + grade + stage + marker, trial, family = binomial) %>%
  tbl_regression(
    include = "trt",
    exponentiate = TRUE,
    label = list(trt ~ "Treatment (adjusted)")
  )

tbl_stack_ex1 <- tbl_stack(list(t1, t2))

# Example 2 -----
# stacking two tbl_merge objects
library(survival)
t3 <-
  coxph(Surv(ttdeath, death) ~ trt, trial) %>%
  tbl_regression(
    exponentiate = TRUE,
    label = list(trt ~ "Treatment (unadjusted)")
  )
```

```

)

t4 <-
  coxph(Surv(ttdeath, death) ~ trt + grade + stage + marker, trial) %>%
  tbl_regression(
    include = "trt",
    exponentiate = TRUE,
    label = list(trt ~ "Treatment (adjusted)")
  )

# first merging, then stacking
row1 <- tbl_merge(list(t1, t3), tab_spanner = c("Tumor Response", "Death"))
row2 <- tbl_merge(list(t2, t4))
tbl_stack_ex2 <-
  tbl_stack(list(row1, row2), group_header = c("Unadjusted Analysis", "Adjusted Analysis"))

```

tbl\_strata

*Stratified gtsummary tables***Description**

**[Maturing]** Build a stratified gtsummary table. Any gtsummary table that accepts a data frame as its first argument can be stratified.

- In `tbl_strata()`, the stratified or subset data frame is passed to the function in `.tbl_fun=`, e.g. `purrr::map(data, .tbl_fun)`.
- In `tbl_strata2()`, both the stratified data frame and the strata level are passed to `.tbl_fun=`, e.g. `purrr::map2(data, strata, .tbl_fun)`

**Usage**

```

tbl_strata(
  data,
  strata,
  .tbl_fun,
  ...,
  .sep = ", ",
  .combine_with = c("tbl_merge", "tbl_stack"),
  .combine_args = NULL,
  .header = ifelse(.combine_with == "tbl_merge", "**{strata}**", "{strata}"),
  .stack_group_header = NULL,
  .quiet = NULL
)

tbl_strata2(
  data,
  strata,
  .tbl_fun,
  ...,
  .sep = ", ",

```

```

.combine_with = c("tbl_merge", "tbl_stack"),
.combine_args = NULL,
.header = ifelse(.combine_with == "tbl_merge", "**{strata}**", "{strata}"),
.stack_group_header = NULL,
.quiet = NULL
)

```

### Arguments

<code>data</code>	a data frame or survey object
<code>strata</code>	character vector or tidy-selector of columns in data to stratify results by
<code>.tbl_fun</code>	A function or formula. If a <i>function</i> , it is used as is. If a formula, e.g. <code>~ .x %&gt;% tbl_summary() %&gt;% add_p()</code> , it is converted to a function. The stratified data frame is passed to this function.
<code>...</code>	Additional arguments passed on to the <code>.tbl_fun</code> function.
<code>.sep</code>	when more than one stratifying variable is passed, this string is used to separate the levels in the spanning header. Default is <code>" , "</code>
<code>.combine_with</code>	One of <code>c("tbl_merge", "tbl_stack")</code> . Names the function used to combine the stratified tables.
<code>.combine_args</code>	named list of arguments that are passed to function specified in <code>.combine_with=</code>
<code>.header</code>	String indicating the headers that will be placed. Default is <code>"**{strata}**"</code> when <code>.combine_with = "tbl_merge"</code> and <code>"{strata}"</code> when <code>.combine_with = "tbl_stack"</code> . Items placed in curly brackets will be evaluated according to <code>glue::glue()</code> syntax. <ul style="list-style-type: none"> <li>• <code>strata</code> stratum levels</li> <li>• <code>n N</code> within stratum</li> <li>• <code>N</code> Overall N</li> </ul> <p>The evaluated value of <code>.header=</code> is also available within <code>tbl_strata2(.tbl_fun=)</code></p>
<code>.stack_group_header</code>	DEPRECATED.
<code>.quiet</code>	Logical indicating whether to print messages in console. Default is <code>FALSE</code>

### Tips

- `tbl_summary()`
  - The number of digits continuous variables are rounded to is determined separately within each stratum of the data frame. Set the `digits=` argument to ensure continuous variables are rounded to the same number of decimal places.
  - If some levels of a categorical variable are unobserved within a stratum, convert the variable to a factor to ensure all levels appear in each stratum's summary table.

### Example Output

### Author(s)

Daniel D. Sjoberg

**See Also**

Other `tbl_regression` tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `combine_terms()`, `inline_text.tbl_regression()`, `modify`, `tbl_merge()`, `tbl_regression()`, `tbl_split()`, `tbl_stack()`

Other `tbl_uvregression` tools: `add_global_p()`, `add_q()`, `bold_italicize_labels_levels`, `inline_text.tbl_uvregression`, `modify`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_uvregression()`

Other `tbl_summary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_summary()`, `add_q()`, `add_stat_label()`, `bold_italicize_labels_levels`, `inline_text.tbl_summary()`, `inline_text.tbl_survfit()`, `modify`, `separate_p_footnotes()`, `tbl_custom_summary()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_summary()`

Other `tbl_survfit` tools: `add_n.tbl_survfit()`, `add_nevent.tbl_survfit()`, `add_p.tbl_survfit()`, `modify`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_survfit()`

Other `tbl_svsummary` tools: `add_n.tbl_summary()`, `add_overall()`, `add_p.tbl_svsummary()`, `add_q()`, `add_stat_label()`, `modify`, `separate_p_footnotes()`, `tbl_merge()`, `tbl_split()`, `tbl_stack()`, `tbl_svsummary()`

**Examples**

```
# Example 1 -----
tbl_strata_ex1 <-
  trial %>%
  select(age, grade, stage, trt) %>%
  mutate(grade = paste("Grade", grade)) %>%
  tbl_strata(
    strata = grade,
    .tbl_fun =
      ~ .x %>%
      tbl_summary(by = trt, missing = "no") %>%
      add_n(),
    .header = "**{strata}**, N = {n}"
  )

# Example 2 -----
tbl_strata_ex2 <-
  trial %>%
  select(grade, response) %>%
  mutate(grade = paste("Grade", grade)) %>%
  tbl_strata2(
    strata = grade,
    .tbl_fun =
      ~ .x %>%
      tbl_summary(
        label = list(response = .y),
        missing = "no",
        statistic = response ~ "{p}"
      ) %>%
      add_ci(pattern = "{stat} ({ci})") %>%
      modify_header(stat_0 = "**Rate (95% CI)**") %>%
      modify_footnote(stat_0 = NA),
    .combine_with = "tbl_stack",
    .combine_args = list(group_header = NULL),
    .quiet = TRUE
  ) %>%
  modify_caption("**Response Rate by Grade**")
```

tbl\_summary

*Create a table of summary statistics***Description**

The `tbl_summary` function calculates descriptive statistics for continuous, categorical, and dichotomous variables. Review the [tbl\\_summary vignette](#) for detailed examples.

**Usage**

```
tbl_summary(
  data,
  by = NULL,
  label = NULL,
  statistic = NULL,
  digits = NULL,
  type = NULL,
  value = NULL,
  missing = NULL,
  missing_text = NULL,
  sort = NULL,
  percent = NULL,
  include = everything()
)
```

**Arguments**

<code>data</code>	A data frame
<code>by</code>	A column name (quoted or unquoted) in <code>data</code> . Summary statistics will be calculated separately for each level of the <code>by</code> variable (e.g. <code>by = trt</code> ). If <code>NULL</code> , summary statistics are calculated using all observations. To stratify a table by two or more variables, use <code>tbl_strata()</code>
<code>label</code>	List of formulas specifying variables labels, e.g. <code>list(age ~ "Age", stage ~ "Path T Stage")</code> . If a variable's label is not specified here, the label attribute ( <code>attr(data\$age, "label")</code> ) is used. If attribute label is <code>NULL</code> , the variable name will be used.
<code>statistic</code>	List of formulas specifying types of summary statistics to display for each variable. The default is <code>list(all_continuous() ~ "{median} ({p25}, {p75})", all_categorical() ~ "{n} ({p}%)")</code> . See below for details.
<code>digits</code>	List of formulas specifying the number of decimal places to round summary statistics. If not specified, <code>tbl_summary</code> guesses an appropriate number of decimals to round statistics. When multiple statistics are displayed for a single variable, supply a vector rather than an integer. For example, if the statistic being calculated is <code>"{mean} ({sd})"</code> and you want the mean rounded to 1 decimal place, and the SD to 2 use <code>digits = list(age ~ c(1, 2))</code> . User may also pass a styling function: <code>digits = age ~ style_sigfig</code>
<code>type</code>	List of formulas specifying variable types. Accepted values are <code>c("continuous", "continuous2", "categorical", "dichotomous")</code> , e.g. <code>type = list(age ~ "continuous", female ~ "dichotomous")</code> . If type not specified for a variable, the function will default to an appropriate summary type. See below for details.



value	List of formulas specifying the value to display for dichotomous variables. gt-summary selectors, e.g. all_dichotomous(), cannot be used with this argument. See below for details.
missing	Indicates whether to include counts of NA values in the table. Allowed values are "no" (never display NA values), "ifany" (only display if any NA values), and "always" (includes NA count row for all variables). Default is "ifany".
missing_text	String to display for count of missing observations. Default is "Unknown".
sort	List of formulas specifying the type of sorting to perform for categorical data. Options are frequency where results are sorted in descending order of frequency and alphanumeric, e.g. sort = list(everything() ~ "frequency")
percent	Indicates the type of percentage to return. Must be one of "column", "row", or "cell". Default is "column".
include	variables to include in the summary table. Default is everything()

### Value

A tbl\_summary object

### select helpers

**Select helpers** from the `\tidyselect\` package and `\gtsummary\` package are available to modify default behavior for groups of variables. For example, by default continuous variables are reported with the median and IQR. To change all continuous variables to mean and standard deviation use `statistic = list(all_continuous() ~ "{mean} ({sd})")`.

All columns with class logical are displayed as dichotomous variables showing the proportion of events that are TRUE on a single row. To show both rows (i.e. a row for TRUE and a row for FALSE) use `type = list(where(is.logical) ~ "categorical")`.

The select helpers are available for use in any argument that accepts a list of formulas (e.g. `statistic`, `type`, `digits`, `value`, `sort`, etc.)

Read more on the [syntax](#) used through the package.

### type argument

The `tbl_summary()` function has four summary types:

- "continuous" summaries are shown on a *single row*. Most numeric variables default to summary type continuous.
- "continuous2" summaries are shown on *2 or more rows*
- "categorical" *multi-line* summaries of nominal data. Character variables, factor variables, and numeric variables with fewer than 10 unique levels default to type categorical. To change a numeric variable to continuous that defaulted to categorical, use `type = list(varname ~ "continuous")`
- "dichotomous" categorical variables that are displayed on a *single row*, rather than one row per level of the variable. Variables coded as TRUE/FALSE, 0/1, or yes/no are assumed to be dichotomous, and the TRUE, 1, and yes rows are displayed. Otherwise, the value to display must be specified in the value argument, e.g. `value = list(varname ~ "level to show")`

**statistic argument**

The statistic argument specifies the statistics presented in the table. The input is a list of formulas that specify the statistics to report. For example, `statistic = list(age ~ "{mean} ({sd})")` would report the mean and standard deviation for age; `statistic = list(all_continuous() ~ "{mean} ({sd})")` would report the mean and standard deviation for all continuous variables. A statistic name that appears between curly brackets will be replaced with the numeric statistic (see [glue::glue](#)).

For categorical variables the following statistics are available to display.

- {n} frequency
- {N} denominator, or cohort size
- {p} formatted percentage

For continuous variables the following statistics are available to display.

- {median} median
- {mean} mean
- {sd} standard deviation
- {var} variance
- {min} minimum
- {max} maximum
- {sum} sum
- {p##} any integer percentile, where ## is an integer from 0 to 100
- {foo} any function of the form `foo(x)` is accepted where `x` is a numeric vector

When the summary type is "continuous2", pass a vector of statistics. Each element of the vector will result in a separate row in the summary table.

For both categorical and continuous variables, statistics on the number of missing and non-missing observations and their proportions are available to display.

- {N\_obs} total number of observations
- {N\_miss} number of missing observations
- {N\_nonmiss} number of non-missing observations
- {p\_miss} percentage of observations missing
- {p\_nonmiss} percentage of observations not missing

Note that for categorical variables, {N\_obs}, {N\_miss} and {N\_nonmiss} refer to the total number, number missing and number non missing observations in the denominator, not at each level of the categorical variable.

**Example Output****Author(s)**

Daniel D. Sjoberg

**See Also**

See [tbl\\_summary vignette](#) for detailed tutorial

See [table gallery](#) for additional examples

Review [list](#), [formula](#), and [selector syntax](#) used throughout gtsummary

Other tbl\_summary tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_summary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_summary\(\)](#), [inline\\_text.tbl\\_survfit\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_custom\\_summary\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

**Examples**

```
# Example 1 -----
tbl_summary_ex1 <-
  trial %>%
  select(age, grade, response) %>%
  tbl_summary()

# Example 2 -----
tbl_summary_ex2 <-
  trial %>%
  select(age, grade, response, trt) %>%
  tbl_summary(
    by = trt,
    label = list(age ~ "Patient Age"),
    statistic = list(all_continuous() ~ "{mean} ({sd})"),
    digits = list(age ~ c(0, 1))
  )

# Example 3 -----
# for convenience, you can also pass named lists to any arguments
# that accept formulas (e.g label, digits, etc.)
tbl_summary_ex3 <-
  trial %>%
  select(age, trt) %>%
  tbl_summary(
    by = trt,
    label = list(age = "Patient Age")
  )

# Example 4 -----
# multi-line summaries of continuous data with type 'continuous2'
tbl_summary_ex4 <-
  trial %>%
  select(age, marker) %>%
  tbl_summary(
    type = all_continuous() ~ "continuous2",
    statistic = all_continuous() ~ c("{median} ({p25}, {p75})", "{min}, {max}"),
    missing = "no"
  )
```

---

tbl_survfit	<i>Creates table of survival probabilities</i>
-------------	--

---

### Description

**[Maturing]** Function takes a survfit object as an argument, and provides a formatted summary table of the results

### Usage

```
tbl_survfit(x, ...)

## S3 method for class 'list'
tbl_survfit(
  x,
  times = NULL,
  probs = NULL,
  statistic = NULL,
  label = NULL,
  label_header = NULL,
  estimate_fun = NULL,
  missing = NULL,
  conf.level = 0.95,
  reverse = FALSE,
  quiet = NULL,
  ...
)

## S3 method for class 'survfit'
tbl_survfit(x, ...)

## S3 method for class 'data.frame'
tbl_survfit(x, y, include = everything(), ...)
```

### Arguments

x	a survfit object, list of survfit objects, or a data frame. If a data frame is passed, a list of survfit objects is constructed using each variable as a stratifying variable.
...	For <code>tbl_survfit.data.frame()</code> and <code>tbl_survfit.survfit()</code> the arguments are passed to <code>tbl_survfit.list()</code> . They are not used when <code>tbl_survfit.list()</code> is called directly.
times	numeric vector of times for which to return survival probabilities.
probs	numeric vector of probabilities with values in (0,1) specifying the survival quantiles to return
statistic	string defining the statistics to present in the table. Default is "{estimate} ({conf.low}, {conf.high})"
label	List of formulas specifying variables labels, e.g. <code>list(age ~ "Age, yrs", stage ~ "Path T Stage")</code> , or a string for a single variable table.

label_header	string specifying column labels above statistics. Default is "{prob} Percentile" for survival percentiles, and "Time {time}" for n-year survival estimates
estimate_fun	function to format the Kaplan-Meier estimates. Default is <code>style_percent()</code> for survival probabilities and <code>style_sigfig</code> for survival times
missing	text to fill when estimate is not estimable. Default is "--"
conf.level	Confidence level for confidence intervals. Default is 0.95
reverse	Flip the probability reported, i.e. $1 - \text{estimate}$ . Default is FALSE. Does not apply to survival quantile requests
quiet	Logical indicating whether to print messages in console. Default is FALSE
y	outcome call, e.g. <code>y = Surv(ttdeath, death)</code>
include	Variable to include as stratifying variables.

### Example Output

#### Author(s)

Daniel D. Sjoberg

#### See Also

Review [list, formula, and selector syntax](#) used throughout gtsummary

Other `tbl_survfit` tools: [add\\_n.tbl\\_survfit\(\)](#), [add\\_nevent.tbl\\_survfit\(\)](#), [add\\_p.tbl\\_survfit\(\)](#), [modify.tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

#### Examples

```
library(survival)

# Example 1 -----
# Pass single survfit() object
tbl_survfit_ex1 <- tbl_survfit(
  survfit(Surv(ttdeath, death) ~ trt, trial),
  times = c(12, 24),
  label_header = "**{time} Month**"
)

# Example 2 -----
# Pass a data frame
tbl_survfit_ex2 <- tbl_survfit(
  trial,
  y = Surv(ttdeath, death),
  include = c(trt, grade),
  probs = 0.5,
  label_header = "**Median Survival**"
)

# Example 3 -----
# Pass a list of survfit() objects
tbl_survfit_ex3 <-
  list(
    survfit(Surv(ttdeath, death) ~ 1, trial),
```

```

    survfit(Surv(ttdeath, death) ~ trt, trial)
  ) %>%
  tbl_survfit(times = c(12, 24))

# Example 4 Competing Events Example -----
# adding a competing event for death (cancer vs other causes)
set.seed(1123)
library(dplyr, warn.conflicts = FALSE, quietly = TRUE)
trial2 <- trial %>%
  mutate(
    death_cr = case_when(
      death == 0 ~ "censor",
      runif(n()) < 0.5 ~ "death from cancer",
      TRUE ~ "death other causes"
    ) %>% factor()
  )

survfit_cr_ex4 <-
  survfit(Surv(ttdeath, death_cr) ~ grade, data = trial2) %>%
  tbl_survfit(times = c(12, 24), label = "Tumor Grade")

```

---

tbl\_svysummary

---

*Create a table of summary statistics from a survey object*


---

## Description

The `tbl_svysummary` function calculates descriptive statistics for continuous, categorical, and dichotomous variables taking into account survey weights and design. It is similar to `tbl_summary()`.

## Usage

```
tbl_svysummary(
  data,
  by = NULL,
  label = NULL,
  statistic = NULL,
  digits = NULL,
  type = NULL,
  value = NULL,
  missing = NULL,
  missing_text = NULL,
  sort = NULL,
  percent = NULL,
  include = everything()
)
```

## Arguments

<code>data</code>	A survey object created with <code>survey::svydesign()</code>
<code>by</code>	A column name (quoted or unquoted) in <code>data</code> . Summary statistics will be calculated separately for each level of the <code>by</code> variable (e.g. <code>by = trt</code> ). If <code>NULL</code> , summary statistics are calculated using all observations. To stratify a table by two or more variables, use <code>tbl_strata()</code>

label	List of formulas specifying variables labels, e.g. <code>list(age ~ "Age", stage ~ "Path T Stage")</code> . If a variable's label is not specified here, the label attribute ( <code>attr(data\$age, "label")</code> ) is used. If attribute label is NULL, the variable name will be used.
statistic	List of formulas specifying types of summary statistics to display for each variable. The default is <code>list(all_continuous() ~ "{median} ({p25}, {p75})", all_categorical() ~ "{n} ({p}%)")</code> . See below for details.
digits	List of formulas specifying the number of decimal places to round summary statistics. If not specified, <code>tbl_summary</code> guesses an appropriate number of decimals to round statistics. When multiple statistics are displayed for a single variable, supply a vector rather than an integer. For example, if the statistic being calculated is <code>"{mean} ({sd})"</code> and you want the mean rounded to 1 decimal place, and the SD to 2 use <code>digits = list(age ~ c(1, 2))</code> . User may also pass a styling function: <code>digits = age ~ style_sigfig</code>
type	List of formulas specifying variable types. Accepted values are <code>c("continuous", "continuous2", "categorical", "dichotomous")</code> , e.g. <code>type = list(age ~ "continuous", female ~ "dichotomous")</code> . If type not specified for a variable, the function will default to an appropriate summary type. See below for details.
value	List of formulas specifying the value to display for dichotomous variables. <code>gt_summary</code> selectors, e.g. <code>all_dichotomous()</code> , cannot be used with this argument. See below for details.
missing	Indicates whether to include counts of NA values in the table. Allowed values are "no" (never display NA values), "ifany" (only display if any NA values), and "always" (includes NA count row for all variables). Default is "ifany".
missing_text	String to display for count of missing observations. Default is "Unknown".
sort	List of formulas specifying the type of sorting to perform for categorical data. Options are <code>frequency</code> where results are sorted in descending order of frequency and <code>alphanumeric</code> , e.g. <code>sort = list(everything() ~ "frequency")</code>
percent	Indicates the type of percentage to return. Must be one of "column", "row", or "cell". Default is "column".
include	variables to include in the summary table. Default is <code>everything()</code>

## Value

A `tbl_svsummary` object

## statistic argument

The `statistic` argument specifies the statistics presented in the table. The input is a list of formulas that specify the statistics to report. For example, `statistic = list(age ~ "{mean} ({sd})")` would report the mean and standard deviation for age; `statistic = list(all_continuous() ~ "{mean} ({sd})")` would report the mean and standard deviation for all continuous variables. A statistic name that appears between curly brackets will be replaced with the numeric statistic (see [glue::glue](#)).

For categorical variables the following statistics are available to display.

- `{n}` frequency
- `{N}` denominator, or cohort size
- `{p}` percentage

- {p.std.error} standard error of the sample proportion computed with `survey::svymean()`
- {n\_unweighted} unweighted frequency
- {N\_unweighted} unweighted denominator
- {p\_unweighted} unweighted formatted percentage

For continuous variables the following statistics are available to display.

- {median} median
- {mean} mean
- {mean.std.error} standard error of the sample mean computed with `survey::svymean()`
- {sd} standard deviation
- {var} variance
- {min} minimum
- {max} maximum
- {p##} any integer percentile, where ## is an integer from 0 to 100
- {sum} sum

Unlike `tbl_summary()`, it is not possible to pass a custom function.

For both categorical and continuous variables, statistics on the number of missing and non-missing observations and their proportions are available to display.

- {N\_obs} total number of observations
- {N\_miss} number of missing observations
- {N\_nonmiss} number of non-missing observations
- {p\_miss} percentage of observations missing
- {p\_nonmiss} percentage of observations not missing
- {N\_obs\_unweighted} unweighted total number of observations
- {N\_miss\_unweighted} unweighted number of missing observations
- {N\_nonmiss\_unweighted} unweighted number of non-missing observations
- {p\_miss\_unweighted} unweighted percentage of observations missing
- {p\_nonmiss\_unweighted} unweighted percentage of observations not missing

Note that for categorical variables, {N\_obs}, {N\_miss} and {N\_nonmiss} refer to the total number, number missing and number non missing observations in the denominator, not at each level of the categorical variable.

## Example Output

### type argument

The `tbl_summary()` function has four summary types:

- "continuous" summaries are shown on a *single row*. Most numeric variables default to summary type continuous.
- "continuous2" summaries are shown on *2 or more rows*



- "categorical" *multi-line* summaries of nominal data. Character variables, factor variables, and numeric variables with fewer than 10 unique levels default to type categorical. To change a numeric variable to continuous that defaulted to categorical, use `type = list(varname ~ "continuous")`
- "dichotomous" categorical variables that are displayed on a *single row*, rather than one row per level of the variable. Variables coded as TRUE/FALSE, 0/1, or yes/no are assumed to be dichotomous, and the TRUE, 1, and yes rows are displayed. Otherwise, the value to display must be specified in the value argument, e.g. `value = list(varname ~ "level to show")`

### select helpers

**Select helpers** from the `\tidyselect\` package and `\gtsummary\` package are available to modify default behavior for groups of variables. For example, by default continuous variables are reported with the median and IQR. To change all continuous variables to mean and standard deviation use `statistic = list(all_continuous() ~ "{mean} ({sd})")`.

All columns with class logical are displayed as dichotomous variables showing the proportion of events that are TRUE on a single row. To show both rows (i.e. a row for TRUE and a row for FALSE) use `type = list(where(is.logical) ~ "categorical")`.

The select helpers are available for use in any argument that accepts a list of formulas (e.g. `statistic`, `type`, `digits`, `value`, `sort`, etc.)

Read more on the [syntax](#) used through the package.

### Author(s)

Joseph Larmarange

### See Also

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

Other `tbl_svysummary` tools: [add\\_n.tbl\\_summary\(\)](#), [add\\_overall\(\)](#), [add\\_p.tbl\\_svysummary\(\)](#), [add\\_q\(\)](#), [add\\_stat\\_label\(\)](#), [modify](#), [separate\\_p\\_footnotes\(\)](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

### Examples

```
# A simple weighted dataset
tbl_svysummary_ex1 <-
  survey::svydesign(~1, data = as.data.frame(Titanic), weights = ~Freq) %>%
  tbl_svysummary(by = Survived, percent = "row", include = c(Class, Age))

# Example 2 -----
# A dataset with a complex design
data(api, package = "survey")
tbl_svysummary_ex2 <-
  survey::svydesign(id = ~dnum, weights = ~pw, data = apiclus1, fpc = ~fpc) %>%
  tbl_svysummary(by = "both", include = c(api00, stype))
```

---

tbl\_uvregression      *Display univariate regression model results in table*


---

### Description

This function estimates univariate regression models and returns them in a publication-ready table. It can create univariate regression models holding either a covariate or outcome constant.

For models holding outcome constant, the function takes as arguments a data frame, the type of regression model, and the outcome variable  $y$ . Each column in the data frame is regressed on the specified outcome. The `tbl_uvregression` function arguments are similar to the [tbl\\_regression](#) arguments. Review the [tbl\\_uvregression vignette](#) for detailed examples.

You may alternatively hold a single covariate constant. For this, pass a data frame, the type of regression model, and a single covariate in the  $x$  argument. Each column of the data frame will serve as the outcome in a univariate regression model. Take care using the  $x$  argument that each of the columns in the data frame are appropriate for the same type of model, e.g. they are all continuous variables appropriate for `lm`, or dichotomous variables appropriate for logistic regression with `glm`.

### Usage

```
tbl_uvregression(
  data,
  method,
  y = NULL,
  x = NULL,
  method.args = NULL,
  exponentiate = FALSE,
  label = NULL,
  include = everything(),
  tidy_fun = NULL,
  hide_n = FALSE,
  show_single_row = NULL,
  conf.level = NULL,
  estimate_fun = NULL,
  pvalue_fun = NULL,
  formula = "{y} ~ {x}",
  add_estimate_to_reference_rows = NULL,
  conf.int = NULL,
  ...
)
```

### Arguments

<code>data</code>	Data frame to be used in univariate regression modeling. Data frame includes the outcome variable(s) and the independent variables. Survey design objects are also accepted.
<code>method</code>	Regression method (e.g. <code>lm</code> , <code>glm</code> , <code>survival::coxph</code> , <code>survey::svyglm</code> , and more).
<code>y</code>	Model outcome (e.g. $y = \text{recurrence}$ or $y = \text{Surv}(\text{time}, \text{recur})$ ). All other column in data will be regressed on $y$ . Specify one and only one of $y$ or $x$

x	Model covariate (e.g. <code>x = trt</code> ). All other columns in data will serve as the outcome in a regression model with <code>x</code> as a covariate. Output table is best when <code>x</code> is a continuous or dichotomous variable displayed on a single row. Specify one and only one of <code>y</code> or <code>x</code>
method.args	List of additional arguments passed on to the regression function defined by <code>method</code> .
exponentiate	Logical indicating whether to exponentiate the coefficient estimates. Default is <code>FALSE</code> .
label	List of formulas specifying variables labels, e.g. <code>list(age ~ "Age", stage ~ "Path T Stage")</code>
include	Variables to include in output. Input may be a vector of quoted variable names, unquoted variable names, or <code>tidyselect</code> select helper functions. Default is <code>everything()</code> .
tidy_fun	Option to specify a particular tidier function for the model. Default is to use <code>broom::tidy()</code> , but if an error occurs then tidying of the model is attempted with <code>parameters::model_parameters()</code> , if installed.
hide_n	Hide N column. Default is <code>FALSE</code>
show_single_row	By default categorical variables are printed on multiple rows. If a variable is dichotomous (e.g. Yes/No) and you wish to print the regression coefficient on a single row, include the variable name(s) here—quoted and unquoted variable name accepted.
conf.level	Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
estimate_fun	Function to round and format coefficient estimates. Default is <code>style_sigfig</code> when the coefficients are not transformed, and <code>style_ratio</code> when the coefficients have been exponentiated.
pvalue_fun	Function to round and format p-values. Default is <code>style_pvalue</code> . The function must have a numeric vector input (the numeric, exact p-value), and return a string that is the rounded/formatted p-value (e.g. <code>pvalue_fun = function(x) style_pvalue(x, digits = 2)</code> or equivalently, <code>purrr::partial(style_pvalue, digits = 2)</code> ).
formula	String of the model formula. Uses <code>glue::glue</code> syntax. Default is <code>"{y} ~ {x}"</code> , where <code>{y}</code> is the dependent variable, and <code>{x}</code> represents a single covariate. For a random intercept model, the formula may be <code>formula = "{y} ~ {x} + (1   gear)"</code> .
add_estimate_to_reference_rows	add a reference value. Default is <code>FALSE</code>
conf.int	Logical indicating whether or not to include a confidence interval in the output. Defaults to <code>TRUE</code> .
...	<b>[Experimental]</b> Additional arguments passed to <code>broom.helpers::tidy_plus_plus()</code> . See <code>?tidy_plus_plus_dots</code> for details.

**Value**

A `tbl_uvregression` object

**Example Output**

## Methods

The default method for `tbl_regression()` model summary uses `broom::tidy(x)` to perform the initial tidying of the model object. There are, however, a few models that use [modifications](#).

- "parsnip/workflows": If the model was prepared using `parsnip/workflows`, the original model fit is extracted and the original `x=` argument is replaced with the model fit. This will typically go unnoticed; however, if you've provided a custom tidier in `tidy_fun=` the tidier will be applied to the model fit object and not the `parsnip/workflows` object.
- "survreg": The scale parameter is removed, `broom::tidy(x) %>% dplyr::filter(term != "Log(scale)")`
- "multinom": This multinomial outcome is complex, with one line per covariate per outcome (less the reference group)
- "gam": Uses the internal tidier `tidy_gam()` to print both parametric and smooth terms.
- "tidycrr": Uses the tidier `tidycmprsk::tidy()` to print the model terms.
- "lmerMod", "glmerMod", "glmmTMB", "glmmadmb", "stanreg", "brmsfit": These mixed effects models use `broom.mixed::tidy(x, effects = "fixed")`. Specify `tidy_fun = broom.mixed::tidy` to print the random components.

## Author(s)

Daniel D. Sjoberg

## See Also

See `tbl_regression` [vignette](#) for detailed examples

Review [list](#), [formula](#), and [selector syntax](#) used throughout `gtsummary`

Other `tbl_uvregression` tools: [add\\_global\\_p\(\)](#), [add\\_q\(\)](#), [bold\\_italicize\\_labels\\_levels](#), [inline\\_text.tbl\\_uvregression](#), [modify](#), [tbl\\_merge\(\)](#), [tbl\\_split\(\)](#), [tbl\\_stack\(\)](#), [tbl\\_strata\(\)](#)

## Examples

```
# Example 1 -----
tbl_uv_ex1 <-
tbl_uvregression(
  trial[c("response", "age", "grade")],
  method = glm,
  y = response,
  method.args = list(family = binomial),
  exponentiate = TRUE
)

# Example 2 -----
# rounding pvalues to 2 decimal places
library(survival)
tbl_uv_ex2 <-
tbl_uvregression(
  trial[c("ttdeath", "death", "age", "grade", "response")],
  method = coxph,
  y = Surv(ttdeath, death),
  exponentiate = TRUE,
  pvalue_fun = function(x) style_pvalue(x, digits = 2)
)
```

---

theme\_gtsummary      *Available gtsummary themes*

---

## Description

**[Maturing]** The following themes are available to use within the gtsummary package. Print theme elements with `theme_gtsummary_journal(set_theme = FALSE) %>% print()`. Review the [themes vignette](#) for details.

## Usage

```
theme_gtsummary_journal(
  journal = c("jama", "lancet", "nejm", "qjecon"),
  set_theme = TRUE
)

theme_gtsummary_compact(set_theme = TRUE, font_size = NULL)

theme_gtsummary_printer(
  print_engine = c("gt", "kable", "kable_extra", "flextable", "huxtable", "tibble"),
  set_theme = TRUE
)

theme_gtsummary_language(
  language = c("de", "en", "es", "fr", "gu", "hi", "is", "ja", "kr", "mr", "nl", "no",
    "pt", "se", "zh-cn", "zh-tw"),
  decimal.mark = NULL,
  big.mark = NULL,
  iqr.sep = NULL,
  ci.sep = NULL,
  set_theme = TRUE
)

theme_gtsummary_continuous2(
  statistic = "{median} ({p25, {p75}})",
  set_theme = TRUE
)

theme_gtsummary_mean_sd(set_theme = TRUE)

theme_gtsummary_eda(set_theme = TRUE)
```

## Arguments

journal	String indicating the journal theme to follow. One of <code>c("jama", "lancet", "nejm", "qjecon")</code> . Details below.
set_theme	Logical indicating whether to set the theme. Default is TRUE. When FALSE the named list of theme elements is returned invisibly
font_size	Numeric font size for compact theme. Default is 13 for gt tables, and 8 for all other output types

<code>print_engine</code>	String indicating the print method. Must be one of "gt", "kable", "kable_extra", "flextable", "tibble"
<code>language</code>	String indicating language. Must be one of "de" (German), "en" (English), "es" (Spanish), "fr" (French), "gu" (Gujarati), "hi" (Hindi), "is" (Icelandic), "ja" (Japanese), "kr" (Korean), "nl" (Dutch), "mr" (Marathi), "no" (Norwegian), "pt" (Portuguese), "se" (Swedish), "zh-c,n" (Chinese Simplified), "zh-tw" (Chinese Traditional) If a language is missing a translation for a word or phrase, please feel free to reach out on <a href="#">GitHub</a> with the translated text!
<code>decimal.mark</code>	The character to be used to indicate the numeric decimal point. Default is "." or <code>getOption("OutDec")</code>
<code>big.mark</code>	Character used between every 3 digits to separate hundreds/thousands/millions/etc. Default is ",", except when <code>decimal.mark = "</code> , when the default is a space.
<code>iqr.sep</code>	string indicating separator for the default IQR in <code>tbl_summary()</code> . If <code>decimal.mark=</code> is NULL, <code>iqr.sep=</code> is ", ". The comma separator, however, can look odd when <code>decimal.mark = "</code> , ". In this case the argument will default to an en dash
<code>ci.sep</code>	string indicating separator for confidence intervals. If <code>decimal.mark=</code> is NULL, <code>ci.sep=</code> is ", ". The comma separator, however, can look odd when <code>decimal.mark = "</code> , ". In this case the argument will default to an en dash
<code>statistic</code>	Default statistic continuous variables

## Themes

- `theme_gtsummary_journal(journal=)`
  - "jama" *The Journal of the American Medical Association*
    - \* Round large p-values to 2 decimal places; separate confidence intervals with "ll to ul".
    - \* `tbl_summary()` Doesn't show percent symbol; use em-dash to separate IQR; run `add_stat_label()`
    - \* `tbl_regression()/tbl_uvregression()` show coefficient and CI in same column
  - "lancet" *The Lancet*
    - \* Use mid-point as decimal separator; round large p-values to 2 decimal places; separate confidence intervals with "ll to ul".
    - \* `tbl_summary()` Doesn't show percent symbol; use em-dash to separate IQR
  - "nejm" *The New England Journal of Medicine*
    - \* Round large p-values to 2 decimal places; separate confidence intervals with "ll to ul".
    - \* `tbl_summary()` Doesn't show percent symbol; use em-dash to separate IQR
  - "qjecon" *The Quarterly Journal of Economics*
    - \* `tbl_summary()` all percentages rounded to one decimal place
    - \* `tbl_regression()/tbl_uvregression()` add significance stars with `add_significance_stars()`; hides CI and p-value from output
- `theme_gtsummary_compact()`
  - tables printed with `gt`, `flextable`, `kableExtra`, or `huxtable` will be compact with smaller font size and reduced cell padding
- `theme_gtsummary_printer(print_engine=)`
  - Use this theme to permanently change the default printer.

- `theme_gtsummary_continuous2()`
  - Set all continuous variables to summary type "continuous2" by default
- `theme_gtsummary_mean_sd()`
  - Set default summary statistics to mean and standard deviation in `tbl_summary()`
  - Set default continuous tests in `add_p()` to t-test and ANOVA
- `theme_gtsummary_eda()`
  - Set all continuous variables to summary type "continuous2" by default
  - In `tbl_summary()` show the median, mean, IQR, SD, and Range by default

Use `reset_gtsummary_theme()` to restore the default settings

Review the [themes vignette](#) to create your own themes.

## Example Output

## See Also

[Themes vignette](#)

[set\\_gtsummary\\_theme\(\)](#), [reset\\_gtsummary\\_theme\(\)](#)

## Examples

```
# Setting JAMA theme for gtsummary
theme_gtsummary_journal("jama")
# Themes can be combined by including more than one
theme_gtsummary_compact()

set_gtsummary_theme_ex1 <-
  trial %>%
  select(age, grade, trt) %>%
  tbl_summary(by = trt) %>%
  as_gt()

# reset gtsummary themes
reset_gtsummary_theme()
```

---

trial

*Results from a simulated study of two chemotherapy agents*

---

## Description

A dataset containing the baseline characteristics of 200 patients who received Drug A or Drug B. Dataset also contains the outcome of tumor response to the treatment.

## Usage

```
trial
```

**Format**

A data frame with 200 rows—one row per patient

**trt** Chemotherapy Treatment

**age** Age

**marker** Marker Level (ng/mL)

**stage** T Stage

**grade** Grade

**response** Tumor Response

**death** Patient Died

**ttdeath** Months to Death/Censor



# Index

- \* **Advanced modifiers**
  - modify\_column\_alignment, 63
  - modify\_column\_hide, 63
  - modify\_column\_indent, 64
  - modify\_column\_merge, 65
  - modify\_fmt\_fun, 67
  - modify\_table\_body, 68
  - modify\_table\_styling, 69
- \* **datasets**
  - trial, 119
- \* **gtsummary output types**
  - as\_flex\_table, 36
  - as\_gt, 38
  - as\_hux\_table, 39
  - as\_kable, 40
  - as\_kable\_extra, 41
  - as\_tibble.gtsummary, 43
- \* **style tools**
  - style\_number, 81
  - style\_percent, 82
  - style\_pvalue, 83
  - style\_ratio, 84
  - style\_sigfig, 85
- \* **tbl\_continuous tools**
  - add\_overall, 18
  - add\_p.tbl\_continuous, 20
  - tbl\_continuous, 87
- \* **tbl\_cross tools**
  - add\_p.tbl\_cross, 21
  - inline\_text.tbl\_cross, 52
  - tbl\_cross, 88
- \* **tbl\_custom\_summary tools**
  - add\_overall, 18
  - continuous\_summary, 48
  - proportion\_summary, 72
  - ratio\_summary, 74
  - tbl\_custom\_summary, 90
- \* **tbl\_regression tools**
  - add\_global\_p, 11
  - add\_q, 28
  - bold\_italicize\_labels\_levels, 44
  - combine\_terms, 47
  - inline\_text.tbl\_regression, 53
  - modify, 60
  - tbl\_merge, 94
  - tbl\_regression, 96
  - tbl\_split, 98
  - tbl\_stack, 99
  - tbl\_strata, 101
- \* **tbl\_summary tbl\_svsummary tools**
  - add\_ci, 4
- \* **tbl\_summary tools**
  - add\_n.tbl\_summary, 12
  - add\_overall, 18
  - add\_p.tbl\_summary, 22
  - add\_q, 28
  - add\_stat\_label, 34
  - bold\_italicize\_labels\_levels, 44
  - inline\_text.tbl\_summary, 55
  - inline\_text.tbl\_survfit, 56
  - modify, 60
  - separate\_p\_footnotes, 77
  - tbl\_custom\_summary, 90
  - tbl\_merge, 94
  - tbl\_split, 98
  - tbl\_stack, 99
  - tbl\_strata, 101
  - tbl\_summary, 104
- \* **tbl\_survfit tools**
  - add\_n.tbl\_survfit, 14
  - add\_nevent.tbl\_survfit, 15
  - add\_p.tbl\_survfit, 24
  - modify, 60
  - tbl\_merge, 94
  - tbl\_split, 98
  - tbl\_stack, 99
  - tbl\_strata, 101
  - tbl\_survfit, 108
- \* **tbl\_svsummary tools**
  - add\_n.tbl\_summary, 12
  - add\_overall, 18
  - add\_p.tbl\_svsummary, 26
  - add\_q, 28
  - add\_stat\_label, 34
  - modify, 60
  - separate\_p\_footnotes, 77

- tbl\_merge, 94
- tbl\_split, 98
- tbl\_stack, 99
- tbl\_strata, 101
- tbl\_svysummary, 110
- \* **tbl\_uvregression tools**
  - add\_global\_p, 11
  - add\_q, 28
  - bold\_italicize\_labels\_levels, 44
  - inline\_text.tbl\_uvregression, 58
  - modify, 60
  - tbl\_merge, 94
  - tbl\_split, 98
  - tbl\_stack, 99
  - tbl\_strata, 101
  - tbl\_uvregression, 114
- add\_ci, 4
- add\_difference, 6
- add\_glance, 8
- add\_glance\_source\_note (add\_glance), 8
- add\_glance\_table (add\_glance), 8
- add\_global\_p, 11, 29, 45, 47, 54, 59, 62, 95, 98–100, 103, 116
- add\_n.tbl\_regression
  - (add\_n\_regression), 17
- add\_n.tbl\_summary, 12, 19, 24, 27, 29, 35, 45, 56, 57, 62, 78, 92, 95, 99, 100, 103, 107, 113
- add\_n.tbl\_survfit, 14, 15, 25, 62, 95, 99, 100, 103, 109
- add\_n.tbl\_svysummary
  - (add\_n.tbl\_summary), 12
- add\_n.tbl\_uvregression
  - (add\_n\_regression), 17
- add\_n\_regression, 17
- add\_nevent.tbl\_regression
  - (add\_nevent\_regression), 16
- add\_nevent.tbl\_survfit, 15, 15, 25, 62, 95, 99, 100, 103, 109
- add\_nevent.tbl\_uvregression
  - (add\_nevent\_regression), 16
- add\_nevent\_regression, 16
- add\_overall, 14, 18, 21, 24, 27, 29, 35, 45, 48, 56, 57, 62, 73, 74, 78, 87, 92, 95, 99, 100, 103, 107, 113
- add\_overall(), 91, 92
- add\_p(), 92
- add\_p.tbl\_continuous, 19, 20, 87
- add\_p.tbl\_cross, 21, 53, 89
- add\_p.tbl\_summary, 14, 19, 22, 29, 35, 45, 56, 57, 62, 78, 92, 95, 99, 100, 103, 107
- add\_p.tbl\_survfit, 15, 24, 62, 95, 99, 100, 103, 109
- add\_p.tbl\_svysummary, 14, 19, 26, 29, 35, 62, 78, 95, 99, 100, 103, 113
- add\_q, 12, 14, 19, 24, 27, 28, 35, 45, 47, 54, 56, 57, 59, 62, 78, 92, 95, 98–100, 103, 107, 113, 116
- add\_significance\_stars, 29
- add\_stat, 31
- add\_stat\_label, 14, 19, 24, 27, 29, 34, 45, 56, 57, 62, 78, 92, 95, 99, 100, 103, 107, 113
- add\_vif, 35
- all\_categorical (select\_helpers), 76
- all\_continuous (select\_helpers), 76
- all\_continuous2 (select\_helpers), 76
- all\_contrasts (select\_helpers), 76
- all\_dichotomous (select\_helpers), 76
- all\_interaction (select\_helpers), 76
- all\_intercepts (select\_helpers), 76
- all\_stat\_cols (select\_helpers), 76
- all\_tests (select\_helpers), 76
- as\_flex\_table, 36, 38–40, 42, 44
- as\_gt, 37, 38, 39, 40, 42, 44
- as\_hux\_table, 37, 38, 39, 40, 42, 44
- as\_hux\_xlsx (as\_hux\_table), 39
- as\_kable, 37–39, 40, 42, 44
- as\_kable\_extra, 37–40, 41, 44
- as\_tibble.gtsummary, 37–40, 42, 43
- bold\_italicize\_labels\_levels, 12, 14, 19, 24, 29, 35, 44, 47, 54, 56, 57, 59, 62, 78, 92, 95, 98–100, 103, 107, 116
- bold\_labels
  - (bold\_italicize\_labels\_levels), 44
- bold\_labels(), 40, 92
- bold\_levels
  - (bold\_italicize\_labels\_levels), 44
- bold\_p, 46
- broom.helpers::tidy\_plus\_plus(), 96, 115
- check\_gtsummary\_theme
  - (set\_gtsummary\_theme), 78
- combine\_terms, 12, 29, 45, 47, 54, 62, 95, 98–100, 103
- continuous\_summary, 19, 48, 73, 74, 92
- continuous\_summary(), 90
- custom\_tidiers, 49
- dplyr::tibble(), 91

- filter\_p(sort\_filter\_p), 80
- get\_gtsummary\_theme
  - (set\_gtsummary\_theme), 78
- glm, 114
- glue::glue, 13, 52, 54, 56, 58, 106, 111, 115
- glue::glue(), 61, 90, 92
- gt::gt, 38
- gt::html(), 9, 61
- gt::md(), 9, 61
- gtsummary themes, 79
- inline\_text.gtsummary, 52
- inline\_text.tbl\_cross, 22, 52, 89
- inline\_text.tbl\_regression, 12, 29, 45, 47, 53, 62, 95, 98–100, 103
- inline\_text.tbl\_summary, 14, 19, 24, 29, 35, 45, 55, 57, 62, 78, 92, 95, 99, 100, 103, 107
- inline\_text.tbl\_survfit, 14, 19, 24, 29, 35, 45, 56, 56, 62, 78, 92, 95, 99, 100, 103, 107
- inline\_text.tbl\_svsummary
  - (inline\_text.tbl\_summary), 55
- inline\_text.tbl\_uvregression, 12, 29, 45, 58, 62, 95, 99, 100, 103, 116
- italicize\_labels
  - (bold\_italicize\_labels\_levels), 44
- italicize\_levels
  - (bold\_italicize\_labels\_levels), 44
- italicize\_levels(), 40
- knitr::kable, 40
- list, formula, and selector syntax, 6, 8, 10, 12, 14, 15, 24, 32, 35, 36, 47, 63, 64, 67, 71, 75, 77, 78, 87, 89, 92, 98, 107, 109, 113, 116
- lm, 114
- modifications, 97, 116
- modify, 12, 14, 15, 19, 24, 25, 27, 29, 35, 45, 47, 54, 56, 57, 59, 60, 78, 92, 95, 98–100, 103, 107, 109, 113, 116
- modify\_caption(modify), 60
- modify\_column\_alignment, 63, 64–68, 71
- modify\_column\_hide, 63, 63, 65–68, 71
- modify\_column\_indent, 63, 64, 64, 66–68, 71
- modify\_column\_merge, 63–65, 65, 67, 68, 71
- modify\_column\_unhide
  - (modify\_column\_hide), 63
- modify\_fmt\_fun, 63–66, 67, 68, 71
- modify\_footnote(modify), 60
- modify\_footnote(), 92
- modify\_header(modify), 60
- modify\_spanning\_header(modify), 60
- modify\_table\_body, 63–67, 68, 71
- modify\_table\_styling, 63–68, 69
- plot, 71
- pool\_and\_tidy\_mice(custom\_tidiers), 49
- print.tbl\_split(tbl\_split), 98
- proportion\_summary, 19, 48, 72, 74, 92
- proportion\_summary(), 90
- ratio\_summary, 19, 48, 73, 74, 92
- ratio\_summary(), 90
- remove\_row\_type, 75
- reset\_gtsummary\_theme
  - (set\_gtsummary\_theme), 78
- reset\_gtsummary\_theme(), 119
- select\_helpers, 76
- separate\_p\_footnotes, 14, 19, 24, 27, 29, 35, 45, 56, 57, 62, 77, 92, 95, 99, 100, 103, 107, 113
- set\_gtsummary\_theme, 78
- set\_gtsummary\_theme(), 119
- show\_header\_names(modify), 60
- sort\_filter\_p, 80
- sort\_p(sort\_filter\_p), 80
- stats::anova, 47
- stats::anova(), 47
- stats::p.adjust, 28
- stats::poisson.test(), 74
- stats::prop.test(), 73
- stats::update, 47
- style\_number, 81, 82–84, 86
- style\_percent, 81, 82, 83, 84, 86
- style\_percent(), 109
- style\_pvalue, 7, 21–23, 25, 27, 28, 53, 56, 57, 81, 82, 83, 84, 86, 97, 115
- style\_ratio, 81–83, 84, 86, 97, 115
- style\_sigfig, 81–84, 85, 97, 109, 115
- style\_sigfig(), 7, 36
- survey::svymean(), 112
- survival::coxph, 114
- syntax, 105, 113
- tbl\_butcher, 86
- tbl\_continuous, 19, 21, 87
- tbl\_cross, 22, 53, 88
- tbl\_custom\_summary, 14, 19, 24, 29, 35, 45, 48, 56, 57, 62, 73, 74, 78, 90, 95, 99, 100, 103, 107

tbl\_custom\_summary(), 48, 72, 74  
 tbl\_merge, 12, 14, 15, 19, 24, 25, 27, 29, 35,  
     45, 47, 54, 56, 57, 59, 62, 78, 92, 94,  
     98–100, 103, 107, 109, 113, 116  
 tbl\_regression, 12, 29, 37–41, 43, 45, 47,  
     54, 62, 95, 96, 99, 100, 103, 114  
 tbl\_split, 12, 14, 15, 19, 24, 25, 27, 29, 35,  
     45, 47, 54, 56, 57, 59, 62, 78, 92, 95,  
     98, 99, 100, 103, 107, 109, 113, 116  
 tbl\_stack, 12, 14, 15, 19, 24, 25, 27, 29, 35,  
     45, 47, 54, 56, 57, 59, 62, 78, 92, 95,  
     98, 99, 99, 103, 107, 109, 113, 116  
 tbl\_strata, 12, 14, 15, 19, 24, 25, 27, 29, 35,  
     45, 47, 54, 56, 57, 59, 62, 78, 92, 95,  
     98–100, 101, 107, 109, 113, 116  
 tbl\_strata2(tbl\_strata), 101  
 tbl\_summary, 13, 14, 19, 20, 23, 24, 29, 34,  
     35, 37–41, 43, 45, 55–57, 62, 78, 92,  
     95, 99, 100, 103, 104  
 tbl\_summary(), 48, 90, 91, 110, 112  
 tbl\_survfit, 15, 25, 57, 62, 95, 99, 100, 103,  
     108  
 tbl\_survfit.data.frame(), 108  
 tbl\_survfit.list(), 108  
 tbl\_survfit.survfit(), 108  
 tbl\_svsummary, 13, 14, 19, 26, 27, 29, 34,  
     35, 62, 78, 95, 99, 100, 103, 110  
 tbl\_uvregression, 12, 29, 45, 58, 59, 62, 95,  
     99, 100, 103, 114  
 tests, 7, 20, 21, 23  
 theme\_gtsummary, 117  
 theme\_gtsummary\_compact  
     (theme\_gtsummary), 117  
 theme\_gtsummary\_continuous2  
     (theme\_gtsummary), 117  
 theme\_gtsummary\_eda(theme\_gtsummary),  
     117  
 theme\_gtsummary\_journal  
     (theme\_gtsummary), 117  
 theme\_gtsummary\_language  
     (theme\_gtsummary), 117  
 theme\_gtsummary\_mean\_sd  
     (theme\_gtsummary), 117  
 theme\_gtsummary\_printer  
     (theme\_gtsummary), 117  
 tibble, 44  
 tidy\_bootstrap(custom\_tidiers), 49  
 tidy\_gam(custom\_tidiers), 49  
 tidy\_robust(custom\_tidiers), 49  
 tidy\_standardize(custom\_tidiers), 49  
 tidy\_wald\_test(custom\_tidiers), 49  
 trial, 119  
 with\_gtsummary\_theme  
     (set\_gtsummary\_theme), 78