

Package ‘hubeau’

October 13, 2022

Type Package

Title Get Data from the French National Database on Water 'Hub'Eau'

Version 0.3.1

Date 2022-08-12

Description Collection of functions to help retrieving data from 'Hub'Eau' the free and public French National APIs on water <<https://hubeau.eaufrance.fr/>>.

License MIT + file LICENSE

URL <https://inrae.github.io/hubeau/>,
<https://github.com/inrae/hubeau#readme>

BugReports <https://github.com/inrae/hubeau/issues>

Depends R (>= 2.10)

Imports httr, purrr, tibble, urltools

Suggests dplyr, spelling, testthat (>= 3.0.0)

Config/testthat.edition 3

Encoding UTF-8

RoxygenNote 7.2.0

Language en-US

NeedsCompilation no

Author David Dorchies [aut, cre] (<<https://orcid.org/0000-0002-6595-7984>>),
Pascal Irz [ctb]

Maintainer David Dorchies <david.dorchies@inrae.fr>

Repository CRAN

Date/Publication 2022-08-16 09:20:08 UTC

R topics documented:

convert_list_to_tibble	2
doApiQuery	3
get_ecoulement_stations	4
get_hydrometrie_obs_elab	5
get_indicateurs_services_communes	7
get_niveaux_nappes_stations	9
get_poisson_observations	10
get_prelevements_points_prelevement	11
hubeau	12
list_apis	13

Index

15

convert_list_to_tibble

Convert list provided by the APIs into a tibble

Description

Convert list provided by the APIs into a tibble

Usage

```
convert_list_to_tibble(l)
```

Arguments

l a [list](#) provided by the API (See [doApiQuery](#))

Details

This function is used internally by all the retrieving data functions for converting data after the call to [doApiQuery](#).

Value

A [tibble::tibble](#) with one row by record and one column by field.

Examples

```
# To get the available APIs in the package
list_apis()

# To get the available endpoints in an API
list_endpoints("prelevements")

# To get available parameters in endpoint "chroniques" of the API "prelevements"
```

```
list_params(api = "prelevements", endpoint = "chroniques")

# To query the endpoint "chroniques" of the API "prelevements"
# on all devices in the commune of Romilly-sur-Seine in 2018
if(interactive()) {
  resp <- doApiQuery(api = "prelevements",
                      endpoint = "chroniques",
                      params = list(code_commune_insee = "10323", annee = "2018"))
  convert_list_to_tibble(resp)
}
```

doApiQuery

Main internal functions for querying the Hub'Eau API endpoints

Description

The function `doQueryApi` is called by all the function querying the API endpoints and return the raw data sent by the endpoint.

Usage

```
doApiQuery(api, endpoint, params)
```

Arguments

<code>api</code>	a <code>character</code> name of the API (e.g.: "indicateurs_services", "prelevements"...), see example for available APIs
<code>endpoint</code>	a <code>character</code> name of the endpoint, see example for available endpoints in an API
<code>params</code>	a <code>list</code> the list of parameters of the queries and their values in the format <code>list(ParamName = "Param value", ...)</code> , use the function <code>list_params</code> for a list of the available filter parameters for a given API endpoint and see the API documentation for their description

Details

Pagination of the queries is handled automatically and the returned `list` is the concatenation of all the results sent by the API.

The functions `get_[api]_[endpoint]` call the function `doQueryApi` and parse the response in a `tibble::tibble` format for the user (See `convert_list_to_tibble`).

By default the user agent used for the query is "<https://github.com/inrae/hubeau>". You can redefine the user agent with the global option "hubeau.user_agent": `options(hubeau.user_agent = "My user agent")`.

Value

A `list` with the concatenated results returned by the API.

Examples

```
# To get the available APIs in the package
list_apis()

# To get the available endpoints in an API
list_endpoints("prelevements")

# To get available parameters in endpoint "chroniques" of the API "prelevements"
list_params(api = "prelevements", endpoint = "chroniques")

# To query the endpoint "chroniques" of the API "prelevements"
# on all devices in the commune of Romilly-sur-Seine in 2018
if(interactive()) {
  resp <- doApiQuery(api = "prelevements",
                      endpoint = "chroniques",
                      params = list(code_commune_insee = "10323", annee = "2018"))
  convert_list_to_tibble(resp)
}
```

get_ecoulement_stations

Retrieve data from API "Ecoulement des cours d'eau"

Description

The data originate from the "ONDE" river low waters monitoring network. Available endpoints are:

- `get_ecoulement_stations` retrieves site data and locations
- `get_ecoulement_observations` retrieves flow information
- `get_ecoulement_campagnes` retrieves annual surveys

See the API documentation for available filter parameters: <https://hubeau.eaufrance.fr/page/api-ecoulement>

Usage

```
get_ecoulement_stations(params)

get_ecoulement_observations(params)

get_ecoulement_campagnes(params)
```

Arguments

<code>params</code>	a list the list of parameters of the queries and their values in the format <code>list(ParamName = "Param value", ...)</code> , use the function list_params for a list of the available filter parameters for a given API endpoint and see the API documentation for their description
---------------------	---

Value

A `tibble::tibble` with one row by record and one column by field.

Examples

```
if(interactive()) {
  # Retrieve 2022 observation campaigns in the Jura French department
  get_ecoulement_campaignes(
    list(code_departement = "39",
         date_campagne_min = "2022-01-01",
         date_campagne_max = "2022-12-31")
  )

  # Retrieve river stations
  stations_39 <- get_ecoulement_stations(
    list(code_departement = "39",
         fields = "code_station,libelle_cours_eau,libelle_commune")
  )
  stations_39

  # Get the query parameters for the requested API/endpoint
  list_params(api = "ecoulement",
              endpoint = "observations")

  # Retrieve the river flow data in the Jura departement in 2022 with
  # a selection of the fields
  onde_39 <- get_ecoulement_observations(
    list(code_departement = "39",
         date_observation_min = "2022-01-01",
         date_observation_max = "2022-12-31",
         fields = "code_station,libelle_station,date_observation,libelle_ecoulement")
  )
  onde_39
}
```

get_hydrometrie_obs_elab

Retrieve data from API "Hydrométrie"

Description

Available endpoints are:

- `get_hydrometrie_obs_elab` retrieves hydrometric elaborate observations (daily/monthly mean flow)
- `get_hydrometrie_observations_tr` retrieves hydrometric "real time" observations ()
- `get_hydrometrie_sites` retrieves hydrometric sites
- `get_hydrometrie_stations` retrieves hydrometric stations

See the API documentation of each endpoint for available filter parameters: <https://hubeau.eaufrance.fr/page/api-hydrometrie>

Usage

```
get_hydrometrie_obs_elab(params)

get_hydrometrie_observations_tr(params, entities = "station")

get_hydrometrie_sites(params, unique_site = TRUE)

get_hydrometrie_stations(params, code_sandre_reseau_station = FALSE)
```

Arguments

params	a list the list of parameters of the queries and their values in the format <code>list(ParamName = "Param value", ...)</code> , use the function list_params for a list of the available filter parameters for a given API endpoint and see the API documentation for their description
entities	1-length character string filtering the rows of the returned value, possible values are: "station" for filtering on station rows, "site" for filtering on site rows, "both" for keeping all the rows
unique_site	optional logical , if set to FALSE sites with several different locations produce one row by different location otherwise the first location found is used for fields <code>code_commune_site</code> , <code>libelle_commune</code> , <code>code_departement</code> , <code>code_region</code> , <code>libelle_region</code> , <code>libelle_departement</code>
code_sandre_reseau_station	optional logical indicating if <code>code_sandre_reseau_station</code> field is included in the result; if so, one line is added by item and other fields are repeated

Value

A [tibble::tibble](#) with one row by record and one column by field.

Examples

```
if(interactive()) {
  # Retrieve the hydrometric sites in the department of Aube
  get_hydrometrie_sites(list(code_departement = "10"))

  # The same operation returning 2 rows for the site 'H0203020' which has 2 different locations
  get_hydrometrie_sites(list(code_departement = "10"), unique_site = FALSE)

  # Retrieve the hydrometric stations in the department of Aube
  get_hydrometrie_stations(list(code_departement = "10"))

  # Which parameters are available for endpoint "obs_elab" of API "hydrometrie"?
  list_params("hydrometrie", "obs_elab")

  # Retrieve the hydrometric monthly mean flow at site 'H0203020'
```

```
get_hydrometrie_obs_elab(list(code_entite = "H0203020", grandeur_hydro_elab = "QmM"))

# Retrieve the hydrometric daily mean flow at site 'H0203020' of the last 30 days
get_hydrometrie_obs_elab(
  list(code_entite = "H0203020",
       date_debut_obs_elab = format(Sys.Date() -30, "%Y-%m-%d"),
       grandeur_hydro_elab = "QmJ"))
}
```

get_indicateurs_services_comunes*Retrieve data from API "Indicateurs des services"***Description**

Retrieve performance indicators collected in drinking water and sanitation services in France.

See [list_params](#) and the API documentation for available filter parameters: <https://hubeau.eaufrance.fr/page/api-indicateurs-services>

Usage

```
get_indicateurs_services_comunes(params)

get_indicateurs_services_indicateurs(params)

get_indicateurs_services_services(params)
```

Arguments

params	a list the list of parameters of the queries and their values in the format <code>list(ParamName = "Param value", ...)</code> , use the function list_params for a list of the available filter parameters for a given API endpoint and see the API documentation for their description
--------	---

Value

`get_indicateurs_services_comunes` returns a [tibble::tibble](#) with one row by commune, by service and by year and the following columns:

- "code_commune_insee": [character](#) identifier of the commune
- "nom_commune": [character](#) name of the commune
- "codes_service": [integer](#) identifier of the drinking water supply and/or sanitation service
- "annee": [integer](#) year of the data
- The following columns are the performance indicators flagged by their respective codes. The documentation of these codes can be found at this URL: <https://www.services.eaufrance.fr/indicateurs/indicateurs>.

`get_indicateurs_services_indicateurs` returns a `tibble::tibble` with one row by service and by year and the following columns:

- "code_service": `character` identifier of the service
- "nom_service": `character` name of the service
- "numero_siren": `character` SIREN identifier of the service
- "type_collectivite": `character` kind of community
- "mode_gestion": `character` management mechanism of the service
- "annee": `integer` year of the data
- "indicateur": value of the indicator
- "uri_indicateur": the link to the indicator documentation

`get_indicateurs_services_services` returns a `tibble::tibble` with one row by commune, by service and by year and the following columns:

- "code_service": `character` identifier of the service
- "nom_service": `character` name of the service
- "code_commune_insee": `character` identifier of the commune
- "nom_commune": `character` name of the commune
- "numero_siren": `character` SIREN identifier of the service
- "type_collectivite": `character` kind of community
- "mode_gestion": `character` management mechanism of the service
- "annee": `integer` year of the data
- The following columns are the performance indicators flagged by their respective codes. The documentation of these codes can be found at this URL: <https://www.services.eaufrance.fr/indicateurs/indicateurs>.

Examples

```
if(interactive()) {
  # Retrieve performance indicator time series in the commune of Romilly-sur-Seine
  get_indicateurs_services_comunes(list(code_commune = "10323"))

  # Retrieve the drinking water withdrawal indicators of the year 2012 for all services
  get_indicateurs_services_indicateurs(list(code_indicateur = "D102.0", annee = "2012"))

  # Retrieve performance indicator time series of Romilly-sur-Seine with service details
  get_indicateurs_services_services(list(code_commune = "10323"))
}
```

get_niveaux_nappes_stations
Retrieve data from API "Piézométrie"

Description

The available endpoints are:

- `get_niveaux_nappes_stations` retrieves list of piezometric stations
- `get_nappes_chroniques` retrieves piezometric archived time series
- `get_nappes_chroniques_tr` retrieves piezometric "real time" data

See the API documentation for available filter parameters: <https://hubeau.eaufrance.fr/page/api-piezometrie>

Usage

```
get_niveaux_nappes_stations(params)

get_niveaux_nappes_chroniques(params)

get_niveaux_nappes_chroniques_tr(params)
```

Arguments

<code>params</code>	a list the list of parameters of the queries and their values in the format <code>list(ParamName = "Param value", ...)</code> , use the function list_params for a list of the available filter parameters for a given API endpoint and see the API documentation for their description
---------------------	---

Value

A [tibble::tibble](#) with one row by record and one column by field.

Examples

```
if(interactive()) {
  # Retrieve the hydrometric stations in the department of Aube
  get_niveaux_nappes_stations(list(code_departement = "10"))

  # Retrieve the archived observed piezometric level at station '07548X0009/F' (old BSS identifier)
  # for the year 2020
  df <- get_niveaux_nappes_chroniques(list(code_bss = "07548X0009/F",
                                            date_debut_mesure = "2020-01-01",
                                            date_fin_mesure = "2020-12-31"))

  # Plot the water elevation (NGF)
  plot(as.POSIXct(df$date_mesure), df$niveau_nappe_eau, type = "l")
```

```
# For retrieving the last real time observed piezometric level
# at station 'BSS001VZGZ' (new BSS identifier)
df <- get_niveaux_nappes_chroniques_tr(list(bss_id = "BSS001VZGZ"))

# Plot the water elevation (NGF)
plot(as.POSIXct(df$date_mesure), df$niveau_eau_ngf, type = "l")
}
```

get_poisson_observations*Retrieve data from API "Poisson"***Description**

Available endpoint:

- `get_poisson_observations` retrieves data of scientific fishery operations

See the API documentation for available filter parameters: <https://hubeau.eaufrance.fr/page/api-poisson>

Usage

```
get_poisson_observations(params)
```

Arguments

<code>params</code>	a list the list of parameters of the queries and their values in the format <code>list(ParamName = "Param value", ...)</code> , use the function list_params for a list of the available filter parameters for a given API endpoint and see the API documentation for their description
---------------------	---

Value

A [tibble::tibble](#) with one row by record and one column by field.

Examples

```
if(interactive()) {
  # Get the query parameters for the requested API/endpoint
  list_params(api = "poisson",
              endpoint = "observations")

  # Retrieve selected fields on a river fish sampled in Brest
  library(dplyr)
  fields <- paste("code_operation",
                  "date_operation",
                  "libelle_point_prelevement_aspe",
                  "effectif_lot",
```

```

    "code_alternatif_taxon",
    sep = ",")
brest_fishes <- get_poisson_observations(
  list(
    libelle_commune = "Brest",
    fields = fields
  )
) %>%
  group_by_at(vars(-effectif_lot)) %>%
  summarise(nb_individuals = sum(effectif_lot))

brest_fishes
}

```

get_prelevements_points_prelement*Retrieve data from API "Prélèvements en eau"***Description**

Available endpoints are:

- `get_prelevements_points_prelement` retrieves withdrawal points
- `get_prelevements_ouvrages` retrieves withdrawal devices
- `get_prelevements_chroniques` retrieves time series of withdrawals

See the API documentation for available filter parameters: <https://hubeau.eaufrance.fr/page/api-prelevements-eau>

Usage

```

get_prelevements_points_prelement(params)

get_prelevements_ouvrages(params)

get_prelevements_chroniques(params)

```

Arguments

`params` a [list](#) the list of parameters of the queries and their values in the format `list(ParamName = "Param value", ...)`, use the function [list_params](#) for a list of the available filter parameters for a given API endpoint and see the API documentation for their description

Value

A [tibble::tibble](#) with one row by record and one column by field.

Examples

```
if(interactive()) {
  # Retrieve the withdrawal points located in Romilly-sur-Seine
  get_prelevements_points_prelevement(list(code_commune_insee = "10323"))

  # Retrieve the withdrawal devices located in Romilly-sur-Seine
  get_prelevements_ouvrages(list(code_commune_insee = "10323"))

  # Retrieve the withdrawal time series of the devices located in Romilly-sur-Seine
  get_prelevements_chroniques(list(code_commune_insee = "10323"))
}
```

hubeau

hubeau: A package for retrieving data on the French databases on water 'Hub'Eau'

Description

The 'hubeau' package provides functions for 'Hub'Eau' APIs and their related endpoints. These functions are named as follow: hubeau::get_[API]_[endpoint].

Currently available APIs and related endpoints are listed below.

API "Ecoulement des cours d'eau":

API documentation: <https://hubeau.eaufrance.fr/page/api-ecoulement>

Available functions:

- `get_ecoulement_stations()`: site data and locations
- `get_ecoulement_observations()`: flow observations collected during campaigns
- `get_ecoulement_campagnes()`: observation campaign information

API "Hydrométrie":

API documentation: <https://hubeau.eaufrance.fr/page/api-hydrometrie>

Available functions:

- `get_hydrometrie_sites()`: hydrometry sites (can contain several stations)
- `get_hydrometrie_stations()`: hydrometry stations
- `get_hydrometrie_observations_tr()`: hydrometry water level and discharge time series
- `get_hydrometrie_obs_elab()`: hydrometric elaborate observations (daily/monthly mean flow)

API "Indicateurs des services":

API documentation: <https://hubeau.eaufrance.fr/page/api-indicateurs-services>

Available functions:

- `get_indicateurs_services_comunes()`: performance indicators by commune
- `get_indicateurs_services_indicateurs()`: performance indicators by indicator
- `get_indicateurs_services_services()`: performance indicators by commune for each service

API "Piézométrie":API documentation: <https://hubeau.eaufrance.fr/page/api-piezometrie>

Available functions:

- `get_niveaux_nappes_chroniques()`: archived time series of piezometric stations
- `get_niveaux_nappes_chroniques_tr()`: real-time time series of piezometric stations
- `get_niveaux_nappes_stations()`: piezometric stations

API "Poisson":API documentation: <https://hubeau.eaufrance.fr/page/api-poisson>

Available function:

- `get_poisson_observations()`: scientific fishery observations

API "Prélèvements en eau":API documentation: <https://hubeau.eaufrance.fr/page/api-prelevements-eau>

Available functions:

- `get_prelevements_chroniques()`: time series of annual withdrawn volumes by device
- `get_prelevements_ouvrages()`: withdrawal devices (can contain several withdrawal points)
- `get_prelevements_points_prelevement()`: withdrawal points

list_apis*List available Hub'Eau APIs, endpoints and filter parameters***Description**`list_apis()` returns the list of available APIs in the package.`list_endpoints()` returns the list of available endpoints for an API.`list_params()` returns the list of available parameters for an API endpoint.**Usage**`list_apis()``list_endpoints(api)``list_params(api, endpoint)`**Arguments**

`api` a **character** name of the API (e.g.: "indicateurs_services", "prelevements"....),
see example for available APIs

`endpoint` a **character** name of the endpoint, see example for available endpoints in an API

Details

The listed APIs correspond to the term [API] used in the name of the functions `get_[API]_[endpoint]` used for querying the APIs.

Value

character vector of APIs, endpoints or filter parameters

Examples

```
# To get the available APIs in the package
list_apis()

# To get the available endpoints in an API
list_endpoints("prelevements")

# To get available parameters in endpoint "chroniques" of the API "prelevements"
list_params(api = "prelevements", endpoint = "chroniques")
```

Index

character, 3, 6–8, 13, 14
convert_list_to_tibble, 2, 3
doApiQuery, 2, 3

get_ecoulement_campagnes
 (get_ecoulement_stations), 4
get_ecoulement_campagnes(), 12
get_ecoulement_observations
 (get_ecoulement_stations), 4
get_ecoulement_observations(), 12
get_ecoulement_stations, 4
get_ecoulement_stations(), 12
get_hydrometrie_obs_elab, 5
get_hydrometrie_obs_elab(), 12
get_hydrometrie_observations_tr
 (get_hydrometrie_obs_elab), 5
get_hydrometrie_observations_tr(), 12
get_hydrometrie_sites
 (get_hydrometrie_obs_elab), 5
get_hydrometrie_sites(), 12
get_hydrometrie_stations
 (get_hydrometrie_obs_elab), 5
get_hydrometrie_stations(), 12
get_indicateurs_services_comunes, 7
get_indicateurs_services_comunes(),
 12
get_indicateurs_services_indicateurs
 (get_indicateurs_services_comunes),
 7
get_indicateurs_services_indicateurs(),
 12
get_indicateurs_services_services
 (get_indicateurs_services_comunes),
 7
get_indicateurs_services_services(),
 12
get_niveaux_nappes_chroniques
 (get_niveaux_nappes_stations),
 9
get_niveaux_nappes_chroniques(), 13
get_niveaux_nappes_chroniques_tr
 (get_niveaux_nappes_stations),
 9
get_niveaux_nappes_chroniques_tr(), 13
get_niveaux_nappes_stations, 9
get_niveaux_nappes_stations(), 13
get_poisson_observations, 10
get_poisson_observations(), 13
get_prelevements_chroniques
 (get_prelevements_points_prelevement),
 11
get_prelevements_chroniques(), 13
get_prelevements_ouvrages
 (get_prelevements_points_prelevement),
 11
get_prelevements_ouvrages(), 13
get_prelevements_points_prelevement,
 11
get_prelevements_points_prelevement(),
 13
hubeau, 12
integer, 7, 8
list, 2–4, 6, 7, 9–11
list_apis, 13
list_endpoints(list_apis), 13
list_params, 3, 4, 6, 7, 9–11
list_params(list_apis), 13
logical, 6
tibble::tibble, 2, 3, 5–11
vector, 14