

Package ‘ibd’

October 13, 2022

Version 1.5

Date 2019-04-24

Title Incomplete Block Designs

Author B N Mandal [aut, cre]

Maintainer B N Mandal <mandal.stat@gmail.com>

Depends R (>= 3.1.1)

Imports lpSolve, car, emmeans, multcomp

Suggests multcompView

Description A collection of several utility functions related to binary incomplete block designs. The package contains function to generate A- and D-efficient binary incomplete block designs with given numbers of treatments, number of blocks and block size. The package also contains function to generate an incomplete block design with specified concurrence matrix. There are functions to generate balanced treatment incomplete block designs and incomplete block designs for test versus control treatments comparisons with specified concurrence matrix. Package also allows performing analysis of variance of data and computing estimated marginal means of factors from experiments using a connected incomplete block design. Tests of hypothesis of treatment contrasts in incomplete block design set up is supported.

License GPL (>= 2)

NeedsCompilation no

Repository CRAN

Date/Publication 2019-04-24 07:10:03 UTC

R topics documented:

aov.ibd	2
A_eff	3
bibd	4
btib	6
btib1	7
Cmatrix	8
design_to_N	9
D_eff	10

ibd	10
ibddata	12
ibdtvc	12
is.connected	14
is.equir	14
is.orthogonal	15
is.proper	16
is.vb	16
N_to_design	17

Index	18
--------------	-----------

aov.ibd	<i>Analysis of variance, least square means and contrast analysis of data from a block design</i>
---------	---

Description

This function performs intrablock analysis of variance of data from experiments using a block design. It also computes estimated marginal means of the factor variables (e.g. treatments) and optionally estimates and tests the contrasts of factor variables (e.g. treatments).

Usage

```
aov.ibd(formula, specs, data, contrast, joint=FALSE, details=FALSE, sort=TRUE, by=NULL,
alpha=0.05, Letters = "ABCDEFGHIJ", ...)
```

Arguments

formula	A formula specifying the model of the form response~treatment+block or response~block+treatment. Make sure the treatment and blocks are factor variables.
specs	A character vector specifying the names of the factors over which estimated marginal means are desired
data	A data frame in which the variables specified in the formula will be found. If missing, the variables are searched for in the standard way.
contrast	A matrix whose rows are contrasts of factors (e.g. treatments)
joint	If contrast argument has more than one row, then whether a joint test of the contrasts will be performed. Default is FALSE. If joint=TRUE, a check is performed whether the contrasts are pairwise orthogonal or not and then if orthogonal, joint test is performed.
details	Logical, if details=TRUE then all objects including lm object from lm(), emm-Grid object from emmeans() are returned. Default is FALSE.
sort	Logical value determining whether the least square means are sorted before the comparisons are produced. Default is TRUE.

by	Character value giving the name or names of variables by which separate families of comparisons are tested. If NULL, all means are compared.
alpha	Numeric value giving the significance level for the comparisons
Letters	Characters to be used for compact letter display of groups of factor variables over which least square means are computed. Default is english alphabet capital letters "ABCDEFGHJIJ"
...	Not used

Details

The function makes use of `lm()` function in R and `Anova()` function in `car` package with specification of Type III sum of squares and `emmeans()`, `contrast()` functions in `emmeans()` package, `cld()` function in `multcomp` package and combines the results in a single place.

Value

Returns a list with following components

<code>lm.obj</code>	An object of class <code>lm</code> if <code>details=TRUE</code>
<code>ANOVA.table</code>	ANOVA table from the fitted <code>lm</code> object
<code>EMMEANS</code>	Estimated marginal means means with compact letter display
<code>contrast.analysis</code>	Contrast analysis result if contrast matrix was supplied

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
data(ibddata)
aov.ibd(y~factor(trt)+factor(blk), data=ibddata)
contrast=matrix(c(1,-1,0,0,0,0,0,0,0,0,1,-1,0,0,0,0), nrow=2, byrow=TRUE)
aov.ibd(y~factor(trt)+factor(blk), specs="trt", data=ibddata, contrast=contrast)
```

A_eff

A-efficiency of a binary incomplete block design

Description

This function computes lower bound to A-efficiency of a binary incomplete block design. Treatment by block incidence matrix of the design is to be supplied as input to the function.

Usage

A_eff(N)

Arguments

N Treatment by block incidence matrix

Value

Aeff A-efficiency

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
N=matrix(c(1,0,0,0,1,0,1,0,0,0,1,0,1,1,0,0,1,0,1,1,0,1,1,0,1,1,0,0,0,0,1,1,0,0,0,1,1,1,0,0,0,1,0,0,
1,0,1,1,0,0),nrow=7,byrow=TRUE)
A_eff(N)
```

bibd

Balanced incomplete block design for given parameters

Description

This function generates a balanced incomplete block design with given number of treatments(v), number of blocks(b), number of replications (r), block size(k) and number of concurrences (lambda).

Usage

```
bibd(v,b,r,k,lambda,ntrial,pbar=FALSE)
```

Arguments

v number of treatments

b number of blocks

r number of replications

k block size

lambda number of concurrences

ntrial number of trials

pbar logical value indicating whether progress bar will be displayed or not. Default is FALSE

Value

v	number of treatments
b	number of blocks
r	number of replications
k	block size
lambda	number of concurrences
design	block contents in a b by k matrix
N	treatments by blocks incidence matrix of the generated design
NNP	concurrence matrix of the generated design
Aeff	Lower bound to the A-efficiency of the generated design
Deff	Lower bound to the D-efficiency of the generated design

Note

The function works best for values of number of treatments (v) up to 30 and block size (k) up to 10. However, for block size (k) up to 3, much larger values of number of treatments (v) may be used.

Author(s)

B N Mandal <mandal.stat@gmail.com>

References

Mandal, B. N., Gupta, V. K. and Parsad, R. (2013). Application of optimization techniques for construction of incomplete block designs. Project report, IASRI, New Delhi.

Mandal, B. N., Gupta, V. K., & Parsad, R. (2014). Efficient Incomplete Block Designs Through Linear Integer Programming. American Journal of Mathematical and Management Sciences, 33(2), 110-124.

Mandal, B. N. (2015). Linear integer programming approach to construction of balanced incomplete block designs. Communications in Statistics-Simulation and Computation, 44:6, 1405-1411.

Examples

```
bibd(7,7,3,3,1,pbar=FALSE)
```

btib *balanced treatment incomplete block designs*

Description

This function generates a balanced treatment incomplete block design for specified parameters.

Usage

```
btib(v,b,r,r0,k,lambda,lambda0,ntrial=5,pbar=FALSE)
```

Arguments

v	number of test treatments
b	number of blocks
r	number of replications of test treatments
r0	number of replications of the control treatment
k	block size
lambda	number of concurrences among test treatments
lambda0	number of concurrences between test treatments and the control treatment
ntrial	number of trials. Default is 5.
pbar	Logical value indicating whether progress bar will be displayed or not. Default is FALSE.

Value

v	number of test treatments
b	number of blocks
r	number of replications of test treatments
r0	number of replications of the control treatment
k	block size
lambda	number of concurrences among test treatments
lambda0	number of concurrences between test treatments and the control treatment
design	generated block design
N	treatment by block incidence matrix of the generated block design
NNP	concurrence matrix of the generated design
Aeff	A-efficiency of the generated design

Note

The function works best for values of number of treatments (v) up to 30 and block size (k) up to 10. However, for block size (k) up to 3, much larger values of number of treatments (v) may be used.

Author(s)

B N Mandal <mandal.stat@gmail.com>

References

Mandal, B. N., Gupta, V. K. and Parsad, R. (2013). Application of optimization techniques for construction of incomplete block designs. Project report, IASRI, New Delhi.

Mandal, B. N., Gupta, V. K., & Parsad, R. (2014). Balanced treatment incomplete block designs through integer programming, *Communications in Statistics - Theory and Methods*, 46:8, 3728-3737.

Examples

```
btib(4,6,3,6,3,1,3,10)
```

 btib1

balanced treatment incomplete block designs

Description

This function generates a balanced treatment incomplete block design for specified parameters by searching all possible combinations.

Usage

```
btib1(v,b,r,r0,k,lambda,lambda0)
```

Arguments

v	number of test treatments
b	number of blocks
r	number of replications of test treatments
r0	number of replications of the control treatment
k	block size
lambda	number of concurrences among test treatments
lambda0	number of concurrences between test treatments and control treatment

Value

v	number of test treatments
b	number of blocks
r	number of replications of test treatments
r0	number of replications of control treatment
k	block size

lambda	number of concurrences among test treatments
lambda0	number of concurrences between test treatments and control treatment
design	generated block design
N	treatment by block incidence matrix of the generated block design
NNP	concurrence matrix of the generated design
Aeff	A-efficiency of the generated design

Note

The function works best for values of number of treatments (v) up to 30 and block size (k) up to 10. However, for block size (k) up to 3, much larger values of number of treatments (v) may be used.

Author(s)

B N Mandal <mandal.stat@gmail.com>

References

Mandal, B. N., Gupta, V. K. and Parsad, R. (2013). Application of optimization techniques for construction of incomplete block designs. Project report, IASRI, New Delhi.

MANDAL, B. N., GUPTA, V. K. and PARSAD, R. (2012). Generation of Binary Incomplete Block Design with a Specified Concurrence Matrix. Journal of Statistics & Applications, 7.

Examples

```
btib(4,6,3,6,3,1,3)
```

Cmatrix	<i>Information matrix from given treatment by block incidence matrix of a block design</i>
---------	--

Description

This function gives the information matrix from a given treatment by block incidence matrix of a block design

Usage

```
Cmatrix(N)
```

Arguments

N treatment by block incidence matrix

Value

Cmatrix v by v information matrix where v is number of treatments

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
N=matrix(c(1,0,0,0,1,0,1,0,0,0,1,0,1,1,0,0,1,0,1,1,0,0,0,0,1,1,0,0,0,0,1,1,0,0,0,1,1,1,0,0,0,1,0,0,
,1,0,1,1,0,0),nrow=7,byrow=TRUE)
Cmatrix(N)
```

design_to_N

block design to treatment by block incidence matrix

Description

This function generates treatment by block incidence matrix from a given block design

Usage

```
design_to_N(design)
```

Arguments

design design

Value

N A treatment by block incidence matrix of order v by b with elements as 0 and 1 where v is the number of treatments and b is the number of blocks

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
d=matrix(c(1,4,6,5,6,7,3,4,5,2,4,7,1,3,7,2,3,6,1,2,5),nrow=7,byrow=TRUE)
design_to_N(d)
```

D_eff	<i>D-efficiency of a binary incomplete block design</i>
-------	---

Description

This function computes lower bound to D-efficiency of a binary incomplete block design. Treatment by block incidence matrix of the design is to be supplied as input to the function.

Usage

```
D_eff(N)
```

Arguments

N	treatment by block incidence matrix
---	-------------------------------------

Value

Deff	Lower bound to D-efficiency
------	-----------------------------

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
N=matrix(c(1,0,0,0,1,0,1,0,0,0,1,0,1,1,0,0,1,0,1,1,0,0,1,0,1,1,0,0,0,0,1,1,0,0,0,1,1,1,0,0,0,1,0,0,
,1,0,1,1,0,0),nrow=7,byrow=TRUE)
D_eff(N)
```

ibd	<i>Binary incomplete block design for given v, b and k and optionally, with a specified concurrence matrix</i>
-----	--

Description

This function generates an A- and D- efficient binary incomplete block design with given number of treatments(v), number of blocks(b) and block size(k) and optionally with a specified concurrence matrix(NNP).

Usage

```
ibd(v,b,k,NNPo,ntrial,pbar=FALSE)
```

Arguments

v	number of treatments
b	number of blocks
k	block size
NNPo	optionally, desired concurrence matrix. If not specified, a nearly balanced concurrence matrix is obtained automatically.
ntrial	number of trials
pbar	progress bar

Value

v	number of treatments
b	number of blocks
k	block size
NNP	specified concurrence matrix
N	incidence matrix of the generated design
design	block contents in a b by k matrix
conc.mat	concurrence matrix of the generated design
A. efficiency	lower bound to A-efficiency of the generated design
D. efficiency	lower bound to D-efficiency of the generated design
time.taken	time taken to generate the design

Note

The function works best for values of number of treatments (v) up to 30 and block size (k) up to 10. However, for block size (k) up to 3, much larger values of number of treatments (v) may be used.

Author(s)

B N Mandal <mandal.stat@gmail.com>

References

- Mandal, B. N., Gupta, V. K. and Parsad, R. (2013). Application of optimization techniques for construction of incomplete block designs. Project report, IASRI, New Delhi.
- Mandal, B. N., Gupta, V. K., & Parsad, R. (2014). Efficient Incomplete Block Designs Through Linear Integer Programming. American Journal of Mathematical and Management Sciences, 33(2), 110-124.

Examples

```
v=9
b=12
k=3
ibd(v,b,k,pbar=FALSE)
```

`ibddata`*Data from an experiment using incomplete block design*

Description

Data from an experiment using incomplete block design

Usage

```
data("ibddata")
```

Format

A data frame with 36 observations on the following 3 variables.

trt Treatments

blk Blocks

y The response variable

Details

The experiment used a balanced incomplete block design.

References

Dey,A. (1986). Theory of block designs. Wiley Eastern Limited, New Delhi.

Examples

```
data(ibddata)
```

`ibdtvc`*incomplete block design for test vs control(s) comparisons*

Description

This function generates an incomplete block design for test vs control(s) comparisons with specified parameters and concurrence matrix.

Usage

```
ibdtvc(v1,v2,b,k,NNPo,ntrial=5,pbar=FALSE)
```

Arguments

v1	number of test treatments
v2	number of control treatments
b	number of blocks
k	block size
NNPo	desired concurrence matrix
ntrial	number of trials, default is 5
pbar	Logical value indicating whether progress bar will be displayed. Default is FALSE.

Value

v1=v1,v2=v2,b=b,k=k,design=design,N=N, NNP=NNP,Aeff=Aeff)

v1	number of test treatments
v2	number of control treatments
b	number of blocks
k	block size
design	generated block design
N	treatment by block incidence matrix of the generated block design
NNP	concurrence matrix of the generated design

Author(s)

B N Mandal <mandal.stat@gmail.com>

References

Mandal, B. N., Gupta, V.K. and Parsad, R. (2013). Binary Incomplete Block Designs with a Specified Concurrence Matrix through Integer Programming, to be submitted for publication

Examples

```
NNPo=matrix(c(7,3,3,3,3,3,3,3,7,3,3,3,3,3,3,3,7,3,3,3,3,3,3,3,7,3,3,3,3,3,3,3,7,
3,3,3,3,3,3,3,7,3,3,3,3,3,3,3,3,9,9,3,3,3,3,3,3,9,9),nrow=8,byrow=TRUE)
ibdtvc(6,2,15,4,NNPo)
```


Value

equir equi-replicated

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
N=matrix(c(1,0,0,0,1,0,1,0,0,0,1,0,1,1,0,0,1,0,1,1,0,1,0,1,1,0,0,0,0,1,1,0,0,0,1,1,1,0,
0,0,1,0,0,1,0,1,1,0,0),nrow=7,byrow=TRUE)
is.equir(N)
```

is.orthogonal *orthogonality a block design*

Description

This function checks whether an incomplete block design is orthogonal or not. Treatment by block incidence matrix of the design is to be supplied as input to the function. If the design is orthogonal, it returns a value of 1 else it returns 0.

Usage

```
is.orthogonal(N)
```

Arguments

N incidence matrix

Value

orthogonal orthogonal

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
N=matrix(c(1,0,0,0,1,0,1,0,0,0,1,0,1,1,0,0,1,0,1,1,0,1,0,1,1,0,0,0,0,1,1,0,0,0,1,1,1,0,
0,0,1,0,0,1,0,1,1,0,0),nrow=7,byrow=TRUE)
is.orthogonal(N)
```


Value

vb variance balanced

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
N=matrix(c(1,0,0,0,1,0,1,0,0,0,1,0,1,1,0,0,1,0,1,1,0,1,0,1,1,0,0,0,0,1,1,0,0,0,1,1,1,0,
0,0,1,0,0,1,0,1,1,0,0),nrow=7,byrow=TRUE)
is.vb(N)
```

N_to_design

Treatment by block incidence matrix from given block design

Description

This function generates the block contents from a given treatment by block incidence matrix

Usage

```
N_to_design(N)
```

Arguments

N treatment by block incidence matrix

Value

design A matrix with number of rows equal to number of blocks and number of columns equal to block size. Constant block size is assumed. Treatments are numbered as 1, 2, ..., v

Author(s)

B N Mandal <mandal.stat@gmail.com>

Examples

```
N=matrix(c(1,0,0,0,1,0,1,0,0,0,1,0,1,1,0,0,1,0,1,1,0,1,0,1,1,0,0,0,0,1,1,0,0,0,1,
1,1,0,0,0,1,0,0,1,0,1,1,0,0),nrow=7,byrow=TRUE)
N_to_design(N)
```

Index

- * **A-efficiency**
 - A_eff, 3
 - bibd, 4
 - btib, 6
 - btib1, 7
 - ibd, 10
 - * **Connectedness**
 - is.connected, 14
 - * **D-efficiency**
 - bibd, 4
 - D_eff, 10
 - ibd, 10
 - * **EMMEANS**
 - aov.ibd, 2
 - * **Estimated marginal means**
 - aov.ibd, 2
 - * **Type III sum of squares**
 - aov.ibd, 2
 - * **analysis of variance**
 - aov.ibd, 2
 - * **balanced incomplete block design**
 - aov.ibd, 2
 - bibd, 4
 - * **block design**
 - is.orthogonal, 15
 - * **concurrence matrix**
 - bibd, 4
 - ibd, 10
 - * **contrast analysis**
 - aov.ibd, 2
 - * **datasets**
 - ibddata, 12
 - * **equi-replicated**
 - is.equir, 14
 - * **incidence matrix**
 - bibd, 4
 - Cmatrix, 8
 - design_to_N, 9
 - ibd, 10
 - N_to_design, 17
 - * **incomplete block design**
 - A_eff, 3
 - aov.ibd, 2
 - btib, 6
 - btib1, 7
 - Cmatrix, 8
 - D_eff, 10
 - design_to_N, 9
 - ibd, 10
 - ibdtvc, 12
 - is.connected, 14
 - is.equir, 14
 - is.proper, 16
 - is.vb, 16
 - N_to_design, 17
 - * **information matrix**
 - Cmatrix, 8
 - * **orthogonal**
 - is.orthogonal, 15
 - * **proper**
 - is.proper, 16
 - * **test vs control(s) comparison**
 - btib, 6
 - btib1, 7
 - ibdtvc, 12
 - * **variance balanced**
 - is.vb, 16
- A_eff, 3
aov.ibd, 2
- bibd, 4
btib, 6
btib1, 7
- Cmatrix, 8
- D_eff, 10
design_to_N, 9

ibd, [10](#)
ibddata, [12](#)
ibdtvc, [12](#)
is.connected, [14](#)
is.equir, [14](#)
is.orthogonal, [15](#)
is.proper, [16](#)
is.vb, [16](#)

N_to_design, [17](#)