

Package ‘kim’

October 13, 2022

Title A Toolkit for Behavioral Scientists

Version 0.5.55

Description A collection of functions for analyzing data typically collected or used by behavioral scientists. Examples of the functions include a function that compares groups in a factorial experimental design, a function that conducts (robust) two-way analysis of variance (ANOVA), and a function that cleans a data set generated by Qualtrics surveys. Some of the functions will require installing additional package(s). Such packages and other references are cited within the section describing the relevant functions. Many functions in this package rely heavily on these two popular R packages:
Dowle et al. (2021) <<https://CRAN.R-project.org/package=data.table>>.
Wickham et al. (2021) <<https://CRAN.R-project.org/package=ggplot2>>.

License GPL-3

URL <https://github.com/jinkim3/kim>, <https://jinkim.science>

BugReports <https://github.com/jinkim3/kim/issues>

Imports data.table, remotes

Suggests boot, ggplot2, moments

Encoding UTF-8

RoxygenNote 7.1.1

NeedsCompilation no

Author Jin Kim [aut, cre] (<<https://orcid.org/0000-0002-5013-3958>>)

Maintainer Jin Kim <jin.m.kim@yale.edu>

Repository CRAN

Date/Publication 2022-07-08 15:40:02 UTC

R topics documented:

akaike_weights	4
barplot_for_counts	5

bracket	5
capitalize	7
change_var_names	7
check_modes	8
check_req_pkg	9
chi_squared_test_pairwise	9
clean_data_from_qualtrics	11
coeffcent_of_variation	12
cohen_d	13
cohen_d_borenstein	14
cohen_d_from_cohen_textbook	15
cohen_d_over_n	16
cohen_d_torchiano	17
combine_data_across_cols	18
comma_sep_string_to_numbers	18
compare_datasets	19
compare_dependent_rs	20
compare_effect_sizes	21
compare_groups	22
compare_independent_rs	24
convert_cols_to_numeric	26
convert_to_excel_formula	27
correlation_matrix	27
cum_percent_plot	28
desc_stats	29
desc_stats_by_group	30
detach_user_installed_pkgs	31
duplicated_values	32
exit_from_parent_function	33
find_duplicates	33
fisher_z_transform	34
floodlight_2_by_continuous	35
forest_plot	38
ggsave_quick	41
histogram	42
histogram_by_group	43
histogram_w_outlier_bins	45
identical_all	47
id_across_datasets	47
install_all_dependencies	48
kurtosis	49
logistic_regression	50
logistic_regression_table	52
logistic_reg_w_interaction	53
loglinear_analysis	54
mann_whitney	56
matrix_prep_dt	56
mediation_analysis	57

merge_data_tables	59
merge_data_table_list	60
modes_of_objects	61
multiple_regression	62
noncentrality_parameter	63
order_rows_specifically_in_dt	64
outlier	65
overlapping_interval	66
p0	67
parallel_analysis	67
percentile_rank	68
pivot_table	69
plot_group_means	70
pm	72
population_variance	72
prep	73
pretty_round_p_value	74
pretty_round_r	75
print_loop_progress	75
proportion_of_values_in_vector	76
q_stat_test_homo_r	78
read_csv	78
read_sole_csv	79
regex_match	80
rel_pos_of_value_in_vector	80
rel_value_of_pos_in_vector	81
remove_from_vector	82
remove_user_installed_pkgs	82
repeated_measures_anova	83
replace_values_in_dt	84
robust_regression	85
round_flexibly	86
scatterplot	87
score_scale_items	90
setup_r_env	91
setwd_to_active_doc	91
se_of_mean	92
simple_effects_analysis	93
skewness	94
spotlight_2_by_continuous	95
standardized_regression	100
start_kim	102
su	103
tabulate_vector	104
theme_kim	105
top_median_or_bottom	106
tv	107
two_way_anova	108

t_test_pairwise	110
und	111
unload_user_installed_pkgs	112
update_kim	113
vlookup	114
weighted_mean_r	114
weighted_z	115
wilcoxon_rank_sum_test	116
write_csv	117
z_to_r_transform	117

Index	119
--------------	------------

akaike_weights	<i>Akaike Weights</i>
----------------	-----------------------

Description

Compare adequacy of different models by calculating their Akaike weights and the associated evidence ratio.

Usage

```
akaike_weights(aic_values = NULL, print_output_explanation = TRUE)
```

Arguments

`aic_values` a vector of AIC values
`print_output_explanation` logical. Should an explanation about how to read the output be printed? (default = TRUE).

Details

Please refer to Wagenmakers & Farrell (2004), doi:10.3758/BF03206482

Value

the output will be a `data.table` showing AIC weights, their evidence ratio(s), etc.

Examples

```
# default reference AIC value is the minimum AIC value, e.g., 202 below.
akaike_weights(c(204, 202, 206, 206, 214))
```

barplot_for_counts *Barplot for counts*

Description

Barplot for counts

Usage

```
barplot_for_counts(data = NULL, x, y)
```

Arguments

data	a data object (a data frame or a data.table)
x	name of the variable that will be on the x axis of the barplot
y	name of the variable that will be on the y axis of the barplot

Examples

```
barplot_for_counts(x = 1:3, y = 7:9)
barplot_for_counts(data = data.frame(
  cyl = names(table(mtcars$cyl)), count = as.vector(table(mtcars$cyl))),
  x = "cyl", y = "count")
```

bracket *Draw a bracket on a ggplot*

Description

Draw a square bracket with a label on a ggplot

Usage

```
bracket(
  xmin = NULL,
  xmax = NULL,
  ymin = NULL,
  ymax = NULL,
  vertical = NULL,
  horizontal = NULL,
  open = NULL,
  bracket_shape = NULL,
  thickness = 2,
```

```

    bracket_color = "black",
    label = NULL,
    label_hjust = NULL,
    label_vjust = NULL,
    label_font_size = 5,
    label_font_face = "bold",
    label_color = "black",
    label_parse = FALSE
  )

```

Arguments

xmin	xmin
xmax	xmax
ymin	ymin
ymax	ymax
vertical	vertical
horizontal	horizontal
open	open
bracket_shape	bracket_shape
thickness	thickness
bracket_color	bracket_color
label	label
label_hjust	label_hjust
label_vjust	label_vjust
label_font_size	label_font_size
label_font_face	label_font_face
label_color	label_color
label_parse	label_parse

Value

a ggplot object; there will be no meaningful output from this function. Instead, this function should be used with another ggplot object

Examples

```

prep(ggplot2)
ggplot(mtcars, aes(x = cyl, y = mpg)) + geom_point() +
bracket(6.1, 6.2, 17, 22, bracket_shape = "]", label = "abc")

```

capitalize	<i>Capitalize a substring</i>
------------	-------------------------------

Description

Capitalizes the first letter (by default) or a substring of a given character string or each element of the character vector

Usage

```
capitalize(x, start = 1, end = 1)
```

Arguments

x	a character string or a character vector
start	starting position of the substring (default = 1)
end	ending position of the substring (default = 1)

Value

a character string or a character vector

Examples

```
capitalize("abc")  
capitalize(c("abc", "yx"), start = 2, end = 3)
```

change_var_names	<i>Change variable names in a data set</i>
------------------	--

Description

Change variable names in a data set

Usage

```
change_var_names(  
  data = NULL,  
  old_var_names = NULL,  
  new_var_names = NULL,  
  skip_absent = FALSE,  
  print_summary = TRUE,  
  output_type = "dt"  
)
```

Arguments

data	a data object (a data frame or a data.table)
old_var_names	a vector of old variable names (i.e., variable names to change)
new_var_names	a vector of new variable names
skip_absent	If skip_absent = TRUE, old variable names that do not exist in the data set will be skipped (default = TRUE).
print_summary	If print_summary = TRUE, a summary of old and new variable names will be printed. (default = TRUE)
output_type	type of the output. If output_type = "dt", the function's output will be a data.table with changed names. If output_type = "summary", the function's output will be a data.table listing old and new variable names. By default, output_type = "dt".

Value

a data.table object with changed variable names

Examples

```
change_var_names(
  mtcars, old = c("mpg", "cyl"), new = c("mpg_new", "cyl_new"))
```

check_modes

Check modes of objects

Description

Check modes of objects

Usage

```
check_modes(..., mode_to_confirm = NULL)
```

Arguments

...	R objects.
mode_to_confirm	The function will test whether each input is of this mode. For example, check_modes(a, mode_to_confirm = "numeric"), the function will check whether the object a is numeric.

Examples

```
check_modes(1L, mode_to_confirm = "numeric")
check_modes(
  TRUE, FALSE, 1L, 1:3, 1.1, c(1.2, 1.3), "abc", 1 + 2i, intToBits(1L),
  mode_to_confirm = "numeric")
```

check_req_pkg	<i>Check for required packages</i>
---------------	------------------------------------

Description

Check whether required packages are installed.

Usage

```
check_req_pkg(pkg = NULL)
```

Arguments

pkg a character vector containing names of packages to check

Value

there will be no output from this function. Rather, the function will check whether the packages given as inputs are installed.

Examples

```
check_req_pkg("data.table")
check_req_pkg(c("base", "utils", "ggplot2", "data.table"))
```

chi_squared_test_pairwise	<i>Chi-squared test, pairwise</i>
---------------------------	-----------------------------------

Description

Conducts a chi-squared test for every possible pairwise comparison with Bonferroni correction

Usage

```
chi_squared_test_pairwise(
  data = NULL,
  iv_name = NULL,
  dv_name = NULL,
  focal_dv_value = NULL,
  contingency_table = TRUE,
  contingency_table_sigfigs = 2,
  percent_and_total = FALSE,
```

```

percentages_only = NULL,
counts_only = NULL,
sigfigs = 3,
chi_sq_test_stats = FALSE
)

```

Arguments

data a data object (a data frame or a data.table)

iv_name name of the independent variable (must be a categorical variable)

dv_name name of the dependent variable (must be a binary variable)

focal_dv_value focal value of the dependent variable whose frequencies will be calculated (i.e., the value of the dependent variable that will be considered a "success" or a result of interest)

contingency_table
If `contingency_table = TRUE` or if `contingency_table = "percentages"`, the percentage of each binary value within each group will be printed. If `contingency_table = "counts"`, a table of frequencies will be printed. If `contingency_table = FALSE`, no contingency table will be printed.

contingency_table_sigfigs
number of significant digits that the contingency table's percentage values should be rounded to (default = 2)

percent_and_total
logical. If `percent_and_total = TRUE`, tabulate percentages of the focal DV value and a total count of the two values in DV. By default `percent_and_total = FALSE`

percentages_only
tabulate percentages of the focal DV value only

counts_only
tabulate counts of the focal DV value only

sigfigs
number of significant digits to round to

chi_sq_test_stats
if `chi_sq_test_stats = TRUE`, chi-squared test statistic and degrees of freedom will be included in the pairwise comparison data.table.

Examples

```

chi_squared_test_pairwise(data = mtcars, iv_name = "vs", dv_name = "am")
chi_squared_test_pairwise(data = mtcars, iv_name = "vs", dv_name = "am",
percentages_only = TRUE)
# using 3 mtcars data sets combined
chi_squared_test_pairwise(
data = rbind(mtcars, rbind(mtcars, mtcars)),
iv_name = "cyl", dv_name = "am")
# include the total counts
chi_squared_test_pairwise(
data = rbind(mtcars, rbind(mtcars, mtcars)),
iv_name = "cyl", dv_name = "am", percent_and_total = TRUE)
# display counts

```

```
chi_squared_test_pairwise(
  data = rbind(mtcars, rbind(mtcars, mtcars)),
  iv_name = "cyl", dv_name = "am", contingency_table = "counts")
```

clean_data_from_qualtrics

Clean data from Qualtrics

Description

Clean a data set downloaded from Qualtrics

Usage

```
clean_data_from_qualtrics(
  data = NULL,
  remove_survey_preview_data = TRUE,
  remove_test_response_data = TRUE,
  default_cols_by_qualtrics = NULL,
  default_cols_by_qualtrics_new = NULL,
  warn_accuracy_loss = FALSE,
  click_data_cols = "rm",
  page_submit_cols = "move_to_right"
)
```

Arguments

data a data object (a data frame or a data.table)

remove_survey_preview_data
logical. Whether to remove data from survey preview (default = TRUE)

remove_test_response_data
logical. Whether to remove data from test response (default = TRUE)

default_cols_by_qualtrics
names of columns that Qualtrics includes in the data set by default (e.g., "StartDate", "Finished"). Accepting the default value `default_cols_by_qualtrics = NULL` will set the names to be those that Qualtrics uses as of Dec 25, 2020.

default_cols_by_qualtrics_new
new names for columns that Qualtrics includes in the data set by default (e.g., "StartDate", "Finished"). Accepting the default value `default_cols_by_qualtrics_new = NULL` will set the names to be those that Qualtrics uses as of Dec 25, 2020 converted to snake_case (e.g., "start_date", "finished").

warn_accuracy_loss
logical. whether to warn the user if converting character to numeric leads to loss of accuracy. (default = FALSE)

click_data_cols

if `click_data_cols = "rm"`, columns containing click data (e.g., "_First Click") will be removed. If `click_data_cols = "move_to_right"`, the columns will be moved to the right (end) of the data set.

page_submit_cols

if `page_submit_cols = "rm"`, columns containing page submit data (e.g., "_Page Submit"; "response time" data) will be removed. If `page_submit_cols = "move_to_right"`, the columns will be moved to the right (end) of the data set.

Value

a `data.table` object

Examples

```
clean_data_from_qualtrics(mtcars)
clean_data_from_qualtrics(mtcars, default_cols_by_qualtrics = "mpg",
  default_cols_by_qualtrics_new = "mpg2")
```

coefficient_of_variation

Coefficient of variation

Description

Calculates the (population or sample) coefficient of variation of a given numeric vector

Usage

```
coefficient_of_variation(vector, pop_or_sample = "pop")
```

Arguments

`vector` a numeric vector

`pop_or_sample` should coefficient of variation be calculated for a "population" or a "sample"?

Value

a numeric value

Examples

```
coefficient_of_variation(1:4, pop_or_sample = "sample")
coefficient_of_variation(1:4, pop_or_sample = "pop")
```

cohen_d	<i>Calculate Cohen's d and its confidence interval using the package 'psych'</i>
---------	--

Description

To run this function, the following package(s) must be installed: Package 'psych' v2.1.9 (or possibly a higher version) by William Revelle (2021), <https://cran.r-project.org/package=psych>

Usage

```
cohen_d(  
  sample_1 = NULL,  
  sample_2 = NULL,  
  data = NULL,  
  iv_name = NULL,  
  dv_name = NULL,  
  ci_range = 0.95,  
  output_type = "all"  
)
```

Arguments

sample_1	a vector of values in the first of two samples
sample_2	a vector of values in the second of two samples
data	a data object (a data frame or a data.table)
iv_name	name of the independent variable
dv_name	name of the dependent variable
ci_range	range of the confidence interval for Cohen's d (default = 0.95)
output_type	If output_type == "all" or if output_type == "d_and_ci", the output will be a vector of Cohen's d and its confidence interval. If output_type == "d", the output will be Cohen's d. If output_type == "ci", the output will be a vector of the confidence interval around Cohen's d. By default, output_type == "all".

Examples

```
## Not run:  
cohen_d(sample_1 = 1:10, sample_2 = 3:12)  
cohen_d(data = mtcars, iv_name = "vs", dv_name = "mpg", ci_range = 0.99)  
sample_dt <- data.table::data.table(iris)[Species != "setosa"]  
cohen_d(data = sample_dt, iv_name = "Species", dv_name = "Petal.Width")  
  
## End(Not run)
```

cohen_d_borenstein	<i>Calculate Cohen's d as illustrated by Borenstein et al. (2009, ISBN: 978-0-470-05724-7)</i>
--------------------	--

Description

Calculates Cohen's d, its standard error, and confidence interval, as illustrated in the Borenstein et al. (2009, ISBN: 978-0-470-05724-7).

Usage

```
cohen_d_borenstein(
  sample_1 = NULL,
  sample_2 = NULL,
  data = NULL,
  iv_name = NULL,
  dv_name = NULL,
  direction = "2_minus_1",
  ci_range = 0.95,
  output_type = "all",
  initial_value = 0
)
```

Arguments

sample_1	a vector of values in the first of two samples
sample_2	a vector of values in the second of two samples
data	a data object (a data frame or a data.table)
iv_name	name of the independent variable
dv_name	name of the dependent variable
direction	If direction == "2_minus_1", Cohen's d will reflect the extent to which the mean of IV level 2 is greater than the mean of IV level 1. If direction == "1_minus_2", Cohen's d will reflect the extent to which the mean of IV level 1 is greater than the mean of IV level 2. By default, direction == "2_minus_1".
ci_range	range of the confidence interval for Cohen's d (default = 0.95)
output_type	If output_type == "all" or if output_type == "d_var_se_and_ci", the output will be a vector of Cohen's d and its variance, SE, and confidence interval. If output_type == "d_se_and_ci", the output will be a vector of Cohen's d and its SE and confidence interval. If output_type == "d_and_ci", the output will be a vector of Cohen's d and its confidence interval. If output_type == "d", the output will be Cohen's d. If output_type == "ci", the output will be a vector of the confidence interval around Cohen's d. If output_type == "se", the output will be the standard error of Cohen's d. By default, output_type == "all".
initial_value	initial value of the noncentrality parameter for optimization (default = 0). Adjust this value if confidence interval results look strange.

Examples

```
cohen_d_borenstein(sample_1 = 1:10, sample_2 = 3:12)
cohen_d_borenstein(
  data = mtcars, iv_name = "vs", dv_name = "mpg", ci_range = 0.99)
sample_dt <- data.table::data.table(iris)[Species != "setosa"]
cohen_d_borenstein(
  data = sample_dt, iv_name = "Species", dv_name = "Petal.Width",
  initial_value = 10)
```

cohen_d_from_cohen_textbook

Cohen's d from Jacob Cohen's textbook (1988)

Description

Calculates Cohen's d as described in Jacob Cohen's textbook (1988), Statistical Power Analysis for the Behavioral Sciences, 2nd Edition Cohen, J. (1988) doi: [10.4324/9780203771587](https://doi.org/10.4324/9780203771587)

Usage

```
cohen_d_from_cohen_textbook(
  sample_1 = NULL,
  sample_2 = NULL,
  data = NULL,
  iv_name = NULL,
  dv_name = NULL
)
```

Arguments

sample_1	a vector of values in the first of two samples
sample_2	a vector of values in the second of two samples
data	a data object (a data frame or a data.table)
iv_name	name of the independent variable
dv_name	name of the dependent variable

Value

the output will be a Cohen's d value (a numeric vector of length one)

Examples

```
cohen_d_from_cohen_textbook(1:10, 3:12)
cohen_d_from_cohen_textbook(
  data = mtcars, iv_name = "vs", dv_name = "mpg"
)
```

cohen_d_over_n *Cohen's d as a function of sample size*

Description

Plot Cohen's d as sample size increases.

Usage

```
cohen_d_over_n(
  data = NULL,
  iv_name = NULL,
  dv_name = NULL,
  save_as_png = FALSE,
  png_name = NULL,
  xlab = NULL,
  ylab = NULL,
  width = 16,
  height = 9
)
```

Arguments

data	a data object (a data frame or a data.table)
iv_name	name of the independent variable (grouping variable)
dv_name	name of the dependent variable (measure variable of interest)
save_as_png	if save = TRUE, the plot will be saved as a PNG file.
png_name	name of the PNG file to be saved. By default, the name will be "cohen_d_over_n_" followed by a timestamp of the current time. The timestamp will be in the format, jan_01_2021_1300_10_000001, where "jan_01_2021" would indicate January 01, 2021; 1300 would indicate 13:00 (i.e., 1 PM); and 10_000001 would indicate 10.000001 seconds after the hour.
xlab	title of the x-axis for the histogram by group. If xlab = FALSE, the title will be removed. By default (i.e., if no input is given), dv_name will be used as the title.
ylab	title of the y-axis for the histogram by group. If ylab = FALSE, the title will be removed. By default (i.e., if no input is given), iv_name will be used as the title.
width	width of the plot to be saved. This argument will be directly entered as the width argument for the ggsave function within ggplot2 package (default = 16)
height	height of the plot to be saved. This argument will be directly entered as the height argument for the ggsave function within ggplot2 package (default = 9)

Value

the output will be a list of (1) ggplot object (histogram by group) and (2) a data.table with Cohen's d by sample size

Examples

```
## Not run:
cohen_d_over_n(data = mtcars, iv_name = "am", dv_name = "mpg")

## End(Not run)
```

cohen_d_torchiano	<i>Calculate Cohen's d and its confidence interval using the package 'effsize'</i>
-------------------	--

Description

To run this function, the following package(s) must be installed: Package 'effsize' v0.8.1 (or possibly a higher version) by Marco Torchiano (2020), <https://cran.r-project.org/package=effsize>

Usage

```
cohen_d_torchiano(
  sample_1 = NULL,
  sample_2 = NULL,
  data = NULL,
  iv_name = NULL,
  dv_name = NULL,
  ci_range = 0.95
)
```

Arguments

sample_1	a vector of values in the first of two samples
sample_2	a vector of values in the second of two samples
data	a data object (a data frame or a data.table)
iv_name	name of the independent variable
dv_name	name of the dependent variable
ci_range	range of the confidence interval for Cohen's d (default = 0.95)

Examples

```
cohen_d_torchiano(1:10, 3:12)
cohen_d_torchiano(
  data = mtcars, iv_name = "vs", dv_name = "mpg", ci_range = 0.99)
```

combine_data_across_cols

Combine data across columns

Description

Combine data across columns. If NA is the only value across all focal columns for given row(s), NA will be returned for those row(s).

Usage

```
combine_data_across_cols(data = NULL, cols = NULL)
```

Arguments

`data` a data object (a data frame or a data.table)
`cols` a character vector containing names of columns, across which to combine data

Value

the output will be a numeric or character vector.

Examples

```
dt <- data.frame(v1 = c(1, NA), v2 = c(NA, 2))
dt
combine_data_across_cols(data = dt, cols = c("v1", "v2"))
dt <- data.frame(v1 = c(1, 2, NA), v2 = c(NA, 4, 3))
dt
combine_data_across_cols(data = dt, cols = c("v1", "v2"))
dt <- data.frame(v1 = c(1, NA, NA), v2 = c(NA, 2, NA))
dt
combine_data_across_cols(data = dt, cols = c("v1", "v2"))
```

comma_sep_string_to_numbers

Convert a comma-separated string of numbers

Description

Convert a comma-separated string of numbers

Usage

```
comma_sep_string_to_numbers(string)
```

Arguments

string a character string consisting of numbers separated by commas

Value

a character string

Examples

```
comma_sep_string_to_numbers("1, 2, 3,4, 5 6")
```

compare_datasets *Compare data sets*

Description

Compares whether or not data sets are identical

Usage

```
compare_datasets(dataset_1 = NULL, dataset_2 = NULL, dataset_list = NULL)
```

Arguments

dataset_1 a data object (a data frame or a data.table)
dataset_2 another data object (a data frame or a data.table)
dataset_list list of data objects (data.frame or data.table)

Value

the output will be a data.table showing differences in data sets

Examples

```
# catch differences in class attributes of the data sets
compare_datasets(
  dataset_1 = data.frame(a = 1:2, b = 3:4),
  dataset_2 = data.table::data.table(a = 1:2, b = 3:4))
# catch differences in number of columns
compare_datasets(
  dataset_1 = data.frame(a = 1:2, b = 3:4, c = 5:6),
  dataset_2 = data.frame(a = 1:2, b = 3:4))
# catch differences in number of rows
compare_datasets(
  dataset_1 = data.frame(a = 1:2, b = 3:4),
  dataset_2 = data.frame(a = 1:10, b = 11:20))
# catch differences in column names
compare_datasets(
```

```

dataset_1 = data.frame(A = 1:2, B = 3:4),
dataset_2 = data.frame(a = 1:2, b = 3:4)
# catch differences in values within corresponding columns
compare_datasets(
dataset_1 = data.frame(a = 1:2, b = c(3, 400)),
dataset_2 = data.frame(a = 1:2, b = 3:4))
compare_datasets(
dataset_1 = data.frame(a = 1:2, b = 3:4, c = 5:6),
dataset_2 = data.frame(a = 1:2, b = c(3, 4), c = c(5, 6)))
# check if data sets in a list are identical
compare_datasets(
dataset_list = list(
dt1 = data.frame(a = 1:2, b = 3:4, c = 5:6),
dt2 = data.frame(a = 1:2, b = 3:4),
dt3 = data.frame(a = 1:2, b = 3:4, c = 5:6)))

```

compare_dependent_rs *Compare dependent correlations*

Description

Compares whether two dependent correlations from the same sample are significantly different each other.

Usage

```

compare_dependent_rs(
  data = NULL,
  var_1_name = NULL,
  var_2_name = NULL,
  var_3_name = NULL,
  one_tailed = FALSE,
  round_r = 3,
  round_p = 3,
  round_t = 2,
  print_summary = TRUE,
  return_dt = FALSE
)

```

Arguments

data	a data object (a data frame or a data.table)
var_1_name	name of the variable whose correlations with two other variables will be compared.
var_2_name	name of the first of the two variables whose correlations with var_1_name will be compared.
var_3_name	name of the second of the two variables whose correlations with var_1_name will be compared.

one_tailed	logical. Should the p value based on a one-tailed t-test? (default = FALSE)
round_r	number of decimal places to which to round correlation coefficients (default = 2)
round_p	number of decimal places to which to round p-values (default = 3)
round_t	number of decimal places to which to round the t-statistic (default = 2)
print_summary	logical. Should the summary be printed? (default = TRUE)
return_dt	logical. Should the function return a summary table as an output, as opposed to returning the output through the "invisible" function? (default = FALSE)

Details

Suppose that Variables A, B, and C are measured from a group of subjects. This function tests whether A is related to B differently than to C. Put differently, this function tests $H_0: r(A, B) = r(A, C)$

For more information on formulas used in this function, please refer to Steiger (1980) doi:10.1037/0033-2909.87.2.245 and Chen & Popovich (2002) doi:10.4135/9781412983808

Value

the output will be a summary of the test comparing two dependent correlations

Examples

```
compare_dependent_rs(
  data = mtcars, var_1_name = "mpg", var_2_name = "hp", var_3_name = "wt")
```

compare_effect_sizes *Compare effect sizes*

Description

Compares effect sizes See p. 156 of Borenstein et al. (2009, ISBN: 978-0-470-05724-7).

Usage

```
compare_effect_sizes(
  effect_sizes = NULL,
  effect_size_variances = NULL,
  round_stats = TRUE,
  round_p = 3,
  round_se = 2,
  round_z = 2,
  pretty_round_p_value = TRUE
)
```

Arguments

effect_sizes a vector of estimated effect sizes
effect_size_variances
 a vector of variances of the effect sizes
round_stats logical. Should the statistics be rounded? (default = TRUE)
round_p number of decimal places to which to round p-values (default = 3)
round_se number of decimal places to which to round the standard errors of the difference (default = 2)
round_z number of decimal places to which to round the z-statistic (default = 2)
pretty_round_p_value
 logical. Should the p-values be rounded in a pretty format (i.e., lower threshold: "<.001"). By default, pretty_round_p_value = TRUE.

Examples

```

compare_effect_sizes(
  effect_sizes = c(0.6111, 0.3241, 0.5),
  effect_size_variances = c(.0029, 0.0033, 0.01))

```

compare_groups	<i>Compare groups</i>
----------------	-----------------------

Description

Compares groups by (1) creating histogram by group; (2) summarizing descriptive statistics by group; and (3) conducting pairwise comparisons (t-tests and Mann-Whitney tests).

Usage

```

compare_groups(
  data = NULL,
  iv_name = NULL,
  dv_name = NULL,
  sigfigs = 3,
  stats = "basic",
  cohen_d = TRUE,
  cohen_d_w_ci = TRUE,
  bonferroni = FALSE,
  mann_whitney = TRUE,
  t_test_stats = FALSE,
  t_test_df_decimals = 1,
  round_p = 3,
  save_as_png = FALSE,

```

```

png_name = NULL,
xlab = NULL,
ylab = NULL,
x_limits = NULL,
x_breaks = NULL,
x_labels = NULL,
width = 4000,
height = 3000,
units = "px",
res = 300,
layout_matrix = NULL,
col_names_nicer = TRUE
)

```

Arguments

data	a data object (a data frame or a data.table)
iv_name	name of the independent variable (grouping variable)
dv_name	name of the dependent variable (measure variable of interest)
sigfigs	number of significant digits to round to
stats	statistics to calculate for each group. If stats = "basic", group size, mean, standard deviation, median, minimum, and maximum will be calculated. If stats = "all", in addition to the aforementioned statistics, standard error, 95% confidence and prediction intervals, skewness, and kurtosis will also be calculated. The stats argument can also be a character vector with types of statistics to calculate. For example, entering stats = c("mean", "median") will calculate mean and median. By default, stats = "basic"
cohen_d	if cohen_d = TRUE, Cohen's d statistics will be included in the pairwise comparison data.table.
cohen_d_w_ci	if cohen_d_w_ci = TRUE, Cohen's d with 95% CI will be included in the output data.table.
bonferroni	if bonferroni = TRUE, Bonferroni tests will be conducted for t-tests or Mann-Whitney tests.
mann_whitney	if TRUE, Mann-Whitney test results will be included in the pairwise comparison data.table. If FALSE, Mann-Whitney tests will not be performed.
t_test_stats	if t_test_stats = TRUE, t-test statistic and degrees of freedom will be included in the pairwise comparison data.table.
t_test_df_decimals	number of decimals for the degrees of freedom in t-tests (default = 1)
round_p	number of decimal places to which to round p-values (default = 3)
save_as_png	if save = "all" or if save = TRUE, the histogram by group, descriptive statistics by group, and pairwise comparison results will be saved as a PNG file.
png_name	name of the PNG file to be saved. By default, the name will be "compare_groups_results_" followed by a timestamp of the current time. The timestamp will be in the format, jan_01_2021_1300_10_000001, where "jan_01_2021" would indicate January 01, 2021; 1300 would indicate 13:00 (i.e., 1 PM); and 10_000001 would indicate 10.000001 seconds after the hour.

xlab	title of the x-axis for the histogram by group. If xlab = FALSE, the title will be removed. By default (i.e., if no input is given), dv_name will be used as the title.
ylab	title of the y-axis for the histogram by group. If ylab = FALSE, the title will be removed. By default (i.e., if no input is given), iv_name will be used as the title.
x_limits	a numeric vector with values of the endpoints of the x axis.
x_breaks	a numeric vector indicating the points at which to place tick marks on the x axis.
x_labels	a vector containing labels for the place tick marks on the x axis.
width	width of the PNG file (default = 4000)
height	height of the PNG file (default = 3000)
units	the units for the width and height arguments. Can be "px" (pixels), "in" (inches), "cm", or "mm". By default, units = "px".
res	The nominal resolution in ppi which will be recorded in the png file, if a positive integer. Used for units other than the default. If not specified, taken as 300 ppi to set the size of text and line widths.
layout_matrix	The layout argument for arranging plots and tables using the grid.arrange function.
col_names_nicer	if col_names_nicer = TRUE, column names will be converted from snake_case to an easier-to-eye format.

Value

the output will be a list of (1) ggplot object (histogram by group) (2) a data.table with descriptive statistics by group; and (3) a data.table with pairwise comparison results. If save_as_png = TRUE, the plot and tables will be also saved on local drive as a PNG file.

Examples

```
## Not run:
compare_groups(data = iris, iv_name = "Species", dv_name = "Sepal.Length")
compare_groups(data = iris, iv_name = "Species", dv_name = "Sepal.Length",
x_breaks = 4:8)

## End(Not run)
```

compare_independent_rs

Compare independent correlations

Description

Compares whether two correlations from two independent samples are significantly different each other. See Field et al. (2012, ISBN: 978-1-4462-0045-2).

Usage

```
compare_independent_rs(
  r1 = NULL,
  n1 = NULL,
  r2 = NULL,
  n2 = NULL,
  one_tailed = FALSE,
  round_p = 3,
  round_z_diff = 2,
  round_r = 2,
  print_summary = TRUE,
  output_type = NULL
)
```

Arguments

r1	correlation in the first sample
n1	size of the first sample
r2	correlation in the second sample
n2	size of the first sample
one_tailed	logical. Should the p value based on a one-tailed t-test? (default = FALSE)
round_p	(only for displaying purposes) number of decimal places to which to round the p-value (default = 3)
round_z_diff	(only for displaying purposes) number of decimal places to which to round the z-score (default = 2)
round_r	(only for displaying purposes) number of decimal places to which to round correlation coefficients (default = 2)
print_summary	logical. Should the summary be printed? (default = TRUE)
output_type	type of the output. If output_type = "z", the function's output will be the z-score of the difference between the two correlations. If output_type = "p", the function's output will be the p-value associated with the z-score of the difference between the two correlations. By default, output_type = NULL, and the function will not return any value other than the printed summary.

Value

the output will be the results of a test comparing two independent correlations.

Examples

```
compare_independent_rs(r1 = .1, n1 = 100, r2 = .2, n2 = 200)
compare_independent_rs(
  r1 = .1, n1 = 100, r2 = .2, n2 = 200, one_tailed = TRUE)
compare_independent_rs(r1 = .506, n1 = 52, r2 = .381, n2 = 51)
```

`convert_cols_to_numeric`*Convert columns to numeric*

Description

Check whether each column in a `data.table` can be converted to numeric, and if so, convert every such column.

Usage

```
convert_cols_to_numeric(  
  data = NULL,  
  classes = "character",  
  warn_accuracy_loss = TRUE,  
  print_summary = TRUE,  
  silent = FALSE  
)
```

Arguments

<code>data</code>	a data object (a data frame or a <code>data.table</code>)
<code>classes</code>	a character vector specifying classes of columns that will be converted. For example, if <code>classes = "character"</code> , all columns of the class "character" will be converted—if they can be converted. The current version of the function only supports converting character columns to numeric.
<code>warn_accuracy_loss</code>	logical. whether to warn the user if converting character to numeric leads to loss of accuracy. (default = TRUE)
<code>print_summary</code>	If <code>print_summary = TRUE</code> , a summary of converted columns will be printed. (default = TRUE)
<code>silent</code>	If <code>silent = FALSE</code> , a message regarding conversion for a <code>data.frame</code> will be printed. If <code>silent = TRUE</code> , this message will be suppressed. By default, <code>silent = FALSE</code> .

Examples

```
data_frame_1 <- data.frame(a = c("1", "2"), b = c("1", "b"), c = 1:2)  
convert_cols_to_numeric(data = data_frame_1)  
data_table_1 <- data.table::data.table(  
  a = c("1", "2"), b = c("1", "b"), c = 1:2)  
convert_cols_to_numeric(data = data_table_1)
```

`convert_to_excel_formula`*Convert character to Excel formula*

Description

Convert elements of a character vector to Excel formulas to preserve the character (string) format when opened in an Excel file.

Usage

```
convert_to_excel_formula(vector = NULL)
```

Arguments

`vector` a character vector

Value

the output will be a character vector formatted as an Excel formula. For example, if an element in the input vector was ".500", this element will be converted to "=.500", which will show up as ".500" in Excel, rather than as "0.5"

Examples

```
## Not run:
# compare the two csv files below
# example 1
dt <- data.table::data.table(a = ".500")
data.table::fwrite(dt, "example1.csv") # the csv will show "0.5"
# example 2
dt <- data.table::data.table(a = convert_to_excel_formula(".500"))
data.table::fwrite(dt, "example2.csv") # the csv will show ".500"

## End(Not run)
```

`correlation_matrix`*correlation matrix*

Description

Creates a correlation matrix

Usage

```
correlation_matrix(
  data = NULL,
  var_names = NULL,
  row_var_names = NULL,
  col_var_names = NULL,
  round_r = 2,
  round_p = 3,
  output_type = "r"
)
```

Arguments

<code>data</code>	a data object (a data frame or a data.table)
<code>var_names</code>	names of the variables for which to calculate all pairwise correlations
<code>row_var_names</code>	names of the variables that will go on the rows of the correlation matrix
<code>col_var_names</code>	names of the variables that will go on the columns of the correlation matrix
<code>round_r</code>	number of decimal places to which to round correlation coefficients (default = 2)
<code>round_p</code>	number of decimal places to which to round p-values (default = 3)
<code>output_type</code>	which value should be filled in cells of the correlation matrix? If <code>output_type = "r"</code> , correlation coefficients; if <code>output_type = "p"</code> , p-values; if <code>output_type = "rp"</code> , correlation coefficients with significance symbols based on p-values; if <code>output_type = "n"</code> , sizes of the samples used to calculate the correlation coefficients

Value

the output will be a correlation matrix in a data.table format

Examples

```
correlation_matrix(data = mtcars, var_names = c("mpg", "cyl", "wt"))
correlation_matrix(data = mtcars,
  row_var_names = c("mpg", "cyl", "hp"), col_var_names = c("wt", "am"))
```

<code>cum_percent_plot</code>	<i>Cumulative percentage plot</i>
-------------------------------	-----------------------------------

Description

Plots or tabulates cumulative percentages associated with elements in a vector

Usage

```
cum_percent_plot(vector, output_type = "plot")
```

Arguments

vector	a numeric vector
output_type	if output_type = "plot", return a cumulative percentage plot; if output_type = "dt", return a data.table with cumulative percentages. By default, output_type = "plot"

Examples

```
cum_percent_plot(c(1:100, NA, NA))
cum_percent_plot(mtcars$mpg)
cum_percent_plot(vector= mtcars$mpg, output_type = "dt")
```

desc_stats	<i>Descriptive statistics</i>
------------	-------------------------------

Description

Returns descriptive statistics for a numeric vector.

Usage

```
desc_stats(
  vector = NULL,
  output_type = "vector",
  sigfigs = 3,
  ci = TRUE,
  pi = TRUE,
  notify_na_count = NULL,
  print_dt = TRUE
)
```

Arguments

vector	a numeric vector
output_type	if output_type = "vector", return a vector of descriptive statistics; if output_type = "dt", return a data.table of descriptive statistics (default = "vector")
sigfigs	number of significant digits to round to (default = 3)
ci	logical. Should 95% CI be included in the descriptive stats? (default = TRUE)
pi	logical. Should 95% PI be included in the descriptive stats? (default = TRUE)
notify_na_count	if TRUE, notify how many observations were removed due to missing values. By default, NA count will be printed only if there are any NA values.
print_dt	if TRUE, print the descriptive stats data.table

Value

if `output_type = "vector"`, the output will be a named numeric vector of descriptive statistics; if `output_type = "dt"`, the output will be data.table of descriptive statistics.

Examples

```
desc_stats(1:100)
desc_stats(1:100, ci = TRUE, pi = TRUE, sigfigs = 2)
desc_stats(c(1:100, NA))
desc_stats(vector = c(1:100, NA), output_type = "dt")
```

desc_stats_by_group *Descriptive statistics by group*

Description

Returns descriptive statistics by group

Usage

```
desc_stats_by_group(
  data = NULL,
  var_for_stats = NULL,
  grouping_vars = NULL,
  stats = "all",
  sigfigs = NULL,
  cols_to_round = NULL
)
```

Arguments

<code>data</code>	a data object (a data frame or a data.table)
<code>var_for_stats</code>	name of the variable for which descriptive statistics will be calculated
<code>grouping_vars</code>	name(s) of grouping variables
<code>stats</code>	statistics to calculate. If <code>stats = "basic"</code> , group size, mean, standard deviation, median, minimum, and maximum will be calculated. If <code>stats = "all"</code> , in addition to the aforementioned statistics, standard error, 95% confidence and prediction intervals, skewness, and kurtosis will also be calculated. The <code>stats</code> argument can also be a character vector with types of statistics to calculate. For example, entering <code>stats = c("mean", "median")</code> will calculate mean and median. By default, <code>stats = "all"</code>
<code>sigfigs</code>	number of significant digits to round to
<code>cols_to_round</code>	names of columns whose values will be rounded

Value

the output will be a data.table showing descriptive statistics of the variable for each of the groups formed by the grouping variables.

Examples

```
desc_stats_by_group(data = mtcars, var_for_stats = "mpg",
grouping_vars = c("vs", "am"))
desc_stats_by_group(data = mtcars, var_for_stats = "mpg",
grouping_vars = c("vs", "am"), sigfigs = 3)
desc_stats_by_group(data = mtcars, var_for_stats = "mpg",
grouping_vars = c("vs", "am"), stats = "basic", sigfigs = 2)
desc_stats_by_group(data = mtcars, var_for_stats = "mpg",
grouping_vars = c("vs", "am"), stats = "basic", sigfigs = 2,
cols_to_round = "all")
desc_stats_by_group(data = mtcars, var_for_stats = "mpg",
grouping_vars = c("vs", "am"), stats = c("mean", "median"), sigfigs = 2,
cols_to_round = "all")
```

detach_user_installed_pkgs

Detach all user-installed packages

Description

Detach all user-installed packages

Usage

```
detach_user_installed_pkgs(exceptions = NULL, force = FALSE, keep_kim = TRUE)
```

Arguments

exceptions	a character vector of names of packages to keep attached
force	logical. Should a package be detached even though other attached packages depend on it? By default, force = FALSE
keep_kim	logical. If keep_kim = FALSE, Package 'kim' will be detached along with all other user-installed packages. If keep_kim = TRUE, Package 'kim' will not be detached. By default, keep_kim = FALSE

Examples

```
## Not run:
detach_user_installed_pkgs()

## End(Not run)
```

duplicated_values *Duplicated values in a vector*

Description

Return all duplicated values in a vector. This function is a copy of the earlier function, `find_duplicates`, in Package 'kim'

Usage

```
duplicated_values(vector = NULL, na.rm = TRUE, sigfigs = 2, output = "summary")
```

Arguments

vector	a vector whose elements will be checked for duplicates
na.rm	logical. If <code>na.rm = TRUE</code> , NA values in the vector will be removed before searching for duplicates. If <code>na.rm = FALSE</code> , NA values will be included in the search as potentially duplicated values. By default, <code>na.rm = TRUE</code> .
sigfigs	number of significant digits to round to in the percent column of the summary (default = 2)
output	type of output. If <code>output = "summary"</code> , the function's output will be a <code>data.table</code> summarizing duplicated values and their counts. If <code>output = "duplicated_values"</code> , the function's output will be a vector of duplicated values. If <code>output = "non_duplicated_values"</code> , the function's output will be a vector of non-duplicated values (default = "summary")

Value

the output will be a `data.table` object (summary), a vector of duplicated values, or a vector non-duplicated values.

Examples

```
duplicated_values(mtcars$cyl)
duplicated_values(mtcars$cyl, output = "duplicated_values")
duplicated_values(vector = c(mtcars$cyl, 11:20, NA, NA))
duplicated_values(vector = c(mtcars$cyl, 11:20, NA, NA), na.rm = FALSE)
duplicated_values(vector = c(mtcars$cyl, 11:20, NA, NA),
na.rm = FALSE, sigfigs = 4, output = "duplicated_values")
```

```
exit_from_parent_function
      Exit from a Parent Function
```

Description

Exit from a Parent Function

Usage

```
exit_from_parent_function(
  n = 1,
  silent = FALSE,
  message = "Exiting from a parent function"
)
```

Arguments

n	the number of generations to go back (default = 1)
silent	logical. If silent = TRUE, a message will be printed.
message	message to print

Examples

```
fn1 <- function() {
  print(1)
  print(2)
}
fn1()
fn2 <- function() {
  print(1)
  exit_from_parent_function()
  print(2)
}
fn2()
```

```
find_duplicates      Find duplicated values in a vector
```

Description

Find duplicated values in a vector

Usage

```
find_duplicates(vector = NULL, na.rm = TRUE, sigfigs = 2, output = "summary")
```

Arguments

vector	a vector whose elements will be checked for duplicates
na.rm	logical. If na.rm = TRUE, NA values in the vector will be removed before searching for duplicates. If na.rm = FALSE, NA values will be included in the search as potentially duplicated values. By default, na.rm = TRUE.
sigfigs	number of significant digits to round to in the percent column of the summary (default = 2)
output	type of output. If output = "summary", the function's output will be a data.table summarizing duplicated values and their counts. If output = "duplicated_values", the function's output will be a vector of duplicated values. If output = "non_duplicated_values", the function's output will be a vector of non-duplicated values (default = "summary")

Value

the output will be a data.table object (summary), a vector of duplicated values, or a vector non-duplicated values.

Examples

```
find_duplicates(mtcars$cyl)
find_duplicates(mtcars$cyl, output = "duplicated_values")
find_duplicates(vector = c(mtcars$cyl, 11:20, NA, NA))
find_duplicates(vector = c(mtcars$cyl, 11:20, NA, NA), na.rm = FALSE)
find_duplicates(vector = c(mtcars$cyl, 11:20, NA, NA),
na.rm = FALSE, sigfigs = 4, output = "duplicated_values")
```

fisher_z_transform *Fisher's Z transformation*

Description

Perform Fisher's r-to-Z transformation for given correlation coefficient(s).

Usage

```
fisher_z_transform(r = NULL)
```

Arguments

r	a (vector of) correlation coefficient(s)
---	--

Value

the output will be a vector of Z values which were transformed from the given r values.

Examples

```
fisher_z_transform(0.99)
fisher_z_transform(r = seq(0.1, 0.5, 0.1))
```

```
floodlight_2_by_continuous
      Floodlight 2 by Continuous
```

Description

Conduct a floodlight analysis for 2 x Continuous design.

Usage

```
floodlight_2_by_continuous(
  data = NULL,
  iv_name = NULL,
  dv_name = NULL,
  mod_name = NULL,
  covariate_name = NULL,
  interaction_p_include = TRUE,
  iv_level_order = NULL,
  output = "reg_lines_plot",
  jitter_x_percent = 0,
  jitter_y_percent = 0,
  dot_alpha = 0.5,
  dot_size = 4,
  interaction_p_value_font_size = 6,
  jn_point_font_size = 6,
  jn_point_label_hjust = NULL,
  plot_margin = ggplot2::unit(c(60, 7, 7, 7), "pt"),
  legend_position = "right",
  reg_line_types = c("solid", "dashed"),
  jn_line_types = c("solid", "solid"),
  sig_region_color = "green",
  sig_region_alpha = 0.08,
  nonsig_region_color = "gray",
  nonsig_region_alpha = 0.08,
  x_axis_title = NULL,
  y_axis_title = NULL,
  legend_title = NULL,
  round_decimals_int_p_value = 3,
  line_of_fit_size = 1,
  round_jn_point_labels = 2
)
```

Arguments

<code>data</code>	a data object (a data frame or a data.table)
<code>iv_name</code>	name of the binary independent variable
<code>dv_name</code>	name of the dependent variable
<code>mod_name</code>	name of the continuous moderator variable
<code>covariate_name</code>	name of the variables to control for
<code>interaction_p_include</code>	logical. Should the plot include a p-value for the interaction term?
<code>iv_level_order</code>	order of levels in the independent variable for legend. By default, it will be set as levels of the independent variable ordered using R's base function <code>sort</code> .
<code>output</code>	type of output (default = "reg_lines_plot"). Possible inputs: "interactions_pkg_results", "simple_effects_plot", "jn_points", "reg_lines_plot"
<code>jitter_x_percent</code>	horizontally jitter dots by a percentage of the range of x values
<code>jitter_y_percent</code>	vertically jitter dots by a percentage of the range of y values
<code>dot_alpha</code>	opacity of the dots (0 = completely transparent, 1 = completely opaque). By default, <code>dot_alpha = 0.5</code>
<code>dot_size</code>	size of the dots (default = 4)
<code>interaction_p_value_font_size</code>	font size for the interaction p value (default = 6)
<code>jn_point_font_size</code>	font size for Johnson-Neyman point labels (default = 6)
<code>jn_point_label_hjust</code>	a vector of <code>hjust</code> values for Johnson-Neyman point labels. By default, the <code>hjust</code> value will be 0.5 for all the points.
<code>plot_margin</code>	margin for the plot By default <code>plot_margin = ggplot2::unit(c(60, 7, 7, 7), "pt")</code>
<code>legend_position</code>	position of the legend (default = "right"). If <code>legend_position = "none"</code> , the legend will be removed.
<code>reg_line_types</code>	types of the regression lines for the two levels of the independent variable. By default, <code>reg_line_types = c("solid", "dashed")</code>
<code>jn_line_types</code>	types of the lines for Johnson-Neyman points. By default, <code>jn_line_types = c("solid", "solid")</code>
<code>sig_region_color</code>	color of the significant region, i.e., range(s) of the moderator variable for which simple effect of the independent variable on the dependent variable is statistically significant.
<code>sig_region_alpha</code>	opacity for <code>sig_region_color</code> . (0 = completely transparent, 1 = completely opaque). By default, <code>sig_region_alpha = 0.08</code>

nonsig_region_color	color of the non-significant region, i.e., range(s) of the moderator variable for which simple effect of the independent variable on the dependent variable is not statistically significant.
nonsig_region_alpha	opacity for nonsig_region_color. (0 = completely transparent, 1 = completely opaque). By default, nonsig_region_alpha = 0.08
x_axis_title	title of the x axis. By default, it will be set as input for mod_name. If x_axis_title = FALSE, it will be removed.
y_axis_title	title of the y axis. By default, it will be set as input for dv_name. If y_axis_title = FALSE, it will be removed.
legend_title	title of the legend. By default, it will be set as input for iv_name. If legend_title = FALSE, it will be removed.
round_decimals_int_p_value	To how many digits after the decimal point should the p value for the interaction term be rounded? (default = 3)
line_of_fit_size	thickness of the lines of fit (default = 1)
round_jn_point_labels	To how many digits after the decimal point should the jn point labels be rounded? (default = 2)

Details

The following package(s) must be installed prior to running this function: Package 'interactions' v1.1.1 (or possibly a higher version) by Jacob A. Long (2020), <https://cran.r-project.org/package=interactions> See the following references: Spiller et al. (2013) doi:10.1509/jmr.12.0420. Kim (2021) doi: [10.5281/zenodo.4445388](https://doi.org/10.5281/zenodo.4445388)

Examples

```
floodlight_2_by_continuous(
  data = mtcars,
  iv_name = "am",
  dv_name = "mpg",
  mod_name = "qsec")
# add covariates
floodlight_2_by_continuous(
  data = mtcars,
  iv_name = "am",
  dv_name = "mpg",
  mod_name = "qsec",
  covariate_name = c("cyl", "hp"))
```

`forest_plot`*Forest plot*

Description

Create a forest plot using outputs from 'metafor' package

Usage

```
forest_plot(  
  estimates = NULL,  
  estimate_ci_ll = NULL,  
  estimate_ci_ul = NULL,  
  point_size_range = c(2, 10),  
  error_bar_size = 1,  
  error_bar_tip_height = 0.3,  
  weights = NULL,  
  diamond_x = NULL,  
  diamond_ci_ll = NULL,  
  diamond_ci_ul = NULL,  
  diamond_height = 1.2,  
  diamond_gap_height = 0.3,  
  diamond_1_tip_at_top_y = -0.5,  
  diamond_colors = "black",  
  study_labels = NULL,  
  diamond_labels = NULL,  
  diamond_label_size = 6,  
  diamond_label_hjust = 0,  
  diamond_label_fontface = "bold",  
  diamond_estimate_label_hjust = 0,  
  diamond_estimate_label_size = 6,  
  diamond_estimate_label_fontface = "bold",  
  round_estimates = 2,  
  x_axis_title = "Observed Outcome",  
  vline_size = 1,  
  vline_intercept = 0,  
  vline_type = "dotted",  
  study_label_hjust = 0,  
  study_label_begin_x = NULL,  
  study_label_begin_x_perc = 60,  
  study_label_size = 6,  
  study_label_fontface = "plain",  
  estimate_label_begin_x = NULL,  
  estimate_label_begin_x_perc = 25,  
  estimate_label_hjust = 0,  
  estimate_label_size = 6,  
  estimate_label_fontface = "plain",
```

```

    x_axis_tick_marks = NULL,
    x_axis_tick_mark_label_size = 6,
    legend_position = "none",
    plot_margin = NULL
)

```

Arguments

```

estimates          default = NULL
estimate_ci_ll    default = NULL
estimate_ci_ul    default = NULL
point_size_range
                  default = c(2, 10)
error_bar_size    default = 1
error_bar_tip_height
                  default = 0.3
weights           default = NULL
diamond_x         default = NULL
diamond_ci_ll     default = NULL
diamond_ci_ul     default = NULL
diamond_height    default = 1.2
diamond_gap_height
                  default = 0.3
diamond_l_tip_at_top_y
                  default = -0.5
diamond_colors    default = "black"
study_labels      default = NULL
diamond_labels    default = NULL
diamond_label_size
                  default = 6
diamond_label_hjust
                  default = 0
diamond_label_fontface
                  default = "bold"
diamond_estimate_label_hjust
                  default = 0
diamond_estimate_label_size
                  default = 6
diamond_estimate_label_fontface
                  default = "bold"
round_estimates   default = 2
x_axis_title      default = "Observed Outcome"
vline_size        default = 1

```

```
vline_intercept      default = 0
vline_type           default = "dotted"
study_label_hjust    default = 0
study_label_begin_x  default = NULL
study_label_begin_x_perc default = 60
study_label_size      default = 6
study_label_fontface default = "plain"
estimate_label_begin_x default = NULL
estimate_label_begin_x_perc default = 25
estimate_label_hjust  default = 0
estimate_label_size   default = 6
estimate_label_fontface default = "plain"
x_axis_tick_marks     default = NULL
x_axis_tick_mark_label_size default = 6
legend_position       default = "none"
plot_margin           default = NULL
```

Examples

```
forest_plot(
  estimates = c(2, 3, 4),
  estimate_ci_ll = c(1, 2, 3),
  estimate_ci_ul = c(3, 4, 6),
  weights = 1:3,
  diamond_x = 2,
  diamond_labels = "RE",
  diamond_ci_ll = 1.8,
  diamond_ci_ul = 2.2,
  estimate_label_begin_x_perc = 40,
  x_axis_tick_marks = seq(-2, 6, 2))
```

ggsave_quick	<i>ggsave quick</i>
--------------	---------------------

Description

quickly save the current plot with a timestamp

Usage

```
ggsave_quick(  
  name = NULL,  
  file_name_extension = "png",  
  timestamp = NULL,  
  width = 16,  
  height = 9  
)
```

Arguments

name	a character string of the png file name. By default, if no input is given (name = NULL), the file name will begin with "ggplot". If the desired output file name is "myplot.png", enter name = "myplot", timestamp = FALSE
file_name_extension	file name extension (default = "png"). If file_name_extension = "svg", Package svglite needs to be installed.
timestamp	if timestamp = TRUE, a timestamp of the current time will be appended to the file name. The timestamp will be in the format, jan_01_2021_1300_10_000001, where "jan_01_2021" would indicate January 01, 2021; 1300 would indicate 13:00 (i.e., 1 PM); and 10_000001 would indicate 10.000001 seconds after the hour. By default, timestamp will be set as TRUE, if no input is given for the name argument, and as FALSE, if an input is given for the name argument.
width	width of the plot to be saved. This argument will be directly entered as the width argument for the ggsave function within ggplot2 package (default = 16)
height	height of the plot to be saved. This argument will be directly entered as the height argument for the ggsave function within ggplot2 package (default = 9)

Value

the output will be a .png image file in the working directory.

Examples

```
## Not run:  
kim:histogram(rep(1:30, 3))  
ggsave_quick()  
  
## End(Not run)
```

 histogram

Histogram

Description

Create a histogram

Usage

```

histogram(
  vector = NULL,
  number_of_bins = 30,
  x_tick_marks = NULL,
  y_tick_marks = NULL,
  fill_color = "cyan4",
  border_color = "black",
  y_axis_title_vjust = 0.85,
  x_axis_title = NULL,
  y_axis_title = NULL,
  cap_axis_lines = FALSE,
  notify_na_count = NULL
)

```

Arguments

<code>vector</code>	a numeric vector
<code>number_of_bins</code>	number of bins for the histogram (default = 30)
<code>x_tick_marks</code>	a vector of values at which to place tick marks on the x axis (e.g., setting <code>x_tick_marks = seq(0, 10, 5)</code> will put tick marks at 0, 5, and 10.)
<code>y_tick_marks</code>	a vector of values at which to place tick marks on the y axis (e.g., setting <code>y_tick_marks = seq(0, 10, 5)</code> will put tick marks at 0, 5, and 10.)
<code>fill_color</code>	color for inside of the bins (default = "cyan4")
<code>border_color</code>	color for borders of the bins (default = "black")
<code>y_axis_title_vjust</code>	position of the y axis title (default = 0.85).
<code>x_axis_title</code>	title for x axis (default = "Value")
<code>y_axis_title</code>	title for y axis (default = "Count")
<code>cap_axis_lines</code>	logical. Should the axis lines be capped at the outer tick marks? (default = FALSE)
<code>notify_na_count</code>	if TRUE, notify how many observations were removed due to missing values. By default, NA count will be printed only if there are any NA values.

Value

the output will be a histogram, a ggplot object.

Examples

```
histogram(1:100)
histogram(c(1:100, NA))
histogram(vector = mtcars[["mpg"]])
histogram(vector = mtcars[["mpg"]], x_tick_marks = seq(10, 36, 2))
histogram(vector = mtcars[["mpg"]], x_tick_marks = seq(10, 36, 2),
y_tick_marks = seq(0, 8, 2), y_axis_title_vjust = 0.5,
y_axis_title = "Freq", x_axis_title = "Values of mpg")
```

histogram_by_group *Histogram by group*

Description

Creates histograms by group to compare distributions.

Usage

```
histogram_by_group(
  data = NULL,
  iv_name = NULL,
  dv_name = NULL,
  order_of_groups_top_to_bot = NULL,
  number_of_bins = 40,
  space_between_histograms = 0.15,
  draw_baseline = FALSE,
  xlab = NULL,
  ylab = NULL,
  x_limits = NULL,
  x_breaks = NULL,
  x_labels = NULL,
  sigfigs = 3
)
```

Arguments

data	a data object (a data frame or a data.table)
iv_name	name of the independent variable
dv_name	name of the dependent variable

<code>order_of_groups_top_to_bot</code>	a character vector indicating the desired presentation order of levels in the independent variable (from the top to bottom). Omitting a group in this argument will remove the group in the set of histograms.
<code>number_of_bins</code>	number of bins for the histograms (default = 40)
<code>space_between_histograms</code>	space between histograms (minimum = 0, maximum = 1, default = 0.15)
<code>draw_baseline</code>	logical. Should the baseline and the trailing lines to either side of the histogram be drawn? (default = FALSE)
<code>xlab</code>	title of the x-axis for the histogram by group. If <code>xlab = FALSE</code> , the title will be removed. By default (i.e., if no input is given), <code>dv_name</code> will be used as the title.
<code>ylab</code>	title of the y-axis for the histogram by group. If <code>ylab = FALSE</code> , the title will be removed. By default (i.e., if no input is given), <code>iv_name</code> will be used as the title.
<code>x_limits</code>	a numeric vector with values of the endpoints of the x axis.
<code>x_breaks</code>	a numeric vector indicating the points at which to place tick marks on the x axis.
<code>x_labels</code>	a vector containing labels for the place tick marks on the x axis.
<code>sigfigs</code>	number of significant digits to round to (default = 3)

Details

The following package(s) must be installed prior to running this function: Package 'ggridges' v0.5.3 (or possibly a higher version) by Claus O. Wilke (2021), <https://cran.r-project.org/package=ggridges>

Value

the output will be a set of vertically arranged histograms (a ggplot object), i.e., one histogram for each level of the independent variable.

Examples

```

histogram_by_group(data = mtcars, iv_name = "cyl", dv_name = "mpg")
histogram_by_group(
  data = mtcars, iv_name = "cyl", dv_name = "mpg",
  order_of_groups_top_to_bot = c("8", "4"), number_of_bins = 10,
  space_between_histograms = 0.5
)
histogram_by_group(
  data = iris, iv_name = "Species", dv_name = "Sepal.Length", x_breaks = 4:8,
  x_limits = c(4, 8))

```

histogram_w_outlier_bins

Histogram with outlier bins

Description

Create a histogram with outlier bins

Usage

```

histogram_w_outlier_bins(
  vector = NULL,
  bin_cutoffs = NULL,
  outlier_bin_left = TRUE,
  outlier_bin_right = TRUE,
  x_tick_marks = NULL,
  x_tick_mark_labels = NULL,
  y_tick_marks = NULL,
  outlier_bin_fill_color = "coral",
  non_outlier_bin_fill_color = "cyan4",
  border_color = "black",
  y_axis_title_vjust = 0.85,
  x_axis_title = NULL,
  y_axis_title = NULL,
  notify_na_count = NULL,
  plot_proportion = TRUE,
  plot_frequency = FALSE,
  mean = TRUE,
  ci = TRUE,
  median = TRUE,
  median_position = 15,
  error_bar_size = 3
)

```

Arguments

vector	a numeric vector
bin_cutoffs	cutoff points for bins
outlier_bin_left	logical. Should the leftmost bin treated as an outlier bin? (default = TRUE)
outlier_bin_right	logical. Should the rightmost bin treated as an outlier bin? (default = TRUE)
x_tick_marks	a vector of values at which to place tick marks on the x axis. Note that the first bar spans from 0.5 to 1.5, second bar from 1.5 to 2.5, ... nth bar from n - 0.5 to n + 0.5. See the example. By default, tick marks will be placed at every cutoff point for bins

<code>x_tick_mark_labels</code>	a character vector to label tick marks. By default, the vector of cutoff points for bins will also be used as labels.
<code>y_tick_marks</code>	a vector of values at which to place tick marks on the y axis (e.g., setting <code>y_tick_marks = seq(0, 10, 5)</code> will put tick marks at 0, 5, and 10.)
<code>outlier_bin_fill_color</code>	color to fill inside of the outlier bins (default = "coral")
<code>non_outlier_bin_fill_color</code>	color to fill inside of the non-outlier bins (default = "cyan4")
<code>border_color</code>	color for borders of the bins (default = "black")
<code>y_axis_title_vjust</code>	position of the y axis title (default = 0.85).
<code>x_axis_title</code>	title for x axis (default = "Value"). If <code>x_axis_title = FALSE</code> , x axis title will be removed from the plot.
<code>y_axis_title</code>	title for y axis. By default, it will be either "Proportion" or "Count".
<code>notify_na_count</code>	if TRUE, notify how many observations were removed due to missing values. By default, NA count will be printed only if there are any NA values.
<code>plot_proportion</code>	logical. Should proportions be plotted, as opposed to frequencies? (default = TRUE)
<code>plot_frequency</code>	logical. Should frequencies be plotted, as opposed to proportions? (default = FALSE). If <code>plot_frequency = TRUE</code> , <code>plot_proportion</code> will switch to be FALSE.
<code>mean</code>	logical. Should mean marked on the histogram? (default = TRUE)
<code>ci</code>	logical. Should 95% confidence interval marked on the histogram? (default = TRUE)
<code>median</code>	logical. Should median marked on the histogram? (default = TRUE)
<code>median_position</code>	position of the median label as a percentage of height of the tallest bin (default = 15)
<code>error_bar_size</code>	size of the error bars (default = 3)

Value

a ggplot object

Examples

```

histogram_w_outlier_bins(vector = 1:100, bin_cutoffs = seq(0, 100, 10))
histogram_w_outlier_bins(vector = 0:89, bin_cutoffs = seq(0, 90, 10),
  x_tick_marks = seq(0.5, 9.5, 3), x_tick_mark_labels = seq(0, 90, 30))
histogram_w_outlier_bins(vector = 1:10, bin_cutoffs = seq(0, 10, 2.5))
histogram_w_outlier_bins(vector = 1:5, bin_cutoffs = seq(0, 10, 2.5))
histogram_w_outlier_bins(vector = 1:15, bin_cutoffs = c(5.52, 10.5))

```

identical_all	<i>Check whether all inputs are identical</i>
---------------	---

Description

Check whether all inputs are identical

Usage

```
identical_all(...)
```

Arguments

... two or more R objects. If a vector or list is entered as an input, the function will test whether the vector's or list's elements are identical.

Value

the output will be TRUE if all inputs are identical or FALSE if not

Examples

```
identical_all(1:3, 1:3) # should return TRUE
identical_all(1:3, 1:3, 1:3, 1:3, 1:3) # should return TRUE
identical_all(1:3, 1:3, 1:3, 1:3, 1:3, 1:4) # should return FALSE
identical_all(1:10) # should return FALSE
identical_all(rep(1, 100)) # should return TRUE
identical_all(list(1, 1, 1)) # should return TRUE
identical_all(TRUE, FALSE) # should return FALSE
identical_all(FALSE, TRUE) # should return FALSE
```

id_across_datasets	<i>ID across datasets</i>
--------------------	---------------------------

Description

Create an ID column in each of the data sets. The ID values will span across the data sets.

Usage

```
id_across_datasets(  
  dt_list = NULL,  
  id_col_name = "id",  
  id_col_position = "first",  
  silent = FALSE  
)
```

Arguments

<code>dt_list</code>	a list of <code>data.table</code> objects
<code>id_col_name</code>	name of the column that will contain ID values. By default, <code>id_col_name = "id"</code> .
<code>id_col_position</code>	position of the newly created ID column. If <code>id_col_position = "first"</code> , the new ID column will be placed as the first column in respective data sets. If <code>id_col_position = "last"</code> , the new ID column will be placed as the last column in respective data sets.
<code>silent</code>	If <code>silent = TRUE</code> , a summary of starting and ending ID values in each data set will not be printed. If <code>silent = FALSE</code> , a summary of starting and ending ID values in each data set will be printed. (default = <code>FALSE</code>)

Value

the output will be a list of `data.table` objects.

Examples

```
# running the examples below requires importing the data.table package.
prep(data.table)
id_across_datasets(
  dt_list = list(setDT(copy(mtcars)), setDT(copy(iris))))
id_across_datasets(
  dt_list = list(setDT(copy(mtcars)), setDT(copy(iris)), setDT(copy(women))),
  id_col_name = "newly_created_id_col",
  id_col_position = "last")
```

```
install_all_dependencies
```

Install all dependencies for all functions

Description

Install all dependencies for all functions in Package 'kim'.

Usage

```
install_all_dependencies()
```

Value

there will be no output from this function. Rather, dependencies of all functions in Package 'kim' will be installed.

Examples

```
## Not run:  
install_all_dependencies()  
  
## End(Not run)
```

kurtosis	<i>Kurtosis</i>
----------	-----------------

Description

Calculate kurtosis of the sample using a formula for either the (1) biased estimator or (2) an unbiased estimator of the population kurtosis. Formulas were taken from DeCarlo (1997), doi:10.1037/1082-989X.2.3.292

Usage

```
kurtosis(vector = NULL, unbiased = TRUE)
```

Arguments

vector	a numeric vector
unbiased	logical. If unbiased = TRUE, the unbiased estimate of the population kurtosis will be calculated. If unbiased = FALSE, the biased estimate of the population kurtosis will be calculated. By default, unbiase = TRUE.

Value

a numeric value, i.e., kurtosis of the given vector

Examples

```
# calculate the unbiased estimator (e.g., kurtosis value that  
# Excel 2016 will produce)  
kim::kurtosis(c(1, 2, 3, 4, 5, 10))  
# calculate the biased estimator (e.g., kurtosis value that  
# R Package 'moments' will produce)  
kim::kurtosis(c(1, 2, 3, 4, 5, 10), unbiased = FALSE)  
# compare with kurtosis from 'moments' package  
moments::kurtosis(c(1, 2, 3, 4, 5, 10))
```

logistic_regression *Logistic regression*

Description

Conduct a logistic regression analysis

Usage

```
logistic_regression(
  data = NULL,
  formula = NULL,
  formula_1 = NULL,
  formula_2 = NULL,
  z_values_keep = FALSE,
  constant_row_clean = TRUE,
  odds_ratio_cols_combine = TRUE,
  round_b_and_se = 3,
  round_z = 3,
  round_p = 3,
  round_odds_ratio = 3,
  round_r_sq = 3,
  round_model_chi_sq = 3,
  pretty_round_p_value = TRUE,
  print_glm_default_summary = FALSE,
  print_summary_dt_list = TRUE,
  print_model_comparison = TRUE,
  output_type = "summary_dt_list"
)
```

Arguments

data	a data object (a data frame or a data.table)
formula	formula for estimating a single logistic regression model
formula_1	formula for estimating logistic regression model 1 of 2
formula_2	formula for estimating logistic regression model 2 of 2
z_values_keep	logical. Should the z values be kept in the table? (default = FALSE)
constant_row_clean	logical. Should the row for the constant be cleared except for b and standard error of b? (default = TRUE)
odds_ratio_cols_combine	logical. Should the odds ratio columns be combined? (default = TRUE)
round_b_and_se	number of decimal places to which to round b and standard error of b (default = 3)
round_z	number of decimal places to which to round z values (default = 3)

round_p	number of decimal places to which to round p-values (default = 3)
round_odds_ratio	number of decimal places to which to round odds ratios (default = 3)
round_r_sq	number of decimal places to which to round R-squared values (default = 3)
round_model_chi_sq	number of decimal places to which to round model chi-squared values (default = 3)
pretty_round_p_value	logical. Should the p-values be rounded in a pretty format (i.e., lower threshold: "<.001"). By default, pretty_round_p_value = TRUE.
print_glm_default_summary	logical. Should the default summary output of the glm objects be printed? (default = FALSE)
print_summary_dt_list	logical. Should the summaries of logistic regressions in a data table format be printed? (default = TRUE)
print_model_comparison	logical. Should the comparison of two logistic regression models be printed? (default = TRUE)
output_type	If output_type = "summary_dt_list" (default), the output of the function will be summaries of the two logistic regressions in a data.table format. If output_type = "glm_object_list", the output of the function will be the two glm objects estimating logistic regression models. If output_type = "glm_default_summary_list", the output of the function will be the R's default summary output for the two glm objects estimating logistic regression models. If output_type = "model_comparison_stats", the output of the function will be statistics from comparison of the two logistic regression models. If output_type = "all", the output of the function will be a list of the aforementioned outputs.

Value

the output will be a summary of logistic regression results, unless set otherwise by the output_type argument to the function.

Examples

```
logistic_regression(data = mtcars, formula = am ~ mpg)
logistic_regression(
  data = mtcars,
  formula_1 = am ~ mpg,
  formula_2 = am ~ mpg + wt)
```

```
logistic_regression_table
```

Logistic regression table

Description

Construct a table of logistic regression results from the given glm object estimating a logistic regression model.

Usage

```
logistic_regression_table(  
  logistic_reg_glm_object = NULL,  
  z_values_keep = FALSE,  
  constant_row_clean = TRUE,  
  odds_ratio_cols_combine = TRUE,  
  round_b_and_se = 3,  
  round_z = 3,  
  round_p = 3,  
  round_odds_ratio = 3,  
  round_r_sq = 3,  
  round_model_chi_sq = 3,  
  pretty_round_p_value = TRUE  
)
```

Arguments

```
logistic_reg_glm_object  
  a glm object estimating a logistic regression model  
z_values_keep  logical. Should the z values be kept in the table? (default = FALSE)  
constant_row_clean  
  logical. Should the row for the constant be cleared except for b and standard  
  error of b? (default = TRUE)  
odds_ratio_cols_combine  
  logical. Should the odds ratio columns be combined? (default = TRUE)  
round_b_and_se  number of decimal places to which to round b and standard error of b (default =  
  3)  
round_z         number of decimal places to which to round z values (default = 3)  
round_p         number of decimal places to which to round p-values (default = 3)  
round_odds_ratio  
  number of decimal places to which to round odds ratios (default = 3)  
round_r_sq     number of decimal places to which to round R-squared values (default = 3)  
round_model_chi_sq  
  number of decimal places to which to round model chi-squared values (default  
  = 3)
```

pretty_round_p_value

logical. Should the p-values be rounded in a pretty format (i.e., lower threshold: "<.001"). By default, pretty_round_p_value = TRUE.

Value

the output will be a summary of logistic regression results.

Examples

```
logistic_regression_table(logistic_reg_glm_object =
  glm(formula = am ~ mpg, family = binomial(), data = mtcars))
logistic_regression_table(logistic_reg_glm_object =
  glm(formula = am ~ mpg, family = binomial(), data = mtcars),
  z_values_keep = TRUE, constant_row_clean = FALSE,
  odds_ratio_cols_combine = FALSE)
```

logistic_reg_w_interaction

Logistic regression with an interaction term

Description

Conduct logistic regression for a model with an interaction between two predictor variables

Usage

```
logistic_reg_w_interaction(
  data = NULL,
  dv_name = NULL,
  iv_1_name = NULL,
  iv_2_name = NULL,
  round_p = 3,
  round_chi_sq = 2,
  dv_ordered_levels = NULL,
  iv_1_ordered_levels = NULL,
  iv_2_ordered_levels = NULL,
  one_line_summary_only = FALSE,
  p_value_interaction_only = FALSE,
  return_dt_w_binary = FALSE
)
```

Arguments

data	a data object (a data frame or a data.table)
dv_name	name of the dependent variable (must be a binary variable)
iv_1_name	name of the first independent variable

`iv_2_name` name of the second independent variable
`round_p` number of decimal places to which to round p-values (default = 3)
`round_chi_sq` number of decimal places to which to round chi square statistics (default = 2)
`dv_ordered_levels` a vector with the ordered levels of the dependent variable, the first and second elements of which will be coded as 0 and 1, respectively, to run logistic regression. E.g., `dv_ordered_levels = c("fail", "pass")`
`iv_1_ordered_levels` (only if the first independent variable is a binary variable) a vector with the ordered levels of the first independent variable, the first and second elements of which will be coded as 0 and 1, respectively, to run logistic regression. E.g., `iv_1_ordered_levels = c("control", "treatment")`
`iv_2_ordered_levels` (only if the second independent variable is a binary variable) a vector with the ordered levels of the first independent variable, the first and second elements of which will be coded as 0 and 1, respectively, to run logistic regression. E.g., `iv_2_ordered_levels = c("male", "female")`
`one_line_summary_only` logical. Should the output simply be a printout of a one-line summary on the interaction term? (default = FALSE)
`p_value_interaction_only` logical. Should the output simply be a p-value of the interaction term in the logistic regression model? (default = FALSE)
`return_dt_w_binary` logical. If `return_dt_w_binary = TRUE`, the function will return a `data.table` with binary variables coded as 0 or 1 (default = FALSE)

Value

the output will be a summary of logistic regression results, unless set otherwise by arguments to the function.

Examples

```
logistic_reg_w_interaction(data = mtcars, dv_name = "vs",
  iv_1_name = "mpg", iv_2_name = "am")
```

`loglinear_analysis` *Loglinear analysis*

Description

Conduct a loglinear analysis

Usage

```
loglinear_analysis(  
  data = NULL,  
  dv_name = NULL,  
  iv_1_name = NULL,  
  iv_2_name = NULL,  
  iv_1_values = NULL,  
  iv_2_values = NULL,  
  output = "all",  
  round_p = 3,  
  round_chi_sq = 2,  
  mosaic_plot = TRUE,  
  report_as_field = FALSE  
)
```

Arguments

data	a data object (a data frame or a data.table)
dv_name	name of the dependent variable
iv_1_name	name of the first independent variable
iv_2_name	name of the second independent variable
iv_1_values	restrict all analyses to observations having these values for the first independent variable
iv_2_values	restrict all analyses to observations having these values for the second independent variable
output	type of the output. If output_type = "all", the function will return a results summary and print a mosaic plot. (default = "all")
round_p	number of decimal places to which to round p-values (default = 3)
round_chi_sq	number of decimal places to which to round chi-squared test statistics (default = 2)
mosaic_plot	If mosaic_plot = TRUE, a mosaic plot will be printed (default = TRUE)
report_as_field	If report_as_field = TRUE, reports summary will follow the format suggested by Andy Field (2012) (ISBN: 978-1-4462-0045-2, p. 851)

Examples

```
loglinear_analysis(data = data.frame(Titanic), "Survived", "Sex", "Age")
```

mann_whitney	<i>Mann-Whitney U Test (Also called Wilcoxon Rank-Sum Test)</i>
--------------	---

Description

A nonparametric equivalent of the independent t-test

Usage

```
mann_whitney(
  data = NULL,
  iv_name = NULL,
  dv_name = NULL,
  iv_level_order = NULL,
  sigfigs = 3
)
```

Arguments

data	a data object (a data frame or a data.table)
iv_name	name of the independent variable (grouping variable)
dv_name	name of the dependent variable (measure variable of interest)
iv_level_order	order of levels in the independent variable. By default, it will be set as levels of the independent variable ordered using R's base function sort.
sigfigs	number of significant digits to round to

Value

the output will be a data.table object with all pairwise Mann-Whitney test results

Examples

```
mann_whitney(data = iris, iv_name = "Species", dv_name = "Sepal.Length")
```

matrix_prep_dt	<i>Prepare a two-column data.table that will be used to fill values in a matrix</i>
----------------	---

Description

Prepare a two-column data.table that will be used to fill values in a matrix

Usage

```
matrix_prep_dt(row_var_names = NULL, col_var_names = NULL)
```


Arguments

`row_var_names` a vector of variable names, each of which will be header of a row in the eventual matrix

`col_var_names` a vector of variable names, each of which will be header of a column in the eventual matrix

Examples

```
matrix_prep_dt(  
  row_var_names = c("mpg", "cyl"),  
  col_var_names = c("hp", "gear")  
)
```

mediation_analysis *Mediation analysis*

Description

Conducts a mediation analysis to estimate an independent variable's indirect effect on dependent variable through a mediator variable. The current version of the package only supports a simple mediation model consisting of one independent variable, one mediator variable, and one dependent variable.

Usage

```
mediation_analysis(  
  data = NULL,  
  iv_name = NULL,  
  mediator_name = NULL,  
  dv_name = NULL,  
  covariates_names = NULL,  
  robust_se = TRUE,  
  iterations = 1000,  
  sigfigs = 3,  
  output_type = "summary_dt",  
  silent = FALSE  
)
```

Arguments

`data` a data object (a data frame or a data.table)

`iv_name` name of the independent variable

`mediator_name` name of the mediator variable

`dv_name` name of the dependent variable

`covariates_names` names of covariates to control for

robust_se	if TRUE, heteroskedasticity-consistent standard errors will be used in quasi-Bayesian simulations. By default, it will be set as FALSE if nonparametric bootstrap is used and as TRUE if quasi-Bayesian approximation is used.
iterations	number of bootstrap samples. The default is set at 1000, but consider increasing the number of samples to 5000, 10000, or an even larger number, if slower handling time is not an issue.
sigfigs	number of significant digits to round to
output_type	if output_type = "summary_dt", return the summary data.table; if output_type = "mediate_output", return the output from the mediate function in the 'mediate' package; if output_type = "indirect_effect_p", return the p value associated with the indirect effect estimated in the mediation model (default = "summary_dt")
silent	if silent = FALSE, mediation analysis summary, estimation method, sample size, and number of simulations will be printed; if silent = TRUE, nothing will be printed. (default = FALSE)

Details

This function requires installing Package 'mediation' v4.5.0 (or possibly a higher version) by Tingley et al. (2019), and uses the source code from a function in the package. <https://cran.r-project.org/package=mediation>

Value

if output_type = "summary_dt", which is the default, the output will be a data.table showing a summary of mediation analysis results; if output_type = "mediate_output", the output will be the output from the mediate function in the 'mediate' package; if output_type = "indirect_effect_p", the output will be the p-value associated with the indirect effect estimated in the mediation model (a numeric vector of length one).

Examples

```
mediation_analysis(
  data = mtcars, iv_name = "cyl",
  mediator_name = "disp", dv_name = "mpg", iterations = 100
)
mediation_analysis(
  data = iris, iv_name = "Sepal.Length",
  mediator_name = "Sepal.Width", dv_name = "Petal.Length",
  iterations = 100
)
```

merge_data_tables	<i>Merge data tables</i>
-------------------	--------------------------

Description

Merge two data.table objects. If there are any duplicated ID values and column names across the two data tables, the cell values in the first data.table will remain intact and the cell values in the second data.table will be discarded for the resulting merged data table.

Usage

```
merge_data_tables(dt1 = NULL, dt2 = NULL, id = NULL, silent = TRUE)
```

Arguments

dt1	the first data.table which will remain intact
dt2	the second data.table which will be joined outside of (around) the first data.table. If there are any duplicated ID values and column names across the two data tables, the cell values in the first data.table will remain intact and the cell values in the second data.table will be discarded for the resulting merged data table.
id	name of the column that will contain the ID values in the two data tables. The name of the ID column must be identical in the two data tables.
silent	If silent = TRUE, no message will be printed regarding how many ID values and column names were duplicated. If silent = FALSE, messages will be printed regarding how many ID values and column names were duplicated. (default = FALSE)

Value

a data.table object, which merges (joins) the second data.table around the first data.table.

Examples

```
data_1 <- data.table::data.table(  
  id_col = c(4, 2, 1, 3),  
  a = 3:6,  
  b = 5:8,  
  c = c("w", "x", "y", "z"))  
data_2 <- data.table::data.table(  
  id_col = c(1, 99, 4),  
  e = 6:8,  
  b = c("p", "q", "r"),  
  d = c(TRUE, FALSE, FALSE))  
merge_data_tables(dt1 = data_1, dt2 = data_2, id = "id_col")  
data_3 <- data.table::data.table(  
  id_col = 99,  
  a = "abc",  
  b = TRUE,
```

```
c = TRUE)
# Note how the value of TRUE gets converted to 1 when merging in Column 'c'
merge_data_tables(data_1, data_3, id = "id_col")
data_4 <- data.table::data.table(
  id_col = c(5, 3),
  a = c("a", NA))
data_5 <- data.table::data.table(
  id_col = 1,
  a = 2)
merge_data_tables(data_4, data_5, id = "id_col")
```

merge_data_table_list *Merge a list of data tables*

Description

Successively merge a list of data.table objects in a recursive fashion. That is, merge the (second data table in the list) around the first data table in the list; then, around this resulting data table, merge the third data table in the list; and so on.

Usage

```
merge_data_table_list(dt_list = NULL, id = NULL, silent = TRUE)
```

Arguments

dt_list	a list of data.table objects
id	name of the column that will contain the ID values in the data tables. The name of the ID column must be identical in the all data tables.
silent	If silent = TRUE, no message will be printed regarding how many ID values and column names were duplicated. If silent = FALSE, messages will be printed regarding how many ID values and column names were duplicated. (default = FALSE)

Details

If there are any duplicated ID values and column names across the data tables, the cell values in the earlier data table will remain intact and the cell values in the later data table will be discarded for the resulting merged data table in each recursion.

Value

a data.table object, which successively merges (joins) a data table around (i.e., outside) the previous data table in the list of data tables.

Examples

```
data_1 <- data.table::data.table(  
  id_col = c(4, 2, 1, 3),  
  a = 3:6,  
  b = 5:8,  
  c = c("w", "x", "y", "z"))  
data_2 <- data.table::data.table(  
  id_col = c(1, 4, 99),  
  d = 6:8,  
  b = c("p", "q", "r"),  
  e = c(TRUE, FALSE, FALSE))  
data_3 <- data.table::data.table(  
  id_col = c(200, 3),  
  f = 11:12,  
  b = c(300, "abc"))  
merge_data_table_list(  
  dt_list = list(data_1, data_2, data_3), id = "id_col")
```

modes_of_objects

Find modes of objects

Description

Find modes of objects

Usage

```
modes_of_objects(...)
```

Arguments

... R objects.

Value

the output will be a data.table listing objects and their mods.

Examples

```
modes_of_objects(  
  TRUE, FALSE, 1L, 1:3, 1.1, c(1.2, 1.3), "abc", 1 + 2i, intToBits(1L))
```

multiple_regression *Multiple regression*

Description

Conduct multiple regression analysis and summarize the results in a data.table.

Usage

```
multiple_regression(
  data = NULL,
  formula = NULL,
  vars_to_mean_center = NULL,
  sigfigs = NULL,
  round_digits_after_decimal = NULL,
  pretty_round_p_value = TRUE,
  return_table_upper_half = FALSE,
  round_r_squared = 3,
  round_f_stat = 2,
  prettify_reg_table_col_names = TRUE,
  silent = FALSE
)
```

Arguments

data	a data object (a data frame or a data.table)
formula	a formula object for the regression equation
vars_to_mean_center	a character vector specifying names of variables that will be mean-centered before the regression model is estimated
sigfigs	number of significant digits to round to
round_digits_after_decimal	round to nth digit after decimal (alternative to sigfigs)
pretty_round_p_value	logical. Should the p-values be rounded in a pretty format (i.e., lower threshold: "<.001"). By default, pretty_round_p_value = TRUE.
return_table_upper_half	logical. Should only the upper part of the table be returned? By default, return_table_upper_half = FALSE.
round_r_squared	number of digits after the decimal both r-squared and adjusted r-squared values should be rounded to (default 3)
round_f_stat	number of digits after the decimal the f statistic of the regression model should be rounded to (default 2)

`prettify_reg_table_col_names` logical. Should the column names of the regression table be made pretty (e.g., change "std_beta" to "Std. Beta")? (Default = TRUE)

`silent` If `silent = FALSE`, a message regarding mean-centered variables will be printed. If `silent = TRUE`, this message will be suppressed. By default, `silent = FALSE`.

Details

To include standardized beta(s) in the regression results table, the following package(s) must be installed prior to running the function: Package 'lm.beta' v1.5-1 (or possibly a higher version) by Stefan Behrendt (2014), <https://cran.r-project.org/package=lm.beta>

Value

the output will be a `data.table` showing multiple regression results.

Examples

```
multiple_regression(data = mtcars, formula = mpg ~ gear * cyl)
multiple_regression(
  data = mtcars, formula = mpg ~ gear * cyl,
  vars_to_mean_center = "gear")
```

noncentrality_parameter

Find noncentrality parameter

Description

Find noncentrality parameter

Usage

```
noncentrality_parameter(t_stat, df, initial_value = 0, ci = 0.95)
```

Arguments

`t_stat` the t-statistic associated with the noncentrality parameters

`df` degrees of freedom associated with the noncentrality parameters

`initial_value` initial value of the noncentrality parameter for optimization (default = 0). Adjust this value if results look strange.

`ci` range of the confidence interval associated with the noncentrality parameters (default = 0.95)

Examples

```
noncentrality_parameter(4.29, 9)
```

```
order_rows_specifically_in_dt
```

Order rows specifically in a data table

Description

Order rows in a data.table in a specific order

Usage

```
order_rows_specifically_in_dt(  
  dt = NULL,  
  col_to_order_by = NULL,  
  specific_order = NULL  
)
```

Arguments

dt	a data.table object
col_to_order_by	a character value indicating the name of the column by which to order the data.table
specific_order	a vector indicating a specific order of the values in the column by which to order the data.table.

Value

the output will be a data.table object whose rows will be ordered as specified.

Examples

```
order_rows_specifically_in_dt(mtcars, "carb", c(3, 2, 1, 4, 8, 6))
```

outlier	<i>Outlier</i>
---------	----------------

Description

Return outliers in a vector

Usage

```
outlier(x = NULL, iqr = 1.5, na.rm = TRUE, type = 7, unique_outliers = FALSE)
```

Arguments

x	a numeric vector
iqr	a nonnegative constant by which interquartile range (IQR) will be multiplied to build a "fence," outside which observations will be considered outliers. For example, if <code>iqr = 1.5</code> , <code>IQR * 1.5</code> will be the "fence" outside which observations will be considered to be outliers. By default, <code>iqr = 1.5</code> .
na.rm	logical. <code>na.rm</code> argument to be passed onto the <code>'quantile'</code> function in the <code>'stats'</code> package. If true, any NA and NaN's are removed from x before the quantiles are computed.
type	type argument to be passed onto the <code>'quantile'</code> function in the <code>'stats'</code> package. An integer between 1 and 9 selecting one of the nine quantile algorithms detailed below to be used. Type <code>'?stats::quantile'</code> for details. By default, <code>type = 7</code>
unique_outliers	logical. If <code>unique_outliers = TRUE</code> , the function will return the unique outlier values. If <code>unique_outliers = FALSE</code> , the function will return all the outlier values in the vector x. By default, <code>unique_outliers = FALSE</code> .

Value

the output will be a numeric vector with outliers removed.

Examples

```
# Example 1
outlier(c(1:10, 100))
# The steps below show how the outlier, 100, was obtained
# v1 is the vector of interest
v1 <- c(1:10, 100)
# quantile
stats::quantile(v1)
# first and third quartiles
q1 <- stats::quantile(v1, 0.25)
q3 <- stats::quantile(v1, 0.75)
# interquartile range
interquartile_range <- unname(q3 - q1)
```

```
# fence, using the default 1.5 as the factor to multiply the IQR
cutoff_low <- unname(q1 - 1.5 * interquartile_range)
cutoff_high <- unname(q3 + 1.5 * interquartile_range)
v1[v1 < cutoff_low | v1 > cutoff_high]
```

overlapping_interval *Find the overlapping interval of two ranges.*

Description

This function should be applied to cases where the two ranges are inclusive of both endpoints. For example, the function can work for a pair of ranges like [0, 1] and [3, 4] but not for pairs like [0, 1) and (3, 5)

Usage

```
overlapping_interval(
  interval_1_begin = NULL,
  interval_1_end = NULL,
  interval_2_begin = NULL,
  interval_2_end = NULL
)
```

Arguments

`interval_1_begin` a number at which the first interval begins (the left **INCLUSIVE** endpoint of interval 1)

`interval_1_end` a number at which the first interval ends (the right **INCLUSIVE** endpoint of interval 1)

`interval_2_begin` a number at which the second interval begins (the left **INCLUSIVE** endpoint of interval 2)

`interval_2_end` a number at which the second interval ends (the right **INCLUSIVE** endpoint of interval 2)

Value

the output will be NULL if there is no overlapping region or a vector of the endpoints of the overlapping interval.

Examples

```
overlapping_interval(1, 3, 2, 4)
overlapping_interval(1, 2.22, 2.22, 3)
```

p0 *Paste0*

Description

A shorthand for the function `paste0` Concatenate vectors after converting to character.

Usage

```
p0(..., collapse = NULL, recycle0 = FALSE)
```

Arguments

...	one or more R objects, to be converted to character vectors. This is the same argument that would be used in the <code>paste0</code> function.
<code>collapse</code>	an optional character string to separate the results. Not <code>NA_character_</code> . This is the same argument that would be used in the <code>paste0</code> function.
<code>recycle0</code>	logical indicating if zero-length character arguments should lead to the zero-length <code>character(0)</code> after the sep-phase (which turns into "" in the collapse-phase, i.e., when <code>collapse</code> is not <code>NULL</code>). This is the same argument that would be used in the <code>paste0</code> function.

Examples

```
paste0("a", "b")
p0("a", "b")
```

parallel_analysis *Parallel analysis*

Description

Conducts a parallel analysis to determine how many factors to retain in a factor analysis.

Usage

```
parallel_analysis(
  data = NULL,
  names_of_vars = NULL,
  iterations = NULL,
  percentile_for_eigenvalue = 95
)
```

Arguments

data a data object (a data frame or a data.table)
names_of_vars names of the variables
iterations number of random data sets. If no input is entered, this value will be set as 30 * number of variables.
percentile_for_eigenvalue percentile used in estimating bias (default = 95).

Details

The following package(s) must be installed prior to running the function: Package 'paran' v1.5.2 (or possibly a higher version) by Alexis Dinno (2018), <https://cran.r-project.org/package=paran>

Examples

```

parallel_analysis(
  data = mtcars, names_of_vars = c("disp", "hp", "drat"))
# parallel_analysis(
# data = mtcars, names_of_vars = c("carb", "vs", "gear", "am"))

```

percentile_rank	<i>Percentile rank</i>
-----------------	------------------------

Description

Calculate percentile rank of each value in a vector

Usage

```
percentile_rank(vector)
```

Arguments

vector a numeric vector

Examples

```

percentile_rank(1:5)
percentile_rank(1:10)
percentile_rank(1:100)

```

pivot_table	<i>Pivot Table</i>
-------------	--------------------

Description

Create a pivot table.

Usage

```
pivot_table(  
  data = NULL,  
  row_names = NULL,  
  col_names = NULL,  
  function_as_character = NULL,  
  sigfigs = 3,  
  output = "dt",  
  remove_col_names = TRUE  
)
```

Arguments

data	a data object (a data frame or a data.table)
row_names	names of variables for constructing rows
col_names	names of variables for constructing columns independent variables
function_as_character	function to perform for each cell in the pivot table
sigfigs	number of significant digits to which to round values in the pivot table (default = 3)
output	type of output. If output = "dt", the function's output will be a pivot table in a data.table format. If output = "subsets", the function's output will be a list of data tables that are subsets representing each cell in the pivot table. By default, output = "dt"
remove_col_names	logical. Should the column names (i.e., v1, v2, ...) be removed in the data table output?

Value

the output will be a contingency table in a data.table format

Examples

```
pivot_table(  
  data = mtcars, col_names = "am", row_names = c("cyl", "vs"),  
  function_as_character = "mean(mpg)")  
pivot_table(  
  data = mtcars, col_names = "am", row_names = c("cyl", "vs"),  
  function_as_character = "mean(mpg)",  
  output = "subsets")
```

```

data = mtcars, col_names = "am", row_names = c("cyl", "vs"),
function_as_character = "sum(mpg < 17)")
pivot_table(
  data = mtcars, col_names = "am", row_names = c("cyl", "vs"),
  function_as_character =
    "round(sum(mpg < 17) / sum(!is.na(mpg)) * 100, 0)")

```

plot_group_means

Plot group means

Description

Creates a plot of sample means and error bars by group.

Usage

```

plot_group_means(
  data = NULL,
  dv_name = NULL,
  iv_name = NULL,
  na.rm = TRUE,
  error_bar = "ci",
  error_bar_range = 0.95,
  lines_connecting_means = TRUE,
  line_size = 1,
  dot_size = 3,
  error_bar_tip_width = 0.13,
  error_bar_thickness = 1,
  position_dodge = 0.13,
  legend_position = "right",
  y_axis_title_vjust = 0.85
)

```

Arguments

data	a data object (a data frame or a data.table)
dv_name	name of the dependent variable
iv_name	name(s) of the independent variable(s). Up to two independent variables can be supplied.
na.rm	logical. If na.rm = TRUE, NA values in independent and dependent variables will be removed before calculating group means.
error_bar	if error_bar = "se"; error bars will be +/-1 standard error, if error_bar = "ci" error bars will be a confidence interval; if error_bar = "pi", error bars will be a prediction interval

error_bar_range	width of the confidence or prediction interval (default = 0.95 for 95 percent confidence or prediction interval). This argument will not apply when error_bar = "se"
lines_connecting_means	logical. Should lines connecting means within each group be drawn? (default = TRUE)
line_size	thickness of the lines connecting group means, (default = 1)
dot_size	size of the dots indicating group means (default = 3)
error_bar_tip_width	graphically, width of the segments at the end of error bars (default = 0.13)
error_bar_thickness	thickness of the error bars (default = 1)
position_dodge	by how much should the group means and error bars be horizontally offset from each other so as not to overlap? (default = 0.13)
legend_position	position of the legend: "none", "top", "right", "bottom", "left", "none" (default = "right")
y_axis_title_vjust	position of the y axis title (default = 0.85). If default is used, y_axis_title_vjust = 0.85, the y axis title will be positioned at 85% of the way up from the bottom of the plot.

Value

by default, the output will be a ggplot object. If output = "table", the output will be a data.table object.

Examples

```
plot_group_means(data = mtcars, dv_name = "mpg", iv_name = c("vs", "am"))
plot_group_means(
  data = mtcars, dv_name = "mpg", iv_name = c("vs", "am"),
  error_bar = "se"
)
plot_group_means(
  data = mtcars, dv_name = "mpg", iv_name = c("vs", "am"),
  error_bar = "pi", error_bar_range = 0.99
)
```

pm *Paste for message*

Description

Combines the base functions paste0 and message

Usage

```
pm(..., collapse = NULL)
```

Arguments

... one or more R objects, to be converted to character vectors. Input(s) to this argument will be passed onto the paste0 function.

collapse an optional character string to separate the results. Not NA_character_. Input(s) to this argument will be passed onto the paste0 function.

Value

there will be no output from this function. Rather, a message will be generated from the arguments.

Examples

```
pm("hello", 123)
pm(c("hello", 123), collapse = ", ")
```

population_variance *Population variance of a vector*

Description

Calculates the population variance, rather than the sample variance, of a vector

Usage

```
population_variance(vector, na.rm = TRUE)
```

Arguments

vector a numeric vector

na.rm if TRUE, NA values will be removed before calculation

Examples

```
population_variance(1:4)
var(1:4)
```

prep	<i>Prepare package(s) for use</i>
------	-----------------------------------

Description

Installs, loads, and attaches package(s). If package(s) are not installed, installs them prior to loading and attaching.

Usage

```
prep(  
  ...,  
  pkg_names_as_object = FALSE,  
  silent_if_successful = FALSE,  
  silent_load_pkgs = NULL  
)
```

Arguments

... names of packages to load and attach, separated by commas, e.g., "ggplot2", data.table. The input can be any number of packages, whose names may or may not be wrapped in quotes.

pkg_names_as_object logical. If pkg_names_as_object = TRUE, the input will be evaluated as one object containing package names. If pkg_names_as_object = FALSE, the input will be considered as literal packages names (default = FALSE).

silent_if_successful logical. If silent_if_successful = TRUE, no message will be printed if preparation of package(s) is successful. If silent_if_successful = FALSE, a message indicating which package(s) were successfully loaded and attached will be printed (default = FALSE).

silent_load_pkgs a character vector indicating names of packages to load silently (i.e., suppress messages that get printed when loading the packaged). By default, silent_load_pkgs = NULL

Value

there will be no output from this function. Rather, packages given as inputs to the function will be installed, loaded, and attached.

Examples

```
prep(data.table)  
prep("data.table", silent_if_successful = TRUE)  
prep("base", utils, ggplot2, "data.table")
```

```
pkgs <- c("ggplot2", "data.table")
prep(pkgs, pkg_names_as_object = TRUE)
prep("data.table", silent_load_pkgs = "data.table")
```

pretty_round_p_value *Pretty round p-value*

Description

Round p-values to the desired number of decimals and remove leading 0s before the decimal.

Usage

```
pretty_round_p_value(
  p_value_vector = NULL,
  round_digits_after_decimal = 3,
  include_p_equals = FALSE
)
```

Arguments

`p_value_vector` one number or a numeric vector
`round_digits_after_decimal`
how many digits after the decimal point should the p-value be rounded to?
`include_p_equals`
if TRUE, output will be a string of mathematical expression including "p", e.g.,
"p < .01" (default = FALSE)

Value

the output will be a character vector with p values, e.g., a vector of strings like "< .001" (or "p < .001").

Examples

```
pretty_round_p_value(0.0495, 3)
pretty_round_p_value(
  p_value_vector = 0.049,
  round_digits_after_decimal = 2, include_p_equals = FALSE)
pretty_round_p_value(c(0.0015, 0.0014, 0.0009), include_p_equals = TRUE)
```

```
pretty_round_r      Pretty round r
```

Description

Round correlation coefficients in APA style (7th Ed.)

Usage

```
pretty_round_r(r = NULL, round_digits_after_decimal = 2)
```

Arguments

```
r                a (vector of) correlation coefficient(s)
round_digits_after_decimal
                  how many digits after the decimal point should the p-value be rounded to? (default = 2)
```

Value

the output will be a character vector of correlation coefficient(s).

Examples

```
pretty_round_r(r = -0.123)
pretty_round_r(c(-0.12345, 0.45678), round_digits_after_decimal = 3)
pretty_round_r(c(-0.12, 0.45), round_digits_after_decimal = 4)
```

```
print_loop_progress  print loop progress
```

Description

Print current progress inside a loop (e.g., for loop or lapply)

Usage

```
print_loop_progress(
  iteration_number = NULL,
  iteration_start = 1,
  iteration_end = NULL,
  text_before = "",
  percent = 1,
  output_method = "cat"
)
```

Arguments

iteration_number	current number of iteration
iteration_start	iteration number at which the loop begins (default = 1)
iteration_end	iteration number at which the loop ends.
text_before	text to add before "Loop Progress..." By default, it is set to be blank, i.e., text_before = ""
percent	if percent = 1, progress level will be printed at every 1 percent progress (default = 1)
output_method	if output_method = "cat", progress level will be printed using the 'cat' function; if output_method = "return", progress level will be returned as the output of the function (default = "cat")

Examples

```

for (i in seq_len(250)) {
  Sys.sleep(0.001)
  print_loop_progress(
    iteration_number = i,
    iteration_end = 250)
}
unlist(lapply(seq_len(7), function (i) {
  Sys.sleep(0.1)
  print_loop_progress(
    iteration_number = i,
    iteration_end = 7)
  return(i)
})))

```

proportion_of_values_in_vector

Proportion of given values in a vector

Description

Proportion of given values in a vector

Usage

```

proportion_of_values_in_vector(
  values = NULL,
  vector = NULL,
  na.exclude = TRUE,
  output_type = "proportion",
  silent = FALSE,

```

```

  conf.level = 0.95,
  correct_yates = TRUE
)

```

Arguments

values	a set of values that will count as successes (hits)
vector	a numeric or character vector containing successes (hits) and failures (misses)
na.exclude	if TRUE, NA values will be removed both from vector and values before calculation (default = TRUE).
output_type	By default, output_type = "proportion". If output_type = "proportion", the function will return the calculated proportion; if output_type = "se", the function will return the standard error of the sample proportion; if output_type = "dt", the function will return the the data table of proportion and confidence intervals.
silent	If silent = TRUE, no message will be printed regarding number of NA values or confidence interval. (default = FALSE)
conf.level	confidence level of the returned confidence interval. Input to this argument will be passed onto the conf.level argument in the prop.test function from the default stats package.
correct_yates	a logical indicating whether Yates' continuity correction should be applied where possible (default = TRUE). Input to this argument will be passed onto the correct argument in the prop.test function from the default stats package.

Examples

```

proportion_of_values_in_vector(
  values = 2:3, vector = c(rep(1:3, each = 10), rep(NA, 10))
)
proportion_of_values_in_vector(
  values = 2:3, vector = c(rep(1:3, each = 10), rep(NA, 10)),
  output_type = "se"
)
proportion_of_values_in_vector(
  values = 2:3, vector = c(rep(1:3, each = 10), rep(NA, 10)),
  conf.level = 0.99
)
proportion_of_values_in_vector(
  values = c(2:3, NA), vector = c(rep(1:3, each = 10), rep(NA, 10)),
  na.exclude = FALSE
)

```

q_stat_test_homo_r *Q statistic for testing homogeneity of correlations*

Description

Calculate the Q statistic to test for homogeneity of correlation coefficients. See p. 235 of the book Hedges & Olkin (1985), *Statistical Methods for Meta-Analysis* (ISBN: 0123363802).

Usage

```
q_stat_test_homo_r(z = NULL, n = NULL)
```

Arguments

z a vector of z values

n a vector of sample sizes which will be used to calculate the weights, which in turn will be used to calculate the weighted z.

Value

the output will be a weighted z value.

Examples

```
q_stat_test_homo_r(1:3, c(100, 200, 300))
q_stat_test_homo_r(z = c(1:3, NA), n = c(100, 200, 300, NA))
```

read_csv *Read a csv file*

Description

Read a csv file

Usage

```
read_csv(name = NULL, head = FALSE, dirname = NULL, ...)
```

Arguments

name a character string of the csv file name without the ".csv" extension. For example, if the csv file to read is "myfile.csv", enter name = "myfile"

head logical. if head = TRUE, prints the first five rows of the data set.

dirname a character string of the directory containing the csv file, e.g., dirname = "c:/Users/Documents"

... optional arguments for the fread function from the data.table package. Any arguments for data.table's fread function can be used, e.g., fill = TRUE, nrow = 100

Value

the output will be a `data.table` object, that is, an output from the `data.table` function, `fread`

Examples

```
## Not run:  
mydata <- read_csv("myfile")  
  
## End(Not run)
```

read_sole_csv	<i>Read the sole csv file in the working directory</i>
---------------	--

Description

Read the sole csv file in the working directory

Usage

```
read_sole_csv(head = FALSE, ...)
```

Arguments

head	logical. if head = TRUE, prints the first five rows of the data set.
...	optional arguments for the <code>fread</code> function from the <code>data.table</code> package. Any arguments for <code>data.table</code> 's <code>fread</code> function can be used, e.g., <code>fill = TRUE</code> , <code>nrows = 100</code>

Value

the output will be a `data.table` object, that is, an output from the `data.table` function, `fread`

Examples

```
mydata <- read_sole_csv()  
mydata <- read_sole_csv(head = TRUE)  
mydata <- read_sole_csv(fill = TRUE, nrows = 5)
```

regex_match	<i>Regular expression matches</i>
-------------	-----------------------------------

Description

Returns elements of a character vector that match the given regular expression

Usage

```
regex_match(regex = NULL, vector = NULL, silent = FALSE, perl = FALSE)
```

Arguments

regex	a regular expression provided, a default theme will be used.
vector	a character vector in which to search for regular expression matches, or a data table whose column names will be searched
silent	logical. If silent = FALSE, a report on regular expression matches will be printed. If silent = TRUE, the report on regular expression matches will not be printed. By default, silent = FALSE
perl	logical. Should Perl-compatible regexps be used?

Examples

```
regex_match("p$", names(mtcars))

colnames_ending_with_p <- regex_match("p$", names(mtcars))
```

rel_pos_of_value_in_vector	<i>Find relative position of a value in a vector</i>
----------------------------	--

Description

Find relative position of a value in a vector that may or may not contain the value

Usage

```
rel_pos_of_value_in_vector(value = NULL, vector = NULL)
```

Arguments

value	a value whose relative position is to be searched in a vector
vector	a numeric vector

Value

a number indicating the relative position of the value in the vector

Examples

```
rel_pos_of_value_in_vector(value = 3, vector = c(2, 4))
rel_pos_of_value_in_vector(value = 3, vector = c(2, 6))
rel_pos_of_value_in_vector(value = 3, vector = 1:3)
```

rel_value_of_pos_in_vector

Find relative value of a position in a vector

Description

Find relative value of a position in a vector

Usage

```
rel_value_of_pos_in_vector(vector = NULL, position = NULL)
```

Arguments

vector	a numeric vector
position	position of a vector

Value

a number indicating the relative value of the position in the vector

Examples

```
rel_value_of_pos_in_vector(vector = c(0, 100), position = 1.5)
rel_value_of_pos_in_vector(vector = 2:4, position = 2)
rel_value_of_pos_in_vector(vector = c(2, 4, 6), position = 2.5)
```

remove_from_vector *Remove from a vector*

Description

Remove certain values from a vector

Usage

```
remove_from_vector(values = NULL, vector = NULL, silent = FALSE)
```

Arguments

values a single value or a vector of values which will be removed from the target vector
vector a character or numeric vector
silent if `silent = FALSE`, a summary of values removed will be printed; if `silent = TRUE`, such summary will not be printed. By default, `silent = FALSE`

Value

the output will be a vector with the given values removed.

Examples

```
remove_from_vector(values = 1, vector = 1:3)  
remove_from_vector(values = NA, vector = c(1:3, NA))  
remove_from_vector(values = c(1, NA), vector = c(1:3, NA))  
remove_from_vector(values = 1:5, vector = 1:10)
```

remove_user_installed_pkgs

Remove all user installed packages

Description

Remove all user installed packages

Usage

```
remove_user_installed_pkgs(  
  exceptions = NULL,  
  type_of_pkg_to_keep = c("base", "recommended"),  
  keep_kim = FALSE  
)
```

Arguments

`exceptions` a character vector of names of packages to keep

`type_of_pkg_to_keep` a character vector indicating types of packages to keep. The default, `type_of_pkg_to_keep = c("base", "recommended")`, keeps all base and recommended packages that come with R when R is installed.

`keep_kim` logical. If `keep_kim = FALSE`, Package 'kim' will be removed along with all other user-installed packages. If `keep_kim = TRUE`, Package 'kim' will not be removed. By default, `keep_kim = FALSE`

Examples

```
## Not run:
remove_user_installed_pkgs()

## End(Not run)
```

```
repeated_measures_anova
      Repeated-Measures ANOVA
```

Description

Conduct a repeated-measures analysis of variance (ANOVA). This analysis will be appropriate for within-subjects experimental design.

Usage

```
repeated_measures_anova(
  data = NULL,
  p_col_name = NULL,
  measure_vars = NULL,
  histograms = TRUE,
  round_w = 2,
  round_epsilon = 2,
  round_df_model = 2,
  round_df_error = 2,
  round_f = 2,
  round_ges = 2
)
```

Arguments

`data` a data object (a data frame or a data.table)

`p_col_name` name of the column identifying participants

`measure_vars` names of the columns containing repeated measures (within-subjects variables)

histograms	logical. If histograms = TRUE, histograms of the repeated measures will be plotted. If histograms = FALSE, no histograms will be plotted.
round_w	number of decimal places to which to round W statistic from Mauchly's test (default = 2)
round_epsilon	number of decimal places to which to round the epsilon statistic from Greenhouse-Geisser or Huynh-Feldt correction (default = 2)
round_df_model	number of decimal places to which to round the corrected degrees of freedom for model (default = 2)
round_df_error	number of decimal places to which to round the corrected degrees of freedom for error (default = 2)
round_f	number of decimal places to which to round the F statistic (default = 2)
round_ges	number of decimal places to which to round generalized eta-squared (default = 2)

Details

The following package(s) must be installed prior to running the function: Package 'ez' v4.4-0 (or possibly a higher version) by Michael A Lawrence (2016), <https://cran.r-project.org/package=ez>

Examples

```
## Not run:
repeated_measures_anova(
  data = mtcars, p_col_name = "cyl", measure_vars = c("wt", "qsec"))

## End(Not run)
```

replace_values_in_dt *Replace values in a data table*

Description

Replace values in a data.table

Usage

```
replace_values_in_dt(
  data = NULL,
  old_values = NULL,
  new_values = NULL,
  silent = FALSE
)
```

Arguments

data	a data object (a data frame or a data.table)
old_values	a vector of old values that need to be replaced
new_values	a new value or a vector of new values that will replace the old values
silent	If silent = FALSE, a message will be printed regarding how many values were replaced. If silent = TRUE, no message will be printed regarding how many values were replaced. (default = FALSE)

Examples

```

replace_values_in_dt(data = mtcars, old_values = 21.0, new_values = 888)
replace_values_in_dt(data = mtcars, old_values = c(0, 1), new_values = 999)
replace_values_in_dt(
data = mtcars, old_values = c(0, 1), new_values = 990:991)
replace_values_in_dt(
data = data.table::data.table(a = NA_character_, b = NA_character_),
old_values = NA, new_values = "")

```

robust_regression	<i>Robust regression (bootstrapped regression)</i>
-------------------	--

Description

Estimate coefficients in a multiple regression model by bootstrapping.

Usage

```

robust_regression(
  data = NULL,
  formula = NULL,
  sigfigs = NULL,
  round_digits_after_decimal = NULL,
  iterations = 1000
)

```

Arguments

data	a data object (a data frame or a data.table)
formula	a formula object for the regression equation
sigfigs	number of significant digits to round to
round_digits_after_decimal	round to nth digit after decimal (alternative to sigfigs)
iterations	number of bootstrap samples. The default is set at 1000, but consider increasing the number of samples to 5000, 10000, or an even larger number, if slower handling time is not an issue.

Details

The following package(s) must be installed prior to running this function: Package 'boot' v1.3-26 (or possibly a higher version) by Canty & Ripley (2021), <https://cran.r-project.org/package=boot>

Examples

```
## Not run:
robust_regression(
  data = mtcars, formula = mpg ~ cyl * hp,
  iterations = 100
)

## End(Not run)
```

round_flexibly	<i>Round flexibly</i>
----------------	-----------------------

Description

Round numbers to a flexible number of significant digits. "Flexible" rounding refers to rounding all numbers to the highest level of precision seen among numbers that would have resulted from the 'signif()' function in base R. The usage examples of this function demonstrate flexible rounding (see below).

Usage

```
round_flexibly(x = NULL, sigfigs = 3)
```

Arguments

x	a numeric vector
sigfigs	number of significant digits to flexibly round to. By default, sigfigs = 3.

Value

the output will be a numeric vector with values rounded to the highest level of precision seen among numbers that result from the 'signif()' function in base R.

Examples

```
# Example 1
# First, observe results from the 'signif' function:
c(0.00012345, pi)
signif(c(0.00012345, pi), 3)
# In the result above, notice how info is lost on some digits
# (e.g., 3.14159265 becomes 3.140000).
# In contrast, flexible rounding retains the lost info in the digits
```

```
round_flexibly(x = c(0.00012345, pi), sigfigs = 3)

# Example 2
# Again, first observe results from the 'signif' function:
c(0.12345, 1234, 0.12, 1.23, .01)
signif(c(0.12345, 1234, 0.12, 1.23, .01), 3)
# In the result above, notice how info is lost on some digits
# (e.g., 1234 becomes 1230.000).
# In contrast, flexible rounding retains the lost info in the digits.
# Specifically, in the example below, 0.12345 rounded to 3 significant
# digits (default) is signif(0.12345, 3) = 0.123 (3 decimal places).
# Because this 3 decimal places is the highest precision seen among
# all numbers, all other numbers will also be rounded to 3 decimal places.
round_flexibly(
c(0.12345, 1234, 0.12, 1.23, .01))

# Example 3
# If the input is a character vector, the original input will be returned.
round_flexibly(c("a", "b", "c"))

# Example 4
# If the input is a list (e.g., a data.frame) that contains at least
# one numeric vector, the numeric vector element(s) will be rounded
# flexibly.
round_flexibly(data.frame(a = c(1.2345, 123.45), b = c("a", "b")))

# Example 5
# If the input is a matrix, all numbers will be rounded flexibly
round_flexibly(matrix(
c(1.23, 2.345, 3.4567, 4.56789), ncol = 2), sigfigs = 3)
```

scatterplot

Scatterplot

Description

Creates a scatter plot and calculates a correlation between two variables.

Usage

```
scatterplot(
  data = NULL,
  x_var_name = NULL,
  y_var_name = NULL,
  dot_label_var_name = NULL,
  weight_var_name = NULL,
  alpha = 1,
  annotate_stats = TRUE,
```

```

  annotate_y_pos = 5,
  annotated_stats_color = "green4",
  annotated_stats_font_size = 6,
  annotated_stats_font_face = "bold",
  line_of_fit_type = "lm",
  ci_for_line_of_fit = FALSE,
  line_of_fit_color = "blue",
  line_of_fit_thickness = 1,
  dot_color = "black",
  x_axis_label = NULL,
  y_axis_label = NULL,
  dot_size = 2,
  dot_label_size = NULL,
  dot_size_range = c(3, 12),
  jitter_x_percent = 0,
  jitter_y_percent = 0,
  cap_axis_lines = FALSE,
  color_dots_by = NULL
)

```

Arguments

<code>data</code>	a data object (a data frame or a data.table)
<code>x_var_name</code>	name of the variable that will go on the x axis
<code>y_var_name</code>	name of the variable that will go on the y axis
<code>dot_label_var_name</code>	name of the variable that will be used to label individual observations
<code>weight_var_name</code>	name of the variable by which to weight the individual observations for calculating correlation and plotting the line of fit
<code>alpha</code>	opacity of the dots (0 = completely transparent, 1 = completely opaque)
<code>annotate_stats</code>	if TRUE, the correlation and p-value will be annotated at the top of the plot (default = TRUE)
<code>annotate_y_pos</code>	position of the annotated stats, expressed as a percentage of the range of y values by which the annotated stats will be placed above the maximum value of y in the data set (default = 5). If <code>annotate_y_pos = 5</code> , and the minimum and maximum y values in the data set are 0 and 100, respectively, the annotated stats will be placed at 5% of the y range (100 - 0) above the maximum y value, $y = 0.05 * (100 - 0) + 100 = 105$.
<code>annotated_stats_color</code>	color of the annotated stats (default = "green4").
<code>annotated_stats_font_size</code>	font size of the annotated stats (default = 6).
<code>annotated_stats_font_face</code>	font face of the annotated stats (default = "bold").

line_of_fit_type	if line_of_fit_type = "lm", a regression line will be fit; if line_of_fit_type = "loess", a local regression line will be fit; if line_of_fit_type = "none", no line will be fit
ci_for_line_of_fit	if ci_for_line_of_fit = TRUE, confidence interval for the line of fit will be shaded
line_of_fit_color	color of the line of fit (default = "blue")
line_of_fit_thickness	thickness of the line of fit (default = 1)
dot_color	color of the dots (default = "black")
x_axis_label	alternative label for the x axis
y_axis_label	alternative label for the y axis
dot_size	size of the dots on the plot (default = 2)
dot_label_size	size for dots' labels on the plot. If no input is entered for this argument, it will be set as dot_label_size = 5 by default. If the plot is to be weighted by some variable, this argument will be ignored, and dot sizes will be determined by the argument dot_size_range
dot_size_range	minimum and maximum size for dots on the plot when they are weighted
jitter_x_percent	horizontally jitter dots by a percentage of the range of x values
jitter_y_percent	vertically jitter dots by a percentage of the range of y values
cap_axis_lines	logical. Should the axis lines be capped at the outer tick marks? (default = TRUE)
color_dots_by	name of the variable that will determine colors of the dots

Details

If a weighted correlation is to be calculated, the following package(s) must be installed prior to running the function: Package 'weights' v1.0 (or possibly a higher version) by John Pasek (2018), <https://cran.r-project.org/package=weights>

Value

the output will be a scatter plot, a ggplot object.

Examples

```
## Not run:
scatterplot(data = mtcars, x_var_name = "wt", y_var_name = "mpg")
scatterplot(
  data = mtcars, x_var_name = "wt", y_var_name = "mpg",
  dot_label_var_name = "hp", weight_var_name = "drat",
  annotate_stats = TRUE)
scatterplot(
```

```

data = mtcars, x_var_name = "wt", y_var_name = "mpg",
dot_label_var_name = "hp", weight_var_name = "cyl",
dot_label_size = 7, annotate_stats = TRUE)

## End(Not run)

```

score_scale_items *Score scale items*

Description

Score items in a scale (e.g., Likert scale items) by computing the sum or mean of the items.

Usage

```

score_scale_items(
  item_list = NULL,
  reverse_item_list = NULL,
  operation = "mean",
  na_summary = TRUE,
  reverse_code_minuend = NULL
)

```

Arguments

`item_list` a list of scale items (i.e., list of vectors of ratings) to code normally (as opposed to reverse coding).

`reverse_item_list` a list of scale items to reverse code.

`operation` if `operation = "mean"`, mean of the scale items will be calculated; if `operation = "sum"`, sum of the scale items will be calculated (default = "mean").

`na_summary` logical. If `na_summary = TRUE` a summary of NA values will be printed; if `na_summary = FALSE` the summary will not be printed (default = TRUE).

`reverse_code_minuend` required for reverse coding; the number from which to subtract item ratings when reverse-coding. For example, if the items to reverse code are measured on a 7-point scale, enter `reverse_code_minuend = 8`.

Examples

```

score_scale_items(item_list = list(1:5, rep(3, 5)),
reverse_item_list = list(rep(5, 5)), reverse_code_minuend = 6)
score_scale_items(item_list = list(c(1, 1), c(1, 5)),
reverse_item_list = list(c(5, 3)),
reverse_code_minuend = 6, na_summary = FALSE)
score_scale_items(item_list = list(c(1, 1), c(1, 5)),
reverse_item_list = list(c(5, 1)),
reverse_code_minuend = 6, operation = "sum")
score_scale_items(item_list = list(1:5, rep(3, 5)))

```

setup_r_env	<i>Set up R environment</i>
-------------	-----------------------------

Description

Set up R environment by (1) clearing the console; (2) removing all objects in the global environment; (3) setting the working directory to the active document (in RStudio only); (4) unloading and loading the kim package.

Usage

```
setup_r_env(  
  clear_console = TRUE,  
  clear_global_env = TRUE,  
  setwd_to_active_doc = TRUE,  
  prep_kim = TRUE  
)
```

Arguments

`clear_console` if TRUE, clear the console (default = TRUE)
`clear_global_env` if TRUE, remove all objects in the global environment (default = TRUE)
`setwd_to_active_doc` if TRUE, set the working directory to the active document in RStudio (default = TRUE)
`prep_kim` if TRUE, unload and load the kim package (default = TRUE)

Examples

```
## Not run:  
setup_r_env()  
  
## End(Not run)
```

setwd_to_active_doc	<i>Set working directory to active document in RStudio</i>
---------------------	--

Description

Set working directory to location of the active document in RStudio

Usage

```
setwd_to_active_doc()
```

Value

there will be no output from this function. Rather, the working directory will be set as location of the active document.

Examples

```
## Not run:  
setwd_to_active_doc()  
  
## End(Not run)
```

se_of_mean	<i>Standard error of the mean</i>
------------	-----------------------------------

Description

Standard error of the mean

Usage

```
se_of_mean(vector, na.rm = TRUE, notify_na_count = NULL)
```

Arguments

vector	a numeric vector
na.rm	if TRUE, NA values will be removed before calculation
notify_na_count	if TRUE, notify how many observations were removed due to missing values. By default, NA count will be printed only if there are any NA values.

Value

the output will be a numeric vector of length one, which will be the standard error of the mean for the given numeric vector.

Examples

```
se_of_mean(c(1:10, NA))
```

`simple_effects_analysis`*Simple Effects Analysis*

Description

Conduct a simple effects analysis to probe a two-way interaction effect. See Field et al. (2012, ISBN: 978-1-4462-0045-2).

Usage

```
simple_effects_analysis(  
  data = NULL,  
  dv_name = NULL,  
  iv_1_name = NULL,  
  iv_2_name = NULL,  
  iv_1_levels = NULL,  
  iv_2_levels = NULL,  
  print_contrast_table = "weights_sums_and_products",  
  output = NULL  
)
```

Arguments

<code>data</code>	a data object (a data frame or a data.table)
<code>dv_name</code>	name of the dependent variable (DV)
<code>iv_1_name</code>	name of the first independent variable (IV1), whose main effects will be examined in the first set of contrasts
<code>iv_2_name</code>	name of the second independent variable (IV2), whose simple effects at each level of IV1 will be examined in the second set of contrasts
<code>iv_1_levels</code>	ordered levels of IV1
<code>iv_2_levels</code>	ordered levels of IV2
<code>print_contrast_table</code>	If <code>print_contrast_table = "weights_sums_and_products"</code> , contrasts' weights, sums of the weights and products will be printed. If <code>print_contrast_table = "weights_only"</code> , only the contrasts will be printed.
<code>output</code>	output can be one of the following: <code>"lm_object"</code> , <code>"table"</code> , <code>"weights_only"</code> , <code>"weights_sums_and_products"</code> , <code>"all"</code> By default, <code>output = NULL</code> , and there will be no output from the function other than the tables of simple effects and contrasts which will be printed on the console by default.

Value

By default, the function will print a table of contrasts and a table of simple effects.

Examples

```
two_way_anova(
  data = mtcars, dv_name = "mpg", iv_1_name = "vs",
  iv_2_name = "am", iterations = 100, plot = TRUE)
simple_effects_analysis(
  data = mtcars, dv_name = "mpg", iv_1_name = "vs",
  iv_2_name = "am")
```

skewness

Skewness

Description

Calculate skewness using one of three formulas: (1) the traditional Fisher-Pearson coefficient of skewness; (2) the adjusted Fisher-Pearson standardized moment coefficient; (3) the Pearson 2 skewness coefficient. Formulas were taken from Doane & Seward (2011), doi: [10.1080/10691898.2011.11889611](https://doi.org/10.1080/10691898.2011.11889611)

Usage

```
skewness(vector = NULL, type = "adjusted")
```

Arguments

vector	a numeric vector
type	a character string indicating the type of skewness to calculate. If type = "adjusted", the adjusted Fisher-Pearson standardized moment coefficient will be calculated. If type = "traditional", the traditional Fisher-Pearson coefficient of skewness will be calculated. If type = "pearson_2", the Pearson 2 skewness coefficient will be calculated. By default, type = "adjusted".

Value

a numeric value, i.e., skewness of the given vector

Examples

```
# calculate the adjusted Fisher-Pearson standardized moment coefficient
kim::skewness(c(1, 2, 3, 4, 5, 10))
# calculate the traditional Fisher-Pearson coefficient of skewness
kim::skewness(c(1, 2, 3, 4, 5, 10), type = "traditional")
# compare with skewness from 'moments' package
moments::skewness(c(1, 2, 3, 4, 5, 10))
# calculate the Pearson 2 skewness coefficient
kim::skewness(c(1, 2, 3, 4, 5, 10), type = "pearson_2")
```

`spotlight_2_by_continuous`*Spotlight 2 by Continuous*

Description

Conduct a spotlight analysis for a 2 x Continuous design. See Spiller et al. (2013) doi:10.1509/jmr.12.0420.

Usage

```
spotlight_2_by_continuous(  
  data = NULL,  
  iv_name = NULL,  
  dv_name = NULL,  
  mod_name = NULL,  
  logistic = NULL,  
  covariate_name = NULL,  
  focal_values = NULL,  
  interaction_p_include = TRUE,  
  iv_level_order = NULL,  
  output_type = "plot",  
  colors = c("red", "blue"),  
  dot_size = 3,  
  observed_dots = FALSE,  
  reg_lines = FALSE,  
  reg_line_size = 1,  
  lines_connecting_est_dv = TRUE,  
  lines_connecting_est_dv_size = 1,  
  estimated_dv_dot_shape = 15,  
  estimated_dv_dot_size = 6,  
  error_bar = "ci",  
  error_bar_range = 0.95,  
  error_bar_tip_width = NULL,  
  error_bar_tip_width_percent = 8,  
  error_bar_thickness = 1,  
  error_bar_offset = NULL,  
  error_bar_offset_percent = 8,  
  simp_eff_bracket_leg_ht = NULL,  
  simp_eff_bracket_leg_ht_perc = 2,  
  simp_eff_bracket_offset = NULL,  
  simp_eff_bracket_offset_perc = 1,  
  simp_eff_bracket_color = "black",  
  simp_eff_bracket_line_size = 1,  
  simp_eff_text_offset = NULL,  
  simp_eff_text_offset_percent = 7,  
  simp_eff_text_hjust = 0.5,  
  simp_eff_text_part_1 = "Simple Effect\n",
```

```

simp_eff_text_color = "black",
simp_eff_font_size = 5,
interaction_p_value_x = NULL,
interaction_p_value_y = NULL,
interaction_p_value_font_size = 6,
interaction_p_value_vjust = -1,
interaction_p_value_hjust = 0.5,
x_axis_breaks = NULL,
x_axis_limits = NULL,
x_axis_tick_mark_labels = NULL,
y_axis_breaks = NULL,
y_axis_limits = NULL,
x_axis_space_left_perc = 10,
x_axis_space_right_perc = 30,
y_axis_tick_mark_labels = NULL,
x_axis_title = NULL,
y_axis_title = NULL,
legend_title = NULL,
legend_position = "right",
y_axis_title_vjust = 0.85,
round_decimals_int_p_value = 3,
jitter_x_percent = 0,
jitter_y_percent = 0,
dot_alpha = 0.2,
reg_line_alpha = 0.5,
jn_point_font_size = 6,
reg_line_types = c("solid", "dashed"),
caption = NULL,
plot_margin = ggplot2::unit(c(60, 30, 7, 7), "pt"),
silent = FALSE
)

```

Arguments

<code>data</code>	a data object (a data frame or a <code>data.table</code>)
<code>iv_name</code>	name of the binary independent variable (IV)
<code>dv_name</code>	name of the dependent variable (DV)
<code>mod_name</code>	name of the continuous moderator variable (MOD)
<code>logistic</code>	logical. Should logistic regressions be conducted, rather than ordinary least squares regressions? By default, ordinary least squares regressions will be conducted.
<code>covariate_name</code>	name(s) of the variable(s) to control for in estimating conditional values of the DV.
<code>focal_values</code>	focal values of the moderator variable at which to estimate IV's effect on DV.
<code>interaction_p_include</code>	logical. Should the plot include a p-value for the interaction term?

<code>iv_level_order</code>	order of levels in the independent variable for legend. By default, it will be set as levels of the independent variable ordered using R's base function <code>sort</code> .
<code>output_type</code>	type of output (default = "plot").
<code>colors</code>	set colors for the two levels of the independent variable. By default, <code>colors = c("red", "blue")</code> .
<code>dot_size</code>	size of the observed_dots (default = 3)
<code>observed_dots</code>	logical. If <code>observed_dots = TRUE</code> , the observed values of all IV, DV, and MOD combinations will be plotted as dots. On top of these dots the spotlight analysis plot will be laid. If <code>observed_dots = FALSE</code> , these dots will not be plotted. By default, <code>observed_dots = FALSE</code> .
<code>reg_lines</code>	logical. If <code>reg_lines = TRUE</code> , the regression lines from regressing DV on MOD at each value of IV will be plotted. If <code>reg_lines = FALSE</code> , these regression lines will not be plotted. By default, <code>observed_dots = FALSE</code> .
<code>reg_line_size</code>	thickness of the regression lines (default = 1).
<code>lines_connecting_est_dv</code>	logical. Should lines connecting the estimated values of DV be drawn? (default = TRUE)
<code>lines_connecting_est_dv_size</code>	thickness of the lines connecting the estimated values of DV (default = 1).
<code>estimated_dv_dot_shape</code>	ggplot value for shape of the dots at estimated values of DV (default = 15, a square shape).
<code>estimated_dv_dot_size</code>	size of the dots at estimated values of DV (default = 6).
<code>error_bar</code>	if <code>error_bar = "se"</code> ; error bars will be +/-1 standard error, if <code>error_bar = "ci"</code> error bars will be a confidence interval. By default, <code>error_bar = "ci"</code> .
<code>error_bar_range</code>	width of the confidence interval (default = 0.95 for a 95 percent confidence interval). This argument will not apply when <code>error_bar = "se"</code>
<code>error_bar_tip_width</code>	graphically, width of the segments at the end of error bars (default = 0.13)
<code>error_bar_tip_width_percent</code>	(default)
<code>error_bar_thickness</code>	thickness of the error bars (default = 1)
<code>error_bar_offset</code>	(default)
<code>error_bar_offset_percent</code>	(default)
<code>simp_eff_bracket_leg_ht</code>	(default)
<code>simp_eff_bracket_leg_ht_perc</code>	(default)

`simp_eff_bracket_offset`
(default)

`simp_eff_bracket_offset_perc`
(default)

`simp_eff_bracket_color`
(default)

`simp_eff_bracket_line_size`
(default)

`simp_eff_text_offset`
(default)

`simp_eff_text_offset_percent`
(default)

`simp_eff_text_hjust`
(default)

`simp_eff_text_part_1`
The first part of the text for labeling simple effects. By default, `simp_eff_text_part_1`
= "Simple Effect\n"

`simp_eff_text_color`
color for the text indicating p-values of simple effects (default = "black").

`simp_eff_font_size`
font size of the text indicating p-values of simple effects (default = 5).

`interaction_p_value_x`
(default)

`interaction_p_value_y`
(default)

`interaction_p_value_font_size`
font size for the interaction p value (default = 6)

`interaction_p_value_vjust`
(default)

`interaction_p_value_hjust`
(default)

`x_axis_breaks` (default)

`x_axis_limits` (default)

`x_axis_tick_mark_labels`
(default)

`y_axis_breaks` (default)

`y_axis_limits` (default)

`x_axis_space_left_perc`
(default)

`x_axis_space_right_perc`
(default)

`y_axis_tick_mark_labels`
(default)

x_axis_title	title of the x axis. By default, it will be set as input for mod_name. If x_axis_title = FALSE, it will be removed.
y_axis_title	title of the y axis. By default, it will be set as input for dv_name. If y_axis_title = FALSE, it will be removed.
legend_title	title of the legend. By default, it will be set as input for iv_name. If legend_title = FALSE, it will be removed.
legend_position	position of the legend (default = "right"). If legend_position = "none", the legend will be removed.
y_axis_title_vjust	position of the y axis title (default = 0.85). If default is used, y_axis_title_vjust = 0.85, the y axis title will be positioned at 85% of the way up from the bottom of the plot.
round_decimals_int_p_value	To how many digits after the decimal point should the p value for the interaction term be rounded? (default = 3)
jitter_x_percent	horizontally jitter dots by a percentage of the range of x values
jitter_y_percent	vertically jitter dots by a percentage of the range of y values
dot_alpha	opacity of the dots (0 = completely transparent, 1 = completely opaque). By default, dot_alpha = 0.2
reg_line_alpha	(default)
jn_point_font_size	(default)
reg_line_types	types of the regression lines for the two levels of the independent variable. By default, reg_line_types = c("solid", "dashed")
caption	(default)
plot_margin	margin for the plot By default plot_margin = ggplot2::unit(c(60, 30, 7, 7), "pt")
silent	If silent = FALSE, (various) messages will be printed. If silent = TRUE, the messages will be suppressed. By default, silent = FALSE.

Examples

```
spotlight_2_by_continuous(
  data = mtcars,
  iv_name = "am",
  dv_name = "mpg",
  mod_name = "qsec")
# control for variables
spotlight_2_by_continuous(
  data = mtcars,
  iv_name = "am",
  dv_name = "mpg",
```

```
mod_name = "qsec",
covariate_name = c("cyl", "hp"))
# control for variables and adjust simple effect labels
spotlight_2_by_continuous(
  data = mtcars,
  iv_name = "am",
  dv_name = "mpg",
  mod_name = "qsec",
  covariate_name = c("cyl", "hp"),
  reg_lines = TRUE,
  observed_dots = TRUE,
  error_bar_offset_percent = 3,
  error_bar_tip_width_percent = 3,
  simp_eff_text_offset_percent = 3,
  simp_eff_bracket_leg_ht_perc = 2,
  dot_alpha = 0.2,
  simp_eff_text_part_1 = "")
# spotlight at specific values
spotlight_2_by_continuous(
  data = mtcars,
  iv_name = "am",
  dv_name = "mpg",
  mod_name = "qsec",
  covariate_name = c("cyl", "hp"),
  focal_values = seq(15, 22, 1),
  reg_lines = TRUE,
  observed_dots = TRUE,
  dot_alpha = 0.2,
  simp_eff_text_part_1 = "",
  simp_eff_font_size = 4,
  error_bar_offset_percent = 3,
  error_bar_tip_width_percent = 3,
  simp_eff_text_offset_percent = 3,
  simp_eff_bracket_leg_ht_perc = 1,
  x_axis_breaks = seq(15, 22, 1))
```

standardized_regression

Standardized Regression

Description

This function standardizes all variables for a regression analysis (i.e., dependent variable and all independent variables) and then conducts a regression with the standardized variables.

Usage

```
standardized_regression(
  data = NULL,
```

```

formula = NULL,
reverse_code_vars = NULL,
sigfigs = NULL,
round_digits_after_decimal = NULL,
round_p = 3,
pretty_round_p_value = TRUE,
return_table_upper_half = FALSE,
round_r_squared = 3,
round_f_stat = 2,
prettify_reg_table_col_names = TRUE
)

```

Arguments

data a data object (a data frame or a data.table)

formula a formula object for the regression equation

reverse_code_vars names of binary variables to reverse code

sigfigs number of significant digits to round to

round_digits_after_decimal round to nth digit after decimal (alternative to sigfigs)

round_p number of decimal places to which to round p-values (default = 3)

pretty_round_p_value logical. Should the p-values be rounded in a pretty format (i.e., lower threshold: "<.001"). By default, pretty_round_p_value = TRUE.

return_table_upper_half logical. Should only the upper part of the table be returned? By default, return_table_upper_half = FALSE.

round_r_squared number of digits after the decimal both r-squared and adjusted r-squared values should be rounded to (default 3)

round_f_stat number of digits after the decimal the f statistic of the regression model should be rounded to (default 2)

prettify_reg_table_col_names logical. Should the column names of the regression table be made pretty (e.g., change "std_beta" to "Std. Beta")? (Default = TRUE)

Value

the output will be a data.table showing multiple regression results.

Examples

```

standardized_regression(data = mtcars, formula = mpg ~ gear * cyl)
standardized_regression(
data = mtcars, formula = mpg ~ gear + gear:am + disp * cyl,

```

```
round_digits_after_decimal = 3)
```

start_kim	<i>Start kim</i>
-----------	------------------

Description

Start kim (update kim; attach default packages; set working directory, etc.) This function requires installing Package 'remotes' v2.4.2 (or possibly a higher version) by Csardi et al. (2021), <https://cran.r-project.org/package=remotes>

Usage

```
start_kim(
  update = TRUE,
  upgrade_other_pkg = FALSE,
  setup_r_env = TRUE,
  default_packages = c("data.table", "ggplot2"),
  silent_load_pkgs = c("data.table", "ggplot2")
)
```

Arguments

update	If update = "force", force updating the package 'kim'. If update = TRUE, compares the currently installed package 'kim' with the most recent version on GitHub and, if the version on GitHub is more recent, ask the user to confirm the update. If confirmed, then update the package. If update = FALSE, skip updating the package. By default, update = "force"
upgrade_other_pkg	input for the upgrade argument to be passed on to <code>remotes::install_github</code> . One of "default", "ask", "always", "never", TRUE, or FALSE. "default" respects the value of the <code>R_REMOTES_UPGRADE</code> environment variable if set, and falls back to "ask" if unset. "ask" prompts the user for which out of date packages to upgrade. For non-interactive sessions "ask" is equivalent to "always". TRUE and FALSE correspond to "always" and "never" respectively. By default, <code>upgrade_other_pkg = FALSE</code> .
setup_r_env	logical. If update = TRUE, runs the function <code>setup_r_env</code> in the package "kim". Type <code>"?kim::setup_r_env"</code> to learn more. By default, <code>setup_r_env = TRUE</code>
default_packages	a vector of names of packages to load and attach. By default, <code>default_packages = c("data.table", "ggplot2")</code>
silent_load_pkgs	a character vector indicating names of packages to load silently (i.e., suppress messages that get printed when loading the packages). By default, <code>silent_load_pkgs = c("data.table", "ggplot2")</code>

Examples

```
## Not run:
start_kim()
start_kim(default_packages = c("dplyr", "ggplot2"))
start_kim(update = TRUE, setup_r_env = FALSE)

## End(Not run)
```

su	<i>su: Sorted unique values</i>
----	---------------------------------

Description

Extract unique elements and sort them

Usage

```
su(x = NULL, na.last = TRUE, decreasing = FALSE)
```

Arguments

x	a vector or a data frame or an array or NULL.
na.last	an argument to be passed onto the 'sort' function (in base R) for controlling the treatment of NA values. If na.last = TRUE, NA values in the data are put last; if na.last = FALSE, NA values are put first; if na.last = NA, NA values are removed. By default, na.last = TRUE
decreasing	logical. Should the sort be increasing or decreasing? An argument to be passed onto the 'sort' function (in base R). By default, decreasing = FALSE

Value

a vector, data frame, or array-like 'x' but with duplicate elements/rows removed.

Examples

```
su(c(10, 3, 7, 10, NA))
su(c("b", "z", "b", "a", NA, NA, NA))
```

tabulate_vector	<i>Tabulate vector</i>
-----------------	------------------------

Description

Shows frequency and proportion of unique values in a table format

Usage

```
tabulate_vector(
  vector = NULL,
  na.rm = TRUE,
  sort_by_decreasing_count = NULL,
  sort_by_increasing_count = NULL,
  sort_by_decreasing_value = NULL,
  sort_by_increasing_value = NULL,
  total_included = TRUE,
  sigfigs = NULL,
  round_digits_after_decimal = NULL,
  output_type = "dt"
)
```

Arguments

vector	a character or numeric vector
na.rm	if TRUE, NA values will be removed before calculating frequencies and proportions.
sort_by_decreasing_count	if TRUE, the output table will be sorted in the order of decreasing frequency.
sort_by_increasing_count	if TRUE, the output table will be sorted in the order of increasing frequency.
sort_by_decreasing_value	if TRUE, the output table will be sorted in the order of decreasing value.
sort_by_increasing_value	if TRUE, the output table will be sorted in the order of increasing value.
total_included	if TRUE, the output table will include a row for total counts.
sigfigs	number of significant digits to round to
round_digits_after_decimal	round to nth digit after decimal (alternative to sigfigs)
output_type	if output_type = "df", return a data.frame. By default, output_type = "dt", which will return a data.table.

Value

if output_type = "dt", which is the default, the output will be a data.table showing the count and proportion (percent) of each element in the given vector; if output_type = "df", the output will be a data.frame showing the count and proportion (percent) of each value in the given vector.

Examples

```
tabulate_vector(c("a", "b", "b", "c", "c", "c", NA))
tabulate_vector(c("a", "b", "b", "c", "c", "c", NA),
  sort_by_increasing_count = TRUE
)
tabulate_vector(c("a", "b", "b", "c", "c", "c", NA),
  sort_by_decreasing_value = TRUE
)
tabulate_vector(c("a", "b", "b", "c", "c", "c", NA),
  sort_by_increasing_value = TRUE
)
tabulate_vector(c("a", "b", "b", "c", "c", "c", NA),
  sigfigs = 4
)
tabulate_vector(c("a", "b", "b", "c", "c", "c", NA),
  round_digits_after_decimal = 1
)
tabulate_vector(c("a", "b", "b", "c", "c", "c", NA),
  output_type = "df"
)
```

theme_kim

Theme Kim

Description

A custom ggplot theme

Usage

```
theme_kim(
  legend_position = "none",
  base_size = 20,
  axis_tick_font_size = 20,
  axis_title_font_size = 24,
  y_axis_title_vjust = 0.85,
  axis_title_margin_size = 24,
  cap_axis_lines = FALSE
)
```

Arguments

legend_position position of the legend (default = "none")

base_size base font size

axis_tick_font_size font size for axis tick marks

`axis_title_font_size` font size for axis title
`y_axis_title_vjust` position of the y axis title (default = 0.85). If default is used, `y_axis_title_vjust = 0.85`, the y axis title will be positioned at 85% of the way up from the bottom of the plot.
`axis_title_margin_size` size of the margin between axis title and the axis line
`cap_axis_lines` logical. Should the axis lines be capped at the outer tick marks? (default = FALSE)

Details

If axis lines are to be capped at the ends, the following package(s) must be installed prior to running the function: Package 'lemon' v0.4.4 (or possibly a higher version) by Edwards et al. (2020), <https://cran.r-project.org/package=lemon>

Value

a ggplot object; there will be no meaningful output from this function. Instead, this function should be used with another ggplot object, e.g., `ggplot(mtcars, aes(x = disp, y = mpg)) + theme_kim()`

Examples

```

prep(ggplot2)
ggplot2::ggplot(mtcars, aes(x = cyl, y = mpg)) + geom_point() + theme_kim()
  
```

`top_median_or_bottom` *Top, median, or bottom*

Description

Indicates whether each value in a vector belongs to top, median, or bottom

Usage

```
top_median_or_bottom(vector)
```

Arguments

`vector` a numeric vector

Value

a character vector indicating whether each element in a vector belongs to "top", "median", or "bottom"

Examples

```
top_median_or_bottom(c(1, 2, 3, NA))
top_median_or_bottom(c(1, 2, 2, NA))
top_median_or_bottom(c(1, 1, 2, NA))
```

 tv

Tabulate vector

Description

Shows frequency and proportion of unique values in a table format. This function is a copy of the earlier function, `tabulate_vector`, in Package 'kim'

Usage

```
tv(
  vector = NULL,
  na.rm = FALSE,
  sort_by_decreasing_count = NULL,
  sort_by_increasing_count = NULL,
  sort_by_decreasing_value = NULL,
  sort_by_increasing_value = NULL,
  total_included = TRUE,
  sigfigs = NULL,
  round_digits_after_decimal = NULL,
  output_type = "dt"
)
```

Arguments

<code>vector</code>	a character or numeric vector
<code>na.rm</code>	if TRUE, NA values will be removed before calculating frequencies and proportions. By default, FALSE.
<code>sort_by_decreasing_count</code>	if TRUE, the output table will be sorted in the order of decreasing frequency.
<code>sort_by_increasing_count</code>	if TRUE, the output table will be sorted in the order of increasing frequency.
<code>sort_by_decreasing_value</code>	if TRUE, the output table will be sorted in the order of decreasing value.
<code>sort_by_increasing_value</code>	if TRUE, the output table will be sorted in the order of increasing value.
<code>total_included</code>	if TRUE, the output table will include a row for total counts.
<code>sigfigs</code>	number of significant digits to round to
<code>round_digits_after_decimal</code>	round to nth digit after decimal (alternative to <code>sigfigs</code>)
<code>output_type</code>	if <code>output_type = "df"</code> , return a data.frame. By default, <code>output_type = "dt"</code> , which will return a data.table.

Value

if `output_type = "dt"`, which is the default, the output will be a `data.table` showing the count and proportion (percent) of each element in the given vector; if `output_type = "df"`, the output will be a `data.frame` showing the count and proportion (percent) of each value in the given vector.

Examples

```
tv(c("a", "b", "b", "c", "c", "c", NA))
tv(c("a", "b", "b", "c", "c", "c", NA),
  sort_by_increasing_count = TRUE
)
tv(c("a", "b", "b", "c", "c", "c", NA),
  sort_by_decreasing_value = TRUE
)
tv(c("a", "b", "b", "c", "c", "c", NA),
  sort_by_increasing_value = TRUE
)
tv(c("a", "b", "b", "c", "c", "c", NA),
  sigfigs = 4
)
tv(c("a", "b", "b", "c", "c", "c", NA),
  round_digits_after_decimal = 1
)
tv(c("a", "b", "b", "c", "c", "c", NA),
  output_type = "df"
)
```

two_way_anova

Two-way ANOVA

Description

Conduct a two-way analysis of variance (ANOVA).

Usage

```
two_way_anova(
  data = NULL,
  dv_name = NULL,
  iv_1_name = NULL,
  iv_2_name = NULL,
  iv_1_values = NULL,
  iv_2_values = NULL,
  sigfigs = 3,
  robust = FALSE,
  iterations = 2000,
  plot = FALSE,
  error_bar = "ci",
```

```

    error_bar_range = 0.95,
    line_size = 1,
    dot_size = 3,
    error_bar_tip_width = 0.13,
    position_dodge = 0.13,
    legend_position = "right",
    output = "anova_table"
)

```

Arguments

<code>data</code>	a data object (a data frame or a data.table)
<code>dv_name</code>	name of the dependent variable
<code>iv_1_name</code>	name of the first independent variable
<code>iv_2_name</code>	name of the second independent variable
<code>iv_1_values</code>	restrict all analyses to observations having these values for the first independent variable
<code>iv_2_values</code>	restrict all analyses to observations having these values for the second independent variable
<code>sigfigs</code>	number of significant digits to which to round values in anova table (default = 3)
<code>robust</code>	if TRUE, conduct a robust ANOVA in addition.
<code>iterations</code>	number of bootstrap samples for robust ANOVA. The default is set at 2000, but consider increasing the number of samples to 5000, 10000, or an even larger number, if slower handling time is not an issue.
<code>plot</code>	if TRUE, print a plot and enable returning an output.
<code>error_bar</code>	if <code>error_bar = "se"</code> ; error bars will be +/-1 standard error, if <code>error_bar = "ci"</code> error bars will be a confidence interval; if <code>error_bar = "pi"</code> , error bars will be a prediction interval
<code>error_bar_range</code>	width of the confidence or prediction interval (default = 0.95 for 95 percent confidence or prediction interval). This argument will not apply when <code>error_bar = "se"</code>
<code>line_size</code>	thickness of the lines connecting group means, (default = 1)
<code>dot_size</code>	size of the dots indicating group means (default = 3)
<code>error_bar_tip_width</code>	graphically, width of the segments at the end of error bars (default = 0.13)
<code>position_dodge</code>	by how much should the group means and error bars be horizontally offset from each other so as not to overlap? (default = 0.13)
<code>legend_position</code>	position of the legend: "none", "top", "right", "bottom", "left", "none" (default = "right")
<code>output</code>	output type can be one of the following: "anova_table", "group_stats", "plot", "levene_test_result", "robust_anova_results", "robust_anova_post_hoc_results", "robust_anova_post_hoc_contrast", "all"

Details

The following package(s) must be installed prior to running this function: Package 'car' v3.0.9 (or possibly a higher version) by Fox et al. (2020), <https://cran.r-project.org/package=car>

If robust ANOVA is to be conducted, the following package(s) must be installed prior to running the function: Package 'WRS2' v1.1-1 (or possibly a higher version) by Mair & Wilcox (2021), <https://cran.r-project.org/package=WRS2>

Value

by default, the output will be "anova_table"

Examples

```
two_way_anova(  
  data = mtcars, dv_name = "mpg", iv_1_name = "vs",  
  iv_2_name = "am", iterations = 100)  
anova_results <- two_way_anova(  
  data = mtcars, dv_name = "mpg", iv_1_name = "vs",  
  iv_2_name = "am", output = "all")  
anova_results
```

t_test_pairwise	<i>t test, pairwise</i>
-----------------	-------------------------

Description

Conducts a t-test for every possible pairwise comparison with Bonferroni correction

Usage

```
t_test_pairwise(  
  data = NULL,  
  iv_name = NULL,  
  dv_name = NULL,  
  sigfigs = 3,  
  cohen_d = TRUE,  
  cohen_d_w_ci = TRUE,  
  bonferroni = TRUE,  
  mann_whitney = TRUE,  
  t_test_stats = FALSE,  
  t_test_df_decimals = 1,  
  sd = FALSE,  
  round_p = 3  
)
```

Arguments

<code>data</code>	a data object (a data frame or a data.table)
<code>iv_name</code>	name of the independent variable
<code>dv_name</code>	name of the dependent variable
<code>sigfigs</code>	number of significant digits to round to
<code>cohen_d</code>	if <code>cohen_d = TRUE</code> , Cohen's d statistics will be included in the output data.table.
<code>cohen_d_w_ci</code>	if <code>cohen_d_w_ci = TRUE</code> , Cohen's d with 95% CI will be included in the output data.table.
<code>bonferroni</code>	if <code>bonferroni = TRUE</code> , Bonferroni tests will be conducted for t-tests or Mann-Whitney tests.
<code>mann_whitney</code>	if <code>TRUE</code> , Mann-Whitney test results will be included in the output data.table. If <code>FALSE</code> , Mann-Whitney tests will not be performed.
<code>t_test_stats</code>	if <code>t_test_stats = TRUE</code> , t-test statistic and degrees of freedom will be included in the output data.table.
<code>t_test_df_decimals</code>	number of decimals for the degrees of freedom in t-tests (default = 1)
<code>sd</code>	if <code>sd = TRUE</code> , standard deviations will be included in the output data.table.
<code>round_p</code>	number of decimal places to which to round p-values (default = 3)

Value

the output will be a data.table showing results of all pairwise comparisons between levels of the independent variable.

Examples

```
## Not run:
t_test_pairwise(data = iris, iv_name = "Species", dv_name = "Sepal.Length")
t_test_pairwise(data = iris, iv_name = "Species",
dv_name = "Sepal.Length", t_test_stats = TRUE, sd = TRUE)
t_test_pairwise(data = iris, iv_name = "Species", dv_name = "Sepal.Length",
mann_whitney = FALSE)

## End(Not run)
```

und

Undocumented functions

Description

A collection of miscellaneous functions lacking documentations

Usage

```
und(fn, ...)
```

Arguments

fn	name of the function
...	arguments for the function

Details

For more information on functions contained within this function, please refer to the following:
 mad_rm, Leys et al. (2013) doi:10.1016/j.jesp.2013.03.013

Value

the output will vary by function

Examples

```
# correlation
und(corr_text, x = 1:5, y = c(1, 2, 2, 2, 3))
# mean center
und(mean_center, 1:10)
# compare results with base function
scale(1:10, scale = TRUE)
# find the modes
und(mode, c(3, 3, 3, 1, 2, 2))
# return values that are not outliers
und(outlier_rm, c(12:18, 100))
kim::outlier(c(1:10, 100))
```

unload_user_installed_pkgs

Unload all user-installed packages

Description

Unload all user-installed packages

Usage

```
unload_user_installed_pkgs(exceptions = NULL, force = FALSE, keep_kim = TRUE)
```

Arguments

exceptions	a character vector of names of packages to keep loaded
force	logical. Should a package be unloaded even though other attached packages depend on it? By default, force = FALSE
keep_kim	logical. If keep_kim = FALSE, Package 'kim' will be detached along with all other user-installed packages. If keep_kim = TRUE, Package 'kim' will not be detached. By default, keep_kim = FALSE

Examples

```
## Not run:
unload_user_installed_pkgs()

## End(Not run)
```

update_kim	<i>Update the package 'kim'</i>
------------	---------------------------------

Description

Updates the current package 'kim' by installing the most recent version of the package from GitHub. This function requires installing Package 'remotes' v2.4.2 (or possibly a higher version) by Csardi et al. (2021), <https://cran.r-project.org/package=remotes>

Usage

```
update_kim(force = TRUE, upgrade_other_pkg = FALSE, confirm = TRUE)
```

Arguments

force	logical. If force = TRUE, force installing the update. If force = FALSE, do not force installing the update. By default, force = TRUE.
upgrade_other_pkg	input for the upgrade argument to be passed on to <code>remotes::install_github</code> . One of "default", "ask", "always", "never", TRUE, or FALSE. "default" respects the value of the R_REMOTES_UPGRADE environment variable if set, and falls back to "ask" if unset. "ask" prompts the user for which out of date packages to upgrade. For non-interactive sessions "ask" is equivalent to "always". TRUE and FALSE correspond to "always" and "never" respectively. By default, upgrade_other_pkg = FALSE.
confirm	logical. If confirm = TRUE, the user will need to confirm the update. If confirm = FALSE, the confirmation step will be skipped. By default, confirm = TRUE.

Value

there will be no output from this function. Rather, executing this function will update the current 'kim' package by installing the most recent version of the package from GitHub.

Examples

```
## Not run:
if (interactive()) {update_kim()}

## End(Not run)
```

vlookup	<i>Vlookup</i>
---------	----------------

Description

Look up values in a reference data.table and return values associated with the looked-up values contained in the reference data.table

Usage

```
vlookup(
  lookup_values = NULL,
  reference_dt = NULL,
  col_name_for_lookup_values = NULL,
  col_name_for_output_values = NULL
)
```

Arguments

`lookup_values` a vector of values to look up

`reference_dt` a data.table containing the values to look up as well as values associated with the looked-up values that need to be returned.

`col_name_for_lookup_values`
in the reference data.table, name of the column containing lookup_values.

`col_name_for_output_values`
in the reference data.table, name of the column containing values to return (i.e., values associated with the looked-up values that will be the function's output)

Examples

```
vlookup(lookup_values = c(2.620, 2.875), reference_dt = mtcars[1:9, ],
  col_name_for_lookup_values = "wt", col_name_for_output_values = "qsec")
```

weighted_mean_r	<i>Weighted mean correlation</i>
-----------------	----------------------------------

Description

Calculate the weighted mean correlation coefficient for a given correlations and sample sizes. See Field (2001) doi:10.1037/1082-989X.6.2.161

Usage

```
weighted_mean_r(r = NULL, n = NULL, ci = 0.95, sigfigs = 3, silent = FALSE)
```

Arguments

r	a (vector of) correlation coefficient(s)
n	a (vector of) sample size(s)
ci	size of the confidence interval. Input can be any value less than 1 and greater than or equal to 0. By default, ci = 0.95. If ci = TRUE, the default value of 0.95 will be used. If ci = FALSE, no confidence interval will be estimated.
sigfigs	number of significant digits to round to (default = 3)
silent	logical. If silent = FALSE, a message regarding the weighted mean correlation and its p-value and CI will be printed. If silent = TRUE, this message will be suppressed. By default, silent = FALSE.

Value

the output will be a list of vector of correlation coefficient(s).

Examples

```
weighted_mean_r(r = c(0.2, 0.4), n = c(100, 100))
weighted_mean_r(r = c(0.2, 0.4), n = c(100, 20000))
# example consistent with using MedCalc
weighted_mean_r(
  r = c(0.51, 0.48, 0.3, 0.21, 0.6, 0.46, 0.22, 0.25),
  n = c(131, 129, 155, 121, 111, 119, 112, 145))
```

weighted_z

Weighted z

Description

Calculate the weighted z (for calculating weighted mean correlation). See p. 231 of the book Hedges & Olkin (1985), *Statistical Methods for Meta-Analysis* (ISBN: 0123363802).

Usage

```
weighted_z(z = NULL, n = NULL)
```

Arguments

z	a vector of z values
n	a vector of sample sizes which will be used to calculate the weights, which in turn will be used to calculate the weighted z.

Value

the output will be a weighted z value.

Examples

```
weighted_z(1:3, c(100, 200, 300))  
weighted_z(z = c(1:3, NA), n = c(100, 200, 300, NA))
```

```
wilcoxon_rank_sum_test
```

Wilcoxon Rank-Sum Test (Also called the Mann-Whitney U Test)

Description

A nonparametric equivalent of the independent t-test

Usage

```
wilcoxon_rank_sum_test(  
  data = NULL,  
  iv_name = NULL,  
  dv_name = NULL,  
  sigfigs = 3  
)
```

Arguments

data	a data object (a data frame or a data.table)
iv_name	name of the independent variable (grouping variable)
dv_name	name of the dependent variable (measure variable of interest)
sigfigs	number of significant digits to round to

Value

the output will be a data.table object with all pairwise Wilcoxon rank-sum test results

Examples

```
wilcoxon_rank_sum_test(  
  data = iris, iv_name = "Species", dv_name = "Sepal.Length")
```

write_csv	<i>Write to a csv file</i>
-----------	----------------------------

Description

Write to a csv file

Usage

```
write_csv(data = NULL, name = NULL, timestamp = NULL)
```

Arguments

data	a data object (a data frame or a data.table)
name	a character string of the csv file name without the ".csv" extension. For example, if the csv file to write to is "myfile.csv", enter name = "myfile"
timestamp	logical. Should the timestamp be appended to the file name?

Value

the output will be a .csv file in the working directory, that is, an output from the data.table function, fwrite

Examples

```
## Not run:
write_csv(mtcars, "mtcars_from_write_csv")
write_csv(mtcars)

## End(Not run)
```

z_to_r_transform	<i>Z to r transformation (Inverse of Fisher's Z transformation)</i>
------------------	---

Description

Perform the Z-to-r transformation (i.e., the inverse of Fisher's r-to-Z transformation) for given Z value(s).

Usage

```
z_to_r_transform(z = NULL)
```

Arguments

z	a (vector of) Z values
---	------------------------

Value

the output will be a vector of correlation coefficient(s) that are the result(s) of the Z-to-r transformation.

Examples

```
z_to_r_transform(2.646652)
z_to_r_transform(z = -3:3)
```

Index

akaike_weights, 4

barplot_for_counts, 5
bracket, 5

capitalize, 7
change_var_names, 7
check_modes, 8
check_req_pkg, 9
chi_squared_test_pairwise, 9
clean_data_from_qualtrics, 11
coefficient_of_variation, 12
cohen_d, 13
cohen_d_borenstein, 14
cohen_d_from_cohen_textbook, 15
cohen_d_over_n, 16
cohen_d_torchiano, 17
combine_data_across_cols, 18
comma_sep_string_to_numbers, 18
compare_datasets, 19
compare_dependent_rs, 20
compare_effect_sizes, 21
compare_groups, 22
compare_independent_rs, 24
convert_cols_to_numeric, 26
convert_to_excel_formula, 27
correlation_matrix, 27
cum_percent_plot, 28

desc_stats, 29
desc_stats_by_group, 30
detach_user_installed_pkgs, 31
duplicated_values, 32

exit_from_parent_function, 33

find_duplicates, 33
fisher_z_transform, 34
floodlight_2_by_continuous, 35
forest_plot, 38

ggsave_quick, 41

histogram, 42
histogram_by_group, 43
histogram_w_outlier_bins, 45

id_across_datasets, 47
identical_all, 47
install_all_dependencies, 48

kurtosis, 49

logistic_reg_w_interaction, 53
logistic_regression, 50
logistic_regression_table, 52
loglinear_analysis, 54

mann_whitney, 56
matrix_prep_dt, 56
mediation_analysis, 57
merge_data_table_list, 60
merge_data_tables, 59
modes_of_objects, 61
multiple_regression, 62

noncentrality_parameter, 63

order_rows_specifically_in_dt, 64
outlier, 65
overlapping_interval, 66

p0, 67
parallel_analysis, 67
percentile_rank, 68
pivot_table, 69
plot_group_means, 70
pm, 72
population_variance, 72
prep, 73
pretty_round_p_value, 74
pretty_round_r, 75

print_loop_progress, 75
proportion_of_values_in_vector, 76

q_stat_test_homo_r, 78

read_csv, 78
read_sole_csv, 79
regex_match, 80
rel_pos_of_value_in_vector, 80
rel_value_of_pos_in_vector, 81
remove_from_vector, 82
remove_user_installed_pkgs, 82
repeated_measures_anova, 83
replace_values_in_dt, 84
robust_regression, 85
round_flexibly, 86

scatterplot, 87
score_scale_items, 90
se_of_mean, 92
setup_r_env, 91
setwd_to_active_doc, 91
simple_effects_analysis, 93
skewness, 94
spotlight_2_by_continuous, 95
standardized_regression, 100
start_kim, 102
su, 103

t_test_pairwise, 110
tabulate_vector, 104
theme_kim, 105
top_median_or_bottom, 106
tv, 107
two_way_anova, 108

und, 111
unload_user_installed_pkgs, 112
update_kim, 113

vlookup, 114

weighted_mean_r, 114
weighted_z, 115
wilcoxon_rank_sum_test, 116
write_csv, 117

z_to_r_transform, 117