

Package ‘mets’

January 17, 2023

Type Package

Title Analysis of Multivariate Event Times

Version 1.3.2

Date 2023-01-16

Author Klaus K. Holst [aut, cre],
Thomas Scheike [aut]

Maintainer Klaus K. Holst <klaus@holst.it>

Description Implementation of various statistical models for multivariate event history data <[doi:10.1007/s10985-013-9244-x](https://doi.org/10.1007/s10985-013-9244-x)>. Including multivariate cumulative incidence models <[doi:10.1002/sim.6016](https://doi.org/10.1002/sim.6016)>, and bivariate random effects probit models (Liability models) <[doi:10.1016/j.csda.2015.01.014](https://doi.org/10.1016/j.csda.2015.01.014)>. Also contains two-stage binomial modelling that can do pairwise odds-ratio dependence modelling based marginal logistic regression models. This is an alternative to the alternating logistic regression approach (ALR).

License GPL (>= 2)

LazyLoad yes

URL <https://kholst.github.io/mets/>

BugReports <https://github.com/kkholst/mets/issues>

Depends R (>= 3.5), timereg (>= 1.9.4)

Imports lava (>= 1.7.1), mvtnorm, numDeriv, compiler, Rcpp, splines,
survival (>= 2.43-1)

Suggests optimx, prodlim, cmprsk, testthat (>= 0.11), ucminf, knitr,
rmarkdown, ggplot2, cowplot, icenReg

VignetteBuilder knitr

ByteCompile yes

LinkingTo Rcpp, RcppArmadillo, mvtnorm

SystemRequirements C++11

Encoding UTF-8

RoxygenNote 7.2.3

NeedsCompilation yes

Repository CRAN

Date/Publication 2023-01-17 09:40:07 UTC

R topics documented:

mets-package	5
aalenfrailty	5
aalenMets	6
back2timereg	7
base1cumhaz	8
base44cumhaz	8
base4cumhaz	8
basehazplot.phreg	9
bicomprisk	10
BinAugmentCifstrata	12
binomial.twostage	14
binreg	19
binregATE	22
binregCasewise	24
biprobit	25
blocksample	27
bmt	28
Bootphreg	29
bptwin	30
casewise	32
casewise.test	33
cif	35
cifreg	36
ClaytonOakes	38
cluster.index	39
concordanceCor	40
cor.cif	42
count.history	46
covarianceRecurrent	48
daggregate	49
Dbvn	51
dby	51
dcor	53
dcut	54
dermalridges	56
dermalridgesMZ	57
diabetes	58
divide.conquer	58
divide.conquer.timereg	59
dlag	60
doubleFGR	61

dprint	63
drcumhaz	64
dreg	65
drelevel	68
dsort	70
dspline	70
dtable	72
dtransform	73
easy.binomial.twostage	74
easy.survival.twostage	78
Effbinreg	80
EVaddGam	82
eventpois	83
EventSplit	84
familycluster.index	86
familyclusterWithProbands.index	87
fast.approx	88
fast.pattern	89
fast.reshape	89
FG_AugmentCifstrata	92
ghaplos	94
gof.phreg	94
gofG.phreg	95
gofM.phreg	96
gofZ.phreg	98
Grandom.cif	99
hapfreqs	103
haplo.surv.discrete	103
haploX	106
interval.logitsurv.discrete	106
ipw	107
ipw2	109
km	111
lifecycle	112
lifetable.matrix	114
LinSpline	115
logitSurv	115
mediatorSurv	116
medweight	118
melanoma	118
mena	119
mets.options	120
migr	120
mlogit	121
multcif	122
np	122
npc	123
phreg	123

phregR	124
plack.cif	125
pmvn	125
predict.phreg	126
print.casewise	127
prob.exceed.recurrent	128
prt	130
random.cif	130
rchaz	133
rcrisk	134
recreg	135
recurrentMarginal	137
resmean.phreg	140
resmeanATE	141
resmeanIPCW	142
rpch	144
sim.cause.cox	145
sim.cif	146
sim.cox	147
simAalenFrailty	149
simClaytonOakes	150
simClaytonOakesWei	151
simMultistate	152
simRecurrent	154
simRecurrentII	155
simRecurrentTS	157
summary.cor	159
survival.iterative	160
survival.twostage	164
survival.twostageCC	169
survivalG	171
test.conc	172
tetrachoric	172
TRACE	173
tpd	174
twin.clustertrunc	174
twinbmi	175
twinlm	176
twinsim	178
twinstut	179
twostageMLE	180

mets-package

Analysis of Multivariate Events

Description

Implementation of various statistical models for multivariate event history data. Including multivariate cumulative incidence models, and bivariate random effects probit models (Liability models)

Author(s)

Klaus K. Holst and Thomas Scheike

Examples

```
## To appear
```

aalenfrailty

Aalen frailty model

Description

Additive hazards model with (gamma) frailty

Usage

```
aalenfrailty(time, status, X, id, theta, B = NULL, ...)
```

Arguments

time	Time variable
status	Status variable (0,1)
X	Covariate design matrix
id	cluster variable
theta	list of thetas (returns score evaluated here), or starting point for optimization (defaults to magic number 0.1)
B	(optional) Cumulative coefficients (update theta by fixing B)
...	Additional arguments to lower level functions

Details

Aalen frailty model

Value

Parameter estimates

Author(s)

Klaus K. Holst

Examples

```
library("timereg")
dd <- simAalenFrailty(5000)
f <- ~1##+x
X <- model.matrix(f,dd) ## design matrix for non-parametric terms
system.time(out<-timereg::aalen(update(f, Surv(time,status)~.),dd,n.sim=0,robust=0))
dix <- which(dd$status==1)
t1 <- system.time(bb <- .Call("Bhat",as.integer(dd$status),
                                X,0.2,as.integer(dd$id),NULL,NULL,
                                PACKAGE="mets"))

spec <- 1
##plot(out,spec=spec)
## plot(dd$time[dix],bb$B2[,spec],col="red",type="s",
##       ylim=c(0,max(dd$time)*c(beta0,beta)[spec]))
## abline(a=0,b=c(beta0,beta)[spec])
##'
##'

## Not run:
thetas <- seq(0.1,2,length.out=10)
Us <- unlist(aalenfrailty(dd$time,dd$status,X,dd$id,as.list(thetas)))
##plot(thetas,Us,type="l",ylim=c(-.5,1)); abline(h=0,lty=2); abline(v=theta,lty=2)
op <- aalenfrailty(dd$time,dd$status,X,dd$id)
op

## End(Not run)
```

Description

Fast Lin-Ying additive hazards model with a possibly stratified baseline. Robust variance is default variance with the summary.

Usage

```
aalenMets(formula, data = data, ...)
```

Arguments

formula	formula with 'Surv' outcome (see coxph)
data	data frame
...	Additional arguments to phreg

Details

influence functions (iid) will follow numerical order of given cluster variable so ordering after \$id will give iid in order of data-set.

Author(s)

Thomas Scheike

Examples

```
data(bmt); bmt$time <- bmt$time+runif(408)*0.001
out <- aalenMets(Surv(time,cause==1)~tcell+platelet+age,data=bmt)
summary(out)

## out2 <- timereg::aalen(Surv(time,cause==1)~const(tcell)+const(platelet)+const(age),data=bmt)
## summary(out2)
```

back2timereg

Convert to timereg object

Description

convert to timereg object

Usage

```
back2timereg(obj)
```

Arguments

obj	no use
-----	--------

Author(s)

Thomas Scheike

base1cumhaz *rate of CRBSI for HPN patients of Copenhagen*

Description

rate of CRBSI for HPN patients of Copenhagen

Source

Estimated data

base44cumhaz *rate of Occlusion/Thrombosis complication for catheter of HPN patients of Copenhagen*

Description

rate of Occlusion/Thrombosis complication for catheter of HPN patients of Copenhagen

Source

Estimated data

base4cumhaz *rate of Mechanical (hole/defect) complication for catheter of HPN patients of Copenhagen*

Description

rate of Mechanical (hole/defect) complication for catheter of HPN patients of Copenhagen

Source

Estimated data

basehazplot.phreg *Plotting the baslines of stratified Cox*

Description

Plotting the baslines of stratified Cox

Usage

```
basehazplot.phreg(  
  x,  
  se = FALSE,  
  time = NULL,  
  add = FALSE,  
  ylim = NULL,  
  xlim = NULL,  
  lty = NULL,  
  col = NULL,  
  lwd = NULL,  
  legend = TRUE,  
  ylab = NULL,  
  xlab = NULL,  
  polygon = TRUE,  
  level = 0.95,  
  stratas = NULL,  
  robust = FALSE,  
  conf.type = c("plain", "log"),  
  ...  
)
```

Arguments

x	phreg object
se	to include standard errors
time	to plot for specific time variables
add	to add to previous plot
ylim	to give ylim
xlim	to give xlim
lty	to specify lty of components
col	to specify col of components
lwd	to specify lwd of components
legend	to specify col of components
ylab	to specify ylab
xlab	to specify xlab

<code>polygon</code>	to get standard error in shaded form
<code>level</code>	of standard errors
<code>stratas</code>	which strata to plot
<code>robust</code>	to use robust standard errors if possible
<code>conf.type</code>	"plain" or "log" transformed
<code>...</code>	Additional arguments to lower level functions

Author(s)

Klaus K. Holst, Thomas Scheike

Examples

```
data(TRACE)
dcut(TRACE) <- ~.
out1 <- phreg(Surv(time,status==9)~vf+chf+strata(wmicat.4),data=TRACE)

par(mfrow=c(2,2))
bplot(out1)
bplot(out1,stratas=c(0,3))
bplot(out1,stratas=c(0,3),col=2:3,lty=1:2,se=TRUE)
bplot(out1,stratas=c(0),col=2,lty=2,se=TRUE,polygon=FALSE)
bplot(out1,stratas=c(0),col=matrix(c(2,1,3),1,3),lty=matrix(c(1,2,3),1,3),se=TRUE,polygon=FALSE)
```

Description

Estimation of concordance in bivariate competing risks data

Usage

```
bicomprisk(
  formula,
  data,
  cause = c(1, 1),
  cens = 0,
  causes,
  indiv,
  strata = NULL,
  id,
  num,
  max.clust = 1000,
  marg = NULL,
  se.clusters = NULL,
  wname = NULL,
```

```

    prodlim = FALSE,
    messages = TRUE,
    model,
    return.data = 0,
    uniform = 0,
    conservative = 1,
    resample.iid = 1,
    ...
)

```

Arguments

formula	Formula with left-hand-side being a Event object (see example below) and the left-hand-side specifying the covariate structure
data	Data frame
cause	Causes (default (1,1)) for which to estimate the bivariate cumulative incidence
cens	The censoring code
causes	causes
indiv	indiv
strata	Strata
id	Clustering variable
num	num
max.clust	max number of clusters in timereg::comp.risk call for iid decomposition, max.clust=NULL uses all clusters otherwise rougher grouping.
marg	marginal cumulative incidence to make standard errors for same clusters for subsequent use in casewise.test()
se.clusters	to specify clusters for standard errors. Either a vector of cluster indices or a column name in data. Defaults to the id variable.
wname	name of additional weight used for paired competing risks data.
prodlim	prodlim to use prodlim estimator (Aalen-Johansen) rather than IPCW weighted estimator based on comp.risk function. These are equivalent in the case of no covariates. These estimators are the same in the case of stratified fitting.
messages	Control amount of output
model	Type of competing risk model (default is Fine-Gray model "fg", see comp.risk).
return.data	Should data be returned (skipping modeling)
uniform	to compute uniform standard errors for concordance estimates based on resampling.
conservative	for conservative standard errors, recommended for larger data-sets.
resample.iid	to return iid residual processes for further computations such as tests.
...	Additional arguments to timereg::comp.risk function

Author(s)

Thomas Scheike, Klaus K. Holst

References

Scheike, T. H.; Holst, K. K. & Hjelmborg, J. B. Estimating twin concordance for bivariate competing risks twin data Statistics in Medicine, Wiley Online Library, 2014 , 33 , 1193-204

Examples

```
library("timereg")

## Simulated data example
prt <- simnordic.random(2000,delayed=TRUE,ptrunc=0.7,
                      cordz=0.5,cormz=2,lambda=0.3)
## Bivariate competing risk, concordance estimates
p11 <- bicomprisk(Event(time,cause)~strata(zyg)+id(id),data=prt,cause=c(1,1))

p11mz <- p11$model$"MZ"
p11dz <- p11$model$"DZ"
par(mfrow=c(1,2))
## Concordance
plot(p11mz,ylim=c(0,0.1));
plot(p11dz,ylim=c(0,0.1));

## entry time, truncation weighting
### other weighting procedure
prt1 <- prt[!prt$truncated,]
prt2 <- ipw2(prt1,cluster="id",same.cens=TRUE,
             time="time",cause="cause",entrytime="entry",
             pairs=TRUE,strata="zyg",obs.only=TRUE)

prt22 <- fast.reshape(prt2,id="id")

prt22$event <- (prt22$cause1==1)*(prt22$cause2==1)*1
prt22$timel <- pmax(prt22$time1,prt22$time2)
ipwc <- timereg::comp.risk(Event(timel,event)~-1+factor(zyg1),
                           data=prt22,cause=1,n.sim=0,model="rcif2",times=50:90,
                           weights=prt22$weights1,cens.weights=rep(1,nrow(prt22)))

p11wmz <- ipwc$cum[,2]
p11wdz <- ipwc$cum[,3]
lines(ipwc$cum[,1],p11wmz,col=3)
lines(ipwc$cum[,1],p11wdz,col=3)
```

Description

Computes the augmentation term for each individual as well as the sum

$$A = \int_0^t H(u, X) \frac{1}{S^*(u, s)} \frac{1}{G_c(u)} dM_c(u)$$

with

$$H(u, X) = F_1^*(t, s) - F_1^*(u, s)$$

using a KM for

$$G_c(t)$$

and a working model for cumulative baseline related to

$$F_1^*(t, s)$$

and

$$s$$

is strata,

$$S^*(t, s) = 1 - F_1^*(t, s) - F_2^*(t, s)$$

.

Usage

```
BinAugmentCifstrata(
  formula,
  data = data,
  cause = 1,
  cens.code = 0,
  km = TRUE,
  time = NULL,
  weights = NULL,
  offset = NULL,
  ...
)
```

Arguments

<code>formula</code>	formula with 'Event', strata model for CIF given by strata, and strataC specifies censoring strata
<code>data</code>	data frame
<code>cause</code>	of interest
<code>cens.code</code>	code of censoring
<code>km</code>	to use Kaplan-Meier
<code>time</code>	of interest
<code>weights</code>	weights for estimating equations
<code>offset</code>	offsets for logistic regression
<code>...</code>	Additional arguments to binreg function.

Details

Standard errors computed under assumption of correct

$$G_c(s)$$

model.

Author(s)

Thomas Scheike

Examples

```
data(bmt)
dcut(bmt,breaks=2) <- ~age
out1<-BinAugmentCifstrata(Event(time,cause)~platelet+agecat.2+
  strata(platelet,agecat.2),data=bmt,cause=1,time=40)
summary(out1)

out2<-BinAugmentCifstrata(Event(time,cause)~platelet+agecat.2+
  strata(platelet,agecat.2)+strataC(platelet),data=bmt,cause=1,time=40)
summary(out2)
```

binomial.twostage

Fits Clayton-Oakes or bivariate Plackett (OR) models for binary data using marginals that are on logistic form. If clusters contain more than two times, the algorithm uses a compososite likelihood based on all pairwise bivariate models.

Description

The pairwise pairwise odds ratio model provides an alternative to the alternating logistic regression (ALR).

Usage

```
binomial.twostage(
  margbin,
  data = parent.frame(),
  method = "nr",
  detail = 0,
  clusters = NULL,
  silent = 1,
  weights = NULL,
  theta = NULL,
  theta.des = NULL,
  var.link = 0,
  var.par = 1,
```

```

var.func = NULL,
iid = 1,
notaylor = 1,
model = "plackett",
marginal.p = NULL,
beta.iid = NULL,
Dbeta.iid = NULL,
strata = NULL,
max.clust = NULL,
se.clusters = NULL,
numDeriv = 0,
random.design = NULL,
pairs = NULL,
dim.theta = NULL,
additive.gamma.sum = NULL,
pair.ascertained = 0,
case.control = 0,
no.opt = FALSE,
twostage = 1,
beta = NULL,
...
)

```

Arguments

<code>margbin</code>	Marginal binomial model
<code>data</code>	data frame
<code>method</code>	Scoring method "nr", for lava NR optimizer
<code>detail</code>	Detail
<code>clusters</code>	Cluster variable
<code>silent</code>	Debug information
<code>weights</code>	Weights for log-likelihood, can be used for each type of outcome in 2x2 tables.
<code>theta</code>	Starting values for variance components
<code>theta.des</code>	design for dependence parameters, when pairs are given the indeces of the theta-design for this pair, is given in pairs as column 5
<code>var.link</code>	Link function for variance
<code>var.par</code>	parametrization
<code>var.func</code>	when alternative parametrizations are used this function can specify how the paramters are related to the λ_j 's.
<code>iid</code>	Calculate i.i.d. decomposition when iid>=1, when iid=2 then avoids adding the uncertainty for marginal paramters for additive gamma model (default).
<code>notaylor</code>	Taylor expansion
<code>model</code>	model
<code>marginal.p</code>	vector of marginal probabilities

beta.iid	iid decomposition of marginal probability estimates for each subject, if based on GLM model this is computed.
Dbeta.iid	derivatives of marginal model wrt marginal parameters, if based on GLM model this is computed.
strata	strata for fitting: considers only pairs where both are from same strata
max.clust	max clusters
se.clusters	clusters for iid decomposition for robust standard errors
numDeriv	uses Fisher scoring approx of second derivative if 0, otherwise numerical derivatives
random.design	random effect design for additive gamma model, when pairs are given the indeces of the pairs random.design rows are given as columns 3:4
pairs	matrix with rows of indeces (two-columns) for the pairs considered in the pairwise composite score, useful for case-control sampling when marginal is known.
dim.theta	dimension of theta when pairs and pairs specific design is given. That is when pairs has 6 columns.
additive.gamma.sum	this is specification of the lamtot in the models via a matrix that is multiplied onto the parameters theta (dimensions=(number random effects x number of theta parameters), when null then sums all parameters. Default is a matrix of 1's
pair.ascertained	if pairs are sampled only when there are events in the pair i.e. Y1+Y2>=1.
case.control	if data is case control data for pair call, and here 2nd column of pairs are probands (cases or controls)
no.opt	for not optimizing
twostage	default twostage=1, to fit MLE use twostage=0
beta	is starting value for beta for MLE version
...	for NR of lava

Details

The reported standard errors are based on a cluster corrected score equations from the pairwise likelihoods assuming that the marginals are known. This gives correct standard errors in the case of the Odds-Ratio model (Plackett distribution) for dependence, but incorrect standard errors for the Clayton-Oakes types model (that is also called "gamma"-frailty). For the additive gamma version of the standard errors are adjusted for the uncertainty in the marginal models via an iid decomposition using the iid() function of lava. For the clayton oakes model that is not specified via the random effects these can be fixed subsequently using the iid influence functions for the marginal model, but typically this does not change much.

For the Clayton-Oakes version of the model, given the gamma distributed random effects it is assumed that the probabilities are independent, and that the marginal survival functions are on logistic form

$$\text{logit}(P(Y = 1|X)) = \alpha + x^T \beta$$

therefore conditional on the random effect the probability of the event is

$$\text{logit}(P(Y = 1|X, Z)) = \exp(-Z \cdot \text{Laplace}^{-1}(\text{lamtot}, \text{lamtot}, P(Y = 1|x)))$$

Can also fit a structured additive gamma random effects model, such the ACE, ADE model for survival data:

Now random.design specifies the random effects for each subject within a cluster. This is a matrix of 1's and 0's with dimension n x d. With d random effects. For a cluster with two subjects, we let the random.design rows be v_1 and v_2 . Such that the random effects for subject 1 is

$$v_1^T(Z_1, \dots, Z_d)$$

, for d random effects. Each random effect has an associated parameter $(\lambda_1, \dots, \lambda_d)$. By construction subjects 1's random effect are Gamma distributed with mean $\lambda_j/v_1^T\lambda$ and variance $\lambda_j/(v_1^T\lambda)^2$. Note that the random effect $v_1^T(Z_1, \dots, Z_d)$ has mean 1 and variance $1/(v_1^T\lambda)$. It is here assumed that $lamtot = v_1^T\lambda$ is fixed over all clusters as it would be for the ACE model below.

The DEFAULT parametrization uses the variances of the random effects (var.par=1)

$$\theta_j = \lambda_j/(v_1^T\lambda)^2$$

For alternative parametrizations (var.par=0) one can specify how the parameters relate to λ_j with the function

Based on these parameters the relative contribution (the heritability, h) is equivalent to the expected values of the random effects $\lambda_j/v_1^T\lambda$

Given the random effects the probabilities are independent and on the form

$$\text{logit}(P(Y = 1|X)) = \exp(-\text{Laplace}^{-1}(\text{lamtot}, \text{lamtot}, P(Y = 1|x)))$$

with the inverse laplace of the gamma distribution with mean 1 and variance lamtot.

The parameters $(\lambda_1, \dots, \lambda_d)$ are related to the parameters of the model by a regression construction *pard* (d x k), that links the d λ parameters with the (k) underlying θ parameters

$$\lambda = \text{theta.des}\theta$$

here using theta.des to specify these low-dimension association. Default is a diagonal matrix.

Author(s)

Thomas Scheike

References

Two-stage binomial modelling

Examples

```
data(twinstut)
twinstut0 <- subset(twinstut, tvparnr<4000)
twinstut <- twinstut0
twinstut$binstut <- (twinstut$stutter=="yes")*1
theta.des <- model.matrix(~1+factor(zyg), data=twinstut)
margbin <- glm(binstut~factor(sex)+age, data=twinstut, family=binomial())
bin <- binomial.twostage(margbin, data=twinstut, var.link=1,
                        clusters=twinstut$tvparnr, theta.des=theta.des, detail=0)
```

```

summary(bin)

twinstut$cage <- scale(twinstut$age)
theta.des <- model.matrix( ~-1+factor(zyg)+cage,data=twinstut)
bina <- binomial.twostage(margbin,data=twinstut,var.link=1,
    clusters=twinstut$tvpnr,theta.des=theta.des)
summary(bina)

theta.des <- model.matrix( ~-1+factor(zyg)+factor(zyg)*cage,data=twinstut)
bina <- binomial.twostage(margbin,data=twinstut,var.link=1,
    clusters=twinstut$tvpnr,theta.des=theta.des)
summary(bina)

## Reduce Ex.Timings
## refers to zygosity of first subject in each pair : zyg1
## could also use zyg2 (since zyg2=zyg1 within twinpair's)
out <- easy.binomial.twostage(stutter~factor(sex)+age,data=twinstut,
    response="binstut",id="tvpnr",var.link=1,
    theta.formula=~-1+factor(zyg1))
summary(out)

## refers to zygosity of first subject in each pair : zyg1
## could also use zyg2 (since zyg2=zyg1 within twinpair's)
desfs<-function(x,num1="zyg1",num2="zyg2")
  c(x[num1]=="dz",x[num1]=="mz",x[num1]=="os")*1

out3 <- easy.binomial.twostage(binstut~factor(sex)+age,
    data=twinstut,response="binstut",id="tvpnr",var.link=1,
    theta.formula=desfs,desnames=c("mz","dz","os"))
summary(out3)

### use of clayton oakes binomial additive gamma model
#####
## Reduce Ex.Timings
data <- simbinClaytonOakes.family.ace(10000,2,1,beta=NULL,alpha=NULL)
margbin <- glm(ybin~x,data=data,family=binomial())
margbin

head(data)
data$number <- c(1,2,3,4)
data$child <- 1*(data$number==3)

### make ace random effects design
out <- ace.family.design(data,member="type",id="cluster")
out$pardes
head(out$des.rv)

bints <- binomial.twostage(margbin,data=data,
    clusters=data$cluster,detail=0,var.par=1,
    theta=c(2,1),var.link=0,
    random.design=out$des.rv,theta.des=out$pardes)
summary(bints)

```

```

data <- simbinClaytonOakes.twin.ace(10000,2,1,beta=NULL,alpha=NULL)
out <- twin.polygen.design(data,id="cluster",zygname="zygosity")
out$pardes
head(out$des.rv)
margbin <- glm(ybin~x,data=data,family=binomial())

bintwin <- binomial.twostage(margbin,data=data,
    clusters=data$cluster,var.par=1,
    theta=c(2,1),random.design=out$des.rv,theta.des=out$pardes)
summary(bintwin)
concordanceTwinACE(bintwin)

```

binreg*Binomial Regression for censored competing risks data***Description**

Simple version of comp.risk function of timereg for just one time-point thus fitting the model

$$P(T \leq t, \epsilon = 1 | X) = \text{expit}(X^T \beta)$$

Usage

```

binreg(
  formula,
  data,
  cause = 1,
  time = NULL,
  beta = NULL,
  offset = NULL,
  weights = NULL,
  cens.weights = NULL,
  cens.model = ~+1,
  se = TRUE,
  kaplan.meier = TRUE,
  cens.code = 0,
  no.opt = FALSE,
  method = "nr",
  augmentation = NULL,
  ...
)

```

Arguments

formula	formula with outcome (see coxph)
----------------	----------------------------------

data	data frame
cause	cause of interest (numeric variable)
time	time of interest
beta	starting values
offset	offsets for partial likelihood
weights	for score equations
cens.weights	censoring weights
cens.model	only stratified cox model without covariates
se	to compute se's based on IPCW
kaplan.meier	uses Kaplan-Meier for IPCW in contrast to exp(-Baseline)
cens.code	gives censoring code
no.opt	to not optimize
method	for optimization
augmentation	to augment binomial regression
...	Additional arguments to lower level funtions

Details

Based on binomial regresion IPCW response estimating equation:

$$X(\Delta I(T \leq t, \epsilon = 1)/G_c(T_i-) - \text{expit}(X^T \beta)) = 0$$

for IPCW adjusted responses.

logitIPCW instead considers

$$XI(\min(T_i, t) < G_i)/G_c(\min(T_i, t))(I(T \leq t, \epsilon = 1) - \text{expit}(X^T \beta)) = 0$$

a standard logistic regression with weights that adjust for IPCW.

variance is based on

$$\sum w_i^2$$

also with IPCW adjustment, and naive.var is variance under known censoring model.

Censoring model may depend on strata.

Author(s)

Thomas Scheike

Examples

```
data(bmt)
# logistic regresion with IPCW binomial regression
out <- binreg(Event(time,cause)~tcell+platelet,bmt,time=50)
summary(out)
predict(out,data.frame(tcell=c(0,1),platelet=c(1,1)),se=TRUE)
```

```

outs <- binreg(Event(time,cause)~tcell+platelet,bmt,time=50,cens.model=~strata(tcell,platelet))
summary(outs)

## glm with IPCW weights
outl <- logitIPCW(Event(time,cause)~tcell+platelet,bmt,time=50)
summary(outl)

#####
### risk-ratio of different causes #####
#####
data(bmt)
bmt$id <- 1:nrow(bmt)
bmt$status <- bmt$cause
bmt$strata <- 1
bmtdob <- bmt
bmtdob$strata <-2
bmtdob <- dtransform(bmtdob,status=1,cause==2)
bmtdob <- dtransform(bmtdob,status=2,cause==1)
###
bmtdob <- rbind(bmt,bmtdob)
dtable(bmtdob,cause+status~strata)

cif1 <- cif(Event(time,cause)~+1,bmt,cause=1)
cif2 <- cif(Event(time,cause)~+1,bmt,cause=2)
bplot(cif1)
bplot(cif2,add=TRUE,col=2)

cifs1 <- binreg(Event(time,cause)~tcell+platelet+age,bmt,cause=1,time=50)
cifs2 <- binreg(Event(time,cause)~tcell+platelet+age,bmt,cause=2,time=50)
summary(cifs1)
summary(cifs2)

cifdob <- binreg(Event(time,status)~-1+factor(strata)+  

  tcell*factor(strata)+platelet*factor(strata)+age*factor(strata)  

  +cluster(id),bmtdob,cause=1,time=50,cens.model=~strata(strata)+cluster(id))
summary(cifdob)

expit <- function(z) 1/(1+exp(-z))

riskratio <- function(p) {
  expit <- function(z) 1/(1+exp(-z)) ## expit
  Z <- rbind(c(1,0,1,1,0,0,0,0), c(0,1,1,1,0,1,1,0))
  lp <- c(Z %*% p)
  p <- expit(lp)
  return(p[1]/p[2])
}

lava::estimate(cifdob,f=riskratio)

```

binregATE*Average Treatment effect for censored competing risks data using Bi-nomial Regression*

Description

Under the standard causal assumptions we can estimate the average treatment effect $E(Y(1) - Y(0))$. We need Consistency, ignorability ($Y(1), Y(0)$ indep A given X), and positivity.

Usage

```
binregATE(
  formula,
  data,
  cause = 1,
  time = NULL,
  beta = NULL,
  treat.model = ~+1,
  cens.model = ~+1,
  offset = NULL,
  weights = NULL,
  cens.weights = NULL,
  se = TRUE,
  kaplan.meier = TRUE,
  cens.code = 0,
  no.opt = FALSE,
  method = "nr",
  augmentation = NULL,
  outcome = c("cif", "rmst", "rmst-cause"),
  model = "exp",
  Ydirect = NULL,
  ...
)
```

Arguments

formula	formula with outcome (see coxph)
data	data frame
cause	cause of interest
time	time of interest
beta	starting values
treat.model	logistic treatment model given covariates
cens.model	only stratified cox model without covariates
offset	offsets for partial likelihood
weights	for score equations

cens.weights	censoring weights
se	to compute se's with IPCW adjustment, otherwise assumes that IPCW weights are known
kaplan.meier	uses Kaplan-Meier for IPCW in contrast to exp(-Baseline)
cens.code	gives censoring code
no.opt	to not optimize
method	for optimization
augmentation	to augment binomial regression
outcome	can do CIF regression "cif"=F(t X), "rmst"=E(min(T, t) X) , or "rmst-cause"=E(I(epsilon==cause) (t - mint(T,t)) X)
model	possible exp model for E(min(T, t) X)=exp(X^t beta) , or E(I(epsilon==cause) (t - mint(T,t)) X)=exp(X^t beta)
Ydirect	use this Y for fitting G model set outcome to "rmst" to fit using the model specified by model
...	Additional arguments to lower level funtions

Details

The first covariate in the specification of the competing risks regression model must be the treatment effect that is a factor. If the factor has more than two levels then it uses the mlogit for propensity score modelling. If there are no censorings this is the same as ordinary logistic regression modelling.

Estimates the ATE using the the standard binary double robust estimating equations that are IPCW censoring adjusted. Rather than binomial regression we also consider a IPCW weighted version of standard logistic regression logitIPCWATE.

The original version of the program with only binary treatment binregATEbin take binary-numeric as input for the treatment, and also computes the ATT and ATC, average treatment effect on the treated (ATT), $E(Y(1) - Y(0) | A=1)$, and non-treated, respectively. Experimental version.

Author(s)

Thomas Scheike

Examples

```

data(bmt)
dfactor(bmt) <- ~.

brs <- binregATE(Event(time,cause)~tcell.f+platelet+age,bmt,time=50,cause=1,
  treat.model=tcell.f~platelet+age)
summary(brs)

brsi <- binregATE(Event(time,cause)~tcell.f+tcell.f*platelet+tcell.f*age,bmt,time=50,cause=1,
  treat.model=tcell.f~platelet+age)
summary(brsi)

```

<code>binregCasewise</code>	<i>Estimates the casewise concordance based on Concordance and marginal estimate using binreg</i>
-----------------------------	---------------------------------------------------------------------------------------------------

Description

Estimates the casewise concordance based on Concordance and marginal estimate using binreg

Usage

```
binregCasewise(concbreg, margbreg, zygs = c("DZ", "MZ"), newdata = NULL, ...)
```

Arguments

<code>concbreg</code>	Concordance
<code>margbreg</code>	Marginal estimate
<code>zygs</code>	order of zygosity for estimation of concordance and casewise.
<code>newdata</code>	to give instead of zygs.
<code>...</code>	to pass to estimate function

Details

Uses cluster iid for the two binomial-regression estimates standard errors better than those of case-wise that are often conservative.

Author(s)

Thomas Scheike

Examples

```
data(prt)
prt <- force.same.cens(prt,cause="status")

dd <- bicompriskData(Event(time, status)~strata(zyg)+id(id), data=prt, cause=c(2, 2))
newdata <- data.frame(zyg=c("DZ","MZ"),id=1)

## concordance
bcif1 <- binreg(Event(time,status)~-1+factor(zyg)+cluster(id), data=dd,
                 time=80, cause=1, cens.model=~strata(zyg))
pconc <- predict(bcif1,newdata)

## marginal estimates
mbcif1 <- binreg(Event(time,status)~cluster(id), data=prt, time=80, cause=2)
mc <- predict(mbcif1,newdata)
mc

cse <- binregCasewise(bcif1,mbcif1)
cse
```

<code>biprobit</code>	<i>Bivariate Probit model</i>
-----------------------	-------------------------------

Description

Bivariate Probit model

Usage

```
biprobit(
  x,
  data,
  id,
  rho = ~1,
  num = NULL,
  strata = NULL,
  eqmarg = TRUE,
  indep = FALSE,
  weights = NULL,
  weights.fun = function(x) ifelse(any(x <= 0), 0, max(x)),
  randomeffect = FALSE,
  vcov = "robust",
  pairs.only = FALSE,
  allmarg = !is.null(weights),
  control = list(trace = 0),
  messages = 1,
  constrain = NULL,
  table = pairs.only,
  p = NULL,
  ...
)
```

Arguments

<code>x</code>	formula (or vector)
<code>data</code>	<code>data.frame</code>
<code>id</code>	The name of the column in the dataset containing the cluster id-variable.
<code>rho</code>	Formula specifying the regression model for the dependence parameter
<code>num</code>	Optional name of order variable
<code>strata</code>	Strata
<code>eqmarg</code>	If TRUE same marginals are assumed (exchangeable)
<code>indep</code>	Independence
<code>weights</code>	Weights
<code>weights.fun</code>	Function defining the bivariate weight in each cluster

<code>randomeffect</code>	If TRUE a random effect model is used (otherwise correlation parameter is estimated allowing for both negative and positive dependence)
<code>vcov</code>	Type of standard errors to be calculated
<code>pairs.only</code>	Include complete pairs only?
<code>allmarg</code>	Should all marginal terms be included
<code>control</code>	Control argument parsed on to the optimization routine. Starting values may be parsed as 'start'.
<code>messages</code>	Control amount of messages shown
<code>constrain</code>	Vector of parameter constraints (NA where free). Use this to set an offset.
<code>table</code>	Type of estimation procedure
<code>p</code>	Parameter vector p in which to evaluate log-Likelihood and score function
<code>...</code>	Optional arguments

Examples

```

data(prt)
prt0 <- subset(prt,country=="Denmark")
a <- biprobit(cancer~1+zyg, ~1+zyg, data=prt0, id="id")
b <- biprobit(cancer~1+zyg, ~1+zyg, data=prt0, id="id",pairs.only=TRUE)
predict(b,newdata=lava::Expand(prt,zyg=c("MZ")))
predict(b,newdata=lava::Expand(prt,zyg=c("MZ","DZ")))

## Reduce Ex.Timings
n <- 2e3
x <- sort(runif(n, -1, 1))
y <- rmvn(n, c(0,0), rho=cbind(tanh(x)))>0
d <- data.frame(y1=y[,1], y2=y[,2], x=x)
dd <- fast.reshape(d)

a <- biprobit(y~1+x,rho=~1+x,data=dd,id="id")
summary(a, mean.contrast=c(1,.5), cor.contrast=c(1,.5))
with(predict(a,data.frame(x=seq(-1,1,by=.1))), plot(p00~x,type="l"))

pp <- predict(a,data.frame(x=seq(-1,1,by=.1)),which=c(1))
plot(pp[,1]~pp$x, type="l", xlab="x", ylab="Concordance", lwd=2, xaxs="i")
lava::confband(pp$x,pp[,2],pp[,3],polygon=TRUE,lty=0,col=lava::Col(1))

pp <- predict(a,data.frame(x=seq(-1,1,by=.1)),which=c(9)) ## rho
plot(pp[,1]~pp$x, type="l", xlab="x", ylab="Correlation", lwd=2, xaxs="i")
lava::confband(pp$x,pp[,2],pp[,3],polygon=TRUE,lty=0,col=lava::Col(1))
with(pp, lines(x,tanh(-x),lwd=2,lty=2))

xp <- seq(-1,1,length.out=6); delta <- mean(diff(xp))
a2 <- biprobit(y~1+x,rho=~1+I(cut(x,breaks=xp)),data=dd,id="id")
pp2 <- predict(a2,data.frame(x=xp[-1]-delta/2),which=c(9)) ## rho
lava::confband(pp2$x,pp2[,2],pp2[,3],center=pp2[,1])

```

```

## Time
## Not run:
  a <- biprobit.time(cancer~1, rho=~1+zyg, id="id", data=prt, eqmarg=TRUE,
                      cens.formula=Surv(time,status==0)~1,
                      breaks=seq(75,100,by=3),fix.censweights=TRUE)

  a <- biprobit.time2(cancer~1+zyg, rho=~1+zyg, id="id", data=prt0, eqmarg=TRUE,
                      cens.formula=Surv(time,status==0)~zyg,
                      breaks=100)

#a1 <- biprobit.time2(cancer~1, rho=~1, id="id", data=subset(prt0,zyg=="MZ"), eqmarg=TRUE,
#                      #           cens.formula=Surv(time,status==0)~1,
#                      #           breaks=100,pairs.only=TRUE)

#a2 <- biprobit.time2(cancer~1, rho=~1, id="id", data=subset(prt0,zyg=="DZ"), eqmarg=TRUE,
#                      #           cens.formula=Surv(time,status==0)~1,
#                      #           breaks=100,pairs.only=TRUE)

## End(Not run)

```

blocksample

Block sampling

Description

Sample blockwise from clustered data

Usage

```
blocksample(data, size, idvar = NULL, replace = TRUE, ...)
```

Arguments

<code>data</code>	Data frame
<code>size</code>	Size of samples
<code>idvar</code>	Column defining the clusters
<code>replace</code>	Logical indicating whether to sample with replacement
<code>...</code>	additional arguments to lower level functions

Details

Original id is stored in the attribute 'id'

Value

`data.frame`

Author(s)

Klaus K. Holst

Examples

```
d <- data.frame(x=rnorm(5), z=rnorm(5), id=c(4,10,10,5,5), v=rnorm(5))
(dd <- blocksample(d,size=20,~id))
attributes(dd)$id

## Not run:
blocksample(data.table::data.table(d),1e6,~id)

## End(Not run)

d <- data.frame(x=c(1,rnorm(9)),
                 z=rnorm(10),
                 id=c(4,10,10,5,5,4,4,5,10,5),
                 id2=c(1,1,2,1,2,1,1,1,1,2),
                 v=rnorm(10))
dsample(d,~id, size=2)
dsample(d,.~id+id2)
dsample(d,x+z~id|x>0,size=5)
```

Description

Bone marrow transplant data with 408 rows and 5 columns.

Format

The data has 408 rows and 5 columns.

cause a numeric vector code. Survival status. 1: dead from treatment related causes, 2: relapse , 0: censored.

time a numeric vector. Survival time.

platelet a numeric vector code. Platelet 1: more than 100×10^9 per L, 0: less.

tcell a numeric vector. T-cell depleted BMT 1:yes, 0:no.

age a numeric vector code. Age of patient, scaled and centered ((age-35)/15).

Source

Simulated data

References

NN

Examples

```
data(bmt)
names(bmt)
```

Bootphreg

*Wild bootstrap for Cox PH regression***Description**

wild bootstrap for uniform bands for Cox models

Usage

```
Bootphreg(
  formula,
  data,
  offset = NULL,
  weights = NULL,
  B = 1000,
  type = c("exp", "poisson", "normal"),
  ...
)
```

Arguments

formula	formula with 'Surv' outcome (see coxph)
data	data frame
offset	offsets for cox model
weights	weights for Cox score equations
B	bootstraps
type	distribution for multiplier
...	Additional arguments to lower level funtions

Author(s)

Klaus K. Holst, Thomas Scheike

References

Wild bootstrap based confidence intervals for multiplicative hazards models, Dobler, Pauly, and Scheike (2018),

Examples

```

n <- 100
x <- 4*rnorm(n)
time1 <- 2*rexp(n)/exp(x*0.3)
time2 <- 2*rexp(n)/exp(x*(-0.3))
status <- ifelse(time1<time2,1,2)
time <- pmin(time1,time2)
rbin <- rbinom(n,1,0.5)
cc <- rexp(n)*(rbin==1)+(rbin==0)*rep(3,n)
status <- ifelse(time < cc,status,0)
time <- ifelse(time < cc,time,cc)
data <- data.frame(time=time,status=status,x=x)

b1 <- Bootphreg(Surv(time,status==1)~x,data,B=1000)
b2 <- Bootphreg(Surv(time,status==2)~x,data,B=1000)
c1 <- phreg(Surv(time,status==1)~x,data)
c2 <- phreg(Surv(time,status==2)~x,data)

### exp to make all bootstraps positive
out <- pred.cif.boot(b1,b2,c1,c2,gplot=0)

cif.true <- (1-exp(-out$time))*.5
with(out,plot(time,cif,ylim=c(0,1),type="l"))
lines(out$time,cif.true,col=3)
with(out,plotConfRegion(time,band.EE,col=1))
with(out,plotConfRegion(time,band.EE.log,col=3))
with(out,plotConfRegion(time,band.EE.log.o,col=2))

```

Description

Liability-threshold model for twin data

Usage

```

bptwin(
  x,
  data,
  id,
  zyg,
  DZ,
  group = NULL,
  num = NULL,
  weights = NULL,
  weights.fun = function(x) ifelse(any(x <= 0), 0, max(x)),

```

```

strata = NULL,
messages = 1,
control = list(trace = 0),
type = "ace",
eqmean = TRUE,
pairs.only = FALSE,
samecens = TRUE,
allmarg = samecens & !is.null(weights),
stderr = TRUE,
robustvar = TRUE,
p,
indiv = FALSE,
constrain,
varlink,
...
)

```

Arguments

x	Formula specifying effects of covariates on the response.
data	data.frame with one observation pr row. In addition a column with the zygosity (DZ or MZ given as a factor) of each individual must be specified as well as a twin id variable giving a unique pair of numbers/factors to each twin pair.
id	The name of the column in the dataset containing the twin-id variable.
zyg	The name of the column in the dataset containing the zygosity variable.
DZ	Character defining the level in the zyg variable corresponding to the dyzogotic twins.
group	Optional. Variable name defining group for interaction analysis (e.g., gender)
num	Optional twin number variable
weights	Weight matrix if needed by the chosen estimator (IPCW)
weights.fun	Function defining a single weight each individual/cluster
strata	Strata
messages	Control amount of messages shown
control	Control argument parsed on to the optimization routine. Starting values may be parsed as 'start'.
type	Character defining the type of analysis to be performed. Should be a subset of "acde" (additive genetic factors, common environmental factors, dominant genetic factors, unique environmental factors).
eqmean	Equal means (with type="cor")?
pairs.only	Include complete pairs only?
samecens	Same censoring
allmarg	Should all marginal terms be included
stderr	Should standard errors be calculated?

robustvar	If TRUE robust (sandwich) variance estimates of the variance are used
p	Parameter vector p in which to evaluate log-Likelihood and score function
indiv	If TRUE the score and log-Likelihood contribution of each twin-pair
constrain	Development argument
varlink	Link function for variance parameters
...	Additional arguments to lower level functions

Author(s)

Klaus K. Holst

See Also

[twinlm](#), [twinlm.time](#), [twinlm.strata](#), [twinsim](#)

Examples

```
data(twinstut)
b0 <- bptwin(stutter~sex,
               data=droplevels(subset(twinstut, zyg%in%c("mz", "dz"))),
               id="tvparnr", zyg="zyg", DZ="dz", type="ae")
summary(b0)
```

casewise	<i>Estimates the casewise concordance based on Concordance and marginal estimate using prodlim but no testing</i>
-----------------	-------------------------------------------------------------------------------------------------------------------

Description

.. content for description (no empty lines) ..

Usage

```
casewise(conc, marg, cause.marg)
```

Arguments

conc	Concordance
marg	Marginal estimate
cause.marg	specifies which cause that should be used for marginal cif based on prodlim

Author(s)

Thomas Scheike

Examples

```

## Reduce Ex.Timings
library(prodlim)
data(prt);
prt <- force.same.cens(prt,cause="status")

### marginal cumulative incidence of prostate cancer##
outm <- prodlim(Hist(time,status)~+1,data=prt)

times <- 60:100
cifmz <- predict(outm,cause=2,time=times,newdata=data.frame(zyg="MZ")) ## cause is 2 (second cause)
cifdz <- predict(outm,cause=2,time=times,newdata=data.frame(zyg="DZ"))

### concordance for MZ and DZ twins
cc <- bicompRisk(Event(time,status)~strata(zyg)+id(id),data=prt,cause=c(2,2),prodlim=TRUE)
cdz <- cc$model$"DZ"
cmz <- cc$model$"MZ"

cdz <- casewise(cdz,outm,cause.marg=2)
cmz <- casewise(cmz,outm,cause.marg=2)

plot(cmz,ci=NULL,ylim=c(0,0.5),xlim=c(60,100),legend=TRUE,col=c(3,2,1))
par(new=TRUE)
plot(cdz,ci=NULL,ylim=c(0,0.5),xlim=c(60,100),legend=TRUE)
summary(cdz)
summary(cmz)

```

casewise.test

Estimates the casewise concordance based on Concordance and marginal estimate using timereg and performs test for independence

Description

Estimates the casewise concordance based on Concordance and marginal estimate using timereg and performs test for independence

Usage

```
casewise.test(conc, marg, test = "no-test", p = 0.01)
```

Arguments

conc	Concordance
marg	Marginal estimate
test	Type of test for independence assumption. "conc" makes test on concordance scale and "case" means a test on the casewise concordance
p	check that marginal probability is greater at some point than p

Details

Uses cluster based conservative standard errors for marginal and sometimes only the uncertainty of the concordance estimates. This works prettely well, alternatively one can use also the functions Casewise for a specific time point

Author(s)

Thomas Scheike

Examples

```
## Reduce Ex.Timings
library("timereg")
data("prt", package="mets");
prt <- force.same.cens(prt, cause="status")

prt <- prt[which(prt$id %in% sample(unique(prt$id), 7500)),]
### marginal cumulative incidence of prostate cancer
times <- seq(60, 100, by=2)
outm <- timereg::comp.risk(Event(time, status)~+1, data=prt, cause=2, times=times)

cifmz <- predict(outm, X=1, uniform=0, resample.iid=1)
cifdz <- predict(outm, X=1, uniform=0, resample.iid=1)

### concordance for MZ and DZ twins
cc <- bicomprisk(Event(time, status)~strata(zyg)+id(id),
                  data=prt, cause=c(2,2))
cdz <- cc$model$"DZ"
cmz <- cc$model$"MZ"

### To compute casewise cluster argument must be passed on,
### here with a max of 100 to limit comp-time
outm <- timereg::comp.risk(Event(time, status)~+1, data=prt,
                            cause=2, times=times, max.clust=100)
cifmz <- predict(outm, X=1, uniform=0, resample.iid=1)
cc <- bicomprisk(Event(time, status)~strata(zyg)+id(id), data=prt,
                  cause=c(2,2), se.clusters=outm$clusters)
cdz <- cc$model$"DZ"
cmz <- cc$model$"MZ"

cdz <- casewise.test(cdz, cifmz, test="case") ## test based on casewise
cmz <- casewise.test(cmz, cifmz, test="conc") ## based on concordance

plot(cmz, ylim=c(0,0.7), xlim=c(60,100))
par(new=TRUE)
plot(cdz, ylim=c(0,0.7), xlim=c(60,100))

slope.process(cdz$casewise[,1], cdz$casewise[,2], iid=cdz$casewise.iid)

slope.process(cmz$casewise[,1], cmz$casewise[,2], iid=cmz$casewise.iid)
```

cif*Cumulative incidence with robust standard errors*

Description

Cumulative incidence with robust standard errors

Usage

```
cif(formula, data = data, cause = 1, cens.code = 0, ...)
```

Arguments

formula	formula with 'Surv' outcome (see coxph)
data	data frame
cause	NULL looks at all, otherwise specify which cause to consider
cens.code	censoring code "0" is default
...	Additional arguments to lower level funtions

Author(s)

Thomas Scheike

Examples

```
data(TRACE)
TRACE$cluster <- sample(1:100,1878,replace=TRUE)
out1 <- cif(Event(time,status)~+1,data=TRACE,cause=9)
out2 <- cif(Event(time,status)~+1+cluster(cluster),data=TRACE,cause=9)

out1 <- cif(Event(time,status)~strata(vf,chf),data=TRACE,cause=9)
out2 <- cif(Event(time,status)~strata(vf,chf)+cluster(cluster),data=TRACE,cause=9)

par(mfrow=c(1,2))
bplot(out1,se=TRUE)
bplot(out2,se=TRUE)
```

cifreg*CIF regression*

Description

CIF logistic for propodds=1 default CIF Fine-Gray (cloglog) regression for propodds=NULL

Usage

```
cifreg(
  formula,
  data = data,
  cause = 1,
  cens.code = 0,
  cens.model = ~1,
  weights = NULL,
  offset = NULL,
  Gc = NULL,
  propodds = 1,
  ...
)
```

Arguments

formula	formula with 'Event' outcome
data	data frame
cause	of interest
cens.code	code of censoring
cens.model	for stratified Cox model without covariates
weights	weights for FG score equations
offset	offsets for FG model
Gc	censoring weights for time argument, default is to calculate these with a Kaplan-Meier estimator, should then give G_c(T_i-)
propodds	1 is logistic model, NULL is fine-gray model
...	Additional arguments to lower level funtions

Details

For FG model:

$$\int (X - E) Y_1(t) w(t) dM_1$$

is computed and summed over clusters and returned multiplied with inverse of second derivative as iid.naive. Where

$$w(t) = G(t)(I(T_i \wedge t < C_i)/G_c(T_i \wedge t))$$

and

$$E(t) = S_1(t)/S_0(t)$$

and

$$S_j(t) = \sum X_i^j Y_{i1}(t) w_i(t) \exp(X_i^T \beta)$$

The iid decomposition of the beta's, however, also have a censoring term that is also computed and added to UUiid (still scaled with inverse second derivative)

$$\int (X - E) Y_1(t) w(t) dM_1 + \int q(s)/p(s) dM_c$$

and returned as iid

For logistic link standard errors are slightly to small since uncertainty from recursive baseline is not considered, so for smaller data-sets it is recommended to use the prop.odds.subdist of timereg that is also more efficient due to use of different weights for the estimating equations. Alternatively, one can also bootstrap the standard errors.

Author(s)

Thomas Scheike

Examples

```
## data with no ties
data(bmt, package="timereg")
bmt$time <- bmt$time+runif(nrow(bmt))*0.01
bmt$id <- 1:nrow(bmt)

## logistic link OR interpretation
ll=cifreg(Event(time,cause)~tcell+platelet+age, data=bmt, cause=1)
summary(ll)
plot(ll)
nd <- data.frame(tcell=c(1,0), platelet=0, age=0)
pll <- predict(ll, nd)
plot(pll)

## Fine-Gray model
fg=cifreg(Event(time,cause)~tcell+platelet+age, data=bmt, cause=1, propodds=NULL)
summary(fg)
plot(fg)
nd <- data.frame(tcell=c(1,0), platelet=0, age=0)
pfg <- predict(fg, nd)
plot(pfg)

sfg <- cifreg(Event(time,cause)~strata(tcell)+platelet+age, data=bmt, cause=1, propodds=NULL)
summary(sfg)
plot(sfg)

### predictions with CI based on iid decomposition of baseline and beta
fg <- cifreg(Event(time,cause)~tcell+platelet+age, data=bmt, cause=1, propodds=NULL, cox.prep=TRUE)
Biid <- IIDbaseline.cifreg(fg, time=20)
```

```
FGprediid(Biid,bmt[1:5,])
```

ClaytonOakes

Clayton-Oakes model with piece-wise constant hazards

Description

Clayton-Oakes frailty model

Usage

```
ClaytonOakes(
  formula,
  data = parent.frame(),
  cluster,
  var.formula = ~1,
  cuts = NULL,
  type = "piecewise",
  start,
  control = list(),
  var.invlink = exp,
  ...
)
```

Arguments

formula	formula specifying the marginal proportional (piecewise constant) hazard structure with the right-hand-side being a survival object (Surv) specifying the entry time (optional), the follow-up time, and event/censoring status at follow-up. The clustering can be specified using the special function cluster (see example below).
data	Data frame
cluster	Variable defining the clustering (if not given in the formula)
var.formula	Formula specifying the variance component structure (if not given via the cluster special function in the formula) using a linear model with log-link.
cuts	Cut points defining the piecewise constant hazard
type	when equal to two.stage , the Clayton-Oakes-Glidden estimator will be calculated via the timereg package
start	Optional starting values
control	Control parameters to the optimization routine
var.invlink	Inverse link function for variance structure model
...	Additional arguments

Author(s)

Klaus K. Holst

Examples

```

set.seed(1)
d <- subset(simClaytonOakes(500,4,2,1,stoptime=2,left=2),truncated)
e <- ClaytonOakes(survival::Surv(lefttime,time,status)~x+cluster(~1,cluster),
                   cuts=c(0,0.5,1,2),data=d)
e

d2 <- simClaytonOakes(500,4,2,1,stoptime=2,left=0)
d2$z <- rep(1,nrow(d2)); d2$z[d2$cluster%in%sample(d2$cluster,100)] <- 0
## Marginal=Cox Proportional Hazards model:
ts <- ClaytonOakes(survival::Surv(time,status)~timereg::prop(x)+cluster(~1,cluster),
                     data=d2,type="two.stage")
## Marginal=Aalens additive model:
ts2 <- ClaytonOakes(survival::Surv(time,status)~x+cluster(~1,cluster),
                      data=d2,type="two.stage")
## Marginal=Piecewise constant:
e2 <- ClaytonOakes(survival::Surv(time,status)~x+cluster(~-1+factor(z),cluster),
                     cuts=c(0,0.5,1,2),data=d2)
e2

e0 <- ClaytonOakes(survival::Surv(time,status)~cluster(~-1+factor(z),cluster),
                     cuts=c(0,0.5,1,2),data=d2)
ts0 <- ClaytonOakes(survival::Surv(time,status)~cluster(~1,cluster),
                      data=d2,type="two.stage")
plot(ts0)
plot(e0,add=TRUE)

e3 <- ClaytonOakes(survival::Surv(time,status)~x+cluster(~1,cluster),cuts=c(0,0.5,1,2),
                     data=d,var.invlink=identity)
e3

```

cluster.index

Finds subjects related to same cluster

Description

Finds subjects related to same cluster

Usage

```
cluster.index(
  clusters,
  index.type = FALSE,
  num = NULL,
```

```
Rindex = 0,
mat = NULL,
return.all = FALSE,
code.na = NA
)
```

Arguments

<code>clusters</code>	list of indeces
<code>index.type</code>	if TRUE then already list of integers of index.type
<code>num</code>	to get numbering according to num-type in separate columns
<code>Rindex</code>	index starts with 1, in C it is 0
<code>mat</code>	to return matrix of indeces
<code>return.all</code>	return all arguments
<code>code.na</code>	how to code missing values

Author(s)

Klaus Holst, Thomas Scheike

References

Cluster indeces

See Also

`familycluster.index` `familyclusterWithProbands.index`

Examples

```
i<-c(1,1,2,2,1,3)
d<- cluster.index(i)
print(d)

type<-c("m","f","m","c","c","c")
d<- cluster.index(i,num=type,Rindex=1)
print(d)
```

Description

Concordance for Twins

Usage

```
concordanceCor(
  object,
  cif1,
  cif2 = NULL,
  messages = TRUE,
  model = NULL,
  coefs = NULL,
  ...
)
```

Arguments

<code>object</code>	Output from the cor.cif, rr.cif or or.cif function
<code>cif1</code>	Marginal cumulative incidence
<code>cif2</code>	Marginal cumulative incidence of other cause (cause2) if it is different from cause1
<code>messages</code>	To print messages
<code>model</code>	Specifies which model that is considered if object not given.
<code>coefs</code>	Specifies dependence parameters if object is not given.
<code>...</code>	Extra arguments, not used.

Details

The concordance is the probability that both twins have experienced the event of interest and is defined as

$$\text{cor}(t) = P(T_1 \leq t, \epsilon_1 = 1, T_2 \leq t, \epsilon_2 = 1)$$

Similarly, the casewise concordance is

$$\text{casewise}(t) = \frac{\text{cor}(t)}{P(T_1 \leq t, \epsilon_1 = 1)}$$

that is the probability that twin "2" has the event given that twins "1" has.

Author(s)

Thomas Scheike

References

Estimating twin concordance for bivariate competing risks twin data Thomas H. Scheike, Klaus K. Holst and Jacob B. Hjelmborg, Statistics in Medicine 2014, 1193-1204

Estimating Twin Pair Concordance for Age of Onset. Thomas H. Scheike, Jacob V B Hjelmborg, Klaus K. Holst, 2015 in Behavior genetics DOI:10.1007/s10519-015-9729-3

cor.cif

Cross-odds-ratio, OR or RR risk regression for competing risks

Description

Fits a parametric model for the log-cross-odds-ratio for the predictive effect of for the cumulative incidence curves for T_1 experiencing cause i given that T_2 has experienced a cause k :

$$\log(COR(i|k)) = h(\theta, z_1, i, z_2, k, t) =_{\text{default}} \theta^T z =$$

with the log cross odds ratio being

$$COR(i|k) = \frac{O(T_1 \leq t, \text{cause}_1 = i | T_2 \leq t, \text{cause}_2 = k)}{O(T_1 \leq t, \text{cause}_1 = i)}$$

the conditional odds divided by the unconditional odds, with the odds being, respectively

$$O(T_1 \leq t, \text{cause}_1 = i | T_2 \leq t, \text{cause}_1 = k) = \frac{P_x(T_1 \leq t, \text{cause}_1 = i | T_2 \leq t, \text{cause}_2 = k)}{P_x((T_1 \leq t, \text{cause}_1 = i)^c | T_2 \leq t, \text{cause}_2 = k)}$$

and

$$O(T_1 \leq t, \text{cause}_1 = i) = \frac{P_x(T_1 \leq t, \text{cause}_1 = i)}{P_x((T_1 \leq t, \text{cause}_1 = i)^c)}.$$

Here B^c is the complement event of B , P_x is the distribution given covariates (x are subject specific and z are cluster specific covariates), and $h()$ is a function that is the simple identity $\theta^T z$ by default.

Usage

```
cor.cif(
  cif,
  data,
  cause = NULL,
  times = NULL,
  cause1 = 1,
  cause2 = 1,
  cens.code = NULL,
  cens.model = "KM",
  Nit = 40,
  detail = 0,
  clusters = NULL,
  theta = NULL,
  theta.des = NULL,
  step = 1,
  sym = 0,
  weights = NULL,
  par.func = NULL,
  dpar.func = NULL,
  dimpar = NULL,
```

```

score.method = "nlsminb",
same.cens = FALSE,
censoring.weights = NULL,
silent = 1,
...
)

```

Arguments

cif	a model object from the timereg::comp.risk function with the marginal cumulative incidence of cause1, i.e., the event of interest, and whose odds the comparison is compared to the conditional odds given cause2
data	a data.frame with the variables.
cause	specifies the causes related to the death times, the value cens.code is the censoring value. When missing it comes from marginal cif.
times	time-vector that specifies the times used for the estimating equations for the cross-odds-ratio estimation.
cause1	specifies the cause considered.
cause2	specifies the cause that is conditioned on.
cens.code	specifies the code for the censoring if NULL then uses the one from the marginal cif model.
cens.model	specified which model to use for the ICPW, KM is Kaplan-Meier alternatively it may be "cox"
Nit	number of iterations for Newton-Raphson algorithm.
detail	if 0 no details are printed during iterations, if 1 details are given.
clusters	specifies the cluster structure.
theta	specifies starting values for the cross-odds-ratio parameters of the model.
theta.des	specifies a regression design for the cross-odds-ratio parameters.
step	specifies the step size for the Newton-Raphson algorithm.
sym	specifies if symmetry is used in the model.
weights	weights for estimating equations.
par.func	parfunc
dpar.func	dparfunc
dimpar	dimpar
score.method	"nlsminb", can also use "nr".
same.cens	if true then censoring within clusters are assumed to be the same variable, default is independent censoring.
censoring.weights	these probabilities are used for the bivariate censoring dist.
silent	1 to suppress output about convergence related issues.
...	Not used.

Details

The OR dependence measure is given by

$$OR(i, k) = \log\left(\frac{O(T_1 \leq t, cause_1 = i | T_2 \leq t, cause_2 = k)}{O(T_1 \leq t, cause_1 = i) | T_2 \leq t, cause_2 = k}\right)$$

This measure is numerically more stable than the COR measure, and is symmetric in i,k.

The RR dependence measure is given by

$$RR(i, k) = \log\left(\frac{P(T_1 \leq t, cause_1 = i, T_2 \leq t, cause_2 = k)}{P(T_1 \leq t, cause_1 = i)P(T_2 \leq t, cause_2 = k)}\right)$$

This measure is numerically more stable than the COR measure, and is symmetric in i,k.

The model is fitted under symmetry (sym=1), i.e., such that it is assumed that T_1 and T_2 can be interchanged and leads to the same cross-odd-ratio (i.e. $COR(i|k) = COR(k|i)$), as would be expected for twins or without symmetry as might be the case with mothers and daughters (sym=0).

$h()$ may be specified as an R-function of the parameters, see example below, but the default is that it is simply $\theta^T z$.

Value

returns an object of type 'cor'. With the following arguments:

theta	estimate of proportional odds parameters of model.
var.theta	variance for gamma.
hess	the derivative of the used score.
score	scores at final stage.
score	scores at final stage.
theta.iid	matrix of iid decomposition of parametric effects.

Author(s)

Thomas Scheike

References

Cross odds ratio Modelling of dependence for Multivariate Competing Risks Data, Scheike and Sun (2012), Biostatistics.

A Semiparametric Random Effects Model for Multivariate Competing Risks Data, Scheike, Zhang, Sun, Jensen (2010), Biometrika.

Examples

```
library("timereg")
data(multcif);
multcif$cause[multcif$cause==0] <- 2
zyg <- rep(rbinom(200,1,0.5),each=2)
theta.des <- model.matrix(~1+factor(zyg))
```

```

times=seq(0.05,1,by=0.05) # to speed up computations use only these time-points
add <- timereg::comp.risk(Event(time,cause)~+1+cluster(id),data=multcif,cause=1,
                           n.sim=0,times=times,model="fg",max.clust=NULL)
add2 <- timereg::comp.risk(Event(time,cause)~+1+cluster(id),data=multcif,cause=2,
                           n.sim=0,times=times,model="fg",max.clust=NULL)

out1 <- cor.cif(add,data=multcif,cause1=1,cause2=1)
summary(out1)

out2 <- cor.cif(add,data=multcif,cause1=1,cause2=1,theta.des=theta.des)
summary(out2)

##out3 <- cor.cif(add,data=multcif,cause1=1,cause2=2,cif2=add2)
##summary(out3)
#####
# investigating further models using parfunc and dparfunc
#####
## Reduce Ex.Timings
set.seed(100)
prt<-simnordic.random(2000,cordz=2,cormz=5)
prt$status <-prt$cause
table(prt$status)

times <- seq(40,100,by=10)
cifmod <- timereg::comp.risk(Event(time,cause)~+1+cluster(id),data=prt,
                               cause=1,n.sim=0,
                               times=times,conservative=1,max.clust=NULL,model="fg")
theta.des <- model.matrix(~1+factor(zyg),data=prt)

parfunc <- function(par,t,pardes)
{
  par <- pardes %*% c(par[1],par[2]) +
    pardes %*% c( par[3]*(t-60)/12,par[4]*(t-60)/12)
  par
}
head(parfunc(c(0.1,1,0.1,1),50,theta.des))

dparfunc <- function(par,t,pardes)
{
  dpar <- cbind(pardes, t(t(pardes) * c( (t-60)/12,(t-60)/12)) )
  dpar
}
head(dparfunc(c(0.1,1,0.1,1),50,theta.des))

names(prt)
or1 <- or.cif(cifmod,data=prt,cause1=1,cause2=1,theta.des=theta.des,
               same.cens=TRUE,theta=c(0.6,1.1,0.1,0.1),
               par.func=parfunc,dpar.func=dparfunc,dimpars=4,
               score.method="nr",detail=1)
summary(or1)

cor1 <- cor.cif(cifmod,data=prt,cause1=1,cause2=1,theta.des=theta.des,

```

```

same.cens=TRUE,theta=c(0.5,1.0,0.1,0.1),
par.func=parfunc,dpar.func=dparfunc,dimpar=4,
control=list(trace=TRUE),detail=1)
summary(cor1)

### piecewise contant OR model
gparfunc <- function(par,t,pardes)
{
cuts <- c(0,80,90,120)
grop <- diff(t<cuts)
paru <- (pardes[,1]==1) * sum(grop*par[1:3]) +
(pardes[,2]==1) * sum(grop*par[4:6])
paru
}

dparfunc <- function(par,t,pardes)
{
cuts <- c(0,80,90,120)
grop <- diff(t<cuts)
par1 <- matrix(c(grop),nrow(pardes),length(grop),byrow=TRUE)
parmz <- par1*(pardes[,1]==1)
pardz <- (pardes[,2]==1) * par1
dpar <- cbind( parmz,pardz)
dpar
}
head(dgparfunc(rep(0.1,6),50,theta.des))
head(gparfunc(rep(0.1,6),50,theta.des))

or1g <- or.cif(cifmod,data=prt,cause1=1,cause2=1,
theta.des=theta.des, same.cens=TRUE,
par.func=gparfunc,dpar.func=dparfunc,
dimpar=6,score.method="nr",detail=1)
summary(or1g)
names(or1g)
head(or1g$theta.iid)

```

count.history

Counts the number of previous events of two types for recurrent events processes

Description

Counts the number of previous events of two types for recurrent events processes

Usage

```
count.history(
  data,
  status = "status",
```

```

    id = "id",
    types = 1:2,
    names.count = "Count",
    lag = TRUE,
    multitype = FALSE
)

```

Arguments

data	data-frame
status	name of status
id	id
types	types of the events (code) related to status
names.count	name of Counts, for example Count1 Count2 when types=c(1,2)
lag	if true counts previously observed, and if lag=FALSE counts up to know
multitype	if multitype then count number of types also when types=c(1,2) for example

Author(s)

Thomas Scheike

Examples

```

#####
## getting some rates to mimick
#####

data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
dr <- drcumhaz
base1 <- base1cumhaz
base4 <- base4cumhaz

#####
### simulating simple model that mimicks data
### now with two event types and second type has same rate as death rate
#####

rr <- simRecurrentII(1000,base1,base4,death.cumhaz=dr)
rr <- count.history(rr)
dtbl<-dtbl(rr,~"Count*"+status,level=1)

```

covarianceRecurrent	<i>Estimation of covariance for bivariate recurrent events with terminal event</i>
---------------------	------------------------------------------------------------------------------------

Description

Estimation of probability of more than k events for recurrent events process where there is terminal event

Usage

```
covarianceRecurrent(
  data,
  type1,
  type2,
  status = "status",
  death = "death",
  start = "start",
  stop = "stop",
  id = "id",
  names.count = "Count"
)
```

Arguments

data	data-frame
type1	type of first event (code) related to status
type2	type of second event (code) related to status
status	name of status
death	name of death indicator
start	start stop call of Hist() of prodlim
stop	start stop call of Hist() of prodlim
id	id
names.count	name of count for number of previous event of different types, here generated by count.history()

Author(s)

Thomas Scheike

References

Scheike, Eriksson, Tribler (2019) The mean, variance and correlation for bivariate recurrent events with a terminal event, JRSS-C

Examples

```
#####
## getting some data to work on
#####
data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
dr <- drcumhaz
base1 <- base1cumhaz
base4 <- base4cumhaz
rr <- simRecurrentII(1000,base1,cumhaz2=base4,death.cumhaz=dr)
rr <- count.history(rr)
rr$strata <- 1
dtable(rr,~death+status)

covrp <- covarianceRecurrent(rr,1,2,status="status",death="death",
                               start="entry",stop="time",id="id",names.count="Count")
par(mfrow=c(1,3))
plot(covrp)

### with strata, each strata in matrix column, provides basis for fast Bootstrap
covrpS <- covarianceRecurrentS(rr,1,2,status="status",death="death",
                                 start="entry",stop="time",strata="strata",id="id",names.count="Count")
```

daggregate

aggregating for for data frames

Description

aggregating for for data frames

Usage

```
daggregate(
  data,
  y = NULL,
  x = NULL,
  subset,
  ...,
  fun = "summary",
  regex = mets.options()$regex,
  missing = FALSE,
  remove.empty = FALSE,
  matrix = FALSE,
  silent = FALSE,
  na.action = na.pass,
  convert = NULL
)
```

Arguments

data	data.frame
y	name of variable, or formula, or names of variables on data frame.
x	name of variable, or formula, or names of variables on data frame.
subset	subset expression
...	additional arguments to lower level functions
fun	function defining aggregation
regex	interpret x,y as regular expressions
missing	Missing used in groups (x)
remove.empty	remove empty groups from output
matrix	if TRUE a matrix is returned instead of an array
silent	suppress messages
na.action	How model.frame deals with 'NA's
convert	if TRUE try to coerce result into matrix. Can also be a user-defined function

Examples

```

data("sTRACE", package="timereg")
daggregate(iris, "^e.al", x="Species", fun=cor, regex=TRUE)
daggregate(iris, Sepal.Length+Petal.Length ~ Species, fun=summary)
daggregate(iris, log(Sepal.Length)+I(Petal.Length>1.5) ~ Species,
           fun=summary)
daggregate(iris, "*Length*", x="Species", fun=head)
daggregate(iris, "^e.al", x="Species", fun=tail, regex=TRUE)
daggregate(sTRACE, status~ diabetes, fun=table)
daggregate(sTRACE, status~ diabetes+sex, fun=table)
daggregate(sTRACE, status + diabetes+sex ~ vf+I(wmi>1.4), fun=table)
daggregate(iris, "^e.al", x="Species", regex=TRUE)
dlist(iris,Petal.Length+Sepal.Length ~ Species | Petal.Length>1.3 & Sepal.Length>5,
      n=list(1:3,-(3:1)))
daggregate(iris, I(Sepal.Length>7)~Species | I(Petal.Length>1.5))
daggregate(iris, I(Sepal.Length>7)~Species | I(Petal.Length>1.5),
           fun=table)

dsum(iris, .~Species, matrix=TRUE, missing=TRUE)

par(mfrow=c(1,2))
data(iris)
drename(iris) <- ~.
daggregate(iris,'sepal'~species|species!="virginica",fun=plot)
daggregate(iris,'sepal'~I(as.numeric(species))|I(as.numeric(species))!=1,fun=summary)

dnumeric(iris) <- ~species
daggregate(iris,'sepal'~species.n|species.n!=1,fun=summary)

```

Dbvn*Derivatives of the bivariate normal cumulative distribution function*

Description

Derivatives of the bivariate normal cumulative distribution function

Usage

```
Dbvn(p,design=function(p,...) {
  return(list(mu=cbind(p[1],p[1]),
              dmu=cbind(1,1),
              S=matrix(c(p[2],p[3],p[3],p[4]),ncol=2),
              dS=rbind(c(1,0,0,0),c(0,1,1,0),c(0,0,0,1)))  )),
  Y=cbind(0,0))
```

Arguments

p	Parameter vector
design	Design function with defines mean, derivative of mean, variance, and derivative of variance with respect to the parameter p
Y	column vector where the CDF is evaluated

Author(s)

Klaus K. Holst

dby

Calculate summary statistics grouped by

Description

Calculate summary statistics grouped by variable

Usage

```
dby(
  data,
  INPUT,
  ...,
  ID = NULL,
  ORDER = NULL,
  SUBSET = NULL,
  SORT = 0,
  COMBINE = !REDUCE,
```

```

NOCHECK = FALSE,
ARGS = NULL,
NAMES,
COLUMN = FALSE,
REDUCE = FALSE,
REGEX = mets.options()$regex,
ALL = TRUE
)

```

Arguments

data	Data.frame
INPUT	Input variables (character or formula)
...	functions
ID	id variable
ORDER	(optional) order variable
SUBSET	(optional) subset expression
SORT	sort order (id+order variable)
COMBINE	If TRUE result is appended to data
NOCHECK	No sorting or check for missing data
ARGS	Optional list of arguments to functions (...)
NAMES	Optional vector of column names
COLUMN	If TRUE do the calculations for each column
REDUCE	Reduce number of redundant rows
REGEX	Allow regular expressions
ALL	if FALSE only the subset will be returned

Details

Calculate summary statistics grouped by
dby2 for column-wise calculations

Author(s)

Klaus K. Holst and Thomas Scheike

Examples

```

n <- 4
k <- c(3,rbinom(n-1,3,0.5)+1)
N <- sum(k)
d <- data.frame(y=rnorm(N),x=rnorm(N),id=rep(seq(n),k),num=unlist(sapply(k,seq)))
d2 <- d[sample(nrow(d)),]

dby(d2, y~id, mean)

```

```

dby(d2, y~id + order(num), cumsum)

dby(d,y ~ id + order(num), dlag)
dby(d,y ~ id + order(num), dlag, ARGS=list(k=1:2))
dby(d,y ~ id + order(num), dlag, ARGS=list(k=1:2), NAMES=c("l1","l2"))

dby(d, y~id + order(num), mean=mean, csum=cumsum, n=length)
dby(d2, y~id + order(num), a=cumsum, b=mean, N=length, l1=function(x) c(NA,x)[-length(x)])

dby(d, y~id + order(num), nn=seq_along, n=length)
dby(d, y~id + order(num), nn=seq_along, n=length)

d <- d[,1:4]
dby(d, x<0) <- list(z=mean)
d <- dby(d, is.na(z), z=1)

f <- function(x) apply(x,1,min)
dby(d, y+x~id, min=f)

dby(d,y+x~id+order(num), function(x) x)

f <- function(x) { cbind(cumsum(x[,1]),cumsum(x[,2]))/sum(x) }
dby(d, y+x~id, f)

## column-wise
a <- d
dby2(a, mean, median, REGEX=TRUE) <- '^[y|x]`~id
a
## wildcards
dby2(a, 'y*'+'x*'~id,mean)

## subset
dby(d, x<0) <- list(z=NA)
d
dby(d, y~id|x>-1, v=mean,z=1)
dby(d, y+x~id|x>-1, mean, median, COLUMN=TRUE)

dby2(d, y+x~id|x>0, mean, REDUCE=TRUE)

dby(d,y~id|x<0,mean,ALL=FALSE)

a <- iris
a <- dby(a,y=1)
dby(a,Species=="versicolor") <- list(y=2)

```

Description

summary, tables, and correlations for data frames

Usage

```
dcor(data, y = NULL, x = NULL, use = "pairwise.complete.obs", ...)
```

Arguments

data	if x is formula or names for data frame then data frame is needed.
y	name of variable, or formula, or names of variables on data frame.
x	possible group variable
use	how to handle missing values
...	Optional additional arguments

Author(s)

Klaus K. Holst and Thomas Scheike

Examples

```
data("sTRACE", package="timereg")
dt<- sTRACE
dt$time2 <- dt$time^2
dt$wmi2 <- dt$wmi^2
head(dt)

dcor(dt)

dcor(dt,~time+wmi)
dcor(dt,~time+wmi,~vf+chf)
dcor(dt,time+wmi~vf+chf)

dcor(dt,c("time*","wmi*"),~vf+chf)
```

dcut

Cutting, sorting, rm (removing), rename for data frames

Description

Cut variables, if breaks are given these are used, otherwise cuts into using group size given by probs, or equispace groups on range. Default is equally sized groups if possible

Usage

```
dcut(
  data,
  y = NULL,
  x = NULL,
  breaks = 4,
  probs = NULL,
```

```

equi = FALSE,
regex = mets.options()$regex,
sep = NULL,
na.rm = TRUE,
labels = NULL,
all = FALSE,
...
)

```

Arguments

data	if x is formula or names for data frame then data frame is needed.
y	name of variable, or formula, or names of variables on data frame.
x	name of variable, or formula, or names of variables on data frame.
breaks	number of breaks, for variables or vector of break points,
probs	groups defined from quantiles
equi	for equi-spaced breaks
regex	for regular expressions.
sep	separator for naming of cut names.
na.rm	to remove NA for grouping variables.
labels	to use for cut groups
all	to do all variables, even when breaks are not unique
...	Optional additional arguments

Author(s)

Klaus K. Holst and Thomas Scheike

Examples

```

data("sTRACE", package="timereg")
sTRACE$age2 <- sTRACE$age^2
sTRACE$age3 <- sTRACE$age^3

mm <- dcut(sTRACE, ~age+wmi)
head(mm)

mm <- dcut(sTRACE, catage4+wmi4~age+wmi)
head(mm)

mm <- dcut(sTRACE, ~age+wmi, breaks=c(2,4))
head(mm)

mm <- dcut(sTRACE, c("age", "wmi"))
head(mm)

mm <- dcut(sTRACE, ~.)

```

```

head(mm)

mm <- dcut(sTRACE,c("age","wmi"),breaks=c(2,4))
head(mm)

gx <- dcut(sTRACE$age)
head(gx)

## Removes all cuts variables with these names wildcards
mm1 <- drm(mm,c(".2",".4"))
head(mm1)

## wildcards, for age, age2, age4 and wmi
head(dcut(mm,c("a*","?m*")))

## with direct assignment
drm(mm) <- c(".2",".4")
head(mm)

dcut(mm) <- c("age","*m*")
dcut(mm) <- ageg1+wmi~age+wmi
head(mm)

#####
## renaming
#####

head(mm)
drename(mm, ~Age+Wmi) <- c("wmi", "age")
head(mm)
mm1 <- mm

## all names to lower
drename(mm1) <- ~.
head(mm1)

## A* to lower
mm2 <- drename(mm,c("A*","W*"))
head(mm2)
drename(mm) <- "A*"
head(mm)

dd <- data.frame(A_1=1:2,B_1=1:2)
funn <- function(x) gsub("_",".",x)
drename(dd) <- ~.
drename(dd,fun=funn) <- ~.
names(dd)

```

Description

Data on dermal ridge counts in left and right hand in (nuclear) families

Format

Data on 50 families with ridge counts in left and right hand for mother, father and each child. Family id in 'family' and gender and child number in 'sex' and 'child'.

Source

Sarah B. Holt (1952). Genetics of dermal ridges: bilateral asymmetry in finger ridge-counts. Annals of Eugenics 17 (1), pp.211–231. DOI: 10.1111/j.1469-1809.1952.tb02513.x

Examples

```
data(dermalridges)
fast.reshape(dermalridges,id="family",varying=c("child.left","child.right","sex"))
```

dermalridgesMZ*Dermal ridges data (monozygotic twins)*

Description

Data on dermal ridge counts in left and right hand in (nuclear) families

Format

Data on dermal ridge counts (left and right hand) in 18 monozygotic twin pairs.

Source

Sarah B. Holt (1952). Genetics of dermal ridges: bilateral asymmetry in finger ridge-counts. Annals of Eugenics 17 (1), pp.211–231. DOI: 10.1111/j.1469-1809.1952.tb02513.x

Examples

```
data(dermalridgesMZ)
fast.reshape(dermalridgesMZ,id="id",varying=c("left","right"))
```

diabetes*The Diabetic Retinopathy Data*

Description

The data was collected to test a laser treatment for delaying blindness in patients with diabetic retinopathy. The subset of 197 patients given in Huster et al. (1989) is used.

Format

This data frame contains the following columns:

- id** a numeric vector. Patient code.
- agedx** a numeric vector. Age of patient at diagnosis.
- time** a numeric vector. Survival time: time to blindness or censoring.
- status** a numeric vector code. Survival status. 1: blindness, 0: censored.
- trteye** a numeric vector code. Random eye selected for treatment. 1: left eye 2: right eye.
- treat** a numeric vector. 1: treatment 0: untreated.
- adult** a numeric vector code. 1: younger than 20, 2: older than 20.

Source

Huster W.J. and Brookmeyer, R. and Self. S. (1989) Modelling paired survival data with covariates, Biometrics 45, 145-56.

Examples

```
data(diabetes)
names(diabetes)
```

divide.conquer*Split a data set and run function*

Description

Split a data set and run function

Usage

```
divide.conquer(func = NULL, data, size, splits, id = NULL, ...)
```

Arguments

func	called function
data	data-frame
size	size of splits
splits	number of splits (ignored if size is given)
id	optional cluster variable
...	Additional arguments to lower level functions

Author(s)

Thomas Scheike, Klaus K. Holst

Examples

```
## avoid dependency on timereg
## library(timereg)
## data(TRACE)
## res <- divide.conquer(prop.odds,TRACE,
## formula=Event(time,status==9)~chf+vf+age,n.sim=0,size=200)
```

divide.conquer.timereg

Split a data set and run function from timereg and aggregate

Description

Split a data set and run function of cox-aalen type and aggregate results

Usage

```
divide.conquer.timereg(func = NULL, data, size, ...)
```

Arguments

func	called function
data	data-frame
size	size of splits
...	Additional arguments to lower level functions

Author(s)

Thomas Scheike, Klaus K. Holst

Examples

```
## library(timereg)
## data(TRACE)
## a <- divide.conquer.timereg(prop.odds,TRACE,
##                               formula=Event(time,status==9)~chf+vf+age,n.sim=0,size=200)
## coef(a)
## a2 <- divide.conquer.timereg(prop.odds,TRACE,
##                               formula=Event(time,status==9)~chf+vf+age,n.sim=0,size=500)
## coef(a2)
##
##if (interactive()) {
##par(mfrow=c(1,1))
##plot(a,xlim=c(0,8),ylim=c(0,0.01))
##par(new=TRUE)
##plot(a2,xlim=c(0,8),ylim=c(0,0.01))
##}
```

dlag

Lag operator

Description

Lag operator

Usage

```
dlag(data, x, k = 1, combine = TRUE, simplify = TRUE, names, ...)
```

Arguments

<code>data</code>	data.frame or vector
<code>x</code>	optional column names or formula
<code>k</code>	lag (vector of integers)
<code>combine</code>	combine results with original data.frame
<code>simplify</code>	Return vector if possible
<code>names</code>	optional new column names
<code>...</code>	additional arguments to lower level functions

Examples

```
d <- data.frame(y=1:10,x=c(10:1))
dlag(d,k=1:2)
dlag(d,~x,k=0:1)
dlag(d$x,k=1)
dlag(d$x,k=-1:2, names=letters[1:4])
```

doubleFGR*Double CIF Fine-Gray model with two causes*

Description

Estimation based on derived hazards and recursive estimating equations. fits two parametrizations
 1)

$$F_1(t, X) = 1 - \exp(-\exp(X^T \beta) \Lambda_1(t))$$

and

$$F_2(t, X_2) = 1 - \exp(-\exp(X_2^T \beta_2) \Lambda_2(t))$$

or restricted version 2)

$$F_1(t, X) = 1 - \exp(-\exp(X^T \beta) \Lambda_1(t))$$

and

$$F_2(t, X_2, X) = (1 - \exp(-\exp(X_2^T \beta_2) \Lambda_2(t))) (1 - F_1(\infty, X))$$

Usage

```
doubleFGR(formula, data, offset = NULL, weights = NULL, X2 = NULL, ...)
```

Arguments

formula	formula with 'Event'
data	data frame
offset	offsets for cox model
weights	weights for Cox score equations
X2	specifies the regression design for second CIF model
...	Additional arguments to lower level funtions

Author(s)

Thomas Scheike

Examples

```
res <- 0
data(bmt)
bmt$age2 <- bmt$age
newdata <- bmt[1:19,]
if (interactive()) par(mfrow=c(5,3))

## same X1 and X2
pr2 <- doubleFGR(Event(time,cause)~age+platelet,data=bmt,restrict=res)
if (interactive()) {
  bplotdFG(pr2,cause=1)
  bplotdFG(pr2,cause=2,add=TRUE)
```

```

}

pp21 <- predictdFG(pr2,newdata=newdata)
pp22 <- predictdFG(pr2,newdata=newdata,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}
pp21 <- predictdFG(pr2)
pp22 <- predictdFG(pr2,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}

pr2 <- doubleFGR(Event(time,cause)~strata(platelet),data=bmt,restrict=res)
if (interactive()) {
  bplotdFG(pr2,cause=1)
  bplotdFG(pr2,cause=2,add=TRUE)
}
pp21 <- predictdFG(pr2,newdata=newdata)
pp22 <- predictdFG(pr2,,newdata=newdata,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}
pp21 <- predictdFG(pr2)
pp22 <- predictdFG(pr2,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}

## different X1 and X2
pr2 <- doubleFGR(Event(time,cause)~age+platelet+age2,data=bmt,X2=3,restrict=res)
if (interactive()) {
  bplotdFG(pr2,cause=1)
  bplotdFG(pr2,cause=2,add=TRUE)
}
pp21 <- predictdFG(pr2,newdata=newdata)
pp22 <- predictdFG(pr2,newdata=newdata,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}
pp21 <- predictdFG(pr2)
pp22 <- predictdFG(pr2,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}

### uden X1
pr2 <- doubleFGR(Event(time,cause)~age+platelet,data=bmt,X2=1:2,restrict=res)

```

```

if (interactive()) {
  bplotdFG(pr2,cause=1)
  bplotdFG(pr2,cause=2,add=TRUE)
}
pp21 <- predictdFG(pr2,newdata=newdata)
pp22 <- predictdFG(pr2,newdata=newdata,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}
pp21 <- predictdFG(pr2)
p22 <- predictdFG(pr2,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}

### without X2
pr2 <- doubleFGR(Event(time,cause)~age+platelet,data=bmt,X2=0,restrict=res)
if (interactive()) {
  bplotdFG(pr2,cause=1)
  bplotdFG(pr2,cause=2,add=TRUE)
}
pp21 <- predictdFG(pr2,newdata=newdata)
pp22 <- predictdFG(pr2,newdata=newdata,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}
pp21 <- predictdFG(pr2)
pp22 <- predictdFG(pr2,cause=2)
if (interactive()) {
  plot(pp21)
  plot(pp22,add=TRUE,col=2)
}

```

dprint

*list, head, print, tail***Description**

listing for data frames

Usage

```
dprint(data, y = NULL, n = 0, ..., x = NULL)
```

Arguments

data	if x is formula or names for data frame then data frame is needed.
y	name of variable, or formula, or names of variables on data frame.
n	Index of observations to print (default c(1:nfirst, n-nlast:last))
...	Optional additional arguments (nfirst,nlast, and print options)
x	possible group variable

Author(s)

Klaus K. Holst and Thomas Scheike

Examples

```
m <- lava::lvm(letters)
d <- lava::sim(m, 20)

dlist(d,~a+b+c)
dlist(d,~a+b+c|a<0 & b>0)
## listing all :
dlist(d,~a+b+c|a<0 & b>0,n=0)
dlist(d,a+b+c~I(d>0)|a<0 & b>0)
dlist(d,..~I(d>0)|a<0 & b>0)
dlist(d,~a+b+c|a<0 & b>0, nlast=0)
dlist(d,~a+b+c|a<0 & b>0, nfirst=3, nlast=3)
dlist(d,~a+b+c|a<0 & b>0, 1:5)
dlist(d,~a+b+c|a<0 & b>0, -(5:1))
dlist(d,~a+b+c|a<0 & b>0, list(1:5,50:55,-(5:1)))
dprint(d,a+b+c ~ I(d>0) |a<0 & b>0, list(1:5,50:55,-(5:1)))
```

Description

Rate for leaving HPN program for patients of Copenhagen

Source

Estimated data

dreg

Regression for data frames with dutility call

Description

Regression for data frames with dutility call

Usage

```
dreg(  
  data,  
  y,  
  x = NULL,  
  z = NULL,  
  x.oneatatime = TRUE,  
  x.base.names = NULL,  
  z.arg = c("clever", "base", "group", "condition"),  
  fun. = lm,  
  summary. = summary,  
  regex = FALSE,  
  convert = NULL,  
  doSummary = TRUE,  
  special = NULL,  
  equal = TRUE,  
  test = 1,  
  ...  
)
```

Arguments

data	data frame
y	name of variable, or formula, or names of variables on data frame.
x	name of variable, or formula, or names of variables on data frame.
z	name of variable, or formula, or names of variables on data frame.
x.oneatatime	x's one at a time
x.base.names	base covariates
z.arg	what is Z, c("clever","base","group","condition"), clever decides based on type of Z, base means that Z is used as fixed baseline covariates for all X, group means the analyses is done based on groups of Z, and condition means that Z specifies a condition on the data
fun.	function lm is default
summary.	summary to use
regex	regex
convert	convert

doSummary	doSummary or not
special	special's
equal	to do pairwise stuff
test	development argument
...	Additional arguments for fun

Author(s)

Klaus K. Holst, Thomas Scheike

Examples

```
##'
data(iris)
dat <- iris
drename(dat) <- ~.
names(dat)
set.seed(1)
dat$time <- runif(nrow(dat))
dat$time1 <- runif(nrow(dat))
dat$status <- rbinom(nrow(dat),1,0.5)
dat$S1 <- with(dat, Surv(time,status))
dat$S2 <- with(dat, Surv(time1,status))
dat$id <- 1:nrow(dat)

mm <- dreg(dat, ".*.length"~"*.width" | I(species=="setosa" & status==1))
mm <- dreg(dat, ".*.length"~"*.width" | species+status)
mm <- dreg(dat, ".*.length"~"*.width" | species)
mm <- dreg(dat, ".*.length"~"*.width" | species+status, z.arg="group")

## Reduce Ex.Timings
y <- "S*~\"*.width"
xs <- dreg(dat, y, fun.=phreg)
xs <- dreg(dat, y, fun.=survdiff)

y <- "S*~\"*.width"
xs <- dreg(dat, y, x.oneatatime=FALSE, fun.=phreg)

## under condition
y <- S1~"*.width" | I(species=="setosa" & sepal.width>3)
xs <- dreg(dat, y, z.arg="condition", fun.=phreg)
xs <- dreg(dat, y, fun.=phreg)

## under condition
y <- S1~"*.width" | species=="setosa"
xs <- dreg(dat, y, z.arg="condition", fun.=phreg)
xs <- dreg(dat, y, fun.=phreg)

## with baseline after |
y <- S1~"*.width" | sepal.length
xs <- dreg(dat, y, fun.=phreg)
```

```
## by group by species, not working
y <- S1~".width" | species
ss <- split(dat, paste(dat$species, dat$status))

xs <- dreg(dat, y, fun.=phreg)

## species as base, species is factor so assumes that this is grouping
y <- S1~".width" | species
xs <- dreg(dat, y, z.arg="base", fun.=phreg)

## background var after | and then one of x's at at time
y <- S1~".width" | status + "sepal"
xs <- dreg(dat, y, fun.=phreg)

## background var after | and then one of x's at at time
##y <- S1~".width" | status + "sepal"
##xs <- dreg(dat, y, x.oneatatime=FALSE, fun.=phreg)
##xs <- dreg(dat, y, fun.=phreg)

## background var after | and then one of x's at at time
##y <- S1~".width" + factor(species)
##xs <- dreg(dat, y, fun.=phreg)
##xs <- dreg(dat, y, fun.=phreg, x.oneatatime=FALSE)

y <- S1~".width" | factor(species)
xs <- dreg(dat, y, z.arg="base", fun.=phreg)

y <- S1~".width" | cluster(id) + factor(species)
xs <- dreg(dat, y, z.arg="base", fun.=phreg)
xs <- dreg(dat, y, z.arg="base", fun.=coxph)

## under condition with groups
y <- S1~".width" | I(sepal.length>4)
xs <- dreg(subset(dat, species=="setosa"), y, z.arg="group", fun.=phreg)

## under condition with groups
y <- S1~".width" + I(log(sepal.length)) | I(sepal.length>4)
xs <- dreg(subset(dat, species=="setosa"), y, z.arg="group", fun.=phreg)

y <- S1~".width" + I(dcut(sepal.length)) | I(sepal.length>4)
xs <- dreg(subset(dat, species=="setosa"), y, z.arg="group", fun.=phreg)

ff <- function(formula, data, ...) {
  ss <- survfit(formula, data, ...)
  kmplot(ss, ...)
  return(ss)
}

if (interactive()) {
  dcut(dat) <- ~".width"
  y <- S1~".4" | I(sepal.length>4)
  par(mfrow=c(1, 2))
```

```
xs <- dreg(dat, y, fun.=ff)
}
```

drelevel*relev levels for data frames***Description**

levels shows levels for variables in data frame, relevel relevels a factor in data.frame

Usage

```
drelevel(
  data,
  y = NULL,
  x = NULL,
  ref = NULL,
  newlevels = NULL,
  regex = mets.options()$regex,
  sep = NULL,
  overwrite = FALSE,
  ...
)
```

Arguments

data	if x is formula or names for data frame then data frame is needed.
y	name of variable, or formula, or names of variables on data frame.
x	name of variable, or formula, or names of variables on data frame.
ref	new reference variable
newlevels	to combine levels of factor in data frame
regex	for regular expressions.
sep	separator for naming of cut names.
overwrite	to overwrite variable
...	Optional additional arguments

Author(s)

Klaus K. Holst and Thomas Scheike

Examples

```

data(mena)
dstr(mena)
dfactor(mena) <- ~twinnum
dnumeric(mena) <- ~twinnum.f

dstr(mena)

mena2 <- drelevel(mena,"cohort",ref="(1980,1982]")
mena2 <- drelevel(mena,~cohort,ref="(1980,1982]")
mena2 <- drelevel(mena,cohortII~cohort,ref="(1980,1982]")
dlevels(mena)
dlevels(mena2)
drelevel(mena,ref="(1975,1977]") <- ~cohort
drelevel(mena,ref="(1980,1982]") <- ~cohort
dlevels(mena,"coh*")
dttable(mena,"coh*",level=1)

### level 1 of zyg as baseline for new variable
drelevel(mena,ref=1) <- ~zyg
drelevel(mena,ref=c("DZ","[1973,1975]")) <- ~ zyg+cohort
drelevel(mena,ref=c("DZ","[1973,1975]")) <- zygdz+cohort.early~ zyg+cohort
### level 2 of zyg and cohort as baseline for new variables
drelevel(mena,ref=2) <- ~ zyg+cohort
dlevels(mena)

##### combining factor levels with newlevels argument

dcut(mena,labels=c("I","II","III","IV")) <- cat4~agemena
dlevels(drelevel(mena,~cat4,newlevels=1:3))
dlevels(drelevel(mena,ncat4~cat4,newlevels=3:2))
drelevel(mena,newlevels=3:2) <- ncat4~cat4
dlevels(mena)

dlevels(drelevel(mena,nca4~cat4,newlevels=list(c(1,4),2:3)))

drelevel(mena,newlevels=list(c(1,4),2:3)) <- nca4..2 ~ cat4
dlevels(mena)

drelevel(mena,newlevels=list("I-III"=c("I","II","III"),"IV"="IV")) <- nca4..3 ~ cat4
dlevels(mena)

drelevel(mena,newlevels=list("I-III"=c("I","II","III"))) <- nca4..4 ~ cat4
dlevels(mena)

drelevel(mena,newlevels=list(group1=c("I","II","III"))) <- nca4..5 ~ cat4
dlevels(mena)

drelevel(mena,newlevels=list(g1=c("I","II","III"),g2="IV")) <- nca4..6 ~ cat4
dlevels(mena)

```

dsort	<i>Sort data frame</i>
-------	------------------------

Description

Sort data according to columns in data frame

Usage

```
dsort(data, x, ..., decreasing = FALSE, return.order = FALSE)
```

Arguments

<code>data</code>	Data frame
<code>x</code>	variable to order by
<code>...</code>	additional variables to order by
<code>decreasing</code>	sort order (vector of length x)
<code>return.order</code>	return order

Value

`data.frame`

Examples

```
data(data="hubble", package="lava")
dsort(hubble, "sigma")
dsort(hubble, hubble$sigma, "v")
dsort(hubble, ~sigma+v)
dsort(hubble, ~sigma-v)

## with direct assignment
dsort(hubble) <- ~sigma-v
```

dspline	<i>Simple linear spline</i>
---------	-----------------------------

Description

Constructs simple linear spline on a data frame using the formula syntax of `dutils` that is adds $(x-cut_i)^*$ ($x > cut_i$) to the data-set for each knot of the spline. The full spline is thus given by `x` and `spline` variables added to the data-set.

Usage

```
dspline(
  data,
  y = NULL,
  x = NULL,
  breaks = 4,
  probs = NULL,
  equi = FALSE,
  regex = mets.options()$regex,
  sep = NULL,
  na.rm = TRUE,
  labels = NULL,
  all = FALSE,
  ...
)
```

Arguments

data	if x is formula or names for data frame then data frame is needed.
y	name of variable, or formula, or names of variables on data frame.
x	name of variable, or formula, or names of variables on data frame.
breaks	number of breaks, for variables or vector of break points,
probs	groups defined from quantiles
equi	for equi-spaced breaks
regex	for regular expressions.
sep	separator for naming of cut names.
na.rm	to remove NA for grouping variables.
labels	to use for cut groups
all	to do all variables, even when breaks are not unique
...	Optional additional arguments

Author(s)

Thomas Scheike

Examples

```
data(TRACE)
TRACE <- dspline(TRACE, ~wmi, breaks=c(1, 1.3, 1.7))
cca <- coxph(Surv(time, status==9) ~ age + vf + chf + wmi, data=TRACE)
cca2 <- coxph(Surv(time, status==9) ~ age + wmi + vf + chf + wmi.spline1 + wmi.spline2 + wmi.spline3, data=TRACE)
anova(cca, cca2)

nd = data.frame(age=50, vf=0, chf=0, wmi=seq(0.4, 3, by=0.01))
nd <- dspline(nd, ~wmi, breaks=c(1, 1.3, 1.7))
pl <- predict(cca2, newdata=nd)
```

```
plot(nd$wmi,pl,type="l")
```

dtable*tables for data frames***Description**

tables for data frames

Usage

```
dtable(
  data,
  y = NULL,
  x = NULL,
  ...,
  level = -1,
  response = NULL,
  flat = TRUE,
  total = FALSE,
  prop = FALSE,
  summary = NULL
)
```

Arguments

<code>data</code>	if <code>x</code> is formula or names for data frame then data frame is needed.
<code>y</code>	name of variable, or formula, or names of variables on data frame.
<code>x</code>	name of variable, or formula, or names of variables on data frame.
<code>...</code>	Optional additional arguments
<code>level</code>	1 for all marginal tables, 2 for all 2 by 2 tables, and null for the full table, possible versus group variable
<code>response</code>	For level=2, only produce tables with columns given by 'response' (index)
<code>flat</code>	produce flat tables
<code>total</code>	add total counts/proportions
<code>prop</code>	Proportions instead of counts (vector of margins)
<code>summary</code>	summary function

Author(s)

Klaus K. Holst and Thomas Scheike

Examples

```

data("sTRACE", package="timereg")

dtable(sTRACE, ~status)
dtable(sTRACE, ~status+vf)
dtable(sTRACE, ~status+vf, level=1)
dtable(sTRACE, ~status+vf, ~chf+diabetes)

dtable(sTRACE, c("*f*", "status"), ~diabetes)
dtable(sTRACE, c("*f*", "status"), ~diabetes, level=2)
dtable(sTRACE, c("*f*", "status"), level=1)

dtable(sTRACE, ~"*f*"+status, level=1)
dtable(sTRACE, ~"*f*"+status+I(wmi>1.4)|age>60, level=2)
dtable(sTRACE, "*f*"+status~I(wmi>0.5)|age>60, level=1)
dtable(sTRACE, status~dcut(age))

dtable(sTRACE, ~status+vf+sex|age>60)
dtable(sTRACE, status+vf+sex~1|age>60, level=2)
dtable(sTRACE, . ~status+vf+sex|age>60, level=1)
dtable(sTRACE, status+vf+sex~diabetes|age>60)
dtable(sTRACE, status+vf+sex~diabetes|age>60, flat=FALSE)

dtable(sTRACE, status+vf+sex~diabetes|age>60, level=1)
dtable(sTRACE, status+vf+sex~diabetes|age>60, level=2)

dtable(sTRACE, status+vf+sex~diabetes|age>60, level=2, prop=1, total=TRUE)
dtable(sTRACE, status+vf+sex~diabetes|age>60, level=2, prop=2, total=TRUE)
dtable(sTRACE, status+vf+sex~diabetes|age>60, level=2, prop=1:2, summary=summary)

```

dtransform

Transform that allows condition

Description

Defines new variables under condition for data frame

Usage

```
dtransform(data, ...)
```

Arguments

data	is data frame
...	new variable definitions including possible if condition

Examples

```
data(mena)

xx <- dtransform(mena,ll=log(agemena)+twinnum)

xx <- dtransform(mena,ll=log(agemena)+twinnum,agemena<15)
xx <- dtransform(xx ,ll=100+agemena,ll2=1000,agemena>15)
dsummary(xx,ll+ll2~I(agemena>15))
```

easy.binomial.twostage

Fits two-stage binomial for describing dependence in binomial data using marginals that are on logistic form using the binomial.twostage function, but call is different and easier and the data manipulation is build into the function. Useful in particular for family design data.

Description

If clusters contain more than two times, the algorithm uses a composite likelihood based on the pairwise bivariate models.

Usage

```
easy.binomial.twostage(
  margbin = NULL,
  data = parent.frame(),
  method = "nr",
  response = "response",
  id = "id",
  Nit = 60,
  detail = 0,
  silent = 1,
  weights = NULL,
  control = list(),
  theta = NULL,
  theta.formula = NULL,
  desnames = NULL,
  deshelp = 0,
  var.link = 1,
  iid = 1,
  step = 1,
  model = "plackett",
  marginal.p = NULL,
  strata = NULL,
  max.clust = NULL,
  se.clusters = NULL
)
```

Arguments

<code>margbin</code>	Marginal binomial model
<code>data</code>	data frame
<code>method</code>	Scoring method
<code>response</code>	name of response variable in data frame
<code>id</code>	name of cluster variable in data frame
<code>Nit</code>	Number of iterations
<code>detail</code>	Detail for more output for iterations
<code>silent</code>	Debug information
<code>weights</code>	Weights for log-likelihood, can be used for each type of outcome in 2x2 tables.
<code>control</code>	Optimization arguments
<code>theta</code>	Starting values for variance components
<code>theta.formula</code>	design for dependence, either formula or design function
<code>desnames</code>	names for dependence parameters
<code>deshelp</code>	if 1 then prints out some data sets that are used, on on which the design function operates
<code>var.link</code>	Link function for variance
<code>iid</code>	Calculate i.i.d. decomposition
<code>step</code>	Step size
<code>model</code>	model
<code>marginal.p</code>	vector of marginal probabilities
<code>strata</code>	strata for fitting
<code>max.clust</code>	max clusters used for i.i.d. decompostion
<code>se.clusters</code>	clusters for iid decomposition for roubst standard errors

Details

The reported standard errors are based on the estimated information from the likelihood assuming that the marginals are known. This gives correct standard errors in the case of the plackett distribution (OR model for dependence), but incorrect for the clayton-oakes types model. The OR model is often known as the ALR model. Our fitting procedures gives correct standard errors due to the ortogonality and is fast.

Examples

```
data(twinstut)
twinstut0 <- subset(twinstut, tvparnr<4000)
twinstut <- twinstut0
twinstut$binstut <- (twinstut$stutter=="yes")*1
theta.des <- model.matrix( ~1+factor(zyg),data=twinstut)
margbin <- glm(binstut~factor(sex)+age,data=twinstut,family=binomial())
bin <- binomial.twostage(margbin,data=twinstut,var.link=1,
                        clusters=twinstut$tvparnr,theta.des=theta.des,detail=0,
```

```

    method="nr")
summary(bin)
lava::estimate(coef=bin$theta,vcov=bin$var.theta,f=function(p) exp(p))

twinstut$cage <- scale(twinstut$age)
theta.des <- model.matrix( ~1+factor(zyg)+cage,data=twinstut)
bina <- binomial.twostage(margin, data=twinstut, var.link=1,
                           clusters=twinstut$tvpnr, theta.des=theta.des, detail=0)
summary(bina)

theta.des <- model.matrix( ~1+factor(zyg)+factor(zyg)*cage,data=twinstut)
bina <- binomial.twostage(margin, data=twinstut, var.link=1,
                           clusters=twinstut$tvpnr, theta.des=theta.des)
summary(bina)

out <- easy.binomial.twostage(stutter~factor(sex)+age,data=twinstut,
                               response="binstut",id="tvpnr",var.link=1,
                               theta.formula=~1+factor(zyg1))
summary(out)

## refers to zygosity of first subject in each pair : zyg1
## could also use zyg2 (since zyg2=zyg1 within twinpair's)
## do not run t save time
# desfs <- function(x,num1="zyg1",namesdes=c("mz","dz","os"))
#   c(x[num1]=="mz",x[num1]=="dz",x[num1]=="os")*1
#
#out3 <- easy.binomial.twostage(binstut~factor(sex)+age,
#                                data=twinstut, response="binstut",id="tvpnr",
#                                var.link=1,theta.formula=desfs,
#                                desnames=c("mz","dz","os"))
#summary(out3)

## Reduce Ex.Timings
n <- 5000
set.seed(100)
dd <- simBinFam(n,beta=0.3)
binfam <- fast.reshape(dd,varying=c("age","x","y"))
## mother, father, children (ordered)
head(binfam)

#####
##### simple analyses of binomial family data #####
#####

desfs <- function(x,num1="num1",num2="num2")
{
  pp <- 1*((x$num1=="m")*(x$num2=="f"))|(x$num1=="f")*(x$num2=="m"))
  pc <- (x$num1=="m" | x$num1=="f")*(x$num2=="b1" | x$num2=="b2")*1
  cc <- (x$num1=="b1")*(x$num2=="b1" | x$num2=="b2")*1
  c(pp,pc,cc)
}

ud <- easy.binomial.twostage(y~1,data=binfam,
                             response="y",id="id",

```

```

theta.formula=desfs,desnames=c("pp","pc","cc"))
summary(ud)

udx <- easy.binomial.twostage(y~+x,data=binfam,
  response="y",id="id",
  theta.formula=desfs,desnames=c("pp","pc","cc"))
summary(udx)

#####
##### now allowing parent child POR to be different for mother and father
#####

desfsi <- function(x,num1="num1",num2="num2")
{
  pp <- (x[num1]=="m")*(x[num2]=="f")*1
  mc <- (x[num1]=="m")*(x[num2]=="b1" | x[num2]=="b2")*1
  fc <- (x[num1]=="f")*(x[num2]=="b1" | x[num2]=="b2")*1
  cc <- (x[num1]=="b1")*(x[num2]=="b1" | x[num2]=="b2")*1
  c(pp,mc,fc,cc)
}

udi <- easy.binomial.twostage(y~+1,data=binfam,
  response="y",id="id",
  theta.formula=desfsi,desnames=c("pp","mother-child","father-child","cc"))
summary(udi)

##now looking to see if interactions with age or age influences marginal models
##converting factors to numeric to make all involved covariates numeric
##to use desfai2 rather then desfai that works on binfam

nbinfam <- binfam
nbinfam$num <- as.numeric(binfam$num)
head(nbinfam)

desfsai <- function(x,num1="num1",num2="num2")
{
  pp <- (x[num1]=="m")*(x[num2]=="f")*1
  ## av age for pp=1 i.e parent pairs
  agepp <- ((as.numeric(x["age1"])+as.numeric(x["age2"]))/2-30)*pp
  mc <- (x[num1]=="m")*(x[num2]=="b1" | x[num2]=="b2")*1
  fc <- (x[num1]=="f")*(x[num2]=="b1" | x[num2]=="b2")*1
  cc <- (x[num1]=="b1")*(x[num2]=="b1" | x[num2]=="b2")*1
  agecc <- ((as.numeric(x["age1"])+as.numeric(x["age2"]))/2-12)*cc
  c(pp,agepp,mc,fc,cc,agecc)
}

desfsai2 <- function(x,num1="num1",num2="num2")
{
  pp <- (x[num1]==1)*(x[num2]==2)*1
  agepp <- (((x["age1"]+x["age2"]))/2-30)*pp ### av age for pp=1 i.e parent pairs
  mc <- (x[num1]==1)*(x[num2]==3 | x[num2]==4)*1
  fc <- (x[num1]==2)*(x[num2]==3 | x[num2]==4)*1
  cc <- (x[num1]==3)*(x[num2]==3 | x[num2]==4)*1
}

```

```

agecc <- ((x[["age1"]]+x[["age2"]])/2-12)*cc ### av age for children
c(pp,agepp,mc,fc,cc,agecc)
}

udxai2 <- easy.binomial.twostage(y~+x+age,data=binfam,
  response="y",id="id",
  theta.formula=desfsai,
  desnames=c("pp","pp-age","mother-child","father-child","cc","cc-age"))
summary(udxai2)

```

easy.survival.twostage

*Wrapper for easy fitting of Clayton-Oakes or bivariate Plackett models
for bivariate survival data*

Description

Fits two-stage model for describing dependence in survival data using marginals that are on cox or aalen form using the twostage function, but call is different and easier and the data manipulation build into the function. Useful in particular for family design data.

Usage

```

easy.survival.twostage(
  margsurv = NULL,
  data = parent.frame(),
  method = "nlminb",
  status = "status",
  time = "time",
  entry = NULL,
  id = "id",
  Nit = 60,
  detail = 0,
  silent = 1,
  weights = NULL,
  control = list(),
  theta = NULL,
  theta.formula = NULL,
  desnames = NULL,
  deshelp = 0,
  var.link = 1,
  step = 0.5,
  model = "plackett",
  marginal.surv = NULL,
  strata = NULL,
  se.clusters = NULL
)

```

Arguments

margsurv	model
data	data frame
method	Scoring method
status	Status at exit time
time	Exit time
entry	Entry time
id	name of cluster variable in data frame
Nit	Number of iterations
detail	Detail for more output for iterations
silent	Debug information
weights	Weights for log-likelihood, can be used for each type of outcome in 2x2 tables.
control	Optimization arguments
theta	Starting values for variance components
theta.formula	design for dependence, either formula or design function
desnames	names for dependence parameters
deshelp	if 1 then prints out some data sets that are used, on which the design function operates
var.link	Link function for variance (exp link)
step	Step size for newton-raphson
model	plackett or clayton-oakes model
marginal.surv	vector of marginal survival probabilities
strata	strata for fitting
se.clusters	clusters for iid decomposition for robust standard errors

Details

If clusters contain more than two times, the algorithm uses a composite likelihood based on the pairwise bivariate models.

The reported standard errors are based on the estimated information from the likelihood assuming that the marginals are known.

Examples

```
library(mets)
data("prt", package="mets")
prtsam <- blocksample(prt, idvar="id", 1e3, replace=FALSE)
margp <- coxph(Surv(time, status==1)~factor(country), data=prtsam)
fitco <- survival.twostage(margp, data=prtsam, clusters=prtsam$id)
summary(fitco)

des <- model.matrix(~1+factor(zyg), data=prtsam);
```

```

fitco <- survival.twostage(margp,data=prtsam,theta.des=des,clusters=prtsam$id)
summary(fitco)
rm(prtsam)

dfam <- simSurvFam(1000)
dfam <- fast.reshape(dfam,var=c("x","time","status"))

desfs <- function(x,num1="num1",num2="num2")
{
  pp <- (x[num1]=="m")*(x[num2]=="f")*1    ## mother-father
  pc <- (x[num1]=="m" | x[num1]=="f")*(x[num2]=="b1" | x[num2]=="b2")*1 ## mother-child
  cc <- (x[num1]=="b1")*(x[num2]=="b1" | x[num2]=="b2")*1           ## child-child
  c(pp,pc,cc)
}

marg <- coxph(Surv(time,status)~factor(num),data=dfam)
out3 <- easy.survival.twostage(marg,data=dfam,time="time",status="status",id="id",
                                deshelp=0,
                                method="nr",theta.formula=desfs,
                                model="plackett",
                                desnames=c("parent-parent","parent-child","child-child"))
summary(out3)

```

Description

Simple version of comp.risk function of timereg for just one time-point thus fitting the model

$$E(T \leq t|X) = \text{expit}(X^T \beta)$$

Usage

```

Effbinreg(
  formula,
  data,
  cause = 1,
  time = NULL,
  beta = NULL,
  offset = NULL,
  weights = NULL,
  cens.weights = NULL,
  cens.model = ~+1,
  se = TRUE,
  kaplan.meier = TRUE,
  cens.code = 0,
  no.opt = FALSE,

```

```

method = "nr",
augmentation = NULL,
h = NULL,
MCaugment = NULL,
...
)

```

Arguments

formula	formula with outcome (see coxph)
data	data frame
cause	cause of interest
time	time of interest
beta	starting values
offset	offsets for partial likelihood
weights	for score equations
cens.weights	censoring weights
cens.model	only stratified cox model without covariates
se	to compute se's based on IPCW
kaplan.meier	uses Kaplan-Meier for IPCW in contrast to exp(-Baseline)
cens.code	gives censoring code
no.opt	to not optimize
method	for optimization
augmentation	to augment binomial regression
h	h for estimating equation
MCaugment	iid of h and censoring model
...	Additional arguments to lower level funtions
model	exp or linear

Details

Based on binomial regresion IPCW response estimating equation:

$$X(\Delta(T \leq t)/G_c(T_i-) - \text{expit}(X^T \beta)) = 0$$

for IPCW adjusted responses.

Based on binomial regresion IPCW response estimating equation:

$$h(X)X(\Delta(T \leq t)/G_c(T_i-) - \text{expit}(X^T \beta)) = 0$$

for IPCW adjusted responses where \$h\$ is given as an argument together with iid of censoring with h. By using appropriately the h argument we can also do the efficient IPCW estimator estimator this works the presurv and prepcif for survival or competing risks data. In this case also the censoring

martingale should be given for variance calculation and this also comes out of the presurv or prepcif functions. (Experimental version at this stage).

Variance is based on

$$\sum w_i^2$$

also with IPCW adjustment, and naive.var is variance under known censoring model.

Censoring model may depend on strata.

Author(s)

Thomas Scheike

EVaddGam

Relative risk for additive gamma model

Description

Computes the relative risk for additive gamma model at time 0

Usage

```
EVaddGam(theta, x1, x2, thetades, ags)
```

Arguments

theta	theta
x1	x1
x2	x2
thetades	thetades
ags	ags

Author(s)

Thomas Scheike

References

Eriksson and Scheike (2015), Additive Gamma frailty models for competing risks data, Biometrics (2015)

Examples

```

lam0 <- c(0.5,0.3)
pars <- c(1,1,1,1,0,1)
## genetic random effects, cause1, cause2 and overall
parg <- pars[c(1,3,5)]
## environmental random effects, cause1, cause2 and overall
parc <- pars[c(2,4,6)]

## simulate competing risks with two causes with hazards 0.5 and 0.3
## ace for each cause, and overall ace
out <- simCompete.twin.ace(10000,parg,parc,0,2,lambda=lam0,overall=1,all.sum=1)

## setting up design for running the model
mm <- familycluster.index(out$cluster)
head(mm$familypairindex,n=10)
pairs <- matrix(mm$familypairindex,ncol=2,byrow=TRUE)
tail(pairs,n=12)
#
kinship <- (out[pairs[,1],"zyg"]=="MZ") + (out[pairs[,1],"zyg"]=="DZ")*0.5

# dout <- make.pairwise.design.competing(pairs,kinship,
#                                         type="ace",compete=length(lambda),overall=1)
# head(dout$ant.rvs)
## MZ
# dim(dout$theta.des)
# dout$random.design[,1]
## DZ
# dout$theta.des[,,nrow(pairs)]
# dout$random.design[,,nrow(pairs)]
#
# thetades <- dout$theta.des[,1]
# x <- dout$random.design[,1]
# x
##EVaddGam(rep(1,6),x[1,],x[3,],thetades,matrix(1,18,6))

# thetades <- dout$theta.des[,nrow(out)/2]
# x <- dout$random.design[,nrow(out)/2]
##EVaddGam(rep(1,6),x[1,],x[4,],thetades,matrix(1,18,6))

```

eventpois

Extract survival estimates from lifetable analysis

Description

Summary for survival analyses via the 'lifetable' function

Usage

```
eventpois()
```

```

object,
...,
timevar,
time,
int.len,
confint = FALSE,
level = 0.95,
individual = FALSE,
length.out = 25
)

```

Arguments

<code>object</code>	glm object (poisson regression)
<code>...</code>	Contrast arguments
<code>timevar</code>	Name of time variable
<code>time</code>	Time points (optional)
<code>int.len</code>	Time interval length (optional)
<code>confint</code>	If TRUE confidence limits are supplied
<code>level</code>	Level of confidence limits
<code>individual</code>	Individual predictions
<code>length.out</code>	Length of time vector

Details

Summary for survival analyses via the 'lifetable' function

Author(s)

Klaus K. Holst

EventSplit

Event split with two time-scales, time and gaptime

Description

splits after cut times for the two time-scales.

Usage

```
EventSplit(
  data,
  time = "time",
  status = "status",
  entry = "start",
  cuts = "cuts",
  name.id = "id",
  gaptme = NULL,
  gaptme.entry = NULL,
  cuttime = c("time", "gaptme"),
  cens.code = 0,
  order.id = TRUE
)
```

Arguments

data	data to be split
time	time variable.
status	status variable.
entry	name of entry variable.
cuts	cuts variable or numeric cut (only one value)
name.id	name of id variable.
gaptme	gaptme variable.
gaptme.entry	name of entry variable for gaptme.
cuttime	to cut after time or gaptme
cens.code	code for the censoring.
order.id	order data after id and start.

Author(s)

Thomas Scheike

Examples

```
rr <- data.frame(time=c(500,1000),start=c(0,500),status=c(1,1),id=c(1,1))
rr$gaptme <- rr$time-rr$start
rr$gapstart <- 0

rr1 <- EventSplit(rr,cuts=600,cuttime="time", gaptme="gaptme",gaptme.entry="gapstart")
rr2 <- EventSplit(rr1,cuts=100,cuttime="gaptme",gaptme="gaptme",gaptme.entry="gapstart")

dlist(rr1,start-time+status+gapstart+gaptme~id)
dlist(rr2,start-time+status+gapstart+gaptme~id)
```

familycluster.index *Finds all pairs within a cluster (family)*

Description

Finds all pairs within a cluster (family)

Usage

```
familycluster.index(clusters, index.type = FALSE, num = NULL, Rindex = 1)
```

Arguments

clusters	list of indeces
index.type	argument of cluster index
num	num
Rindex	index starts with 1 in R, and 0 in C

Author(s)

Klaus Holst, Thomas Scheike

References

Cluster indeces

See Also

`cluster.index` `familyclusterWithProbands.index`

Examples

```
i<-c(1,1,2,2,1,3)
d<- familycluster.index(i)
print(d)
```

familyclusterWithProbands.index

Finds all pairs within a cluster (famly) with the proband (case/control)

Description

second column of pairs are the probands and the first column the related subjects

Usage

```
familyclusterWithProbands.index(
  clusters,
  probands,
  index.type = FALSE,
  num = NULL,
  Rindex = 1
)
```

Arguments

clusters	list of indeces giving the clusters (families)
probands	list of 0,1 where 1 specifies which of the subjects that are probands
index.type	argument passed to other functions
num	argument passed to other functions
Rindex	index starts with 1, in C is it is 0

Author(s)

Klaus Holst, Thomas Scheike

References

Cluster indeces

See Also

familycluster.index cluster.index

Examples

```
i<-c(1,1,2,2,1,3)
p<-c(1,0,0,1,0,1)
d<- familyclusterWithProbands.index(i,p)
print(d)
```

fast.approx*Fast approximation***Description**

Fast approximation

Usage

```
fast.approx(
  time,
  new.time,
  equal = FALSE,
  type = c("nearest", "right", "left"),
  sorted = FALSE,
  ...
)
```

Arguments

<code>time</code>	Original ordered time points
<code>new.time</code>	New time points
<code>equal</code>	If TRUE a list is returned with additional element
<code>type</code>	Type of matching, nearest index, nearest greater than or equal (right), number of elements smaller than y otherwise the closest value above new.time is returned.
<code>sorted</code>	Set to true if new.time is already sorted
...	Optional additional arguments

Author(s)

Klaus K. Holst

Examples

```
id <- c(1,1,2,2,7,7,10,10)
fast.approx(unique(id),id)

t <- 0:6
n <- c(-1,0,0.1,0.9,1,1.1,1.2,6,6.5)
fast.approx(t,n,type="left")
```

fast.pattern

Fast pattern

Description

Fast pattern

Usage

```
fast.pattern(x, y, categories = 2, ...)
```

Arguments

x	Matrix (binary) of patterns. Optionally if y is also passed as argument, then the pattern matrix is defined as the elements agreeing in the two matrices.
y	Optional matrix argument with same dimensions as x (see above)
categories	Default 2 (binary)
...	Optional additional arguments

Author(s)

Klaus K. Holst

Examples

```
X <- matrix(rbinom(100,1,0.5),ncol=4)
fast.pattern(X)

X <- matrix(rbinom(100,3,0.5),ncol=4)
fast.pattern(X,categories=4)
```

fast.reshape

Fast reshape

Description

Fast reshape/tranpose of data

Usage

```
fast.reshape(
  data,
  varying,
  id,
  num,
  sep = "",
  keep,
  idname = "id",
  numname = "num",
  factor = FALSE,
  idcombine = TRUE,
  labelnum = FALSE,
  labels,
  regex = mets.options()$regex,
  dropid = FALSE,
  ...
)
```

Arguments

data	data.frame or matrix
varying	Vector of prefix-names of the time varying variables. Optional for Long->Wide reshaping.
id	id-variable. If omitted then reshape Wide->Long.
num	Optional number/time variable
sep	String separating prefix-name with number/time
keep	Vector of column names to keep
idname	Name of id-variable (Wide->Long)
numname	Name of number-variable (Wide->Long)
factor	If true all factors are kept (otherwise treated as character)
idcombine	If TRUE and id is vector of several variables, the unique id is combined from all the variables. Otherwise the first variable is only used as identifier.
labelnum	If TRUE varying variables in wide format (going from long->wide) are labeled 1,2,3,... otherwise use 'num' variable. In long-format (going from wide->long) varying variables matching 'varying' prefix are only selected if their postfix is a number.
labels	Optional labels for the number variable
regex	Use regular expressions
dropid	Drop id in long format (default FALSE)
...	Optional additional arguments

Author(s)

Thomas Scheike, Klaus K. Holst

Examples

```

m <- lava::lvm(c(y1,y2,y3,y4)~x)
d <- lava::sim(m,5)
d
fast.reshape(d,"y")
fast.reshape(fast.reshape(d,"y"),id="id")

##### From wide-format
(dd <- fast.reshape(d,"y"))
## Same with explicit setting new id and number variable/column names
## and separator "" (default) and dropping x
fast.reshape(d,"y",idname="a",timevar="b",sep="",keep=c())
## Same with 'reshape' list-syntax
fast.reshape(d,list(c("y1","y2","y3","y4")),labelnum=TRUE)

##### From long-format
fast.reshape(dd,id="id")
## Restrict set up within-cluster varying variables
fast.reshape(dd,"y",id="id")
fast.reshape(dd,"y",id="id",keep="x",sep=".")  

  

#####
x <- data.frame(id=c(5,5,6,6,7),y=1:5,x=1:5,tv=c(1,2,2,1,2))
x
(xw <- fast.reshape(x,id="id"))
(xl <- fast.reshape(xw,c("y","x"),idname="id2",keep=c()))
(xl <- fast.reshape(xw,c("y","x","tv")))
(xw2 <- fast.reshape(xl,id="id",num="num"))
fast.reshape(xw2,c("y","x"),idname="id")

### more generally:
### varying=list(c("ym","yf","yb1","yb2"), c("zm","zf","zb1","zb2"))
### varying=list(c("ym","yf","yb1","yb2"))

##### Family cluster example
d <- mets:::simBinFam(3)
d
fast.reshape(d,var="y")
fast.reshape(d,varying=list(c("ym","yf","yb1","yb2")))

d <- lava::sim(lava::lvm(~y1+y2+ya),10)
d
(dd <- fast.reshape(d,"y"))
fast.reshape(d,"y",labelnum=TRUE)
fast.reshape(dd,id="id",num="num")
fast.reshape(dd,id="id",num="num",labelnum=TRUE)
fast.reshape(d,c(a="y"),labelnum=TRUE) ## New column name

#####
m <- lava::lvm(c(y1,y2,y3,y4)~ x+z1+z3+z5)
d <- lava::sim(m,3)

```

```

d
fast.reshape(d,c("y","z"))

##### not-varying syntax:
fast.reshape(d,-c("x"))

##### Automatically define varying variables from trailing digits
fast.reshape(d)

##### Prostate cancer example
data(prt)
head(prtw <- fast.reshape(prt,"cancer",id="id"))
ftable(cancer1~cancer2,data=prtw)
rm(prtw)

```

FG_AugmentCifstrata *Augmentation for Fine-Gray model based on stratified NPMLE Cif
(Aalen-Johansen)*

Description

Computes the augmentation term for each individual as well as the sum

$$A(\beta) = \int H(t, X, \beta) \frac{F_2^*(t, s)}{S^*(t, s)} \frac{1}{G_c(t)} dM_c$$

with

$$H(t, X, \beta) = \int_t^\infty (X - E(\beta, t)) G_c(t) d\Lambda_1^* i(t, s)$$

using a KM for

$$G_c(t)$$

and a working model for cumulative baseline related to

$$F_1^*(t, s)$$

and

$$s$$

is strata,

$$S^*(t, s) = 1 - F_1^*(t, s) - F_2^*(t, s)$$

, and

$$E(\beta^p, t)$$

is given. Assumes that no strata for baseline of fine-Gray model that is augmented.

Usage

```
FG_AugmentCifstrata(
  formula,
  data = data,
  E = NULL,
  cause = NULL,
  cens.code = 0,
  km = TRUE,
  case.weights = NULL,
  weights = NULL,
  offset = NULL,
  ...
)
```

Arguments

formula	formula with 'Event', strata model for CIF given by strata, and strataC specifies censoring strata
data	data frame
E	from FG-model
cause	of interest
cens.code	code of censoring
km	to use Kaplan-Meier
case.weights	weights for FG score equations (that follow dN_1)
weights	weights for FG score equations
offset	offsets for FG model
...	Additional arguments to lower level funtions

Details

After a couple of iterations we end up with a solution of

$$\int (X - E(\beta)) Y_1(t) w(t) dM_1 + A(\beta)$$

the augmented FG-score.

Standard errors computed under assumption of correct

G_c

model.

Author(s)

Thomas Scheike

Examples

```

set.seed(100)
rho1 <- 0.2; rho2 <- 10
n <- 400
beta=c(0.0,-0.1,-0.5,0.3)
datas <- simul.cifs(n,rho1,rho2,beta,rc=0.2)
dtable(datas,~status)
dsort(datas) <- ~time
fg <- cifreg(Event(time,status)~Z1+Z2,data=datas,cause=1,propodds=NULL)
summary(fg)

fgaugS <- FG_AugmentCifstrata(Event(time,status)~Z1+Z2+strata(Z1,Z2),data=datas,cause=1,E=fg$E)
summary(fgaugS)
fgaugS2 <- FG_AugmentCifstrata(Event(time,status)~Z1+Z2+strata(Z1,Z2),data=datas,cause=1,E=fgaugS$E)
summary(fgaugS2)

```

ghaplos

ghaplos haplo-types for subjects of haploX data

Description

ghaplos haplo-types for subjects of haploX data

Source

Simulated data

gof.phreg

GOF for Cox PH regression

Description

Cumulative score process residuals for Cox PH regression p-values based on Lin, Wei, Ying resampling.

Usage

```
## S3 method for class 'phreg'
gof(object, n.sim = 1000, silent = 1, robust = NULL, ...)
```

Arguments

object	is phreg object
n.sim	number of simulations for score processes
silent	to show timing estimate will be produced for longer jobs
robust	to control whether robust dM_i(t) or dN_i are used for simulations
...	Additional arguments to lower level functions

Author(s)

Thomas Scheike and Klaus K. Holst

Examples

```
library(mets)
data(sTRACE)

m1 <- phreg(Surv(time,status==9)~vf+chf+diabetes,data=sTRACE)
gg <- gof(m1)
gg
par(mfrow=c(1,3))
plot(gg)

m1 <- phreg(Surv(time,status==9)~strata(vf)+chf+diabetes,data=sTRACE)
## to get Martingale ~ dN based simulations
gg <- gof(m1)
gg

## to get Martingale robust simulations, specify cluster in call
sTRACE$id <- 1:500
m1 <- phreg(Surv(time,status==9)~vf+chf+diabetes+cluster(id),data=sTRACE)
gg <- gof(m1)
gg

m1 <- phreg(Surv(time,status==9)~strata(vf)+chf+diabetes+cluster(id),data=sTRACE)
gg <- gof(m1)
gg
```

gofG.phreg

Stratified baseline graphical GOF test for Cox covariates in PH regression

Description

Looks at stratified baseline in Cox model and plots all baselines versus each other to see if lines are straight, with 50 resample versions under the assumption that the stratified Cox is correct

Usage

```
gofG.phreg(x, sim = 0, silent = 1, lm = TRUE, ...)
```

Arguments

x	phreg object
sim	to simulate some variation from cox model to put on graph
silent	to keep it absolutely silent
lm	add line to plot, regressing the cumulatives on each other
...	Additional arguments to lower level functions

Author(s)

Thomas Scheike and Klaus K. Holst

Examples

```
data(tTRACE)

m1 <- phreg(Surv(time,status==9)~strata(vf)+chf+wmi,data=tTRACE)
m2 <- phreg(Surv(time,status==9)~vf+strata(chf)+wmi,data=tTRACE)
par(mfrow=c(2,2))

gofG.phreg(m1)
gofG.phreg(m2)

bplot(m1,log="y")
bplot(m2,log="y")
```

gofM.phreg

GOF for Cox covariates in PH regression

Description

Cumulative residuals after model matrix for Cox PH regression p-values based on Lin, Wei, Ying resampling.

Usage

```
gofM.phreg(
  formula,
  data,
  offset = NULL,
  weights = NULL,
  modelmatrix = NULL,
  n.sim = 1000,
  silent = 1,
  ...
)
```

Arguments

formula	formula for cox regression
data	data for model
offset	offset
weights	weights
modelmatrix	matrix for cumulating residuals
n.sim	number of simulations for score processes

silent	to keep it absolutely silent, otherwise timing estimate will be produced for longer jobs.
...	Additional arguments to lower level functions

Details

That is, computes

$$U(t) = \int_0^t M^t d\hat{M}$$

and resamples its asymptotic distribution.

This will show if the residuals are consistent with the model. Typically, M will be a design matrix for the continuous covariates that gives for example the quartiles, and then the plot will show if for the different quartiles of the covariate the risk prediction is consistent over time (time x covariate interaction).

Author(s)

Thomas Scheike and Klaus K. Holst

Examples

```
library(mets)
data(TRACE)
set.seed(1)
TRACEsam <- blocksample(TRACE,idvar="id",replace=FALSE,100)

dcut(TRACEsam)  <- ~.
mm <- model.matrix(~-1+factor(wmicat.4),data=TRACEsam)
m1 <- gofM.phreg(Surv(time,status==9)~vf+chf+wmi,data=TRACEsam,modelmatrix=mm)
summary(m1)
if (interactive()) {
  par(mfrow=c(2,2))
  plot(m1)
}

m1 <- gofM.phreg(Surv(time,status==9)~strata(vf)+chf+wmi,data=TRACEsam,modelmatrix=mm)
summary(m1)

## cumulative sums in covariates, via design matrix mm
mm <- cumContr(TRACEsam$wmi,breaks=10,equi=TRUE)
m1 <- gofM.phreg(Surv(time,status==9)~strata(vf)+chf+wmi,data=TRACEsam,
  modelmatrix=mm,silent=0)
summary(m1)
```

gofZ.phreg*GOF for Cox covariates in PH regression*

Description

That is, computes

$$U(z, \tau) = \int_0^\tau M(z)^t d\hat{M}$$

and resamples its asymptotic distribution.

Usage

```
gofZ.phreg(
  formula,
  data,
  vars = NULL,
  offset = NULL,
  weights = NULL,
  breaks = 50,
  equi = FALSE,
  n.sim = 1000,
  silent = 1,
  ...
)
```

Arguments

formula	formula for cox regression
data	data for model
vars	which variables to test for linearity
offset	offset
weights	weights
breaks	number of breaks for cumulatives in covariate direction
equi	equidistant breaks or not
n.sim	number of simulations for score processes
silent	to keep it absolutely silent, otherwise timing estimate will be produced for longer jobs.
...	Additional arguments to lower level funtions

Details

This will show if the residuals are consistent with the model evaluated in the z covariate. M is here chosen based on a grid (z_1, ..., z_m) and the different columns are $I(Z_i \leq z_l)$. for $l = 1, \dots, m$. The process in z is resampled to find extreme values. The time-points of evaluation is by default 50 points, chosen as 2

The p-value is valid but depends on the chosen grid. When the number of break points are high this will give the orginal test of Lin, Wei and Ying for linearity, that is also computed in the timereg package.

Author(s)

Thomas Scheike and Klaus K. Holst

Examples

```
library(mets)
data(TRACE)
set.seed(1)
TRACESam <- blocksample(TRACE,idvar="id",replace=FALSE,100)

## cumulative sums in covariates, via design matrix mm
## Reduce Ex.Timings
m1 <- gofZ.phreg(Surv(time,status==9)~strata(vf)+chf+wmi+age,data=TRACESam)
summary(m1)
plot(m1,type="z")
```

Grandom.cif

Additive Random effects model for competing risks data for polygenic modelling

Description

Fits a random effects model describing the dependence in the cumulative incidence curves for subjects within a cluster. Given the gamma distributed random effects it is assumed that the cumulative incidence curves are independent, and that the marginal cumulative incidence curves are on additive form

$$P(T \leq t, cause = 1|x, z) = P_1(t, x, z) = 1 - \exp(-x^T A(t) - tz^T \beta)$$

Usage

```
Grandom.cif(
  cif,
  data,
  cause = NULL,
  cif2 = NULL,
  times = NULL,
```

```

cause1 = 1,
cause2 = 1,
cens.code = NULL,
cens.model = "KM",
Nit = 40,
detail = 0,
clusters = NULL,
theta = NULL,
theta.des = NULL,
weights = NULL,
step = 1,
sym = 0,
same.cens = FALSE,
censoring.weights = NULL,
silent = 1,
var.link = 0,
score.method = "nr",
entry = NULL,
estimator = 1,
trunkp = 1,
admin.cens = NULL,
random.design = NULL,
...
)

```

Arguments

cif	a model object from the timereg::comp.risk function with the marginal cumulative incidence of cause2, i.e., the event that is conditioned on, and whose odds the comparision is made with respect to
data	a data.frame with the variables.
cause	specifies the causes related to the death times, the value cens.code is the censoring value.
cif2	specificies model for cause2 if different from cause1.
times	time points
cause1	cause of first coordinate.
cause2	cause of second coordinate.
cens.code	specifies the code for the censoring if NULL then uses the one from the marginal cif model.
cens.model	specified which model to use for the ICPW, KM is Kaplan-Meier alternatively it may be "cox"
Nit	number of iterations for Newton-Raphson algorithm.
detail	if 0 no details are printed during iterations, if 1 details are given.
clusters	specifies the cluster structure.
theta	specifies starting values for the cross-odds-ratio parameters of the model.

theta.des	specifies a regression design for the cross-odds-ratio parameters.
weights	weights for score equations.
step	specifies the step size for the Newton-Raphson algorithm.
sym	1 for symmetric and 0 otherwise
same.cens	if true then censoring within clusters are assumed to be the same variable, default is independent censoring.
censoring.weights	Censoring probabilities
silent	debug information
var.link	if var.link=1 then var is on log-scale.
score.method	default uses "nlminb" optimizer, alternatively, use the "nr" algorithm.
entry	entry-age in case of delayed entry. Then two causes must be given.
estimator	estimator
trunkp	gives probability of survival for delayed entry, and related to entry-ages given above.
admin.cens	Administrative censoring
random.design	specifies a regression design of 0/1's for the random effects.
...	extra arguments.

Details

We allow a regression structure for the independent gamma distributed random effects and their variances that may depend on cluster covariates.

random.design specifies the random effects for each subject within a cluster. This is a matrix of 1's and 0's with dimension n x d. With d random effects. For a cluster with two subjects, we let the random.design rows be v_1 and v_2 . Such that the random effects for subject 1 is

$$v_1^T(Z_1, \dots, Z_d)$$

, for d random effects. Each random effect has an associated parameter $(\lambda_1, \dots, \lambda_d)$. By construction subjects 1's random effect are Gamma distributed with mean $\lambda_1/v_1^T \lambda$ and variance $\lambda_1/(v_1^T \lambda)^2$. Note that the random effect $v_1^T(Z_1, \dots, Z_d)$ has mean 1 and variance $1/(v_1^T \lambda)$.

The parameters $(\lambda_1, \dots, \lambda_d)$ are related to the parameters of the model by a regression construction $pard$ (d x k), that links the d λ parameters with the (k) underlying θ parameters

$$\lambda = pard\theta$$

Value

returns an object of type 'random.cif'. With the following arguments:

theta	estimate of parameters of model.
var.theta	variance for gamma.
hess	the derivative of the used score.
score	scores at final stage.
theta.iid	matrix of iid decomposition of parametric effects.

Author(s)

Thomas Scheike

References

- A Semiparametric Random Effects Model for Multivariate Competing Risks Data, Scheike, Zhang, Sun, Jensen (2010), Biometrika.
- Cross odds ratio Modelling of dependence for Multivariate Competing Risks Data, Scheike and Sun (2013), Biostatistics.
- Scheike, Holst, Hjelmborg (2014), LIDA, Estimating heritability for cause specific hazards based on twin data

Examples

```
## Reduce Ex.Timings
d <- simnordic.random(5000,delayed=TRUE,
                      cordz=1.0,cormz=2,lambda=0.3,country=TRUE)
times <- seq(50,90,by=10)
addm <- timereg::comp.risk(Event(time,cause)~-1+factor(country)+cluster(id),data=d,
                             times=times,cause=1,max.clust=NULL)

### making group indicator
mm <- model.matrix(~-1+factor(zyg),d)

out1m<-random.cif(addm,data=d,cause1=1,cause2=1,theta=1,
                     theta.des=mm,same.cens=TRUE)
summary(out1m)

## this model can also be formulated as a random effects model
## but with different parameters
out2m<-Grandom.cif(addm,data=d,cause1=1,cause2=1,
                     theta=c(0.5,1),step=1.0,
                     random.design=mm,same.cens=TRUE)
summary(out2m)
1/out2m$theta
out1m$theta

#####
##### ACE modelling of twin data #####
#####
### assume that zygin gives the zygosity of mono and dizygotic twins
### 0 for mono and 1 for dizygotic twins. We now formulate and AC model
zygin <- d$zyg=="DZ"

n <- nrow(d)
### random effects for each cluster
des.rv <- cbind(mm,(zygin==1)*rep(c(1,0),(zygin==1)*rep(c(0,1)),1)
### design making parameters half the variance for dizygotic components
pardes <- rbind(c(1,0), c(0.5,0),c(0.5,0), c(0.5,0), c(0,1))

outacem <-Grandom.cif(addm,data=d,cause1=1,cause2=1,
```

```
same.cens=TRUE,theta=c(0.35,0.15),  
step=1.0,theta.des=pardes,random.design=des.rv)  
summary(outacem)
```

hapfreqs

hapfreqs data set

Description

hapfreqs data set

Source

Simulated data

haplo.surv.discrete *Discrete time to event haplo type analysis*

Description

Can be used for logistic regression when time variable is "1" for all id.

Usage

```
haplo.surv.discrete(  
  X = NULL,  
  y = "y",  
  time.name = "time",  
  Haplos = NULL,  
  id = "id",  
  desnames = NULL,  
  designfunc = NULL,  
  beta = NULL,  
  no.opt = FALSE,  
  method = "NR",  
  stderr = TRUE,  
  designMatrix = NULL,  
  response = NULL,  
  idhap = NULL,  
  design.only = FALSE,  
  covnames = NULL,  
  fam = binomial,  
  weights = NULL,  
  offsets = NULL,
```

```

idhapweights = NULL,
...
)

```

Arguments

X	design matrix data-frame (sorted after id and time variable) with id time response and desnames
y	name of response (binary response with logistic link) from X
time.name	to sort after time for X
Haplos	(data.frame with id, haplo1, haplo2 (haplotypes (h)) and p=P(h G)) haplotypes given as factor.
id	name of id variale from X
desnames	names for design matrix
designfunc	function that computes design given haplotypes h=(h1,h2) x(h)
beta	starting values
no.opt	optimization TRUE/FALSE
method	NR, nlm
stderr	to return only estimate
designMatrix	gives response and designMatrix directly not implemented (mush contain: p, id, idhap)
response	gives response and design directly designMatrix not implemented
idhap	name of id-hap variable to specify different haplotypes for different id
design.only	to return only design matrices for haplo-type analyses.
covnames	names of covariates to extract from object for regression
fam	family of models, now binomial default and only option
weights	weights following id for GLM
offsets	following id for GLM
idhapweights	weights following id-hap for GLM (WIP)
...	Additional arguments to lower level funtions lava::NR optimizer or nlm

Details

Cycle-specific logistic regression of haplo-type effects with known haplo-type probabilities. Given observed genotype G and unobserved haplotypes H we here mix out over the possible haplotypes using that P(H|G) is provided.

$$S(t|x, G) = E(S(t|x, H)|G) = \sum_{h \in G} P(h|G)S(t|z, h)$$

so survival can be computed by mixing out over possible h given g.

Survival is based on logistic regression for the discrete hazard function of the form

$$\text{logit}(P(T = t|T \geq t, x, h)) = \alpha_t + x(h)\beta$$

where $x(h)$ is a regression design of x and haplotypes $h = (h_1, h_2)$

Likelihood is maximized and standard errors assumes that $P(H|G)$ is known.

The design over the possible haplotypes is constructed by merging X with Haplos and can be viewed by `design.only=TRUE`

Author(s)

Thomas Scheike

Examples

```
## some haplotypes of interest
types <- c("DCGCGCTCACG", "DTCCGCTGACG", "ITCAGTTGACG", "ITCCGCTGAGG")

## some haplotypes frequencies for simulations
data(hapfreqs)

www <- which(hapfreqs$haplotype %in% types)
hapfreqs$freq[www]

baseline=hapfreqs$haplotype[9]
baseline

designftypes <- function(x,sm=0) {# {{{
hap1=x[1]
hap2=x[2]
if (sm==0) y <- 1*( (hap1==types) | (hap2==types))
if (sm==1) y <- 1*(hap1==types) + 1*(hap2==types)
return(y)
}}}

tcoef=c(-1.93110204, -0.47531630, -0.04118204, -1.57872602, -0.22176426, -0.13836416,
0.88830288, 0.60756224, 0.39802821, 0.32706859)

data(hHaplos)
data(haploX)

haploX$time <- haploX$times
Xdes <- model.matrix(~factor(time),haploX)
colnames(Xdes) <- paste("X",1:ncol(Xdes),sep="")
X <- dkeep(haploX,~id+y+time)
X <- cbind(X,Xdes)
Haplos <- dkeep(ghaplos,~id+"haplo*"+p)
desnames=paste("X",1:6,sep="") # six X's related to 6 cycles
out <- haplo.surv.discrete(X=X,y="y",time.name="time",
                           Haplos=Haplos,desnames=desnames,designfunc=designftypes)
names(out$coef) <- c(desnames,types)
out$coef
summary(out)
```

haploX

*haploX covariates and response for haplo survival discrete survival***Description**

haploX covariates and response for haplo survival discrete survival

Source

Simulated data

interval.logitsurv.discrete

*Discrete time to event interval censored data***Description**

$$\text{logit}(P(T > t|x)) = \log(G(t)) + x\beta$$

$$P(T > t|x) = \frac{1}{1 + G(t)\exp(x\beta)}$$

Usage

```
interval.logitsurv.discrete(
  formula,
  data,
  beta = NULL,
  no.opt = FALSE,
  method = "NR",
  stderr = TRUE,
  weights = NULL,
  offsets = NULL,
  exp.link = 1,
  increment = 1,
  ...
)
```

Arguments

formula	formula
data	data
beta	starting values
no.opt	optimization TRUE/FALSE

method	NR, nlm
stderr	to return only estimate
weights	weights following id for GLM
offsets	following id for GLM
exp.link	parametrize increments $\exp(\alpha) > 0$
increment	using increments $dG(t)=\exp(\alpha)$ as parameters
...	Additional arguments to lower level funtions lava::NR optimizer or nlm

Details

This is thus also the cumulative odds model, since

$$P(T \leq t|x) = \frac{G(t) \exp(x\beta)}{1 + G(t)\exp(x\beta)}$$

The baseline $G(t)$ is written as $\text{cumsum}(\exp(\alpha))$ and this is not the standard parametrization that takes log of $G(t)$ as the parameters.

Input are intervals given by $[t_{l,r}]$ where t_r can be infinity for right-censored intervals When truly discrete $]0,1]$ will be an observation at 1, and $]j,j+1]$ will be an observation at $j+1$

Likelihood is maximized:

$$\prod P(T_i > t_{il}|x) - P(T_i > t_{ir}|x)$$

Author(s)

Thomas Scheike

Examples

```
data(ttpd)
dtble(ttpd,~entry+time2)
out <- interval.logitsurv.discrete(Interval(entry,time2)~X1+X2+X3+X4,ttpd)
summary(out)

pred <- predictlogitSurvd(out,se=FALSE)
plotSurvd(pred)
```

Description

Internal function. Calculates Inverse Probability of Censoring Weights (IPCW) and adds them to a data.frame

Usage

```
ipw(
  formula,
  data,
  cluster,
  same.cens = FALSE,
  obs.only = FALSE,
  weight.name = "w",
  trunc.prob = FALSE,
  weight.name2 = "wt",
  indi.weight = "pr",
  cens.model = "aalen",
  pairs = FALSE,
  theta.formula = ~1,
  ...
)
```

Arguments

<code>formula</code>	Formula specifying the censoring model
<code>data</code>	data frame
<code>cluster</code>	clustering variable
<code>same.cens</code>	For clustered data, should same censoring be assumed (bivariate probability calculated as minimum of the marginal probabilities)
<code>obs.only</code>	Return data with uncensored observations only
<code>weight.name</code>	Name of weight variable in the new data.frame
<code>trunc.prob</code>	If TRUE truncation probabilities are also calculated and stored in 'weight.name2' (based on Clayton-Oakes gamma frailty model)
<code>weight.name2</code>	Name of truncation probabilities
<code>indi.weight</code>	Name of individual censoring weight in the new data.frame
<code>cens.model</code>	Censoring model (default Aalens additive model)
<code>pairs</code>	For paired data (e.g. twins) only the complete pairs are returned (With pairs=TRUE)
<code>theta.formula</code>	Model for the dependence parameter in the Clayton-Oakes model (truncation only)
<code>...</code>	Additional arguments to censoring model

Author(s)

Klaus K. Holst

Examples

```
## Not run:
data("prt", package="mets")
prt <- ipw(Surv(time, status==0)~country, data=prt[sample(nrow(prt), 5000), ],
```

```

    cluster="id",weight.name="w")
plot(0,type="n",xlim=range(prtw$time),ylim=c(0,1),xlab="Age",ylab="Probability")
count <- 0
for (l in unique(prtw$country)) {
  count <- count+1
  prtw <- prtw[order(prtw$time),]
  with(subset(prtw,country==l),
    lines(time,w,col=count,lwd=2))
}
legend("topright",legend=unique(prtw$country),col=1:4,pch=-1,lty=1)

## End(Not run)

```

ipw2*Inverse Probability of Censoring Weights***Description**

Internal function. Calculates Inverse Probability of Censoring and Truncation Weights and adds them to a data.frame

Usage

```

ipw2(
  data,
  times = NULL,
  entrytime = NULL,
  time = "time",
  cause = "cause",
  same.cens = FALSE,
  cluster = NULL,
  pairs = FALSE,
  strata = NULL,
  obs.only = TRUE,
  cens.formula = NULL,
  cens.code = 0,
  pair.cweight = "pcw",
  pair.tweight = "ptw",
  pair.weight = "weights",
  cname = "cweights",
  tname = "tweights",
  weight.name = "indi.weights",
  prec.factor = 100,
  ...
)

```

Arguments

<code>data</code>	data frame
<code>times</code>	possible time argument for specifying a maximum value of time tau=max(times), to specify when things are considered censored or not.
<code>entrytime</code>	name of entry-time for truncation.
<code>time</code>	name of time variable on data frame.
<code>cause</code>	name of cause indicator on data frame.
<code>same.cens</code>	For clustered data, should same censoring be assumed and same truncation (bivariate probability calculated as minimum of the marginal probabilities)
<code>cluster</code>	name of clustering variable
<code>pairs</code>	For paired data (e.g. twins) only the complete pairs are returned (With pairs=TRUE)
<code>strata</code>	name of strata variable to get weights stratified.
<code>obs.only</code>	Return data with uncensored observations only
<code>cens.formula</code>	model for Cox models for truncation and right censoring times.
<code>cens.code</code>	censoring.code
<code>pair.cweight</code>	Name of weight variable in the new data.frame for right censoring of pairs
<code>pair.tweight</code>	Name of weight variable in the new data.frame for left truncation of pairs
<code>pair.weight</code>	Name of weight variable in the new data.frame for right censoring and left truncation of pairs
<code>cname</code>	Name of weight variable in the new data.frame for right censoring of individuals
<code>tname</code>	Name of weight variable in the new data.frame for left truncation of individuals
<code>weight.name</code>	Name of weight variable in the new data.frame for right censoring and left truncation of individuals
<code>prec.factor</code>	To let tied censoring and truncation times come after the death times.
<code>...</code>	Additional arguments to censoring model

Author(s)

Thomas Scheike

Examples

```
library("timereg")
set.seed(1)
d <- simnordic.random(5000,delayed=TRUE,ptrunc=0.7,
                      cordz=0.5,cormz=2,lambda=0.3,country=FALSE)
d$strata <- as.numeric(d$country)+(d$zyg=="MZ")*4
times <- seq(60,100,by=10)
c1 <- timereg::comp.risk(Event(time,cause)~1+cluster(id),data=d,cause=1,
                           model="fg",times=times,max.clust=NULL,n.sim=0)
mm=model.matrix(~1+zyg,data=d)
out1<-random.cif(c1,data=d,cause1=1,cause2=1,same.cens=TRUE,theta.des=mm)
summary(out1)
```

```

pc1 <- predict(c1,X=1,se=0)
plot(pc1)

dl <- d[!d$truncated,]
dl <- ipw2(dl,cluster="id",same.cens=TRUE,time="time",entrytime="entry",cause="cause",
           strata="strata",prec.factor=100)
cl <- timereg::comp.risk(Event(time,cause)~+1+
  cluster(id),
  data=dl,cause=1,model="fg",
  weights=dl$indi.weights,cens.weights=rep(1,nrow(dl)),
  times=times,max.clust=NULL,n.sim=0)
pcl <- predict(cl,X=1,se=0)
lines(pcl$time,pcl$P1,col=2)
mm=model.matrix(~-1+factor(zyg),data=dl)
out2<-random.cif(cl,data=dl,cause1=1,cause2=1,theta.des=mm,
                   weights=dl$weights,censoring.weights=rep(1,nrow(dl)))
summary(out2)

```

km

Kaplan-Meier with robust standard errors

Description

Kaplan-Meier with robust standard errors Robust variance is default variance with the summary.

Usage

```

km(
  formula,
  data = data,
  conf.type = "log",
  conf.int = 0.95,
  robust = TRUE,
  ...
)

```

Arguments

formula	formula with 'Surv' outcome (see coxph)
data	data frame
conf.type	transformation
conf.int	level of confidence intervals
robust	for robust standard errors based on martingales
...	Additional arguments to lower level funtions

Author(s)

Thomas Scheike

Examples

```
data(TRACE)
TRACE$cluster <- sample(1:100,1878,replace=TRUE)
out1 <- km(Surv(time,status==9)~strata(vf,chf),data=TRACE)
out2 <- km(Surv(time,status==9)~strata(vf,chf)+cluster(cluster),data=TRACE)

par(mfrow=c(1,2))
bplot(out1,se=TRUE)
bplot(out2,se=TRUE)
```

lifecourse

Life-course plot

Description

Life-course plot for event life data with recurrent events

Usage

```
lifecourse(
  formula,
  data,
  id = "id",
  group = NULL,
  type = "l",
  lty = 1,
  col = 1:10,
  alpha = 0.3,
  lwd = 1,
  recurrent.col = NULL,
  recurrent.lty = NULL,
  legend = NULL,
  pchlegend = NULL,
  by = NULL,
  status.legend = NULL,
  place.sl = "bottomright",
  xlab = "Time",
  ylab = "",
  add = FALSE,
  ...
)
```

Arguments

formula	Formula (Event(start,slut,status) ~ ...)
data	data.frame
id	Id variable

group	group variable
type	Type (line 'l', stair 's', ...)
lty	Line type
col	Colour
alpha	transparency (0-1)
lwd	Line width
recurrent.col	col of recurrence type
recurrent.lty	lty's of of recurrence type
legend	position of optional id legend
pchlegend	point type legends
by	make separate plot for each level in 'by' (formula, name of column, or vector)
status.legend	Status legend
place.sl	Placement of status legend
xlab	Label of X-axis
ylab	Label of Y-axis
add	Add to existing device
...	Additional arguments to lower level arguments

Author(s)

Thomas Scheike, Klaus K. Holst

Examples

```

data = data.frame(id=c(1,1,1,2,2),start=c(0,1,2,3,4),slut=c(1,2,4,4,7),
                  type=c(1,2,3,2,3),status=c(0,1,2,1,2),group=c(1,1,1,2,2))
l1 = lifecourse(Event(start,slut,status)~id,data,id="id")
l1 = lifecourse(Event(start,slut,status)~id,data,id="id",recurrent.col="type")

l1 = lifecourse(Event(start,slut,status)~id,data,id="id",group=~group,col=1:2)
op <- par(mfrow=c(1,2))
l1 = lifecourse(Event(start,slut,status)~id,data,id="id",by=~group)
par(op)
legends=c("censored","pregnant","married")
l1 = lifecourse(Event(start,slut,status)~id,data,id="id",group=~group,col=1:2,status.legend=legends)

```

lifetable.matrix *Life table*

Description

Create simple life table

Usage

```
## S3 method for class 'matrix'
lifetable(x, strata = list(), breaks = c(),
          weights=NULL, confint = FALSE, ...)

## S3 method for class 'formula'
lifetable(x, data=parent.frame(), breaks = c(),
          weights=NULL, confint = FALSE, ...)
```

Arguments

x	time formula (Surv) or matrix/data.frame with columns time,status or entry,exit,status
strata	strata
breaks	time intervals
weights	weights variable
confint	if TRUE 95% confidence limits are calculated
...	additional arguments to lower level functions
data	data.frame

Author(s)

Klaus K. Holst

Examples

```
library(timereg)
data(TRACE)

d <- with(TRACE,lifetable(Surv(time,status==9)~sex+vf,breaks=c(0,0.2,0.5,8.5)))
summary(glm(events ~ offset(log(atrisk))+factor(int.end)*vf + sex*vf,
           data=d,poisson))
```

LinSpline

*Simple linear spline***Description**

Simple linear spline

Usage

```
LinSpline(x, knots, num = TRUE, name = "Spline")
```

Arguments

x	variable to make into spline
knots	cut points
num	to give names x1 x2 and so forth
name	name of spline expansion name.1 name.2 and so forth

Author(s)

Thomas Scheike

logitSurv

*Proportional odds survival model***Description**

Semiparametric Proportional odds model, that has the advantage that

$$\text{logit}(S(t|x)) = \log(\Lambda(t)) + x\beta$$

so covariate effects give OR of survival.

Usage

```
logitSurv(formula, data, offset = NULL, weights = NULL, ...)
```

Arguments

formula	formula with 'Surv' outcome (see coxph)
data	data frame
offset	offsets for exp(x beta) terms
weights	weights for score equations
...	Additional arguments to lower level funtions

Details

This is equivalent to using a hazards model

$$Z\lambda(t) \exp(x\beta)$$

where Z is gamma distributed with mean and variance 1.

Author(s)

Thomas Scheike

References

The proportional odds cumulative incidence model for competing risks, Eriksson, Frank and Li, Jianing and Scheike, Thomas and Zhang, Mei-Jie, Biometrics, 2015, 3, 687–695, 71,

Examples

```
data(TRACE)
dcut(TRACE) <- ~.
out1 <- logitSurv(Surv(time,status==9)~vf+chf+strata(wmicat.4),data=TRACE)
summary(out1)
gof(out1)
plot(out1)
```

Description

Mediation analysis in survival context with robust standard errors taking the weights into account via influence function computations. Mediator and exposure must be factors. This is based on numerical derivative wrt parameters for weighting. See vignette for more examples.

Usage

```
mediatorSurv(
  survmodel,
  weightmodel,
  data = data,
  wdata = wdata,
  id = "id",
  silent = TRUE,
  ...
)
```

Arguments

survmodel	with mediation model (binreg, aalenMets, phreg)
weightmodel	mediation model
data	for computations
wdata	weighted data expansion for computations
id	name of id variable, important for SE computations
silent	to be silent
...	Additional arguments to survival model

Author(s)

Thomas Scheike

Examples

```

n <- 400
dat <- kumarsimRCT(n,rho1=0.5,rho2=0.5,rct=2,censpar=c(0,0,0,0),
                     beta = c(-0.67, 0.59, 0.55, 0.25, 0.98, 0.18, 0.45, 0.31),
                     treatmodel = c(-0.18, 0.56, 0.56, 0.54),restrict=1)
dfactor(dat) <- dnr.f~dnr
dfactor(dat) <- gp.f~gp
drename(dat) <- ttt24~"ttt24*"
dat$id <- 1:n
dat$ftime <- 1

weightmodel <- fit <- glm(gp.f~dnr.f+preauto+ttt24,data=dat,family=binomial)
wdata <- medweight(fit,data=dat)

### fitting models with and without mediator
aaMss2 <- binreg(Event(time,status)~gp+dnr+preauto+ttt24+cluster(id),data=dat,time=50,cause=2)
aaMss22 <- binreg(Event(time,status)~dnr+preauto+ttt24+cluster(id),data=dat,time=50,cause=2)

### estimating direct and indirect effects (under strong strong assumptions)
aaMss <- binreg(Event(time,status)~dnr.f0+dnr.f1+preauto+ttt24+cluster(id),
                 data=wdata,time=50,weights=wdata$weights,cause=2)
## to compute standard errors , requires numDeriv
library(numDeriv)
l1 <- mediatorSurv(aaMss,fit,data=dat,wdata=wdata)
summary(l1)
## not run bootstrap (to save time)
## bll <- BootmediatorSurv(aaMss,fit,data=dat,k.boot=500)

```

medweight	<i>Computes mediation weights</i>
-----------	-----------------------------------

Description

Computes mediation weights for either binary or multinomial mediators. The important part is that the influence functions can be obtained to compute standard errors.

Usage

```
medweight(
  fit,
  data = data,
  var = NULL,
  name.weight = "weights",
  id.name = "id",
  ...
)
```

Arguments

fit	either glm-binomial or mlogit (mets package)
data	data frame with data
var	is NULL reads mediator and exposure from formulae in the fit.
name.weight	name of weights
id.name	name of id variable, important for SE computations
...	Additional arguments to

Author(s)

Thomas Scheike

melanoma	<i>The Melanoma Survival Data</i>
----------	-----------------------------------

Description

The melanoma data frame has 205 rows and 7 columns. It contains data relating to survival of patients after operation for malignant melanoma collected at Odense University Hospital by K.T. Drzewiecki.

Format

This data frame contains the following columns:

no a numeric vector. Patient code.

status a numeric vector code. Survival status. 1: dead from melanoma, 2: alive, 3: dead from other cause.

days a numeric vector. Survival time.

ulc a numeric vector code. Ulceration, 1: present, 0: absent.

thick a numeric vector. Tumour thickness (1/100 mm).

sex a numeric vector code. 0: female, 1: male.

Source

Andersen, P.K., Borgan O, Gill R.D., Keiding N. (1993), *Statistical Models Based on Counting Processes*, Springer-Verlag.

Drzewiecki, K.T., Ladefoged, C., and Christensen, H.E. (1980), Biopsy and prognosis for cutaneous malignant melanoma in clinical stage I. Scand. J. Plast. Reconstr. Surg. 14, 141-144.

Examples

```
data(melanoma)
names(melanoma)
```

mena

Menarche data set

Description

Menarche data set

Source

Simulated data

<code>mets.options</code>	<i>Set global options for mets</i>
---------------------------	------------------------------------

Description

Extract and set global parameters of `mets`.

Usage

```
mets.options(...)
```

Arguments

<code>...</code>	Arguments
------------------	-----------

Details

- `regex`: If TRUE character vectors will be interpreted as regular expressions (`dby`, `dcut`, ...)
- `silent`: Set to FALSE to disable various output messages

Value

list of parameters

Examples

```
## Not run:  
mets.options(regex=TRUE)  
  
## End(Not run)
```

<code>migr</code>	<i>Migraine data</i>
-------------------	----------------------

Description

Migraine data

mlogit*Multinomial regression based on phreg regression***Description**

Fits multinomial regression model

$$P_i = \frac{\exp(X_i^\beta)}{\sum_{j=1}^K \exp(X_j^\beta)}$$

for

$$i = 1, \dots, K$$

where

$$\beta_1 = 0$$

, such that

$$\sum_j P_j = 1$$

using phreg function. Therefore the ratio

$$\frac{P_i}{P_1} = \exp(X_i^\beta)$$

Usage

```
mlogit(formula, data, offset = NULL, weights = NULL, fix.X = FALSE, ...)
```

Arguments

<code>formula</code>	formula with outcome (see coxph)
<code>data</code>	data frame
<code>offset</code>	offsets for partial likelihood
<code>weights</code>	for score equations
<code>fix.X</code>	to have same coefficients for all categories
<code>...</code>	Additional arguments to lower level functions

Details

Coefficients give log-Relative-Risk relative to baseline group (first level of factor, so that it can reset by relevel command). Standard errors computed based on sandwich form

$$DU^{-1} \sum U_i^2 DU^{-1}$$

Can also get influence functions (possibly robust) via iid() function, response should be a factor.

Can fit cumulative odds model as a special case of interval.logitsurv.discrete

Author(s)

Thomas Scheike

Examples

```

data(bmt)
dfactor(bmt) <- cause1f~cause
drelevel(bmt,ref=3) <- cause3f~cause
dlevels(bmt)

mreg <- mlogit(cause1f~+1,bmt)
summary(mreg)

mreg <- mlogit(cause1f~tcell+platelet,bmt)
summary(mreg)

mreg3 <- mlogit(cause3f~tcell+platelet,bmt)
summary(mreg3)

## inverse information standard errors
lava::estimate(coef=mreg3$coef,vcov=mreg3$II)

## predictions based on seen response or not
newdata <- data.frame(tcell=c(1,1,1),platelet=c(0,1,1),cause1f=c("2","1","0"))
predictmlogit(mreg,newdata,response=FALSE)
predictmllogit(mreg,newdata)

```

multcif

Multivariate Cumulative Incidence Function example data set

Description

Multivariate Cumulative Incidence Function example data set

Source

Simulated data

np

np data set

Description

np data set

Source

Simulated data

npc

For internal use

Description

For internal use

Author(s)

Klaus K. Holst

phreg

Fast Cox PH regression

Description

Fast Cox PH regression Robust variance is default variance with the summary.

Usage

```
phreg(formula, data, offset = NULL, weights = NULL, ...)
```

Arguments

formula	formula with 'Surv' outcome (see coxph)
data	data frame
offset	offsets for cox model
weights	weights for Cox score equations
...	Additional arguments to lower level funtions

Details

influence functions (iid) will follow numerical order of given cluster variable so ordering after \$id will give iid in order of data-set.

Author(s)

Klaus K. Holst, Thomas Scheike

Examples

```

data(TRACE)
dcut(TRACE) <- ~.
out1 <- phreg(Surv(time,status==9)~vf+chf+strata(wmicat.4),data=TRACE)
out2 <- phreg(Event(time,status)~vf+chf+strata(wmicat.4),data=TRACE)
## tracesim <- timereg::sim.cox(out1,1000)
## sout1 <- phreg(Surv(time,status==1)~vf+chf+strata(wmicat.4),data=tracesim)
## robust standard errors default
summary(out1)
out1 <- phreg(Surv(time,status!=0)~vf+chf+strata(wmicat.4),data=TRACE)
summary(out2)

par(mfrow=c(1,2))
bplot(out1)
## bplot(sout1,se=TRUE)

## computing robust variance for baseline
rob1 <- robust.phreg(out1)
bplot(rob1,se=TRUE,robust=TRUE)

## making iid decomposition of regression parameters
betaiid <- lava:::iid(out1)

## making iid decomposition of baseline at a specific time-point
Aiid <- mets:::IIDbaseline.phreg(out1,time=30)

```

phregR

Fast Cox PH regression and calculations done in R to make play and adjustments easy

Description

Fast Cox PH regression with R implementation to play and adjust in R function: FastCoxPLstrataR

Usage

```
phregR(formula, data, offset = NULL, weights = NULL, ...)
```

Arguments

formula	formula with 'Surv' outcome (see coxph)
data	data frame
offset	offsets for cox model
weights	weights for Cox score equations
...	Additional arguments to lower level funtions

Details

Robust variance is default variance with the summary.

influence functions (iid) will follow numerical order of given cluster variable so ordering after \$id will give iid in order of data-set.

Author(s)

Klaus K. Holst, Thomas Scheike

plack.cif

plack Computes concordance for or.cif based model, that is Plackett random effects model

Description

.. content for description (no empty lines) ..

Usage

plack.cif(cif1, cif2, object)

Arguments

- | | |
|--------|-------------------------------------------|
| cif1 | Cumulative incidence of first argument. |
| cif2 | Cumulative incidence of second argument. |
| object | or.cif object with dependence parameters. |

Author(s)

Thomas Scheike

pmvn

Multivariate normal distribution function

Description

Multivariate normal distribution function

Usage

pmvn(lower, upper, mu, sigma, cor = FALSE)

Arguments

<code>lower</code>	lower limits
<code>upper</code>	upper limits
<code>mu</code>	mean vector
<code>sigma</code>	variance matrix or vector of correlation coefficients
<code>cor</code>	if TRUE sigma is treated as standardized (correlation matrix)

Examples

```
lower <- rbind(c(0,-Inf),c(-Inf,0))
upper <- rbind(c(Inf,0),c(0,Inf))
mu <- rbind(c(1,1),c(-1,1))
sigma <- diag(2)+1
pmvn(lower=lower,upper=upper,mu=mu,sigma=sigma)
```

predict.phreg*Predictions from proportional hazards model***Description**

Predictions from proportional hazards model

Usage

```
## S3 method for class 'phreg'
predict(
  object,
  newdata,
  times = NULL,
  individual.time = FALSE,
  tminus = FALSE,
  se = TRUE,
  robust = FALSE,
  conf.type = "log",
  conf.int = 0.95,
  km = FALSE,
  ...
)
```

Arguments

<code>object</code>	phreg object
<code>newdata</code>	data.frame
<code>times</code>	Time where to predict variable, default is all time-points from the object sorted

individual.time	to use one (individual) time per subject, and then newdata and times have same length and makes only predictions for these individual times.
tminus	to make predictions in T- that is strictly before given times, useful for IPCW techniques
se	with standard errors and upper and lower confidence intervals.
robust	to get robust se's.
conf.type	transformation for survival estimates, default is log
conf.int	significance level
km	to use Kaplan-Meier product-limit for baseline

$$S_{s0}(t) = (1 - dA_{s0}(t))$$

, otherwise take exp of cumulative baseline.

... Additional arguments to plot functions

print.casewise *prints Concordance test*

Description

prints Concordance test

Usage

```
## S3 method for class 'casewise'
print(x, digits = 3, ...)
```

Arguments

x	output from casewise.test
digits	number of digits
...	Additional arguments to lower level functions

Author(s)

Thomas Scheike

`prob.exceed.recurrent` *Estimation of probability of more than k events for recurrent events process*

Description

Estimation of probability of more than k events for recurrent events process where there is terminal event, based on this also estimate of variance of recurrent events. The estimator is based on cumulative incidence of exceeding "k" events. In contrast the probability of exceeding k events can also be computed as a counting process integral, and this is implemented in prob.exceedRecurrent

Usage

```
prob.exceed.recurrent(
  data,
  type,
  status = "status",
  death = "death",
  start = "start",
  stop = "stop",
  id = "id",
  times = NULL,
  exceed = NULL,
  cifmets = TRUE,
  strata = NULL,
  all.cifs = FALSE,
  ...
)
```

Arguments

<code>data</code>	data-frame
<code>type</code>	type of event (code) related to status
<code>status</code>	name of status
<code>death</code>	name of death indicator
<code>start</code>	start stop call of Hist() of prodlim
<code>stop</code>	start stop call of Hist() of prodlim
<code>id</code>	id
<code>times</code>	time at which to get probabilities $P(N_1(t) \geq n)$
<code>exceed</code>	n's for which to compute probabilities $P(N_1(t) \geq n)$
<code>cifmets</code>	if true uses cif of mets package rather than prodlim
<code>strata</code>	to stratify according to variable, only for cifmets=TRUE, when strata is given then only consider the output in the all.cifs
<code>all.cifs</code>	if true then returns list of all fitted objects in cif.exceed
<code>...</code>	Additional arguments to lower level functions

Author(s)

Thomas Scheike

References

Scheike, Eriksson, Tribler (2019) The mean, variance and correlation for bivariate recurrent events with a terminal event, JRSS-C

Examples

```
#####
## getting some rates to mimick
#####

data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
dr <- drcumhaz
base1 <- base1cumhaz
base4 <- base4cumhaz

cor.mat <- corM <- rbind(c(1.0, 0.6, 0.9), c(0.6, 1.0, 0.5), c(0.9, 0.5, 1.0))
rr <- simRecurrentII(1000,base4,cumhaz2=base4,death.cumhaz=dr,cens=2/5000)
rr <- count.history(rr)
dtbl(rr,~death+status)

oo <- prob.exceedRecurrent(rr,1)
bplot(oo)

par(mfrow=c(1,2))
with(oo,plot(time,mu,col=2,type="l"))
##
with(oo,plot(time,varN,type="l"))

### Bivariate probability of exceeding
oo <- prob.exceedBiRecurrent(rr,1,2,exceed1=c(1,5),exceed2=c(1,2))
with(oo, matplot(time,pe1e2,type="s"))
nc <- ncol(oo$pe1e2)
legend("topleft",legend=colnames(oo$pe1e2),lty=1:nc,col=1:nc)

### do not test to avoid dependence on prodlim
### now estimation based on cumulative incidence, but do not test to avoid dependence on prodlim
### library(prodlim)
pp <- prob.exceed.recurrent(rr,1,status="status",death="death",start="entry",stop="time",id="id")
with(pp, matplot(times,prob,type="s"))
##
with(pp, matlines(times,se.lower,type="s"))
with(pp, matlines(times,se.upper,type="s"))
```

prt	<i>Prostate data set</i>
-----	--------------------------

Description

Prostate data set

Source

Simulated data

random.cif	<i>Random effects model for competing risks data</i>
------------	------------------------------------------------------

Description

Fits a random effects model describing the dependence in the cumulative incidence curves for subjects within a cluster. Given the gamma distributed random effects it is assumed that the cumulative incidence curves are independent, and that the marginal cumulative incidence curves are on the form

$$P(T \leq t, cause = 1 | x, z) = P_1(t, x, z) = 1 - \exp(-x^T A(t) \exp(z^T \beta))$$

We allow a regression structure for the random effects variances that may depend on cluster covariates.

Usage

```
random.cif(
  cif,
  data,
  cause = NULL,
  cif2 = NULL,
  cause1 = 1,
  cause2 = 1,
  cens.code = NULL,
  cens.model = "KM",
  Nit = 40,
  detail = 0,
  clusters = NULL,
  theta = NULL,
  theta.des = NULL,
  sym = 1,
  step = 1,
  same.cens = FALSE,
```

```

var.link = 0,
score.method = "nr",
entry = NULL,
trunkp = 1,
...
)

```

Arguments

cif	a model object from the comp.risk function with the marginal cumulative incidence of cause2, i.e., the event that is conditioned on, and whose odds the comparision is made with respect to
data	a data.frame with the variables.
cause	specifies the causes related to the death times, the value cens.code is the censoring value.
cif2	specifies model for cause2 if different from cause1.
cause1	cause of first coordinate.
cause2	cause of second coordinate.
cens.code	specifies the code for the censoring if NULL then uses the one from the marginal cif model.
cens.model	specified which model to use for the ICPW, KM is Kaplan-Meier alternatively it may be "cox"
Nit	number of iterations for Newton-Raphson algorithm.
detail	if 0 no details are printed during iterations, if 1 details are given.
clusters	specifies the cluster structure.
theta	specifies starting values for the cross-odds-ratio parameters of the model.
theta.des	specifies a regression design for the cross-odds-ratio parameters.
sym	1 for symmetry 0 otherwise
step	specifies the step size for the Newton-Raphson algorithm.m
same.cens	if true then censoring within clusters are assumed to be the same variable, default is independent censoring.
var.link	if var.link=1 then var is on log-scale.
score.method	default uses "nlminb" optimzer, alternatively, use the "nr" algorithm.
entry	entry-age in case of delayed entry. Then two causes must be given.
trunkp	gives probability of survival for delayed entry, and related to entry-ages given above.
...	extra arguments.

Value

returns an object of type 'cor'. With the following arguments:

theta	estimate of proportional odds parameters of model.
-------	----------------------------------------------------

<code>var.theta</code>	variance for gamma.
<code>hess</code>	the derivative of the used score.
<code>score</code>	scores at final stage.
<code>score</code>	scores at final stage.
<code>theta.iid</code>	matrix of iid decomposition of parametric effects.

Author(s)

Thomas Scheike

References

A Semiparametric Random Effects Model for Multivariate Competing Risks Data, Scheike, Zhang, Sun, Jensen (2010), Biometrika.

Cross odds ratio Modelling of dependence for Multivariate Competing Risks Data, Scheike and Sun (2012), work in progress.

Examples

```
## Reduce Ex.Timings
d <- simnordic.random(5000,delayed=TRUE,cordz=0.5,cormz=2,lambda=0.3,country=TRUE)
times <- seq(50,90,by=10)
add1 <- timereg::comp.risk(Event(time,cause)~-1+factor(country)+cluster(id),data=d,
times=times,cause=1,max.clust=NULL)

#### making group indicator
mm <- model.matrix(~-1+factor(zyg),d)

out1<-random.cif(add1,data=d,cause1=1,cause2=1,theta=1,same.cens=TRUE)
summary(out1)

out2<-random.cif(add1,data=d,cause1=1,cause2=1,theta=1,
theta.des=mm,same.cens=TRUE)
summary(out2)

#####
##### 2 different causes
#####

add2 <- timereg::comp.risk(Event(time,cause)~-1+factor(country)+cluster(id),data=d,
times=times,cause=2,max.clust=NULL)
out3 <- random.cif(add1,data=d,cause1=1,cause2=2,cif2=add2,sym=1,same.cens=TRUE)
summary(out3) ## negative dependence

out4 <- random.cif(add1,data=d,cause1=1,cause2=2,cif2=add2,theta.des=mm,sym=1,same.cens=TRUE)
summary(out4) ## negative dependence
```

rchaz*Simulation of Piecewise constant hazard model (Cox).*

Description

Simulates data from piecewise constant baseline hazard that can also be of Cox type. Censor data at highest value of the break points.

Usage

```
rchaz(
  cumhazard,
  rr,
  n = NULL,
  entry = NULL,
  cum.hazard = TRUE,
  cause = 1,
  extend = FALSE
)
```

Arguments

cumhazard	cumulative hazard, or piece-constant rates for periods defined by first column of input.
rr	relative risk for simulations, alternatively when rr=1 specify n
n	number of simulation if rr not given
entry	delayed entry time for simulations.
cum.hazard	specifies wheter input is cumulative hazard or rates.
cause	name of cause
extend	to extend piecewise constant with constant rate. Default is average rate over time from cumulative (when TRUE), if numeric then uses given rate.

Details

For a piecewise linear cumulative hazard the inverse is easy to compute with and delayed entry x we compute

$$\Lambda^{-1}(\Lambda(x) + E/RR)$$

, where RR are the relative risks and E is exponential with mean 1. This quantity has survival function

$$P(T > t | T > x) = \exp(-RR(\Lambda(t) - \Lambda(x)))$$

Author(s)

Thomas Scheike

Examples

```

chaz <- c(0,1,1.5,2,2.1)
breaks <- c(0,10, 20, 30, 40)
cumhaz <- cbind(breaks,chaz)
n <- 100
X <- rbinom(n,1,0.5)
beta <- 0.2
rrcox <- exp(X * beta)

pctime <- rchaz(cumhaz,n=1000,cum.hazard=FALSE)
pctimecox <- rchaz(cumhaz,rrcox,cum.hazard=FALSE)

```

rcrisk

Simulation of Piecewise constant hazard models with two causes (Cox).

Description

Simulates data from piecewise constant baseline hazard that can also be of Cox type. Censor data at highest value of the break points for either of the cumulatives.

Usage

```
rcrisk(cumhaz1, cumhaz2, rr1, rr2, n = NULL, cens = NULL, rrc = NULL, ...)
```

Arguments

<code>cumhaz1</code>	cumulative hazard of cause 1
<code>cumhaz2</code>	cumulative hazard of cause 1
<code>rr1</code>	number of simulations or vector of relative risk for simulations.
<code>rr2</code>	number of simulations or vector of relative risk for simulations.
<code>n</code>	number of simulation if rr not given
<code>cens</code>	to censor further , rate or cumulative hazard
<code>rrc</code>	retlativ risk for censoring.
<code>...</code>	arguments for rchaz

Author(s)

Thomas Scheike

Examples

```

library(mets); data(bmt); library(survival)

cox1 <- phreg(Surv(time,cause==1)~tcell+platelet,data=bmt)
cox2 <- phreg(Surv(time,cause==2)~tcell+platelet,data=bmt)

X1 <- bmt[,c("tcell","platelet")]
n <- 100
xid <- sample(1:nrow(X1),n,replace=TRUE)
Z1 <- X1[xid,]
Z2 <- X1[xid,]
rr1 <- exp(as.matrix(Z1) %*% cox1$coef)
rr2 <- exp(as.matrix(Z2) %*% cox2$coef)

d <- rcrisk(cox1$cum,cox2$cum,rr1,rr2)
dd <- cbind(d,Z1)

scox1 <- phreg(Surv(time,status==1)~tcell+platelet,data=dd)
scox2 <- phreg(Surv(time,status==2)~tcell+platelet,data=dd)
par(mfrow=c(1,2))
plot(cox1); plot(scox1,add=TRUE)
plot(cox2); plot(scox2,add=TRUE)
cbind(cox1$coef,scox1$coef,cox2$coef,scox2$coef)

```

recreg

Recurrent events regression with terminal event

Description

Fits Ghosh-Lin IPCW Cox-type model

Usage

```

recreg(
  formula,
  data = data,
  cause = 1,
  death.code = c(2),
  cens.code = 0,
  cens.model = ~1,
  weights = NULL,
  offset = NULL,
  Gc = NULL,
  wcomp = NULL,
  ...
)

```

Arguments

formula	formula with 'EventCens' outcome
data	data frame
cause	of interest
death.code	codes for death (terminating event)
cens.code	code of censoring (1 default)
cens.model	for stratified Cox model without covariates
weights	weights for score equations
offset	offsets for model
Gc	censoring weights for time argument, default is to calculate these with a Kaplan-Meier estimator, should then give G_c(T_i-)
wcomp	weights for composite outcome, so when cause=c(1,3), we might have wcomp=c(1,2).
...	Additional arguments to lower level funtions

Details

For Cox type model :

$$E(dN_1(t)|X) = \mu_0(t)dt \exp(X^T \beta)$$

by solving Cox-type IPCW weighted score equations

$$\int (Z - E(t))w(t)dN_1(t)$$

where

$$w(t) = G(t)(I(T_i \wedge t < C_i)/G_c(T_i \wedge t))$$

and

$$E(t) = S_1(t)/S_0(t)$$

and

$$S_j(t) = \sum X_i^j w_i(t) \exp(X_i^T \beta)$$

The iid decomposition of the beta's are on the form

$$\int (Z - E)w(t)dM_1 + \int q(s)/p(s)dM_c$$

and returned as iid.

Events, deaths and censorings are specified via stop start structure and the Event call, that via a status vector and cause (code), censoring-codes (cens.code) and death-codes (death.code) indentifies these. See example and vignette.

Author(s)

Thomas Scheike

Examples

```

## data with no ties
data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
Lam1 <- base1cumhaz; Lam2 <- base4cumhaz; LamD <- drcumhaz
## simulates recurrent events of types 1 and 2 and with terminal event D and censoring
rr <- simRecurrentII(1000,Lam1,cumhaz2=Lam2,death.cumhaz=LamD,cens=3/5000)
rr <- count.history(rr)
rr$cens <- 0
nid <- max(rr$id)
rr$revnr <- revcumsumstrata(rep(1,nrow(rr)),rr$id-1,nid)
rr$x <- rnorm(nid)[rr$id]
rr$statusG <- rr$status
rr <- dtransform(rr,statusG=3,death==1)
datatable(rr,~statusG+status+death)
dcut(rr) <- gx~x

ll <- recreg(Event(start,stop,statusG)~x+cluster(id),data=rr,cause=1,death.code=3)
summary(ll)

## censoring stratified after quartiles of x
lls <- recreg(Event(start, stop, statusG)~x+cluster(id),data=rr,cause=1,
               death.code=3,cens.model=~strata(gx))
summary(lls)

```

Description

Fast Marginal means of recurrent events. Using the Lin and Ghosh (2000) standard errors. Fitting two models for death and recurrent events these are combined to prducte the estimator

$$\int_0^t S(u|x=0)dR(u|x=0)$$

the mean number of recurrent events, here

$$S(u|x=0)$$

is the probability of survival for the baseline group, and

$$dR(u|x=0)$$

is the hazard rate of an event among survivors for the baseline. Here

$$S(u|x=0)$$

is estimated by

$$\exp(-\Lambda_d(u|x=0))$$

with

$$\Lambda_d(u|x=0)$$

being the cumulative baseline for death.

Usage

```
recurrentMarginal(recurrent, death, fixbeta = NULL, km = TRUE, ...)
```

Arguments

recurrent	phreg object with recurrent events
death	phreg object with deaths
fixbeta	to force the estimation of standard errors to think of regression coefficients as known/fixed
km	if true then uses Kaplan-Meier for death, otherwise exp(- Nelson-Aalen)
...	Additional arguments to lower level funtions

Details

Assumes no ties in the sense that jump times needs to be unique, this is particularly so for the stratified version.

Author(s)

Thomas Scheike

References

Ghosh and Lin (2002) Nonparametric Analysis of Recurrent events and death, Biometrics, 554–562.

Examples

```
data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
dr <- drcumhaz
base1 <- base1cumhaz
base4 <- base4cumhaz
rr <- simRecurrent(1000,base1,death.cumhaz=dr)
rr$x <- rnorm(nrow(rr))
rr$strata <- floor((rr$id-0.01)/500)

## to fit non-parametric models with just a baseline
xr <- phreg(Surv(entry,time,status)~cluster(id),data=rr)
dr <- phreg(Surv(entry,time,death)~cluster(id),data=rr)
par(mfrow=c(1,3))
```

```

bplot(dr,se=TRUE)
title(main="death")
bplot(xr,se=TRUE)
### robust standard errors
rxr <- robust.phreg(xr,fixbeta=1)
bplot(rxr,se=TRUE,robust=TRUE,add=TRUE,col=4)

## marginal mean of expected number of recurrent events
out <- recurrentMarginal(xr,dr)
bplot(out,se=TRUE,ylab="marginal mean",col=2)

#####
##### with strata #####
#####
xr <- phreg(Surv(entry,time,status)~strata(strata)+cluster(id),data=rr)
dr <- phreg(Surv(entry,time,death)~strata(strata)+cluster(id),data=rr)
par(mfrow=c(1,3))
bplot(dr,se=TRUE)
title(main="death")
bplot(xr,se=TRUE)
rxr <- robust.phreg(xr,fixbeta=1)
bplot(rxr,se=TRUE,robust=TRUE,add=TRUE,col=1:2)

out <- recurrentMarginal(xr,dr)
bplot(out,se=TRUE,ylab="marginal mean",col=1:2)

#####
##### cox case #####
#####
xr <- phreg(Surv(entry,time,status)~x+cluster(id),data=rr)
dr <- phreg(Surv(entry,time,death)~x+cluster(id),data=rr)
par(mfrow=c(1,3))
bplot(dr,se=TRUE)
title(main="death")
bplot(xr,se=TRUE)
rxr <- robust.phreg(xr)
bplot(rxr,se=TRUE,robust=TRUE,add=TRUE,col=1:2)

out <- recurrentMarginal(xr,dr)
bplot(out,se=TRUE,ylab="marginal mean",col=1:2)

#####
##### CIF #####
#####
### use of function to compute cumulative incidence (cif) with robust standard errors
data(bmt)
bmt$id <- 1:nrow(bmt)
xr <- phreg(Surv(time,cause==1)~cluster(id),data=bmt)
dr <- phreg(Surv(time,cause!=0)~cluster(id),data=bmt)

out <- recurrentMarginal(xr,dr,km=TRUE)
bplot(out,se=TRUE,ylab="cumulative incidence")

```

resmean.phreg	<i>Restricted mean for stratified Kaplan-Meier or Cox model with martingale standard errors</i>
---------------	-------------------------------------------------------------------------------------------------

Description

Restricted mean for stratified Kaplan-Meier or stratified Cox with martingale standard error. Standard error is computed using linear interpolation between standard errors at jump-times. Plots gives restricted mean at all times. Years lost can be computed based on this and decomposed into years lost for different causes using the cif.yearslost function that is based on integrating the cumulative incidence functions. One particular feature of these functions are that the restricted mean and years-lost are computed for all event times as functions and can be viewed. When times are given and beyond the last event time within a strata the curves are extrapolated using the estimates of cumulative incidence.

Usage

```
resmean.phreg(x, times = NULL, covs = NULL, ...)
```

Arguments

x	phreg object
times	possible times for which to report restricted mean
covs	possible covariate for Cox model
...	Additional arguments to lower level funtions

Author(s)

Thomas Scheike

Examples

```
data(bmt); bmt$time <- bmt$time+runif(408)*0.001
out1 <- phreg(Surv(time,cause!=0)~strata(tcell,platelet),data=bmt)

rm1 <- resmean.phreg(out1,times=10*(1:6))
summary(rm1)
par(mfrow=c(1,2))
plot(rm1,se=1)
plot(rm1,years.lost=TRUE,se=1)

## years.lost decomposed into causes
drm1 <- cif.yearslost(Event(time,cause)~strata(tcell,platelet),data=bmt,times=10*(1:6))
summary(drm1)
```

resmeanATE

Average Treatment effect for Restricted Mean for censored competing risks data using IPCW

Description

Under the standard causal assumptions we can estimate the average treatment effect $E(Y(1) - Y(0))$. We need Consistency, ignorability ($Y(1), Y(0)$ indep A given X), and positivity.

Usage

```
resmeanATE(
  formula,
  data,
  outcome = c("rmst", "rmst-cause"),
  model = "exp",
  ...
)
```

Arguments

formula	formula with 'Event' outcome
data	data-frame
outcome	"rmst"= $E(\min(T, t) X)$, or "rmst-cause"= $E(I(\epsilon\text{psilon} == \text{cause}) (t - \min(T, t)) X)$
model	possible exp model for relevant mean model that is $\exp(X^t \beta)$
...	Additional arguments to pass to binregATE

Details

The first covariate in the specification of the competing risks regression model must be the treatment effect that is a factor. If the factor has more than two levels then it uses the mlogit for propensity score modelling. We consider the outcome $\min(T; \tau)$ or $I(\epsilon\text{psilon} == \text{cause}) (t - \min(T; t))$ that gives years lost due to cause "cause".

Estimates the ATE using the the standard binary double robust estimating equations that are IPCW censoring adjusted.

Author(s)

Thomas Scheike

Examples

```
library(mets); data(bmt); bmt$event <- bmt$cause!=0; dfactor(bmt) <- tcell~tcell
out <- resmeanATE(Event(time,event)~tcell+platelet,data=bmt,time=40,treat.model=tcell~platelet)
summary(out)

out1 <- resmeanATE(Event(time,cause)~tcell+platelet,data=bmt,cause=1,outcome="rmst-cause",
                     time=40,treat.model=tcell~platelet)
summary(out1)
```

resmeanIPCW

Restricted IPCW mean for censored survival data

Description

Simple and fast version for IPCW regression for just one time-point thus fitting the model

$$E(\min(T, t)|X) = \exp(X^T \beta)$$

or in the case of competing risks data

$$E(I(\epsilon = 1)(t - \min(T, t))|X) = \exp(X^T \beta)$$

thus given years lost to cause.

Usage

```
resmeanIPCW(
  formula,
  data,
  cause = 1,
  time = NULL,
  beta = NULL,
  offset = NULL,
  weights = NULL,
  cens.weights = NULL,
  cens.model = ~+1,
  se = TRUE,
  kaplan.meier = TRUE,
  cens.code = 0,
  no.opt = FALSE,
  method = "nr",
  model = "exp",
  augmentation = NULL,
  h = NULL,
  MCaugment = NULL,
  Ydirect = NULL,
  ...
)
```

Arguments

formula	formula with outcome (see coxph)
data	data frame
cause	cause of interest
time	time of interest
beta	starting values
offset	offsets for partial likelihood
weights	for score equations
cens.weights	censoring weights
cens.model	only stratified cox model without covariates
se	to compute se's based on IPCW
kaplan.meier	uses Kaplan-Meier for IPCW in contrast to exp(-Baseline)
cens.code	gives censoring code
no.opt	to not optimize
method	for optimization
model	exp or linear
augmentation	to augment binomial regression
h	h for estimating equation
MCaugment	iid of h and censoring model
Ydirect	to bypass the construction of the response Y=min(T,tau) and use this instead
...	Additional arguments to lower level funtions

Details

When the status is binary assumes it is a survival setting and default is to consider outcome Y=min(T,t), if status has more than two levels, then computes years lost due to that particular cause, thus

Based on binomial regresion IPCW response estimating equation:

$$X(\Delta(\min(T, t))/G_c(\min(T_i, t)) - \exp(X^T \beta)) = 0$$

for IPCW adjusted responses. Here

$$\Delta(\min(T, t))I(\min(T, t) \leq C)$$

is indicator of being uncensored.

Can also solve the binomial regresion IPCW response estimating equation:

$$h(X)X(\Delta(\min(T, t))/G_c(\min(T_i, t)) - \exp(X^T \beta)) = 0$$

for IPCW adjusted responses where \$h\$ is given as an argument together with iid of censoring with h.

By using appropriately the h argument we can also do the efficient IPCW estimator estimator.

Variance is based on

$$\sum w_i^2$$

also with IPCW adjustment, and naive.var is variance under known censoring model.

When Ydirect is given it solves :

$$X(\Delta(\min(T, t))Y_{direct}/G_c(\min(T_i, t)) - \exp(X^T \beta)) = 0$$

for IPCW adjusted responses.

Censoring model may depend on strata.

Author(s)

Thomas Scheike

Examples

```
data(bmt); bmt$time <- bmt$time+runif(nrow(bmt))*0.001
# E( min(T; t) | X ) = exp( a+b X) with IPCW estimation
out <- resmeanIPCW(Event(time,cause!=0)~tcell+platelet+age,bmt,
                     time=50,cens.model=~strata(platelet),model="exp")
summary(out)

### same as Kaplan-Meier for full censoring model
bmt$int <- with(bmt,strata(tcell,platelet))
out <- resmeanIPCW(Event(time,cause!=0)~-1+int,bmt,time=30,
                     cens.model=~strata(platelet,tcell),model="lin")
estimate(out)
out1 <- phreg(Surv(time,cause!=0)~strata(tcell,platelet),data=bmt)
rm1 <- resmean.phreg(out1,times=30)
summary(rm1)

## competing risks years-lost for cause 1
out <- resmeanIPCW(Event(time,cause)~-1+int,bmt,time=30,cause=1,
                     cens.model=~strata(platelet,tcell),model="lin")
estimate(out)
## same as integrated cumulative incidence
rmc1 <- cif.yearslost(Surv(time,cause!=0)~cause+strata(tcell,platelet),data=bmt,times=30)
summary(rmc1)
```

rpch

Piecewise constant hazard distribution

Description

Piecewise constant hazard distribution

Usage

```
rpch(n, lambda = 1, breaks = c(0, Inf))
```

Arguments

n	sample size
lambda	rate parameters
breaks	time cut-points

sim.cause.cox

Simulation of cause specific from Cox models.

Description

Simulates data that looks like fit from cause specific Cox models. Censor data automatically. When censoring is given in the list of causes this will give censoring that looks like the data. Covariates are drawn from data-set with replacement. This gives covariates like the data.

Usage

```
sim.cause.cox(coxs, n, data=NULL, cens=NULL, rrc=NULL, ...)
```

Arguments

coxs	list of cox models.
n	number of simulations.
data	to extract covariates for simulations (draws from observed covariates).
cens	specifies censoring model, if NULL then only censoring for each cause at end of last event of this type. if "is.matrix" then uses cumulative. hazard given, if "is.scalar" then uses rate for exponential, and if not given then takes average rate of in simulated data from cox model. But censoring can also be given as a cause.
rrc	possible vector of relative risk for cox-type censoring.
...	arguments for rchaz, for example entry-time

Author(s)

Thomas Scheike

Examples

```
nsim <- 100

data(bmt)
# coxph
cox1 <- coxph(Surv(time,cause==1)~tcell+platelet,data=bmt)
cox2 <- coxph(Surv(time,cause==2)~tcell+platelet,data=bmt)
coxs <- list(cox1,cox2)
dd <- sim.cause.cox(coxs,nsim,data=bmt)
scox1 <- coxph(Surv(time,status==1)~tcell+platelet,data=dd)
scox2 <- coxph(Surv(time,status==2)~tcell+platelet,data=dd)
```

```

cbind(cox1$coef,scox1$coef)
cbind(cox2$coef,scox2$coef)

data(bmt)
cox1 <- phreg(Surv(time,cause==1)~tcell+platelet,data=bmt)
cox2 <- phreg(Surv(time,cause==2)~tcell+platelet,data=bmt)
coxs <- list(cox1,cox2)
dd <- sim.cause.cox(coxs,nsim,data=bmt)
scox1 <- phreg(Surv(time,status==1)~tcell+platelet,data=dd)
scox2 <- phreg(Surv(time,status==2)~tcell+platelet,data=dd)
cbind(cox1$coef,scox1$coef)
cbind(cox2$coef,scox2$coef)
par(mfrow=c(1,2))
plot(cox1); plot(sc ox1,add=TRUE);
plot(cox2); plot(sc ox2,add=TRUE);

cox1 <- phreg(Surv(time,cause==1)~strata(tcell)+platelet,data=bmt)
cox2 <- phreg(Surv(time,cause==2)~strata(tcell)+platelet,data=bmt)
coxs <- list(cox1,cox2)
dd <- sim.cause.cox(coxs,nsim,data=bmt)
scox1 <- phreg(Surv(time,status==1)~strata(tcell)+platelet,data=dd)
scox2 <- phreg(Surv(time,status==2)~strata(tcell)+platelet,data=dd)
cbind(cox1$coef,scox1$coef)
cbind(cox2$coef,scox2$coef)
par(mfrow=c(1,2))
plot(cox1); plot(sc ox1,add=TRUE);
plot(cox2); plot(sc ox2,add=TRUE);

```

sim.cif*Simulation of output from Cumulative incidence regression model***Description**

Simulates data that looks like fit from fitted cumulative incidence model

Usage

```
sim.cif(cif,n,data=NULL,Z=NULL,drawZ=TRUE,cens=NULL,rrc=NULL,cumstart=c(0,0),...)
```

Arguments

cif	output form prop.odds.subdist or ccr (cmprsk), can also call invsubdist with with cumulative and linear predictor
n	number of simulations.
data	to extract covariates for simulations (draws from observed covariates).
Z	to use these covariates for simulation rather than drawing new ones.
drawZ	to random sample from Z or not

cens	specifies censoring model, if "is.matrix" then uses cumulative hazard given, if "is.scalar" then uses rate for exponential, and if not given then takes average rate of in simulated data from cox model.
rrc	possible vector of relative risk for cox-type censoring.
cumstart	to start cumulatives at time 0 in 0.
...	arguments for invsubdist

Author(s)

Thomas Scheike

Examples

```
data(bmt)

scif <- cifreg(Event(time,cause)~tcell+platelet+age,data=bmt,cause=1,prop=NULL)
summary(scif)
plot(scif)
#####
# simulating several causes with specific cumulatives
#####

cif1 <- cifreg(Event(time,cause)~tcell+age,data=bmt,cause=1,prop=NULL)
cif2 <- cifreg(Event(time,cause)~tcell+age,data=bmt,cause=2,prop=NULL)
# dd <- sim.cifsRestrict(list(cif1,cif2),200,data=bmt)
dd <- sim.cifs(list(cif1,cif2),200,data=bmt)
scif1 <- cifreg(Event(time,cause)~tcell+age,data=dd,cause=1)
scif2 <- cifreg(Event(time,cause)~tcell+age,data=dd,cause=2)

par(mfrow=c(1,2))
plot(cif1); plot(scif1,add=TRUE,col=2)
plot(cif2); plot(scif2,add=TRUE,col=2)
```

sim.cox

Simulation of output from Cox model.

Description

Simulates data that looks like fit from Cox model. Censor data automatically for highest value of the event times by using cumulative hazard.

Usage

```
sim.cox(cox,n,data=NULL,cens=NULL,rrc=NULL,entry=NULL,...)
```

Arguments

<code>cox</code>	output form coxph or cox.aalen model fitting cox model.
<code>n</code>	number of simulations.
<code>data</code>	to extract covariates for simulations (draws from observed covariates).
<code>cens</code>	specifies censoring model, if "is.matrix" then uses cumulative hazard given, if "is.scalar" then uses rate for exponential, and if not given then takes average rate of in simulated data from cox model.
<code>rrc</code>	possible vector of relative risk for cox-type censoring.
<code>entry</code>	delayed entry variable for simulation.
<code>...</code>	arguments for rchaz, for example entry-time

Author(s)

Thomas Scheike

Examples

```

data(sTRACE)
cox <- coxph(Surv(time,status==9)~vf+chf+wmi,data=sTRACE)
sim1 <- sim.cox(cox,1000,data=sTRACE)
cc <- coxph(Surv(time,status)~vf+chf+wmi,data=sim1)
cbind(cox$coef,cc$coef)

cor(sim1[,c("vf","chf","wmi")])
cor(sTRACE[,c("vf","chf","wmi")])

cox <- phreg(Surv(time, status==9)~vf+chf+wmi,data=sTRACE)
sim3 <- sim.cox(cox,1000,data=sTRACE)
cc <- phreg(Surv(time, status)~vf+chf+wmi,data=sim3)
cbind(cox$coef,cc$coef)
plot(cox,se=TRUE)
plot(cc,add=TRUE,col=2)

cox <- phreg(Surv(time,status==9)~strata(chf)+vf+wmi,data=sTRACE)
sim3 <- sim.cox(cox,100,data=sTRACE)
cc <- phreg(Surv(time, status)~strata(chf)+vf+wmi,data=sim3)
cbind(cox$coef,cc$coef)
plot(cox)
plot(cc,add=TRUE,col=2)

```

simAalenFrailty *Simulate from the Aalen Frailty model*

Description

Simulate observations from Aalen Frailty model with Gamma distributed frailty and constant intensity.

Usage

```
simAalenFrailty(  
  n = 5000,  
  theta = 0.3,  
  K = 2,  
  beta0 = 1.5,  
  beta = 1,  
  cens = 1.5,  
  cuts = 0,  
  ...  
)
```

Arguments

n	Number of observations in each cluster
theta	Dependence parameter (variance of frailty)
K	Number of clusters
beta0	Baseline (intercept)
beta	Effect (log hazard ratio) of covariate
cens	Censoring rate
cuts	time cuts
...	Additional arguments

Author(s)

Klaus K. Holst

<code>simClaytonOakes</code>	<i>Simulate from the Clayton-Oakes frailty model</i>
------------------------------	------------------------------------------------------

Description

Simulate observations from the Clayton-Oakes copula model with piecewise constant marginals.

Usage

```
simClaytonOakes(
  K,
  n,
  eta,
  beta,
  stoptime,
  lam = 1,
  left = 0,
  pairleft = 0,
  trunc.prob = 0.5,
  same = 0
)
```

Arguments

<code>K</code>	Number of clusters
<code>n</code>	Number of observations in each cluster
<code>eta</code>	variance
<code>beta</code>	Effect (log hazard ratio) of covariate
<code>stoptime</code>	Stopping time
<code>lam</code>	constant hazard
<code>left</code>	Left truncation
<code>pairleft</code>	pairwise (1) left truncation or individual (0)
<code>trunc.prob</code>	Truncation probability
<code>same</code>	if 1 then left-truncation is same also for univariate truncation

Author(s)

Thomas Scheike and Klaus K. Holst

simClaytonOakesWei *Simulate from the Clayton-Oakes frailty model*

Description

Simulate observations from the Clayton-Oakes copula model with Weibull type baseline and Cox marginals.

Usage

```
simClaytonOakesWei(  
  K,  
  n,  
  eta,  
  beta,  
  stoptime,  
  weiscale = 1,  
  weishape = 2,  
  left = 0,  
  pairleft = 0  
)
```

Arguments

K	Number of clusters
n	Number of observations in each cluster
eta	1/variance
beta	Effect (log hazard ratio) of covariate
stoptime	Stopping time
weiscale	weibull scale parameter
weishape	weibull shape parameter
left	Left truncation
pairleft	pairwise (1) left truncation or individual (0)

Author(s)

Klaus K. Holst

simMultistate	<i>Simulation of illness-death model</i>
---------------	------------------------------------------

Description

Simulation of illness-death model

Usage

```
simMultistate(
  n,
  cumhaz,
  cumhaz2,
  death.cumhaz,
  death.cumhaz2,
  rr = NULL,
  rr2 = NULL,
  rd = NULL,
  rd2 = NULL,
  gap.time = FALSE,
  max.recurrent = 100,
  dependence = 0,
  var.z = 0.22,
  cor.mat = NULL,
  cens = NULL,
  ...
)
```

Arguments

<code>n</code>	number of id's
<code>cumhaz</code>	cumulative hazard of going from state 1 to 2.
<code>cumhaz2</code>	cumulative hazard of going from state 2 to 1.
<code>death.cumhaz</code>	cumulative hazard of death from state 1.
<code>death.cumhaz2</code>	cumulative hazard of death from state 2.
<code>rr</code>	relative risk adjustment for cumhaz
<code>rr2</code>	relative risk adjustment for cumhaz2
<code>rd</code>	relative risk adjustment for death.cumhaz
<code>rd2</code>	relative risk adjustment for death.cumhaz2
<code>gap.time</code>	if true simulates gap-times with specified cumulative hazard
<code>max.recurrent</code>	limits number recurrent events to 100

dependence	0:independence; 1:all share same random effect with variance var.z; 2:random effect exp(normal) with correlation structure from cor.mat; 3:additive gamma distributed random effects, z1=(z11+z12)/2 such that mean is 1 , z2=(z11^cor.mat(1,2)+z13)/2, z3=(z12^cor.mat(2,3)+z13^cor.mat(1,3))/2, with z11 z12 z13 are gamma with mean and variance 1 , first random effect is z1 and for N1 second random effect is z2 and for N2 third random effect is for death
var.z	variance of random effects
cor.mat	correlation matrix for var.z variance of random effects
cens	rate of censoring exponential distribution
...	Additional arguments to lower level funtions

Details

simMultistate with different death intensities from states 1 and 2

Must give cumulative hazards on some time-range

Author(s)

Thomas Scheike

Examples

```
#####
## getting some rates to mimick
#####
data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
dr <- drcumhaz
dr2 <- drcumhaz
dr2[,2] <- 1.5*drcumhaz[,2]
base1 <- base1cumhaz
base4 <- base4cumhaz
cens <- rbind(c(0,0),c(2000,0.5),c(5110,3))

iddata <- simMultistate(100,base1,base1,dr,dr2,cens=cens)
dlist(iddata,.~id|id<3,n=0)

### estimating rates from simulated data
c0 <- phreg(Surv(start,stop,status==0)~+1,iddata)
c3 <- phreg(Surv(start,stop,status==3)~+strata(from),iddata)
c1 <- phreg(Surv(start,stop,status==1)~+1,subset(iddata,from==2))
c2 <- phreg(Surv(start,stop,status==2)~+1,subset(iddata,from==1))
###
par(mfrow=c(2,3))
bplot(c0)
lines(cens,col=2)
bplot(c3,main="rates 1-> 3 , 2->3")
lines(dr,col=1,lwd=2)
lines(dr2,col=2,lwd=2)
```

```
###  
bplot(c1,main="rate 1->2")  
lines(base1,lwd=2)  
###  
bplot(c2,main="rate 2->1")  
lines(base1,lwd=2)
```

simRecurrent*Simulation of recurrent events data based on cumulative hazards***Description**

Simulation of recurrent events data based on cumulative hazards

Usage

```
simRecurrent(  
  n,  
  cumhaz,  
  death.cumhaz = NULL,  
  gap.time = FALSE,  
  cens = NULL,  
  max.recurrent = 100,  
  dhaz = NULL,  
  dependence = 0,  
  var.z = 2,  
  cor.mat = NULL,  
  ...  
)
```

Arguments

n	number of id's
cumhaz	cumulative hazard of recurrent events
death.cumhaz	cumulative hazard of death
gap.time	if true simulates gap-times with specified cumulative hazard
cens	rate of exponential on total time i.e. on death time-scale
max.recurrent	limits number recurrent events to 100
dhaz	rate for death hazard if it is extended to time-range of first event
dependence	=0 independence, =1 all share same random effect with variance var.z =2 random effect exp(normal) with correlation structure from cor.mat, first random effect is z1 and shared for a possible second cause, second random effect is for death
var.z	variance of random effects
cor.mat	correlation matrix for var.z variance of random effects
...	Additional arguments to lower level funtions

Details

Must give hazard of death and recurrent events. Possible with two event types and their dependence can be specified but the two recurrent events need to have the same random effect, simRecurrentII more flexible !

Author(s)

Thomas Scheike

Examples

```
#####
## getting some rates to mimick
#####

data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
dr <- drcumhaz
base1 <- base1cumhaz
base4 <- base4cumhaz

#####
### simulating simple model that mimicks data
#####
rr <- simRecurrent(5,base1,death.cumhaz=dr)
dlist(rr,.~id,n=0)

rr <- simRecurrent(1000,base1,death.cumhaz=dr)
par(mfrow=c(1,3))
showfitsim(causes=1,rr,dr,base1,base1)

#####
### simulating simple model
### random effect for all causes (Z shared for death and recurrent)
#####

rr <- simRecurrent(1000,base1,death.cumhaz=dr,dependence=1,var.gamma=0.4)
### marginals do fit after input after integrating out
par(mfrow=c(2,2))
showfitsim(causes=1,rr,dr,base1,base1)
```

Description

Simulation of recurrent events data based on cumulative hazards

Usage

```
simRecurrentII(
  n,
  cumhaz,
  cumhaz2,
  death.cumhaz = NULL,
  r1 = NULL,
  r2 = NULL,
  rd = NULL,
  rc = NULL,
  gap.time = FALSE,
  max.recurrent = 100,
  dhaz = NULL,
  haz2 = NULL,
  dependence = 0,
  var.z = 0.22,
  cor.mat = NULL,
  cens = NULL,
  ...
)
```

Arguments

n	number of id's
cumhaz	cumulative hazard of recurrent events
cumhaz2	cumulative hazard of recurrent events of type 2
death.cumhaz	cumulative hazard of death
r1	potential relative risk adjustment of rate
r2	potential relative risk adjustment of rate
rd	potential relative risk adjustment of rate
rc	potential relative risk adjustment of rate
gap.time	if true simulates gap-times with specified cumulative hazard
max.recurrent	limits number recurrent events to 100
dhaz	rate for death hazard if it is extended to time-range of first event
haz2	rate of second cause if it is extended to time-range of first event
dependence	0:independence; 1:all share same random effect with variance var.z; 2:random effect exp(normal) with correlation structure from cor.mat; 3:additive gamma distributed random effects, z1=(z11+z12)/2 such that mean is 1 , z2=(z11^cor.mat(1,2)+z13)/2, z3=(z12^cor.mat(2,3)+z13^cor.mat(1,3))/2, with z11 z12 z13 are gamma with mean and variance 1 , first random effect is z1 and for N1 second random effect is z2 and for N2 third random effect is for death
var.z	variance of random effects
cor.mat	correlation matrix for var.z variance of random effects
cens	rate of censoring exponential distribution
...	Additional arguments to lower level funtions

Details

Must give hazard of death and two recurrent events. Possible with two event types and their dependence can be specified but the two recurrent events need to share random effect. Based on drawing the from cumhaz and cumhaz2 and taking the first event rather the cumulative and then distributing it out. Key advantage of this is that there is more flexibility wrt random effects

Author(s)

Thomas Scheike

Examples

```
#####
## getting some rates to mimick
#####

data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
dr <- drcumhaz
base1 <- base1cumhaz
base4 <- base4cumhaz

cor.mat <- corM <- rbind(c(1.0, 0.6, 0.9), c(0.6, 1.0, 0.5), c(0.9, 0.5, 1.0))

#####
### simulating simple model that mimicks data
### now with two event types and second type has same rate as death rate
#####
set.seed(100)
rr <- simRecurrentII(1000,base1,base4,death.cumhaz=dr)
dtbl(rr,~death+status)
par(mfrow=c(2,2))
showfitsim(causes=2,rr,dr,base1,base4)
```

simRecurrentTS

*Simulation of recurrent events data based on cumulative hazards:
Two-stage model*

Description

Simulation of recurrent events data based on cumulative hazards

Usage

```
simRecurrentTS(
  n,
  cumhaz,
```

```

cumhaz2,
death.cumhaz = NULL,
nu = rep(1, 3),
share1 = 0.3,
vargamD = 2,
vargam12 = 0.5,
gap.time = FALSE,
max.recurrent = 100,
cens = NULL,
...
)

```

Arguments

n	number of id's
cumhaz	cumulative hazard of recurrent events
cumhaz2	cumulative hazard of recurrent events of type 2
death.cumhaz	cumulative hazard of death
nu	powers of random effects where nu > -1/shape
share1	how random effect for death splits into two parts
vargamD	variance of random effect for death
vargam12	shared random effect for N1 and N2
gap.time	if true simulates gap-times with specified cumulative hazard
max.recurrent	limits number recurrent events to 100
cens	rate of censoring exponential distribution
...	Additional arguments to lower level funtions

Details

Model is constructed such that marginals are on specified form by linear approximations of cumulative hazards that are on a specific form to make them equivalent to marginals after integrating out over survivors. Therefore $E(dN_1 | D>t) = \text{cumhaz}$, $E(dN_2 | D>t) = \text{cumhaz2}$, and hazard of death is death.cumhazard

Must give hazard of death and two recurrent events. Hazard of death is death.cumhazard two event types and their dependence can be specified but the two recurrent events need to share random effect.

Random effect for death $Z.death = (Zd1 + Zd2)$, $Z1 = (Zd1^{\text{nu1}}) Z12$, $Z2 = (Zd2^{\text{nu2}}) Z12^{\text{nu3}}$

$$Z.death = Zd1 + Zd2$$

gamma distributions

$$Zdj$$

gamma distribution with mean parameters (sharej), vargamD , $\text{share2} = 1 - \text{share1}$

$$Z12$$

gamma distribution with mean 1 and variance vargam12

Author(s)

Thomas Scheike

Examples

```
#####
## getting some rates to mimick
#####

data(base1cumhaz)
data(base4cumhaz)
data(drcumhaz)
dr <- drcumhaz
base1 <- base1cumhaz
base4 <- base4cumhaz

rr <- simRecurrentTS(1000,base1,base4,death.cumhaz=dr)
dttable(rr,~death+status)
showfitsim(causes=2,rr,dr,base1,base4)
```

`summary.cor`

Summary for dependence models for competing risks

Description

Computes concordance and casewise concordance for dependence models for competing risks models of the type cor.cif, rr.cif or or.cif for the given cumulative incidences and the different dependence measures in the object.

Usage

```
## S3 method for class 'cor'
summary(object, marg.cif = NULL, marg.cif2 = NULL, digits = 3, ...)
```

Arguments

- | | |
|------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|
| <code>object</code> | object from cor.cif rr.cif or or.cif for dependence between competing risks data for two causes. |
| <code>marg.cif</code> | a number that gives the cumulative incidence in one time point for which concordance and casewise concordance are computed. |
| <code>marg.cif2</code> | the cumulative incidence for cause 2 for concordance and casewise concordance are computed. Default is that it is the same as <code>marg.cif</code> . |
| <code>digits</code> | digits in output. |
| ... | Additional arguments. |

Value

prints summary for dependence model.

<code>casewise</code>	gives casewise concordance that is, probability of cause 2 (related to cif2) given that cause 1 (related to cif1) has occurred.
<code>concordance</code>	gives concordance that is, probability of cause 2 (related to cif2) and cause 1 (related to cif1).
<code>cif1</code>	cumulative incidence for cause1.
<code>cif2</code>	cumulative incidence for cause1.

Author(s)

Thomas Scheike

References

Cross odds ratio Modelling of dependence for Multivariate Competing Risks Data, Scheike and Sun (2012), Biostatistics.

A Semiparametric Random Effects Model for Multivariate Competing Risks Data, Scheike, Zhang, Sun, Jensen (2010), Biometrika.

Examples

```
## library("timereg")
## data("multcif", package="mets") # simulated data
## multcif$cause[multcif$cause==0] <- 2
##
## times=seq(0.1,3,by=0.1) # to speed up computations use only these time-points
## add <- timereg::comp.risk(Event(time,cause)~+1+cluster(id),
##                               data=multcif, n.sim=0, times=times, cause=1)
## #
## out1<-cor.cif(add, data=multcif, cause1=1, cause2=1, theta=log(2+1))
## summary(out1)
## 
## pad <- predict(add, X=1, se=0, uniform=0)
## summary(out1, marg.cif=pad)
```

Description

Fits additive gamma frailty model with additive hazard conditional on the random effects

$$\lambda_{ij} = (V_{ij}^T Z)(X_{ij}^T \alpha(t))$$

The baseline $\alpha(t)$ is profiled out using marginal modelling adjusted for the random effects structure as in Eriksson and Scheike (2015). One advantage of the standard frailty model is that one can deal with competing risks for this model.

For all models the standard errors do not reflect this uncertainty of the baseline estimates, and might therefore be a bit too small. To remedy this one can do bootstrapping.

If clusters contain more than two times, we use a composite likelihood based on the pairwise bivariate models. Can also fit a additive gamma random effects model described in detail below.

We allow a regression structure for the independent gamma distributed random effects and their variances that may depend on cluster covariates. So

$$\theta = z_j^T \alpha$$

where z is specified by theta.des. The reported standard errors are based on the estimated information from the likelihood assuming that the marginals are known.

Can also fit a structured additive gamma random effects model, such as the ACE, ADE model for survival data.

Now random.design specifies the random effects for each subject within a cluster. This is a matrix of 1's and 0's with dimension n x d. With d random effects. For a cluster with two subjects, we let the random.design rows be v_1 and v_2 . Such that the random effects for subject 1 is

$$v_1^T(Z_1, \dots, Z_d)$$

, for d random effects. Each random effect has an associated parameter $(\lambda_1, \dots, \lambda_d)$. By construction subjects 1's random effect are Gamma distributed with mean $\lambda_j/v_1^T \lambda$ and variance $\lambda_j/(v_1^T \lambda)^2$. Note that the random effect $v_1^T(Z_1, \dots, Z_d)$ has mean 1 and variance $1/(v_1^T \lambda)$. It is here assumed that lamtot = $v_1^T \lambda$ is fixed over all clusters as it would be for the ACE model below. The lamtot parameter may be specified separately for some sets of the parameters in the additive.gamma.sum (ags) matrix is specified and then lamtot for the j'th random effect is $ags_j^T \lambda$.

Based on these parameters the relative contribution (the heritability, h) is equivalent to the expected values of the random effects $\lambda_j/v_1^T \lambda$

The DEFAULT parametrization uses the variances of the random effects

$$\theta_j = \lambda_j/(v_1^T \lambda)^2$$

For alternative parametrizations one can specify how the parameters relate to λ_j with the function Given the random effects the survival distributions within a cluster are independent and on the form

$$P(T > t|x, z) = \exp(-ZA(t) \exp(Z^t \beta))$$

The parameters $(\lambda_1, \dots, \lambda_d)$ are related to the parameters of the model by a regression construction pard (d x k), that links the d λ parameters with the (k) underlying θ parameters

$$\lambda = \text{theta.des} \theta$$

here using theta.des to specify these low-dimension association. Default is a diagonal matrix.

The case.control option that can be used with the pair specification of the pairwise parts of the estimating equations. Here it is assumed that the second subject of each pair is the proband.

Usage

```
survival.iterative(
  margsurv,
  data = parent.frame(),
  method = "nr",
  Nit = 60,
  detail = 0,
  clusters = NULL,
  silent = 1,
  weights = NULL,
  control = list(),
  theta = NULL,
  theta.des = NULL,
  var.link = 1,
  iid = 1,
  step = 0.5,
  model = "clayton.oakes",
  marginal.trunc = NULL,
  marginal.survival = NULL,
  marginal.status = NULL,
  strata = NULL,
  se.clusters = NULL,
  max.clust = NULL,
  numDeriv = 0,
  random.design = NULL,
  pairs = NULL,
  pairs.rvs = NULL,
  numDeriv.method = "simple",
  additive.gamma.sum = NULL,
  var.par = 1,
  cr.models = NULL,
  case.control = 0,
  ascertained = 0,
  shut.up = 0
)
```

Arguments

<code>margsurv</code>	Marginal model
<code>data</code>	data frame
<code>method</code>	Scoring method "nr", "nlminb", "optimize", "nlm"
<code>Nit</code>	Number of iterations
<code>detail</code>	Detail
<code>clusters</code>	Cluster variable
<code>silent</code>	Debug information
<code>weights</code>	Weights

control	Optimization arguments
theta	Starting values for variance components
theta.des	design for dependence parameters, when pairs are given this is could be a (pairs) x (numer of parameters) x (max number random effects) matrix
var.link	Link function for variance
iid	Calculate i.i.d. decomposition
step	Step size
model	model
marginal.trunc	marginal left truncation probabilities
marginal.survival	optional vector of marginal survival probabilities
marginal.status	related to marginal survival probabilities
strata	strata for fitting, see example
se.clusters	for clusters for se calculation with iid
max.clust	max se.clusters for se calculation with iid
numDeriv	to get numDeriv version of second derivative, otherwise uses sum of squared score
random.design	random effect design for additive gamma model, when pairs are given this is a (pairs) x (2) x (max number random effects) matrix, see pairs.rvs below
pairs	matrix with rows of indeces (two-columns) for the pairs considered in the pairwise composite score, useful for case-control sampling when marginal is known.
pairs.rvs	for additive gamma model and random.design and theta.des are given as arrays, this specifice number of random effects for each pair.
numDeriv.method	uses simple to speed up things and second derivative not so important.
additive.gamma.sum	for two.stage=0, this is specification of the lamtot in the models via a matrix that is multiplied onto the parameters theta (dimensions=(number random effects x number of theta parameters), when null then sums all parameters.
var.par	is 1 for the default parametrization with the variances of the random effects, var.par=0 specifies that the λ_j 's are used as parameters.
cr.models	competing risks models for two.stage=0, should be given as a list with models for each cause
case.control	assumes case control structure for "pairs" with second column being the probands, when this options is used the twostage model is profiled out via the paired estimating equations for the survival model.
ascertained	if the pair are sampled only when there is an event. This is in contrast to case.control sampling where a proband is given. This can be combined with control probands. Pair-call of twostage is needed and second column of pairs are the first jump time with an event for ascertained pairs, or time of control proband.
shut.up	to make the program more silent in the context of iterative procedures for case-control and ascertained sampling

Author(s)

Thomas Scheike

`survival.twostage`

Two stage survival model for multivariate survival data

Description

Fits Clayton-Oakes or bivariate Plackett models for bivariate survival data using marginals that are on Cox form. The dependence can be modelled via

1. Regression design on dependence parameter.
2. Random effects, additive gamma model.

If clusters contain more than two subjects, we use a composite likelihood based on the pairwise bivariate models, for full MLE see `twostageMLE`.

The two-stage model is constructed such that given the gamma distributed random effects it is assumed that the survival functions are independent, and that the marginal survival functions are on Cox form (or additive form)

$$P(T > t|x) = S(t|x) = \exp(-\exp(x^T \beta) A_0(t))$$

One possibility is to model the variance within clusters via a regression design, and then one can specify a regression structure for the independent gamma distributed random effect for each cluster, such that the variance is given by

$$\theta = h(z_j^T \alpha)$$

where z is specified by `theta.des`, and a possible link function `var.link=1` will use the exponential link $h(x) = \exp(x)$, and `var.link=0` the identity link $h(x) = x$. The reported standard errors are based on the estimated information from the likelihood assuming that the marginals are known (unlike the `twostageMLE` and for the additive gamma model below).

Can also fit a structured additive gamma random effects model, such as the ACE, ADE model for survival data. In this case the `random.design` specifies the random effects for each subject within a cluster. This is a matrix of 1's and 0's with dimension $n \times d$. With d random effects. For a cluster with two subjects, we let the `random.design` rows be v_1 and v_2 . Such that the random effects for subject 1 is

$$v_1^T (Z_1, \dots, Z_d)$$

, for d random effects. Each random effect has an associated parameter $(\lambda_1, \dots, \lambda_d)$. By construction subjects 1's random effect are Gamma distributed with mean $\lambda_j/v_1^T \lambda$ and variance $\lambda_j/(v_1^T \lambda)^2$. Note that the random effect $v_1^T (Z_1, \dots, Z_d)$ has mean 1 and variance $1/(v_1^T \lambda)$. It is here assumed that $lamtot = v_1^T \lambda$ is fixed within clusters as it would be for the ACE model below.

Based on these parameters the relative contribution (the heritability, h) is equivalent to the expected values of the random effects: $\lambda_j/v_1^T \lambda$

The DEFAULT parametrization (`var.par=1`) uses the variances of the random effects

$$\theta_j = \lambda_j/(v_1^T \lambda)^2$$

For alternative parametrizations one can specify how the parameters relate to λ_j with the argument var.par=0.

For both types of models the basic model assumptions are that given the random effects of the clusters the survival distributions within a cluster are independent and 'on the form

$$P(T > t|x, z) = \exp(-Z \cdot \text{Laplace}^{-1}(\text{lamtot}, \text{lamtot}, S(t|x)))$$

with the inverse laplace of the gamma distribution with mean 1 and variance 1/lamtot.

The parameters $(\lambda_1, \dots, \lambda_d)$ are related to the parameters of the model by a regression construction pard (d x k), that links the $d \lambda$ parameters with the (k) underlying θ parameters

$$\lambda = \text{theta.des}\theta$$

here using theta.des to specify these low-dimension association. Default is a diagonal matrix. This can be used to make structural assumptions about the variances of the random-effects as is needed for the ACE model for example.

The case.control option that can be used with the pair specification of the pairwise parts of the estimating equations. Here it is assumed that the second subject of each pair is the proband.

Usage

```
survival.twostage(
  margsurv,
  data = parent.frame(),
  method = "nr",
  detail = 0,
  clusters = NULL,
  silent = 1,
  weights = NULL,
  theta = NULL,
  theta.des = NULL,
  var.link = 1,
  baseline.iid = 1,
  model = "clayton.oakes",
  marginal.trunc = NULL,
  marginal.survival = NULL,
  strata = NULL,
  se.clusters = NULL,
  numDeriv = 1,
  random.design = NULL,
  pairs = NULL,
  dim.theta = NULL,
  numDeriv.method = "simple",
  additive.gamma.sum = NULL,
  var.par = 1,
  no.opt = FALSE,
  ...
)
```

Arguments

<code>margsurv</code>	Marginal model
<code>data</code>	data frame
<code>method</code>	Scoring method "nr", for lava NR optimizer
<code>detail</code>	Detail
<code>clusters</code>	Cluster variable
<code>silent</code>	Debug information
<code>weights</code>	Weights
<code>theta</code>	Starting values for variance components
<code>theta.des</code>	design for dependence parameters, when pairs are given the indeces of the theta-design for this pair, is given in pairs as column 5
<code>var.link</code>	Link function for variance: exp-link.
<code>baseline.iid</code>	to adjust for baseline estimation, using phreg function on same data.
<code>model</code>	model
<code>marginal.trunc</code>	marginal left truncation probabilities
<code>marginal.survival</code>	optional vector of marginal survival probabilities
<code>strata</code>	strata for fitting, see example
<code>se.clusters</code>	for clusters for se calculation with iid
<code>numDeriv</code>	to get numDeriv version of second derivative, otherwise uses sum of squared scores for each pair
<code>random.design</code>	random effect design for additive gamma model, when pairs are given the indeces of the pairs random.design rows are given as columns 3:4
<code>pairs</code>	matrix with rows of indeces (two-columns) for the pairs considered in the pairwise composite score, useful for case-control sampling when marginal is known.
<code>dim.theta</code>	dimension of the theta parameter for pairs situation.
<code>numDeriv.method</code>	uses simple to speed up things and second derivative not so important.
<code>additive.gamma.sum</code>	for two.stage=0, this is specification of the lamtot in the models via a matrix that is multiplied onto the parameters theta (dimensions=(number random effects x number of theta parameters), when null then sums all parameters.
<code>var.par</code>	is 1 for the default parametrization with the variances of the random effects, var.par=0 specifies that the λ_j 's are used as parameters.
<code>no.opt</code>	for not optimizng
<code>...</code>	Additional arguments to maximizer NR of lava. and ascertained sampling

Author(s)

Thomas Scheike

References

- Twostage estimation of additive gamma frailty models for survival data. Scheike (2019), work in progress
- Shih and Louis (1995) Inference on the association parameter in copula models for bivariate survival data, *Biometrics*, (1995).
- Glidden (2000), A Two-Stage estimator of the dependence parameter for the Clayton Oakes model, LIDA, (2000).
- Measuring early or late dependence for bivariate twin data Scheike, Holst, Hjelmborg (2015), LIDA
- Estimating heritability for cause specific mortality based on twins studies Scheike, Holst, Hjelmborg (2014), LIDA
- Additive Gamma frailty models for competing risks data, *Biometrics* (2015) Eriksson and Scheike (2015),

Examples

```

data(diabetes)

# Marginal Cox model with treat as covariate
margph <- phreg(Surv(time,status)~treat+cluster(id),data=diabetes)
### Clayton-Oakes, MLE
fitco1<-twostageMLE(margph,data=diabetes,theta=1.0)
summary(fitco1)

### Plackett model
mph <- phreg(Surv(time,status)~treat+cluster(id),data=diabetes)
fitp <- survival.twostage(mph,data=diabetes,theta=3.0,Nit=40,
                           clusters=diabetes$id,var.link=1,model="plackett")
summary(fitp)

### Clayton-Oakes
fitco2 <- survival.twostage(mph,data=diabetes,theta=0.0,detail=0,
                            clusters=diabetes$id,var.link=1,model="clayton.oakes")
summary(fitco2)
fitco3 <- survival.twostage(margph,data=diabetes,theta=1.0,detail=0,
                            clusters=diabetes$id,var.link=0,model="clayton.oakes")
summary(fitco3)

### without covariates but with stratified
marg <- phreg(Surv(time,status)~+strata(treat)+cluster(id),data=diabetes)
fitpa <- survival.twostage(marg,data=diabetes,theta=1.0,
                           clusters=diabetes$id,model="clayton.oakes")
summary(fitpa)

fitcoa <- survival.twostage(marg,data=diabetes,theta=1.0,clusters=diabetes$id,
                           model="clayton.oakes")
summary(fitcoa)

### Piecewise constant cross hazards ratio modelling
#####

```

```

d <- subset(simClaytonOakes(2000,2,0.5,0,stoptime=2,left=0),!truncated)
udp <- piecewise.twostage(c(0,0.5,2),data=d,method="optimize",
                           id="cluster",timevar="time",
                           status="status",model="clayton.oakes",silent=0)
summary(udp)

## Reduce Ex.Timings
### Same model using the strata option, a bit slower
#####
## makes the survival pieces for different areas in the plane
##ud1=surv.boxarea(c(0,0),c(0.5,0.5),data=d,id="cluster",timevar="time",status="status")
##ud2=surv.boxarea(c(0,0.5),c(0.5,2),data=d,id="cluster",timevar="time",status="status")
##ud3=surv.boxarea(c(0.5,0),c(2,0.5),data=d,id="cluster",timevar="time",status="status")
##ud4=surv.boxarea(c(0.5,0.5),c(2,2),data=d,id="cluster",timevar="time",status="status")

## everything done in one call
ud <- piecewise.data(c(0,0.5,2),data=d,timevar="time",status="status",id="cluster")
ud$strata <- factor(ud$strata);
ud$intstrata <- factor(ud$intstrata)

## makes strata specific id variable to identify pairs within strata
## se's computed based on the id variable across strata "cluster"
ud$idstrata <- ud$id+(as.numeric(ud$strata)-1)*2000

marg2 <- timereg::alen(Surv(boxtime,status)~-1+factor(num):factor(intstrata),
                        data=ud,n.sim=0,robust=0)
tdes <- model.matrix(~-1+factor(strata),data=ud)
fitp2 <- survival.twostage(marg2,data=ud,se.clusters=ud$cluster,clusters=ud$idstrata,
                           model="clayton.oakes",theta.des=tdes,step=0.5)
summary(fitp2)

### now fitting the model with symmetry, i.e. strata 2 and 3 same effect
ud$stratas <- ud$strata;
ud$stratas[ud$strata=="0.5-2,0-0.5"] <- "0-0.5,0.5-2"
tdes2 <- model.matrix(~-1+factor(stratas),data=ud)
fitp3 <- survival.twostage(marg2,data=ud,clusters=ud$idstrata,se.cluster=ud$cluster,
                           model="clayton.oakes",theta.des=tdes2,step=0.5)
summary(fitp3)

### same model using strata option, a bit slower
fitp4 <- survival.twostage(marg2,data=ud,clusters=ud$cluster,se.cluster=ud$cluster,
                           model="clayton.oakes",theta.des=tdes2,step=0.5,strata=ud$strata)
summary(fitp4)

## Reduce Ex.Timings
### structured random effects model additive gamma ACE
### simulate structured two-stage additive gamma ACE model
data <- simClaytonOakes.twin.ace(4000,2,1,0,3)
out <- twin.polygen.design(data,id="cluster")
pardes <- out$pardes
pardes

```

```

des.rv <- out$des.rv
head(des.rv)
aa <- phreg(Surv(time,status)~xx+cluster(cluster),data=data,robust=0)
ts <- survival.twostage(aa,data=data,clusters=data$cluster,detail=0,
    theta=c(2,1),var.link=0,step=0.5,
    random.design=des.rv,theta.des=pardes)
summary(ts)

```

`survival.twostageCC` *Twostage survival model for multivariate survival data*

Description

older extended version of `survival.twostage` with more options and different maximizer.

Usage

```

survival.twostageCC(
  margsurv,
  data = parent.frame(),
  method = "nr",
  Nit = 60,
  detail = 0,
  clusters = NULL,
  silent = 1,
  weights = NULL,
  control = list(),
  theta = NULL,
  theta.des = NULL,
  var.link = 1,
  baseline.iid = 1,
  step = 0.5,
  model = "clayton.oakes",
  marginal.trunc = NULL,
  marginal.survival = NULL,
  marginal.status = NULL,
  strata = NULL,
  se.clusters = NULL,
  numDeriv = 0,
  random.design = NULL,
  pairs = NULL,
  dim.theta = NULL,
  numDeriv.method = "simple",
  additive.gamma.sum = NULL,
  var.par = 1,
  cr.models = NULL,

```

```

    case.control = 0,
    ascertained = 0,
    shut.up = 0
)

```

Arguments

margsurv	Marginal model
data	data frame
method	Scoring method "nr", "nlminb", "optimize", "nlm"
Nit	Number of iterations
detail	Detail
clusters	Cluster variable
silent	Debug information
weights	Weights
control	Optimization arguments
theta	Starting values for variance components
theta.des	design for dependence parameters, when pairs are given the indeces of the theta-design for this pair, is given in pairs as column 5
var.link	Link function for variance: exp-link.
baseline.iid	to adjust for baseline estimation, using phreg function on same data.
step	Step size
model	model
marginal.trunc	marginal left truncation probabilities
marginal.survival	optional vector of marginal survival probabilities
marginal.status	related to marginal survival probabilities
strata	strata for fitting, see example
se.clusters	for clusters for se calculation with iid
numDeriv	to get numDeriv version of second derivative, otherwise uses sum of squared score
random.design	random effect design for additive gamma model, when pairs are given the indeces of the pairs random.design rows are given as columns 3:4
pairs	matrix with rows of indeces (two-columns) for the pairs considered in the pairwise composite score, useful for case-control sampling when marginal is known.
dim.theta	dimension of the theta parameter for pairs situation.
numDeriv.method	uses simple to speed up things and second derivative not so important.
additive.gamma.sum	for two.stage=0, this is specification of the lamtot in the models via a matrix that is multiplied onto the parameters theta (dimensions=(number random effects x number of theta parameters), when null then sums all parameters.

<code>var.par</code>	is 1 for the default parametrization with the variances of the random effects, <code>var.par=0</code> specifies that the λ_j 's are used as parameters.
<code>cr.models</code>	competing risks models for two.stage=0, should be given as a list with models for each cause
<code>case.control</code>	assumes case control structure for "pairs" with second column being the probands, when this options is used the twostage model is profiled out via the paired estimating equations for the survival model.
<code>ascertained</code>	if the pair are sampled only when there is an event. This is in contrast to case.control sampling where a proband is given. This can be combined with control probands. Pair-call of twostage is needed and second column of pairs are the first jump time with an event for ascertained pairs, or time of control proband.
<code>shut.up</code>	to make the program more silent in the context of iterative procedures for case-control

Author(s)

Thomas Scheike

survivalG

G-estimator for Cox and Fine-Gray model

Description

Computes G-estimator

$$\hat{S}(t, A = a) = n^{-1} \sum_i \hat{S}(t, A = a, Z_i)$$

for the Cox model based on phreg og the Fine-Gray model based on the cifreg function. Assumes that the first covariate is \$A\$ and this is a factor. Gives influence functions of these risk estimates and SE's are based on these.

Usage

```
survivalG(x, data, time = NULL)
```

Arguments

<code>x</code>	phreg or cifreg object
<code>data</code>	data frame for risk averaging
<code>time</code>	for estimate

Author(s)

Thomas Scheike

Examples

```

data(bmt); bmt$time <- bmt$time+runif(408)*0.001
bmt$event <- (bmt$cause!=0)*1
dfactor(bmt) <- tcell~tcell

fg1 <- cifreg(Event(time,cause)~tcell+platelet+age,bmt,cause=1,
               cox.prep=TRUE,propodds=NULL)
summary(survivalG(fg1,bmt,50))

ss <- phreg(Surv(time,event)~tcell+platelet+age,bmt)
summary(survivalG(ss,bmt,50))

```

test.conc

Concordance test Compares two concordance estimates

Description

.. content for description (no empty lines) ..

Usage

```
test.conc(conc1, conc2, same.cluster = FALSE)
```

Arguments

conc1	Concordance estimate of group 1
conc2	Concordance estimate of group 2
same.cluster	if FALSE then groups are independent, otherwise estimates are based on same data.

Author(s)

Thomas Scheike

tetrachoric

Estimate parameters from odds-ratio

Description

Calculate tetrachoric correlation of probabilities from odds-ratio

Usage

```
tetrachoric(P, OR, approx = 0, ...)
```

Arguments

P	Joint probabilities or marginals (if OR is given)
OR	Odds-ratio
approx	If TRUE an approximation of the tetrachoric correlation is used
...	Additional arguments

Examples

```
tetrachoric(0.3,1.25) # Marginal p1=p2=0.3, OR=2
P <- matrix(c(0.1,0.2,0.2,0.5),2)
prod(diag(P))/prod(lava:::revdiag(P))
##mets:::assoc(P)
tetrachoric(P)
or2prob(2,0.1)
or2prob(2,c(0.1,0.2))
```

Description

The TRACE data frame contains 1877 patients and is a subset of a data set consisting of approximately 6000 patients. It contains data relating survival of patients after myocardial infarction to various risk factors.

Format

This data frame contains the following columns:

- id** a numeric vector. Patient code.
- status** a numeric vector code. Survival status. 9: dead from myocardial infarction, 0: alive, 7: dead from other causes.
- time** a numeric vector. Survival time in years.
- chf** a numeric vector code. Clinical heart pump failure, 1: present, 0: absent.
- diabetes** a numeric vector code. Diabetes, 1: present, 0: absent.
- vf** a numeric vector code. Ventricular fibrillation, 1: present, 0: absent.
- wmi** a numeric vector. Measure of heart pumping effect based on ultrasound measurements where 2 is normal and 0 is worst.
- sex** a numeric vector code. 1: female, 0: male.
- age** a numeric vector code. Age of patient.

Details

sTRACE is a subsample consisting of 300 patients.

tTRACE is a subsample consisting of 1000 patients.

Source

The TRACE study group.

Jensen, G.V., Torp-Pedersen, C., Hildebrandt, P., Kober, L., F. E. Nielsen, Melchior, T., Joen, T. and P. K. Andersen (1997), Does in-hospital ventricular fibrillation affect prognosis after myocardial infarction?, European Heart Journal 18, 919–924.

Examples

```
data(TRACE)
names(TRACE)
```

ttpd

ttpd discrete survival data on interval form

Description

ttpd discrete survival data on interval form

Source

Simulated data

twin.clustertrunc

Estimation of twostage model with cluster truncation in bivariate situation

Description

Estimation of twostage model with cluster truncation in bivariate situation

Usage

```
twin.clustertrunc(
  survformula,
  data = parent.frame(),
  theta.des = NULL,
  clusters = NULL,
  var.link = 1,
  Nit = 10,
  final.fitting = FALSE,
  ...
)
```

Arguments

survformula	Formula with survival model aalen or cox.aalen, some limitation on model specification due to call of fast.reshape (so for example interactions and * and : do not work here, expand prior to call)
data	Data frame
theta.des	design for dependence parameters in two-stage model
clusters	clustering variable for twins
var.link	exp link for theta
Nit	number of iteration
final.fitting	TRUE to do final estimation with SE and ... arguments for marginal models
...	Additional arguments to lower level functions

Author(s)

Thomas Scheike

Examples

```
library("timereg")
data(diabetes)
v <- diabetes$time*runif(nrow(diabetes))*rbinom(nrow(diabetes),1,0.5)
diabetes$v <- v

aout <- twin.clustertrunc(Surv(v,time,status)~1+ treat+adult,
  data=diabetes,clusters="id")
aout$two      ## twostage output
par(mfrow=c(2,2))
plot(aout$marg) ## marginal model output

out <- twin.clustertrunc(Surv(v,time,status)~1+prop(treat)+prop(adult),
  data=diabetes,clusters="id")
out$two      ## twostage output
plot(out$marg) ## marginal model output
```

twinbmi

BMI data set

Description

BMI data set

Format

Self-reported BMI-values on 11,411 subjects

tvpnr: twin id bmi: BMI (m/kg²) age: Age gender: (male/female) zyg: zygosity, MZ:=mz, DZ(same sex):=dz, DZ(opposite sex):=os

twinlm*Classic twin model for quantitative traits*

Description

Fits a classical twin model for quantitative traits.

Usage

```
twinlm(
  formula,
  data,
  id,
  zyg,
  DZ,
  group = NULL,
  group.equal = FALSE,
  strata = NULL,
  weights = NULL,
  type = c("ace"),
  twinnum = "twinnum",
  binary = FALSE,
  ordinal = 0,
  keep = weights,
  estimator = NULL,
  constrain = TRUE,
  control = list(),
  messages = 1,
  ...
)
```

Arguments

formula	Formula specifying effects of covariates on the response
data	<code>data.frame</code> with one observation pr row. In addition a column with the zygosity (DZ or MZ given as a factor) of each individual must be specified as well as a twin id variable giving a unique pair of numbers/factors to each twin pair
id	The name of the column in the dataset containing the twin-id variable.
zyg	The name of the column in the dataset containing the zygosity variable
DZ	Character defining the level in the zyg variable corresponding to the dyzogotic twins. If this argument is missing, the reference level (i.e. the first level) will be interpreted as the dyzogotic twins
group	Optional. Variable name defining group for interaction analysis (e.g., gender)
group.equal	If TRUE marginals of groups are assumed to be the same
strata	Strata variable name

weights	Weights matrix if needed by the chosen estimator. For use with Inverse Probability Weights
type	Character defining the type of analysis to be performed. Can be a subset of "aced" (additive genetic factors, common environmental factors, unique environmental factors, dominant genetic factors). Other choices are: <ul style="list-style-type: none"> • "0" (or "sat"): Saturated model where twin 1 and twin 2 within each twin pair may have a different marginal distribution. • "1" (or "flex","zyg"): Within twin pairs the marginal distribution is the same, but the marginal distribution may differ between MZ and DZ twins. A free correlation structure within MZ and DZ twins. • "2" (or "u", "eqmarg"): All individuals have the same marginals but a free correlation structure within MZ and DZ twins. The default value is an additive polygenic model type="ace".
twinnum	The name of the column in the dataset numbering the twins (1,2). If it does not exist in data it will automatically be created.
binary	If TRUE a liability model is fitted. Note that if the right-hand-side of the formula is a factor, character vector, or logical variable, then the liability model is automatically chosen (wrapper of the bptwin function).
ordinal	If non-zero (number of bins) a liability model is fitted.
keep	Vector of variables from data that are not specified in formula, to be added to data.frame of the SEM
estimator	Choice of estimator/model
constrain	Development argument
control	Control argument parsed on to the optimization routine
messages	Control amount of messages shown
...	Additional arguments parsed on to lower-level functions

Value

Returns an object of class `twinlm`.

Author(s)

Klaus K. Holst

See Also

`bptwin`, `twinlm.time`, `twinlm.strata`, `twinsim`

Examples

```
## Simulate data
set.seed(1)
d <- twinsim(1000,b1=c(1,-1),b2=c(),acde=c(1,1,0,1))
## E(y|z1,z2) = z1 - z2. var(A) = var(C) = var(E) = 1
```

```

## E.g to fit the data to an ACE-model without any confounders we simply write
ace <- twinlm(y ~ 1, data=d, DZ="DZ", zyg="zyg", id="id")
ace
## An AE-model could be fitted as
ae <- twinlm(y ~ 1, data=d, DZ="DZ", zyg="zyg", id="id", type="ae")
## LRT:
lava:::compare(ace,ace)
## AIC
AIC(ae)-AIC(ace)
## To adjust for the covariates we simply alter the formula statement
ace2 <- twinlm(y ~ x1+x2, data=d, DZ="DZ", zyg="zyg", id="id", type="ace")
## Summary/GOF
summary(ace2)
## Reduce Ex.Timings
## An interaction could be analyzed as:
ace3 <- twinlm(y ~ x1+x2 + x1:I(x2<0), data=d, DZ="DZ", zyg="zyg", id="id", type="ace")
ace3
## Categorical variables are also supported
d2 <- transform(d,x2cat=cut(x2,3,labels=c("Low","Med","High")))
ace4 <- twinlm(y ~ x1+x2cat, data=d2, DZ="DZ", zyg="zyg", id="id", type="ace")

```

twinsim*Simulate twin data***Description**

Simulate twin data from a linear normal ACE/ADE/AE model.

Usage

```

twinsim(
  nMZ = 100,
  nDZ = nMZ,
  b1 = c(),
  b2 = c(),
  mu = 0,
  acde = c(1, 1, 0, 1),
  randomslope = NULL,
  threshold = 0,
  cens = FALSE,
  wide = FALSE,
  ...
)

```

Arguments

nMZ	Number of monozygotic twin pairs
nDZ	Number of dizygotic twin pairs

b1	Effect of covariates (labelled x1,x2,...) of type 1. One distinct covariate value for each twin/individual.
b2	Effect of covariates (labelled g1,g2,...) of type 2. One covariate value for each twin pair.
mu	Intercept parameter.
acde	Variance of random effects (in the order A,C,D,E)
randomslope	Logical indicating whether to include random slopes of the variance components w.r.t. x1,x2,...
threshold	Threshold used to define binary outcome y0
cens	Logical variable indicating whether to censor outcome
wide	Logical indicating if wide data format should be returned
...	Additional arguments parsed on to lower-level functions

Author(s)

Klaus K. Holst

See Also

[twinlm](#)

twinstut

Stutter data set

Description

Based on nation-wide questionnaire answers from 33,317 Danish twins

Format

tvpnr: twin-pair id
 zyg: zygosity, MZ:=mz, DZ(same sex):=dz, DZ(opposite sex):=os
 stutter: stutter status (yes/no)
 age: age nr: number within twin-pair

twostageMLE

*Twostage survival model fitted by pseudo MLE***Description**

Fits Clayton-Oakes clustered survival data using marginals that are on Cox form in the likelihood for the dependence parameter as in Glidden (2000). The dependence can be modelled via a

1. Regression design on dependence parameter.

We allow a regression structure for the independent gamma distributed random effects and their variances that may depend on cluster covariates. So

$$\theta = h(z_j^T \alpha)$$

where z is specified by theta.des . The link function can be the exp when var.link=1

Usage

```
twostageMLE(
  margsurv,
  data = parent.frame(),
  theta = NULL,
  theta.des = NULL,
  var.link = 0,
  method = "NR",
  no.opt = FALSE,
  weights = NULL,
  se.cluster = NULL,
  ...
)
```

Arguments

margsurv	Marginal model from phreg
data	data frame
theta	Starting values for variance components
theta.des	design for dependence parameters, when pairs are given this is could be a (pairs) x (numer of parameters) x (max number random effects) matrix
var.link	Link function for variance if 1 then uses exp link
method	type of opitmizer, default is Newton-Raphson "NR"
no.opt	to not optimize, for example to get score and iid for specific theta
weights	cluster specific weights, but given with length equivalent to data-set, weights for score equations
se.cluster	specifies how the influence functions are summed before squared when computing the variance. Note that the id from the marginal model is used to construct MLE, and then these scores can be summed with the se.cluster argument.
...	arguments to be passed to optimizer

Author(s)

Thomas Scheike

References

- Measuring early or late dependence for bivariate twin data Scheike, Holst, Hjelmborg (2015), LIDA
Twostage modelling of additive gamma frailty models for survival data. Scheike and Holst, working paper
Shih and Louis (1995) Inference on the association parameter in copula models for bivariate survival data, Biometrics, (1995).
Glidden (2000), A Two-Stage estimator of the dependence parameter for the Clayton Oakes model, LIDA, (2000).

Examples

```
data(diabetes)
dd <- phreg(Surv(time,status==1)~treat+cluster(id),diabetes)
oo <- twostageMLE(dd,data=diabetes)
summary(oo)

theta.des <- model.matrix(~-1+factor(adult),diabetes)

oo <-twostageMLE(dd,data=diabetes,theta.des=theta.des)
summary(oo)
```

Index

- * **binomial**
 - binomial.twostage, 14
 - easy.binomial.twostage, 74
- * **data**
 - base1cumhaz, 8
 - base44cumhaz, 8
 - base4cumhaz, 8
 - dermalridges, 56
 - dermalridgesMZ, 57
 - drcumhaz, 64
 - ghaplos, 94
 - hapfreqs, 103
 - haploX, 106
 - mena, 119
 - migr, 120
 - multcif, 122
 - np, 122
 - prt, 130
 - ttpd, 174
 - twinbmi, 175
 - twinstut, 179
- * **models**
 - blocksample, 27
 - mets.options, 120
 - twinlm, 176
 - twinsim, 178
- * **package**
 - bmt, 28
 - diabetes, 58
 - melanoma, 118
 - mets-package, 5
 - TRACE, 173
- * **regression**
 - binomial.twostage, 14
 - easy.binomial.twostage, 74
 - twinlm, 176
 - twinsim, 178
- * **survival**
 - cor.cif, 42
- easy.survival.twostage, 78
- EventSplit, 84
- Grandom.cif, 99
- LinSpline, 115
- random.cif, 130
- rchaz, 133
- rcrisk, 134
- sim.cause.cox, 145
- sim.cif, 146
- sim.cox, 147
- summary.cor, 159
- survival.iterative, 160
- survival.twostage, 164
- survival.twostageCC, 169
- twostageMLE, 180
- * **twostage**
 - easy.survival.twostage, 78
- * **utilities**
 - blocksample, 27
 - npc, 123
- aalenfrailty, 5
- aalenMets, 6
- ace.family.design (npc), 123
- addCums (rchaz), 133
- alpha2kendall (npc), 123
- alpha2spear (npc), 123
- ascertained.pairs (npc), 123
- back2timereg, 7
- base1cumhaz, 8
- base44cumhaz, 8
- base4cumhaz, 8
- basecumhaz (basehazplot.phreg), 9
- basehazplot.phreg, 9
- bicomprisk, 10
- bicompriskData (bicomprisk), 10
- BinAugmentCifstrata, 12
- binomial.twostage, 14
- binreg, 19

binregATE, 22
binregATEbin (binregATE), 22
binregCasewise, 24
binregt (binreg), 19
biprobit, 25
blocksample, 27
bmt, 28
Bootcovariancerecurrence
 (covarianceRecurrent), 48
BootcovariancerecurrenceS
 (covarianceRecurrent), 48
BootmediatorSurv (mediatorSurv), 116
Bootphreg, 29
bplot (basehazplot.phreg), 9
bplotdFG (doubleFGR), 61
bptwin, 30, 177

casewise, 32
casewise.bin (casewise.test), 33
casewise.test, 33
cause.pchazard.sim (rcrisk), 134
CCbinomial.twostage (npc), 123
cif, 35
cif.yearslost (resmean.phreg), 140
cifreg, 36
ClaytonOakes, 38
cluster.index, 39
coarse.clust (npc), 123
coefmat (npc), 123
concordance.cor (concordanceCor), 40
concordanceCor, 40
concordanceTwinACE (npc), 123
concordanceTwostage (npc), 123
cor.cif, 42
corsim.prostate (npc), 123
count.history, 46
count.historyVar (count.history), 46
countID (cluster.index), 39
covarianceRecurrent, 48
covarianceRecurrentS
 (covarianceRecurrent), 48
covfr (predict.phreg), 126
covfridstrata (predict.phreg), 126
covfridstrataCov (predict.phreg), 126
covIntH1dM1IntH2dM2 (simRecurrent), 154
cpred (fast.approx), 88
cumContr (gofZ.phreg), 98
cumsum2strata (predict.phreg), 126
cumsumidstratasum (predict.phreg), 126

cumsumidstratasumCov (predict.phreg),
 126
cumsumstrata (predict.phreg), 126
cumsumstratasum (predict.phreg), 126

daggr (daggregate), 49
daggregate, 49
Dbvn, 51
dby, 51
dby2 (dby), 51
dby2<- (dby), 51
dby<- (dby), 51
dbyr (dby), 51
dcor, 53
dcount (dcor), 53
dcut, 54
dcut<- (dcut), 54
ddrop (dcut), 54
ddrop<- (dcut), 54
dermalridges, 56
dermalridgesMZ, 57
deval (dcor), 53
deval2 (dcor), 53
dfactor (drelevel), 68
dfactor<- (drelevel), 68
dhead (dprint), 63
diabetes, 58
diffstrata (cifreg), 36
dInterval
 (interval.logitsurv.discrete),
 106
divide.conquer, 58
divide.conquer.timereg, 59
dkeep (dcut), 54
dkeep<- (dcut), 54
dlag, 60
dlag<- (dlag), 60
dlev (drelevel), 68
dlev<- (drelevel), 68
dlevel (drelevel), 68
dlevel<- (drelevel), 68
dlevels (drelevel), 68
dlist (dprint), 63
dmean (dcor), 53
dmeansd (dcor), 53
dmvн (pmvn), 125
dnames (dcut), 54
dnames<- (dcut), 54
dnumeric (drelevel), 68

dnumeric<- (drelevel), 68
 doubleFGR, 61
 dprint, 63
 dquantile (dcor), 53
 drcumhaz, 64
 dreg, 65
 drelev (drelevel), 68
 drelev<- (drelevel), 68
 drelevel, 68
 drelevel<- (drelevel), 68
 drename (dcut), 54
 drename<- (dcut), 54
 dreshape (fast.reshape), 89
 drm (dcut), 54
 drm<- (dcut), 54
 drop.specials (npc), 123
 drop.strata (FG_AugmentCifstrata), 92
 dsample (blocksample), 27
 dscalar (dcor), 53
 dsd (dcor), 53
 dsort, 70
 dsort2 (dsort), 70
 dsort<- (dsort), 70
 dspline, 70
 dspline<- (dspline), 70
 dstr (dcor), 53
 dsubset (dcor), 53
 dsum (dcor), 53
 dsummary (dcor), 53
 dtab (datatable), 72
 datatable, 72
 dtail (dprint), 63
 dtrans (dtransform), 73
 dtrans<- (dtransform), 73
 dtransform, 73
 dtransform<- (dtransform), 73
 dunique (dcut), 54

 easy.binomial.twostage, 74
 easy.survival.twostage, 78
 Effbinreg, 80
 EVaddGam, 82
 eventpois, 83
 EventSplit, 84
 extendCums (simMultistate), 152

 familycluster.index, 86
 familyclusterWithProbands.index, 87
 fast.approx, 88

 fast.cluster (npc), 123
 fast.pattern, 89
 fast.reshape, 89
 FastCoxPLstrataR (phregR), 124
 faster.reshape (npc), 123
 FG_AugmentCifstrata, 92
 FGprediid (cifreg), 36
 folds (npc), 123
 force.same.cens (npc), 123

 ghaplos, 94
 GLprediid (recreg), 135
 gof.phreg, 94
 gofG.phreg, 95
 gofM.phreg, 96
 gofZ.phreg, 98
 Random.cif, 99
 groupable (npc), 123

 hapfreqs, 103
 haplo.surv.discrete, 103
 haploX, 106
 headstrata (predict.phreg), 126

 IIDbaseline.cifreg (cifreg), 36
 IIDbaseline.phreg (phreg), 123
 ilap (npc), 123
 indexstrata (fast.approx), 88
 indexstratarightR (cifreg), 36
 Interval (interval.logitsurv.discrete),
 106
 interval.logitsurv.discrete, 106
 invsubdist (sim.cif), 146
 ipw, 107
 ipw2, 109

 jumptimes (npc), 123

 kendall.ClaytonOakes.twin.ace (npc), 123
 kendall.normal.twin.ace (npc), 123
 km, 111
 kumarsim (binregATE), 22
 kumarsimRCT (binregATE), 22

 lifecourse, 112
 lifetable (lifetable.matrix), 114
 lifetable.matrix, 114
 lin.approx (rchaz), 133
 LinSpline, 115
 logitATE (binregATE), 22

logitIPCW (binreg), 19
logitIPCWATE (binregATE), 22
logitSurv, 115
loglikMVN (pmvn), 125

make.pairwise.design (npc), 123
matdoubleindex (predict.phreg), 126
matplot.mets.twostage (npc), 123
mdi (predict.phreg), 126
mediatorSurv, 116
medweight, 118
melanoma, 118
mena, 119
mets-package, 5
mets.options, 120
migr, 120
mlogit, 121
multcif, 122
mystrata (cluster.index), 39
mystrata2index (cluster.index), 39

nonparcuminc (npc), 123
normalATE (binregATE), 22
np, 122
npc, 123

object.defined (npc), 123
or.cif (cor.cif), 42
or2prob (tetrachoric), 172

p11.binomial.twostage.RV (npc), 123
pairRisk (cluster.index), 39
pbvn (pmvn), 125
pcif (eventpois), 83
phreg, 123
phregR, 124
piecewise.data (npc), 123
piecewise.twostage (npc), 123
plack.cif, 125
plack.cif2 (plack.cif), 125
plot.covariace.recurrent
 (covarianceRecurrent), 48
plotConfRegion (basehazplot.phreg), 9
plotConfRegionSE (basehazplot.phreg), 9
plotcr (npc), 123
plotstrata (basehazplot.phreg), 9
plotSurvd (haplo.surv.discrete), 103
pmvn, 125
ppch (rpch), 144

pre.cifs (sim.cif), 146
pred.cif.boot (Bootphreg), 29
predict.phreg, 126
predictCumhaz (fast.approx), 88
predictdFG (doubleFGR), 61
predictlogitSurv
 (interval.logitsurv.discrete),
 106
predictmlogit (mlogit), 121
predictPairPlack (npc), 123
predictSurvd (haplo.surv.discrete), 103
print.casewise, 127
prob.exceed.recurrent, 128
prob.exceedBiRecurrent
 (prob.exceed.recurrent), 128
prob.exceedBiRecurrentStrata
 (prob.exceed.recurrent), 128
prob.exceedRecurrent
 (prob.exceed.recurrent), 128
prob.exceedRecurrentStrata
 (prob.exceed.recurrent), 128
procform (npc), 123
procform3 (npc), 123
procformdata (npc), 123
prt, 130

random.cif, 130
randomDes (survival.twostage), 164
rchaz, 133
rcrisk, 134
read.fit (sim.cox), 147
readmargsurv (survival.twostage), 164
readPhreg (phreg), 123
recmarg (recurrentMarginal), 137
recreg, 135
recregIPCW (recreg), 135
recurrentMarginal, 137
recurrentMarginalAIPCW
 (recurrentMarginal), 137
recurrentMarginalAIPCWdata
 (recurrentMarginal), 137
recurrentMarginalIPCW
 (recurrentMarginal), 137
resmean.phreg, 140
resmeanATE, 141
resmeanIPCW, 142
revcumsum (predict.phreg), 126
revcumsum2strata (predict.phreg), 126
revcumsum2stratafdN (predict.phreg), 126

revcumsumidstratasum (predict.phreg), 126
 revcumsumidstratasumCov (predict.phreg), 126
 revcumsumstrata (predict.phreg), 126
 revcumsumstratasum (predict.phreg), 126
 rmst.phreg (resmean.phreg), 140
 rmstATE (resmeanATE), 141
 rmstIPCW (resmeanIPCW), 142
 rmvn (pmvn), 125
 robust.basehaz.phreg (predict.phreg), 126
 robust.phreg (phreg), 123
 rpch, 144
 rr.cif (cor.cif), 42
 scalecumhaz (recreg), 135
 scoreMVN (pmvn), 125
 setup.cif (FG_AugmentCifstrata), 92
 showfitsim (simRecurrent), 154
 sim (npc), 123
 sim.base (sim.cox), 147
 sim.cause.cox, 145
 sim.cif, 146
 sim.cifs (sim.cif), 146
 sim.cifsRestrict (sim.cif), 146
 sim.cox, 147
 simAalenFrailty, 149
 simbinClaytonOakes.family.ace (npc), 123
 simbinClaytonOakes.pairs (npc), 123
 simbinClaytonOakes.twin.ace (npc), 123
 simBinFam (npc), 123
 simBinFam2 (npc), 123
 simBinPlack (npc), 123
 simClaytonOakes, 150
 simClaytonOakes.family.ace (npc), 123
 simClaytonOakes.twin.ace (npc), 123
 simClaytonOakesLam (simClaytonOakes), 150
 simClaytonOakesWei, 151
 simCompete.simple (npc), 123
 simCompete.twin.ace (npc), 123
 simCox (npc), 123
 simFrailty.simple (npc), 123
 simlogitSurvd (interval.logitsurv.discrete), 106
 simMultistate, 152
 simnordic (npc), 123
 simrchaz (rchaz), 133
 simRecurrent, 154
 simRecurrentGamma (simRecurrent), 154
 simRecurrentII, 155
 simRecurrentTS, 157
 simsubdist (sim.cif), 146
 simSurvFam (npc), 123
 simTPP (haplo.surv.discrete), 103
 simul.cifs (FG_AugmentCifstrata), 92
 simulate.cox (sim.cox), 147
 slope.process (casewise.test), 33
 squareintHdM (simRecurrent), 154
 sTRACE (TRACE), 173
 strataAugment (recreg), 135
 strataC (FG_AugmentCifstrata), 92
 subdist (sim.cif), 146
 summary.cor, 159
 summaryTimeobject (prob.exceed.recurrent), 128
 sumstrata (predict.phreg), 126
 surv.boxarea (npc), 123
 survival.iterative, 160
 survival.twostage, 164
 survival.twostageCC, 169
 survivalG, 171
 tailstrata (predict.phreg), 126
 test.conc, 172
 tetrachoric, 172
 tie.breaker (recurrentMarginal), 137
 TRACE, 173
 ttpd, 174
 tTRACE (TRACE), 173
 twin.clustertrunc, 174
 twin.polygen.design (npc), 123
 twinbmi, 175
 twinlm, 32, 176, 179
 twinlm.strata, 32, 177
 twinlm.time, 32, 177
 twinlm.time (bptwin), 30
 twinsim, 32, 177, 178
 twinstut, 179
 twostage.aalen (survival.twostage), 164
 twostage.cox.aalen (survival.twostage), 164
 twostage.coxpath (survival.twostage), 164
 twostage.phreg (survival.twostage), 164
 twostageMLE, 180

`vecAllStrata(cifreg)`, [36](#)