

Package ‘mlr3cluster’

December 22, 2022

Title Cluster Extension for 'mlr3'

Version 0.1.6

Description Extends the 'mlr3' package with cluster analysis.

License LGPL-3

URL <https://mlr3cluster.mlr-org.com>,
<https://github.com/mlr-org/mlr3cluster>

BugReports <https://github.com/mlr-org/mlr3cluster/issues>

Depends R (>= 3.1.0), mlr3 (>= 0.14.0)

Imports backports (>= 1.1.10), checkmate, clue, clusterCrit, cluster,
data.table, mlr3misc (>= 0.9.4), paradox, R6, stats

Suggests dbscan, e1071, ClusterR, kernlab, apcluster, LPCM, mclust,
mlbench, RWeka, testthat

Encoding UTF-8

RoxygenNote 7.2.3

Collate 'LearnerClust.R' 'aaa.R' 'LearnerClustAffinityPropagation.R'
'LearnerClustAgnes.R' 'LearnerClustCMeans.R'
'LearnerClustCobweb.R' 'LearnerClustDBSCAN.R'
'LearnerClustDiana.R' 'LearnerClustEM.R' 'LearnerClustFanny.R'
'LearnerClustFarthestFirst.R' 'LearnerClustFeatureless.R'
'LearnerClustHclust.R' 'LearnerClustKKMeans.R'
'LearnerClustKMeans.R' 'LearnerClustMclust.R'
'LearnerClustMeanShift.R' 'LearnerClustMiniBatchKMeans.R'
'LearnerClustPAM.R' 'LearnerClustSimpleKMeans.R'
'LearnerClustXMeans.R' 'MeasureClust.R' 'measures.R'
'MeasureClustInternal.R' 'PredictionClust.R'
'PredictionDataClust.R' 'TaskClust.R' 'TaskClust_usarrest.R'
'as_prediction_clust.R' 'as_task_clust.R' 'helper.R' 'zzz.R'

NeedsCompilation no

Author Damir Pulatov [cre, aut],

Michel Lang [aut] (<<https://orcid.org/0000-0001-9754-0393>>)

Maintainer Damir Pulatov <damirpolat@protonmail.com>

Repository CRAN

Date/Publication 2022-12-22 18:00:02 UTC

R topics documented:

mlr3cluster-package	3
as_prediction_clust	3
as_task_clust	4
LearnerClust	5
MeasureClust	7
mlr_learners_clust.agnes	9
mlr_learners_clust.ap	10
mlr_learners_clust.cmeans	12
mlr_learners_clust.cobweb	13
mlr_learners_clust.dbscan	15
mlr_learners_clust.diana	16
mlr_learners_clust.em	19
mlr_learners_clust.fanny	20
mlr_learners_clust.featureless	22
mlr_learners_clust.ff	23
mlr_learners_clust.hclust	25
mlr_learners_clust.kkmeans	26
mlr_learners_clust.kmeans	28
mlr_learners_clust.MBatchKMeans	29
mlr_learners_clust.mclust	31
mlr_learners_clust.meanshift	33
mlr_learners_clust.pam	34
mlr_learners_clust.SimpleKMeans	36
mlr_learners_clust.xmeans	37
mlr_measures_clust.ch	39
mlr_measures_clust.db	40
mlr_measures_clust.dunn	41
mlr_measures_clust.silhouette	41
mlr_measures_clust.wss	42
mlr_tasks_usarrests	43
PredictionClust	43
TaskClust	45
Index	47

mlr3cluster-package *mlr3cluster: Cluster Extension for 'mlr3'*

Description

Extends the 'mlr3' package with cluster analysis.

Author(s)

Maintainer: Damir Pulatov <damirpolat@protonmail.com>

Authors:

- Michel Lang <michellang@gmail.com> ([ORCID](#))

See Also

Useful links:

- <https://mlr3cluster.mlr-org.com>
- <https://github.com/mlr-org/mlr3cluster>
- Report bugs at <https://github.com/mlr-org/mlr3cluster/issues>

as_prediction_clust *Convert to a Cluster Prediction*

Description

Convert object to a [PredictionClust](#).

Usage

```
as_prediction_clust(x, ...)  
  
## S3 method for class 'PredictionClust'  
as_prediction_clust(x, ...)  
  
## S3 method for class 'data.frame'  
as_prediction_clust(x, ...)
```

Arguments

x	(any) Object to convert.
...	(any) Additional arguments.

Value

[PredictionClust](#).

Examples

```
if (requireNamespace("e1071")) {
  # create a prediction object
  task = tsk("usarrests")
  learner = lrn("clust.kmeans")
  learner = lrn("clust.cmeans", predict_type = "prob")
  learner$train(task)
  p = learner$predict(task)

  # convert to a data.table
  tab = as.data.table(p)

  # convert back to a Prediction
  as_prediction_clust(tab)

  # split data.table into a 3 data.tables based on UrbanPop
  f = cut(task$data(rows = tab$row_ids)$UrbanPop, 3)
  tabs = split(tab, f)

  # convert back to list of predictions
  preds = lapply(tabs, as_prediction_clust)

  # calculate performance in each group
  sapply(preds, function(p) p$score(task = task))
}
```

as_task_clust

Convert to a Cluster Task

Description

Convert object to a [TaskClust](#). This is a S3 generic, specialized for at least the following objects:

1. [TaskClust](#): ensure the identity.
2. [data.frame\(\)](#) and [DataBackend](#): provides an alternative to calling constructor of [TaskClust](#).

Usage

```
as_task_clust(x, ...)
```

```
## S3 method for class 'TaskClust'
as_task_clust(x, clone = FALSE, ...)
```

```
## S3 method for class 'data.frame'
as_task_clust(x, id = deparse(substitute(x)), ...)
```

```
## S3 method for class 'DataBackend'
as_task_clust(x, id = deparse(substitute(x)), ...)

## S3 method for class 'formula'
as_task_clust(x, data, id = deparse(substitute(data)), ...)
```

Arguments

x	(any) Object to convert.
...	(any) Additional arguments.
clone	(logical(1)) If TRUE, ensures that the returned object is not the same as the input x.
id	(character(1)) Id for the new task. Defaults to the (deparsed and substituted) name of the data argument.
data	(data.frame()) Data frame containing all columns specified in formula x.

Value

[TaskClust](#).

Examples

```
as_task_clust(datasets::USArrests)
```

LearnerClust

Cluster Learner

Description

This Learner specializes [mlr3::Learner](#) for cluster problems:

- task_type is set to "clust".
- Creates [Predictions](#) of class [PredictionClust](#).
- Possible values for predict_types are:
 - "partition": Integer indicating the cluster membership.
 - "prob": Probability for belonging to each cluster.

Predefined learners can be found in the [mlr3misc::Dictionary mlr3::mlr_learners](#).

Super class

[mlr3::Learner](#) -> LearnerClust

Public fields

- assignments (NULL | vector())
Cluster assignments from learned model.
- save_assignments (logical())
Should assignments for 'train' data be saved in the learner? Default is TRUE.

Methods**Public methods:**

- [LearnerClust\\$new\(\)](#)
- [LearnerClust\\$reset\(\)](#)
- [LearnerClust\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerClust$new(
  id,
  param_set = ps(),
  predict_types = "partition",
  feature_types = character(),
  properties = character(),
  packages = character(),
  label = NA_character_,
  man = NA_character_
)
```

Arguments:

- `id` (character(1))
Identifier for the new instance.
- `param_set` ([paradox::ParamSet](#))
Set of hyperparameters.
- `predict_types` (character())
Supported predict types. Must be a subset of [mlr_reflections\\$learner_predict_types](#).
- `feature_types` (character())
Feature types the learner operates on. Must be a subset of [mlr_reflections\\$task_feature_types](#).
- `properties` (character())
Set of properties of the [Learner](#). Must be a subset of [mlr_reflections\\$learner_properties](#).
The following properties are currently standardized and understood by learners in [mlr3](#):
- "missings": The learner can handle missing values in the data.
 - "weights": The learner supports observation weights.
 - "importance": The learner supports extraction of importance scores, i.e. comes with an `$importance()` extractor function (see section on optional extractors in [Learner](#)).
 - "selected_features": The learner supports extraction of the set of selected features, i.e. comes with a `$selected_features()` extractor function (see section on optional extractors in [Learner](#)).

- "oob_error": The learner supports extraction of estimated out of bag error, i.e. comes with a `oob_error()` extractor function (see section on optional extractors in [Learner](#)).
- `packages` (character())
Set of required packages. A warning is signaled by the constructor if at least one of the packages is not installed, but loaded (not attached) later on-demand via `requireNamespace()`.
- `label` (character(1))
Label for the new instance.
- `man` (character(1))
String in the format `[pkg]::[topic]` pointing to a manual page for this object. The referenced help package can be opened via method `$help()`.

Method `reset()`: Reset assignments field before calling parent's `reset()`.

Usage:

`LearnerClust$reset()`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

`LearnerClust$clone(deep = FALSE)`

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3)
library(mlr3cluster)
ids = mlr_learners$keys("^clust")
ids

# get a specific learner from mlr_learners:
lrn = mlr_learners$get("clust.kmeans")
print(lrn)
```

MeasureClust

Cluster Measure

Description

This measure specializes [mlr3::Measure](#) for cluster analysis:

- `task_type` is set to "clust".
- Possible values for `predict_type` are "partition" and "prob".

Predefined measures can be found in the [mlr3misc::Dictionary mlr3::mlr_measures](#).

Super class

[mlr3::Measure](#) -> MeasureClust

Methods

Public methods:

- [MeasureClust\\$new\(\)](#)

Method new(): Creates a new instance of this [R6](#) class.

Usage:

```
MeasureClust$new(
  id,
  range,
  minimize = NA,
  aggregator = NULL,
  properties = character(),
  predict_type = "partition",
  task_properties = character(),
  packages = character(),
  label = NA_character_,
  man = NA_character_
)
```

Arguments:

id (character(1))

Identifier for the new instance.

range (numeric(2))

Feasible range for this measure as `c(lower_bound, upper_bound)`. Both bounds may be infinite.

minimize (logical(1))

Set to TRUE if good predictions correspond to small values, and to FALSE if good predictions correspond to large values. If set to NA (default), tuning this measure is not possible.

aggregator (function(x))

Function to aggregate individual performance scores `x` where `x` is a numeric vector. If NULL, defaults to [mean\(\)](#).

properties (character())

Properties of the measure. Must be a subset of [mlr_reflections\\$measure_properties](#). Supported by `mlr3`:

- "requires_task" (requires the complete [Task](#)),
- "requires_learner" (requires the trained [Learner](#)),
- "requires_train_set" (requires the training indices from the [Resampling](#)), and
- "na_score" (the measure is expected to occasionally return NA or NaN).

predict_type (character(1))

Required predict type of the [Learner](#). Possible values are stored in [mlr_reflections\\$learner_predict_types](#).

task_properties (character())

Required task properties, see [Task](#).

packages (character())

Set of required packages. A warning is signaled by the constructor if at least one of the packages is not installed, but loaded (not attached) later on-demand via [requireNamespace\(\)](#).

label (character(1))

Label for the new instance.

man (character(1))

String in the format [pkg]::[topic] pointing to a manual page for this object. The referenced help package can be opened via method \$help().

See Also

Example cluster measures: [clust.dunn](#)

mlr_learners_clust.agnes

Agglomerative Hierarchical Clustering Learner

Description

A **LearnerClust** for agglomerative hierarchical clustering implemented in `cluster::agnes()`. The predict method uses `stats::cutree()` which cuts the tree resulting from hierarchical clustering into specified number of groups (see parameter `k`). The default number for `k` is 2.

Dictionary

This **Learner** can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.agnes")
lrn("clust.agnes")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **cluster**

Parameters

Id	Type	Default	Levels	Range
metric	character	euclidean	euclidean, manhattan	-
stand	logical	FALSE	TRUE, FALSE	-
method	character	average	average, single, complete, ward, weighted, flexible, gaverage	-
trace.lev	integer	0		$[0, \infty)$
k	integer	2		$[1, \infty)$
par.method	untyped	-		-

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustAgnes
```

Methods**Public methods:**

- [LearnerClustAgnes\\$new\(\)](#)
- [LearnerClustAgnes\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerClustAgnes$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustAgnes$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("cluster")) {
  learner = mlr3::lrn("clust.agnes")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.ap *Affinity Propagation Clustering Learner*

Description

A [LearnerClust](#) for Affinity Propagation clustering implemented in [apcluster::apcluster\(\)](#). [apcluster::apcluster\(\)](#) doesn't have set a default for similarity function. Therefore, the `s` parameter here is set to `apcluster::negDistMat(r = 2L)` by default since this is what is used in the original paper on Affinity Propagation clustering. The `predict` method computes the closest cluster exemplar to find the cluster memberships for new data. The code is taken from [StackOverflow](#) answer by the `apcluster` package maintainer.

Dictionary

This [Learner](#) can be instantiated via the dictionary [mlr_learners](#) or with the associated sugar function [lrn\(\)](#):

```
mlr_learners$get("clust.ap")
lrn("clust.ap")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **apcluster**

Parameters

Id	Type	Default	Levels	Range
s	untyped	apcluster::negDistMat, 2		-
p	untyped	NA		-
q	numeric	-		[0, 1]
maxits	integer	1000		[1, ∞)
convits	integer	100		[1, ∞)
lam	numeric	0.9		[0.5, 1]
includeSim	logical	FALSE	TRUE, FALSE	-
details	logical	FALSE	TRUE, FALSE	-
nonoise	logical	FALSE	TRUE, FALSE	-
seed	integer	-		$(-\infty, \infty)$

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustAP`

Methods**Public methods:**

- `LearnerClustAP$new()`
- `LearnerClustAP$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustAP$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustAP$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```

if (requireNamespace("apcluster")) {
  learner = mlr3::lrn("clust.ap")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}

```

mlr_learners_clust.cmeans

Fuzzy C-Means Clustering Learner

Description

A **LearnerClust** for fuzzy clustering implemented in `e1071::cmeans()`. `e1071::cmeans()` doesn't have a default value for the number of clusters. Therefore, the `centers` parameter here is set to 2 by default. The predict method uses `clue::cl_predict()` to compute the cluster memberships for new data.

Dictionary

This **Learner** can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```

mlr_learners$get("clust.cmeans")
lrn("clust.cmeans")

```

Meta Information

- Task type: "clust"
- Predict Types: "partition", "prob"
- Feature Types: "logical", "integer", "numeric"
- Required Packages: **mlr3**, **mlr3cluster**, **e1071**

Parameters

Id	Type	Default	Levels	Range
centers	untyped	2		-
iter.max	integer	100		[1, ∞)
verbose	logical	FALSE	TRUE, FALSE	-
dist	character	euclidean	euclidean, manhattan	-
method	character	cmeans	cmeans, ufcl	-
m	numeric	2		[1, ∞)
rate.par	numeric	-		[0, 1]
weights	untyped	1		-
control	untyped	-		-

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustCMeans`

Methods**Public methods:**

- `LearnerClustCMeans$new()`
- `LearnerClustCMeans$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustCMeans$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustCMeans$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("e1071")) {
  learner = mlr3::lrn("clust.cmeans")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.cobweb

Cobweb Clustering Learner

Description

A `LearnerClust` for Cobweb clustering implemented in `RWeka::Cobweb()`. The `predict` method uses `RWeka::predict.Weka_clusterer()` to compute the cluster memberships for new data.

Dictionary

This `Learner` can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.cobweb")
lrn("clust.cobweb")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **RWeka**

Parameters

Id	Type	Default	Range
A	numeric	1	$[0, \infty)$
C	numeric	0.002	$[0, \infty)$
S	integer	42	$[1, \infty)$

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustCobweb`

Methods

Public methods:

- `LearnerClustCobweb$new()`
- `LearnerClustCobweb$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustCobweb$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustCobweb$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("RWeka")) {
  learner = mlr3::lrn("clust.cobweb")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.dbscan

Density-Based Clustering Learner

Description

A [LearnerClust](#) for density-based clustering implemented in [dbscan::dbscan\(\)](#). The predict method uses [dbscan::predict.dbscan_fast\(\)](#) to compute the cluster memberships for new data.

Dictionary

This [Learner](#) can be instantiated via the dictionary [mlr_learners](#) or with the associated sugar function [lrn\(\)](#):

```
mlr_learners$get("clust.dbscan")
lrn("clust.dbscan")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **dbscan**

Parameters

Id	Type	Default	Levels	Range
eps	numeric	-		$[0, \infty)$
minPts	integer	5		$[0, \infty)$
borderPoints	logical	TRUE	TRUE, FALSE	-
weights	untyped	-		-
search	character	kdtree	kdtree, linear, dist	-
bucketSize	integer	10		$[1, \infty)$
splitRule	character	SUGGEST	STD, MIDPT, FAIR, SL_MIDPT, SL_FAIR, SUGGEST	-
approx	numeric	0		$(-\infty, \infty)$

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustDBSCAN
```

Methods

Public methods:

- [LearnerClustDBSCAN\\$new\(\)](#)
- [LearnerClustDBSCAN\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustDBSCAN$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustDBSCAN$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("dbscan")) {
  learner = mlr3::lrn("clust.dbscan")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.diana

Divisive Hierarchical Clustering Learner

Description

A [LearnerClust](#) for divisive hierarchical clustering implemented in `cluster::diana()`. The predict method uses `stats::cutree()` which cuts the tree resulting from hierarchical clustering into specified number of groups (see parameter `k`). The default value for `k` is 2.

Dictionary

This [Learner](#) can be instantiated via the [dictionary mlr_learners](#) or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.diana")
lrn("clust.diana")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **cluster**

Parameters

Id	Type	Default	Levels	Range
metric	character	euclidean	euclidean, manhattan	-
stand	logical	FALSE	TRUE, FALSE	-
trace.lev	integer	0		$[0, \infty)$
k	integer	2		$[1, \infty)$

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustDiana`

Methods

Public methods:

- `LearnerClustDiana$new()`
- `LearnerClustDiana$clone()`

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerClustDiana$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustDiana$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("cluster")) {
  learner = mlr3::lrn("clust.diana")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

 mlr_learners_clust.em *Expectation-Maximization Clustering Learner*

Description

A [LearnerClust](#) for Expectation-Maximization clustering implemented in `RWeka::list_Weka_interfaces()`. The predict method uses `RWeka::predict.Weka_clusterer()` to compute the cluster memberships for new data.

Dictionary

This [Learner](#) can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.em")
lrn("clust.em")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **RWeka**

Parameters

Id	Type	Default	Levels	Range
I	integer	100		$[1, \infty)$
ll_cv	numeric	1e-06		$[1e - 06, \infty)$
ll_iter	numeric	1e-06		$[1e - 06, \infty)$
M	numeric	1e-06		$[1e - 06, \infty)$
max	integer	-1		$[-1, \infty)$
N	integer	-1		$[-1, \infty)$
num_slots	integer	1		$[1, \infty)$
S	integer	100		$[0, \infty)$
X	integer	10		$[1, \infty)$
K	integer	10		$[1, \infty)$
V	logical	FALSE	TRUE, FALSE	-
output_debug_info	logical	FALSE	TRUE, FALSE	-

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustEM`

Methods**Public methods:**

- `LearnerClustEM$new()`
- `LearnerClustEM$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustEM$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustEM$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("RWeka")) {
  learner = mlr3::lrn("clust.em")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.fanny

Fuzzy Analysis Clustering Learner

Description

A `LearnerClust` for fuzzy clustering implemented in `cluster::fanny()`. `cluster::fanny()` doesn't have a default value for the number of clusters. Therefore, the `k` parameter which corresponds to the number of clusters here is set to 2 by default. The `predict` method copies cluster assignments and memberships generated for train data. The `predict` does not work for new data.

Dictionary

This `Learner` can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.fanny")
lrn("clust.fanny")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”, “prob”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **cluster**

Parameters

Id	Type	Default	Levels	Range
k	integer	2		$[1, \infty)$
memb.exp	numeric	2		$[1, \infty)$
metric	character	euclidean	euclidean, manhattan, SqEuclidean	-
stand	logical	FALSE	TRUE, FALSE	-
maxit	integer	500		$[0, \infty)$
tol	numeric	1e-15		$[0, \infty)$
trace.lev	integer	0		$[0, \infty)$

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustFanny`

Methods**Public methods:**

- `LearnerClustFanny$new()`
- `LearnerClustFanny$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustFanny$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustFanny$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("cluster")) {
  learner = mlr3::lrn("clust.fanny")
  print(learner)
}
```

```
# available parameters:
learner$param_set$ids()
}
```

```
mlr_learners_clust.featureless
Featureless Clustering Learner
```

Description

A simple [LearnerClust](#) which randomly (but evenly) assigns observations to `num_clusters` partitions (default: 1 partition).

Dictionary

This [Learner](#) can be instantiated via the [dictionary mlr_learners](#) or with the associated sugar function [lrn\(\)](#):

```
mlr_learners$get("clust.featureless")
lrn("clust.featureless")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”, “prob”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**

Parameters

Id	Type	Default	Range
num_clusters	integer	1	[1, ∞)

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustFeatureless
```

Methods

Public methods:

- [LearnerClustFeatureless\\$new\(\)](#)
- [LearnerClustFeatureless\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustFeatureless$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustFeatureless$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("mlr3")) {
  learner = mlr3::lrn("clust.featureless")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.ff *Farthest First Clustering Learner*

Description

A **LearnerClust** for Farthest First clustering implemented in `RWeka::FarthestFirst()`. The `predict` method uses `RWeka::predict.Weka_clusterer()` to compute the cluster memberships for new data.

Dictionary

This **Learner** can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.ff")
lrn("clust.ff")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **RWeka**

Parameters

Id	Type	Default	Levels	Range
N	integer	2		[1, ∞)
S	integer	1		[1, ∞)
output_debug_info	logical	FALSE	TRUE, FALSE	-

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustFF`

Methods

Public methods:

- `LearnerClustFarthestFirst$new()`
- `LearnerClustFarthestFirst$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustFarthestFirst$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustFarthestFirst$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
## Not run:
if (requireNamespace("RWeka")) {
  learner = mlr3::lrn("clust.ff")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
## End(Not run)
```

mlr_learners_clust.hclust

Agglomerative Hierarchical Clustering Learner

Description

A [LearnerClust](#) for agglomerative hierarchical clustering implemented in `stats::hclust()`. Difference Calculation is done by `stats::dist()`

Dictionary

This [Learner](#) can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.hclust")
lrn("clust.hclust")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, ‘stats’

Parameters

Id	Type	Default	Levels	Range
method	character	complete	ward.D, ward.D2, single, complete, average, mcquitty, median, centroid	-
members	untyped			-
distmethod	character	euclidean	euclidean, maximum, manhattan, canberra, binary, minkowski	-
diag	logical	FALSE	TRUE, FALSE	-
upper	logical	FALSE	TRUE, FALSE	-
p	numeric	2		$(-\infty, \infty)$
k	integer	2		$[1, \infty)$

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustHclust
```

Methods

Public methods:

- [LearnerClustHclust\\$new\(\)](#)
- [LearnerClustHclust\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerClustHclust$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustHclust$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("stats")) {
  learner = mlr3::lrn("clust.hclust")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

```
mlr_learners_clust.kkmeans
```

Kernel K-Means Clustering Learner

Description

A [LearnerClust](#) for kernel k-means clustering implemented in [kernlab::kkmeans\(\)](#). [kernlab::kkmeans\(\)](#) doesn't have a default value for the number of clusters. Therefore, the `centers` parameter here is set to 2 by default. Kernel parameters have to be passed directly and not by using the `kpar` list in `kkmeans`. The `predict` method finds the nearest center in kernel distance to assign clusters for new data points.

Dictionary

This [Learner](#) can be instantiated via the [dictionary mlr_learners](#) or with the associated sugar function [lrn\(\)](#):

```
mlr_learners$get("clust.kkmeans")
lrn("clust.kkmeans")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **kernlab**

Parameters

Id	Type	Default	Levels	Range
centers	untyped	2		-
kernel	character	rbfdot	vanilladot, polydot, rbfdot, tanhdot, laplacedot, besseldot, anovadot, splinedot	-
sigma	numeric	-		$[0, \infty)$
degree	integer	3		$[1, \infty)$
scale	numeric	1		$[0, \infty)$
offset	numeric	1		$(-\infty, \infty)$
order	integer	1		$(-\infty, \infty)$
alg	character	kkmeans	kkmeans, kerninghan	-
p	numeric	1		$(-\infty, \infty)$

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustKKMeans
```

Methods**Public methods:**

- `LearnerClustKKMeans$new()`
- `LearnerClustKKMeans$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustKKMeans$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustKKMeans$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```

if (requireNamespace("kernlab")) {
  learner = mlr3::lrn("clust.kkmeans")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}

```

mlr_learners_clust.kmeans

K-Means Clustering Learner

Description

A [LearnerClust](#) for k-means clustering implemented in `stats::kmeans()`. `stats::kmeans()` doesn't have a default value for the number of clusters. Therefore, the `centers` parameter here is set to 2 by default. The predict method uses `clue::cl_predict()` to compute the cluster memberships for new data.

Dictionary

This [Learner](#) can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```

mlr_learners$get("clust.kmeans")
lrn("clust.kmeans")

```

Meta Information

- Task type: "clust"
- Predict Types: "partition"
- Feature Types: "logical", "integer", "numeric"
- Required Packages: **mlr3**, **mlr3cluster**, 'stats', **clue**

Parameters

Id	Type	Default	Levels	Range
centers	untyped	2		-
iter.max	integer	10		[1, ∞)
algorithm	character	Hartigan-Wong	Hartigan-Wong, Lloyd, Forgy, MacQueen	-
nstart	integer	1		[1, ∞)
trace	integer	0		[0, ∞)

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustKMeans
```

Methods**Public methods:**

- [LearnerClustKMeans\\$new\(\)](#)
- [LearnerClustKMeans\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustKMeans$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustKMeans$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("stats") && requireNamespace("clue")) {
  learner = mlr3::lrn("clust.kmeans")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

```
mlr_learners_clust.MBatchKMeans
```

Mini Batch K-Means Clustering Learner

Description

A [LearnerClust](#) for mini batch k-means clustering implemented in [ClusterR::MiniBatchKmeans\(\)](#). [ClusterR::MiniBatchKmeans\(\)](#) doesn't have a default value for the number of clusters. Therefore, the `clusters` parameter here is set to 2 by default. The `predict` method uses [ClusterR::predict_MBatchKMeans\(\)](#) to compute the cluster memberships for new data. The learner supports both partitional and fuzzy clustering.

Dictionary

This [Learner](#) can be instantiated via the [dictionary mlr_learners](#) or with the associated sugar function [lrn\(\)](#):

```
mlr_learners$get("clust.MBatchKMeans")
lrn("clust.MBatchKMeans")
```

Meta Information

- Task type: "clust"
- Predict Types: "partition", "prob"
- Feature Types: "logical", "integer", "numeric"
- Required Packages: **mlr3**, **mlr3cluster**, **ClusterR**

Parameters

Id	Type	Default	Levels	Range
clusters	integer	2		$[1, \infty)$
batch_size	integer	10		$[1, \infty)$
num_init	integer	1		$[1, \infty)$
max_iters	integer	100		$[1, \infty)$
init_fraction	numeric	1		$[0, 1]$
initializer	character	kmeans++	optimal_init, quantile_init, kmeans++, random	-
early_stop_iter	integer	10		$[1, \infty)$
verbose	logical	FALSE	TRUE, FALSE	-
CENTROIDS	untyped			-
tol	numeric	1e-04		$[0, \infty)$
tol_optimal_init	numeric	0.3		$[0, \infty)$
seed	integer	1		$(-\infty, \infty)$

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustMiniBatchKMeans
```

Methods**Public methods:**

- [LearnerClustMiniBatchKMeans\\$new\(\)](#)
- [LearnerClustMiniBatchKMeans\\$clone\(\)](#)

Method [new\(\)](#): Creates a new instance of this [R6](#) class.

Usage:

```
LearnerClustMiniBatchKMeans$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustMiniBatchKMeans$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("ClusterR")) {
  learner = mlr3::lrn("clust.MBatchKMeans")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.mclust

Gaussian Mixture Models-Based Clustering Learner

Description

A [LearnerClust](#) for model-based clustering implemented in `mclust::Mclust()`. The predict method uses `mclust::predict.Mclust()` to compute the cluster memberships for new data.

Dictionary

This [Learner](#) can be instantiated via the [dictionary mlr_learners](#) or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.mclust")
lrn("clust.mclust")
```

Meta Information

- Task type: "clust"
- Predict Types: "partition", "prob"
- Feature Types: "logical", "integer", "numeric"
- Required Packages: **mlr3**, **mlr3cluster**, **mclust**

Parameters

Id	Type	Default
G	untyped	c , 1:9
modelNames	untyped	-
prior	untyped	-
control	untyped	mclust::emControl
initialization	untyped	-
x	untyped	-

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustMclust
```

Methods**Public methods:**

- [LearnerClustMclust\\$new\(\)](#)
- [LearnerClustMclust\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
LearnerClustMclust$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustMclust$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("mclust")) {
  learner = mlr3::lrn("clust.mclust")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

```
mlr_learners_clust.meanshift
      Mean Shift Clustering Learner
```

Description

A [LearnerClust](#) for Mean Shift clustering implemented in [LPCM: :ms\(\)](#). There is no predict method for [LPCM: :ms\(\)](#), so the method returns cluster labels for the 'training' data.

Dictionary

This [Learner](#) can be instantiated via the [dictionary mlr_learners](#) or with the associated sugar function [lrn\(\)](#):

```
mlr_learners$get("clust.meanshift")
lrn("clust.meanshift")
```

Meta Information

- Task type: "clust"
- Predict Types: "partition"
- Feature Types: "logical", "integer", "numeric"
- Required Packages: **mlr3**, **mlr3cluster**, **LPCM**

Parameters

Id	Type	Default	Range
h	untyped	-	-
subset	untyped	-	-
scaled	integer	1	$[0, \infty)$
iter	integer	200	$[1, \infty)$
thr	numeric	0.01	$(-\infty, \infty)$

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustMeanShift
```

Methods

Public methods:

- [LearnerClustMeanShift\\$new\(\)](#)
- [LearnerClustMeanShift\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustMeanShift$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustMeanShift$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("LPCM")) {
  learner = mlr3::lrn("clust.meanshift")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.pam

Partitioning Around Medoids Clustering Learner

Description

A `LearnerClust` for PAM clustering implemented in `cluster::pam()`. `cluster::pam()` doesn't have a default value for the number of clusters. Therefore, the `k` parameter which corresponds to the number of clusters here is set to 2 by default. The predict method uses `clue::cl_predict()` to compute the cluster memberships for new data.

Dictionary

This `Learner` can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.pam")
lrn("clust.pam")
```

Meta Information

- Task type: "clust"
- Predict Types: "partition"
- Feature Types: "logical", "integer", "numeric"
- Required Packages: **mlr3**, **mlr3cluster**, **cluster**

Parameters

Id	Type	Default	Levels	Range
k	integer	2		$[1, \infty)$
metric	character	-	euclidian, manhattan	-
medoids	untyped			-
stand	logical	FALSE	TRUE, FALSE	-
do.swap	logical	TRUE	TRUE, FALSE	-
pamonce	integer	0		$[0, 5]$
trace.lev	integer	0		$[0, \infty)$

Super classes

```
mlr3::Learner -> mlr3cluster::LearnerClust -> LearnerClustPAM
```

Methods

Public methods:

- `LearnerClustPAM$new()`
- `LearnerClustPAM$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustPAM$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustPAM$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("cluster")) {
  learner = mlr3::lrn("clust.pam")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_learners_clust.SimpleKMeans

K-Means Clustering Learner from Weka

Description

A [LearnerClust](#) for Simple K Means clustering implemented in [RWeka::SimpleKMeans\(\)](#). The predict method uses [RWeka::predict.Weka_clusterer\(\)](#) to compute the cluster memberships for new data.

Dictionary

This [Learner](#) can be instantiated via the dictionary [mlr_learners](#) or with the associated sugar function [lrn\(\)](#):

```
mlr_learners$get("clust.SimpleKMeans")
lrn("clust.SimpleKMeans")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **RWeka**

Parameters

Id	Type	Default	Levels	Range
A	untyped	weka.core.EuclideanDistance		-
C	logical	FALSE	TRUE, FALSE	-
fast	logical	FALSE	TRUE, FALSE	-
I	integer	100		$[1, \infty)$
init	integer	0		$[0, 3]$
M	logical	FALSE	TRUE, FALSE	-
max_candidates	integer	100		$[1, \infty)$
min_density	integer	2		$[1, \infty)$
N	integer	2		$[1, \infty)$
num_slots	integer	1		$[1, \infty)$
O	logical	FALSE	TRUE, FALSE	-
periodic_pruning	integer	10000		$[1, \infty)$
S	integer	10		$[0, \infty)$
t2	numeric	-1		$(-\infty, \infty)$
t1	numeric	-1.5		$(-\infty, \infty)$
V	logical	FALSE	TRUE, FALSE	-
output_debug_info	logical	FALSE	TRUE, FALSE	-

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustSimpleKMeans`

Methods**Public methods:**

- `LearnerClustSimpleKMeans$new()`
- `LearnerClustSimpleKMeans$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustSimpleKMeans$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustSimpleKMeans$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
if (requireNamespace("RWeka")) {
  learner = mlr3::lrn("clust.SimpleKMeans")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

`mlr_learners_clust.xmeans`

X-means Clustering Learner

Description

A `LearnerClust` for X-means clustering implemented in `RWeka::XMeans()`. The predict method uses `RWeka::predict.Weka_clusterer()` to compute the cluster memberships for new data.

Dictionary

This `Learner` can be instantiated via the dictionary `mlr_learners` or with the associated sugar function `lrn()`:

```
mlr_learners$get("clust.xmeans")
lrn("clust.xmeans")
```

Meta Information

- Task type: “clust”
- Predict Types: “partition”
- Feature Types: “logical”, “integer”, “numeric”
- Required Packages: **mlr3**, **mlr3cluster**, **RWeka**

Parameters

Id	Type	Default	Levels	Range
B	numeric	1		[0, ∞)
C	numeric	0		[0, ∞)
D	untyped	weka.core.EuclideanDistance		-
H	integer	4		[1, ∞)
I	integer	1		[1, ∞)
J	integer	1000		[1, ∞)
K	untyped			-
L	integer	2		[1, ∞)
M	integer	1000		[1, ∞)
S	integer	10		[1, ∞)
U	integer	0		[0, ∞)
use_kdtree	logical	FALSE	TRUE, FALSE	-
N	untyped	-		-
O	untyped	-		-
Y	untyped	-		-
output_debug_info	logical	FALSE	TRUE, FALSE	-

Super classes

`mlr3::Learner` -> `mlr3cluster::LearnerClust` -> `LearnerClustXMeans`

Methods**Public methods:**

- `LearnerClustXMeans$new()`
- `LearnerClustXMeans$clone()`

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
LearnerClustXMeans$new()
```

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
LearnerClustXMeans$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Examples

```
if (requireNamespace("RWeka")) {
  learner = mlr3::lrn("clust.xmeans")
  print(learner)

  # available parameters:
  learner$param_set$ids()
}
```

mlr_measures_clust.ch *Calinski Harabasz Pseudo F-Statistic*

Description

The score function calls `clusterCrit::intCriteria()` from package **clusterCrit**. Argument `crit` is set to "Calinski_Harabasz".

The score function calls `clusterCrit::intCriteria()` from package **clusterCrit**. Argument `crit` is set to "Calinski_Harabasz".

Format

`R6::R6Class()` inheriting from `MeasureClust`.

`R6::R6Class()` inheriting from `MeasureClust`.

Construction

This measures can be retrieved from the dictionary `mlr_measures`:

```
mlr_measures$get("clust.ch")
msr("clust.ch")
```

This measures can be retrieved from the dictionary `mlr_measures`:

```
mlr_measures$get("clust.ch")
msr("clust.ch")
```

Meta Information

- Range: $[0, \infty)$
- Minimize: FALSE
- Required predict type: partition
- Range: $[0, \infty)$
- Minimize: FALSE
- Required predict type: partition

See Also

Dictionary of Measures: [mlr3::mlr_measures](#)

`as.data.table(mlr_measures)` for a complete table of all (also dynamically created) [mlr3::Measure](#) implementations.

Dictionary of Measures: [mlr3::mlr_measures](#)

`as.data.table(mlr_measures)` for a complete table of all (also dynamically created) [mlr3::Measure](#) implementations.

Other cluster measures: [mlr_measures_clust.db](#), [mlr_measures_clust.dunn](#), [mlr_measures_clust.silhouette](#), [mlr_measures_clust.wss](#)

Other cluster measures: [mlr_measures_clust.db](#), [mlr_measures_clust.dunn](#), [mlr_measures_clust.silhouette](#), [mlr_measures_clust.wss](#)

`mlr_measures_clust.db` *Davies-Bouldin Cluster Separation Measure*

Description

The score function calls `clusterCrit::intCriteria()` from package **clusterCrit**. Argument `crit` is set to "Davies_Bouldin".

Format

`R6::R6Class()` inheriting from [MeasureClust](#).

Construction

This measures can be retrieved from the dictionary [mlr_measures](#):

```
mlr_measures$get("clust.db")
msr("clust.db")
```

Meta Information

- Range: $[0, \infty)$
- Minimize: TRUE
- Required predict type: partition

See Also

Dictionary of Measures: [mlr3::mlr_measures](#)

`as.data.table(mlr_measures)` for a complete table of all (also dynamically created) [mlr3::Measure](#) implementations.

Other cluster measures: [mlr_measures_clust.ch](#), [mlr_measures_clust.dunn](#), [mlr_measures_clust.silhouette](#), [mlr_measures_clust.wss](#)

`mlr_measures_clust.dunn`*Dunn Index*

Description

The score function calls `clusterCrit::intCriteria()` from package **clusterCrit**. Argument `crit` is set to "Dunn".

Format

`R6::R6Class()` inheriting from `MeasureClust`.

Construction

This measures can be retrieved from the dictionary `mlr_measures`:

```
mlr_measures$get("clust.dunn")
msr("clust.dunn")
```

Meta Information

- Range: $[0, \infty)$
- Minimize: FALSE
- Required predict type: partition

See Also

Dictionary of Measures: `mlr3::mlr_measures`

`as.data.table(mlr_measures)` for a complete table of all (also dynamically created) `mlr3::Measure` implementations.

Other cluster measures: `mlr_measures_clust.ch`, `mlr_measures_clust.db`, `mlr_measures_clust.silhouette`, `mlr_measures_clust.wss`

`mlr_measures_clust.silhouette`*Rousseeuw's Silhouette Quality Index*

Description

The score function calls `clusterCrit::intCriteria()` from package **clusterCrit**. Argument `crit` is set to "Silhouette".

Format

[R6::R6Class\(\)](#) inheriting from [MeasureClust](#).

Construction

This measures can be retrieved from the dictionary [mlr_measures](#):

```
mlr_measures$get("clust.silhouette")
msr("clust.silhouette")
```

Meta Information

- Range: $[0, \infty)$
- Minimize: FALSE
- Required predict type: partition

See Also

Dictionary of Measures: [mlr3::mlr_measures](#)

`as.data.table(mlr_measures)` for a complete table of all (also dynamically created) [mlr3::Measure](#) implementations.

Other cluster measures: [mlr_measures_clust.ch](#), [mlr_measures_clust.db](#), [mlr_measures_clust.dunn](#), [mlr_measures_clust.wss](#)

`mlr_measures_clust.wss`

Within Sum of Squares

Description

The score function calls `clusterCrit::intCriteria()` from package **clusterCrit**. Argument `crit` is set to "Trace_W".

Format

[R6::R6Class\(\)](#) inheriting from [MeasureClust](#).

Construction

This measures can be retrieved from the dictionary [mlr_measures](#):

```
mlr_measures$get("clust.wss")
msr("clust.wss")
```

Meta Information

- Range: $[0, \infty)$
- Minimize: TRUE
- Required predict type: partition

See Also

Dictionary of Measures: [mlr3::mlr_measures](#)

`as.data.table(mlr_measures)` for a complete table of all (also dynamically created) [mlr3::Measure](#) implementations.

Other cluster measures: [mlr_measures_clust.ch](#), [mlr_measures_clust.db](#), [mlr_measures_clust.dunn](#), [mlr_measures_clust.silhouette](#)

`mlr_tasks_usarrests` *US Arrests Cluster Task*

Description

A cluster task for the [datasets::USArrests](#) data set. Rownames are stored as variable "states" with column role "name".

Format

[R6::R6Class](#) inheriting from [TaskClust](#).

Construction

```
mlr_tasks$get("usarrests")
tsk("usarrests")
```

`PredictionClust` *Prediction Object for Cluster Analysis*

Description

This object wraps the predictions returned by a learner of class [LearnerClust](#), i.e. the predicted partition and cluster probability.

Super class

[mlr3::Prediction](#) -> `PredictionClust`

Active bindings

`partition (integer())`
Access the stored partition.

`prob (matrix())`
Access to the stored probabilities.

Methods**Public methods:**

- [PredictionClust\\$new\(\)](#)
- [PredictionClust\\$clone\(\)](#)

Method `new()`: Creates a new instance of this [R6](#) class.

Usage:

```
PredictionClust$new(
  task = NULL,
  row_ids = task$row_ids,
  partition = NULL,
  prob = NULL,
  check = TRUE
)
```

Arguments:

`task` ([TaskClust](#))

Task, used to extract defaults for `row_ids`.

`row_ids` (`integer()`)

Row ids of the predicted observations, i.e. the row ids of the test set.

`partition` (`integer()`)

Vector of cluster partitions.

`prob` (`matrix()`)

Numeric matrix of cluster membership probabilities with one column for each cluster and one row for each observation. Columns must be named with cluster numbers, row names are automatically removed. If `prob` is provided, but `partition` is not, the cluster memberships are calculated from the probabilities using `max.col()` with `ties.method` set to "first".

`check` (`logical(1)`)

If TRUE, performs some argument checks and predict type conversions.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
PredictionClust$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3)
library(mlr3cluster)
task = tsk("usarrests")
learner = lrn("clust.kmeans")
p = learner$train(task)$predict(task)
p$predict_types
head(as.data.table(p))
```

TaskClust

*Cluster Task***Description**

This task specializes [mlr3::Task](#) for cluster problems. As an unsupervised task, this task has no target column. The `task_type` is set to "clust".

Predefined tasks are stored in the [dictionary mlr_tasks](#).

Super classes

```
mlr3::Task -> mlr3::TaskUnsupervised -> TaskClust
```

Methods**Public methods:**

- [TaskClust\\$new\(\)](#)
- [TaskClust\\$clone\(\)](#)

Method `new()`: Creates a new instance of this R6 class.

Usage:

```
TaskClust$new(id, backend, label = NA_character_)
```

Arguments:

`id` (`character(1)`)

Identifier for the new instance.

`backend` ([DataBackend](#))

Either a [DataBackend](#), or any object which is convertible to a [DataBackend](#) with `as_data_backend()`.

E.g., a `data.frame()` will be converted to a [DataBackendDataTable](#).

`label` (`character(1)`)

Label for the new instance.

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
TaskClust$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Examples

```
library(mlr3)
library(mlr3cluster)
task = TaskClust$new("usarrests", backend = USArrests)
task$task_type

# possible properties:
mlr_reflections$task_properties$clust
```

Index

- * **Prediction**
 - PredictionClust, 43
- * **Task**
 - TaskClust, 45
- * **cluster measures**
 - mlr_measures_clust.ch, 39
 - mlr_measures_clust.db, 40
 - mlr_measures_clust.dunn, 41
 - mlr_measures_clust.silhouette, 41
 - mlr_measures_clust.wss, 42

- apcluster::apcluster(), 10
- as_prediction_clust, 3
- as_task_clust, 4

- clue::cl_predict(), 12, 28, 34
- clust.dunn, 9
- cluster::agnes(), 9
- cluster::diana(), 16
- cluster::fanny(), 20
- cluster::pam(), 34
- clusterCrit::intCriteria(), 39–42
- ClusterR::MiniBatchKmeans(), 29
- ClusterR::predict_MBatchKMeans(), 29

- data.frame(), 4
- DataBackend, 4, 45
- DataBackendDataTable, 45
- datasets::USArrests, 43
- dbscan::dbscan(), 15
- dbscan::predict.dbscan_fast(), 15
- Dictionary, 40–43
- dictionary, 9, 10, 12, 13, 15, 16, 19, 20, 22, 23, 25, 26, 28, 30, 31, 33, 34, 36, 37, 45

- e1071::cmeans(), 12

- kernlab::kkmeans(), 26

- Learner, 6–10, 12, 13, 15, 16, 19, 20, 22, 23, 25, 26, 28, 30, 31, 33, 34, 36, 37
- LearnerClust, 5, 9, 10, 12, 13, 15, 16, 19, 20, 22, 23, 25, 26, 28, 29, 31, 33, 34, 36, 37, 43
- LearnerClustAgnes
 - (mlr_learners_clust.agnes), 9
- LearnerClustAP (mlr_learners_clust.ap), 10
- LearnerClustCMeans
 - (mlr_learners_clust.cmeans), 12
- LearnerClustCobweb
 - (mlr_learners_clust.cobweb), 13
- LearnerClustDBSCAN
 - (mlr_learners_clust.dbscan), 15
- LearnerClustDiana
 - (mlr_learners_clust.diana), 16
- LearnerClustEM (mlr_learners_clust.em), 19
- LearnerClustFanny
 - (mlr_learners_clust.fanny), 20
- LearnerClustFarthestFirst
 - (mlr_learners_clust.ff), 23
- LearnerClustFeatureless
 - (mlr_learners_clust.featureless), 22
- LearnerClustHclust
 - (mlr_learners_clust.hclust), 25
- LearnerClustKKMeans
 - (mlr_learners_clust.kkmeans), 26
- LearnerClustKMeans
 - (mlr_learners_clust.kmeans), 28
- LearnerClustMclust
 - (mlr_learners_clust.mclust), 31
- LearnerClustMeanShift
 - (mlr_learners_clust.meanshift), 33
- LearnerClustMiniBatchKMeans

- (mlr_learners_clust.MBatchKMeans), 29
- LearnerClustPAM
 - (mlr_learners_clust.pam), 34
- LearnerClustSimpleKMeans
 - (mlr_learners_clust.SimpleKMeans), 36
- LearnerClustXMeans
 - (mlr_learners_clust.xmeans), 37
- LPCM::ms(), 33
- lrn(), 9, 10, 12, 13, 15, 16, 19, 20, 22, 23, 25, 26, 28, 30, 31, 33, 34, 36, 37

- max.col(), 44
- mclust::Mclust(), 31
- mclust::predict.Mclust(), 31
- mean(), 8
- MeasureClust, 7, 39–42
- Measures, 40–43
- mlr3::Learner, 5, 10, 11, 13–15, 18, 20–22, 24, 25, 27, 29, 30, 32, 33, 35, 37, 38
- mlr3::Measure, 7, 40–43
- mlr3::mlr_learners, 5
- mlr3::mlr_measures, 7, 40–43
- mlr3::Prediction, 43
- mlr3::Task, 45
- mlr3::TaskUnsupervised, 45
- mlr3cluster (mlr3cluster-package), 3
- mlr3cluster-package, 3
- mlr3cluster::LearnerClust, 10, 11, 13–15, 18, 20–22, 24, 25, 27, 29, 30, 32, 33, 35, 37, 38
- mlr3misc::Dictionary, 5, 7
- mlr_learners, 9, 10, 12, 13, 15, 16, 19, 20, 22, 23, 25, 26, 28, 30, 31, 33, 34, 36, 37
- mlr_learners_clust.agnes, 9
- mlr_learners_clust.ap, 10
- mlr_learners_clust.cmeans, 12
- mlr_learners_clust.cobweb, 13
- mlr_learners_clust.dbscan, 15
- mlr_learners_clust.diana, 16
- mlr_learners_clust.em, 19
- mlr_learners_clust.fanny, 20
- mlr_learners_clust.featureless, 22
- mlr_learners_clust.ff, 23
- mlr_learners_clust.hclust, 25
- mlr_learners_clust.kkmeans, 26
- mlr_learners_clust.kmeans, 28
- mlr_learners_clust.MBatchKMeans, 29
- mlr_learners_clust.mclust, 31
- mlr_learners_clust.meanshift, 33
- mlr_learners_clust.pam, 34
- mlr_learners_clust.SimpleKMeans, 36
- mlr_learners_clust.xmeans, 37
- mlr_measures, 39–42
- mlr_measures_clust.ch, 39, 40–43
- mlr_measures_clust.db, 40, 40, 41–43
- mlr_measures_clust.dunn, 40, 41, 42, 43
- mlr_measures_clust.silhouette, 40, 41, 41, 43
- mlr_measures_clust.wss, 40–42, 42
- mlr_reflections\$learner_predict_types, 6, 8
- mlr_reflections\$learner_properties, 6
- mlr_reflections\$measure_properties, 8
- mlr_reflections\$task_feature_types, 6
- mlr_tasks, 45
- mlr_tasks_usarrests, 43

- paradox::ParamSet, 6
- Prediction, 5
- PredictionClust, 3–5, 43

- R6, 6, 8, 10, 11, 13, 14, 16, 18, 20, 21, 23, 24, 26, 27, 29, 30, 32, 34, 35, 37, 38, 44, 45
- R6::R6Class, 43
- R6::R6Class(), 39–42
- requireNamespace(), 7, 8
- Resampling, 8
- RWeka::Cobweb(), 13
- RWeka::FarthestFirst(), 23
- RWeka::list_Weka_interfaces(), 19
- RWeka::predict.Weka_clusterer(), 13, 19, 23, 36, 37
- RWeka::SimpleKMeans(), 36
- RWeka::XMeans(), 37

- stats::cutree(), 9, 16
- stats::dist(), 25
- stats::hclust(), 25
- stats::kmeans(), 28

- Task, 8
- TaskClust, 4, 5, 43, 44, 45