

Package ‘mutossGUI’

October 13, 2022

Version 0.1-11

Title A Graphical User Interface for the MuToss Project

Author MuToss Coding Team (Berlin 2010), Gilles Blanchard, Thorsten Dickhaus,
Niklas Hack, Frank Konietzschke, Kornelius Rohmeyer,
Jonathan Rosenblatt, Marsel Scheer, Wiebke Werft

Maintainer Kornelius Rohmeyer <rohmeier@small-projects.de>

Description The mutossGUI package provides a graphical user interface for the MuToss Project.

Depends R (>= 2.8.0), mutoss (>= 0.1-6), multcomp, plotrix

Imports rJava (>= 0.8-0), JavaGD (>= 0.5-2), CommonJavaJars (>= 1.0.5), JGR

SystemRequirements Java (>= 5.0)

License GPL

URL <http://mutoss.r-forge.r-project.org/>

NeedsCompilation no

Repository CRAN

Date/Publication 2017-12-04 10:16:54 UTC

R topics documented:

mutossGUI	2
reportBug	3
Index	4

`mutossGUI`*Function to start the MuTossGUI Java class*

Description

Starts the graphical user interface for the MuToss system.

Usage

```
mutossGUI(debugOutput=FALSE)
```

Arguments

`debugOutput` If FALSE (the default) the verbose output for debugging will only be written to the file `mutoss.log` in the java temporary directory (`System.getProperty("java.io.tmpdir")`). If set to TRUE the output is also printed to the R Console. Note that the behavior can only be influenced the first time the GUI is called in an R session. After that this parameter is ignored.

Details

This function executes the method `startGUI()` of the Java class `MuTossGUI` defined in the JAR file `inst/java/mutossgui.jar` inside the R package. Further details are given in the package vignette.

Value

None (invisible NULL).

Author(s)

Kornelius Rohmeyer <rohmeier@small-projects.de>

Examples

```
## Not run:  
mutossGUI()  
  
## End(Not run)
```

`reportBug`*Function to Report Bugs in MuTossGUI*

Description

This function opens a graphical user interface for reporting bugs with the mutoss Java GUI.

Usage

```
reportBug()
```

Details

This function collects all necessary information for debugging from the current session. The information that is sent can be reviewed before sending.

Value

None (invisible NULL).

Author(s)

Kornelius Rohmeyer <rohrmeyer@small-projects.de>

Examples

```
## Not run:  
reportBug()  
  
## End(Not run)
```

Index

* **manip**

mutossGUI, [2](#)

reportBug, [3](#)

mutossGUI, [2](#)

reportBug, [3](#)