

# Package ‘mvnormtest’

October 13, 2022

**Version** 0.1-9

**Date** 2012-04-04

**Title** Normality test for multivariate variables

**Author** Slawomir Jarek

**Maintainer** Slawomir Jarek <slawomir.jarek@gallus.edu.pl>

**Description** Generalization of shapiro-wilk test for multivariate variables.

**License** GPL

**Depends** stats

**Repository** CRAN

**Date/Publication** 2012-04-12 11:49:53

**NeedsCompilation** no

## R topics documented:

mshapiro.test . . . . .	1
<b>Index</b>	<b>3</b>

---

mshapiro.test	<i>Shapiro-Wilk Multivariate Normality Test</i>
---------------	---

---

### Description

Performs the Shapiro-Wilk test for multivariate normality.

### Usage

```
mshapiro.test(U)
```

**Arguments**

U a numeric matrix of data values, the number of which must be for each sample between 3 and 5000.

**Value**

A list with class "htest" containing the following components:

statistic	the value of the Shapiro-Wilk statistic.
p.value	the p-value for the test.
method	the character string "Shapiro-Wilk normality test".
data.name	a character string giving the name(s) of the data.

**Author(s)**

Slawomir Jarek (<slawomir.jarek@gallus.edu.pl>)

**References**

Czeslaw Domanski (1998) Wlasnosci testu wielowymiarowej normalnosci Shapiro-Wilka i jego zastosowanie. *Cracow University of Economics Rector's Lectures*, **No. 37**.

Patrick Royston (1982) An Extension of Shapiro and Wilk's  $W$  Test for Normality to Large Samples. *Applied Statistics*, **31**, 115–124.

Patrick Royston (1982) Algorithm AS 181: The  $W$  Test for Normality. *Applied Statistics*, **31**, 176–180.

Patrick Royston (1995) A Remark on Algorithm AS 181: The  $W$  Test for Normality. *Applied Statistics*, **44**, 547–551.

**See Also**

[shapiro.test](#) for univariate samples, [qqnorm](#) for producing a normal quantile-quantile plot.

**Examples**

```
library(mvnormtest)
data(EuStockMarkets)

C <- t(EuStockMarkets[15:29,1:4])
mshapiro.test(C)

C <- t(EuStockMarkets[14:29,1:4])
mshapiro.test(C)

R <- t(diff(t(log(C))))
mshapiro.test(R)

dR <- t(diff(t(R)))
mshapiro.test(dR)
```

# Index

\* **htest**

    mshapiro.test, 1

mshapiro.test, 1

qqnorm, 2

shapiro.test, 2