

Package ‘paws.common’

January 11, 2023

Type Package

Title Paws Low-Level Amazon Web Services API

Version 0.5.4

Description Functions for making low-level API requests to Amazon Web Services <<https://aws.amazon.com>>. The functions handle building, signing, and sending requests, and receiving responses. They are designed to help build higher-level interfaces to individual services, such as Simple Storage Service (S3).

License Apache License (>= 2.0)

Encoding UTF-8

LinkingTo Rcpp

Imports base64enc, curl, digest, httr, jsonlite, methods, utils, Rcpp, xml2

Suggests covr, crayon, mockery, rstudioapi, testthat

SystemRequirements pandoc (>= 1.12.3) - <http://pandoc.org>

RoxygenNote 7.2.3

Collate 'RcppExports.R' 'struct.R' 'handlers.R' 'iniutil.R' 'dateutil.R' 'credential_sso.R' 'credential_sts.R' 'url.R' 'net.R' 'credential_providers.R' 'credentials.R' 'client.R' 'config.R' 'convert.R' 'service.R' 'custom_dynamodb.R' 'custom_rds.R' 'util.R' 'xmlutil.R' 'stream.R' 'custom_s3.R' 'error.R' 'handlers_core.R' 'handlers_ec2query.R' 'handlers_jsonrpc.R' 'handlers_query.R' 'handlers_rest.R' 'handlers_restjson.R' 'handlers_restxml.R' 'idempotency.R' 'jsonutil.R' 'logging.R' 'onLoad.R' 'populate.R' 'populateutil.R' 'tags.R' 'queryutil.R' 'request.R' 'signer_v4.R' 'signer_query.R' 'signer_s3.R' 'signer_s3v4.R' 'signer_v2.R' 'time.R'

NeedsCompilation yes

Author David Kretch [aut],
Adam Banker [aut],
Dyfan Jones [cre],
Amazon.com, Inc. [cph]

Maintainer Dyfan Jones <dyfan.r.jones@gmail.com>

Repository CRAN

Date/Publication 2023-01-11 15:30:02 UTC

R topics documented:

get_config	2
is_empty	3
is_empty_xml	3
new_handlers	4
new_operation	5
new_request	6
new_service	7
paws_config_log	8
populate	9
send_request	10
set_config	10
tags	11

Index	13
--------------	-----------

get_config	<i>Get the service configuration from the service object.</i>
------------	---

Description

Look up the service configuration from the service object, e.g. when calling `svc$operation()`, `get_config()` will look up `svc`, then get any configuration stored in it, as if the operation function were a method and the service object were a class instance.

Usage

```
get_config()
```

Details

`get_config` must be called directly by the operation function and assigned immediately, not provided as an argument to another function.

We look up the service object then fetch its data so we can both support documentation tooltips in RStudio and also have class-object-like behavior. Alternatives that do not support documentation tooltips in RStudio include reference classes (RC), R6 classes, and any modification of the functions at run-time, e.g. inserting the configuration into the function definition for each operation in a particular service object.

is_empty	<i>Check whether an object is empty</i>
----------	---

Description

Check whether an object is empty, e.g. has no sub-elements, is NA, or is the empty string.

Usage

```
is_empty(x)
```

Arguments

x	An object.
---	------------

Examples

```
is_empty(NA) # TRUE
is_empty("") # TRUE
is_empty(list()) # TRUE
is_empty(list(list())) # TRUE

is_empty(1) # FALSE
is_empty(list(1)) # FALSE
is_empty(list(list(1))) # FALSE
```

is_empty_xml	<i>Check whether an object is empty for xml builds</i>
--------------	--

Description

Check whether an object is empty, e.g. has no sub-elements, is NA

Usage

```
is_empty_xml(x)
```

Arguments

x	An object.
---	------------

Examples

```
is_empty_xml(NA) # TRUE
is_empty_xml(list()) # TRUE
is_empty_xml(list(list())) # TRUE

is_empty_xml(1) # FALSE
is_empty_xml("") # FALSE
is_empty_xml(list(1)) # FALSE
is_empty_xml(list(list(1))) # FALSE
```

new_handlers	<i>Return request handlers for a service</i>
--------------	--

Description

Return request handlers for a given protocol and request signer.

Usage

```
new_handlers(protocol, signer)
```

Arguments

protocol	Protocol: ec2query, jsonrpc, query, rest, restjson, or restxml.
signer	Signer: v2 or v4.

See Also

Other API request functions: [new_operation\(\)](#), [new_request\(\)](#), [new_service\(\)](#), [send_request\(\)](#)

Examples

```
# Get the handlers needed for an API using REST-JSON and AWS signature V4.
handlers <- new_handlers("restjson", "v4")
```

new_operation	<i>Return an API operation object</i>
---------------	---------------------------------------

Description

Return an API operation object, with information on what to request for a given API operation. For example, the S3 service's "list buckets" operation is named `ListBuckets`, it requires a GET request, and so on.

Usage

```
new_operation(  
  name,  
  http_method,  
  http_path,  
  paginator,  
  before_presign_fn = NULL  
)
```

Arguments

<code>name</code>	The API operation name.
<code>http_method</code>	The HTTP method, e.g. "GET" or "POST".
<code>http_path</code>	The HTTP path.
<code>paginator</code>	Currently unused.
<code>before_presign_fn</code>	Currently unused.

See Also

Other API request functions: [new_handlers\(\)](#), [new_request\(\)](#), [new_service\(\)](#), [send_request\(\)](#)

Examples

```
# Save info about the S3 ListBuckets API operation.  
op <- new_operation(  
  name = "ListBuckets",  
  http_method = "GET",  
  http_path = "/",  
  paginator = list()  
)
```

new_request	<i>Return an API request object</i>
-------------	-------------------------------------

Description

Return an API request object with everything needed to make a request.

Usage

```
new_request(client, operation, params, data, dest = NULL)
```

Arguments

client	A service client, e.g. from <code>new_service</code> .
operation	An operation, e.g. from <code>new_operation</code> .
params	A populated input object.
data	An empty output object.
dest	Control where the response body is written

See Also

Other API request functions: [new_handlers\(\)](#), [new_operation\(\)](#), [new_service\(\)](#), [send_request\(\)](#)

Examples

```
## Not run:
# Make a request object for the S3 ListBuckets operation.
metadata <- list(
  endpoints = list("*" = list(endpoint = "s3.{region}.amazonaws.com", global = FALSE)),
  service_name = "s3"
)
client <- new_service(metadata, new_handlers("restxml", "s3"))
op <- new_operation("ListBuckets", "GET", "/", list())
params <- list()
data <- tag_add(list(Buckets = list()), list(type = "structure"))
req <- new_request(client, op, params, data)

## End(Not run)
```

new_service	<i>Return an AWS API service object</i>
-------------	---

Description

Return an API service object with information and handlers needed to make API requests.

Usage

```
new_service(metadata, handlers, cfgs = NULL)
```

Arguments

metadata A named list of API metadata. It should look like:

```
list(
  service_name = "string",
  endpoints = list("region" = list(endpoint = "endpoint", global = FALSE)),
  service_id = "string",
  api_version = "string",
  signing_name = "string"|NULL,
  json_version = "string",
  target_prefix = "string"
)
```

handlers A set of handlers, e.g. from new_handlers.

cfgs A config defined by the service. Defaults to null.

Region and credentials

new_service requires that you've set your AWS region in one of:

1. AWS_REGION R environment variable
2. AWS_REGION OS environment variable (Linux and macOS)
3. ~/.aws/config AWS configuration file

new_service also requires that you've set your AWS credentials in one of:

1. AWS_ACCESS_KEY_ID and AWS_SECRET_ACCESS_KEY R environment variables
2. AWS_ACCESS_KEY_ID and AWS_SECRET_ACCESS_KEY OS environment variables (Linux and macOS)
3. ~/.aws/credentials AWS credentials file
4. IAM role

See Also

Other API request functions: [new_handlers\(\)](#), [new_operation\(\)](#), [new_request\(\)](#), [send_request\(\)](#)

Examples

```
## Not run:
# Metadata for the S3 API.
metadata <- list(
  service_name = "s3",
  endpoints = list("us-east-1" = list(endpoint = "s3.amazonaws.com", global = FALSE)),
  service_id = "S3",
  api_version = "2006-03-01",
  signing_name = NULL,
  json_version = "",
  target_prefix = ""
)

# Handlers for S3.
handlers <- new_handlers("restxml", "v4")

# Build a service object for S3, containing the information necessary to
# build, send, and receive requests.
service <- new_service(metadata, handlers)

## End(Not run)
```

paws_config_log

paws logging system

Description

Ability to configure paws logging system, through the use of paws helper function ``paws_config_log`` or R:base options function. Users are able to change logging levels without calling `paws.common` by the use of options e.g. `options("paws.log_level" = 2L)`.

- `paws.log_level` integer: The minimum log level that should be tracked
- `paws.log_file` character: path for logs to populate, default output logs to console.
- `paws.log_timestamp_fmt` character: see [format.POSIXct\(\)](#)

Usage

```
paws_config_log(
  level = 2L,
  file = "",
  timestamp_fmt = "%Y-%m-%d %H:%M:%OS3"
)
```


Arguments

level	integer to determine the level logging threshold. <ul style="list-style-type: none"> • 4L : DEBUG • 3L : INFO • 2L : WARNING • 1L : ERROR
file	character path for logs to populate, default output logs to console.
timestamp_fmt	character for timestamp format, see format.POSIXct() .

Examples

```
# log to a file
temp_file = tempfile()
paws_config_log(file = temp_file)
unlink(temp_file)

# change log threshold to INFO
paws_config_log(level = 3L)

# reset to default config
paws_config_log()
```

populate	<i>Populate a list with data from another list</i>
----------	--

Description

populate copies data from a list (e.g. input by a user) to another list with a similar shape. The second list, called the interface, will generally also contain extra metadata for making API requests, such as names or types.

Usage

```
populate(input, interface)
```

Arguments

input	A list with data to copy.
interface	A list of a similar shape to copy data into.

Examples

```
# Make an interface with metadata, e.g. type.
interface <- tag_add(list(foo = c(), bar = c()), list(type = "structure"))

# Combine data and the metadata from the interface.
populate(list(foo = 1, bar = 2), interface)
```

send_request	<i>Send a request and handle the response</i>
--------------	---

Description

Send a request and handle the response. Build the HTTP request, send it to AWS, interpret the response, and throw an error if the response is not ok.

Usage

```
send_request(request)
```

Arguments

request	A request, e.g. from <code>new_request</code> .
---------	---

See Also

Other API request functions: [new_handlers\(\)](#), [new_operation\(\)](#), [new_request\(\)](#), [new_service\(\)](#)

Examples

```
## Not run:  
# Send a request and handle the response.  
resp <- send_request(req)  
  
## End(Not run)
```

set_config	<i>Add configuration settings to a service object.</i>
------------	--

Description

`set_config` adds a given set of configuration settings in `cfgs` to a service object, i.e. the service object for S3. Configuration settings can include credentials, region, endpoint, etc. These configuration settings will be used whenever an operation is called from that service object.

Usage

```
set_config(svc, cfgs = list())
```

Arguments

svc	A service object containing service operations.
cfgs	A list of optional configuration settings.

Details

`set_config` explicitly makes the `credentials` property mutable, such that when the SDK retrieves credentials later on, it will save them in the service object. This means that credentials don't need to be fetched on each operation, only if and when the saved credentials expire.

The optional configuration settings can include the following:

```
list(
  credentials = list(
    creds = list(
      access_key_id = "string",
      secret_access_key = "string",
      session_token = "string"
    ),
    profile = "string"
  ),
  endpoint = "string",
  region = "string"
)
```

Examples

```
# Create a config object with custom credentials and endpoint.
config <- set_config(
  svc = list(),
  cfigs = list(
    credentials = list(
      creds = list(
        access_key_id = "abc",
        secret_access_key = "123"
      )
    ),
    endpoint = "https://foo.com"
  )
)
```

tags

Get, set, and delete object tags

Description

Tags are metadata stored in an object's attributes, used to store types and names needed to make AWS API requests.

`tag_get` returns the value of the given tag, or "" if the tag doesn't exist.

`tag_has` returns whether the object has the given tag.

`tag_add` returns the object after adding the given list of tags and values.

`tag_del` returns the object after recursively deleting tags in `tags`, or all tags if NULL.

`type` returns broadly what type an object is, based on its type tag.

Usage

```
tag_get(object, tag)

tag_get_all(object)

tag_has(object, tag)

tag_add(object, tags)

tag_del(object, tags = NULL)

type(object)
```

Arguments

object	An object.
tag	A tag name.
tags	A list of tags. <ul style="list-style-type: none">• tag_add: A named vector with tag names and their values.• tag_del: A character vector of tags to delete.

Examples

```
foo <- list()
foo <- tag_add(foo, list(tag_name = "tag_value"))
tag_has(foo, "tag_name") # TRUE
tag_get(foo, "tag_name") # "tag_value"
tag_get(foo, "not_exist") # ""
foo <- tag_del(foo)
tag_has(foo, "tag_name") # FALSE
```

Index

* API request functions

- `new_handlers`, 4
- `new_operation`, 5
- `new_request`, 6
- `new_service`, 7
- `send_request`, 10

`format.POSIXct()`, 8, 9

`get_config`, 2

`is_empty`, 3

`is_empty_xml`, 3

`new_handlers`, 4, 5–7, 10

`new_operation`, 4, 5, 6, 7, 10

`new_request`, 4, 5, 6, 7, 10

`new_service`, 4–6, 7, 10

`paws_config_log`, 8

`populate`, 9

`send_request`, 4–7, 10

`set_config`, 10

`tag_add(tags)`, 11

`tag_del(tags)`, 11

`tag_get(tags)`, 11

`tag_get_all(tags)`, 11

`tag_has(tags)`, 11

`tags`, 11

`type(tags)`, 11