

# Package ‘pergola’

October 14, 2022

**Type** Package

**Title** Toolbox for Polyploid Genetic Data

**Version** 1.0

**Date** 2016-03-31

**Description** Provides tools for linkage mapping in polyploids.  
It implements the method PERGOLA, which is a fast, deterministic method to calculate the order of markers in a linkage group.

**License** GPL-3

**Imports** seriation, utils, stats

**LazyData** true

**Suggests** knitr, gclus, dendextend, dendextendRcpp, Matrix, rmarkdown,  
grDevices

**VignetteBuilder** knitr

**RoxygenNote** 5.0.1

**URL** <http://github.com/grafab/pergola>

**BugReports** <http://github.com/grafab/pergola/issues>

**NeedsCompilation** no

**Author** Fabian Grandke [aut, cre],  
Dirk Metzler [ths]

**Maintainer** Fabian Grandke <grafabian@gmail.com>

**Repository** CRAN

**Date/Publication** 2016-04-03 16:29:32

## R topics documented:

add_offset . . . . .	2
bases2genotypes . . . . .	3
calcRec . . . . .	3
calcSarf . . . . .	4

maketangle . . . . .	5
map2dend . . . . .	6
pergola . . . . .	6
plotChr . . . . .	7
plotRf . . . . .	7
pullMap . . . . .	8
shuffleInput . . . . .	9
simHexa . . . . .	10
simTetra . . . . .	10
sortLeafs . . . . .	11
splitChr . . . . .	11
swapChrs . . . . .	12
switchChrs . . . . .	13

<b>Index</b>	<b>14</b>
--------------	-----------

---

add_offset	<i>Add offset</i>
------------	-------------------

---

## Description

Add offset to zero distance markers to allow computation of correlation between maps.

## Usage

```
add_offset(map, offset = 0.1)
```

## Arguments

map	One map. Required.
offset	Numeric value for offset.

## Value

Map object.

## Examples

```
data(simTetra)
simTetrageno <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetrageno, 4)
split <- splitChr(rfMat, nchr = 7)
split <- sortLeafs(rfMat, split)
map <- pullMap(rfMat, split = split)
map <- add_offset(map)
```

---

bases2genotypes	<i>Transform bases into genotypes</i>
-----------------	---------------------------------------

---

**Description**

Preprocess the input data in case bases are provided instead of genotypes

**Usage**

```
bases2genotypes(input, ploidy)
```

**Arguments**

input	Matrix of genotype bases. Rows represent the individual markers. Columns represent samples, dependenden on the ploidy.
ploidy	Ploidy level of the organism. Influences how many columns are collapsed into one.

**Value**

Matrix of genotypes. The number of columns is 1/ploidy of the input.

**Examples**

```
data(simTetra)
bases2genotypes(simTetra, 4)
```

---

calcRec	<i>Recombination frequencies computation</i>
---------	--

---

**Description**

Calculate recombination frequencies for a whole matrix

**Usage**

```
calcRec(input, ploidy, sparse = FALSE, ...)
```

**Arguments**

input	Matrix of genotypes. Rows represent markers. Columns represent samples.
ploidy	Ploidy level of the organism.
sparse	Logical, if the matrix is a sparse matrix or not.
...	arguments are forwarded to pairwRF.

**Value**

Matrix of pairwise recombination frequencies.

**Examples**

```
data(simTetra)
simTetraGen <- bases2genotypes(simTetra, ploidy = 4)
calcRec(simTetraGen, 4)
```

---

calcSarf	<i>Calculates the SARF value of given input.</i>
----------	--

---

**Description**

The sum of adjacent recombination frequency (SARF) is a measure of how well the marker order is. This function calculates it for a given matrix of pairwise recombination frequencies and marker order. The SARF criterion can be extended to a neighborhood  $> 1$ .

**Usage**

```
calcSarf(rf, ord = 1:(ncol(rf)), n = 1)
```

**Arguments**

rf	Matrix of pairwise recombination frequencies.
ord	Vector with marker order.
n	Number of neighbors, which are included in the calculation.

**Value**

Single numeric value, which is the result of the SARF calculation.

**References**

Liu, B.H. 1998, *Statistical genomics: linkage, mapping, and QTL analysis*.

**Examples**

```
data(simTetra)
simTetraGeno <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetraGeno, 4)
split <- splitChr(rfMat, nchr = 7)
split <- sortLeafs(rfMat, split)
calcSarf(rfMat, split$order, n = 1)
calcSarf(rfMat, split$order, n = 2)
calcSarf(rfMat, split$order, n = 3)
```

---

maketangle	<i>Create a gray scale tanglegram</i>
------------	---------------------------------------

---

### Description

Create tanglegram. Removes markers, that are not in both trees. Calculates alternating light and dark shades of grey.

### Usage

```
maketangle(dend1, dend2, cutheight, k = NULL, ncol = k, ...)
```

### Arguments

dend1	First dendrogram. Required.
dend2	Second dendrogram. Required.
cutheight	The height, at which dend1 is cut. Influences number of colors.
k	Number of desired linkage groups.
ncol	Number of desired colors.
...	Other parameters are forwarded to the tanglegram command.

### Value

None. Plotting only.

### Examples

```
data(simTetra)
simTetraGen <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetraGen, 4)
split <- splitChr(rfMat, nchr = 7)
split <- sortLeafs(rfMat, split)
map <- pullMap(rfMat, split = split)
dend <- map2dend(map)
maketangle(dend, dend, cutheight = 500, k = 7, ncol = 7)
```

---

`map2dend`*Transforming a map into a dendrogram*

---

**Description**

Create dendrogram object. The map specific distance are ignored and only the grouping and ordering is maintained. Allows for comparison of whole map with package 'dendextend'

**Usage**

```
map2dend(map, mergeoff = 0L)
```

**Arguments**

<code>map</code>	One map. Required.
<code>mergeoff</code>	Numeric, offset between chromosomes, to avoid equal heights in dendrogram. Equal heights lead to problems in <code>cor_bakers_gamma()</code> .

**Value**

Dendrogram object.

**Examples**

```
data(simTetra)
simTetragero <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetragero, 4)
split <- splitChr(rfMat, nchr = 7)
split <- sortLeafs(rfMat, split)
map <- pullMap(rfMat, split = split)
dend <- map2dend(map)
plot(dend)
```

---

`pergola`*Toolbox for polyploid genetic data*

---

**Description**

This package provides multiple tools to work with polyploid data.

**Details**

Load the dataset `simTetra` and analyse it according to the vignette.

---

plotChr *Plotting one or two linkage maps*

---

**Description**

Visualization of one or two linkage maps. Used as comparison between two different maps (e.g. different parameters or linkage mapping tools).

**Usage**

```
plotChr(map1, map2 = NULL, cex = 1, labels = c("Map 1", "Map 2"), ...)
```

**Arguments**

map1	Numeric vector with marker positions.
map2	Optional second map for comparison.
cex	Font size in the figure.
labels	Labels for the two blocks
...	arguments are forwarded to plot.

**Value**

None. Plotting only.

**Examples**

```
data(simTetra)
simTetraGen <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetraGen, 4)
split <- splitChr(rfMat, nchr = 7)
split <- sortLeafs(rfMat, split)
map <- pullMap(rfMat, split = split)
plotChr(map[[1]])
```

---

plotRf *Plot recombination frequencies*

---

**Description**

Graphical representation of recombination frequencies to support supervised estimation of the numbers of clusters

**Usage**

```
plotRf(rf, plottype = "dendrogram", method = "single", cex.axis = 1, ...)
```

**Arguments**

rf	Matrix of pairwise recombination frequencies.
plottype	Default is "dendrogram". Any other value will plot the recombination frequencies.
method	Default is "single", which is used for the hierarchical clustering.
cex.axis	Size of axis labels in image plot.
...	arguments are forwarded to image.

**Value**

None.

**Examples**

```
data(simTetra)
simTetraGen <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetraGen, 4)
plotRf(rfMat)
```

---

pullMap

*Creates map object*

---

**Description**

Creates map object from matrix of pairwise recombination frequencies.

**Usage**

```
pullMap(rf, split, fun = "haldane", corr = 1)
```

**Arguments**

rf	Matrix of pairwise recombination frequencies.
split	Split object.
fun	Function to space the markers on the map. Default is "haldane". Alternatives are "kosambi", "carter" and "none".
corr	Corrector, if recombinations are overestimated. Allows to multiply all spaces by a fixed factor.

**Value**

Ordered vector of marker locations. Each marker has a name attribute.



## Examples

```
data(simTetra)
simTetragero <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetragero, 4)
split <- splitChr(rfMat, nchr = 7)
split <- sortLeafs(rfMat, split)
pullMap(rfMat, split = split)
```

---

shuffleInput	<i>Randomize marker order and alleles within samples In simulated datasets, the order of markers and alleles within samples is often given. To remove any prior knowledge, that would not be available, the data should be randomized. Thus, the performance of our tool can be validated unbiased.</i>
--------------	---

---

## Description

Randomize marker order and alleles within samples

In simulated datasets, the order of markers and alleles within samples is often given. To remove any prior knowledge, that would not be available, the data should be randomized. Thus, the performance of our tool can be validated unbiased.

## Usage

```
shuffleInput(input, ploidy = 4, ignore = 0)
```

## Arguments

input	Matrix of genotypes. Rows represent markers. Columns represent samples.
ploidy	Ploidy level of the organism. Default is 4.
ignore	In case of unnecessary fronsstanding columns (e.g. parental genotypes or row-names), these can be excluded from the randomization.

## Value

Matrix of the same size as the input matrix. The markers are in a random order and the alleles within the samples are in a random order.

## Examples

```
data(simTetra)
shuffleInput(simTetra, 4)
```

---

simHexa	<i>Hexaploid F2 population</i>
---------	--------------------------------

---

**Description**

100 offspring genotypes from an F2 crossing population. Generated with PedigreeSim (Voorrips et al, 2012).

**Usage**

```
simHexa
```

**Format**

A data frame with 131 rows and 600 variables:

**Source**

<https://github.com/PBR/pedigreeSim>

---

simTetra	<i>Tetraploid F2 population</i>
----------	---------------------------------

---

**Description**

100 offspring genotypes from an F2 crossing population. Generated with PedigreeSim (Voorrips et al, 2012).

**Usage**

```
simTetra
```

**Format**

A data frame with 131 rows and 400 variables:

**Source**

<https://github.com/PBR/pedigreeSim>

---

sortLeafs	<i>Chromosome wise leaf ordering</i>
-----------	--------------------------------------

---

**Description**

Calculates the optimal leaf ordering pairwise for all linkage groups.

**Usage**

```
sortLeafs(rf, df, method = "seriation", maxSarf = NULL)
```

**Arguments**

rf	Matrix of pairwise recombination frequencies.
df	Vector of cluster numbers, created by splitChr(). Zeros indicated filtered markers and will be ignored.
method	Name of method. Default: seriation (uses the optimal leaf ordering algorithm from the seriation package). Alternatives endlink (order.endlink from gclus) and endlink-global (ignores linkage groups).
maxSarf	Maximum number of neighbor to include into SARF extension.

**Value**

Vector of global marker order.

**Examples**

```
data(simTetra)
simTetragero <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetragero, 4)
split <- splitChr(rfMat, nchr = 7)
sortLeafs(rfMat, split)
```

---

splitChr	<i>Split markers into chromosomes</i>
----------	---------------------------------------

---

**Description**

This function splits markers into linkage groups (LG), which ideally represent chromosomes. The split is based on hierarchical clustering with a single linkage distance.

**Usage**

```
splitChr(rf, height = 0.4, nchr = NULL, method = "single",
  filter = FALSE, thresh = 0.05, rm.dup = TRUE)
```

**Arguments**

rf	Matrix of pairwise recombination frequencies.
height	Threshold value for grouping the markers.
nchr	Expected number of chromosomes.
method	Default is "single", which is used for the hierarchical clustering.
filter	Logical, if the result should be filtered or not. Default is FALSE. Creates zeros for the markers below the threshold.
thresh	Threshold for filtering. Default is 0.05, i.e. linkage groups with less than 5% of markers, are filtered out.
rm.dup	Logical, if the duplicated markers should be filtered out. TRUE is highly recommended because the markers have no added value for the linkage map.

**Value**

Vector of cluster relationship. Same length and order as the matrix of recombination frequencies.

**Examples**

```
data(simTetra)
simTetrageno<-bases2genotypes(simTetra, 4)
rfMat<-calcRec(simTetrageno, 4)
splitChr(rfMat, nchr = 7)
```

---

 swapChrs

*Swap chromosomes*


---

**Description**

Finds best matching chromosome for each chromosome and brings them into the same order.

**Usage**

```
swapChrs(map, comp)
```

**Arguments**

map	Map to switch.
comp	Other map for comparison.

**Value**

map

**Examples**

```
data(simTetra)
simTetrageno <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetrageno, 4)
split <- splitChr(rfMat, nchr = 7)
split <- sortLeafs(rfMat, split)
map <- pullMap(rfMat, split = split)
split <- sortLeafs(rfMat, split, method = "endlink")
map2 <- pullMap(rfMat, split = split)
map <- swapChrs(map, map2)
```

---

switchChrs

*Switch Chromosomes*

---

**Description**

Wrapper function to switch chromosomes for the whole map

**Usage**

```
switchChrs(map, comp)
```

**Arguments**

map	Map to switch.
comp	Other map for comparison.

**Value**

map

**Examples**

```
data(simTetra)
simTetrageno <- bases2genotypes(simTetra, 4)
rfMat <- calcRec(simTetrageno, 4)
split <- splitChr(rfMat, nchr = 7)
split <- sortLeafs(rfMat, split)
map <- pullMap(rfMat, split = split)
split <- sortLeafs(rfMat, split, method = "endlink")
map2 <- pullMap(rfMat, split = split)
map <- switchChrs(map, map2)
```

# Index

## \* datasets

simHexa, [10](#)

simTetra, [10](#)

add\_offset, [2](#)

bases2genotypes, [3](#)

calcRec, [3](#)

calcSarf, [4](#)

maketangle, [5](#)

map2dend, [6](#)

pergola, [6](#)

pergola-package (pergola), [6](#)

plotChr, [7](#)

plotRf, [7](#)

pullMap, [8](#)

shuffleInput, [9](#)

simHexa, [10](#)

simTetra, [10](#)

sortLeafs, [11](#)

splitChr, [11](#)

swapChrs, [12](#)

switchChrs, [13](#)