

# Package ‘qMRI’

October 13, 2022

**Type** Package

**Title** Methods for Quantitative Magnetic Resonance Imaging ('qMRI')

**Version** 1.2

**Date** 2020-02-20

**Maintainer** Karsten Tabelow <karsten.tabelow@wias-berlin.de>

**Depends** R (>= 3.5), awsMethods (>= 1.0), methods

**Imports** oro.nifti (>= 0.9), stringr, aws (>= 2.4), adimpro (>= 0.9)

**LazyData** TRUE

**Description** Implementation of methods for estimation of quantitative maps from Multi-Parameter Mapping (MPM) acquisitions (Weiskopf et al. (2013) <doi:10.3389/fnins.2013.00095>) including adaptive smoothing methods in the framework of the ESTATICS model (Estimating the apparent transverse relaxation time (R2\*) from images with different contrasts, Weiskopf et al. (2014) <doi:10.3389/fnins.2014.00278>). The smoothing method is described in Mohammadi et al. (2017). <doi:10.20347/WIAS.PREPRINT.2432>. Usage of the package is also described in Polzehl and Tabelow (2019), Magnetic Resonance Brain Imaging, Chapter 6, Springer, Use R! Series. <doi:10.1007/978-3-030-29184-6\_6>.

**License** GPL (>= 2)

**Copyright** This package is Copyright (C) 2015-2020 Weierstrass Institute for Applied Analysis and Stochastics.

**URL** <http://www.wias-berlin.de/research/ats/imaging/>

**Suggests** covr, testthat, knitr, rmarkdown

**VignetteBuilder** knitr

**RoxygenNote** 6.1.1

**NeedsCompilation** yes

**Author** Joerg Polzehl [aut],  
Karsten Tabelow [aut, cre],  
WIAS Berlin [cph, fnd]

**Repository** CRAN

**Date/Publication** 2020-02-25 01:20:02 UTC

## R topics documented:

qMRI-package	2
calculateQI	5
colMT	8
estimateESTATICS	8
extract-methods	11
readMPMData	15
smoothESTATICS	17
writeESTATICS	20
writeQI	22

<b>Index</b>	<b>25</b>
--------------	-----------

---

qMRI-package	<i>Methods for Quantitative Magnetic Resonance Imaging ('qMRI')</i>
--------------	---

---

## Description

Implementation of methods for estimation of quantitative maps from Multi-Parameter Mapping (MPM) acquisitions (Weiskopf et al. (2013) <doi:10.3389/fnins.2013.00095>) including adaptive smoothing methods in the framework of the ESTATICS model (Estimating the apparent transverse relaxation time ( $R2^*$ ) from images with different contrasts, Weiskopf et al. (2014) <doi:10.3389/fnins.2014.00278>). The smoothing method is described in Mohammadi et al. (2017). <doi:10.20347/WIAS.PREPRINT.2432>. Usage of the package is also described in Polzehl and Tabelow (2019), Magnetic Resonance Brain Imaging, Chapter 6, Springer, Use R! Series. <doi:10.1007/978-3-030-29184-6\_6>.

## Details

The DESCRIPTION file:

```

Package:      qMRI
Type:         Package
Title:        Methods for Quantitative Magnetic Resonance Imaging ('qMRI')
Version:      1.2
Date:         2020-02-20
Authors@R:   c(person("Joerg", "Polzehl", role = c("aut"), email = "joerg.polzehl@wias-berlin.de"), person("Karsten", "Tabelow", role = c("cre"), email = "karsten.tabelow@wias-berlin.de"))
Maintainer:  Karsten Tabelow <karsten.tabelow@wias-berlin.de>
Depends:     R (>= 3.5), awsMethods (>= 1.0), methods
Imports:     oro.nifti (>= 0.9), stringr, aws (>= 2.4), adimpro (>= 0.9)
LazyData:   TRUE
Description: Implementation of methods for estimation of quantitative maps from Multi-Parameter Mapping (MPM) acquisitions
License:     GPL (>= 2)
Copyright:   This package is Copyright (C) 2015-2020 Weierstrass Institute for Applied Analysis and Stochastics.
URL:         http://www.wias-berlin.de/research/ats/imaging/
Suggests:   covr, testthat, knitr, rmarkdown
VignetteBuilder: knitr
RoxygenNote: 6.1.1
Author:      Joerg Polzehl [aut], Karsten Tabelow [aut, cre], WIAS Berlin [cph, fnd]

```

## Index of help topics:

calculateQI	Obtain quantitative maps from estimated ESTATICs parameters.
colMT	MT map color scheme
estimateESTATICS	Estimate parameters in the ESTATICs model.
extract.ANY-method	Methods to extract information from objects of class '"MPMData"', '"ESTATICSModel"', '"sESTATICSModel"' and '"qMaps"'.
qMRI-package	Methods for Quantitative Magnetic Resonance Imaging ('qMRI')
readMPMData	Read experimental Multi-Parameter Mapping (MPM) data.
smoothESTATICS	Adaptive smoothing of ESTATICs parameters and MPM data
writeESTATICS	Write maps of ESTATICs parameters in standardized form as NIfTI files.
writeQI	Write estimated maps in standardized form as NIfTI files.

**Author(s)**

Karsten Tabelow <tabelow@wias-berlin.de>

J"org Polzehl <polzehl@wias-berlin.de>

Maintainer: Karsten Tabelow <karsten.tabelow@wias-berlin.de>

**References**

Weiskopf, N.; Suckling, J.; Williams, G.; Correia, M. M.; Inkster, B.; Tait, R.; Ooi, C.; Bullmore, E. T. & Lutti, A. Quantitative multi-parameter mapping of R1, PD(\*), MT, and R2(\*) at 3T: a multi-center validation. *Front Neurosci*, Wellcome Trust Centre for Neuroimaging, UCL Institute of Neurology, University College London, UK., 2013, 7, 95

J. Polzehl, K. Tabelow (2019). *Magnetic Resonance Brain Imaging: Modeling and Data Analysis Using R*. Springer, Use R! series. Doi:10.1007/978-3-030-29184-6.

**See Also**

[aws](#)

**Examples**

```
dataDir <- system.file("extdata",package="qMRI")
#
# set file names for T1w, MTw and PDw images
#
t1Names <- paste0("t1w_",1:8, ".nii.gz")
mtNames <- paste0("mtw_",1:6, ".nii.gz")
pdNames <- paste0("pdw_",1:8, ".nii.gz")
t1Files <- file.path(dataDir, t1Names)
```

```

mtFiles <- file.path(dataDir, mtNames)
pdFiles <- file.path(dataDir, pdNames)
#
# file names of mask and B1 field map
#
B1File <- file.path(dataDir, "B1map.nii.gz")
maskFile <- file.path(dataDir, "mask.nii.gz")
#
# Acquisition parameters (TE, TR, Flip Angle) for T1w, MTw and PDw images
#
TE <- c(2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4)
TR <- rep(25, 22)
FA <- c(rep(21, 8), rep(6, 6), rep(6, 8))
#
# read MPM example data
#
library(qMRI)
mpm <- readMPMData(t1Files, pdFiles, mtFiles,
                  maskFile, TR = TR, TE = TE,
                  FA = FA, verbose = FALSE)
#
# Estimate Parameters in the ESTATICS model
#
modelMPM <- estimateESTATICS(mpm, method = "NLR")
#
# smooth maps of ESTATICS Parameters
#
setCores(2)
modelMPMsp1 <- smoothESTATICS(modelMPM,
                              kstar = 16,
                              alpha = 0.004,
                              patchsize=1,
                              verbose = TRUE)
#
# resulting ESTATICS parameter maps for central coronal slice
#
if(require(adimpro)){
  rimage.options(zquantiles=c(.01,.99), ylab="z")
  oldpar <- par(mfrow=c(2,4),mar=c(3,3,3,1),mgp=c(2,1,0))
  pnames <- c("T1", "MT", "PD", "R2star")
  modelCoeff <- extract(modelMPM, "modelCoeff")
  for(i in 1:4){
    rimage(modelCoeff[i, , 11, ])
    title(pnames[i])
  }
  modelCoeff <- extract(modelMPMsp1, "modelCoeff")
  for(i in 1:4){
    rimage(modelCoeff[i, , 11, ])
    title(paste("smoothed", pnames[i]))
  }
}
}

```

```

#
# Compute quantitative maps (R1, R2star, PD, MT)
#
qMRIMaps <- calculateQI(modelMPPM,
                        b1File = B1File,
                        TR2 = 3.4)
qMRISmoothedp1Maps <- calculateQI(modelMPPMsp1,
                                  b1File = B1File,
                                  TR2 = 3.4)

#
# resulting quantitative maps for central coronal slice
#
if(require(adimpro)){
  rimage.options(zquantiles=c(.01,.99), ylab="z")
  par(mfrow=c(2,4),mar=c(3,3,3,1),mgp=c(2,1,0))
  nmaps <- c("R1", "R2star", "PD", "MT")
  qmap <- extract(qMRIMaps, nmaps)
  for (i in 1:4) rimage(qmap[[i]][,11,], main=nmaps[i])
  qmap <- extract(qMRISmoothedp1Maps, nmaps)
  for (i in 1:4) rimage(qmap[[i]][,11,], main=paste("Smoothed", nmaps[i]))
}
par(oldpar)

```

---

calculateQI

*Obtain quantitative maps from estimated ESTATICS parameters.*


---

## Description

Quantitative imaging parameters are calculated from the estimated parameters in the ESTATICS model. This involves a correction for magnetic field inhomogeneities if the information is provided in argument `b1File` and use of a second of a second recovery delay `TR2` in case of Dual-Excitation FLASH measurements (Helms 2008).

## Usage

```
calculateQI(mpmESTATICSModel, b1File = NULL, TR2 = 0, verbose = TRUE)
```

## Arguments

<code>mpmESTATICSModel</code>	Object of class 'ESTATICSModel' as returned from function <a href="#">estimateESTATICS</a> .
<code>b1File</code>	(optional) Name of a file containing a B1-field inhomogeneity map (.nii)
<code>TR2</code>	second recovery delay <code>TR2</code> in case of Dual-Excitation FLASH measurements.
<code>verbose</code>	logical: Monitor process.

**Value**

List with components

b1Map	b1Map
R1	Estimated map of R1
R2star	Estimated map of R2star
PD	Estimated map of PD
MT	Estimated map of delta (if MT-series was used)
model	Type of ESTATICS model used
t1Files	filenames T1
mtFiles	filenames MT
pdFiles	filenames PD
mask	brainmask

and class-attribute 'qMaps' .

**Author(s)**

Karsten Tabelow <tabelow@wias-berlin.de>  
 J"org Polzehl <polzehl@wias-berlin.de>

**References**

Helms, G.; Dathe, H.; Kallenberg, K. & Dechent, P. High-Resolution Maps of Magnetization Transfer with Inherent Correction for RF Inhomogeneity and T1 Relaxation Obtained from 3D FLASH MRI *Magn. Res. Med.*, 2008, 60, 1396-1407

Weiskopf, N.; Suckling, J.; Williams, G.; Correia, M. M.; Inkster, B.; Tait, R.; Ooi, C.; Bullmore, E. T. & Lutti, A. Quantitative multi-parameter mapping of R1, PD(\*), MT, and R2(\*) at 3T: a multi-center validation. *Front Neurosci*, Wellcome Trust Centre for Neuroimaging, UCL Institute of Neurology, University College London, UK., 2013, 7, 95

J. Polzehl, K. Tabelow (2019). *Magnetic Resonance Brain Imaging: Modeling and Data Analysis Using R*. Springer, Use R! series. Doi:10.1007/978-3-030-29184-6.

**See Also**

[readMPMData](#), [estimateESTATICS](#), [smoothESTATICS](#), [writeESTATICS](#), [awsLocalSigma](#)

**Examples**

```
dataDir <- system.file("extdata", package="qMRI")
#
# set file names for T1w, MTw and PDw images
#
t1Names <- paste0("t1w_", 1:8, ".nii.gz")
mtNames <- paste0("mtw_", 1:6, ".nii.gz")
pdNames <- paste0("pdw_", 1:8, ".nii.gz")
t1Files <- file.path(dataDir, t1Names)
```

```

mtFiles <- file.path(dataDir, mtNames)
pdFiles <- file.path(dataDir, pdNames)
#
# file names of mask and B1 field map
#
B1File <- file.path(dataDir, "B1map.nii.gz")
maskFile <- file.path(dataDir, "mask0.nii.gz")
#
# Acquisition parameters (TE, TR, Flip Angle) for T1w, MTw and PDw images
#
TE <- c(2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4)
TR <- rep(25, 22)
FA <- c(rep(21, 8), rep(6, 6), rep(6, 8))
#
# read MPM example data
#
library(qMRI)
mpm <- readMPMData(t1Files, pdFiles, mtFiles,
                  maskFile, TR = TR, TE = TE,
                  FA = FA, verbose = FALSE)
#
# limit calculations to voxel in the central coronal slice
# to reduce execution time of the example
#
# Estimate Parameters in the ESTATICS model
#
modelMPM <- estimateESTATICS(mpm, method = "NLR")
#
# resulting ESTATICS parameter maps for central coronal slice
#
if(require(adimpro)){
  rimage.options(zquantiles=c(.01,.99), ylab="z")
  oldpar <- par(mfrow=c(2,2),mar=c(3,3,3,1),mgp=c(2,1,0))
  pnames <- c("T1", "MT", "PD", "R2star")
  modelCoeff <- extract(modelMPM, "modelCoeff")
  for(i in 1:4){
    rimage(modelCoeff[i, , 11, ])
    title(pnames[i])
  }
}
#
# Compute quantitative maps (R1, R2star, PD, MT)
#
qMRIMaps <- calculateQI(modelMPM,
                      b1File = B1File,
                      TR2 = 3.4)
#
# resulting quantitative maps for central coronal slice
#
if(require(adimpro)){

```

```

rimage.options(zquantiles=c(.01,.99), ylab="z")
par(mfrow=c(2,2),mar=c(3,3,3,1),mgp=c(2,1,0))
nmaps <- c("R1", "R2star", "PD", "MT")
qmap <- extract(qMRIMaps, nmaps)
for (i in 1:4){
  rimage(qmap[[i]][,11,], main=nmaps[i])
}
par(oldpar)
}

```

---

colMT

*MT map color scheme*


---

### Description

Color map implementing the color scheme for MT maps. This is the plasma scale from Matplotlib (pyplot) generated by function `plasma` from package **viridisLite**.

### Usage

```
colMT
```

### Format

A vector with 256 RGB color values.

---

estimateESTATICS

*Estimate parameters in the ESTATICS model.*


---

### Description

Evaluation of the ESTATICS model (Weisskopf (2013)) using nonlinear least squares regression and a quasi-likelihood approach assuming a noncentral chi- or a Rician distribution for the data. The latter should be preferred in case of low SNR (high resolution) data to avoid biased parameter estimates. Quasi-likelihood estimation requires a specification of the scale parameter  $\sigma$  of the data distribution.

### Usage

```

estimateESTATICS(mpdata, TEScale = 100, dataScale = 1000, method = c("NLR", "QL"),
  sigma = NULL, L = 1, maxR2star = 50,
  varest = c("RSS", "data"), verbose = TRUE)

```



**Arguments**

mpmdata	Object of class MPMPData as created by <code>readMPMPData</code> .
TEScale	scale factor for TE (used for improved numerical stability)
dataScale	scale factor for image intensities (used for improved numerical stability)
method	either "NLR" or "QL". Specifies non-linear regression or quasi-likelihood.
sigma	scale parameter sigma of signal distribution (either a scalar or a 3D array). (only needed in case of method="QL".)
L	effective number of receiver coils ( $2*L$ is degrees of freedom of the signal distribution). $L=1$ for Rician distribution. (only needed in case of method="QL".)
maxR2star	maximum value allowed for the R2star parameter in the ESTATICS model.
varest	For parameter covariance estimation use either residual sum of squares (RSS) or estimate variances for T1, MT (is available) and PD from highest intensity images using function <code>awsLocalSigmafrom</code> from package <b>aws</b> .
verbose	logical: Monitor process.

**Value**

list with components	
modelCoeff	Estimated parameter maps
invCov	map of inverse covariance matrices
rsigma	map of residual standard deviations
isConv	convergence indicator map
isThresh	logical map indicating where $R2star == maxR2star$ .
sdim	image dimension
nFiles	number of images
t1Files	vector of T1 filenames
pdFiles	vector of PD filenames
mtFiles	vector of MT filenames
model	model used (depends on specification of MT files)
maskFile	filename of brain mask
mask	brain mask
sigma	sigma
L	L
TR	TR values
TE	TE values
FA	Flip angles (FA)
TEScale	TEScale
dataScale	dataScale
and class-attribute 'ESTATICSModel'	

**Author(s)**

Karsten Tabelow <tabelow@wias-berlin.de>  
 J"org Polzehl <polzehl@wias-berlin.de>

**References**

Weiskopf, N.; Suckling, J.; Williams, G.; Correia, M. M.; Inkster, B.; Tait, R.; Ooi, C.; Bullmore, E. T. & Lutti, A. Quantitative multi-parameter mapping of R1, PD(\*), MT, and R2(\*) at 3T: a multi-center validation. *Front Neurosci*, Wellcome Trust Centre for Neuroimaging, UCL Institute of Neurology, University College London, UK., 2013, 7, 95

J. Polzehl, K. Tabelow (2019). *Magnetic Resonance Brain Imaging: Modeling and Data Analysis Using R*. Springer, Use R! series. Doi:10.1007/978-3-030-29184-6.

**See Also**

[readMPMData](#), [calculateQI](#), [smoothESTATICS](#), [writeESTATICS](#), [awsLocalSigma](#)

**Examples**

```
dataDir <- system.file("extdata", package="qMRI")
#
# set file names for T1w, MTw and PDw images
#
t1Names <- paste0("t1w_", 1:8, ".nii.gz")
mtNames <- paste0("mtw_", 1:6, ".nii.gz")
pdNames <- paste0("pdw_", 1:8, ".nii.gz")
t1Files <- file.path(dataDir, t1Names)
mtFiles <- file.path(dataDir, mtNames)
pdFiles <- file.path(dataDir, pdNames)
#
# file names of mask and B1 field map
#
B1File <- file.path(dataDir, "B1map.nii.gz")
maskFile <- file.path(dataDir, "mask0.nii.gz")
#
# Acquisition parameters (TE, TR, Flip Angle) for T1w, MTw and PDw images
#
TE <- c(2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4)
TR <- rep(25, 22)
FA <- c(rep(21, 8), rep(6, 6), rep(6, 8))
#
# read MPM example data
#
library(qMRI)
mpm <- readMPMData(t1Files, pdFiles, mtFiles,
                  maskFile, TR = TR, TE = TE,
                  FA = FA, verbose = FALSE)
#
```

```
# Estimate Parameters in the ESTATICS model
#
modelMPM <- estimateESTATICS(mpm, method = "NLR")
# Alternatively using Quasi-Likelihood
sigma <- 50
modelMPMQL <- estimateESTATICS(mpm, method = "QL",
                               sigma = array(sigma,mpm$sdim), L = 1)
```

---

extract-methods            *Methods to extract information from objects of class "MPMData", "ESTATICSModel", "sESTATICSModel" and "qMaps".*

---

### Description

The extract-methods extract and/or compute specified statistics from object of class "MPMData", "ESTATICSModel", "sESTATICSModel" and "qMaps". The [-methods can be used to reduce objects of class "MPMData", "ESTATICSModel", "sESTATICSModel" and "qMaps" such that they .

### Usage

```
## S3 method for class 'MPMData'
extract(x, what, ...)
## S3 method for class 'ESTATICSModel'
extract(x, what, ...)
## S3 method for class 'sESTATICSModel'
extract(x, what, ...)
## S3 method for class 'qMaps'
extract(x, what, ...)
## S3 method for class 'MPMData'
x[i, j, k, ...]
## S3 method for class 'ESTATICSModel'
x[i, j, k, ...]
## S3 method for class 'sESTATICSModel'
x[i, j, k, ...]
## S3 method for class 'qMaps'
x[i, j, k, ...]
```

### Arguments

x	object of class "MPMData", "ESTATICSModel", "sESTATICSModel" or "qMaps".
what	Character vector of names of statistics to extract. See Methods Section for details.
i	index vector for first spatial dimension
j	index vector for second spatial dimension
k	index vector for third spatial dimension
...	additional parameters, currently unused.

**Value**

A list with components carrying the names of the options specified in argument `what`.

**Methods**

**class(x) = "ANY"** Returns a warning for `extract`

**class(x) = "MPMData"** Depending the occurrence of names in `what` a list with the specified components is returned

- "ddata" mpm data
- "sdim" dimension of image cube
- "nFiles" number of images / image files
- "t1Files" character - filenames of t1Files
- "pdFiles" character - filenames of pdFiles
- "mtFiles" character - filenames of mtFiles
- "model" Number of the ESTATIC model that can be used
- "maskFile" character - filenames of maskFile
- "mask" mask
- "TR" vector of TR values
- "TE" vector of TE values
- "FA" vector of FA values

**class(x) = "ESTATICSModel"** Depending the occurrence of names in `what` a list with the specified components is returned

- "modelCoeff" Estimated parameter maps
- "invCov" map of inverse covariance matrices
- "rsigma" map of residual standard deviations
- "isConv" convergence indicator map
- "isThresh" logical map indicating where  $R2star == \max R2star$ .
- "sdim" image dimension
- "nFiles" number of images
- "t1Files" vector of T1 filenames
- "pdFiles" vector of PD filenames
- "mtFiles" vector of MT filenames
- "model" model used (depends on specification of MT files)
- "maskFile" filename of brain mask
- "mask" brain mask
- "sigma" sigma
- "L" L
- "TR" TR values
- "TE" TE values
- "FA" Flip angles (FA)
- "TEScale" TEScale
- "dataScale" dataScale

**class(x) = "sESTATICSModel"** Depending the occurrence of names in what a list with the specified components is returned

- "modelCoeff" Estimated parameter maps
- "invCov" map of inverse covariance matrices
- "rsigma" map of residual standard deviations
- "isConv" convergence indicator map
- "bi" Sum of weights map from AWS/PAWS
- "smoothPar" smoothing parameters used in AWS/PAWS
- "smoothedData" smoothed mpmData
- "isThresh" logical map indicating where  $R2star == \max R2star$ .
- "sdim" image dimension
- "nFiles" number of images
- "t1Files" vector of T1 filenames
- "pdFiles" vector of PD filenames
- "mtFiles" vector of MT filenames
- "model" model used (depends on specification of MT files)
- "maskFile" filename of brain mask
- "mask" brain mask
- "sigma" sigma
- "L" L
- "TR" TR values
- "TE" TE values
- "FA" Flip angles (FA)
- "TEScale" TEScale
- "dataScale" dataScale

**class(x) = "qMaps"** Depending the occurrence of names in what a list with the specified components is returned

- b1Map b1Map
- R1 Estimated map of R1
- R2star Estimated map of R2star
- PD Estimated map of PD
- MT Estimated map of delta (if MT-series was used)
- model Type of ESTATICS model used
- t1Files filenames T1
- mtFiles filenames MT
- pdFiles filenames PD
- mask brainmask

#### Author(s)

Karsten Tabelow <tabelow@wias-berlin.de>  
 J"org Polzehl <polzehl@wias-berlin.de>

**Examples**

```

dataDir <- system.file("extdata",package="qMRI")
#
# set file names for T1w, MTw and PDw images
#
t1Names <- paste0("t1w_",1:8,".nii.gz")
mtNames <- paste0("mtw_",1:6,".nii.gz")
pdNames <- paste0("pdw_",1:8,".nii.gz")
t1Files <- file.path(dataDir, t1Names)
mtFiles <- file.path(dataDir, mtNames)
pdFiles <- file.path(dataDir, pdNames)
#
# file names of mask and B1 field map
#
B1File <- file.path(dataDir, "B1map.nii.gz")
maskFile <- file.path(dataDir, "mask0.nii.gz")
#
# Acquisition parameters (TE, TR, Flip Angle) for T1w, MTw and PDw images
#
TE <- c(2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4)
TR <- rep(25, 22)
FA <- c(rep(21, 8), rep(6, 6), rep(6, 8))
#
# read MPM example data
#
library(qMRI)
mpm <- readMPMData(t1Files, pdFiles, mtFiles,
                  maskFile, TR = TR, TE = TE,
                  FA = FA, verbose = FALSE)
#
# display some data
#
data <- extract(mpm,"ddata")
if(require(adimpro)){
  rimage.options(ylab = "z")
  oldpar <- par(mfrow=c(1,3),mar=c(3,3,3,1),mgp=c(2,1,0))
  rimage(data[1,,11], main="first T1w image")
  rimage(data[9,,11], main="first MTw image")
  rimage(data[15,,11], main="first PDw image")
}
#
# Estimate Parameters in the ESTATICS model
#
modelMPM <- estimateESTATICS(mpm, method = "NLR")
#
# Parameter maps and residual standard deviation
#
z <- extract(modelMPM,c("rsigma","modelCoeff"))
if(require(adimpro)){
  rimage.options(ylab = "z")

```

```

par(mfrow=c(1,5),mar=c(3,3,3,1),mgp=c(2,1,0))
rimage(z$modelCoeff[1,,11,], main="S_T1")
rimage(z$modelCoeff[2,,11,], main="S_MT")
rimage(z$modelCoeff[3,,11,], main="S_PD")
rimage(z$modelCoeff[4,,11,], main="R2star")
rimage(z$rsigma[,11,], main="Residual sd")
}
#
# Compute quantitative maps (R1, R2star, PD, MT)
#
qMRIMaps <- calculateQI(modelMPM,
                        b1File = B1File,
                        TR2 = 3.4)
#
# resulting quantitative maps for central coronal slice
#
if(require(adimpro)){
rimage.options(zquantiles=c(.01,.99), ylab="z")
par(mfrow=c(2,4),mar=c(3,3,3,1),mgp=c(2,1,0))
nmaps <- c("R1","R2star","PD","MT")
qmap <- extract(qMRIMaps,nmaps)
for (i in 1:4) rimage(qmap[[i]][,11,],main=nmaps[i])
}
par(oldpar)

```

---

readMPMData

*Read experimental Multi-Parameter Mapping (MPM) data.*


---

## Description

The function reads data generated in Multimodal Parameter Mapping (MPM) experiments.

## Usage

```

readMPMData(t1Files = NULL, pdFiles = NULL, mtFiles = NULL, maskFile = NULL,
            TR = NULL, TE = NULL, FA = NULL, wghts = NULL, verbose = TRUE)

```

## Arguments

t1Files	Vector of filenames corresponding to T1 weighted images (in Nifti-Format) with varying TE
pdFiles	Vector of filenames corresponding to PD weighted images (in Nifti-Format) with varying TE
mtFiles	optional Vector of filenames corresponding to MT weighted images (in Nifti-Format) with varying TE
maskFile	optional filename for mask (in Nifti-Format)
TR	optional numeric TR vector, if omitted information is extracted from .nii files if possible

TE	optional numeric TE vector, if omitted information is extracted from .nii files if possible
FA	optional numeric FA (flip-angle) vector, if omitted information is extracted from .nii files if possible
wghts	optional weights for MPM data volumes. Only needed is volumes have different data variance, e.g., in case of averages of multiple acquisitions.
verbose	logical - provide information on progress

### Value

List with components

ddata	mpm data
sdim	dimension of image cube
nFiles	number of images / image files
t1Files	character - filenames of t1Files
pdFiles	character - filenames of pdFiles
mtFiles	character - filenames of mtFiles
model	Number of the ESTATICS model that can be used
maskFile	character - filenames of maskFile
mask	mask
TR	vector of TR values
TE	vector of TE values
FA	vector of FA values
and class-attribute 'mpmData'	

### Author(s)

Karsten Tabelow <tabelow@wias-berlin.de>  
 J"org Polzehl <polzehl@wias-berlin.de>

### References

Weiskopf, N.; Suckling, J.; Williams, G.; Correia, M. M.; Inkster, B.; Tait, R.; Ooi, C.; Bullmore, E. T. & Lutti, A. Quantitative multi-parameter mapping of R1, PD(\*), MT, and R2(\*) at 3T: a multi-center validation. *Front Neurosci*, Wellcome Trust Centre for Neuroimaging, UCL Institute of Neurology, University College London, UK., 2013, 7, 95

J. Polzehl, K. Tabelow (2019). *Magnetic Resonance Brain Imaging: Modeling and Data Analysis Using R*. Springer, Use R! series. Doi:10.1007/978-3-030-29184-6.

### See Also

[estimateESTATICS](#), [calculateQI](#), [smoothESTATICS](#), [writeESTATICS](#), [awsLocalSigma](#)



**Examples**

```

dataDir <- system.file("extdata", package="qMRI")
#
# set file names for T1w, MTw and PDw images
#
t1Names <- paste0("t1w_", 1:8, ".nii.gz")
mtNames <- paste0("mtw_", 1:6, ".nii.gz")
pdNames <- paste0("pdw_", 1:8, ".nii.gz")
t1Files <- file.path(dataDir, t1Names)
mtFiles <- file.path(dataDir, mtNames)
pdFiles <- file.path(dataDir, pdNames)
#
# file names of mask and B1 field map
#
B1File <- file.path(dataDir, "B1map.nii.gz")
maskFile <- file.path(dataDir, "mask.nii.gz")
#
# Acquisition parameters (TE, TR, Flip Angle) for T1w, MTw and PDw images
#
TE <- c(2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4)
TR <- rep(25, 22)
FA <- c(rep(21, 8), rep(6, 6), rep(6, 8))
#
# read MPM example data
#
library(qMRI)
mpm <- readMPMData(t1Files, pdFiles, mtFiles,
                  maskFile, TR = TR, TE = TE,
                  FA = FA, verbose = FALSE)

```

---

smoothESTATICS

*Adaptive smoothing of ESTATICS parameters and MPM data*


---

**Description**

Performs adaptive smoothing of parameter maps in the ESTATICS model and if `mpmData` is specified these data. Implements both vectorized variants of the Adaptive Weights Smoothing (AWS, Polzehl and Spokoiny (2006)) and patchwise AWS (PAWS, Polzehl et al (2018)) algorithms with weighting schemes determined by the estimated parameter maps and their covariances.

**Usage**

```

smoothESTATICS(mpmESTATICSModel, mpmData = NULL, kstar = 16, alpha = 0.025,
              patchsize = 0, wghts = NULL, verbose = TRUE)

```

**Arguments**

mpmESTATICSModel	Object of class 'ESTATICSModel' as returned from function <code>estimateESTATICS</code> .
mpmData	(optional) Object of class MPMDData as created by <code>readMPMDData</code> from which the parameter maps were obtained.
kstar	Maximum number of steps.
alpha	specifies the scale parameter for the adaptation criterion. smaller values are more restrictive.
patchsize	Patchsize in PAWS, 0 corresponds to AWS, alternative values are 1 and 2.
wghts	(optional) voxel size if measurements are not isotropic.
verbose	logical - provide information on progress

**Value**

list with components	
modelCoeff	Estimated parameter maps
invCov	map of inverse covariance matrices
isConv	convergence indicator map
bi	Sum of weights map from AWS/PAWS
smoothPar	smoothing parameters used in AWS/PAWS
smoothedData	smoothed mpmData
sdim	image dimension
nFiles	number of images
t1Files	vector of T1 filenames
pdFiles	vector of PD filenames
mtFiles	vector of MT filenames
model	model used (depends on specification of MT files)
maskFile	filename of brain mask
mask	brain mask
sigma	sigma
L	L
TR	TR values
TE	TE values
FA	Flip angles (FA)
TEScale	TEScale
dataScale	dataScale
and class-attribute 'sESTATICSModel'	

**Author(s)**

Karsten Tabelow <tabelow@wias-berlin.de>  
 J"org Polzehl <polzehl@wias-berlin.de>

**References**

- J. Polzehl, V. Spokoiny, Propagation-separation approach for local likelihood estimation, *Probab. Theory Related Fields* 135 (3), (2006) , pp. 335–362.
- J. Polzehl, K. Papafitsorus, K. Tabelow (2018). Patch-wise adaptive weights smoothing. *WIAS-Preprint* 2520.
- J. Polzehl, K. Tabelow (2019). *Magnetic Resonance Brain Imaging: Modeling and Data Analysis Using R*. Springer, Use R! series. Doi:10.1007/978-3-030-29184-6.

**See Also**

[readMPMData, estimateESTATICS](#)

**Examples**

```
dataDir <- system.file("extdata", package="qMRI")
#
# set file names for T1w, MTw and PDw images
#
t1Names <- paste0("t1w_", 1:8, ".nii.gz")
mtNames <- paste0("mtw_", 1:6, ".nii.gz")
pdNames <- paste0("pdw_", 1:8, ".nii.gz")
t1Files <- file.path(dataDir, t1Names)
mtFiles <- file.path(dataDir, mtNames)
pdFiles <- file.path(dataDir, pdNames)
#
# file names of mask and B1 field map
#
B1File <- file.path(dataDir, "B1map.nii.gz")
maskFile <- file.path(dataDir, "mask.nii.gz")
#
# Acquisition parameters (TE, TR, Flip Angle) for T1w, MTw and PDw images
#
TE <- c(2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4)
TR <- rep(25, 22)
FA <- c(rep(21, 8), rep(6, 6), rep(6, 8))
#
# read MPM example data
#
library(qMRI)
mpm <- readMPMData(t1Files, pdFiles, mtFiles,
                  maskFile, TR = TR, TE = TE,
                  FA = FA, verbose = FALSE)
#
```

```

# Estimate Parameters in the ESTATICS model
#
modelMPM <- estimateESTATICS(mpm, method = "NLR")
#
# smooth maps of ESTATICS Parameters
#
setCores(2)
modelMPMsp1 <- smoothESTATICS(modelMPM,
                              kstar = 16,
                              alpha = 0.004,
                              patchsize=1,
                              verbose = TRUE)

#
# resulting ESTATICS parameter maps for central coronal slice
#
if(require(adimpro)){
  rimage.options(zquantiles=c(.01,.99), ylab="z")
  oldpar <- par(mfrow=c(2,4),mar=c(3,3,3,1),mgp=c(2,1,0))
  pnames <- c("T1", "MT", "PD", "R2star")
  modelCoeff <- extract(modelMPM, "modelCoeff")
  for(i in 1:4){
    rimage(modelCoeff[i,,11,])
    title(pnames[i])
  }
  modelCoeff <- extract(modelMPMsp1, "modelCoeff")
  for(i in 1:4){
    rimage(modelCoeff[i,,11,])
    title(paste("smoothed", pnames[i]))
  }
}
par(oldpar)

```

---

writeESTATICS	<i>Write maps of ESTATICS parameters in standardized form as NIfTI files.</i>
---------------	---

---

### Description

R2, ST1, SPD and, if available, SMT-maps are written as compressed NIFTI files into directory the speecified directory. If `class(mpmESTATICSModel) == "sESTATICSModel"` and an smoothed data are stored in `mpmESTATICSModel$smoothedData` the smoothed data are stored as ompressed NIfTI files in `dir` with filenames assembled using prefix and the names of the data source files.

### Usage

```
writeESTATICS(mpmESTATICSModel, dir = NULL, prefix = "estatics", verbose = TRUE)
```

**Arguments**

mpmESTATICSModel	Object of class 'ESTATICSModel' or 'sESTATICSModel' as returned from function <a href="#">estimateESTATICS</a> or <a href="#">smoothESTATICS</a> .
dir	Directory name (or path) for output.
prefix	Prefix for file names
verbose	logical - provide information on progress

**Value**

The function returns NULL

**Author(s)**

Karsten Tabelow <tabelow@wias-berlin.de>  
 J\"org Polzehl <polzehl@wias-berlin.de>

**See Also**

[readMPMData](#), [estimateESTATICS](#), [smoothESTATICS](#)

**Examples**

```
dataDir <- system.file("extdata",package="qMRI")
outDir <- tempdir()
#
# set file names for T1w, MTw and PDw images
#
t1Names <- paste0("t1w_",1:8,".nii.gz")
mtNames <- paste0("mtw_",1:6,".nii.gz")
pdNames <- paste0("pdw_",1:8,".nii.gz")
t1Files <- file.path(dataDir, t1Names)
mtFiles <- file.path(dataDir, mtNames)
pdFiles <- file.path(dataDir, pdNames)
#
# file names of mask and B1 field map
#
B1File <- file.path(dataDir, "B1map.nii.gz")
maskFile <- file.path(dataDir, "mask0.nii.gz")
#
# Acquisition parameters (TE, TR, Flip Angle) for T1w, MTw and PDw images
#
TE <- c(2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4)
TR <- rep(25, 22)
FA <- c(rep(21, 8), rep(6, 6), rep(6, 8))
#
# read MPM example data
#
```

```

library(qMRI)
mpm <- readMPMData(t1Files, pdFiles, mtFiles,
                  maskFile, TR = TR, TE = TE,
                  FA = FA, verbose = FALSE)

#
# Estimate Parameters in the ESTATICS model
#
modelMPM <- estimateESTATICS(mpm, method = "NLR")
#
# resulting ESTATICS parameter maps for central coronal slice
#
if(require(adimpro)){
  rimage.options(zquantiles=c(.01,.99), ylab="z")
  oldpar <- par(mfrow=c(2,2),mar=c(3,3,3,1),mgp=c(2,1,0))
  pnames <- c("T1","MT","PD","R2star")
  modelCoeff <- extract(modelMPM,"modelCoeff")
  for(i in 1:4){
    rimage(modelCoeff[i,,11,])
    title(pnames[i])
  }
}
#
# write ESTATICS parameter maps
#
writeESTATICS(modelMPM, dir=outDir, prefix="estatics")
par(oldpar)

```

---

writeQI

*Write estimated maps in standardized form as NIfTI files.*


---

### Description

Quantitative R2, R1, PD and, if available, MT-maps are written as compressed NIFTI files into directory the specified directory.

### Usage

```
writeQI(qi, dir = NULL, prefix="qmap", verbose = TRUE)
```

### Arguments

qi	Object of class 'qMaps' as returned from function <a href="#">calculateQI</a>
dir	Directory name (or path) for output.
prefix	Prefix for file names
verbose	logical - provide information on progress

### Value

The function returns NULL

**Author(s)**

Karsten Tabelow <tabelow@wias-berlin.de>  
 Jörn Polzehl <polzehl@wias-berlin.de>

**See Also**

[readMPMData](#), [estimateESTATICS](#), [calculateQI](#)

**Examples**

```
dataDir <- system.file("extdata", package="qMRI")
outDir <- tempdir()
#
# set file names for T1w, MTw and PDw images
#
t1Names <- paste0("t1w_", 1:8, ".nii.gz")
mtNames <- paste0("mtw_", 1:6, ".nii.gz")
pdNames <- paste0("pdw_", 1:8, ".nii.gz")
t1Files <- file.path(dataDir, t1Names)
mtFiles <- file.path(dataDir, mtNames)
pdFiles <- file.path(dataDir, pdNames)
#
# file names of mask and B1 field map
#
B1File <- file.path(dataDir, "B1map.nii.gz")
maskFile <- file.path(dataDir, "mask0.nii.gz")
#
# Acquisition parameters (TE, TR, Flip Angle) for T1w, MTw and PDw images
#
TE <- c(2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8,
        2.3, 4.6, 6.9, 9.2, 11.5, 13.8, 16.1, 18.4)
TR <- rep(25, 22)
FA <- c(rep(21, 8), rep(6, 6), rep(6, 8))
#
# read MPM example data
#
library(qMRI)
mpm <- readMPMData(t1Files, pdFiles, mtFiles,
                  maskFile, TR = TR, TE = TE,
                  FA = FA, verbose = FALSE)
#
# Estimate Parameters in the ESTATICS model
#
modelMPM <- estimateESTATICS(mpm, method = "NLR")
#
# resulting ESTATICS parameter maps for central coronal slice
#
if(require(adimpro)){
  rimage.options(zquantiles=c(.01,.99), ylab="z")
  oldpar <- par(mfrow=c(2,2),mar=c(3,3,3,1),mgp=c(2,1,0))
  pnames <- c("T1", "MT", "PD", "R2star")
```

```
modelCoeff <- extract(modelMPM,"modelCoeff")
for(i in 1:4){
  rimage(modelCoeff[i,,11,])
  title(pnames[i])
}
}
#
# Compute quantitative maps (R1, R2star, PD, MT)
#
qMRIMaps <- calculateQI(modelMPM,
                        b1File = B1File,
                        TR2 = 3.4)
#
# resulting quantitative maps for central coronal slice
#
if(require(adimpro)){
  rimage.options(zquantiles=c(.01,.99), ylab="z")
  par(mfrow=c(2,2),mar=c(3,3,3,1),mgp=c(2,1,0))
  nmaps <- c("R1","R2star","PD","MT")
  qmap <- extract(qMRIMaps,nmaps)
  for (i in 1:4) rimage(qmap[[i]][,11,],main=nmaps[i])
}
#
# write qmaps
#
writeQI(qMRIMaps, dir=outDir, prefix="qmap")
par(oldpar)
```



# Index

- \* **IO**
    - readMPMData, [15](#)
    - writeESTATICS, [20](#)
    - writeQI, [22](#)
  - \* **datasets**
    - colMT, [8](#)
  - \* **manip**
    - extract-methods, [11](#)
  - \* **methods**
    - extract-methods, [11](#)
  - \* **models**
    - calculateQI, [5](#)
    - estimateESTATICS, [8](#)
  - \* **model**
    - smoothESTATICS, [17](#)
  - \* **package**
    - qMRI-package, [2](#)
  - \* **regression**
    - estimateESTATICS, [8](#)
  - \* **smooth**
    - smoothESTATICS, [17](#)
  - [.ANY-method (extract-methods), [11](#)
  - [.ESTATICSModel (extract-methods), [11](#)
  - [.MPMData (extract-methods), [11](#)
  - [.qMaps (extract-methods), [11](#)
  - [.sESTATICSModel (extract-methods), [11](#)
- aws, [3](#)
- awsLocalSigma, [6](#), [10](#), [16](#)
- calculateQI, [5](#), [10](#), [16](#), [22](#), [23](#)
- colMT, [8](#)
- estimateESTATICS, [5](#), [6](#), [8](#), [16](#), [18](#), [19](#), [21](#), [23](#)
- extract-methods, [11](#)
- extract.ANY-method (extract-methods), [11](#)
- extract.ESTATICSModel  
(extract-methods), [11](#)
- extract.MPMData (extract-methods), [11](#)
- extract.qMaps (extract-methods), [11](#)
- extract.sESTATICSModel  
(extract-methods), [11](#)
- qMRI (qMRI-package), [2](#)
- qMRI-package, [2](#)
- readMPMData, [6](#), [9](#), [10](#), [15](#), [18](#), [19](#), [21](#), [23](#)
- smoothESTATICS, [6](#), [10](#), [16](#), [17](#), [21](#)
- writeESTATICS, [6](#), [10](#), [16](#), [20](#)
- writeQI, [22](#)