

Package ‘rcites’

October 14, 2022

Type Package

Title R Interface to the Species+ Database

Version 1.2.0

Description A programmatic interface to the Species+ <<https://speciesplus.net/>> database via the Species+/CITES Checklist API <<https://api.speciesplus.net/>>.

URL <https://docs.ropensci.org/rcites/>,
<https://github.com/ropensci/rcites>

BugReports <https://github.com/ropensci/rcites/issues>

License MIT + file LICENSE

Depends R (>= 3.1.0)

Imports cli, curl, httr, jsonlite

Suggests knitr, testthat, tibble, rmarkdown, rworldmap (>= 1.3.6), vcr (>= 0.6.0)

Encoding UTF-8

RoxygenNote 7.1.2

VignetteBuilder knitr

Config/testthat/edition 3

NeedsCompilation no

Author Kevin Cazelles [aut, cre] (<<https://orcid.org/0000-0001-6619-9874>>),
Jonas Geschke [aut] (<<https://orcid.org/0000-0002-5654-9313>>),
Ignasi Bartomeus [aut] (<<https://orcid.org/0000-0001-7893-4389>>),
Jonathan Goldenberg [ctb],
Marie-Bé Leduc [ctb],
Yasmine Verzelen [ctb],
Noam Ross [rev],
Margaret Siple [rev]

Maintainer Kevin Cazelles <kevin.cazelles@gmail.com>

Repository CRAN

Date/Publication 2021-11-04 20:20:02 UTC

R topics documented:

print.spp	2
set_token	3
spp_cites_legislation	4
spp_distributions	5
spp_eu_legislation	7
spp_references	8
spp_taxonconcept	9

Index	12
--------------	-----------

print.spp	<i>Print methods for objects of class spp_raw*.</i>
-----------	---

Description

Print the outputs of a Species+ API call.

Usage

```
## S3 method for class 'spp_raw'
print(x, ...)

## S3 method for class 'spp_raw_multi'
print(x, ...)

## S3 method for class 'spp_cites_leg'
print(x, ...)

## S3 method for class 'spp_cites_leg_multi'
print(x, ...)

## S3 method for class 'spp_distr'
print(x, ...)

## S3 method for class 'spp_distr_multi'
print(x, ...)

## S3 method for class 'spp_eu_leg'
print(x, ...)

## S3 method for class 'spp_eu_leg_multi'
print(x, ...)

## S3 method for class 'spp_refs'
print(x, ...)
```

```
## S3 method for class 'spp_refs_multi'  
print(x, ...)  
  
## S3 method for class 'spp_taxon'  
print(x, ...)
```

Arguments

x an object of class spp_raw*.
... ignored.

Value

The JSON result.

set_token	<i>Login helper function</i>
-----------	------------------------------

Description

Set and forget the authentication token for the current session.

Usage

```
set_token(token = NULL)  
  
forget_token()
```

Arguments

token a character string (with quotes) containing your token. If NULL, then the token can be passed without quotes (not as character string) after a prompt.

Functions

- set_token: set the environment variable SPECIESPLUS_TOKEN.
- forget_token: forget the environment variable SPECIESPLUS_TOKEN.

References

<https://api.speciesplus.net/documentation>

Examples

```
## Not run:
# NB: the token below is not working
set_token('8QW6Qgh57sBG2k0gtt')
# interactively
set_token()

## End(Not run)
```

spp_cites_legislation *Get current CITES appendix listings and reservations*

Description

Retrieve current CITES appendix listings and reservations, CITES quotas, and CITES suspensions for a given taxon concept.

Usage

```
spp_cites_legislation(
  taxon_id,
  scope = "current",
  language = "en",
  raw = FALSE,
  token = NULL,
  verbose = TRUE,
  pause = 1,
  ...
)
```

Arguments

taxon_id	a vector of character strings containing species' taxon concept identifiers (see spp_taxonconcept()).
scope	vector of character strings indicating the time scope of legislation, values are taken among current, historic and all. Default is current.
language	vector of character strings indicating the language for the text of legislation notes, values are taken among en (English), fr (French) and es (Spanish). Default is en.
raw	a logical. Should raw data be returned?
token	a character string containing the authentication token, see https://api.speciesplus.net/documentation . Default is set to NULL and requires the environment variable SPECIESPLUS_TOKEN to be set directly in Renvi ron. Alternatively, set_token() can be used to set SPECIESPLUS_TOKEN for the current session.
verbose	a logical. Should extra information be reported on progress?

pause a duration (in second) to suspend execution for (see `Sys.sleep()`). This was added cause the web API returns a 404 error too many requests in a short time interval.

... Further named parameters, see `httr::GET()`.

Value

If `raw` is set to `TRUE` then an object of class `spp_raw` (or `spp_raw_multi` if `length(taxon_id) > 1`) is returned which is essentially a list of lists (see option `as = 'parsed'` in `httr::content()`). Otherwise, an object of class `spp_cites_leg` (or `spp_cites_leg_multi` if `length(taxon_id) > 1`) is returned which is a list of three data frames:

1. `cites_listings`: lists CITES annex listings EU suspensions,
2. `cites_quotas`: lists CITES quotas,
3. `cites_suspensions`: lists CITES suspensions.

References

https://api.speciesplus.net/documentation/v1/cites_legislation/index.html

Examples

```
res1 <- spp_cites_legislation(taxon_id = 4521)
res2 <- spp_cites_legislation(taxon_id = c('4521', '3210', '10255'))
res3 <- spp_cites_legislation(taxon_id = 4521, scope = 'all',
  verbose = FALSE, config=httr::verbose())
res4 <- spp_cites_legislation(taxon_id = 4521, language = 'fr')
```

`spp_distributions` *Get distributions data available for a given taxon concept*

Description

Retrieve distributions data available for a given taxon concept for which the the taxon identifier is known.

Usage

```
spp_distributions(
  taxon_id,
  language = "en",
  raw = FALSE,
  token = NULL,
  verbose = TRUE,
  pause = 1,
  ...
)
```

Arguments

taxon_id	a vector of character strings containing species' taxon concept identifiers (see spp_taxonconcept()).
language	vector of character strings indicating the language for the names of distributions, values are taken among en (English), fr (French) and es (Spanish). Default is en.
raw	a logical. Should raw data be returned?
token	a character string containing the authentication token, see https://api.speciesplus.net/documentation . Default is set to NULL and requires the environment variable SPECIESPLUS_TOKEN to be set directly in Renvirom. Alternatively, <code>set_token()</code> can be used to set SPECIESPLUS_TOKEN for the current session.
verbose	a logical. Should extra information be reported on progress?
pause	a duration (in second) to suspend execution for (see Sys.sleep()). This was added cause the web API returns a 404 error too many requests in a short time interval.
...	Further named parameters, see httr::GET() .

Value

If `raw` is set to `TRUE` then an object of class `spp_raw` (or `spp_raw_multi` if `length(taxon_id)>1`) is returned which is essentially a list of lists (see option `as = 'parsed'` in [httr::content\(\)](#)). Otherwise, an object of class `spp_distr` (or `spp_distr_multi` if `length(taxon_id) > 1`) is returned which is a list of two data frames:

1. `distributions`: lists distributions for a given taxon concept,
2. `references`: lists the corresponding references. In case `taxon_id` includes several elements

References

<https://api.speciesplus.net/documentation/v1/distributions/index.html>

Examples

```
res1 <- spp_distributions(taxon_id = '4521')
res2 <- spp_distributions(taxon_id = c('4521', '3210', '10255'))
res3 <- spp_distributions(taxon_id = '4521', raw = TRUE)
res4 <- spp_distributions(taxon_id = '4521', language = 'fr',
  verbose = FALSE, config = httr::progress())
```

spp_eu_legislation *Get current EU annex listings, SRG opinions, and EU suspensions*

Description

Retrieve current EU annex listings, SRG opinions, and EU suspensions for a given taxon concept (identifier must be known).

Usage

```
spp_eu_legislation(
  taxon_id,
  scope = "current",
  language = "en",
  raw = FALSE,
  token = NULL,
  verbose = TRUE,
  pause = 1,
  ...
)
```

Arguments

taxon_id	a vector of character strings containing species' taxon concept identifiers (see spp_taxonconcept()).
scope	vector of character strings indicating the time scope of legislation, values are taken among current, historic and all. Default is set to current.
language	vector of character strings indicating the language for the text of legislation notes, values are taken among en (English), fr (French) and es (Spanish). Default is en.
raw	a logical. Should raw data be returned?
token	a character string containing the authentication token, see https://api.speciesplus.net/documentation . Default is set to NULL and requires the environment variable SPECIESPLUS_TOKEN to be set directly in Renvi ron. Alternatively, set_token() can be used to set SPECIESPLUS_TOKEN for the current session.
verbose	a logical. Should extra information be reported on progress?
pause	a duration (in second) to suspend execution for (see Sys.sleep()). This was added cause the web API returns a 404 error too many requests in a short time interval.
...	Further named parameters, see httr::GET() .

Value

If `raw` is set to `TRUE` then an object of class `spp_raw` (or `spp_raw_multi` if `length(taxon_id)>1`) is returned which is essentially a list of lists (see option `as = 'parsed'` in `httr::content()`). Otherwise, an object of class `spp_eu_leg` (or `spp_eu_leg_multi` if `length(taxon_id)>1`) is returned which is a list of two data frames:

1. `eu_listings`: lists EU annex listings EU suspensions,
2. `eu_decisions`: lists EU decisions

References

https://api.speciesplus.net/documentation/v1/eu_legislation/index.html

Examples

```
res1 <- spp_eu_legislation(taxon_id = '4521')
res2 <- spp_eu_legislation(taxon_id = c('4521', '3210', '10255'))
res3 <- spp_eu_legislation(taxon_id = '4521', scope = 'historic')
res4 <- spp_eu_legislation(taxon_id = '4521', scope = 'all', language='fr',
  verbose = FALSE, config=httr::verbose())
```

spp_references

Get references for a given taxon concept

Description

Retrieve available references for a given taxon concept.

Usage

```
spp_references(
  taxon_id,
  raw = FALSE,
  token = NULL,
  verbose = TRUE,
  pause = 1,
  ...
)
```

Arguments

`taxon_id` a vector of character strings containing species' taxon concept identifiers (see `spp_taxonconcept()`).

`raw` a logical. Should raw data be returned?

token	a character string containing the authentication token, see https://api.speciesplus.net/documentation . Default is set to NULL and requires the environment variable SPECIESPLUS_TOKEN to be set directly in Renvi ron. Alternatively, <code>set_token()</code> can be used to set SPECIESPLUS_TOKEN for the current session.
verbose	a logical. Should extra information be reported on progress?
pause	a duration (in second) to suspend execution for (see <code>Sys.sleep()</code>). This was added cause the web API returns a 404 error too many requests in a short time interval.
...	Further named parameters, see <code>httr::GET()</code> .

Value

If `raw` is set to TRUE then an object of class `spp_raw` (or `spp_raw_multi` if `length(taxon_id) > 1`) is returned which is essentially a list of lists (see option `as = 'parsed'` in `httr::content()`). Otherwise, an object of class `spp_refs` (or `spp_refs_multi` if `length(taxon_id) > 1`) is returned which is a list of one data frame:

- references that includes the identifier of the reference and the corresponding citation.

References

<https://api.speciesplus.net/documentation/v1/references/index.html>

Examples

```
res1 <- spp_references(taxon_id = '4521')
res2 <- spp_references(c('4521', '3210', '10255'))
res3 <- spp_references(taxon_id = '4521', raw = TRUE, verbose = FALSE,
  config = httr::progress())
```

spp_taxonconcept	<i>Get taxon concepts for a search term</i>
------------------	---

Description

Retrieve the taxon concept of a specific taxon (scientific name).

Usage

```
spp_taxonconcept(
  query_taxon,
  taxonomy = "CITES",
  with_descendants = FALSE,
  language = NULL,
  updated_since = NULL,
```

```

per_page = 500,
pages = NULL,
raw = FALSE,
token = NULL,
verbose = TRUE,
pause = 1,
...
)

```

Arguments

query_taxon	a character string containing the query (e.g. species). Scientific taxa only (max 255 characters).
taxonomy	filter taxon concepts by taxonomy, accepts either 'CITES' or 'CMS' as its value. Default sets to 'CITES'.
with_descendants	a logical. Should the search by name be broadened to include higher taxa?
language	filter languages returned for common names. Value should be a vector of character strings including one or more country codes (two-letters country code ISO 3166-1 alpha-2). Default is set to NULL, showing all available languages.
updated_since	a timestamp. Only entries updated after (and including) this timestamp will be pulled.
per_page	an integer that indicates how many objects are returned per page for paginated responses. Default set to 500 which is the maximum.
pages	a vector of integer that contains page numbers. Default is set to NULL, i.e. all pages are accessed.
raw	a logical. Should raw data be returned?
token	a character string containing the authentication token, see https://api.speciesplus.net/documentation . Default is set to NULL and requires the environment variable SPECIESPLUS_TOKEN to be set directly in Renvi ron. Alternatively, set_token() can be used to set SPECIESPLUS_TOKEN for the current session.
verbose	a logical. Should extra information be reported on progress?
pause	a duration (in second) to suspend execution for (see Sys.sleep()). This was added cause the web API returns a 404 error too many requests in a short time interval.
...	Further named parameters, see http::GET() .

Value

If raw = TRUE, then a object of class spp_raw is returned, which is a list of lists. If raw = FALSE, then an object of class spp_taxon is returned, it is a collection of seven data frames:

1. all_id: general information for all entries, including non-active taxon concepts,
2. general: includes general information for active taxon concepts,
3. higher_taxa: includes taxonomy information,

4. `accepted_names`: list of accepted names (only for synonyms),
5. `common_names`: list of common names (only for accepted names),
6. `synonyms`: list of synonyms (only for accepted names),
7. `cites_listing`: list of current CITES listings with annotations (missing if `taxonomy == 'CMS'`).

References

https://api.speciesplus.net/documentation/v1/taxon_concepts/index.html

Examples

```
res1 <- spp_taxonconcept(query_taxon = 'Loxodonta africana')
res2 <- spp_taxonconcept(query_taxon = 'Amazilia versicolor', raw = TRUE)
res3 <- spp_taxonconcept(query_taxon = '', taxonomy = 'CMS', pages = c(1, 3),
  language = 'EN', config = htr::progress())
res4 <- spp_taxonconcept(query_taxon = '', per_page = 20, pages = 44)
```

Index

`forget_token (set_token)`, 3

`httr::content()`, 5, 6, 8, 9

`httr::GET()`, 5–7, 9, 10

`print.spp`, 2

`print.spp_cites_leg (print.spp)`, 2

`print.spp_cites_leg_multi (print.spp)`, 2

`print.spp_distr (print.spp)`, 2

`print.spp_distr_multi (print.spp)`, 2

`print.spp_eu_leg (print.spp)`, 2

`print.spp_eu_leg_multi (print.spp)`, 2

`print.spp_raw (print.spp)`, 2

`print.spp_raw_multi (print.spp)`, 2

`print.spp_refs (print.spp)`, 2

`print.spp_refs_multi (print.spp)`, 2

`print.spp_taxon (print.spp)`, 2

`set_token`, 3

`set_token()`, 4, 7, 9

`spp_cites_legislation`, 4

`spp_distributions`, 5

`spp_eu_legislation`, 7

`spp_references`, 8

`spp_taxonconcept`, 9

`spp_taxonconcept()`, 4, 6–8

`Sys.sleep()`, 5–7, 9, 10