

Package ‘rcssci’

November 7, 2022

Type Package

Title Visualization of Restricted Cubic Splines

Version 0.2.0

Maintainer Zhiqiang Nie <niezhiqiang@gdph.org.cn>

Description Restricted Cubic Splines were performed to explore the shape of association form of ``U, inverted U, L" shape and test linearity or non-linearity base on ``Cox,Logistic,linear" regression, and auto output Restricted Cubic Splines figures.
The Restricted Cubic Splines method were based on Suli Huang (2022) <doi:10.1016/j.ecoenv.2022.113183>, Amit Kaura (2019) <doi:10.1136/bmj.l6055>, and Harrell Jr (2015, ISBN:978-3-319-19424-0 (Print) 978-3-319-19425-7 (Online)).

Depends R (>= 4.2.0)

LazyData true

Imports pacman, rms, ggplot2, survminer, segmented, survival, dplyr, patchwork, Cairo

Encoding UTF-8

License Artistic-2.0

BugReports <https://github.com/popnie/RCSsci/issues>

RoxygenNote 7.2.1

NeedsCompilation no

Author Zhiqiang Nie [aut, cre, cph] (ORCID = 0000-0001-7642-3286, wechat = Biostatistics-SCI), JunZhang [ctb], Chaolei Chen [ctb]

Repository CRAN

Date/Publication 2022-11-07 14:50:02 UTC

R topics documented:

rcssci_cox 2

rcssci_linear	3
rcssci_logistic	4
rsc_cox.lshap	5
rsc_cox.nshap	6
rsc_cox.prob	7
rsc_cox.ushap	8
rsc_linear.lshap	9
rsc_linear.nshap	10
rsc_linear.prob	11
rsc_linear.ushap	12
rsc_logistic.lshap	13
rsc_logistic.nshap	14
rsc_logistic.prob	15
rsc_logistic.ushap	16
sbpdata	17

Index	18
--------------	-----------

rcssci_cox

rcssci_cox

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	sensor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcssci_cox(data=sbpdata, y = "status", x = "sbp", time = "time",
prob=0.1, filepath=tempdir())
# library(rcssci)
# rcssci_cox(knot=4, data=sbpdata, y = "status", x = "sbp", covs=c("age"),
# time = "time", prob=0.1, filepath="D:/temp")
```

rcssci_linear

rcssci_linear

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter, range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U, J, S, L, log, -log, temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcssci_linear(data=sbpdata, y = "sbp", x = "age",
prob=0.1, filepath=tempdir())
# library(rcssci)
# rcssci_linear(knot=4, data=sbpdata, y = "sbp", x = "age",
# covs=c("gender"), prob=0.1, filepath="D:/temp")
```

rcssci_logistic

rcssci_logistic

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter, range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U, J, S, L, log, -log, temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcssci_logistic(data=sbpdata, y = "status", x = "sbp",
prob=0.1, filepath=tempdir())
# library(rcssci)
# rcssci_logistic(knot=4, data=sbpdata, y = "status", x = "sbp",
# covs=c("age", "gender"), prob=0.1, filepath="D:/temp")
```

rcox.lshap	<i>rcox.lshap</i>
------------	-------------------

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	sensor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcox.lshap(data=sbpdata, y = "status", x = "sbp", time = "time",
prob=0.1, filepath=tempdir())
# library(rcssci)
# rcox.lshap(knot=4, data=sbpdata, y = "status", x = "sbp", covs=c("age"),
# time = "time", prob=0.1, filepath="D:/temp")
```

 rcs_cox.nshap

rcs_cox.nshap

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	sensor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_cox.nshap(data=sbpdata, y = "status", x = "sbp", time = "time",
prob=0.1, filepath=tempdir())
# library(rcssci)
# rcs_cox.nshap(knot=4, data=sbpdata, y = "status", x = "sbp", covs=c("age"),
# time = "time", prob=0.1, filepath="D:/temp")
```

rcox_prob	<i>rcox_prob</i>
-----------	------------------

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	sensor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcox_prob(data=sbpdata, y = "status",x = "sbp",time = "time",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcox_prob(knot=4,data=sbpdata, y = "status",x = "sbp",covs=c("age"),
# time = "time", prob=0.1,filepath="D:/temp")
```

 rcs_cox.ushap

rsc_cox.ushap

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
time	sensor time
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

Cox models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rsc_cox.ushap(data=sbpdata, y = "status",x = "sbp",time = "time",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rsc_cox.ushap(knot=4,data=sbpdata, y = "status",x = "sbp",covs=c("age"),
# time = "time", prob=0.1,filepath="D:/temp")
```

r _{cs} _linear.lshap	<i>r_{cs}_linear.lshap</i>
-------------------------------	------------------------------------

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_linear.lshap(data=sbpdata, y = "sbp", x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_linear.lshap(knot=4,data=sbpdata, y = "sbp", x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

rcs_linear.nshap *rcs_linear.nshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_linear.nshap(data=sbpdata, y = "sbp", x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci
# rcs_linear.nshap(knot=4,data=sbpdata, y = "sbp", x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

rsc_linear.prob	<i>rsc_linear.prob</i>
-----------------	------------------------

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rsc_linear.prob(data=sbpdata, y = "sbp", x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rsc_linear.prob(knot=4,data=sbpdata, y = "sbp", x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

rcs_linear.ushap *rcs_linear.ushap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

linear models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_linear.ushap(data=sbpdata, y = "sbp", x = "age",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_linear.ushap(knot=4,data=sbpdata, y = "sbp", x = "age",
# covs=c("gender"),prob=0.1,filepath="D:/temp")
```

rsc_logistic.lshap *rsc_logistic.lshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rsc_logistic.lshap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rsc_logistic.lshap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcs_logistic.nshap *rcs_logistic.nshap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_logistic.nshap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_logistic.nshap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rsc_logistic.prob *rsc_logistic.prob*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rsc_logistic.prob(data=sbpdata, y = "status", x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rsc_logistic.prob(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age","gender"),prob=0.1,filepath="D:/temp")
```

rcs_logistic.ushap *rcs_logistic.ushap*

Description

restricted cubic splines (RCS) published in SCI.

Arguments

data	data.frame.Rdata
knot	knot=3-7 or automatic calculate by AIC min
y	outcome=0,1
covs	covariables, univariate analysis without "covs" command, multivariable analysis with "covs" command
prob	position parameter,range from 0-1
x	main exposure and X-axis when plotting
filepath	path of plots output.

Details

logistic models with RCS splines were performed to explore the shape linear or nonlinear(U, inverted U,J,S,L,log,-log,temporary plateau shape)

Value

message.print PH assumption and other message

Author(s)

Zhiqiang Nie, <niezhiqiang@gdph.org.cn>

Examples

```
library(rcssci)
rcs_logistic.ushap(data=sbpdata, y = "status",x = "sbp",
prob=0.1,filepath=tempdir())
# library(rcssci)
# rcs_logistic.ushap(knot=4,data=sbpdata, y = "status",x = "sbp",
# covs=c("age", "gender"),prob=0.1,filepath="D:/temp")
```

sbpdata	<i>A data on sbp and status.</i>
---------	----------------------------------

Description

A data on sbp and status.

Usage

```
data(sbpdata)
```

Format

An object of class `tbl_df` (inherits from `tbl`, `data.frame`) with 3621 rows and 5 columns.

Examples

```
data(sbpdata)
```

Index

* datasets

sbpdata, [17](#)

rsc_cox.lshap, [5](#)

rsc_cox.nshap, [6](#)

rsc_cox.prob, [7](#)

rsc_cox.ushap, [8](#)

rsc_linear.lshap, [9](#)

rsc_linear.nshap, [10](#)

rsc_linear.prob, [11](#)

rsc_linear.ushap, [12](#)

rsc_logistic.lshap, [13](#)

rsc_logistic.nshap, [14](#)

rsc_logistic.prob, [15](#)

rsc_logistic.ushap, [16](#)

rcssci_cox, [2](#)

rcssci_linear, [3](#)

rcssci_logistic, [4](#)

sbpdata, [17](#)