

Package ‘rdss’

January 17, 2023

Title Companion Datasets and Functions for Research Design in the Social Sciences

Version 1.0.0

Description Helper functions to accompany the Blair, Coppock, and Humphreys (2022) “Research Design in the Social Sciences: Declaration, Diagnosis, and Re-design” <<https://book.declaredesign.org>>. ‘rdss’ includes datasets, helper functions, and plotting components to enable use and replication of the book.

Imports dplyr, rlang (>= 1.0.0), generics, ggplot2, tibble, tidyr, dataverse, readr, prediction, broom, purrr, estimatr, randomizr

License MIT + file LICENSE

Encoding UTF-8

LazyData true

RoxygenNote 7.2.3

Suggests testthat (>= 3.0.0), rdrobust, DIDmultiplegt, broom.mixed, grf, CausalQueries, metafor, cjoint, lme4, rstanarm, spdep, DeclareDesign

Depends R (>= 2.10)

Config/testthat/edition 3

NeedsCompilation no

Author Graeme Blair [aut, cre] (<<https://orcid.org/0000-0001-9164-2102>>), Alexander Coppock [aut] (<<https://orcid.org/0000-0002-5733-2386>>), Macartan Humphreys [aut] (<<https://orcid.org/0000-0001-7029-2326>>)

Maintainer Graeme Blair <graeme.blair@gmail.com>

Repository CRAN

Date/Publication 2023-01-17 17:40:02 UTC

R topics documented:

add_parens	2
best_predictor	3
bonilla_tillery	3

causal_forest_handler	4
clingingsmith_etal	5
conjoint_assignment	5
conjoint_inquiries	6
conjoint_measurement	6
dd_palette	7
did_multiplegt_tidy	8
estimator_AS_tidy	8
fairfax	9
foos_etal	9
format_num	10
get_exposure_AS	10
get_rdss_file	11
hex_add_alpha	11
lag_by_group	12
la_voter_file	12
make_interval_entry	13
make_se_entry	13
post_stratification_helper	14
process_tracing_estimator	15
rdrobust_helper	16
rdss	16
rma_helper	17
rma_mu_tau	17
theme_dd	18
tidy.amce	18
tidy.rdrobust	19
tidy_stan	20

Index **21**

add_parens	<i>Add parentheses around standard error estimates</i>
------------	--

Description

Add parentheses around standard error estimates

Usage

```
add_parens(x, digits = 3)
```

Arguments

x	Numeric vector
digits	Number of digits to retain

Value

A character vector with enclosing parentheses

Examples

```
std.error <- c(0.12, 0.001, 1.2)
add_parens(std.error)
```

best_predictor	<i>Best predictor function from causal_forest</i>
----------------	---

Description

Best predictor function from causal_forest

Usage

```
best_predictor(data, covariate_names, cuts = 20)
```

Arguments

data	A data.frame of covariates
covariate_names	A character vector of covariates to assess
cuts	Either a numeric vector of two or more unique cut points or a single number (greater than or equal to 2) giving the number of intervals into which each covariate is to be cut.

Value

a data.frame of the best predictors

bonilla_tillery	<i>Replication data for Bonilla and Tillery (2020), American Political Science Review (obtained from Dataverse 10.7910/DVN/IUZDQI)</i>
-----------------	--

Description

Replication data for Bonilla and Tillery (2020), American Political Science Review (obtained from Dataverse 10.7910/DVN/IUZDQI)

Usage

```
bonilla_tillery
```

Format

A data.frame

causal_forest_handler *Tidy helper function for causal_forest function*

Description

Runs estimates estimation function from interference package and returns tidy data frame output

Usage

```
causal_forest_handler(data, covariate_names, share_train = 0.5, ...)
```

Arguments

data	A data.frame
covariate_names	Names of covariates
share_train	Share of units to be used for training
...	Options to causal_forest

Details

<https://draft.declaredesign.org/complex-designs.html#discovery-using-causal-forests>

See ?causal_forest for further details

Value

a data.frame of estimates

Examples

```
library(DeclareDesign)
library(ggplot2)

dat <- fabricate(
  N = 1000,
  A = rnorm(N),
  B = rnorm(N),
  Z = complete_rs(N),
  Y = A*Z + rnorm(N))

# note: remove num.threads = 1 to use more processors
estimates <- causal_forest_handler(data = dat, covariate_names = c("A", "B"), num.threads = 1)

ggplot(data = estimates, aes(A, pred)) + geom_point()
```

clingingsmith_etal	<i>Replication data for David Clingingsmith, Asim Ijaz Khwaja, Michael Kremer (2020): Estimating the Impact of The Hajj: Religion and Tolerance in Islam's Global Gathering. The Quarterly Journal of Economics, Volume 124, Issue 3, August 2009, Pages 1133–1170</i>
--------------------	--

Description

Replication data for David Clingingsmith, Asim Ijaz Khwaja, Michael Kremer (2020): Estimating the Impact of The Hajj: Religion and Tolerance in Islam's Global Gathering. The Quarterly Journal of Economics, Volume 124, Issue 3, August 2009, Pages 1133–1170

Usage

```
clingingsmith_etal
```

Format

A data.frame

conjoint_assignment	<i>Conjoint experiment assignment handler: conducts complete random assignment of all attribute levels</i>
---------------------	--

Description

See <https://book.declaredesign.org/experimental-descriptive.html#conjoint-experiments>

Usage

```
conjoint_assignment(data, levels_list)
```

Arguments

data	A data.frame
levels_list	List of conjoint levels to assign

Value

a data.frame with random assignment added

conjoint_inquiries *Conjoint experiment inquiries handler*

Description

See <https://book.declaredesign.org/experimental-descriptive.html#conjoint-experiments>

Usage

```
conjoint_inquiries(data, levels_list, utility_fn)
```

Arguments

data	A data.frame
levels_list	List of conjoint levels
utility_fn	a function that takes data and returns an additional column called U, which represents the utility of the choice

Value

a data.frame of estimand values

conjoint_measurement *Conjoint experiment assignment handler: conducts complete random assignment of all attribute levels*

Description

See <https://book.declaredesign.org/experimental-descriptive.html#conjoint-experiments>

Usage

```
conjoint_measurement(data, utility_fn)
```

Arguments

data	A data.frame
utility_fn	a function that takes data and returns an additional column called U, which represents the utility of the choice

Value

a data.frame

dd_palette	<i>Access color palette used in the book "Research Design: Declare, Diagnose, Redesign" (Blair, Coppock, Humphreys)</i>
------------	---

Description

Based on Karthik Ram's wesanderson package (<https://github.com/karthik/wesanderson>)

Usage

```
dd_palette(name, n)
```

Arguments

name	Color palette name (character)
n	Number of colors

Details

Available color palettes:

```
color_palette = c("#72B4F3", "#F38672", "#C6227F")
```

```
grey_palette = c("#72B4F3", "#F38672", "#C6227F", gray(0.8))
```

```
dd_dark_blue = "#3564ED"
```

```
dd_light_blue = "#72B4F3"
```

```
dd_orange = "#F38672"
```

```
dd_purple = "#7E43B6"
```

```
dd_gray = gray(0.2)
```

```
dd_pink = "#C6227F"
```

```
dd_light_gray = gray(0.8)
```

```
dd_dark_blue_alpha = "#3564EDA0"
```

```
dd_light_blue_alpha = "#72B4F3A0"
```

Value

character vector of colors

`did_multiplegt_tidy` *Tidy helper function for did_multiplegt*

Description

Runs `did_multiplegt` estimation function and returns tidy data frame output

Usage

```
did_multiplegt_tidy(data, ...)
```

Arguments

<code>data</code>	a data.frame
<code>...</code>	options passed to <code>did_multiplegt</code>

Details

See <https://book.declaredesign.org/observational-causal.html#difference-in-differences>

Value

a data.frame of estimates

`estimator_AS_tidy` *Tidy helper function for estimator_AS function*

Description

Runs `estimates` estimation function from `interference` package and returns tidy data frame output

Usage

```
estimator_AS_tidy(data, permutatation_matrix, adj_matrix)
```

Arguments

<code>data</code>	a data.frame
<code>permutatation_matrix</code>	a permutation matrix of random assignments
<code>adj_matrix</code>	an adjacency matrix

Details

The estimator_AS_tidy function requires the 'interference' package, which is not yet available on CRAN.

To use this function:

1. install the developer version of interference via `remotes::install_github('szonszein/interference')` and
2. install the developer version of rdss via `remotes::install_github('DeclareDesign/rdss@remotes')`

See <https://book.declaredesign.org/experimental-causal.html#experiments-over-networks>

Value

a data.frame of estimates

<code>fairfax</code>	<i>Shapefile of Fairfax County, Virginia, voting precincts</i>
----------------------	--

Description

An sf object containing the boundaries of voting precincts for Fairfax County, Virginia as well as precinct ID, name, district, polling place name, address, city, zip code, area, length, and geometry (polygons)

Usage

```
fairfax
```

Format

An sf object with 236 rows and 10 variables:

<code>foos_etal</code>	<i>Replication data for Foos, John, Muller, and Cunningham (2021), Journal of Politics (derived from from Dataverse 10.7910/DVN/NDPXND)</i>
------------------------	---

Description

Replication data for Foos, John, Muller, and Cunningham (2021), Journal of Politics (derived from from Dataverse 10.7910/DVN/NDPXND)

Usage

```
foos_etal
```

Format

A data.frame

format_num	<i>Round and pad a number to a specific decimal place</i>
------------	---

Description

Round and pad a number to a specific decimal place

Usage

```
format_num(x, digits = 3)
```

Arguments

x	Numeric vector
digits	Number of digits to retain

Value

a character vector of formatted numbers

Examples

```
std.error <- c(0.12, 0.001, 1.2)
format_num(std.error)
```

get_exposure_AS	<i>Helper function to obtain the observed exposure for the Aronow and Samii estimator</i>
-----------------	---

Description

See <https://book.declaredesign.org/experimental-causal.html#experiments-over-networks>

Usage

```
get_exposure_AS(obs_exposure)
```

Arguments

obs_exposure	A numeric vector
--------------	------------------

Value

a data.frame of observed exposure to a treatment created using the interference package

get_rdss_file	<i>Download a replication file from the dataverse archive for Research Design in the Social Sciences: Declaration, Diagnosis, and Redesign</i>
---------------	--

Description

See <https://dataverse.harvard.edu/dataset.xhtml?persistentId=doi:10.7910/DVN/HYVPO5> for a full list of available files

Usage

```
get_rdss_file(name)
```

Arguments

name quoted name of the file on the dataverse archive

Value

an r object

Examples

```
diagnosis_2.1 <- get_rdss_file("diagnosis_2.1")  
diagnosis_2.1
```

hex_add_alpha	<i>Add alpha transparency to a color defined in hexadecimal</i>
---------------	---

Description

Add alpha transparency to a color defined in hexadecimal

Usage

```
hex_add_alpha(col, alpha)
```

Arguments

col Original color code in hex
alpha Level of alpha transparency to add

Value

color codes with alpha added

lag_by_group	<i>Generate lags in grouped data</i>
--------------	--------------------------------------

Description

See <https://book.declaredesign.org/observational-causal.html#difference-in-differences>

Usage

```
lag_by_group(x, groups, n = 1, order_by, default = NA)
```

Arguments

x	Vector of values
groups	Grouping variable
n	Positive integer of length 1, giving the number of positions to lead or lag by
order_by	Ordering variable withing group (e.g., time)
default	Value used for non-existent rows. Defaults to NA.

Value

vector of lagged values

la_voter_file	<i>Voter file sample for Los Angeles County</i>
---------------	---

Description

A dataset containing the party registration, age, census tract number, and voter turnout in 2012 for 1,000 randomly-sampled registered voters in Los Angeles County, California.

Usage

```
la_voter_file
```

Format

A data frame with 1000 rows and 4 variables:

party political party registration
age age of voter in years
census_tract US Census tract number
voted_2012 voter turnout in 2012 election

Source

California Secretary of State.

make_interval_entry *Format confidence intervals for nice printing*

Description

Format confidence intervals for nice printing

Usage

```
make_interval_entry(conf.low, conf.high, digits = 2)
```

Arguments

conf.low	a numeric vector of lower bounds
conf.high	a numeric vector of upper bounds
digits	number of digits to retain

Value

a character vector of intervals

Examples

```
conf.low <- c(-0.1652, 0.00304, -6.352)
conf.high <- c(0.3052, 0.00696, -1.648)

make_interval_entry(conf.low, conf.high)
```

make_se_entry *Format estimates and standard errors for nice printing*

Description

Format estimates and standard errors for nice printing

Usage

```
make_se_entry(estimate, std.error, digits = 2)
```

Arguments

estimate	a numeric vector of parameter estimates
std.error	a numeric vector of standard error estimates
digits	number of digits to retain

Value

a character vector of formatted estimates and standard errors

Examples

```
estimate <- c(0.07, 0.005, -4)
std.error <- c(0.12, 0.001, 1.2)

make_se_entry(estimate, std.error)
```

post_stratification_helper

Post stratification estimator helper

Description

Calculates predicted values from a multilevel regression and the post-stratified state-level estimates

Usage

```
post_stratification_helper(model_fit, data, group, weights)
```

Arguments

model_fit	a model fit object from, e.g., glmer or lm_robust
data	a data.frame
group	unquoted name of the group variable to construct estimates for
weights	unquoted name of post-stratification weights variable

Details

Please see <https://book.declaredesign.org/observational-descriptive.html#multi-level-regression-and-poststratification>

Value

data.frame of post-stratified group-level estimates

process_tracing_estimator
Process tracing estimator

Description

Draw conclusions from a model given a query, data, and process tracing strategies

Usage

```
process_tracing_estimator(causal_model, query, data, strategies)
```

Arguments

causal_model	a model generated by CausalQueries
query	a causal query of interest
data	a single row dataset with data on nodes in the model
strategies	a vector describing sets of nodes to be examined e.g. c("X", "X-Y")

Details

See <https://book.declaredesign.org/observational-causal.html#process-tracing>

Value

a data.frame of estimates

Examples

```
process_tracing_estimator(  
  CausalQueries::make_model("X -> Y"),  
  "Y[X=1] > Y[X=0]",  
  data.frame(X=1, Y = 1),  
  "X-Y")
```

rdrobust_helper	<i>Helper function for using rdrobust as a model in declare_estimator</i>
-----------------	---

Description

Helper function for using rdrobust as a model in declare_estimator

Usage

```
rdrobust_helper(data, y, x, subset = NULL, ...)
```

Arguments

data	a data.frame
y	unquoted name of the outcome variable
x	unquoted name of the running variable
subset	an optional vector specifying a subset of observations to be used in the fitting process
...	Other arguments to rdrobust

Value

rdrobust model fit object

rdss	<i>rdss package</i>
------	---------------------

Description

Companion datasets and functions for the book "Research Design in the Social Sciences: Declaration, Diagnosis, and Redesign" (book.declaredesign.org)

rma_helper	<i>Helper function for rma function in metafor package</i>
------------	--

Description

See <https://book.declaredesign.org/complex-designs.html#meta-analysis>

Usage

```
rma_helper(data, yi, sei, method = "REML", ...)
```

Arguments

data	a data.frame
yi	unquoted variable name of estimates used in meta-analysis
sei	unquoted variable name of standard errors used in meta-analysis
method	character string to specify whether a fixed- or a random/mixed-effects model should be fitted. A fixed-effects model (with or without moderators) is fitted when using method = "FE". Random/mixed-effects models are fitted by setting method equal to one of the following: "DL", "HE", "SJ", "ML", "REML", "EB", "HS", "HSk", or "GENQ". Default is "REML".
...	Further options to be passed to rma

Details

See ?rma for further details

Value

a data.frame of estimates

rma_mu_tau	<i>Extract mu and tau parameters from rma model fit</i>
------------	---

Description

See <https://book.declaredesign.org/complex-designs.html#meta-analysis>

Usage

```
rma_mu_tau(fit)
```

Arguments

fit	Fit object from the rma function in the metafor package
-----	---

Value

a data.frame of estimates

theme_dd	<i>ggplot Theme used in the book "Research Design: Declare, Diagnose, Redesign" (Blair, Coppock, Humphreys)</i>
----------	---

Description

ggplot Theme used in the book "Research Design: Declare, Diagnose, Redesign" (Blair, Coppock, Humphreys)

Usage

```
theme_dd()
```

Value

ggplot theme

tidy.amce	<i>Tidy estimates from the amce estimator</i>
-----------	---

Description

Runs amce estimation function and returns tidy data frame output

Usage

```
## S3 method for class 'amce'
tidy(x, alpha = 0.05, ...)
```

Arguments

x	an amce fit object from cjoint::amce
alpha	Confidence level
...	Extra arguments to pass to tidy

Details

See <https://book.declaredesign.org/experimental-descriptive.html#conjoint-experiments>

Value

a data.frame of estimates

Examples

```
library(cjoint)

data(immigrationconjoint)
data(immigrationdesign)

# Run AMCE estimator using all attributes in the design
results <- amce(Chosen_Immigrant ~ Gender + Education + `Language Skills` +
  `Country of Origin` + Job + `Job Experience` + `Job Plans` +
  `Reason for Application` + `Prior Entry`, data = immigrationconjoint,
  cluster = TRUE, respondent.id = "CaseID", design = immigrationdesign)

# Print summary
tidy(results)
```

tidy.rdrobust

Tidy helper function for rdrobust function

Description

Runs rdrobust estimation function and returns tidy data frame output

Usage

```
## S3 method for class 'rdrobust'
tidy(x, ...)
```

Arguments

x	Model fit object from rdrobust
...	Other arguments (not used)

Details

See <https://book.declaredesign.org/observational-causal.html#regression-discontinuity-designs>

Value

a data.frame of estimates

tidy_stan	<i>Tidy results from a stanreg regression and exponentiate the estimated coefficient</i>
-----------	--

Description

Note no standard errors or other summary statistics are provided

Note no standard errors or other summary statistics are provided

Usage

```
tidy_stan(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

```
tidy_stan(x, conf.int = FALSE, conf.level = 0.95, exponentiate = FALSE, ...)
```

Arguments

x	A stanreg fit from stan_glm
conf.int	Logical indicating whether or not to include a confidence interval in the tidied output. Defaults to FALSE.
conf.level	The confidence level to use for the confidence interval if conf.int = TRUE. Must be strictly greater than 0 and less than 1. Defaults to 0.95, which corresponds to a 95 percent confidence interval.
exponentiate	Logical indicating whether or not to exponentiate the the coefficient estimates. Defaults to FALSE. Note that standard errors are not included when exponentiate = TRUE.
...	Other arguments to broom.mixed::tidy

Details

See <https://book.declaredesign.org/choosing-an-answer-strategy.html#bayesian-formalizations>

See <https://book.declaredesign.org/choosing-an-answer-strategy.html#bayesian-formalizations>

Value

data.frame of results

data.frame of results

Index

* datasets

- bonilla_tillery, [3](#)
- clingingsmith_etal, [5](#)
- fairfax, [9](#)
- foos_etal, [9](#)
- la_voter_file, [12](#)

[add_parens](#), [2](#)

[best_predictor](#), [3](#)

[bonilla_tillery](#), [3](#)

[causal_forest_handler](#), [4](#)

[clingingsmith_etal](#), [5](#)

[conjoint_assignment](#), [5](#)

[conjoint_inquiries](#), [6](#)

[conjoint_measurement](#), [6](#)

[dd_palette](#), [7](#)

[did_multiplegt_tidy](#), [8](#)

[estimator_AS_tidy](#), [8](#)

[fairfax](#), [9](#)

[foos_etal](#), [9](#)

[format_num](#), [10](#)

[get_exposure_AS](#), [10](#)

[get_rdss_file](#), [11](#)

[hex_add_alpha](#), [11](#)

[la_voter_file](#), [12](#)

[lag_by_group](#), [12](#)

[make_interval_entry](#), [13](#)

[make_se_entry](#), [13](#)

[post_stratification_helper](#), [14](#)

[process_tracing_estimator](#), [15](#)

[rdrobust_helper](#), [16](#)

[rdss](#), [16](#)

[rma_helper](#), [17](#)

[rma_mu_tau](#), [17](#)

[theme_dd](#), [18](#)

[tidy.amce](#), [18](#)

[tidy.rdrobust](#), [19](#)

[tidy_stan](#), [20](#)