

Package ‘roger’

November 19, 2022

Type Package

Title Automated Grading of R Scripts

Version 1.3-1

Date 2022-11-19

Description Tools for grading the coding style and documentation of R scripts. This is the R component of Roger the Omni Grader, an automated grading system for computer programming projects based on Unix shell scripts; see <<https://gitlab.com/roger-project>>. The package also provides an R interface to the shell scripts. Inspired by the lintr package.

Depends R (>= 4.0.0)

Imports utils

Suggests tinytest

SystemRequirements roger-base (for interface functions only)

License GPL (>= 2)

URL <https://roger-project.gitlab.io>

BugReports <https://gitlab.com/roger-project/roger-rpkg/-/issues>

Encoding UTF-8

NeedsCompilation no

Author Vincent Goulet [aut, cre],
Samuel Fr chet te [aut],
Jean-Christophe Langlois [aut],
Jim Hester [ctb]

Maintainer Vincent Goulet <vincent.goulet@act.ulaval.ca>

Repository CRAN

Date/Publication 2022-11-19 19:50:02 UTC

R topics documented:

assignment_style	2
commas_style	3
comments_style	4
curly_braces_style	5
documentation_linters	7
getSourceData	9
line_length_style	11
nomagic_style	12
ops_spaces_style	13
parentheses_style	14
roger-interface	16
square_brackets_style	18
trailing_blank_lines_style	19
trailing_whitespace_style	21
unnneeded_concatenation_style	22

Index	24
--------------	-----------

assignment_style	<i>Validation of the Assignment Operator</i>
------------------	--

Description

Check that the left assign symbol (<-) is used to assign values to objects instead of the equation assign symbol (=).

Usage

```
assignment_style(srcData)
```

Arguments

srcData a list as returned by [getSourceData](#).

Details

Although = is a proper assignment symbol at the top-level, its use is discouraged in R. Good coding practices dictate to rather use <- for (left) assignment to objects.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines	faulty line numbers;
message	text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct coding practice
fil <- tempfile(fileext = ".R")
cat("x <- 2", file = fil, sep = "\n")
assignment_style(getSourceData(fil))

## Incorrect coding practice
cat("x = 2", file = fil, sep = "\n")
assignment_style(getSourceData(fil))
```

commas_style

Validation of Spacing Around Commas

Description

Check that commas are never preceded by a space, unless the previous symbol is also a comma, and always followed by one, unless the comma ends the line.

Usage

```
commas_style(srcData)
```

Arguments

srcData a list as returned by [getSourceData](#).

Details

Good coding practices dictate to follow commas by a space, unless it ends its line, and to never put a space before. An exception to the latter rule is consecutive commas, as in indexing of arrays.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines faulty line numbers;
message text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct use of spacing around a comma
fil <- tempfile(fileext = ".R")
cat("x <- c(2, 3, 5)", "crossprod(2,", "x)",
     "a <- array(1:24, 2:4)", "a[1, , ]",
     file = fil, sep = "\n")
commas_style(getSourceData(fil))

## Incorrect use of spacing around a comma
fil <- tempfile(fileext = ".R")
cat("x <- c(2,3, 5)", "crossprod(2 ,", "x)",
     "a <- array(1:24, 2:4)", "a[1,, ]",
     file = fil, sep = "\n")
commas_style(getSourceData(fil))
```

 comments_style

Validation of Comments

Description

Check that comment delimiters and the text of comments, when there is any, are separated by at least one space.

Usage

```
comments_style(srcData)
```

Arguments

srcData a list as returned by [getSourceData](#).

Details

Good coding practices dictate to follow the comment delimiters by at least one space when a comment contains text.

The accepted delimiters are: one or more `\#` symbols possibly followed immediately by any combination of punctuation characters of the `[:punct:]` class (see [regex](#)).

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines	faulty line numbers;
message	text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct comments
fil <- tempfile(fileext = ".R")
cat("### foo",
    "##-- bar",
    "##  ",
    "#",
    "###*",
    file = fil, sep = "\n")
comments_style(getSourceData(fil))

## Incorrect comments
fil <- tempfile(fileext = ".R")
cat("###foo",
    "###+bar",
    file = fil, sep = "\n")
comments_style(getSourceData(fil))
```

curly_braces_style *Validation of the Positioning of Braces*

Description

Check that the opening and closing braces are positioned according to standard bracing styles rules.

Usage

```
close_brace_style(srcData)
open_brace_style(srcData, style = c("R", "1TBS"))
open_brace_unique_style(srcData)
```

Arguments

srcData a list as returned by [getSourceData](#).

style character string of a supported bracing style.

Details

Good coding practices dictate to use one bracing style uniformly in a script.

The "R" bracing style has both opening and closing braces on their own lines, left aligned with their corresponding statement:

```

if (x > 0)
{
  ...
}

```

The "1TBS" bracing style, also known as "K&R" style, has the opening brace immediately follow its corresponding statement, separated by a space. The closing brace lies on its own line, left aligned with the statement:

```

if (x > 0) {
  ...
}

```

`open_brace_style` validates that the coding style in argument is used for opening braces in a script file. `open_brace_unique_style` validates that only one style is used throughout the script.

These functions use `getParseText` and, therefore, require that the "keep.source" option is TRUE.

Value

Boolean. When FALSE, a `message` indicates the nature of the error and the faulty lines, and the returned value has the following `attributes`:

<code>lines</code>	faulty line numbers;
<code>message</code>	text of the error message.

Examples

```

## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct positioning of braces in R bracing style
fil <- tempfile(fileext = ".R")
cat("x <- 2",
    "if (x <= 2)",
    "{",
    "  y <- 3",
    "  x + y",
    "}",
    file = fil, sep = "\n")
srcData <- getSourceData(fil)
open_brace_style(srcData, style = "R")
close_brace_style(srcData)

## Above code in invalid in 1TBS bracing style
open_brace_style(srcData, style = "1TBS")

## Incorrect positioning of the opening brace and
## misalignment of the closing brace

```

```
fil <- tempfile(fileext = ".R")
cat("f <- function(x) {",
    "  x^2",
    " }",
    file = fil, sep = "\n")
srcData <- getSourceData(fil)
open_brace_style(srcData, style = "R")
close_brace_style(srcData)

## Incorrect simultaneous use of two bracing styles
fil <- tempfile(fileext = ".R")
cat("x <- 2",
    "if (x <= 2)",
    "{",
    "  y <- 3",
    "  x + y",
    "}",
    "for (i in 1:5) {",
    "  x + i",
    "}",
    file = fil, sep = "\n")
open_brace_unique_style(getSourceData(fil))
```

documentation_linters *Validation of Documentation*

Description

Check for comments and proper documentation of a function in a script file.

The expected documentation format is not unlike R help pages; see details.

Usage

```
any_comments(srcData, ...)
```

```
any_doc(srcData, ...)
```

```
signature_doc(srcData, ...)
```

```
section_doc(srcData, pattern, ...)
```

```
description_section_doc(srcData, ...)
```

```
arguments_section_doc(srcData, ...)
```

```
value_section_doc(srcData, ...)
```

```
examples_section_doc(srcData, ...)
```

```
formals_doc(srcData, ...)
```

Arguments

srcData	a list as returned by getSourceData .
pattern	character string containing a regular expression describing a keyword to match in the documentation.
...	further arguments passed to grepl .

Details

any_comments checks that a script file contains at least one non empty comment, that is, a string with at least one character other than whitespace after the comment delimiters.

The other functions check the documentation provided with function definitions in a script file. Comments starting in column 1 are considered documentation.

any_doc checks that the file contains some documentation.

signature_doc checks that the signature (or usage information) of every function is present in the documentation.

section_doc checks that the documentation contains a section title corresponding to pattern for every (or as many) function definition. Functions description_section_doc, arguments_section_doc, value_section_doc and examples_section_doc are wrappers for common patterns Description, Arguments?, Value and Examples?, respectively.

formals_doc checks that the description of every formal argument is present in the documentation.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error, and the returned value has the following [attributes](#):

nlines	number of lines checked for comments or documentation (any_comments and any_doc only);
fun	names of functions without a signature in the documentation (signature_doc only);
sections	number of sections missing from documentation (section_doc and wrapper functions only);
formals	formal arguments missing from documentation (formals_doc only);
message	text of the error message.

References

Goulet, V., [Programmer avec R](#) for the standard documentation format these functions were developed for.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)
```



```
## Script with non empty comments.
fil <- tempfile(fileext = ".R")
cat(file = fil, "
#-
## here is foo
#-
foo <- function(x, y = 2)
  x + y #addition
")
any_comments(getSourceData(fil))

## Script with embedded documentation.
fil <- tempfile(fileext = ".R")
cat(file = fil, "
###
### foo(x, y = 2)
###
## Adding two vectors
##
## Arguments
##
## x: a vector
## y: another vector
##
## Value
##
## Sum of the two vectors.
##
## Examples
##
## foo(1:5)
##
foo <- function(x, y = 2)
  x + y
")
fooData <- getSourceData(fil)

## Elements present in the documentation
any_comments(fooData)
any_doc(fooData)
arguments_section_doc(fooData)
value_section_doc(fooData)
examples_section_doc(fooData)
formals_doc(fooData)

## Missing section title
description_section_doc(fooData)
```

Description

Get parse information and source code from an R script file.

Usage

```
getSourceData(file, encoding, keep.source = getOption("keep.source"))
```

Arguments

file	a connection object or a character.
encoding	encoding to be assumed for input strings.
keep.source	a logical value; if TRUE, keep source reference information.

Details

The parse information of the script file is obtained using [getParseData](#). The source code is read in using [readLines](#). Arguments file, encoding and keep.source should be compatible with these functions.

Linters using results of this function may not work properly if the encoding argument does not match the encoding of the script file.

Value

A list of two elements:

parseData	parse information data frame;
Lines	source code character vector of length the number of lines in the file.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

fil <- tempfile(fileext = ".R")
cat("## A simple function",
    "foo <- function(x, y)",
    "{",
    "  z <- x + y",
    "  if (z > 3)",
    "    (x * y)^2",
    "  else",
    "    sqrt(x * y)",
    "}",
    file = fil, sep = "\n")
getSourceData(fil)
```

line_length_style	<i>Validation of Length of Code and Comments Lines</i>
-------------------	--

Description

Check that the length of code and comment lines does not exceed a given limit in number of characters.

Usage

```
line_length_style(srcData, nchar_max = 80L)
```

Arguments

srcData	a list as returned by getSourceData .
nchar_max	maximum number of characters per line.

Details

Good coding practice dictates to limit line length to a value around 80 characters for readability purposes.

The line length is determined from the column number ending each line of code in the parse information. This may give unintended results if the encoding used in [getParseData](#) does not match the encoding of the script file and the latter contains non ASCII characters.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines	faulty line numbers;
message	text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Valid line length
fil <- tempfile(fileext = ".R")
cat("## innocuous comment",
    "x <- 2",
    "y <- 3",
    "x + y",
    file = fil, sep = "\n")
line_length_style(getSourceData(fil))
```

```
## Limit valid line length to only 20 characters
fil <- tempfile(fileext = ".R")
cat("## no longer innocuous comment",
    "x <- 2",
    "y <- 3",
    "x + y",
    file = fil, sep = "\n")
line_length_style(getSourceData(fil), 20)
```

nomagic_style

Validation of Magic Numbers

Description

Check the absence of *magic numbers* in code.

Usage

```
nomagic_style(srcData, ignore = c(-1, 0, 1, 2, 100),
              ignore.also = NULL)
```

Arguments

srcData	a list as returned by getSourceData .
ignore	vector of numbers not considered as magic.
ignore.also	vector of numbers not considered as magic in addition to those in ignore.

Details

Good coding practices dictate to avoid using “magic numbers” (unnamed or insufficiently documented numerical constants) in code. For example, in the expression `y <- x + 42`, 42 is a magic number.

When scanning the code for magic numbers, the following numerical constants are ignored:

- numbers in vectors `ignore` and `ignore.also`, with or without a suffix `L` denoting integer values;
- numbers used as the only expression in indexing;
- numbers in “simple” assignments to variables with all uppercase names.

“Simple” assignments serve to assign magic numbers to objects. Such expressions should contain at most three levels of sub-expressions and hold on a single line of code. The following expressions contain one, two and three levels of sub-expressions, respectively: `MAX <- 4294967295`, `MAX <- 4294967296 - 1`, `MAX <- 2^32 - 1`.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines	faulty line numbers;
message	text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

fil <- tempfile(fileext = ".R")
cat("MAX <- 2^6 - 1",
    "size <- 42",
    "x <- rnorm(MAX)",
    "runif(123)",
    "x[1]",
    "x[1] * 7 + 2",
    "x[33]",
    "x * 100",
    "x <- numeric(0)",
    "y <- logical(5)",
    file = fil, sep = "\n")

## Default list of ignored magic numbers
nomagic_style(getSourceData(fil))

## Additional exceptions
nomagic_style(getSourceData(fil), ignore.also = c(5, 42))
```

ops_spaces_style *Validation of Spacing Around Operators*

Description

Check that spacing around infix and unary operators is valid.

Usage

```
ops_spaces_style(srcData, ops = ops_list)
```

Arguments

srcData	a list as returned by getSourceData .
ops	vector of R parser tokens corresponding to infix operators to check for correct spacing; see details.

Details

Good coding practices dictate to surround infix operators with spaces (including line breaks) and to follow unary operators immediately by their argument.

The default value for argument `ops` is an internal object containing the following R parser tokens: '+', '-', '*', GT, GE, LT, LE, EQ, NE, AND, OR, AND2, OR2, '!', LEFT_ASSIGN, RIGHT_ASSIGN, EQ_ASSIGN, EQ_SUB, SPECIAL.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

<code>lines</code>	faulty line numbers;
<code>message</code>	text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct use of spacing around '+' and '-' operators
fil <- tempfile(fileext = ".R")
cat("2 + 3",
    "-2",
    "(4\n + 2)",
    "4 +\n2",
    file = fil, sep = "\n")
ops_spaces_style(getSourceData(fil), c("'+'", "'-'"))

## Incorrect use of spacing around '>' and '!' operators
fil <- tempfile(fileext = ".R")
cat("2> 3",
    "4 >2",
    "6>3",
    "! FALSE",
    "!\nFALSE",
    file = fil, sep = "\n")
ops_spaces_style(getSourceData(fil), c("GT", "'!'"))
```

parentheses_style *Validation of Spacing Around Parentheses*

Description

Check that spacing around parentheses is valid.

Usage

```
open_parenthesis_style(srcData)
close_parenthesis_style(srcData)
left_parenthesis_style(srcData)
```

Arguments

srcData a list as returned by [getSourceData](#).

Details

Good coding practices dictate the correct spacing around parentheses. First, opening parentheses should not be immediately followed by a space. Second, closing parentheses should not be immediately preceded by a space. Third, left (or opening) parentheses should always be preceded by a space, except in function calls, at the start of sub-expressions, after operators / and ^, or after an optional left parenthesis.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines	faulty line numbers;
message	text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct use of spacing around parentheses
fil <- tempfile(fileext = ".R")
cat("x <- c(2, 3, 5)",
    "if (any((2 * x) > 4))",
    "  sum(x)",
    "1/(x + 1)",
    "2^(x - 1)",
    "2^((x - 1))",
    file = fil, sep = "\n")
srcData <- getSourceData(fil)
open_parenthesis_style(srcData)
close_parenthesis_style(srcData)
left_parenthesis_style(srcData)

## Incorrect use of spacing around parentheses
fil <- tempfile(fileext = ".R")
cat("x <- c(2, 3, 5 )",
    "if(any(x > 4))",
    "  sum( x )",
    file = fil, sep = "\n")
```

```
srcData <- getSourceData(fil)
open_parenthesis_style(srcData)
close_parenthesis_style(srcData)
left_parenthesis_style(srcData)
```

roger-interface

R Interface for Roger Command Line Tools

Description

R interfaces to the Roger base system command line tools `roger checkreq`, `roger clone`, `roger grade`, `roger push`, `roger switch` and `roger validate`.

Usage

```
roger_checkreq(file = "./requirements.txt", ...,
               .debugOnly = FALSE)

roger_clone(pattern, project, rogerrc_file = NULL, machine = NULL,
            curl_options = NULL, api = NULL, quiet = FALSE, ...,
            .debugOnly = FALSE)

roger_grade(dir = getwd(), config_file = NULL, time_limit = NULL,
            detached_head = FALSE, output_file = NULL,
            quiet = FALSE, ..., .debugOnly = FALSE)

roger_push(branch, repos = getwd(), create = FALSE, file = NULL,
           add_file = NULL, message = NULL, quiet = FALSE, ...,
           .debugOnly = FALSE)

roger_switch(branch, repos = getwd(), quiet = FALSE, ...,
             .debugOnly = FALSE)

roger_validate(dir = getwd(), config_file = NULL,
              check_local_repos = TRUE, ..., .debugOnly = FALSE)
```

Arguments

<code>file</code>	requirements file name for <code>checkreq</code> ; name of the grading results file for <code>push</code> (overriding the default, locale dependent, value).
<code>pattern</code>	regular expression pattern.
<code>project</code>	name of a Git project containing repositories.
<code>dir</code>	character vector of directory names containing projects to grade or validate; only the first one is used by <code>validate</code> .
<code>repos</code>	character vector of Git repository names to publish grading results into.

branch	name of the branch in which to publish the grading results (identical for every repository).
add_file	character vector of file names to publish along with the grading results.
api	character string; name of the REST API used to retrieve the urls of the repositories.
check_local_repos	boolean; check the status of the local repository?
config_file	name of grading or validation configuration file; overrides the defaults gradeconf and valideconf.
create	boolean; is branch a new branch to create in the repositories?
curl_options	character vector of command line options to pass to curl.
detached_head	boolean; leave the repositories in a detached head state for further manual grading?
machine	URI and context of the Git server.
message	character vector of commit messages pasted together to form a single paragraph.
output_file	grading results file name; if NULL or -, results are written to standard output.
rogerrc_file	path to the rogerrc file.
quiet	boolean; suppress output?
time_limit	date and time in ISO 8601 format (YYYY-MM-DD HH:MM:SS) by which to grade a project in a Git repository.
...	further arguments passed to system2 .
.debugOnly	boolean; print the system call only?

Details

These functions build calls to the Roger base system command line tools and execute them using [system2](#).

Command line option values are always quoted with [shQuote](#).

Refer to the command line tools documentation for detailed information on the arguments and options.

Value

Character vector containing the standard output and standard error of the command line tools.

Note

The interface functions require that the Roger base system is installed on your machine and in your system path. See the Roger Project download page <https://roger-project.gitlab.io/download/>.

Examples

```

## Sample usage for students
## Not run: ## Validate the project in the current directory using the
## configuration file 'validateconf-prototype'.
roger_validate(config_file = "validateconf-prototype")
## End(Not run)

## Sample usage for graders.
## Not run: ## First check the availability of the grading tools.
roger_checkreq()

## Clone all repositories matching the pattern '[0-9]{9}_prototype'
## in the BitBucket project 'a2042-12345'.
roger_clone("[0-9]{9}_prototype", "a2042-12345")

## Grade all directories (repositories) starting with '[0-9]*'
## as of 2020-04-30 23:59:59 using the configuration in file
## 'gradeconf-prototype'; write results in file 'GRADING.txt'
## of each directory; leave repositories in detached head state
## for manual grading of files.
roger_grade("[0-9]*/", config_file = "gradeconf-prototype",
            time_limit = "2020-04-30 23:59:59", detached_head = TRUE,
            output_file = "GRADING.txt")

## Publish results in every repository in a new branch
## 'grading-results'. No need to specify the grading results file
## name since 'GRADING.txt' is the default in an English locale.
roger_push("grading-results", "[0-9]*/", create = TRUE,
          message = c("Here are your grading results"))

## Return all repositories to main branch.
roger_switch("main", "[0-9]*/")
## End(Not run)

```

square_brackets_style *Validation of Spacing Around Square Brackets*

Description

Check that spacing around square brackets is valid.

Usage

```

open_bracket_style(srcData)
close_bracket_style(srcData)

```

Arguments

srcData a list as returned by [getSourceData](#).

Details

Good coding practices dictate the correct spacing around square brackets: opening brackets should not be immediately followed by a space; closing brackets should not be immediately preceded by a space, unless that space is after a comma.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines	faulty line numbers;
message	text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct use of spacing around square brackets
fil <- tempfile(fileext = ".R")
cat("x <- c(1, 2, 3, 5, 7, 9)",
    "x[x > 3 & x < 7]",
    "dim(x) <- c(2, 3)",
    "x[1, ]",
    file = fil, sep = "\n")
srcData <- getSourceData(fil)
open_bracket_style(srcData)
close_bracket_style(srcData)

## Incorrect use of spacing around square brackets
fil <- tempfile(fileext = ".R")
cat("x <- c(1, 2, 3, 5, 7, 9)",
    "x[ x > 3 & x < 7 ]",
    "dim(x) <- c(2, 3)",
    "x[1,]",
    "x[1, ]",
    file = fil, sep = "\n")
srcData <- getSourceData(fil)
open_bracket_style(srcData)
close_bracket_style(srcData)
```

trailing_blank_lines_style

Validation of Trailing Blank Lines

Description

Check that a script file does not contain superfluous trailing blank lines.

Usage

```
trailing_blank_lines_style(srcData)
```

Arguments

srcData a list as returned by [getSourceData](#).

Details

Good coding practices dictate that a script file should not end with blank lines.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines	faulty line numbers;
message	text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct script without trailing blank lines
fil <- tempfile(fileext = ".R")
cat("## A simple function",
    "foo <- function(x, y)",
    "{",
    "  x + y",
    "}",
    file = fil, sep = "\n")
trailing_blank_lines_style(getSourceData(fil))

## Incorrect script with trailing blank lines
fil <- tempfile(fileext = ".R")
cat("## A simple function",
    "foo <- function(x, y)",
    "{",
    "  x + y",
    "}",
    "",
    "",
    file = fil, sep = "\n")
trailing_blank_lines_style(getSourceData(fil))
```

trailing_whitespace_style
Validation of Trailing Whitespace

Description

Check that a script file does not contain unnecessary whitespace at the end of lines.

Usage

```
trailing_whitespace_style(srcData)
```

Arguments

srcData a list as returned by [getSourceData](#).

Details

Good coding practices dictate that a script file should contain unnecessary whitespace (space or tabulation) at the end of lines.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

lines faulty line numbers;
message text of the error message.

Examples

```
## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct script without trailing whitespace
fil <- tempfile(fileext = ".R")
cat("## A simple function",
    "foo <- function(x, y)",
    "{",
    "  x + y",
    "}",
    file = fil, sep = "\n")
trailing_whitespace_style(getSourceData(fil))

## Incorrect script with trailing whitespace
fil <- tempfile(fileext = ".R")
cat("## A simple function",
    "foo <- function(x, y)",
```

```

    "{ ",
    "  x + y",
    "}\t",
    file = fil, sep = "\n")
trailing_whitespace_style(getSourceData(fil))

```

unneded_concatenation_style

Validation of Concatenation Usage

Description

Check that function `c` is used with more than one argument.

Usage

```
unneded_concatenation_style(srcData)
```

Arguments

`srcData` a list as returned by [getSourceData](#).

Details

Function `c` is used to combine its arguments. Therefore, good coding practice dictates that the function should never be used with zero or one argument.

Usage with zero argument to create an empty vector should be replaced by calls to object creation functions like [numeric](#) or [character](#).

Usage with one argument is a superfluous call to `c` that should just be replaced by the argument.

Value

Boolean. When FALSE, a [message](#) indicates the nature of the error and the faulty lines, and the returned value has the following [attributes](#):

<code>lines</code>	faulty line numbers;
<code>message</code>	text of the error message.

Examples

```

## Keep parse data in non interactive sessions.
if (!interactive())
  op <- options(keep.source = TRUE)

## Correct use of the 'c()' function
fil <- tempfile(fileext = ".R")
cat("x <- c(1, 2, 3, 4)", file = fil)
unneded_concatenation_style(getSourceData(fil))

```

```
## Incorrect uses of the 'c()' function
fil <- tempfile(fileext = ".R")
cat("x <- c()",
    "x <- c(42)",
    file = fil, sep = "\n")
unneded_concatenation_style(getSourceData(fil))
```

Index

- * **documentation**
 - documentation_linters, 7
- * **programming**
 - documentation_linters, 7
- =, 2
- any_comments (documentation_linters), 7
- any_doc (documentation_linters), 7
- arguments_section_doc
 - (documentation_linters), 7
- assignment_style, 2
- attributes, 2–4, 6, 8, 11, 13–15, 19–22
- c, 22
- character, 22
- close_brace_style (curly_braces_style), 5
- close_bracket_style
 - (square_brackets_style), 18
- close_parenthesis_style
 - (parentheses_style), 14
- commas_style, 3
- comments_style, 4
- curly_braces_style, 5
- description_section_doc
 - (documentation_linters), 7
- documentation_linters, 7
- examples_section_doc
 - (documentation_linters), 7
- formals_doc (documentation_linters), 7
- getParseData, 10, 11
- getParseText, 6
- getSourceData, 2–5, 8, 9, 11–13, 15, 18, 20–22
- grepl, 8
- left_parenthesis_style
 - (parentheses_style), 14
- line_length_style, 11
- message, 2–4, 6, 8, 11, 13–15, 19–22
- nomagic_style, 12
- numeric, 22
- open_brace_style (curly_braces_style), 5
- open_brace_unique_style
 - (curly_braces_style), 5
- open_bracket_style
 - (square_brackets_style), 18
- open_parenthesis_style
 - (parentheses_style), 14
- ops_spaces_style, 13
- parentheses_style, 14
- readLines, 10
- regex, 4
- roger-interface, 16
- roger_checkreq (roger-interface), 16
- roger_clone (roger-interface), 16
- roger_grade (roger-interface), 16
- roger_push (roger-interface), 16
- roger_switch (roger-interface), 16
- roger_validate (roger-interface), 16
- section_doc (documentation_linters), 7
- shQuote, 17
- signature_doc (documentation_linters), 7
- square_brackets_style, 18
- system2, 17
- trailing_blank_lines_style, 19
- trailing_whitespace_style, 21
- unnneeded_concatenation_style, 22
- value_section_doc
 - (documentation_linters), 7