

# Package ‘streambugs’

October 14, 2022

**Type** Package

**Title** Parametric Ordinary Differential Equations Model of Growth, Death, and Respiration of Macroinvertebrate and Algae Taxa

**Version** 1.2

**Date** 2020-10-20

**Author** Nele Schuwirth, Peter Reichert, Mikolaj Rybinski

**Maintainer** Nele Schuwirth <nele.schuwirth@eawag.ch>

**Description** Numerically solve and plot solutions of a parametric ordinary differential equations model of growth, death, and respiration of macroinvertebrate and algae taxa dependent on pre-defined environmental factors. The model (version 1.0) is introduced in Schuwirth, N. and Reichert, P., (2013) <DOI:10.1890/12-0591.1>. This package includes model extensions and the core functions introduced and used in Schuwirth, N. et al. (2016) <DOI:10.1111/1365-2435.12605>, Kattwinkel, M. et al. (2016) <DOI:10.1021/acs.est.5b04068>, Mondy, C. P., and Schuwirth, N. (2017) <DOI:10.1002/eap.1530>, and Paillex, A. et al. (2017) <DOI:10.1111/fwb.12927>.

**URL** <https://www.eawag.ch/en/departement/siam/projects/streambugs/>

**BugReports** <https://gitlab.com/NeleSchuwirth/streambugs/-/issues>

**License** GPL-3

**Depends** R (>= 3.5.0)

**Imports** deSolve (>= 1.20)

**Suggests** testthat

**RoxygenNote** 7.1.1

**Encoding** UTF-8

**NeedsCompilation** yes

**SystemRequirements** C99

**Repository** CRAN

**Date/Publication** 2020-10-20 16:50:03 UTC

## R topics documented:

streambugs-package . . . . .	2
construct.statevariables . . . . .	2
count.feeding.links . . . . .	3
decode.statevarnames . . . . .	4
foodweb.plot . . . . .	5
plot.streambugs . . . . .	6
run.streambugs . . . . .	7
streambugs.example.model.extended . . . . .	9
streambugs.example.model.toy . . . . .	9
streambugs.get.sys.def . . . . .	10
streambugs.write.sys.def . . . . .	11
<b>Index</b>	<b>12</b>

---

streambugs-package	<i>Simulator of development of macroinvertebrate and algae taxa</i>
--------------------	---

---

### Description

The main function of **streambugs** is `run.streambugs`. Remaining functions have auxiliary purpose to facilitate model creation, writing, and plotting of the simulation results, or to provide ready to use examples.

### See Also

Useful links:

- <https://www.eawag.ch/en/departement/siam/projects/streambugs/>
- Report bugs at <https://gitlab.com/NeleSchuwirth/streambugs/-/issues>

---

construct.statevariables	<i>Construct the streambugs ODE state variable names</i>
--------------------------	--

---

### Description

Construct encoded labels of streambugs ODE state variable names from reach names, habitat names, and "taxa" names for at least one of the POM, Algae, or Invertebrates groups.

**Usage**

```
construct.statevariables(
  Reaches,
  Habitats,
  POM = NULL,
  Algae = NULL,
  Invertebrates = NULL
)
```

**Arguments**

Reaches	reach names character vector; duplicates are dropped
Habitats	habitats names character vector; duplicates are dropped
POM	optional ("taxa") character vector of POM (particulate organic matter) group; duplicates are dropped (note: at least one "taxon" name out of all groups has to be given)
Algae	optional taxa character vector of Algae group; duplicates are dropped (note: at least one taxon name out of all groups has to be given)
Invertebrates	optional taxa character vector of Invertebrates group duplicates are dropped (note: at least one taxon name out of all groups has to be given)

**Value**

vector with state variable names in the form of "Reach\_Habitat\_Taxon\_Group"

**Examples**

```
Reaches      <- paste0("Reach",1:2)
Habitats     <- paste0("Hab",1:1)
y.names <- construct.statevariables(Reaches,Habitats,Invertebrates=c("Baetis","Ecdyonurus"))
```

---

count.feeding.links     *Count feeding links between taxa in streambugs ODE.*

---

**Description**

Count number of global "Cons" stoichiometric interactions (feeding links) between streambugs ODE state variables (taxa) in all habitats.

**Usage**

```
count.feeding.links(y.names, par)
```

**Arguments**

`y.names` same as `y.names` in [run.streambugs](#)  
`par` same as `par` in [run.streambugs](#)

**Value**

Integer number of feeding links, which is a number of feeding links in a single habitat times number of habitats and number of reaches.

**Examples**

```
m <- streambugs.example.model.toy()
count.feeding.links(m$y.names, m$par)

# feeding links count does not change w/ number of habitats (nor reaches)
m <- streambugs.example.model.toy(n.Habitats=10)
count.feeding.links(m$y.names, m$par)
```

---

`decode.statevarnames` *Decode the streambugs ODE state variable names*

---

**Description**

Extract reach names, habitat names, taxa names and optional group names from encoded labels of streambugs ODE state variable names.

**Usage**

```
decode.statevarnames(y.names)
```

**Arguments**

`y.names` vector with state variable names in the form of "Reach\_Habitat\_Taxon" or "Reach\_Habitat\_Taxon\_Group"

**Value**

List with:

`$y.names` names of state variables (input argument)

`$y.reaches`, `$y.reaches`, `$y.habitats`, `$y.taxa`, **and** `$y.groups`: Names of, respectively, reaches, habitats, taxa, and of groups of each state variable

`$reaches`, `$habitats`, `$taxa`, `$groups`: Unique names of, respectively, reaches, habitats, taxa, and of groups of state variables

`$ind.fA`: Indices used for the areal fractions of each reach and habitat

**Examples**

```
y.names <- c("Reach1_Hab1_Baetis_Invertebrates", "Reach1_Hab1_Ecdyonurus_Invertebrates",
            "Reach2_Hab1_Baetis_Invertebrates", "Reach2_Hab1_Ecdyonurus_Invertebrates")
decode.statevarnames(y.names)
```

---

 foodweb.plot

*Plot the streambugs "foodweb" graph.*


---

**Description**

Plot the "foodweb" graph depicting interactions between ODE variables in a streambugs model.

**Usage**

```
foodweb.plot(
  y.names,
  par,
  file = NA,
  cex = 1,
  font = 1,
  title = "",
  lwd = 1,
  bg = colors()[1],
  lcol = colors()[555],
  ncrit = 8,
  lcrit = 20,
  survivals = NA,
  observed = NA,
  texts = TRUE,
  pointcol = FALSE,
  ...
)
```

**Arguments**

y.names	same as y.names in <a href="#">run.streambugs</a>
par	same as par in <a href="#">run.streambugs</a>
file	optional name of a PDF file to plot to
cex	same as cex in <a href="#">par</a> , consumed by here by multiple text generating functions
font	same as font in <a href="#">par</a> , consumed here by <a href="#">text</a> as a font type for taxa names
title	optional title for the plot
lwd	same as lwd in <a href="#">par</a> , consumed here by <a href="#">lines</a> as a line width for the "food web" edges
bg	same as bg in <a href="#">par</a>

lcol	same as col in <code>par</code> , consumed here by <code>lines</code> as a line color for the "food web" edges
ncrit	number of inverts in one line at which they are shifted up and down, alternating
lcrit	number of letters/characters of state names which are plotted at level 2
survivals	vector with the entries "survived" or "extinct" for all state variables with names matching names of taxa state variables and "SusPOM"
observed	vector with the entries "never"/"notobserved", "observed", "sometimes", "always", or NA/"NA" for all state variables, with names matching names of taxa state variables and "SusPOM"
texts	if to plot as "food web" nodes as texts with taxa names; otherwise, plot points
pointcol	if to color text or point nodes using Eawag coloring scheme (eawagfarben); otherwise plot all in the same color
...	additional arguments for the <code>pdf</code> graphics device, relevant only if file argument was given.

### Examples

```
model <- streambugs.example.model.toy()
foodweb.plot(model$y.names, model$par, cex=1.1, title="complete foodweb", ncrit=8,
             lcrit=7, lwd=2, bg="white", lcol="blue", font=2)
```

---

plot.streambugs      *Plot the results of streambugs ODE run*

---

### Description

Plot time series of all streambugs ODE state variables, for each reach, habitat and group, resulting from the `run.streambugs` function call.

### Usage

```
## S3 method for class 'streambugs'
plot(x, y, inp = NA, ...)
```

### Arguments

x	matrix with results derived by <code>run.streambugs</code>
y	same as par in <code>run.streambugs</code>
inp	same as inp in <code>run.streambugs</code>
...	additional argument for the <code>plot</code> function call

### Examples

```
m <- streambugs.example.model.toy()
r <- run.streambugs(y.names=m$y.names, times=m$times, par=m$par, inp=m$inp, C=TRUE)
plot(x=r$res, y=m$par, inp=m$inp)
```

---

run.streamebugs	<i>Run the streamebugs ODE model</i>
-----------------	--------------------------------------

---

### Description

Numerically solve streamebugs ODE model (in either R or C version) for given parameters, inputs and time points, using the [ode](#) routine.

### Usage

```
run.streamebugs(
  y.names,
  times,
  par,
  inp = NA,
  C = FALSE,
  file.def = NA,
  file.res = NA,
  file.add = NA,
  return.res.add = FALSE,
  tout.add = NA,
  verbose = TRUE,
  method = "lsoda",
  rtol = 1e-04,
  atol = 1e-04,
  ...
)
```

### Arguments

y.names	state variables names, either as a vector encoded in the form "Reach_Habitat_Taxon" or "Reach_Habitat_Taxon_Group", or a list as returned by <a href="#">decode.statevarnames</a> function
times	vector with time points for which output is wanted; the first
par	vector with constant parameters and model inputs
inp	list with time-dependent parameters or model inputs with one list element for each parameter or input that includes a matrix where first column is the time and second the corresponding parameter or input value
C	identifier for C- or R-Version
file.def	file name for writing system definition
file.res	file name for results
file.add	file name for additional output (e.g. process rates)
return.res.add	returns res.add output additionally to res
tout.add	optional identifier for specific output times for the additional output, if NA all res.add is calculated for all times

verbose	prints some outputs to console
method	method used by <code>ode</code>
rtol	argument of <code>ode</code> function defining relative error tolerance, either a scalar or an array of the same size as <code>y.names</code>
atol	argument of <code>ode</code> function defining absolute error, either a scalar or an array of the same size as <code>y.names</code>
...	further arguments passed to <code>ode</code>

### Value

A list with:

`$res` matrix of class `streambugs` with up to as many rows as elements in `times` and as many columns as elements in `y.names`, plus an additional column for the time value. There will be a row for each element in `times` unless the FORTRAN routine "lsoda" returns with an unrecoverable error.

`$res.add` optional additional output matrix with process rates and taxon specific factors, present only if `return.res.add` input parameter is set to `TRUE`.

### Model syntax

See "docs/Streambugs\_syntax.pdf" file in the package installation folder: `system.file("docs", "Streambugs_syntax.pdf", package="streambugs")`.

### Examples

```
m <- streambugs.example.model.toy()
# Display inputs: list of perturbed variables with time points and new values
m$inp
# Simulate
res.C.default <- run.streambugs(y.names = m$y.names, times = m$times,
  par = m$par, inp = m$inp, C = TRUE)
# Modify input (halve second perturbation size) and re-simulate
m$inp$Reach3_w[2,2] <- m$inp$Reach3_w[2,2] / 2
m$inp
res.C.modified <- run.streambugs(y.names = m$y.names, times = m$times,
  par = m$par, inp = m$inp, C = TRUE)
# Compare exemplary trajectory of organic matter in one of the habitats
var.name <- "Reach3_Hab1_POM1_POM"
plot(m$times, res.C.default$res[, var.name], type="l", col="red")
lines(m$times, res.C.modified$res[, var.name], col="green")
```

---

`streambugs.example.model.extended`*Set-up the streambugs extended model*

---

**Description**

Set-up state variables, parameters, input, and output times of the streambugs extended model. All these are defined and read from .dat files The model is ready to run with [run.streambugs](#).

**Usage**

```
streambugs.example.model.extended()
```

**Value**

List with:

`$name` name of the example

`$y.names` list with names of state variables as returned by the [decode.statevarnames](#) function

`$times, $par, $inp`: corresponding input parameters of the [run.streambugs](#) function

**Model syntax**

See "docs/Streambugs\_syntax.pdf" file in the package installation folder: `system.file("docs", "Streambugs_syntax.pdf", package="streambugs")`.

**Examples**

```
model <- streambugs.example.model.extended()
# display values of microhabitat tolerance values for Lumbriculidae taxa
model$par[grepl("^Lumbriculidae_microhabtolval", names(model$par))]
```

---

`streambugs.example.model.toy`*Set-up the streambugs toy model*

---

**Description**

Set-up state variables, parameters, input, and output times of the streambugs toy model. The model is ready to run with [run.streambugs](#).

**Usage**

```
streambugs.example.model.toy(n.Reaches = 3, n.Habitats = 2)
```

**Arguments**

n.Reaches	Number of reaches in the toy example
n.Habitats	Number of habitats in the toy example

**Value**

List with:

\$name name of the example

\$y.names list with names of state variables as returned by the [decode.statevarnames](#) function

\$times, \$par, \$inp: corresponding input parameters of the [run.streambugs](#) function

**Model syntax**

See "docs/Streambugs\_syntax.pdf" file in the package installation folder: `system.file("docs", "Streambugs_syntax.pdf", package="streambugs")`.

**Examples**

```
model <- streambugs.example.model.toy()
# display values of the exponent "q" in the food limitation term; Note:
model$par[grepl("(.*_)?q$", names(model$par))]
```

---

```
streambugs.get.sys.def
```

*Get system definition of the streambugs ODE model*

---

**Description**

Get a structured representation of the streambugs ODE system definition.

**Usage**

```
streambugs.get.sys.def(y.names, par, inp = NA)
```

**Arguments**

y.names	state variables names, either as a vector encoded in the form "Reach_Habitat_Taxon" or "Reach_Habitat_Taxon_Group", or a list as returned by <a href="#">decode.statevarnames</a> function
par	vector with constant parameters and model inputs
inp	list with time-dependent parameters or model inputs with one list element for each parameter or input that includes a matrix where first column is the time and second the corresponding parameter or input value

**Value**

List with definition of the model including input state variables, parameters, and inputs, as well as the derived model structure including global parameters, environmental conditions of reaches and habitats, initial conditions, taxa properties, stoichiometric coefficients of all processes, and process definitions for each state variable.

**Examples**

```
m <- streambugs.example.model.toy()
sys.def <- streambugs.get.sys.def(y.names=m$y.names, par=m$par, inp=m$inp)
# Get initial conditions for all state variables
sys.def$par.initcond$parvals
# Get stoichiometric coefficients of consumption within the food web
sys.def$par.stoich.web$Cons
# Get stoichiometric coefficients of death process for each taxon
# (transforming them into a dead organic matter "POM")
sys.def$par.stoich.taxon$Death
```

---

```
streambugs.write.sys.def
```

*Write system definition of the streambugs ODE model*

---

**Description**

Write system definition of the streambugs ODE model into a human-readable text file.

**Usage**

```
streambugs.write.sys.def(sys.def, file = NA)
```

**Arguments**

sys.def	system definition generated by the function <a href="#">streambugs.get.sys.def</a>
file	file name

**Examples**

```
m <- streambugs.example.model.toy()
sys.def <- streambugs.get.sys.def(y.names=m$y.names, par=m$par, inp=m$inp)
file.name <- tempfile(m$name, fileext=".dat")
streambugs.write.sys.def(sys.def, file.name)
file.show(file.name, delete.file=TRUE)
```

# Index

`construct.statevariables`, 2  
`count.feeding.links`, 3  
  
`decode.statevarnames`, 4, 7, 9, 10  
  
`foodweb.plot`, 5  
  
`lines`, 5, 6  
  
`ode`, 7, 8  
  
`par`, 5, 6  
`pdf`, 6  
`plot`, 6  
`plot.streambugs`, 6  
  
`run.streambugs`, 2, 4–6, 7, 9, 10  
  
`streambugs (streambugs-package)`, 2  
`streambugs-package`, 2  
`streambugs.example.model.extended`, 9  
`streambugs.example.model.toy`, 9  
`streambugs.get.sys.def`, 10, 11  
`streambugs.write.sys.def`, 11  
  
`text`, 5