

# Package ‘taskscheduleR’

October 14, 2022

**Type** Package

**Title** Schedule R Scripts and Processes with the Windows Task Scheduler

**Description** Schedule R scripts/processes with the Windows task scheduler. This allows R users to automate R processes on specific time points from R itself.

**Maintainer** Jan Wijffels <jwi.jffels@bnosac.be>

**License** AGPL-3

**Version** 1.6

**URL** <https://github.com/bnosac/taskscheduleR>

**OS\_type** windows

**Imports** data.table, tools, utils

**VignetteBuilder** knitr

**Suggests** knitr, rmarkdown, miniUI, shiny, testthat

**RoxygenNote** 7.1.2

**NeedsCompilation** no

**Author** Jan Wijffels [aut, cre, cph],  
BNOSAC [cph],  
Oliver Belmans [cph, aut]

**Repository** CRAN

**Date/Publication** 2022-03-16 09:40:02 UTC

## R topics documented:

taskscheduleR-package . . . . .	2
taskschedulerAddin . . . . .	2
taskscheduler_create . . . . .	3
taskscheduler_delete . . . . .	5
taskscheduler_ls . . . . .	6
taskscheduler_runnow . . . . .	6
taskscheduler_stop . . . . .	7

<b>Index</b>	<b>8</b>
--------------	----------

taskscheduleR-package *Schedule R Scripts/Processes with the Windows Task Scheduler*

---

### Description

Schedule R scripts/processes with the Windows task scheduler. This allows R users to automate R processes on specific timepoints from R itself. The package is basically a wrapper around the Schtasks.exe functionality. More information about schtasks can be found at <https://msdn.microsoft.com/en-us/library/windows/desktop/bb736357> or at the doc folder inside this package.

---

taskschedulerAddin *Launch an RStudio addin which allows to schedule an Rscript interactively.*

---

### Description

Launch an RStudio addin which allows to schedule an Rscript interactively.

### Usage

```
taskschedulerAddin(RscriptRepository, debug = TRUE)
```

### Arguments

RscriptRepository path to the folder where R scripts will be copied to and launched. Defaults to the extdata folder in the taskscheduleR R library

debug passed on to [taskscheduler\\_create](#)

### Value

the return of [runGadget](#)

### Examples

```
## Not run:  
taskschedulerAddin()  
  
## End(Not run)
```

---

taskscheduler\_create *Schedule an R script with the Windows task scheduler.*

---

## Description

Schedule an R script with the Windows task scheduler. E.g. daily, weekly, once, at startup, ... More information about the scheduling format can be found in the docs/schtasks.pdf file inside this package. The rscript file will be scheduled with Rscript.exe and the log of the run will be put in the .log file which can be found in the same directory as the location of the rscript

## Usage

```
taskscheduler_create(
  taskname = basename(rscript),
  rscript,
  schedule = c("ONCE", "MONTHLY", "WEEKLY", "DAILY", "HOURLY", "MINUTE", "ONLOGON",
    "ONIDLE"),
  starttime = format(Sys.time() + 62, "%H:%M"),
  startdate = format(Sys.Date(), "%d/%m/%Y"),
  days = c("*", "MON", "TUE", "WED", "THU", "FRI", "SAT", "SUN", 1:31),
  months = c("*", "JAN", "FEB", "MAR", "APR", "MAY", "JUN", "JUL", "AUG", "SEP", "OCT",
    "NOV", "DEC"),
  modifier,
  idletime = 60L,
  Rexe = file.path(Sys.getenv("R_HOME"), "bin", "Rscript.exe"),
  rscript_args = "",
  schtasks_extra = "",
  debug = FALSE
)
```

## Arguments

taskname	a character string with the name of the task. Defaults to the filename. Should not contain any spaces.
rscript	the full path to the .R script with the R code to execute. Should not contain any spaces.
schedule	when to schedule the rscript. Either one of 'ONCE', 'MONTHLY', 'WEEKLY', 'DAILY', 'HOURLY', 'MINUTE', 'ONLOGON', 'ONIDLE'.
starttime	a timepoint in HH:mm format indicating when to run the script. Defaults to within 62 seconds.
startdate	a date that specifies the first date on which to run the task. Only applicable if schedule is of type 'MONTHLY', 'WEEKLY', 'DAILY', 'HOURLY', 'MINUTE'. Defaults to today in '%d/%m/%Y' format. Change to your locale format if needed.

days	character string with days on which to run the script if schedule is 'WEEKLY' or 'MONTHLY'. Possible values are * (all days). For weekly: 'MON', 'TUE', 'WED', 'THU', 'FRI', 'SAT', 'SUN' or a vector of these in your locale. For monthly: 1:31 or a vector of these.
months	character string with months on which to run the script if schedule is 'MONTHLY'. Possible values are * (all months) or 'JAN', 'FEB', 'MAR', 'APR', 'MAY', 'JUN', 'JUL', 'AUG', 'SEP', 'OCT', 'NOV', 'DEC' or a vector of these in your locale.
modifier	a modifier to apply. See the docs/schtasks.pdf
idletime	integer containing a value that specifies the amount of idle time to wait before running a scheduled ONIDLE task. The valid range is 1 - 999 minutes.
Rexe	path to Rscript.exe which will be used to run the script. Defaults to Rscript at the bin folder of R_HOME.
rscript_args	character string with further arguments passed on to Rscript. See args in <a href="#">Rscript</a> .
schtasks_extra	character string with further schtasks arguments. See the inst/docs/schtasks.pdf
debug	logical to print the system call to screen

## Value

the system call to schtasks /Create

## Examples

```
myscript <- system.file("extdata", "helloworld.R", package = "taskscheduleR")
cat(readLines(myscript), sep = "\n")

## Not run:
## Run script once at a specific timepoint (within 62 seconds)
runon <- format(Sys.time() + 62, "%H:%M")
taskscheduler_create(taskname = "myfancyscript", rscript = myscript,
  schedule = "ONCE", starttime = runon)

## Run every day at the same time on 09:10, starting from tomorrow on
## Mark: change the format of startdate to your locale if needed (e.g. US: %m/%d/%Y)
taskscheduler_create(taskname = "myfancyscriptdaily", rscript = myscript,
  schedule = "DAILY", starttime = "09:10", startdate = format(Sys.Date()+1, "%d/%m/%Y"))

## Run every week on Sunday at 09:10
taskscheduler_create(taskname = "myfancyscript_sun", rscript = myscript,
  schedule = "WEEKLY", starttime = "09:10", days = 'SUN')

## Run every 5 minutes, starting from 10:40
taskscheduler_create(taskname = "myfancyscript_5min", rscript = myscript,
  schedule = "MINUTE", starttime = "10:40", modifier = 5)

## Run every minute, giving some command line arguments which can be used in the script itself
taskscheduler_create(taskname = "myfancyscript_withargs_a", rscript = myscript,
  schedule = "MINUTE", rscript_args = "productxyz 20160101")
taskscheduler_create(taskname = "myfancyscript_withargs_b", rscript = myscript,
```

```

    schedule = "MINUTE", rscript_args = c("productabc", "20150101"))

alltasks <- taskscheduler_ls()
subset(alltasks, TaskName %in% c("myfancyscript", "myfancyscriptdaily"))
# The field TaskName might have been different on Windows with non-english language locale

taskscheduler_delete(taskname = "myfancyscript")
taskscheduler_delete(taskname = "myfancyscriptdaily")
taskscheduler_delete(taskname = "myfancyscript_sun")
taskscheduler_delete(taskname = "myfancyscript_5min")
taskscheduler_delete(taskname = "myfancyscript_withargs_a")
taskscheduler_delete(taskname = "myfancyscript_withargs_b")

## Have a look at the log
mylog <- system.file("extdata", "helloworld.log", package = "taskscheduleR")
cat(readLines(mylog), sep = "\n")

## End(Not run)

```

---

taskscheduler\_delete *Delete a specific task which was scheduled in the Windows task scheduler.*

---

## Description

Delete a specific task which was scheduled in the Windows task scheduler.

## Usage

```
taskscheduler_delete(taskname)
```

## Arguments

taskname            the name of the task to delete. See the example.

## Value

the system call to schtasks /Delete

## Examples

```

## Not run:
x <- taskscheduler_ls()
x
# The field TaskName might have been different on Windows with non-english language locale
task <- x$TaskName[1]
taskscheduler_delete(taskname = task)

## End(Not run)

```

---

taskscheduler_ls	<i>Get all the tasks which are currently scheduled at the Windows task scheduler.</i>
------------------	---

---

### Description

Get all the tasks which are currently scheduled at the Windows task scheduler.

### Usage

```
taskscheduler_ls(encoding = "UTF-8", ...)
```

### Arguments

encoding	encoding of the CSV which schtasks.exe generates. Defaults to UTF-8.
...	optional arguments passed on to fread in order to read in the CSV file which schtasks generates

### Value

a data.frame with scheduled tasks as returned by schtasks /Query for which the Taskname or second column in the dataset the preceding \ is removed

### Examples

```
x <- taskscheduler_ls()
x
```

---

taskscheduler_runnow	<i>Immediately run a specific task available in the Windows task scheduler.</i>
----------------------	---

---

### Description

Immediately run a specific task available in the Windows task scheduler.

### Usage

```
taskscheduler_runnow(taskname)
```

### Arguments

taskname	the name of the task to run. See the example.
----------	---

### Value

the system call to schtasks /Run

## Examples

```
## Not run:
myscript <- system.file("extdata", "helloworld.R", package = "taskscheduleR")
taskscheduler_create(taskname = "myfancyscript", rscript = myscript,
  schedule = "ONCE", starttime = format(Sys.time() + 10*60, "%H:%M"))

taskscheduler_runnow("myfancyscript")
Sys.sleep(5)
taskscheduler_stop("myfancyscript")

taskscheduler_delete(taskname = "myfancyscript")

## End(Not run)
```

---

taskscheduler_stop	<i>Stop the run of a specific task which is running in the Windows task scheduler.</i>
--------------------	--

---

## Description

Stop the run of a specific task which is running in the Windows task scheduler.

## Usage

```
taskscheduler_stop(taskname)
```

## Arguments

taskname            the name of the task to stop. See the example.

## Value

the system call to schtasks /End

## Examples

```
## Not run:
myscript <- system.file("extdata", "helloworld.R", package = "taskscheduleR")
taskscheduler_create(taskname = "myfancyscript", rscript = myscript,
  schedule = "ONCE", starttime = format(Sys.time() + 10*60, "%H:%M"))

taskscheduler_runnow("myfancyscript")
Sys.sleep(5)
taskscheduler_stop("myfancyscript")

taskscheduler_delete(taskname = "myfancyscript")

## End(Not run)
```

# Index

Rscript, [4](#)  
runGadget, [2](#)

taskcheduler\_runnow  
    (taskscheduler\_runnow), [6](#)  
taskcheduler\_stop (taskscheduler\_stop),  
    [7](#)

taskscheduleR (taskscheduleR-package), [2](#)  
taskscheduleR-package, [2](#)  
taskscheduler\_create, [2](#), [3](#)  
taskscheduler\_delete, [5](#)  
taskscheduler\_ls, [6](#)  
taskscheduler\_runnow, [6](#)  
taskscheduler\_stop, [7](#)  
taskschedulerAddin, [2](#)