Package 'uncorbets'

October 12, 2022

Type Package

Title Uncorrelated Bets via Minimum Torsion Algorithm

Version 0.1.1

Description Implements Minimum Torsion for portfolio diversification as described in Meucci, Attilio (2013) <doi:10.2139/ssrn.2276632>.

License MIT + file LICENSE

URL https://github.com/Reckziegel/uncorbets

BugReports https://github.com/Reckziegel/uncorbets/issues

Imports assertthat (>= 0.2.1), NlcOptim (>= 0.6), stats

Suggests spelling, covr, testthat (>= 3.0.0)

Config/testthat/edition 3

Encoding UTF-8

RoxygenNote 7.1.2

Language en-US

Depends R (>= 2.10)

NeedsCompilation no

Author Bernardo Reckziegel [aut, cre, cph]

Maintainer Bernardo Reckziegel <bernardo_cse@hotmail.com>

Repository CRAN

Date/Publication 2021-09-24 04:30:02 UTC

R topics documented:

effective_bets *Effective Number of Bets*

Description

Computes the diversification probability distribution and the effective number of bets of an allocation.

Usage

```
effective_bets(b, sigma, t)
```

Arguments

b	A vector of exposures (allocations).
sigma	A n x n covariance matrix.
t	A n x n torsion matrix.

Value

A list of length 2 with:

- p: the diversification probability distribution;
- enb: the effective number of bets.

Examples

```
# extract the invariants from the data
set.seed(123)
log_ret <- matrix(rnorm(400), ncol = 4) / 10

# compute the covariance matrix
sigma <- stats::cov(log_ret)

# torsion
torsion_cov <- torsion(sigma = sigma, model = 'minimum-torsion', method ='exact')

# 1/N reference
b <- rep(1 / ncol(log_ret), ncol(log_ret))

# ENB
effective_bets(b = b, sigma = sigma, t = torsion_cov)
```

`max_effective_bets` *Risk-Diversification powered by the Minimum Torsion Algorithm*

Description

Finds the allocation that maximizes the `effective_bets`.

Usage

```
max_effective_bets(x0, sigma, t, tol = 1e-20, maxeval = 5000L, maxiter = 5000L)
```

Arguments

`x0`	A `numeric` vector for the search starting point. Usually the "one over n" allocation.
`sigma`	A `n x n` covariance matrix.
`t`	A `n x n` torsion matrix.
`tol`	An `interger` with the convergence tolerance.
`maxeval`	An `integer` with the maximum number of evaluations of the objective function.
`maxiter`	An `integer` with the maximum number of iterations.

Value

A `list` with the following components:

- `weights`: the optimal allocation policy
- `enb`: the optimal effective number of bets
- `counts`: the number of iterations of the objective and the gradient
- `lambda_lb`: the lower bound Lagrange multipliers
- `lambda_ub`: the upper bound Lagrange multipliers
- `lambda_eq`: the equality Lagrange multipliers
- `gradient`: the gradient of the objective function at the optimum
- `hessian`: hessian of the objective function at the optimum

See Also

`solnl`

Examples

```
# extract the invariants from the data
set.seed(123)
log_ret <- matrix(stats::rnorm(400), ncol = 4) / 10

# compute the covariance matrix
sigma <- stats::cov(log_ret)

# torsion
torsion_cov <- torsion(sigma = sigma, model = 'minimum-torsion', method = 'exact')

# 1/N reference
b <- rep(1 / ncol(log_ret), ncol(log_ret))

max_effective_bets(x0 = b, sigma = sigma, t = torsion_cov)
```

`torsion` *Computes the Minimum Torsion Matrix*

Description

Computes the Principal Components Torsion and the Minimum Torsion for diversification analysis.

Usage

```
torsion(sigma, model = "minimum-torsion", method = "exact", max_niter = 10000L)
```

Arguments

`sigma`	A n x n covariance matrix.
`model`	One of: "pca" or "minimum-torsion".
`method`	One of: "approximate" or "exact". Only used when `model = "minimum-torsion"`.
`max_niter`	An `integer` with the maximum number of iterations.

Value

A n x n torsion matrix.

Examples

```
# extract the invariants from the data
set.seed(123)
log_ret <- matrix(rnorm(400), ncol = 4) / 10

# calculate the covariance matrix
sigma <- stats::cov(log_ret)

# torsion
torsion(sigma = sigma, model = 'minimum-torsion', method ='exact')
```

Index