

Package ‘yamlet’

January 10, 2023

Type Package

Title Versatile Curation of Table Metadata

Version 0.10.8

Author Tim Bergsma

Maintainer Tim Bergsma <bergsmat@gmail.com>

BugReports <https://github.com/bergsmat/yamlet/issues>

Description A YAML-based mechanism for working with table metadata. Supports compact syntax for creating, modifying, viewing, exporting, importing, displaying, and plotting metadata coded as column attributes. The ‘yamlet’ dialect is valid ‘YAML’ with defaults and conventions chosen to improve readability. See ?yamlet, ?decorate.data.frame and ?modify.default. See ?read_yamlet ?write_yamlet, ?io_csv, and ?ggplot.decorated.

License GPL-3

Encoding UTF-8

Imports yaml, csv (>= 0.6.2), encode, units, spork, ggplot2, scales, dplyr (>= 0.8.1), rlang, xtable, tidyr, vctrs, pillar

RoxygenNote 7.2.1

VignetteBuilder knitr

Suggests testthat (>= 2.1.0), magrittr, table1, knitr, rmarkdown, gridExtra, haven

NeedsCompilation no

Repository CRAN

Date/Publication 2023-01-10 17:50:02 UTC

R topics documented:

as.integer.classified	2
as_dvec.units	4

as_units.dvec	4
canonical.decorated	5
classified.default	6
decorate.character	7
decorate.data.frame	9
decorations.data.frame	10
desolve.classified	11
desolve.decorated	12
ggplot.decorated	13
io_csv	16
io_table	17
is_dvec	18
mimic.default	18
modify.default	20
print.decorated_ggplot	21
read_yamlet	23
resolve.decorated	24
write_yamlet	25
yamlet	26
yamlet_options	27

Index 30

as.integer.classified *Coerce Classified to Integer*

Description

Coerces classified to integer. Result is like `as.integer(as.numeric(x)) + offset` but has a guide giving original values. If you need a simple integer, consider coercing first to numeric.

Usage

```
## S3 method for class 'classified'
as.integer(
  x,
  offset = 0L,
  ...,
  persistence = getOption("yamlet_persistence", TRUE)
)
```

Arguments

x	classified, see classified
offset	an integer value to add to intermediate result
...	passed to as.numeric , <code>as.integer</code> , and <code>codesolve</code>
persistence	whether to return 'dvec' (<code>is.integer()</code> : TRUE) or just integer.

Value

integer (possibly of class dvec)

See Also

Other classified: [.classified(), [<-classified(), [[.classified(), [[<-classified(),
c.classified(), classified.classified(), classified.data.frame(), classified.default(),
classified.dvec(), classified(), desolve.classified(), unclassified.classified(), unclassified.data.frame(),
unclassified()

Examples

```
library(magrittr)

# create factor with codelist attribute
classified(c('knife', 'fork', 'spoon'))

# give back a simple numeric
classified(c('knife', 'fork', 'spoon')) %>% as.numeric

# intentionally preserve levels as 'guide' attribute
classified(c('knife', 'fork', 'spoon')) %>% as.integer

# implement offset
classified(c('knife', 'fork', 'spoon')) %>% as.integer(-1)

# globally defeat the 'persistence' paradigm
options(yamlet_persistence = FALSE)
c('knife', 'fork', 'spoon') %>%
  classified %>%
  as.integer %>%
  class

# remove option to restore default persistence paradigm
options(yamlet_persistence = NULL)
c('knife', 'fork', 'spoon') %>%
  classified %>%
  as.integer %>%
  class

# locally defeat persistence paradigm
c('knife', 'fork', 'spoon') %>%
  classified %>%
  as.integer(persistence = FALSE) %>%
  class
```

as_dvec.units *Coerce Units to Decorated Vector*

Description

Coerces units to dvec.

Usage

```
## S3 method for class 'units'
as_dvec(x, ...)
```

Arguments

x	units
...	passed arguments

Examples

```
library(magrittr)
library(dplyr)
a <- data.frame(id = 1:4, wt = c(70, 80, 70, 80), sex = c(0,1,0,1))
a %<>% decorate('wt: [ body weight, kg ]')
a %<>% decorate('sex: [ sex, [ female: 0, male: 1]]')
a %<>% decorate('id: identifier')
a %<>% resolve
a %<>% mutate(wt = as_units(wt))
a %<>% mutate(wt = as_dvec(wt))
str(a$wt)
```

as_units.dvec *Coerce Decorated Vector to Units*

Description

Coerces dvec to units. If x has a units attribute, it is used to create class 'units'. It is an error if x has no units attribute.

Usage

```
## S3 method for class 'dvec'
as_units(x, ..., preserve = getOption("yamlet_as_units_preserve", "label"))
```

Arguments

x	dvec
...	ignored
preserve	attributes to preserve; just label by default (class and units are handled implicitly)

Examples

```
library(magrittr)
a <- data.frame(id = 1:4, wt = c(70, 80, 70, 80), sex = c(0,1,0,1))
a %<>% decorate('wt: [ body weight, kg ]')
a %<>% decorate('sex: [ sex, [ female: 0, male: 1]]')
a %<>% decorate('id: identifier')
a %<>% resolve
a$wt %>% as_units
```

canonical.decorated *Sort Decorations*

Description

Enforces canonical attribute order for class 'decorated'. Set of default_keys will be augmented with all observed attribute names and will be expanded or reduced as necessary for each data item.

Usage

```
## S3 method for class 'decorated'
canonical(
  x,
  default_keys = getOption("yamlet_default_keys", list("label", "guide")),
  ...
)
```

Arguments

x	decorated
default_keys	attribute names in preferred order
...	ignored

Value

decorated

See Also

Other canonical: `canonical.yamlet()`, `canonical()`

Other interface: `classified.data.frame()`, `decorate.character()`, `decorate.data.frame()`, `desolve.decorated()`, `ggplot.decorated()`, `io_csv.character()`, `io_csv.data.frame()`, `io_res.character()`, `io_res.decorated()`, `io_table.character()`, `io_table.data.frame()`, `io_yamlet.character()`, `io_yamlet.data.frame()`, `is_parseable.default()`, `mimic.default()`, `modify.default()`, `promote.list()`, `read_yamlet()`, `resolve.decorated()`, `selected.default()`, `write_yamlet()`

Examples

```
# make some decorated data
library(magrittr)
x <- data.frame(x = 1, y = 1, z = factor('a'))
x %<>% decorate('
x: [ guide: mm, desc: this, label: foo ]
"y": [ guide: bar, desc: other ]
')

# retrieve decorations: label not first!
decorations(x)

# sort label first by default
decorations(canonical(x))

# equivalent invocation
canonical(decorations(x))
```

classified.default *Create Classified by Default*

Description

Creates a factor of subclass 'classified', for which there are attribute-preserving methods. In particular, classified has a `codelist` attribute indicating the origin of its levels: it is constructed from the `codelist` attribute of `x` if available, or from 'levels' and 'labels' by default. Unlike the case for `factor`, length of labels cannot be one (i.e., different from length of levels).

Usage

```
## Default S3 method:
classified(
  x = character(),
  levels,
  labels = levels,
  exclude = NA,
  ordered = is.ordered(x),
  nmax = NA,
```

```
    ...
  )
```

Arguments

x	see factor
levels	see factor
labels	see factor , must have same length as levels
exclude	see factor
ordered	see factor
nmax	see factor
...	ignored

Value

'classified' 'factor'

See Also

Other classified: [\[.classified\(\)](#), [\[<-.classified\(\)](#), [\[\[.classified\(\)](#), [\[\[<-.classified\(\)](#), [as.integer.classified\(\)](#), [c.classified\(\)](#), [classified.classified\(\)](#), [classified.data.frame\(\)](#), [classified.dvec\(\)](#), [classified\(\)](#), [desolve.classified\(\)](#), [unclassified.classified\(\)](#), [unclassified.data.frame\(\)](#), [unclassified\(\)](#)

Examples

```
# classified creates a factor with a corresponding codelist attribute
classified(c('a','b','c'))

# codelist 'remembers' the origins of levels
classified(c('a','b','c'), labels = c('A','B','C'))

# classified is 'reversible'
library(magrittr)
c('a','b','c') %>%
  classified(labels = c('A','B','C')) %>%
  unclassified
```

decorate.character *Decorate Character*

Description

Treats x as a file path. By default, metadata is sought from a file with the same base but the 'yaml' extension.

Usage

```
## S3 method for class 'character'
decorate(
  x,
  meta = NULL,
  ...,
  read = getOption("yamlet_import", as.csv),
  ext = getOption("yamlet_extension", ".yaml")
)
```

Arguments

x	file path for table data
meta	file path for corresponding yamlet metadata, or a yamlet object
...	passed to read (if accepted) and to as_yamlet.character
read	function or function name for reading x
ext	file extension for metadata file, if relevant

Value

class 'decorated' 'data.frame'

See Also

Other decorate: [as_decorated.default\(\)](#), [as_decorated\(\)](#), [decorate.data.frame\(\)](#), [decorate.list\(\)](#), [decorate\(\)](#), [decorations.data.frame\(\)](#), [decorations\(\)](#), [redecorate\(\)](#)

Other interface: [canonical.decorated\(\)](#), [classified.data.frame\(\)](#), [decorate.data.frame\(\)](#), [desolve.decorated\(\)](#), [ggplot.decorated\(\)](#), [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#), [io_yamlet.character\(\)](#), [io_yamlet.data.frame\(\)](#), [is_parseable.default\(\)](#), [mimic.default\(\)](#), [modify.default\(\)](#), [promote.list\(\)](#), [read_yamlet\(\)](#), [resolve.decorated\(\)](#), [selected.default\(\)](#), [write_yamlet\(\)](#)

Examples

```
# find data file
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
file

# find metadata file
meta <- system.file(package = 'yamlet', 'extdata', 'quinidine.yaml')
meta

# decorate with explicit metadata reference
a <- decorate(file, meta)

# rely on default metadata path
b <- decorate(file)
```



```
# in this case: same
stopifnot(identical(a, b))
```

```
decorate.data.frame  Decorate Data Frame
```

Description

Decorates a data.frame. Expects metadata in yamlet format, and loads it onto columns as attributes.

Usage

```
## S3 method for class 'data.frame'
decorate(
  x,
  meta = NULL,
  ...,
  persistence = getOption("yamlet_persistence", TRUE)
)
```

Arguments

x	data.frame
meta	file path for corresponding yaml metadata, or a yamlet; an attempt will be made to guess the file path if x has a 'source' attribute
...	passed to decorate.list
persistence	whether to coerce decorated columns to 'dvec' where suitable method exists

Details

As of v0.8.8, the data.frame method for decorate() coerces affected columns using [as_dvec](#) if persistence is true and a suitable method exists. 'vctrs' methods are implemented for class dvec to help attributes persist during tidyverse operations. Details are described in [c.dvec](#). Disable this functionality with options(yamlet_persistence = FALSE).

Value

class 'decorated' 'data.frame'

See Also

[decorate.list](#)

Other interface: [canonical.decorated\(\)](#), [classified.data.frame\(\)](#), [decorate.character\(\)](#), [desolve.decorated\(\)](#), [ggplot.decorated\(\)](#), [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#), [io_yamlet.character\(\)](#), [io_yamlet.data.frame\(\)](#), [is_parseable.default\(\)](#), [mimic.default\(\)](#), [modify.default\(\)](#), [promote.list\(\)](#), [read_yamlet\(\)](#), [resolve.decorated\(\)](#), [selected.default\(\)](#), [write_yamlet\(\)](#)

Other decorate: [as_decorated.default\(\)](#), [as_decorated\(\)](#), [decorate.character\(\)](#), [decorate.list\(\)](#), [decorate\(\)](#), [decorations.data.frame\(\)](#), [decorations\(\)](#), [redecorate\(\)](#)

Examples

```
# find data path
library(csv)
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
file
dat <- as.csv(file) # dat now has 'source' attribute

# use source attribute to find metadata
a <- decorate(as.csv(file))

# supply metadata path (or something close) explicitly
b <- decorate(dat, meta = file)

# these are equivalent
stopifnot(identical(a, b))
```

decorations.data.frame

Retrieve Decorations for Data Frame

Description

Retrieve the decorations of a data.frame; i.e., the metadata used to decorate it. Returns a list with same names as the data.frame. By default, 'class' and 'level' attributes are excluded from the result, as you likely don't want to manipulate these independently.

Usage

```
## S3 method for class 'data.frame'
decorations(
  x,
  ...,
  exclude_attr = getOption("yamlet_exclude_attr", c("class", "levels"))
)
```

Arguments

x	data.frame
...	optional unquoted column names to limit output (passed to select)
exclude_attr	attributes to remove from the result

Value

named list of class 'yamlet'

See Also

Other decorate: [as_decorated.default\(\)](#), [as_decorated\(\)](#), [decorate.character\(\)](#), [decorate.data.frame\(\)](#), [decorate.list\(\)](#), [decorate\(\)](#), [decorations\(\)](#), [redecorate\(\)](#)

Examples

```
# prepare a decorated data.frame
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
x <- decorate(file)

# retrieve the decorations
decorations(x, Subject, time, conc)
```

desolve.classified *Desolve Guide for Classified*

Description

Un-resolves explicit usage of default key 'guide' to implicit usage for class 'classified'. Calls [drop_title](#) (a non-action by default), [unclassified](#), followed by [implicit_guide](#).

Usage

```
## S3 method for class 'classified'
desolve(x, ...)
```

Arguments

x classified
 ... passed to [drop_title](#), [unclassified](#), and [unclassified](#)

Value

dvec

See Also

Other resolve: [desolve.decorated\(\)](#), [desolve.dvec\(\)](#), [desolve\(\)](#), [resolve.decorated\(\)](#), [resolve.dvec\(\)](#), [resolve\(\)](#)

Other classified: [\[.classified\(\)](#), [\[<-.classified\(\)](#), [\[\[.classified\(\)](#), [\[\[<-.classified\(\)](#), [as.integer.classified\(\)](#), [c.classified\(\)](#), [classified.classified\(\)](#), [classified.data.frame\(\)](#), [classified.default\(\)](#), [classified.dvec\(\)](#), [classified\(\)](#), [unclassified.classified\(\)](#), [unclassified.data.frame\(\)](#), [unclassified\(\)](#)

Examples

```

library(magrittr)
x <- as_dvec(
  4:6,
  guide = list(a = 4L, b = 5L, c = 6L)
)

# untouched
x %>% str

# resolved
x %>% resolve %>% str

# resolved and desolved
x %>% resolve %>% desolve %>% str

```

desolve.decorated *Desolve Guide for Decorated*

Description

Un-resolves explicit usage of default key 'guide' to implicit usage for 'decorated' class. Simply calls [drop_title](#), [unclassified](#), and [implicit_guide](#).

Usage

```

## S3 method for class 'decorated'
desolve(x, ...)

```

Arguments

x decorated
 ... passed to [drop_title](#), [unclassified](#), and [implicit_guide](#)

Value

decorated

See Also

Other resolve: [desolve.classified\(\)](#), [desolve.dvec\(\)](#), [desolve\(\)](#), [resolve.decorated\(\)](#), [resolve.dvec\(\)](#), [resolve\(\)](#)

Other interface: [canonical.decorated\(\)](#), [classified.data.frame\(\)](#), [decorate.character\(\)](#), [decorate.data.frame\(\)](#), [ggplot.decorated\(\)](#), [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#), [io_yamlet.character\(\)](#), [io_yamlet.data.frame\(\)](#), [is_parseable.default\(\)](#), [mimic.default\(\)](#), [modify.default\(\)](#), [promote.list\(\)](#), [read_yamlet\(\)](#), [resolve.decorated\(\)](#), [selected.default\(\)](#), [write_yamlet\(\)](#)

Examples

```
library(magrittr)
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
x <- decorate(file)

# this is how Age, glyco, Race look when resolved
x %>% resolve %>% decorations(Age, glyco, Race)

# we can resolve two of them and then 'unresolve' all of them
x %>% resolve(glyco, Race) %>% desolve %>% decorations(Age, glyco, Race)
```

ggplot.decorated	<i>Create a New ggplot for a Decorated Data Frame</i>
------------------	---

Description

Creates a new `ggplot` object for a decorated data.frame. This is the `ggplot()` method for class `'decorated'`. It creates a `ggplot` object using the default method, but reclassifies it as `'decorated_ggplot'` so that a custom print method is invoked; see [print.decorated_ggplot](#).

Usage

```
## S3 method for class 'decorated'
ggplot(data, ...)
```

Arguments

<code>data</code>	decorated, see decorate
<code>...</code>	passed to ggplot

Details

This approach is similar to but more flexible than the method for [ggready](#). For fine control, you can switch between `'data.frame'` and `'decorated'` using [as_decorated](#) (supplies null decorations) and [as.data.frame](#) (preserves decorations).

Value

return value like [ggplot](#) but inheriting `'decorated_ggplot'`

See Also

`decorate` `resolve` `ggready`

Other decorated_ggplot: [ggplot_build.decorated_ggplot\(\)](#), [print.decorated_ggplot\(\)](#)

Other interface: [canonical.decorated\(\)](#), [classified.data.frame\(\)](#), [decorate.character\(\)](#), [decorate.data.frame\(\)](#), [desolve.decorated\(\)](#), [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#),

```
io_yamlet.character(), io_yamlet.data.frame(), is_parseable.default(), mimic.default(),
modify.default(), promote.list(), read_yamlet(), resolve.decorated(), selected.default(),
write_yamlet()
```

Examples

```
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
library(ggplot2)
library(dplyr)
library(magrittr)
# par(ask = FALSE)

x <- decorate(file)
x %<>% filter(!is.na(conc))

# Manipulate class to switch among ggplot methods.
class(x)
class(data.frame(x))
class(as_decorated(data.frame(x)))

# The bare data.frame gives boring labels and un-ordered groups.
map <- aes(x = time, y = conc, color = Heart)
data.frame(x) %>% ggplot(map) + geom_point()

# Decorated data.frame uses supplied labels.
# Notice CHF levels are still not ordered. (Moderate first.)
x %>% ggplot(map) + geom_point()

# If we resolve Heart, CHF levels are ordered.
x %<>% resolve(Heart)
x %>% ggplot(map) + geom_point()

# We can map aesthetics as decorations.
x %<>% decorate('Heart: [ color: [gold, purple, green]]')
x %>% ggplot(map) + geom_point()

# Colors are matched to particular levels. Purple drops out here:
x %>% filter(Heart != 'Moderate') %>% ggplot(map) + geom_point()

# We can resolve other columns for a chance to enrich the output with units.
x %<>% resolve
suppressWarnings( # because this complains for columns with no units
  x <- modify(x, title = paste0(label, '\n(', units, ')'))
)
x %>% ggplot(map) + geom_point()

# Or something fancier.
x %<>% modify(conc, title = 'conc_serum. (mg*L^-1.)')
x %>% ggplot(map) + geom_point()

# The y-axis title is deliberately given in spork syntax for elegant coercion:
library(spork)
x %<>% modify(conc, expression = as.expression(as_plotmath(as_spork(title))))
```

```

x %>% ggplot(map) + geom_point()
# Add a fancier label for Heart, and facet by a factor:
x %<>% modify(Heart, expression = as.expression(as_plotmath(as_spork('CHF^\\*'))))
x %>% ggplot(map) + geom_point() + facet_wrap(~Creatinine)

# ggready handles the units and plotmath implicitly for a 'standard' display:
x %>% ggready %>% ggplot(map) + geom_point() + facet_wrap(~Creatinine)

# Notice that instead of over-writing the label
# attribute, we are creating a stack of label
# substitutes (title, expression) so that
# label is still available as an argument
# if we want to try something else. The
# print method by default looks for all of these.
# Precedence is expression, title, label, column name.
# Precedence can be controlled using
# options(decorated_ggplot_search = c(a, b, ...)).

# Here we try a dataset with conditional labels and units.

file <- system.file(package = 'yamlet', 'extdata', 'phenobarb.csv')
x <- file %>% decorate %>% resolve
# Note that value has two elements for label and guide.
x %>% decorations(value)

# The print method defaults to the first, with warning.
map <- aes(x = time, y = value, color = event)

x %>% ggplot(map) + geom_point()

# If we subset appropriately, the relevant value is substituted.
x %>% filter(event == 'conc') %>% ggplot(map) + geom_point()

x %>% filter(event == 'conc') %>%
ggplot(aes(x = time, y = value, color = ApgarInd)) + geom_point()

x %>% filter(event == 'dose') %>%
ggplot(aes(x = time, y = value, color = Wt)) +
geom_point() +
scale_y_log10() +
scale_color_gradientn(colours = rainbow(4))

# print.decorated_ggplot will attempt to honor coordinated aesthetics.
x <- data.frame(x = c(1:6, 3:8), y = c(1:6, 1:6), z = letters[c(1:6, 1:6)])
x %<>% decorate('z: [color: ["red", "blue", "green", "gold", "black", "magenta"]]')
x %<>% decorate('z: [fill: ["red", "blue", "green", "gold", "black", "magenta"]]')
x %<>% decorate('z: [shape: [20, 21, 22, 23, 24, 25]]')
x %<>% decorate('z: [linetype: [6, 5, 4, 3, 2, 1]]')
x %<>% decorate('z: [alpha: [ .9, .8, .7, .6, .5, .4]]')
x %<>% decorate('z: [size: [1, 1.5, 2, 2.5, 3, 3.5]]')
x %>% ggplot(aes(
  x, y,

```

```

    color = z,
    fill = z,
    shape = z,
    linetype = z,
    alpha = z,
    size = z,
  )) +
  geom_point() +
  geom_line(size = 1)

```

 io_csv

Import and Export Documented Tables as CSV

Description

Imports or exports documented tables as comma-separated variable. Generic, with methods that extend [as.csv](#).

Usage

```
io_csv(x, ...)
```

Arguments

x	object
...	passed arguments

Value

See methods.

See Also

Other io: [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_res\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#), [io_table\(\)](#), [io_yamlet.character\(\)](#), [io_yamlet.data.frame\(\)](#), [io_yamlet.yamlet\(\)](#), [io_yamlet\(\)](#)

Examples

```

# generate some decorated data
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
x <- decorate(file)

# get a temporary filepath
out <- file.path(tempdir(), 'out.csv')

# save file using io_csv (returns filepath)
foo <- io_csv(x, out)
stopifnot(identical(out, foo))

```



```
# read using this filepath
y <- io_csv(foo)

# lossless round-trip (ignoring source attribute)
attr(x, 'source') <- NULL
attr(y, 'source') <- NULL
stopifnot(identical(x, y))
```

io_table

Import and Export Documented Tables

Description

Imports or exports documented tables. Generic, with methods that extend [read.table](#) and [write.table](#).

Usage

```
io_table(x, ...)
```

Arguments

x	object
...	passed arguments

Value

See methods.

See Also

Other io: [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_csv\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_res\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#), [io_yamlet.character\(\)](#), [io_yamlet.data.frame\(\)](#), [io_yamlet.yamlet\(\)](#), [io_yamlet\(\)](#)

Examples

```
# generate some decorated data
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
x <- decorate(file)

# get a temporary filepath
out <- file.path(tempdir(), 'out.tab')

# save file using io_table (returns filepath)
foo <- io_table(x, out)
stopifnot(identical(out, foo))

# read using this filepath
```

```

y <- io_table(foo, as.is = TRUE)

# lossless round-trip
attr(x, 'source') <- NULL
rownames(x) <- NULL
rownames(y) <- NULL
stopifnot(identical(x, y))

```

is_dvec	<i>Test if Class is dvec</i>
---------	------------------------------

Description

Tests whether x inherits 'dvec'.

Usage

```
is_dvec(x)
```

Arguments

x object

Value

logical

Examples

```

is_dvec(1L)
is_dvec(as_dvec(1L))

```

mimic.default	<i>Try To Look Like Another Equal-length Variable</i>
---------------	---

Description

Tries to mimic another vector or factor. If meaningful and possible, x acquires a guide attribute with labels from corresponding values in y. Any codelist attribute is removed. No guide is created for zero-length x. If x is a factor, unused levels are removed.

Usage

```

## Default S3 method:
mimic(x, y = x, ...)

```

Arguments

x	vector-like
y	vector-like, same length as x
...	ignored arguments

Value

same class as x

See Also

Other mimic: `mimic.classified()`, `mimic()`

Other interface: `canonical.decorated()`, `classified.data.frame()`, `decorate.character()`, `decorate.data.frame()`, `desolve.decorated()`, `ggplot.decorated()`, `io_csv.character()`, `io_csv.data.frame()`, `io_res.character()`, `io_res.decorated()`, `io_table.character()`, `io_table.data.frame()`, `io_yamlet.character()`, `io_yamlet.data.frame()`, `is_parseable.default()`, `modify.default()`, `promote.list()`, `read_yamlet()`, `resolve.decorated()`, `selected.default()`, `write_yamlet()`

Examples

```
library(magrittr)
library(dplyr)
let <- letters[1:5]
LET <- LETTERS[1:5]
int <- 0L:4L
num <- as.numeric(int)
fac <- factor(let)
css <- classified(let)

# any of these can mimic any other
str(mimic(LET, let))
str(mimic(num, let))
str(mimic(let, num))

# factors get a guide and classifieds get a named codelist
str(mimic(fac, int))
str(mimic(css, int))

# int can 'pick up' the factor levels as guide names
str(mimic(int, css))

# if two variables mean essentially the same thing,
# mimic lets you save space
x <- data.frame(id = 1:2, ID = c('A', 'B'))
x
x %<>% mutate(id = mimic(id, ID)) %>% select(-ID)
x
# ID still available, in principle:
x %>% as_decorated %>% resolve
```

 modify.default

Modify Attributes of Indicated Components by Default

Description

Modifies the attributes of each indicated element (all elements by default). Tries to assign the value of an expression to the supplied label, with existing attributes and the object itself (.) available as arguments. Gives a warning if the supplied label is considered reserved. Intends to support anything with one or more non-empty names.

Usage

```
## Default S3 method:
modify(
  x,
  ...,
  .reserved = getOption("yamlet_modify_reserved", c("class", "levels", "labels",
    "names"))
)
```

Arguments

x	object
...	indicated columns, or name-value pairs
.reserved	reserved labels that warn on assignment

Details

The name of the component itself is available during assignments as attribute 'name' (any pre-existing attribute 'name' is temporarily masked). After all assignments are complete, the value of 'name' is enforced at the object level. Thus, modify expressions can modify component names.

As currently implemented, the expression is evaluated by `eval_tidy`, with attributes supplied as the data argument. Thus, names in the expression may be disambiguated, e.g. with `.data`. See examples.

Value

same class as x

See Also

Other modify: `modify()`, `named()`, `selected.default()`, `selected()`

Other interface: `canonical.decorated()`, `classified.data.frame()`, `decorate.character()`, `decorate.data.frame()`, `desolve.decorated()`, `ggplot.decorated()`, `io_csv.character()`, `io_csv.data.frame()`, `io_res.character()`, `io_res.decorated()`, `io_table.character()`, `io_table.data.frame()`, `io_yamlet.character()`, `io_yamlet.data.frame()`, `is_parseable.default()`, `mimic.default()`, `promote.list()`, `read_yamlet()`, `resolve.decorated()`, `selected.default()`, `write_yamlet()`

Examples

```

library(magrittr)
library(dplyr)
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
x <- decorate(file)

# modify selected columns
x %<>% modify(title = paste(label, '(', guide, ')'), time)
x %>% select(time, conc) %>% decorations

# modify (almost) all columns
x %<>% modify(title = paste(label, '(', guide, ')'), -Subject)
x %>% select(time, conc) %>% decorations

# use column itself
x %<>% modify(`defined values` = sum(!is.na(.)))
x %>% select(time) %>% decorations

# rename column
x %<>% modify(time, name = label)
names(x)

# warn if assignment fails
## Not run:
\donttest{
x %<>% modify(title = foo, time)
}
## End(Not run)

# support lists
list(a = 1, b = 1:10, c = letters) %>%
modify(length = length(.), b:c)

x %<>% select(Subject) %>% modify(label = NULL, `defined values` = NULL)

# distinguish data and environment
location <- 'environment'
x %>% modify(where = location) %>% decorations
x %>% modify(where = .env$location) %>% decorations
## Not run:
\donttest{
x%>% modify(where = .data$location) %>% decorations
}
## End(Not run)
x %>% modify(location = 'attributes', where = location) %>% decorations
x %>% modify(location = 'attributes', where = .data$location) %>% decorations

```

print.decorated_ggplot

Substitute Expressions, Titles, Labels and Aesthetics in ggplots

Description

Default labels (e.g. mappings for x, y, etc.) will be used to search data for more meaningful labels, taking first available from attributes with names in search. Likewise, if mappings for colour (color), fill, size, etc. (see defaults for discrete) indicate columns that have these defined as attributes, an attempt is made to add a corresponding discrete scale if one does not exist already. Values are recycled if necessary and are specific by ordinal position to the corresponding level of the corresponding variable. Levels are defined in increasing priority by `sort(unique(x))`, any guide attribute, any factor levels, or any codelist attribute.

Usage

```
## S3 method for class 'decorated_ggplot'
print(
  x,
  ...,
  search = getOption("yamlet_decorated_ggplot_search", c("expression", "title", "label")),
  discrete = getOption("yamlet_decorated_ggplot_discrete", c("colour", "fill", "size",
    "shape", "linetype", "alpha")),
  drop = getOption("yamlet_decorated_ggplot_drop", TRUE)
)
```

Arguments

x	class 'decorated_ggplot' from ggplot.decorated
...	passed arguments
search	attribute names from which to seek label substitutes
discrete	discrete aesthetics to map from data decorations where available
drop	should unused factor levels be omitted from data-driven discrete scales?

Value

see [print.ggplot](#)

See Also

Other decorated_ggplot: [ggplot.decorated\(\)](#), [ggplot_build.decorated_ggplot\(\)](#)

Examples

```
example(ggplot.decorated)
```

read_yamlet	<i>Read Yamlet</i>
-------------	--------------------

Description

Reads yamlet from file. Similar to [io_yamlet.character](#) but also reads text fragments.

Usage

```
read_yamlet(  
  x,  
  ...,  
  default_keys = getOption("yamlet_default_keys", list("label", "guide"))  
)
```

Arguments

x file path for yamlet, or vector of yamlet in storage syntax
... passed to [as_yamlet](#)
default_keys character: default keys for the first n anonymous members of each element

Value

yamlet: a named list with default keys applied

See Also

[decorate.data.frame](#)

Other interface: [canonical.decorated\(\)](#), [classified.data.frame\(\)](#), [decorate.character\(\)](#), [decorate.data.frame\(\)](#), [desolve.decorated\(\)](#), [ggplot.decorated\(\)](#), [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#), [io_yamlet.character\(\)](#), [io_yamlet.data.frame\(\)](#), [is_parseable.default\(\)](#), [mimic.default\(\)](#), [modify.default\(\)](#), [promote.list\(\)](#), [resolve.decorated\(\)](#), [selected.default\(\)](#), [write_yamlet\(\)](#)

Examples

```
library(csv)  
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')  
meta <- system.file(package = 'yamlet', 'extdata', 'quinidine.yaml')  
x <- as.csv(file)  
y <- read_yamlet(meta)  
x <- decorate(x, meta = y)  
stopifnot(identical(x, decorate(file)))
```

resolve.decorated *Resolve Guide for Decorated*

Description

Resolves implicit usage of default key 'guide' to explicit usage for decorated class. Calls [explicit_guide](#), [classified](#), and [make_title](#).

Usage

```
## S3 method for class 'decorated'
resolve(x, ...)
```

Arguments

x	decorated
...	passed to explicit_guide , classified , and make_title

Value

decorated

See Also

Other resolve: [desolve.classified\(\)](#), [desolve.decorated\(\)](#), [desolve.dvec\(\)](#), [desolve\(\)](#), [resolve.dvec\(\)](#), [resolve\(\)](#)

Other interface: [canonical.decorated\(\)](#), [classified.data.frame\(\)](#), [decorate.character\(\)](#), [decorate.data.frame\(\)](#), [desolve.decorated\(\)](#), [ggplot.decorated\(\)](#), [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#), [io_yamlet.character\(\)](#), [io_yamlet.data.frame\(\)](#), [is_parseable.default\(\)](#), [mimic.default\(\)](#), [modify.default\(\)](#), [promote.list\(\)](#), [read_yamlet\(\)](#), [selected.default\(\)](#), [write_yamlet\(\)](#)

Examples

```
# generate some decorated data
library(magrittr)
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
x <- decorate(file)
x %>% decorations(Age, glyco)

# resolve everything, and show selected decorations
x %>% resolve %>% decorations(Age, glyco)

# resolve selectively, and show selected decorations
x %>% resolve(glyco) %>% decorations(Age, glyco)
```

write_yamlet	<i>Write Yamlet</i>
--------------	---------------------

Description

Writes yamlet to file. Similar to [io_yamlet.yamlet](#) but returns invisible storage format instead of invisible storage location.

Usage

```
write_yamlet(
  x,
  con = stdout(),
  eol = "\n",
  useBytes = FALSE,
  default_keys = getOption("yamlet_default_keys", list("label", "guide")),
  fileEncoding = getOption("encoding"),
  block = FALSE,
  ...
)
```

Arguments

x	something that can be coerced to class 'yamlet', like a yamlet object or a decorated data.frame
con	passed to writeLines
eol	end-of-line; passed to writeLines as sep
useBytes	passed to writeLines
default_keys	character: default keys for the first n anonymous members of each element
fileEncoding	if con is character, passed to file as encoding
block	whether to write block scalars
...	passed to as_yamlet and to as.character.yamlet

Value

invisible character representation of yamlet (storage syntax)

See Also

[decorate.list](#)

Other interface: [canonical.decorated\(\)](#), [classified.data.frame\(\)](#), [decorate.character\(\)](#), [decorate.data.frame\(\)](#), [desolve.decorated\(\)](#), [ggplot.decorated\(\)](#), [io_csv.character\(\)](#), [io_csv.data.frame\(\)](#), [io_res.character\(\)](#), [io_res.decorated\(\)](#), [io_table.character\(\)](#), [io_table.data.frame\(\)](#), [io_yamlet.character\(\)](#), [io_yamlet.data.frame\(\)](#), [is_parseable.default\(\)](#), [mimic.default\(\)](#), [modify.default\(\)](#), [promote.list\(\)](#), [read_yamlet\(\)](#), [resolve.decorated\(\)](#), [selected.default\(\)](#)

Examples

```
library(csv)
file <- system.file(package = 'yamlet', 'extdata', 'quinidine.csv')
meta <- system.file(package = 'yamlet', 'extdata', 'quinidine.yaml')
x <- as.csv(file)
y <- read_yamlet(meta)
x <- decorate(x, meta = y)
identical(x, decorate(file))
tmp <- tempfile()
write_yamlet(x, tmp)
stopifnot(identical(read_yamlet(meta), read_yamlet(tmp)))
```

yamlet

yamlet: Versatile Curation of Table Metadata

Description

The **yamlet** package supports storage and retrieval of table metadata in yaml format. The most important function is `decorate.character`: it lets you 'decorate' your data by attaching attributes retrieved from a file in yaml format. Typically your data will be of class 'data.frame', but it could be anything that is essentially a named list.

Storage Format

Storage format for 'yamlet' is a text file containing well-formed yaml. Technically, it is a map of sequences. Though well formed, it need not be complete: attributes or their names may be missing.

In the simplest case, the data specification consists of a list of column (item) names, followed by semicolons. Perhaps you only have one column:

```
mpg:
```

or maybe several:

```
mpg:
```

```
cyl:
```

```
disp:
```

If you know descriptive labels for your columns, provide them (skip a space after the colon).

```
mpg: fuel economy
```

```
cyl: number of cylinders
```

```
disp: displacement
```

If you know units, create a sequence with square brackets.

```
mpg: [ fuel economy, miles/gallon ]
```

```
cyl: number of cylinders
```

```
disp: [ displacement , in^3 ]
```

If you are going to give units, you probably should give a key first, since the first anonymous element is 'label' by default, and the second is 'guide'. (A guide can be units for numeric variables, factor levels/labels for categorical variables, or a format string for dates, times, and datetimes.) You could give just the units but you would have to be specific:

```
mpg: [units: miles/gallon]
```

You can over-ride default keys by providing them in your data:

```
mpg: [units: miles/gallon]
_keys: [label, units]
```

Notice that stored yamlet can be informationally defective while syntactically correct. If you don't know an item key at the time of data authoring, you can omit it:

```
race: [race, [white: 0, black: 1, 2, asian: 3 ]]
```

Or perhaps you know the key but not the value:

```
race: [race, [white: 0, black: 1, asian: 2, ? other ]]
```

Notice that race is factor-like; the factor sequence is nested within the attribute sequence. Equivalently:

```
race: [label: race, guide: [white: 0, black: 1, asian: 2, ? other ]]
```

If you have a codelist of length one, you should still enclose it in brackets:

```
sex: [Sex, [ M ]]
```

To get started using yamlet, see `?as_yamlet.character` and examples there. See also `?decorate` which adds yamlet values to corresponding items in your data. See also `?print.decorated` which uses label attributes, if present, as axis labels.

Note: the quinidine and phenobarb datasets in the examples are borrowed from **nlme** (`?Quinidine`, `?Phenobarb`), with some reorganization.

yamlet_options

Display Global Yamlet Options

Description

Displays global yamlet options: those options whose names begin with 'yamlet_'.

- **yamlet_append_units_open**: see `append_units.default`. Controls how labels are constructed for variables with 'units' attributes. In brief, units are wrapped in parentheses, and appended to the label.
- **yamlet_append_units_close**: see `append_units.default`. Controls how labels are constructed for variables with 'units' attributes. In brief, units are wrapped in parentheses, and appended to the label.
- **yamlet_append_units_style**: see `append_units.default`. Determines parsing as 'plot-math' or 'latex', or 'plain' for no parsing.
- **yamlet_append_units_target**: see `append_units.default`. By default, append result is assigned to attribute 'label', but could be something else like 'title'.

- **yamlet_default_keys**: see [as_yamlet.character](#). The first two yamlet attributes without specified names are assumed to be 'label' and 'guide'.
- **yamlet_persistence**: see [decorate.list](#) and [as.integer.classified](#). By default, persistence of column attributes is implemented by creating 'dvec' objects (decorated vectors) using [vctrs](#) methodology.
- **yamlet_cell_value**: see [as.data.frame.yamlet](#). Controls how cells are calculated when converting yamlet (decorations) to a data.frame.
- **yamlet_import**: see [decorate.character](#). Controls how primary data is read from file (default: `as.csv()`).
- **yamlet_extension**: see [decorate.character](#). Controls what file extension is expected for yamlet metadata (default: `'.yaml'`)
- **yamlet_overwrite**: see [decorate.list](#). Controls whether existing decorations are overwritten.
- **yamlet_exclude_attr**: see [decorations.data.frame](#) Controls what attributes are excluded from display.
- **yamlet_with_title**: see [make_title.dvec](#) and [drop_title.dvec](#). For objects with (implied) units attributes, titles are by default automatically created on `resolve()` and destroyed on `desolve()`. Interacts with `yamlet_append_units_*`.
- **yamlet_infer_guide**: see [explicit_guide.yamlet](#). Identifies the function that will be used to reclassify 'guide' as something more explicit.
- **yamlet_explicit_guide_overwrite**: see [explicit_guide.data.frame](#) and [explicit_guide.dvec](#). In the latter case, controls whether existing attributes are overwritten.
- **yamlet_explicit_guide_simplify**: [explicit_guide.data.frame](#) and [explicit_guide.dvec](#). Ordinarily, the 'guide' attribute is removed if something more useful can be inferred.
- **yamlet_decorated_ggplot_search**: see [print.decorated_ggplot](#). The print method for `decorated_ggplot` populates axis labels by searching first for attributes named 'expression', 'title', and 'label'. Customizable.
- **yamlet_decorated_ggplot_discrete**: see [print.decorated_ggplot](#). Discrete aesthetics to map from data decorations where available.
- **yamlet_decorated_ggplot_drop**: see [print.decorated_ggplot](#). Should unused factor levels be omitted from data-driven discrete scales?
- **yamlet_ggreedy_parse**: see [ggready.data.frame](#), [ggready.decorated](#). Whether to parse axis labels. TRUE by default, but may be problematic if unintended.
- **yamlet_modify_reserved**: see [modify.default](#). A list of reserved labels that warn on reassignment.
- **yamlet_promote_reserved**: see [promote.list](#). Attributes to leave untouched when promoting singularities.
- **yamlet_promote**: see [filter.decorated](#). Whether to promote when filtering 'decorated'.
- **yamlet_as_units_preserve**: [as_units.dvec](#). What attributes to preserve when converting dvec to units. Just 'label' by default. Assign `options(yamlet_as_units_preserve = character(0))` to remove all.

Usage

```
yamlet_options()
```

Value

list

Examples

```
yamlet_options()
```

Index

- * **canonical**
 - canonical.decorated, 5
- * **classified**
 - as.integer.classified, 2
 - classified.default, 6
 - desolve.classified, 11
- * **decorated_ggplot**
 - ggplot.decorated, 13
 - print.decorated_ggplot, 22
- * **decorate**
 - decorate.character, 7
 - decorate.data.frame, 9
 - decorations.data.frame, 10
- * **interface**
 - canonical.decorated, 5
 - decorate.character, 7
 - decorate.data.frame, 9
 - desolve.decorated, 12
 - ggplot.decorated, 13
 - mimic.default, 18
 - modify.default, 20
 - read_yamlet, 23
 - resolve.decorated, 24
 - write_yamlet, 25
- * **io**
 - io_csv, 16
 - io_table, 17
- * **mimic**
 - mimic.default, 18
- * **modify**
 - modify.default, 20
- * **resolve**
 - desolve.classified, 11
 - desolve.decorated, 12
 - resolve.decorated, 24
- [.classified, 3, 7, 11
- [[.classified, 3, 7, 11
- append_units.default, 27
- as.character.yamlet, 25
- as.csv, 16
- as.data.frame, 13
- as.data.frame.yamlet, 28
- as.integer, 2
- as.integer.classified, 2, 7, 11, 28
- as.numeric, 2
- as_decorated, 8, 9, 11, 13
- as_decorated.default, 8, 9, 11
- as_dvec, 9
- as_dvec.units, 4
- as_units.dvec, 4, 28
- as_yamlet, 23, 25
- as_yamlet.character, 8, 28
- c.classified, 3, 7, 11
- c.dvec, 9
- canonical, 6
- canonical.decorated, 5, 8, 9, 12, 13, 19, 20, 23–25
- canonical.yamlet, 6
- classified, 2, 3, 7, 11, 24
- classified.classified, 3, 7, 11
- classified.data.frame, 3, 6–9, 11–13, 19, 20, 23–25
- classified.default, 3, 6, 11
- classified.dvec, 3, 7, 11
- decorate, 8, 9, 11, 13
- decorate.character, 6, 7, 9, 11–13, 19, 20, 23–26, 28
- decorate.data.frame, 6, 8, 9, 11–13, 19, 20, 23–25
- decorate.list, 8, 9, 11, 25, 28
- decorations, 8, 9, 11
- decorations.data.frame, 8, 9, 10, 28
- desolve, 2, 11, 12, 24
- desolve.classified, 3, 7, 11, 12, 24
- desolve.decorated, 6, 8, 9, 11, 12, 13, 19, 20, 23–25
- desolve.dvec, 11, 12, 24

- drop_title, [11](#), [12](#)
- drop_title.dvec, [28](#)

- eval_tidy, [20](#)
- explicit_guide, [24](#)
- explicit_guide.data.frame, [28](#)
- explicit_guide.dvec, [28](#)
- explicit_guide.yamlet, [28](#)

- factor, [6](#), [7](#)
- file, [25](#)
- filter.decorated, [28](#)

- ggplot, [13](#)
- ggplot.decorated, [6](#), [8](#), [9](#), [12](#), [13](#), [19](#), [20](#), [22–25](#)
- ggplot_build.decorated_ggplot, [13](#), [22](#)
- ggready, [13](#)
- ggready.data.frame, [28](#)
- ggready.decorated, [28](#)

- implicit_guide, [11](#), [12](#)
- io_csv, [16](#), [17](#)
- io_csv.character, [6](#), [8](#), [9](#), [12](#), [13](#), [16](#), [17](#), [19](#), [20](#), [23–25](#)
- io_csv.data.frame, [6](#), [8](#), [9](#), [12](#), [13](#), [16](#), [17](#), [19](#), [20](#), [23–25](#)
- io_res, [16](#), [17](#)
- io_res.character, [6](#), [8](#), [9](#), [12](#), [13](#), [16](#), [17](#), [19](#), [20](#), [23–25](#)
- io_res.decorated, [6](#), [8](#), [9](#), [12](#), [13](#), [16](#), [17](#), [19](#), [20](#), [23–25](#)
- io_table, [16](#), [17](#)
- io_table.character, [6](#), [8](#), [9](#), [12](#), [13](#), [16](#), [17](#), [19](#), [20](#), [23–25](#)
- io_table.data.frame, [6](#), [8](#), [9](#), [12](#), [13](#), [16](#), [17](#), [19](#), [20](#), [23–25](#)
- io_yamlet, [16](#), [17](#)
- io_yamlet.character, [6](#), [8](#), [9](#), [12](#), [14](#), [16](#), [17](#), [19](#), [20](#), [23–25](#)
- io_yamlet.data.frame, [6](#), [8](#), [9](#), [12](#), [14](#), [16](#), [17](#), [19](#), [20](#), [23–25](#)
- io_yamlet.yamlet, [16](#), [17](#), [25](#)
- is_dvec, [18](#)
- is_parseable.default, [6](#), [8](#), [9](#), [12](#), [14](#), [19](#), [20](#), [23–25](#)

- make_title, [24](#)
- make_title.dvec, [28](#)

- mimic, [19](#)
- mimic.classified, [19](#)
- mimic.default, [6](#), [8](#), [9](#), [12](#), [14](#), [18](#), [20](#), [23–25](#)
- modify, [20](#)
- modify.default, [6](#), [8](#), [9](#), [12](#), [14](#), [19](#), [20](#), [23–25](#), [28](#)

- named, [20](#)

- print.decorated_ggplot, [13](#), [21](#), [28](#)
- print.ggplot, [22](#)
- promote.list, [6](#), [8](#), [9](#), [12](#), [14](#), [19](#), [20](#), [23–25](#), [28](#)

- read.table, [17](#)
- read_yamlet, [6](#), [8](#), [9](#), [12](#), [14](#), [19](#), [20](#), [23](#), [24](#), [25](#)
- redecorate, [8](#), [9](#), [11](#)
- resolve, [11](#), [12](#), [24](#)
- resolve.decorated, [6](#), [8](#), [9](#), [11](#), [12](#), [14](#), [19](#), [20](#), [23](#), [24](#), [25](#)
- resolve.dvec, [11](#), [12](#), [24](#)

- select, [10](#)
- selected, [20](#)
- selected.default, [6](#), [8](#), [9](#), [12](#), [14](#), [19](#), [20](#), [23–25](#)

- unclassified, [3](#), [7](#), [11](#), [12](#)
- unclassified.classified, [3](#), [7](#), [11](#)
- unclassified.data.frame, [3](#), [7](#), [11](#)

- write.table, [17](#)
- write_yamlet, [6](#), [8](#), [9](#), [12](#), [14](#), [19](#), [20](#), [23](#), [24](#), [25](#)
- writeLines, [25](#)

- yamlet, [26](#)
- yamlet_options, [27](#)