

Package ‘zen4R’

January 19, 2023

Version 0.8

Date 2023-01-19

Title Interface to 'Zenodo' REST API

Maintainer Emmanuel Blondel <emmanuel.blondel1@gmail.com>

Depends R (>= 3.3.0), methods

Imports R6, httr, jsonlite, XML, xml2, keyring, tools, atom4R

Suggests testthat, parallel, knitr, markdown

Description Provides an Interface to 'Zenodo' (<<https://zenodo.org>>) REST API, including management of depositions, attribution of DOIs by 'Zenodo' and upload and download of files.

License MIT + file LICENSE

URL <https://github.com/eblondel/zen4R>

BugReports <https://github.com/eblondel/zen4R/issues>

LazyLoad yes

RoxygenNote 7.2.1

Encoding UTF-8

VignetteBuilder knitr

NeedsCompilation no

Author Emmanuel Blondel [aut, cre] (<<https://orcid.org/0000-0002-5870-5762>>),
Julien Barde [ctb] (<<https://orcid.org/0000-0002-3519-6141>>),
Stephen Eglen [ctb] (<<https://orcid.org/0000-0001-8607-8025>>),
Hans Van Calster [ctb] (<<https://orcid.org/0000-0001-8595-8426>>),
Floris Vanderhaeghe [ctb] (<<https://orcid.org/0000-0002-6378-6229>>)

Repository CRAN

Date/Publication 2023-01-19 18:00:02 UTC

R topics documented:

download_zenodo	2
export_zenodo	3
get_versions	4
zen4R	4
zen4RLogger	5
ZenodoManager	7
ZenodoRecord	17
ZenodoRequest	37
zenodo_pat	39

Index	40
--------------	-----------

download_zenodo	<i>download_zenodo</i>
-----------------	------------------------

Description

download_zenodo allows to download archives attached to a Zenodo record, identified by its DOI or concept DOI.

Usage

```
download_zenodo(
  doi,
  path = ".",
  files = list(),
  logger = NULL,
  quiet = FALSE,
  ...
)
```

Arguments

doi	a Zenodo DOI or concept DOI
path	the target directory where to download files
files	subset of filenames to restrain to download. If ignored, all files will be downloaded.
logger	a logger to print Zenodo API-related messages. The logger can be either NULL, "INFO" (with minimum logs), or "DEBUG" (for complete curl http calls logs)
quiet	Logical (FALSE by default). Do you want to suppress informative messages (not warnings)?
...	any other arguments for parallel downloading (more information at ZenodoRecord , downloadFiles() documentation)

Examples

```
## Not run:
#simple download (sequential)
download_zenodo("10.5281/zenodo.2547036")

library(parallel)
#download files as parallel using a cluster approach (for both Unix/Win systems)
download_zenodo("10.5281/zenodo.2547036",
  parallel = TRUE, parallel_handler = parLapply, cl = makeCluster(2))

#download files as parallel using mclapply (for Unix systems)
download_zenodo("10.5281/zenodo.2547036",
  parallel = TRUE, parallel_handler = mclapply, mc.cores = 2)

## End(Not run)
```

export_zenodo	<i>export_zenodo</i>
---------------	----------------------

Description

export_zenodo allows to export a Zenodo record, identified by its DOI or concept DOI, using one of the export formats supported by Zenodo.

Usage

```
export_zenodo(doi, filename, format, append_format = TRUE, logger = NULL)
```

Arguments

doi	a Zenodo DOI or concept DOI
filename	a base file name (without file extension) to export to.
format	a valid Zenodo export format among the following: BibTeX, CSL, DataCite, DublinCore, DCAT, JSON, JSON-LD, GeoJSON, MARCXML.
append_format	wether format name has to be appended to the filename. Default is TRUE (for backward compatibility reasons). Set it to FALSE if you want to use only the filename.
logger	a logger to print Zenodo API-related messages. The logger can be either NULL, "INFO" (with minimum logs), or "DEBUG" (for complete curl http calls logs)

Value

the exported file name (with extension)

Examples

```
## Not run:
export_zenodo("10.5281/zenodo.2547036", filename = "test", format = "BibTeX", append_format = F)

## End(Not run)
```

get_versions	<i>get_versions</i>
--------------	---------------------

Description

get_versions allows to execute a workflow

Usage

```
get_versions(doi, logger = NULL)
```

Arguments

doi	a Zenodo DOI or concept DOI
logger	a logger to print messages. The logger can be either NULL, "INFO" (with minimum logs), or "DEBUG" (for complete curl http calls logs)

Value

an object of class data.frame giving the record versions including date, version number and version-specific DOI.

Examples

```
## Not run:
get_versions("10.5281/zenodo.2547036")

## End(Not run)
```

zen4R	<i>Interface to 'Zenodo' REST API</i>
-------	---------------------------------------

Description

Provides an Interface to 'Zenodo' (<<https://zenodo.org>>) REST API, including management of depositions, attribution of DOIs by 'Zenodo', upload and download of files.

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

zen4RLogger

zen4RLogger

Description

zen4RLogger

zen4RLogger

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a simple logger

Public fields

verbose.info logger info status

verbose.debug logger debug status

loggerType Logger type, either "INFO", "DEBUG" or NULL (if no logger)

Methods

Public methods:

- [zen4RLogger\\$logger\(\)](#)
- [zen4RLogger\\$INFO\(\)](#)
- [zen4RLogger\\$WARN\(\)](#)
- [zen4RLogger\\$ERROR\(\)](#)
- [zen4RLogger\\$new\(\)](#)
- [zen4RLogger\\$getClassName\(\)](#)
- [zen4RLogger\\$getClass\(\)](#)
- [zen4RLogger\\$clone\(\)](#)

Method [logger\(\)](#): internal logger function for the Zenodo manager

Usage:

```
zen4RLogger$logger(type, text)
```

Arguments:

type logger message type, "INFO", "WARN", or "ERROR"

text log message

Method [INFO\(\)](#): internal INFO logger function

Usage:

```
zen4RLogger$INFO(text)
```

Arguments:

text log message

Method WARN(): internal WARN logger function

Usage:

zen4RLogger\$WARN(text)

Arguments:

text log message

Method ERROR(): internal ERROR logger function

Usage:

zen4RLogger\$ERROR(text)

Arguments:

text log message

Method new(): initialize the Zenodo logger

Usage:

zen4RLogger\$new(logger = NULL)

Arguments:

logger logger type NULL, 'INFO', or 'DEBUG'

Method getClassName(): Get object class name

Usage:

zen4RLogger\$getClassName()

Returns: the class name, object of class character

Method getClass(): Get object class

Usage:

zen4RLogger\$getClass()

Returns: the class, object of class R6

Method clone(): The objects of this class are cloneable with this method.

Usage:

zen4RLogger\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Logger class used internally by zen4R

ZenodoManager	<i>ZenodoManager</i>
---------------	----------------------

Description

ZenodoManager

ZenodoManager

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an ZenodoManager

Super class

[zen4R](#): [zen4RLogger](#) -> ZenodoManager

Public fields

anonymous Zenodo manager anonymous status, TRUE when no token is specified

Methods**Public methods:**

- [ZenodoManager\\$new\(\)](#)
- [ZenodoManager\\$getToken\(\)](#)
- [ZenodoManager\\$getLicenses\(\)](#)
- [ZenodoManager\\$getLicenseById\(\)](#)
- [ZenodoManager\\$getCommunities\(\)](#)
- [ZenodoManager\\$getCommunityById\(\)](#)
- [ZenodoManager\\$getGrants\(\)](#)
- [ZenodoManager\\$getGrantsByName\(\)](#)
- [ZenodoManager\\$getGrantById\(\)](#)
- [ZenodoManager\\$getFunders\(\)](#)
- [ZenodoManager\\$getFundersByName\(\)](#)
- [ZenodoManager\\$getFunderById\(\)](#)
- [ZenodoManager\\$getDepositions\(\)](#)
- [ZenodoManager\\$getDepositionByConceptDOI\(\)](#)
- [ZenodoManager\\$getDepositionByDOI\(\)](#)
- [ZenodoManager\\$getDepositionById\(\)](#)
- [ZenodoManager\\$getDepositionByConceptId\(\)](#)

- ZenodoManager\$depositRecord()
- ZenodoManager\$depositRecordVersion()
- ZenodoManager\$deleteRecord()
- ZenodoManager\$deleteRecordByDOI()
- ZenodoManager\$deleteRecords()
- ZenodoManager\$createEmptyRecord()
- ZenodoManager\$editRecord()
- ZenodoManager\$discardChanges()
- ZenodoManager\$publishRecord()
- ZenodoManager\$getFiles()
- ZenodoManager\$uploadFile()
- ZenodoManager\$deleteFile()
- ZenodoManager\$getRecords()
- ZenodoManager\$getRecordByConceptDOI()
- ZenodoManager\$getRecordByDOI()
- ZenodoManager\$getRecordById()
- ZenodoManager\$getRecordByConceptId()
- ZenodoManager\$clone()

Method new(): initializes the Zenodo Manager

Usage:

```
ZenodoManager$new(
  url = "https://zenodo.org/api",
  token = zenodo_pat(),
  logger = NULL,
  keyring_backend = "env"
)
```

Arguments:

`url` Zenodo API URL. By default, the url is set to "https://zenodo.org/api". For tests, the Zenodo sandbox API URL can be used: https://sandbox.zenodo.org/api

`token` the user token. By default an attempt will be made to retrieve token using `zenodo_pat`

`logger` logger type. The logger can be either NULL, "INFO" (with minimum logs), or "DEBUG" (for complete curl http calls logs)

`keyring_backend` The **keyring** backend used to store user token. The `keyring_backend` can be set to use a different backend for storing the Zenodo token with **keyring** (Default value is 'env').

Method getToken(): Get user token

Usage:

```
ZenodoManager$getToken()
```

Returns: the token, object of class character

Method getLicenses(): Get Licenses supported by Zenodo.

Usage:

ZenodoManager\$getLicenses(pretty = TRUE)

Arguments:

pretty Prettify the output. By default the argument *pretty* is set to TRUE which will returns the list of licenses as data.frame. Set *pretty* = FALSE to get the raw list of licenses.

Returns: list of licenses as data.frame or list

Method getLicenseById(): Get license by Id.

Usage:

ZenodoManager\$getLicenseById(id)

Arguments:

id license id

Returns: the license

Method getCommunities(): Get Communities supported by Zenodo.

Usage:

ZenodoManager\$getCommunities(pretty = TRUE)

Arguments:

pretty Prettify the output. By default the argument *pretty* is set to TRUE which will returns the list of communities as data.frame. Set *pretty* = FALSE to get the raw list of communities

Returns: list of communities as data.frame or list

Method getCommunityById(): Get community by Id.

Usage:

ZenodoManager\$getCommunityById(id)

Arguments:

id community id

Returns: the community

Method getGrants(): Get Grants supported by Zenodo.

Usage:

ZenodoManager\$getGrants(q = "", pretty = TRUE, size = 1000)

Arguments:

q an Elasticsearch compliant query, object of class character. Default is empty. Note that the Zenodo API restrains a maximum number of 10,000 grants to be retrieved. Consequently, not all grants can be listed from Zenodo, a query has to be specified.

pretty Prettify the output. By default the argument *pretty* is set to TRUE which will returns the list of grants as data.frame. Set *pretty* = FALSE to get the raw list of grants

size number of grants to be returned. By default equal to 1000.

Returns: list of grants as data.frame or list

Method getGrantsByName(): Get grants by name.

Usage:

ZenodoManager\$getGrantsByName(name, pretty = TRUE)

Arguments:

name name

pretty Prettify the output. By default the argument pretty is set to TRUE which will returns the list of grants as data.frame. Set pretty = FALSE to get the raw list of grants

Returns: list of grants as data.frame or list

Method getGrantById(): Get grant by Id.

Usage:

ZenodoManager\$getGrantById(id)

Arguments:

id grant id

Returns: the grant

Method getFunders(): Get Funders supported by Zenodo based on a query.

Usage:

ZenodoManager\$getFunders(q = "", pretty = TRUE, size = 1000)

Arguments:

q an ElasticSearch compliant query, object of class character. Default is empty. Note that the Zenodo API restrains a maximum number of 10,000 funders to be retrieved. Consequently, not all funders can be listed from Zenodo, a query has to be specified.

pretty Prettify the output. By default the argument pretty is set to TRUE which will returns the list of funders as data.frame. Set pretty = FALSE to get the raw list of funders

size number of funders to be returned. By default equal to 1000.

Returns: list of funders as data.frame or list

Method getFundersByName(): Get funders by name.

Usage:

ZenodoManager\$getFundersByName(name, pretty = TRUE)

Arguments:

name name

pretty Prettify the output. By default the argument pretty is set to TRUE which will returns the list of funders as data.frame. Set pretty = FALSE to get the raw list of funders

Returns: list of funders as data.frame or list

Method getFunderById(): Get funder by Id.

Usage:

ZenodoManager\$getFunderById(id)

Arguments:

id funder id

Returns: the funder

Method `getDepositions()`: Get the list of Zenodo records deposited in your Zenodo workspace. By default the list of depositions will be returned by page with a size of 10 results per page (default size of the Zenodo API). The parameter `q` allows to specify an ElasticSearch-compliant query to filter depositions (default query is empty to retrieve all records). The argument `all_versions`, if set to `TRUE` allows to get all versions of records as part of the depositions list. The argument `exact` specifies that an exact matching is wished, in which case paginated search will be disabled (only the first search page will be returned). Examples of ElasticSearch queries for Zenodo can be found at <https://help.zenodo.org/guides/search/>.

Usage:

```
ZenodoManager$getDepositions(
  q = "",
  size = 10,
  all_versions = FALSE,
  exact = TRUE,
  quiet = FALSE
)
```

Arguments:

`q` Elastic-Search-compliant query, as object of class character. Default is ""
`size` number of depositions to be retrieved per request (paginated). Default is 10
`all_versions` object of class logical indicating if all versions of deposits have to be retrieved. Default is FALSE
`exact` object of class logical indicating if exact matching has to be applied. Default is TRUE
`quiet` object of class logical indicating if logs have to be skipped. Default is FALSE

Returns: a list of ZenodoRecord

Method `getDepositionByConceptDOI()`: Get a Zenodo deposition record by concept DOI (generic DOI common to all deposition record versions).

Usage:

```
ZenodoManager$getDepositionByConceptDOI(conceptdoi)
```

Arguments:

`conceptdoi` the concept DOI, object of class character

Returns: an object of class ZenodoRecord if record does exist, NULL otherwise

Method `getDepositionByDOI()`: Get a Zenodo deposition record by DOI.

Usage:

```
ZenodoManager$getDepositionByDOI(doi)
```

Arguments:

`doi` the DOI, object of class character

Returns: an object of class ZenodoRecord if record does exist, NULL otherwise

Method `getDepositionById()`: Get a Zenodo deposition record by ID.

Usage:

```
ZenodoManager$getDepositionById(recid)
```

Arguments:

recid the record ID, object of class character

Returns: an object of class ZenodoRecord if record does exist, NULL otherwise

Method `getDepositionByConceptId()`: Get a Zenodo deposition record by concept ID.

Usage:

```
ZenodoManager$getDepositionByConceptId(conceptrecid)
```

Arguments:

conceptrecid the record concept ID, object of class character

Returns: an object of class ZenodoRecord if record does exist, NULL otherwise

Method `depositRecord()`: Deposits a record on Zenodo.

Usage:

```
ZenodoManager$depositRecord(record, publish = FALSE)
```

Arguments:

record the record to deposit, object of class ZenodoRecord

publish object of class logical indicating if record has to be published (default FALSE). Can be set to TRUE (to use CAUTIOUSLY, only if you want to publish your record)

Returns: TRUE if deposited (and eventually published), FALSE otherwise

Method `depositRecordVersion()`: Deposits a record version on Zenodo. For details about the behavior of this function, see <https://developers.zenodo.org/#new-version>

Usage:

```
ZenodoManager$depositRecordVersion(
  record,
  delete_latest_files = TRUE,
  files = list(),
  publish = FALSE
)
```

Arguments:

record the record version to deposit, object of class ZenodoRecord

delete_latest_files object of class logical indicating if latest files have to be deleted. Default is TRUE

files a list of files to be uploaded with the new record version

publish object of class logical indicating if record has to be published (default FALSE)

Returns: TRUE if deposited (and eventually published), FALSE otherwise

Method `deleteRecord()`: Deletes a record given its ID

Usage:

```
ZenodoManager$deleteRecord(recordId)
```

Arguments:

recordId the ID of the record to be deleted

Returns: TRUE if deleted, FALSE otherwise

Method deleteRecordByDOI(): Deletes a record by DOI

Usage:

```
ZenodoManager$deleteRecordByDOI(doi)
```

Arguments:

doi the DOI of the record to be deleted

Returns: TRUE if deleted, FALSE otherwise

Method deleteRecords(): Deletes all Zenodo deposited (unpublished) records. The parameter q allows to specify an ElasticSearch-compliant query to filter depositions (default query is empty to retrieve all records). Examples of ElasticSearch queries for Zenodo can be found at <https://help.zenodo.org/guides/search/>.

Usage:

```
ZenodoManager$deleteRecords(q = "", size = 10)
```

Arguments:

q an ElasticSearch compliant query, object of class character

size number of records to be passed to \$getDepositions method

Returns: TRUE if all records have been deleted, FALSE otherwise

Method createEmptyRecord(): Creates an empty record in the Zenodo deposit. Returns the record newly created in Zenodo, as an object of class ZenodoRecord with an assigned identifier.

Usage:

```
ZenodoManager$createEmptyRecord()
```

Returns: an object of class ZenodoRecord

Method editRecord(): Unlocks a record already submitted. Required to edit metadata of a Zenodo record already published.

Usage:

```
ZenodoManager$editRecord(recordId)
```

Arguments:

recordId the ID of the record to unlock and set in editing mode.

Returns: an object of class ZenodoRecord

Method discardChanges(): Discards changes on a Zenodo record.

Usage:

```
ZenodoManager$discardChanges(recordId)
```

Arguments:

recordId the ID of the record for which changes have to be discarded.

Returns: an object of class ZenodoRecord

Method publishRecord(): Publishes a Zenodo record.

Usage:

ZenodoManager\$publishRecord(recordId)

Arguments:

recordId the ID of the record to be published.

Returns: an object of class ZenodoRecord

Method getFiles(): Get list of files attached to a Zenodo record.

Usage:

ZenodoManager\$getFiles(recordId)

Arguments:

recordId the ID of the record.

Returns: list of files

Method uploadFile(): Uploads a file to a Zenodo record

Usage:

ZenodoManager\$uploadFile(path, record = NULL, recordId = NULL)

Arguments:

path Local path of the file

record object of class ZenodoRecord

recordId ID of the record. Deprecated, use record instead to take advantage of the new Zenodo bucket upload API.

Method deleteFile(): Deletes a file for a record

Usage:

ZenodoManager\$deleteFile(recordId, fileId)

Arguments:

recordId ID of the record

fileId ID of the file to delete

Method getRecords(): Get the list of Zenodo records. By default the list of records will be returned by page with a size of 10 results per page (default size of the Zenodo API). The parameter q allows to specify an ElasticSearch-compliant query to filter depositions (default query is empty to retrieve all records). The argument all_versions, if set to TRUE allows to get all versions of records as part of the depositions list. The argument exact specifies that an exact matching is wished, in which case paginated search will be disabled (only the first search page will be returned). Examples of ElasticSearch queries for Zenodo can be found at <https://help.zenodo.org/guides/search/>.

Usage:

```
ZenodoManager$getRecords(
  q = "",
  size = 10,
  all_versions = FALSE,
  exact = FALSE
)
```

Arguments:

q Elastic-Search-compliant query, as object of class character. Default is ""
size number of records to be retrieved per request (paginated). Default is 10
all_versions object of class logical indicating if all versions of records have to be retrieved.
Default is FALSE
exact object of class logical indicating if exact matching has to be applied. Default is TRUE
quiet object of class logical indicating if logs have to be skipped. Default is FALSE

Returns: a list of ZenodoRecord

Method `getRecordByConceptDOI()`: Get Record by concept DOI*Usage:*

```
ZenodoManager$getRecordByConceptDOI(conceptdoi)
```

Arguments:

conceptdoi the concept DOI

Returns: a object of class ZenodoRecord

Method `getRecordByDOI()`: Get Record by DOI*Usage:*

```
ZenodoManager$getRecordByDOI(doi)
```

Arguments:

doi the DOI

Returns: a object of class ZenodoRecord

Method `getRecordById()`: Get Record by ID*Usage:*

```
ZenodoManager$getRecordById(recid)
```

Arguments:

recid the record ID

Returns: a object of class ZenodoRecord

Method `getRecordByConceptId()`: Get Record by concept ID*Usage:*

```
ZenodoManager$getRecordByConceptId(conceptrecid)
```

Arguments:

conceptrecid the concept ID

Returns: a object of class ZenodoRecord

Method `clone()`: The objects of this class are cloneable with this method.*Usage:*

```
ZenodoManager$clone(deep = FALSE)
```

Arguments:

deep Whether to make a deep clone.

Note

Main user class to be used with **zen4R**

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

Examples

```
## Not run:
ZENODO <- ZenodoManager$new(
  url = "https://sandbox.zenodo.org/api",
  token = "<your_token>",
  logger = "INFO"
)

#create (deposit) an empty record
newRec <- ZENODO$createEmptyRecord()

#create and fill a local (not yet deposited) record
myrec <- ZenodoRecord$new()
myrec$setTitle("my R package")
myrec$setDescription("A description of my R package")
myrec$setUploadType("software")
myrec$addCreator(
  firstname = "John", lastname = "Doe",
  affiliation = "Independent", orcid = "0000-0000-0000-0000"
)
myrec$setLicense("mit")
myrec$setAccessRight("open")
myrec$setDOI("mydoi") #use this method if your DOI has been assigned elsewhere, outside Zenodo
myrec$addCommunity("ecfunded")

#deposit the record
myrec <- ZENODO$depositRecord(myrec)

#publish a record (with caution!!)
#this method will PUBLISH the deposition done earlier
ZENODO$publishRecord(myrec$id)
#With even more caution the publication can be done with a shortcut argument at deposit time
ZENODO$depositRecord(myrec, publish = TRUE)

#delete a record (by id)
#this methods only works for unpublished deposits
#(if a record is published, it cannot be deleted anymore!)
ZENODO$deleteRecord(myrec$id)

#HOW TO UPLOAD FILES to a deposit

#upload a file
ZENODO$uploadFile("path/to/your/file", record = myrec)
```

```

#list files
zen_files <- ZENODO$getFiles(myrec$id)

#delete a file?
ZENODO$deleteFile(myrec$id, zen_files[[1]]$id)

## End(Not run)

```

ZenodoRecord

ZenodoRecord

Description

ZenodoRecord
ZenodoRecord

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling an ZenodoRecord

Super class

[zen4R](#): : [zen4RLogger](#) -> ZenodoRecord

Public fields

conceptdoi record Concept DOI (common to all record versions)
conceptrecid record concept id
created record creation date
doi record doi
doi_url record doi URL
files list of files associated to the record
id record id
links list of links associated to the record
metadata metadata elements associated to the record
modified record modification date
owner record owner
record_id record_id
state record state
submitted record submission status
title record title
version record version

Methods**Public methods:**

- ZenodoRecord\$new()
- ZenodoRecord\$prereserveDOI()
- ZenodoRecord\$setDOI()
- ZenodoRecord\$getConceptDOI()
- ZenodoRecord\$getFirstDOI()
- ZenodoRecord\$getLastDOI()
- ZenodoRecord\$getVersions()
- ZenodoRecord\$setUploadType()
- ZenodoRecord\$setPublicationType()
- ZenodoRecord\$setImageType()
- ZenodoRecord\$setPublicationDate()
- ZenodoRecord\$setEmbargoDate()
- ZenodoRecord\$setTitle()
- ZenodoRecord\$setDescription()
- ZenodoRecord\$setAccessRight()
- ZenodoRecord\$setAccessConditions()
- ZenodoRecord\$addCreator()
- ZenodoRecord\$removeCreator()
- ZenodoRecord\$removeCreatorByName()
- ZenodoRecord\$removeCreatorByAffiliation()
- ZenodoRecord\$removeCreatorByORCID()
- ZenodoRecord\$removeCreatorByGND()
- ZenodoRecord\$addContributor()
- ZenodoRecord\$removeContributor()
- ZenodoRecord\$removeContributorByName()
- ZenodoRecord\$removeContributorByAffiliation()
- ZenodoRecord\$removeContributorByORCID()
- ZenodoRecord\$removeContributorByGND()
- ZenodoRecord\$setLicense()
- ZenodoRecord\$setVersion()
- ZenodoRecord\$setLanguage()
- ZenodoRecord\$addRelatedIdentifier()
- ZenodoRecord\$removeRelatedIdentifier()
- ZenodoRecord\$setReferences()
- ZenodoRecord\$addReference()
- ZenodoRecord\$removeReference()
- ZenodoRecord\$setKeywords()
- ZenodoRecord\$addKeyword()
- ZenodoRecord\$removeKeyword()
- ZenodoRecord\$addSubject()

- `ZenodoRecord$removeSubject()`
- `ZenodoRecord$removeSubjectByTerm()`
- `ZenodoRecord$removeSubjectByIdentifier()`
- `ZenodoRecord$setNotes()`
- `ZenodoRecord$setCommunities()`
- `ZenodoRecord$addCommunity()`
- `ZenodoRecord$removeCommunity()`
- `ZenodoRecord$setGrants()`
- `ZenodoRecord$addGrant()`
- `ZenodoRecord$removeGrant()`
- `ZenodoRecord$setJournalTitle()`
- `ZenodoRecord$setJournalVolume()`
- `ZenodoRecord$setJournalIssue()`
- `ZenodoRecord$setJournalPages()`
- `ZenodoRecord$setConferenceTitle()`
- `ZenodoRecord$setConferenceAcronym()`
- `ZenodoRecord$setConferenceDates()`
- `ZenodoRecord$setConferencePlace()`
- `ZenodoRecord$setConferenceUrl()`
- `ZenodoRecord$setConferenceSession()`
- `ZenodoRecord$setConferenceSessionPart()`
- `ZenodoRecord$setImprintPublisher()`
- `ZenodoRecord$setImprintISBN()`
- `ZenodoRecord$setImprintPlace()`
- `ZenodoRecord$setPartofTitle()`
- `ZenodoRecord$setPartofPages()`
- `ZenodoRecord$setThesisUniversity()`
- `ZenodoRecord$addThesisSupervisor()`
- `ZenodoRecord$removeThesisSupervisor()`
- `ZenodoRecord$removeThesisSupervisorByName()`
- `ZenodoRecord$removeThesisSupervisorByAffiliation()`
- `ZenodoRecord$removeThesisSupervisorByORCID()`
- `ZenodoRecord$removeThesisSupervisorByGND()`
- `ZenodoRecord$addLocation()`
- `ZenodoRecord$removeLocation()`
- `ZenodoRecord$exportAs()`
- `ZenodoRecord$exportAsBibTeX()`
- `ZenodoRecord$exportAsCSL()`
- `ZenodoRecord$exportAsDataCite()`
- `ZenodoRecord$exportAsDublinCore()`
- `ZenodoRecord$exportAsDCAT()`
- `ZenodoRecord$exportAsJSON()`

- [ZenodoRecord\\$exportAsJSONLD\(\)](#)
- [ZenodoRecord\\$exportAsGeoJSON\(\)](#)
- [ZenodoRecord\\$exportAsMARCXML\(\)](#)
- [ZenodoRecord\\$exportAsAllFormats\(\)](#)
- [ZenodoRecord\\$listFiles\(\)](#)
- [ZenodoRecord\\$downloadFiles\(\)](#)
- [ZenodoRecord\\$print\(\)](#)
- [ZenodoRecord\\$toDCEntry\(\)](#)
- [ZenodoRecord\\$clone\(\)](#)

Method `new()`: method is used to instantiate a [ZenodoRecord](#)

Usage:

```
ZenodoRecord$new(obj = NULL, logger = "INFO")
```

Arguments:

`obj` an optional list object to create the record

`logger` a logger to print log messages. It can be either `NULL`, `"INFO"` (with minimum logs), or `"DEBUG"` (for complete curl http calls logs)

Method `prereserveDOI()`: Set `prereserve_doi` if `TRUE`, `FALSE` otherwise to create a record without prereserved DOI by Zenodo. By default, this method will be called to prereserve a DOI assuming the record created doesn't yet handle a DOI. To avoid prereserving a DOI call `$prereserveDOI(FALSE)` on your record.

Usage:

```
ZenodoRecord$prereserveDOI(prereserve)
```

Arguments:

`prereserve` whether a DOI has to be pre-reserved by Zenodo

Method `setDOI()`: Set the DOI. This method can be used if a DOI has been already assigned outside Zenodo. This method will call the method `$prereserveDOI(FALSE)`.

Usage:

```
ZenodoRecord$setDOI(doi)
```

Arguments:

`doi` DOI to set for the record

Method `getConceptDOI()`: Get the concept (generic) DOI. The concept DOI is a generic DOI common to all versions of a Zenodo record. When a deposit is unsubmitted, this concept DOI is inherited based on the prereserved DOI of the first record version.

Usage:

```
ZenodoRecord$getConceptDOI()
```

Returns: the concept DOI, object of class `character`

Method `getFirstDOI()`: Get DOI of the first record version.

Usage:

```
ZenodoRecord$getFirstDOI()
```

Returns: the first DOI, object of class character

Method getLastDOI(): Get DOI of the latest record version.

Usage:

```
ZenodoRecord$getLastDOI()
```

Returns: the last DOI, object of class character

Method getVersions(): Get record versions with creation/publication date, version (ordering number) and DOI.

Usage:

```
ZenodoRecord$getVersions()
```

Returns: a data.frame with the record versions

Method setUploadType(): Set the upload type (mandatory).

Usage:

```
ZenodoRecord$setUploadType(uploadType)
```

Arguments:

uploadType record upload type among the following values: 'publication', 'poster', 'presentation', 'dataset', 'image', 'video', 'software', 'lesson', 'physicalobject', 'other'

Method setPublicationType(): Set the publication type (mandatory if upload type is 'publication').

Usage:

```
ZenodoRecord$setPublicationType(publicationType)
```

Arguments:

publicationType record publication type among the following values: 'annotationcollection', 'book', 'section', 'conferencepaper', 'datamanagementplan', 'article', 'patent', 'preprint', 'deliverable', 'milestone', 'proposal', 'report', 'softwaredocumentation', 'taxonomicreatment', 'technicalnote', 'thesis', 'workingpaper', 'other'

Method setImageType(): Set the image type (mandatory if image type is 'image').

Usage:

```
ZenodoRecord$setImageType(imageType)
```

Arguments:

imageType record publication type among the following values: 'figure', 'plot', 'drawing', 'diagram', 'photo', or 'other'

Method setPublicationDate(): Set the publication date.

Usage:

```
ZenodoRecord$setPublicationDate(publicationDate)
```

Arguments:

publicationDate object of class Date

Method setEmbargoDate(): Set the embargo date.

Usage:

```
ZenodoRecord$setEmbargoDate(embargoDate)
```

Arguments:

embargoDate object of class Date

Method setTitle(): Set the record title.

Usage:

```
ZenodoRecord$setTitle(title)
```

Arguments:

title object of class character

Method setDescription(): Set the record description

Usage:

```
ZenodoRecord$setDescription(description)
```

Arguments:

description object of class character

Method setAccessRight(): Set the access right.

Usage:

```
ZenodoRecord$setAccessRight(accessRight)
```

Arguments:

accessRight record access right among the following values: 'open', 'embargoed', 'restricted', 'closed'

Method setAccessConditions(): set the access conditions.

Usage:

```
ZenodoRecord$setAccessConditions(accessConditions)
```

Arguments:

accessConditions object of class character

Method addCreator(): Add a creator for the record. One approach is to use the `firstname` and `lastname` arguments, that by default will be concatenated for Zenodo as `lastname, firstname`. For more flexibility over this, the `name` argument can be directly used.

Usage:

```
ZenodoRecord$addCreator(  
  firstname,  
  lastname,  
  name = paste(lastname, firstname, sep = ", "),  
  affiliation = NULL,  
  orcid = NULL,  
  gnd = NULL  
)
```

Arguments:

firstname creator first name

lastname creator last name
name creator name
affiliation creator affiliation (optional)
orcid creator ORCID (optional)
gnd creator GND (optional)

Returns: TRUE if added, FALSE otherwise

Method removeCreator(): Removes a creator by a property. The by parameter should be the name of the creator property ('name' - in the form 'lastname, firstname', 'affiliation', 'orcid' or 'gnd').

Usage:

ZenodoRecord\$removeCreator(by, property)

Arguments:

by property used as criterion to remove the creator
property property value used to remove the creator

Returns: TRUE if removed, FALSE otherwise

Method removeCreatorByName(): Removes a creator by name.

Usage:

ZenodoRecord\$removeCreatorByName(name)

Arguments:

name creator name

Returns: TRUE if removed, FALSE otherwise

Method removeCreatorByAffiliation(): Removes a creator by affiliation.

Usage:

ZenodoRecord\$removeCreatorByAffiliation(affiliation)

Arguments:

affiliation creator affiliation

Returns: TRUE if removed, FALSE otherwise

Method removeCreatorByORCID(): Removes a creator by ORCID.

Usage:

ZenodoRecord\$removeCreatorByORCID(orcid)

Arguments:

orcid creator ORCID

Returns: TRUE if removed, FALSE otherwise

Method removeCreatorByGND(): Removes a creator by GND.

Usage:

ZenodoRecord\$removeCreatorByGND(gnd)

Arguments:

gnd creator GND

Returns: TRUE if removed, FALSE otherwise

Method addContributor(): Add a contributor for the record. Firstname, lastname, and type are mandatory.

Usage:

```
ZenodoRecord$addContributor(
  firstname,
  lastname,
  type,
  affiliation = NULL,
  orcid = NULL,
  gnd = NULL
)
```

Arguments:

firstname contributor first name

lastname contributor last name

type contributor type, among values: ContactPerson, DataCollector, DataCurator, DataManager, Distributor, Editor, Funder, HostingInstitution, Producer, ProjectLeader, ProjectManager, ProjectMember, RegistrationAgency, RegistrationAuthority, RelatedPerson, Researcher, ResearchGroup, RightsHolder, Supervisor, Sponsor, WorkPackageLeader, Other.

affiliation contributor affiliation (optional)

orcid contributor orcid (optional)

gnd contributor gnd (optional)

Returns: TRUE if added, FALSE otherwise

Method removeContributor(): Removes a contributor by a property. The by parameter should be the name of the contributor property ('name' - in the form 'lastname, firstname', 'affiliation', 'orcid' or 'gnd'). FALSE otherwise.

Usage:

```
ZenodoRecord$removeContributor(by, property)
```

Arguments:

by property used as criterion to remove the contributor

property property value used to remove the contributor

Returns: TRUE if removed, FALSE otherwise

Method removeContributorByName(): Removes a contributor by name.

Usage:

```
ZenodoRecord$removeContributorByName(name)
```

Arguments:

name contributor name

Returns: TRUE if removed, FALSE otherwise

Method removeContributorByAffiliation(): Removes a contributor by affiliation.

Usage:

ZenodoRecord\$removeContributorByAffiliation(affiliation)

Arguments:

affiliation contributor affiliation

Returns: TRUE if removed, FALSE otherwise

Method removeContributorByORCID(): Removes a contributor by ORCID.

Usage:

ZenodoRecord\$removeContributorByORCID(orcid)

Arguments:

orcid contributor ORCID

Returns: TRUE if removed, FALSE otherwise

Method removeContributorByGND(): Removes a contributor by GND.

Usage:

ZenodoRecord\$removeContributorByGND(gnd)

Arguments:

gnd contributor GND

Returns: TRUE if removed, FALSE otherwise

Method setLicense(): Set license. The license should be set with the Zenodo id of the license. If not recognized by Zenodo, the function will return an error. The list of licenses can be fetched with the ZenodoManager and the function \$getLicenses().

Usage:

ZenodoRecord\$setLicense(licenseId)

Arguments:

licenseId a license Id

Method setVersion(): Set record version.

Usage:

ZenodoRecord\$setVersion(version)

Arguments:

version the record version to set

Method setLanguage(): Set the language.

Usage:

ZenodoRecord\$setLanguage(language)

Arguments:

language ISO 639-2 or 639-3 code

Method addRelatedIdentifier(): Adds a related identifier with a given relation.

Usage:

ZenodoRecord\$addRelatedIdentifier(relation, identifier, resource_type = NULL)

Arguments:

relation relation type among following values: isCitedBy, cites, isSupplementTo, isSupplementedBy, isContinuedBy, continues, isDescribedBy, describes, hasMetadata, isMetadataFor, isNewVersionOf, isPreviousVersionOf, isPartOf, hasPart, isReferencedBy, references, isDocumentedBy, documents, isCompiledBy, compiles, isVariantFormOf, isOriginalFormOf, isIdenticalTo, isAlternateIdentifier, isReviewedBy, reviews, isDerivedFrom, isSourceOf, requires, isRequiredBy, isObsoletedBy, obsoletes

identifier resource identifier

resource_type optional resource type, value among possible publication types, image types, or upload types (except 'publication' and 'image' for which a publication/image has to be specified). Default is NULL

Method removeRelatedIdentifier(): Removes a related identifier with a given relation.

Usage:

ZenodoRecord\$removeRelatedIdentifier(relation, identifier)

Arguments:

relation relation type among following values: isCitedBy, cites, isSupplementTo, isSupplementedBy, isContinuedBy, continues, isDescribedBy, describes, hasMetadata, isMetadataFor, isNewVersionOf, isPreviousVersionOf, isPartOf, hasPart, isReferencedBy, references, isDocumentedBy, documents, isCompiledBy, compiles, isVariantFormOf, isOriginalFormOf, isIdenticalTo, isAlternateIdentifier, isReviewedBy, reviews, isDerivedFrom, isSourceOf, requires, isRequiredBy, isObsoletedBy, obsoletes

identifier resource identifier

Method setReferences(): Set references

Usage:

ZenodoRecord\$setReferences(references)

Arguments:

references a vector or list of references to set for the record

Method addReference(): Add a reference

Usage:

ZenodoRecord\$addReference(reference)

Arguments:

reference the reference to add

Returns: TRUE if added, FALSE otherwise

Method removeReference(): Remove a reference

Usage:

ZenodoRecord\$removeReference(reference)

Arguments:

reference the reference to remove

Returns: TRUE if removed, FALSE otherwise

Method setKeywords(): Set keywords

Usage:

ZenodoRecord\$setKeywords(keywords)

Arguments:

keywords a vector or list of keywords to set for the record

Method addKeyword(): Add a keyword

Usage:

ZenodoRecord\$addKeyword(keyword)

Arguments:

keyword the keyword to add

Returns: TRUE if added, FALSE otherwise

Method removeKeyword(): Remove a keyword

Usage:

ZenodoRecord\$removeKeyword(keyword)

Arguments:

keyword the keyword to remove

Returns: TRUE if removed, FALSE otherwise

Method addSubject(): Adds a subject given a term and identifier

Usage:

ZenodoRecord\$addSubject(term, identifier)

Arguments:

term subject term

identifier subject identifier

Method removeSubject(): Removes subject(s) by a property. The by parameter should be the name of the subject property ('term' or 'identifier').

Usage:

ZenodoRecord\$removeSubject(by, property)

Arguments:

by property used as criterion to remove subjects

property property value used to remove subjects

Returns: TRUE if at least one subject is removed, FALSE otherwise.

Method removeSubjectByTerm(): Removes subject(s) by term.

Usage:

ZenodoRecord\$removeSubjectByTerm(term)

Arguments:

term the term to use to remove subject(s)

Returns: TRUE if at least one subject is removed, FALSE otherwise.

Method removeSubjectByIdentifier(): Removes subject(s) by identifier

Usage:

```
ZenodoRecord$removeSubjectByIdentifier(identifier)
```

Arguments:

identifier the identifier to use to remove subject(s)

Returns: TRUE if at least one subject is removed, FALSE otherwise.

Method setNotes(): Set notes. HTML is not allowed

Usage:

```
ZenodoRecord$setNotes(notes)
```

Arguments:

notes object of class character

Method setCommunities(): Set a vector of character strings identifying communities

Usage:

```
ZenodoRecord$setCommunities(communities)
```

Arguments:

communities a vector or list of communities. Values should among known communities. The list of communities can fetched with the ZenodoManager and the function \$getCommunities(). Each community should be set with the Zenodo id of the community. If not recognized by Zenodo, the function will return an error.

Method addCommunity(): Adds a community to the record metadata.

Usage:

```
ZenodoRecord$addCommunity(community)
```

Arguments:

community community to add. The community should be set with the Zenodo id of the community. If not recognized by Zenodo, the function will return an error. The list of communities can fetched with the ZenodoManager and the function \$getCommunities().

Returns: TRUE if added, FALSE otherwise

Method removeCommunity(): Removes a community from the record metadata.

Usage:

```
ZenodoRecord$removeCommunity(community)
```

Arguments:

community community to remove. The community should be set with the Zenodo id of the community.

Returns: TRUE if removed, FALSE otherwise

Method setGrants(): Set a vector of character strings identifying grants

Usage:

```
ZenodoRecord$setGrants(grants)
```

Arguments:

grants a vector or list of grants Values should among known grants The list of grants can fetched with the ZenodoManager and the function \$getGrants(). Each grant should be set with the Zenodo id of the grant If not recognized by Zenodo, the function will raise a warning only.

Method addGrant(): Adds a grant to the record metadata.

Usage:

```
ZenodoRecord$addGrant(grant)
```

Arguments:

grant grant to add. The grant should be set with the id of the grant. If not recognized by Zenodo, the function will return an warning only. The list of grants can fetched with the ZenodoManager and the function \$getGrants().

Returns: TRUE if added, FALSE otherwise

Method removeGrant(): Removes a grant from the record metadata.

Usage:

```
ZenodoRecord$removeGrant(grant)
```

Arguments:

grant grant to remove. The grant should be set with the Zenodo id of the grant

Returns: TRUE if removed, FALSE otherwise

Method setJournalTitle(): Set Journal title to the record metadata

Usage:

```
ZenodoRecord$setJournalTitle(title)
```

Arguments:

title a title, object of class character

Method setJournalVolume(): Set Journal volume to the record metadata

Usage:

```
ZenodoRecord$setJournalVolume(volume)
```

Arguments:

volume a volume

Method setJournalIssue(): Set Journal issue to the record metadata

Usage:

```
ZenodoRecord$setJournalIssue(issue)
```

Arguments:

issue an issue

Method setJournalPages(): Set Journal pages to the record metadata

Usage:

ZenodoRecord\$setJournalPages(pages)

Arguments:

pages number of pages

Method setConferenceTitle(): Set conference title to the record metadata

Usage:

ZenodoRecord\$setConferenceTitle(title)

Arguments:

title conference title, object of class character

Method setConferenceAcronym(): Set conference acronym to the record metadata

Usage:

ZenodoRecord\$setConferenceAcronym(acronym)

Arguments:

acronym conference acronym, object of class character

Method setConferenceDates(): Set conference dates to the record metadata

Usage:

ZenodoRecord\$setConferenceDates(dates)

Arguments:

dates conference dates, object of class character

Method setConferencePlace(): Set conference place to the record metadata

Usage:

ZenodoRecord\$setConferencePlace(place)

Arguments:

place conference place, object of class character

Method setConferenceUrl(): Set conference url to the record metadata

Usage:

ZenodoRecord\$setConferenceUrl(url)

Arguments:

url conference url, object of class character

Method setConferenceSession(): Set conference session to the record metadata

Usage:

ZenodoRecord\$setConferenceSession(session)

Arguments:

session conference session, object of class character

Method setConferenceSessionPart(): Set conference session part to the record metadata

Usage:

ZenodoRecord\$setConferenceSessionPart(part)

Arguments:

part conference session part, object of class character

Method setImprintPublisher(): Set imprint publisher to the record metadata

Usage:

ZenodoRecord\$setImprintPublisher(publisher)

Arguments:

publisher the publisher, object of class character

Method setImprintISBN(): Set imprint ISBN to the record metadata

Usage:

ZenodoRecord\$setImprintISBN(isbn)

Arguments:

isbn the ISBN, object of class character

Method setImprintPlace(): Set imprint place to the record metadata

Usage:

ZenodoRecord\$setImprintPlace(place)

Arguments:

place the place, object of class character

Method setPartofTitle(): Set title to which record is part of

Usage:

ZenodoRecord\$setPartofTitle(title)

Arguments:

title the title, object of class character

Method setPartofPages(): Set pages to which record is part of

Usage:

ZenodoRecord\$setPartofPages(pages)

Arguments:

pages the pages, object of class character

Method setThesisUniversity(): Set thesis university

Usage:

ZenodoRecord\$setThesisUniversity(university)

Arguments:

university the university, object of class character

Method addThesisSupervisor(): Adds thesis supervisor

Usage:

```
ZenodoRecord$addThesisSupervisor(
  firstname,
  lastname,
  affiliation = NULL,
  orcid = NULL,
  gnd = NULL
)
```

Arguments:

```
firstname supervisor first name
lastname supervisor last name
affiliation supervisor affiliation (optional)
orcid supervisor ORCID (optional)
gnd supervisor GND (optional)
```

Method `removeThesisSupervisor()`: Removes a thesis supervisor by a property. The `by` parameter should be the name of the thesis supervisor property ('name' - in the form 'lastname, firstname', 'affiliation', 'orcid' or 'gnd').

Usage:

```
ZenodoRecord$removeThesisSupervisor(by, property)
```

Arguments:

```
by property used as criterion to remove the thesis supervisor
property property value used to remove the thesis supervisor
```

Returns: TRUE if removed, FALSE otherwise

Method `removeThesisSupervisorByName()`: Removes a thesis supervisor by name.

Usage:

```
ZenodoRecord$removeThesisSupervisorByName(name)
```

Arguments:

```
name thesis supervisor name
```

Returns: TRUE if removed, FALSE otherwise

Method `removeThesisSupervisorByAffiliation()`: Removes a thesis supervisor by affiliation

Usage:

```
ZenodoRecord$removeThesisSupervisorByAffiliation(affiliation)
```

Arguments:

```
affiliation thesis supervisor affiliation
```

Returns: TRUE if removed, FALSE otherwise

Method `removeThesisSupervisorByORCID()`: Removes a thesis supervisor by ORCID

Usage:

```
ZenodoRecord$removeThesisSupervisorByORCID(orcid)
```

Arguments:

orcid thesis supervisor ORCID

Returns: TRUE if removed, FALSE otherwise

Method removeThesisSupervisorByGND(): Removes a thesis supervisor by GND

Usage:

ZenodoRecord\$removeThesisSupervisorByGND(gnd)

Arguments:

gnd thesis supervisor GND

Returns: TRUE if removed, FALSE otherwise

Method addLocation(): Adds a location to the record metadata.

Usage:

ZenodoRecord\$addLocation(place, description = NULL, lat = NULL, lon = NULL)

Arguments:

place place (required)

description description

lat latitude

lon longitude

Method removeLocation(): Removes a grant from the record metadata.

Usage:

ZenodoRecord\$removeLocation(place)

Arguments:

place place (required)

Returns: TRUE if removed, FALSE otherwise

Method exportAs(): Exports record to a file by format.

Usage:

ZenodoRecord\$exportAs(format, filename, append_format = TRUE)

Arguments:

format the export format to use. Possibles values are: BibTeX, CSL, DataCite, DublinCore, DCAT, JSON, JSON-LD, GeoJSON, MARCXML

filename the target filename (without extension)

append_format whether format name has to be appended to the filename. Default is TRUE (for backward compatibility reasons). Set it to FALSE if you want to use only the filename.

Returns: the written file name (with extension)

Method exportAsBibTeX(): Exports record as BibTeX

Usage:

ZenodoRecord\$exportAsBibTeX(filename)

Arguments:

filename the target filename (without extension)

Returns: the written file name (with extension)

Method exportAsCSL(): Exports record as CSL

Usage:

ZenodoRecord\$exportAsCSL(filename)

Arguments:

filename the target filename (without extension)

Returns: the written file name (with extension)

Method exportAsDataCite(): Exports record as DataCite

Usage:

ZenodoRecord\$exportAsDataCite(filename)

Arguments:

filename the target filename (without extension)

Returns: the written file name (with extension)

Method exportAsDublinCore(): Exports record as DublinCore

Usage:

ZenodoRecord\$exportAsDublinCore(filename)

Arguments:

filename the target filename (without extension)

Returns: the written file name (with extension)

Method exportAsDCAT(): Exports record as DCAT

Usage:

ZenodoRecord\$exportAsDCAT(filename)

Arguments:

filename the target filename (without extension)

Returns: the written file name (with extension)

Method exportAsJSON(): Exports record as JSON

Usage:

ZenodoRecord\$exportAsJSON(filename)

Arguments:

filename the target filename (without extension)

Returns: the written file name (with extension)

Method exportAsJSONLD(): Exports record as JSONLD

Usage:

ZenodoRecord\$exportAsJSONLD(filename)

Arguments:

filename the target filename (without extension)

Method `exportAsGeoJSON()`: Exports record as GeoJSON

Usage:

```
ZenodoRecord$exportAsGeoJSON(filename)
```

Arguments:

filename the target filename (without extension)

Returns: the written file name (with extension)

Method `exportAsMARCXML()`: Exports record as MARCXML

Usage:

```
ZenodoRecord$exportAsMARCXML(filename)
```

Arguments:

filename the target filename (without extension)

Returns: the written file name (with extension)

Method `exportAsAllFormats()`: Exports record in all Zenodo record export formats. This function will create one file per Zenodo metadata formats.

Usage:

```
ZenodoRecord$exportAsAllFormats(filename)
```

Arguments:

filename the target filename (without extension)

Method `listFiles()`: list files attached to the record

Usage:

```
ZenodoRecord$listFiles(pretty = TRUE)
```

Arguments:

pretty whether a pretty output (data.frame) should be returned (default TRUE), otherwise the raw list of files is returned.

Returns: the files, as data.frame or list

Method `downloadFiles()`: Downloads files attached to the record

Usage:

```
ZenodoRecord$downloadFiles(
  path = ".",
  files = list(),
  parallel = FALSE,
  parallel_handler = NULL,
  cl = NULL,
  quiet = FALSE,
  ...
)
```

Arguments:

`path` target download path (by default it will be the current working directory)

`files` (list of) file(s) to download. If not specified, by default all files will be downloaded.

`parallel` whether download has to be done in parallel using the chosen `parallel_handler`.
Default is FALSE

`parallel_handler` The parallel handler to use eg. `mclapply`. To use a different parallel handler (such as eg `parLapply` or `parSapply`), specify its function in `parallel_handler` argument. For cluster-based parallel download, this is the way to proceed. In that case, the cluster should be created earlier by the user with `makeCluster` and passed as `cl` argument. After downloading all files, the cluster will be stopped automatically.

`cl` an optional cluster for cluster-based parallel handlers

`quiet` (default is FALSE) can be set to suppress informative messages (not warnings).

... arguments inherited from `parallel::mclapply` or the custom `parallel_handler` can be added (eg. `mc.cores` for `mclapply`)

Method `print()`: Prints a [ZenodoRecord](#)

Usage:

```
ZenodoRecord$print(..., format = "internal", depth = 1)
```

Arguments:

... any other parameter. Not used

`format` format to use for printing. By default, `internal` uses an **zen4R** internal printing method. Other methods available are those supported by Zenodo for record export, and can be used only if the record has already been published (with a DOI). Attempts to print using a Zenodo export format for a record will raise a warning message and revert to "internal" format

`depth` an internal depth parameter for indentation of print statements, in case of listing or recursive use of print

Method `toDCEntree()`: Maps to an [atom4R DCEntree](#). Note: applies only to published records.

Usage:

```
ZenodoRecord$toDCEntree()
```

Returns: an object of class `DCEntree`

Method `clone()`: The objects of this class are cloneable with this method.

Usage:

```
ZenodoRecord$clone(deep = FALSE)
```

Arguments:

`deep` Whether to make a deep clone.

Note

See examples in [download_zenodo](#) utility function.

Author(s)

Emmanuel Blondel <emmanuel.blondell@gmail.com>

ZenodoRequest	<i>ZenodoRequest</i>
---------------	----------------------

Description

ZenodoRequest

ZenodoRequest

Format

[R6Class](#) object.

Value

Object of [R6Class](#) for modelling a generic Zenodo request

Super class

[zen4R](#): [zen4RLogger](#) -> ZenodoRequest

Methods**Public methods:**

- [ZenodoRequest\\$new\(\)](#)
- [ZenodoRequest\\$execute\(\)](#)
- [ZenodoRequest\\$getRequest\(\)](#)
- [ZenodoRequest\\$getRequestHeaders\(\)](#)
- [ZenodoRequest\\$getStatus\(\)](#)
- [ZenodoRequest\\$getResponse\(\)](#)
- [ZenodoRequest\\$getException\(\)](#)
- [ZenodoRequest\\$getResult\(\)](#)
- [ZenodoRequest\\$setResult\(\)](#)
- [ZenodoRequest\\$clone\(\)](#)

Method `new()`: Initializes a ZenodoRequest

Usage:

```
ZenodoRequest$new(  
  url,  
  type,  
  request,  
  data = NULL,  
  file = NULL,  
  token,  
  logger = NULL,  
  ...  
)
```

Arguments:

url request URL

type Type of request: 'GET', 'POST', 'PUT', 'DELETE'

request the method request

data payload (optional)

file to be uploaded (optional)

token user token

logger the logger type

... any other arg

Method execute(): Executes the request

Usage:

ZenodoRequest\$execute()

Method getRequest(): Get request

Usage:

ZenodoRequest\$getRequest()

Method getRequestHeaders(): Get request headers

Usage:

ZenodoRequest\$getRequestHeaders()

Method getStatus(): Get request status

Usage:

ZenodoRequest\$getStatus()

Method getResponse(): Get request response

Usage:

ZenodoRequest\$getResponse()

Method getException(): Get request exception

Usage:

ZenodoRequest\$getException()

Method getResult(): Get request result

Usage:

ZenodoRequest\$getResult()

Method setResult(): Set request result

Usage:

ZenodoRequest\$setResult(result)

Arguments:

result result to be set

Method clone(): The objects of this class are cloneable with this method.

Usage:

ZenodoRequest\$clone(deep = FALSE)

Arguments:

deep Whether to make a deep clone.

Note

Abstract class used internally by **zen4R**

Author(s)

Emmanuel Blondel <emmanuel.blondel1@gmail.com>

zenodo_pat

zenodo_pat

Description

Get Zenodo personal access token, looking in env var 'ZENODO_PAT'

Usage

zenodo_pat(quiet = TRUE)

Arguments

quiet Hide log message, default is TRUE

Index

- * **Request**
 - ZenodoRequest, [37](#)
- * **Zenodo**
 - ZenodoRequest, [37](#)
- * **logger**
 - zen4RLogger, [5](#)
- * **manager**
 - ZenodoManager, [7](#)
- * **record**
 - ZenodoRecord, [17](#)
- * **zenodo**
 - ZenodoManager, [7](#)
 - ZenodoRecord, [17](#)

- DCEntry, [36](#)
- download_zenodo, [2](#), [36](#)

- export_zenodo, [3](#)

- get_versions, [4](#)

- R6Class, [5](#), [7](#), [17](#), [37](#)

- zen4R, [4](#)
- zen4R-package (zen4R), [4](#)
- zen4R: : zen4RLogger, [7](#), [17](#), [37](#)
- zen4RLogger, [5](#)
- zenodo_pat, [8](#), [39](#)
- ZenodoManager, [7](#)
- ZenodoRecord, [2](#), [17](#), [20](#), [36](#)
- ZenodoRequest, [37](#)